

# JMcDM: A Julia package for multiple-criteria decision-making tools

Mehmet Hakan Satman<sup>a</sup>, Bahadır Fatih Yıldırım<sup>b</sup>, Ersagun Kuruca<sup>c</sup>

<sup>a</sup>*Istanbul University, Department of Econometrics, Beyazit, Istanbul, Turkey*

<sup>b</sup>*Istanbul University, Department of Transportation and Logistics, Avcılar, Istanbul, Turkey*

<sup>c</sup>*Istanbul Technical University, Department of Computer Engineering, Sarıyer, Istanbul, Turkey*

---

## Abstract

*JMcDM* is a *Julia* package that implements some leading multiple-criteria decision making tools for both researchers and developers. *Julia*'s REPL is well suited for researchers to perform their analysis using different methods and compare their results. The package also provides the necessary infrastructure and utility functions for writing recently published methods. The proposed package has also brought MCDA tools to a relatively new language such as *Julia* with its significant performance promises. The methods developed in the package are also designed to be familiar to users who previously used *R* and *Python* languages. The paper presents the basics of the design, example usage, and code snippets.

*Keywords:* julia, multiple-criteria, decision-making, outranking

---

## Required Metadata

### Current code version

Ancillary data table required for subversion of the codebase. Kindly replace examples in right column with the correct information about your current code, and leave the left column as it is.

Nr.	Code metadata description	Please fill in this column
C1	Current code version	v0.1.6
C2	Permanent link to code/repository used for this code version	<a href="https://github.com/jbytecode/JMcDM">https://github.com/jbytecode/JMcDM</a>
C3	Code Ocean compute capsule	
C4	Legal Code License	MIT
C5	Code versioning system used	git
C6	Software code languages, tools, and services used	Julia
C7	Compilation requirements, operating environments & dependencies	Julia 1.4
C8	If available Link to developer documentation/manual	<a href="https://jbytecode.github.io/JMcDM/docs/build">https://jbytecode.github.io/JMcDM/docs/build</a>
C9	Support email for questions	mhsatman@istanbul.edu.tr

Table 1: Code metadata (mandatory)

## 1. Motivation and significance

The one-dimensional array  $a$  is in ascending order if and only if  $a_i \leq a_{i+1}$  where  $i = 1, 2, \dots, n - 1$ , and  $n$  is the length of array. In other terms, the process of ordering numbers requires the logical  $\leq$  operator to be perfectly defined. Since the operator  $\leq$  is not defined for any set of points in higher dimensions,  $\mathbb{R}^p$  for  $p \geq 2$ , there is not a unique ordering of points.

In multi-dimensional case, the binary domination operator  $\succ$  applied on points  $a$  and  $b$ ,  $a \succ b$ , is true iff each item in  $a$  is not worse than the corresponding item in  $b$  and at least one item is better than the corresponding item in  $b$  [1]. On the other hand, the more relaxed operator  $\succeq$  returns true

11 if each item in  $a$  is as good as the corresponding item in  $b$  [2]. Several  
 12 outranking methods in MCDA (Multiple-Criteria Decision Analysis) define  
 13 a unique ranking mechanism to select the best alternative among others.

14 Suppose a decision process has  $n$  alternatives and  $m$  criteria which are  
 15 either to be maximized or minimized. Each single criterion has a weight  
 16  $0 \leq w_i \leq 1$  where  $\sum_i^m w_i = 1$ .  $f_i$  is either maximum or minimum.  $g_j(\cdot)$  is  
 17 evolution function and it is taken as  $g_j(x) = x$  in many methods. A multiple  
 18 criteria decision problem can be represented using the decision table

<b>Criteria</b>	$C_1$	$C_2$	$\dots$	$C_m$
<b>Weights</b>	$w_1$	$w_2$	$\dots$	$w_m$
<b>Functions</b>	$f_1$	$f_2$	$\dots$	$f_m$
$A_1$	$g_1(A_1)$	$g_2(A_1)$	$\dots$	$g_m(A_1)$
$A_2$	$g_1(A_2)$	$g_2(A_2)$	$\dots$	$g_m(A_2)$
$\vdots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$
$A_n$	$g_1(A_n)$	$g_2(A_n)$	$\dots$	$g_m(A_n)$

Table 2: A decision matrix in general form

19 without loss of generality. When  $A_1, A_2, \dots, A_n$  are alternatives and  $C_1, C_2,$   
 20  $\dots, C_m$  are different situations of a single criterion then the decision problem  
 21 is said to be single criterion decision problem. If  $A_i$  and  $C_j$  are strategies of  
 22 two game players then  $g_j(A_i)$  is the gain of the row player when she selects  
 23 the strategy  $i$  and the column player selects the strategy  $C_j$ .

24 MCDA is used in material selection [3, 4], supplier selection [5, 6], per-  
 25 sonnel selection [7], inventory classification [8], service provider selection  
 26 [9, 10, 11, 12], strategy selection [13, 14, 15], location selection [16, 17],  
 27 project selection [18, 19, 20], performance evaluation [21, 22, 23], risk evalu-  
 28 ation [24, 25], allocation problems [6, 26, 27], and site selection [28, 29, 30]

29 [problems in the literature.](#)

30 Multiple-criteria decision-making (MCDM) tools provide several algo-  
31 rithms for ordering or selecting alternatives and/or determining the weights  
32 when there is uncertainty. Although some algorithms are suitable for hand  
33 calculations, a computer software is often required. *PyTOPS* is a Python  
34 tool for TOPSIS [31]. *Super Decisions* is a software package which is mainly  
35 focused on AHP (Analytic Hierarchy Process) and ANP (Analytic Network  
36 Process) [32]. *Visual Promethee* implements Promethee method on Win-  
37 dows platforms [33]. *M-BACBETH* is an other commercial software product  
38 that implements MACBETH with a easy to use GUI. [34]. *Sanna* is a stan-  
39 dard MS Excel add-in application that supports several basic methods for  
40 multi-criteria evaluation of alternatives (WSA, TOPSIS, ELECTRE I and  
41 III, PROMETHEE I and II, MAPPAC and ORESTE) [35]. *DEA Frontier*  
42 software requires Excel add-in that can solve up to 50 DMUs with unlimited  
43 number of inputs and outputs (subject to the capacity of the standard MS  
44 Excel Solver) [36].

45 *JMcDM* is designed to provide a developer-friendly library for solving  
46 multiple-criteria decision problems in Julia [37]. Since Julia is a dynamic  
47 language, it is also useful for researchers that familiar with REPL environ-  
48 ments. The package includes multi-criteria decision methods as well as a  
49 game solver for zero-sum games and methods for single criterion methods.

## 50 **2. Software description**

### 51 *2.1. Software Architecture*

52 *JMcDM* provides a framework for performing multi-criteria decision anal-  
53 ysis as well as it includes utility functions for development of new methods.  
54 Each single MCDM method returns an object in subtype of `MCDMResult`

55 which is defined as

```
56 abstract type MCDMResult end
```

57 and it is used to derive new return types. For instance, the `topsis()` function

58 always returns a `TopsisResult` object which is defined as

```
59 struct TopsisResult <: MCDMResult
60     decisionMatrix::DataFrame
61     weights::Array{Float64,1}
62     normalizedDecisionMatrix::DataFrame
63     normalizedWeightedDecisionMatrix::DataFrame
64     bestIndex::Int64
65     scores::Array{Float64,1}
66 end
```

67 and holds many outputs in a single `struct`. Function definitions are also

68 similar but they may differ depending on the requirements of algorithms.

69 For instance the function `topsis` is defined as

```
70 function topsis(
71     decisionMat::DataFrame,
72     weights::Array{Float64,1},
73     fns::Array{Function,1})::TopsisResult
```

74 where `decisionMat` is the decision matrix, `weights` are weights of criteria,

75 and `fns` is an array of functions (either `minimum` or `maximum`) that determine

76 the optimization directions.

77 The package is registered in Julia package repository and it is available

78 for downloading and installing using Julia's package manager.

```

79 julia> using Pkg
80 julia> Pkg.add("JMcdM")

81 and

82 julia> ]
83 (@v1.5) pkg> add JMcdM

```

84 present two distinct ways of downloading and installing the package.

## 85 *2.2. Software Functionalities*

86 The package implements methods for TOPSIS<sup>1</sup> [38], ELECTRE<sup>2</sup>[39],  
87 PROMETHEE<sup>3</sup> [40], DEMATEL<sup>4</sup> [41], MOORA<sup>5</sup> [42], VIKOR<sup>6</sup> [43, 44],  
88 AHP<sup>7</sup> [45], GRA<sup>8</sup> [46], NDS<sup>9</sup> [1], SAW<sup>10</sup> [47, 48], ARAS<sup>11</sup> [49], WPM<sup>12</sup> [48],  
89 WASPAS<sup>13</sup> [50], EDAS<sup>14</sup> [8], MARCOS<sup>15</sup> [5], MABAC<sup>16</sup> [51], MAIRCA<sup>17</sup>  
90 [52], COPRAS<sup>18</sup> [53], COCOSO<sup>19</sup> [54], CRITIC<sup>20</sup> [55], and Entropy[56] for

---

<sup>1</sup>Technique for Order Preference by Similarity to Ideal Solutions

<sup>2</sup>Elimination and Choice Translating Reality

<sup>3</sup>Preference Ranking Organization METHod for Enrichment of Evaluations

<sup>4</sup>The Decision Making Trial and Evaluation Laboratory

<sup>5</sup>Multi-Objective Optimization By Ratio Analysis

<sup>6</sup>VlseKriterijumska Optimizacija I Kaompromisno Resenje in Serbian

<sup>7</sup>Analytic Hierarchy Process

<sup>8</sup>Grey Relational Analysis

<sup>9</sup>Non-dominated Sorting

<sup>10</sup>Simple Additive Weighting

<sup>11</sup>Additive Ratio Assessment

<sup>12</sup>Weighted Product Model

<sup>13</sup>Weighted Aggregated Sum Product ASsessment

<sup>14</sup>Evaluation based on Distance from Average Solution

<sup>15</sup>Measurement Alternatives and Ranking according to COmpromise Solution

<sup>16</sup>Multi-Attributive Border Approximation area Comparison

<sup>17</sup>Multi Attributive Ideal-Real Comparative Analysis

<sup>18</sup>COMplex PROportional ASsessment

<sup>19</sup>Combined Compromise Solution

<sup>20</sup>CRiteria Importance Through Intercriteria Correlation

multiple-criteria tools. The package also performs DEA for Data Envelopment Analysis [57] and includes a method for zero-sum game solver. The list of other tools and utility functions are listed and documented in the source code as well as in the online documentation.

### 2.3. Sample code snippets analysis

Suppose a decision problem is given in Table 3.

Criteria	Age	Size	Price	Distance	Population
Weights	0.35	0.15	0.25	0.20	0.05
Functions	min	max	min	min	max
$A_1$	6	140	150000	950	1500
$A_2$	4	90	100000	1500	2000
$A_3$	12	140	75000	550	1100

Table 3: Decision matrix

In this sample problem, a decision maker is subject to select an apartment by considering age of the building, size (in  $m^2$ s), price (in \$), distance to city centre (in  $ms$ ), and nearby population. The data can be entered as a two-dimensional array (matrix) or as a DataFrame object:

```
julia> using JMCDM, DataFrames
julia> df = DataFrame(
:age      => [6.0, 4, 12],
:size     => [140.0, 90, 140],
:price    => [150000.0, 100000, 75000],
:distance => [950.0, 1500, 550],
:population => [1500.0, 2000, 1100]);
```

108 The weight vector `w`, vector of directions `fns`, and `topsis()` function call  
109 can be performed using the *Julia* REPL.

```
110 julia> w = [0.35, 0.15, 0.25, 0.20, 0.05];
111 julia> fns = [minimum, maximum, minimum, minimum, maximum];
112 julia> result = topsis(df, w, fns);
113 julia> result.scores
114 3-element Array{Float64,1}:
115  0.5854753145549456
116  0.6517997936899308
117  0.41850223305822903
118
119 julia> result.bestIndex
120 2
```

121 In the output above it is shown that the alternative  $A_2$  has a score of  
122 0.65179 and it is selected as the best. The same analysis can be performed  
123 using `saw()` for the method of Simple Additive Weighting

```
124 julia> result = saw(df, w, fns);
125 julia> result.bestIndex
126 2
```

127 as well as using `wpm` for the method of Weighted Product Method

```
128 julia> result = wpm(df, w, fns);
129 julia> result.bestIndex
130 2
```

131 For any method, `?methodname` shows the documentation as in the same  
132 way in other Julia packages.



133 2.3.1. Game Solver

134 A two-player zero-sum game is not a multi-criteria decision method. On  
 135 the other hand, assuming the column player's choices are natural states for  
 136 the row player, the game matrix represents gains or costs for the row player  
 137 depending on the alternative she plays. Table 4 represents the gains of the  
 138 row player for a Rock & Paper % Scissors game. Each time the game is  
 139 played, the winner takes 1 point.

	Rock	Paper	Scissors
Rock	0	-1	1
Paper	1	0	-1
Scissors	-1	1	0

Table 4: Game matrix for the Rock & Paper & Scissors game

140 Table 4 shows that the row player wins the game if she selects **Rock** and  
 141 the column player selects **Paper**. Similarly, she loses the game if she selects  
 142 **Scissors** and the column player selects **Rock**. A tie has a zero gain for  
 143 both players. The problem is selecting the best strategy for the row player.  
 144 *JMcDM* implements the `game()` method for calculating value and the best  
 145 strategy of this kind of games. The code snippet below represent the problem.

```
146 julia> mat = [0 -1 1; 1 0 -1; -1 1 0];
147 julia> dm = makeDecisionMatrix(mat);
148 julia> result = game(dm);
```

149 The `makeDecisionMatrix()` method returns a modified copy of the matrix  
 150 `mat` as the minimum value of the new matrix is non-negative. The function  
 151 `game()` returns a `GameResult` object which holds the value of the game and  
 152 the probabilities of the alternatives for the row player.

```

153 julia> result.value
154 0.0
155 julia> result.row_player_probabilities
156 3-element Array{Float64,1}:
157 0.3333333333333333
158 0.3333333333333337
159 0.3333333333333333

```

160 It is shown that the value of the game is zero and the row player should  
161 selects the alternatives with equal probability of  $\frac{1}{3}$ .

### 162 **3. Illustrative Examples**

163 Since *JMcDM* is designed as a software library and for REPL use, it does  
164 not implement a significant user interface. However, the `summary()` function  
165 provides a useful way to perform a list of methods and returns a text based  
166 result to compare results.

```

167 julia> methods1 = [:topsis, :electre, :vikor,
168 :moora, :cocoso, :wpm, :waspas]
169 julia> result1 = summary(df, w, fns, methods1);

```

170 Figure 1 represents the output of the `summary()` call for methods TOP-  
171 SIS, ELECTRE, VIKOR, MOORA, COCOSO, WPM, and WASPAS, re-  
172 spectively.

```

173 julia> methods2 = [:aras, :saw, :edas, :marcos,
174 :mabac, :mairca, :grey];
175 julia> result2 = summary(df, w, fns, methods2);

```

176 Figure 2 represents the output of the `summary()` call for methods ARAS,  
177 SAW, EDAS, MARCOS, MABAC, MAIRCA, and GREY, respectively.

```
julia> result1
```

3x7 DataFrame

Row	topsis	electre	cocoso	moora	vikor	wpm	waspas
	String	String	String	String	String	String	String
1			✓	✓	✓		
2	✓	✓				✓	✓
3		✓					

Figure 1: Results of TOPSIS, ELECTRE, VIKOR, MOORA, COCOSO, WPM, and WASPAS

```
julia> result2
```

3x7 DataFrame

Row	grey	aras	saw	edas	marcos	mabac	mairca
	String	String	String	String	String	String	String
1							
2		✓	✓	✓	✓		
3	✓					✓	✓

Figure 2: Results of ARAS, SAW, EDAS, MARCOS, MABAC, MAIRCA, and GREY

## 178 4. Impact

179 *JMcDM* provides a moderate number of MCDA tools and utility func-  
180 tions for developing new methods as well as performing decision analysis  
181 using a single function call for each method. A researcher can easily perform  
182 sequential analysis by changing the problem parameters and can compare  
183 results of many tools. Existing software packages are mainly focused on pro-  
184 viding a small subset of methods. *JMcDM* is an all-in-one solution and has  
185 potential for increasing user productivity. Seeing the different results pro-  
186 duced by the methods together also helps to discover which parameters the  
187 research is more sensitive to and the reasons for them.

## 188 5. Conclusions

189 Multiple-criteria decision-making tools are used in various disciplines in  
190 the literature. Since it is difficult to calculate these tools manually, many  
191 software packages and programs have been developed. However, these pack-  
192 ages include a selected subset of methods. *JMcDM* is a *Julia* package that  
193 contains a significant amount of tools in the literature. Implementations of  
194 these tools are straightforward to use in *Julia* REPL for researchers. *JMcDM*  
195 also provides the necessary infrastructure for the development of new meth-  
196 ods in the literature with its utility functions, comprehensive documentation,  
197 and unit tests compiled from many text books. The proposed package has  
198 also brought MCDA tools to a relatively new language such as *Julia* with sig-  
199 nificant performance promises. The methods in the package are also designed  
200 to be familiar to users who previously used *R* and *Python* languages.

## 201 **6. Conflict of Interest**

202 We wish to confirm that there are no known conflicts of interest associated  
203 with this publication and there has been no significant financial support for  
204 this work that could have influenced its outcome.

## 205 **Acknowledgements**

206 The authors would like to thank the Editor-in-Chief, editors, reviewers for  
207 providing extremely insightful comments, and other staff of the SoftwareX  
208 Journal.

## 209 **References**

- 210 [1] K. Deb, A. Pratap, S. Agarwal, T. Meyarivan, A fast and elitist multiob-  
211 jective genetic algorithm: NSGA-II, IEEE Transactions on Evolutionary  
212 Computation 6 (2) (2002) 182–197. doi:10.1109/4235.996017.
- 213 [2] S. Greco, J. Figueira, M. Ehrgott, Multiple criteria decision analysis,  
214 Vol. 37, Springer, 2016.
- 215 [3] K. Maniya, M. Bhatt, A selection of material using a novel type decision-  
216 making method: Preference selection index method, Materials & Design  
217 31 (4) (2010) 1785–1789. doi:10.1016/j.matdes.2009.11.020.  
218 URL <https://doi.org/10.1016%2Fj.matdes.2009.11.020>
- 219 [4] I. Emovon, O. S. Oghenenyero, Application of MCDM method in  
220 material selection for optimal design: A review, Results in Materials 7  
221 (2020) 100115. doi:10.1016/j.rinma.2020.100115.  
222 URL <https://doi.org/10.1016%2Fj.rinma.2020.100115>

- [5] Ž. Stević, D. Pamučar, A. Puška, P. Chatterjee, Sustainable supplier selection in healthcare industries using a new MCDM method: Measurement of alternatives and ranking according to COMpromise solution (MARCOS), *Computers & Industrial Engineering* 140 (2020) 106231. doi:10.1016/j.cie.2019.106231.  
URL <https://doi.org/10.1016%2Fj.cie.2019.106231>
- [6] A. Rezaei, M. R. Galankashi, S. Mansoorzadeh, F. M. Rafiei, Supplier selection and order allocation with lean manufacturing criteria: An integrated MCDM and bi-objective modelling approach, *Engineering Management Journal* 32 (4) (2020) 253–271. doi:10.1080/10429247.2020.1753490.  
URL <https://doi.org/10.1080%2F10429247.2020.1753490>
- [7] A. Ulutaş, G. Popovic, D. Stanujkic, D. Karabasevic, E. K. Zavadskas, Z. Turskis, A new hybrid MCDM model for personnel selection based on a novel grey PIPRECIA and grey OCRA methods, *Mathematics* 8 (10) (2020) 1698. doi:10.3390/math8101698.  
URL <https://doi.org/10.3390%2Fmath8101698>
- [8] M. K. Ghorabae, E. K. Zavadskas, L. Olfat, Z. Turskis, Multi-criteria inventory classification using a new method of evaluation based on distance from average solution (EDAS), *Informatica* 26 (3) (2015) 435–451. doi:10.15388/informatica.2015.57.  
URL <https://doi.org/10.15388%2Finformatica.2015.57>
- [9] E. ÖZCAN, M. AHISKALI, 3pl service provider selection with a goal programming model supported with multicriteria decision making approaches, *GAZI UNIVERSITY JOURNAL OF SCIENCE* 33 (2) (2020)

- 248 413–427. doi:10.35378/gujs.552070.  
 249 URL <https://doi.org/10.35378%2Fgujs.552070>
- 250 [10] A. R. Mishra, P. Rani, K. Pandey, Fermatean fuzzy CRITIC-EDAS  
 251 approach for the selection of sustainable third-party reverse logistics  
 252 providers using improved generalized score function, Journal of Ambi-  
 253 ent Intelligence and Humanized Computing (feb 2021). doi:10.1007/  
 254 s12652-021-02902-w.  
 255 URL <https://doi.org/10.1007%2Fs12652-021-02902-w>
- 256 [11] R. R. Kumar, B. Kumari, C. Kumar, CCS-OSSR: A framework based  
 257 on hybrid MCDM for optimal service selection and ranking of cloud  
 258 computing services, Cluster Computing (aug 2020). doi:10.1007/  
 259 s10586-020-03166-3.  
 260 URL <https://doi.org/10.1007%2Fs10586-020-03166-3>
- 261 [12] A. E. Youssef, An integrated MCDM approach for cloud service selection  
 262 based on TOPSIS and BWM, IEEE Access 8 (2020) 71851–71865. doi:  
 263 10.1109/access.2020.2987111.  
 264 URL <https://doi.org/10.1109%2Faccess.2020.2987111>
- 265 [13] G. Büyüközkan, E. Mukul, E. Kongar, Health tourism strategy se-  
 266 lection via SWOT analysis and integrated hesitant fuzzy linguistic  
 267 AHP-MABAC approach, Socio-Economic Planning Sciences (2020)  
 268 100929doi:10.1016/j.seps.2020.100929.  
 269 URL <https://doi.org/10.1016%2Fj.seps.2020.100929>
- 270 [14] A. Jain, J. D. Darbari, A. Kaul, P. C. Jha, Selection of a green mar-  
 271 keting strategy using MCDM under fuzzy environment, in: Advances  
 272 in Intelligent Systems and Computing, Springer Singapore, 2019, pp.

- 273 499–512. doi:10.1007/978-981-15-0184-5\_43.  
 274 URL [https://doi.org/10.1007%2F978-981-15-0184-5\\_43](https://doi.org/10.1007%2F978-981-15-0184-5_43)
- 275 [15] Y. S. ÖZDEMİR, , A. ÜSKÜDAR, Strategy selection by using interval  
 276 type-2 fuzzy mcdm and an application, Journal of Engineering Research  
 277 8 (3) (2020) 172–189. doi:10.36909/jer.v8i3.8176.  
 278 URL <https://doi.org/10.36909%2Fjer.v8i3.8176>
- 279 [16] S. Tadić, M. Krstić, V. Roso, N. Brnjac, Dry port terminal location se-  
 280 lection by applying the hybrid grey MCDM model, Sustainability 12 (17)  
 281 (2020) 6983. doi:10.3390/su12176983.  
 282 URL <https://doi.org/10.3390%2Fsu12176983>
- 283 [17] A. Karaşan, İ. Kaya, M. Erdoğan, Location selection of electric vehicles  
 284 charging stations by using a fuzzy MCDM method: a case study in  
 285 turkey, Neural Computing and Applications 32 (9) (2018) 4553–4574.  
 286 doi:10.1007/s00521-018-3752-2.  
 287 URL <https://doi.org/10.1007%2Fs00521-018-3752-2>
- 288 [18] D. Pramanik, S. C. Mondal, A. Halder, A framework for managing un-  
 289 certainty in information system project selection: an intelligent fuzzy  
 290 approach, International Journal of Management Science and Engineer-  
 291 ing Management 15 (1) (2019) 70–78. doi:10.1080/17509653.2019.  
 292 1604191.  
 293 URL <https://doi.org/10.1080%2F17509653.2019.1604191>
- 294 [19] C.-Y. Huang, H.-L. Hsieh, H. Chen, Evaluating the investment projects  
 295 of spinal medical device firms using the real option and DANP-mV based  
 296 MCDM methods, International Journal of Environmental Research and



- Public Health 17 (9) (2020) 3335. doi:10.3390/ijerph17093335.  
URL <https://doi.org/10.3390%2Fijerph17093335>
- [20] D. G. B. Souza, C. E. S. Silva, N. Y. Soma, Selecting projects on the  
brazilian r&d energy sector: A fuzzy-based approach for criteria selec-  
tion, IEEE Access 8 (2020) 50209–50226. doi:10.1109/access.2020.  
2979666.  
URL <https://doi.org/10.1109%2Faccess.2020.2979666>
- [21] M. Abdel-Basset, W. Ding, R. Mohamed, N. Metawa, An integrated  
plithogenic MCDM approach for financial performance evaluation of  
manufacturing industries, Risk Management 22 (3) (2020) 192–218.  
doi:10.1057/s41283-020-00061-4.  
URL <https://doi.org/10.1057%2Fs41283-020-00061-4>
- [22] B. F. Yildirim, B. A. Mercangoz, Evaluating the logistics performance of  
OECD countries by using fuzzy AHP and ARAS-g, Eurasian Economic  
Review 10 (1) (2019) 27–45. doi:10.1007/s40822-019-00131-3.  
URL <https://doi.org/10.1007%2Fs40822-019-00131-3>
- [23] B. A. Mercangoz, , B. Yildirim, S. K. Yildirim, Time period based  
COPRAS-g method: application on the logistics performance index,  
Logforum 16 (2) (2020) 239–250. doi:10.17270/j.log.2020.432.  
URL <https://doi.org/10.17270%2Fj.log.2020.432>
- [24] S. Guo, W. Zhang, X. Gao, Business risk evaluation of electricity retail  
company in china using a hybrid MCDM method, Sustainability 12 (5)  
(2020) 2040. doi:10.3390/su12052040.  
URL <https://doi.org/10.3390%2Fsu12052040>

- [25] Y. Duan, Y. Sun, Y. Zhang, X. Fan, Q. Dong, S. Guo, Risk evaluation of electric power grid investment in china employing a hybrid novel MCDM method, *Mathematics* 9 (5) (2021) 473. doi:10.3390/math9050473.  
URL <https://doi.org/10.3390/math9050473>
- [26] E. F. E. A. Mills, M. A. Baafi, N. Amowine, K. Zeng, A HYBRID GREY MCDM APPROACH FOR ASSET ALLOCATION: EVIDENCE FROM CHINA'S SHANGHAI STOCK EXCHANGE, *Journal of Business Economics and Management* 21 (2) (2020) 446–472. doi:10.3846/jbem.2020.11967.  
URL <https://doi.org/10.3846/jbem.2020.11967>
- [27] D. Sarma, A. Das, P. Dutta, U. K. Bera, A cost minimization resource allocation model for disaster relief operations with an information crowdsourcing-based MCDM approach, *IEEE Transactions on Engineering Management* (2020) 1–21doi:10.1109/tem.2020.3015775.  
URL <https://doi.org/10.1109/tem.2020.3015775>
- [28] A. Ghosh, N. Ghorui, S. P. Mondal, S. Kumari, B. K. Mondal, A. Das, M. S. Gupta, Application of hexagonal fuzzy MCDM methodology for site selection of electric vehicle charging station, *Mathematics* 9 (4) (2021) 393. doi:10.3390/math9040393.  
URL <https://doi.org/10.3390/math9040393>
- [29] G. Sisay, S. L. Gebre, K. Getahun, GIS-based potential landfill site selection using MCDM-AHP modeling of gondar town, ethiopia, *African Geographical Review* (2020) 1–20doi:10.1080/19376812.2020.1770105.  
URL <https://doi.org/10.1080/19376812.2020.1770105>
- [30] M. Lin, C. Huang, Z. Xu, MULTIMOORA based MCDM model for

- 346 site selection of car sharing station under picture fuzzy environment,  
 347 Sustainable Cities and Society 53 (2020) 101873. doi:10.1016/j.scs.  
 348 2019.101873.  
 349 URL <https://doi.org/10.1016%2Fj.scs.2019.101873>
- 350 [31] V. Yadav, S. Karmakar, P. P. Kalbar, A. Dikshit, PyTOPS: A python  
 351 based tool for TOPSIS, SoftwareX 9 (2019) 217–222. doi:10.1016/j.  
 352 softx.2019.02.004.
- 353 [32] W. Adams, R. Saaty, Super decisions software guide (2003).  
 354 URL [https://superdecisions.com/sd\\_resources/v28\\_man01.pdf](https://superdecisions.com/sd_resources/v28_man01.pdf)
- 355 [33] B. Mareschal, Y. D. Smet, Visual PROMETHEE: Developments of the  
 356 PROMETHEE - GAIA multicriteria decision aid methods, in: 2009  
 357 IEEE International Conference on Industrial Engineering and Engineer-  
 358 ing Management, IEEE, 2009. doi:10.1109/ieem.2009.5373124.
- 359 [34] C. A. Bana e Costa, J.-M. de Corte, J.-C. Vansnick, MACBETH  
 360 (Measuring Attractiveness by a Categorical Based Evaluation Tech-  
 361 nique), Wiley Encyclopedia of Operations Research and Management  
 362 Science, John Wiley & Sons, Inc., 2011. doi:10.1002/9780470400531.  
 363 eorms0970.  
 364 URL <https://doi.org/10.1002/9780470400531.eorms0970>
- 365 [35] J. Jablonsky, MS excel based software support tools for decision prob-  
 366 lems with multiple criteria, Procedia Economics and Finance 12 (2014)  
 367 251–258. doi:10.1016/s2212-5671(14)00342-6.  
 368 URL <https://doi.org/10.1016%2Fs2212-5671%2814%2900342-6>
- 369 [36] J. Zhu, Quantitative Models for Performance Evaluation and Bench-  
 370 marking, Springer International Publishing, 2014. doi:10.1007/

- 371 978-3-319-06647-9.  
 372 URL <https://doi.org/10.1007%2F978-3-319-06647-9>
- 373 [37] J. Bezanson, A. Edelman, S. Karpinski, V. B. Shah, Julia: A fresh  
 374 approach to numerical computing, SIAM Review 59 (1) (2017) 65–98.  
 375 doi:10.1137/141000671.  
 376 URL <https://doi.org/10.1137%2F141000671>
- 377 [38] C.-L. Hwang, K. Yoon, Methods for multiple attribute decision making,  
 378 in: Multiple Attribute Decision Making, Springer Berlin Heidelberg,  
 379 1981, pp. 58–191. doi:10.1007/978-3-642-48318-9\_3.
- 380 [39] B. Roy, Classement et choix en présence de points de vue multiples,  
 381 RAIRO - Operations Research - Recherche Opérationnelle 2 (V1) (1968)  
 382 57–75.  
 383 URL <http://eudml.org/doc/104443>
- 384 [40] J.-P. Brans, P. Vincke, Note—a preference ranking organisation method:  
 385 (the promethee method for multiple criteria decision-making), Manage-  
 386 ment science 31 (6) (1985) 647–656.
- 387 [41] A. Gabus, E. Fontela, World problems, an invitation to further thought  
 388 within the framework of dematel, Battelle Geneva Research Center,  
 389 Geneva, Switzerland (1972) 1–8.
- 390 [42] W. K. Brauers, E. K. Zavadskas, The moora method and its application  
 391 to privatization in a transition economy, Control and cybernetics 35  
 392 (2006) 445–469.
- 393 [43] S. Opricovic, Multicriteria optimization of civil engineering systems,  
 394 Faculty of Civil Engineering, Belgrade 2 (1) (1998) 5–21.

- [44] S. Opricovic, G.-H. Tzeng, Multicriteria planning of post-earthquake sustainable reconstruction, *Computer-Aided Civil and Infrastructure Engineering* 17 (3) (2002) 211–220. doi:10.1111/1467-8667.00269. URL <https://doi.org/10.1111%2F1467-8667.00269>
- [45] T. L. Saaty, A scaling method for priorities in hierarchical structures, *Journal of Mathematical Psychology* 15 (3) (1977) 234–281. doi:10.1016/0022-2496(77)90033-5. URL <https://doi.org/10.1016%2F0022-2496%2877%2990033-5>
- [46] D. Ju-Long, Control problems of grey systems, *Systems & Control Letters* 1 (5) (1982) 288–294. doi:10.1016/s0167-6911(82)80025-x. URL <https://doi.org/10.1016%2Fs0167-6911%2882%2980025-x>
- [47] C. W. Churchman, R. L. Ackoff, An approximate measure of value, *Journal of the Operations Research Society of America* 2 (2) (1954) 172–187. doi:10.1287/opre.2.2.172. URL <https://doi.org/10.1287%2Fopre.2.2.172>
- [48] E. Triantaphyllou, S. H. Mann, An examination of the effectiveness of multi-dimensional decision-making methods: A decision-making paradox, *Decision Support Systems* 5 (3) (1989) 303–312. doi:10.1016/0167-9236(89)90037-7. URL <https://doi.org/10.1016%2F0167-9236%2889%2990037-7>
- [49] E. K. Zavadskas, Z. Turskis, A new additive ratio assessment (aras) method in multicriteria decision-making, *Technological and Economic Development of Economy* 16 (2) (2010) 159–172.
- [50] E. K. Zavadskas, Z. Turskis, J. Antucheviciene, Optimization of weighted aggregated sum product assessment, *Electronics and Electrical*

- 420 Engineering 122 (6) (jun 2012). doi:10.5755/j01.eee.122.6.1810.  
 421 URL <https://doi.org/10.5755%2Fj01.eee.122.6.1810>
- 422 [51] D. Pamučar, G. Čirović, The selection of transport and handling re-  
 423 sources in logistics centers using multi-attributive border approximation  
 424 area comparison (MABAC), Expert Systems with Applications 42 (6)  
 425 (2015) 3016–3028. doi:10.1016/j.eswa.2014.11.057.  
 426 URL <https://doi.org/10.1016%2Fj.eswa.2014.11.057>
- 427 [52] D. Pamučar, L. Vasin, L. Lukovac, Selection of railway level crossings for  
 428 investing in security equipment using hybrid dematel-marica model, in:  
 429 XVI international scientific-expert conference on railway, railcon, 2014,  
 430 pp. 89–92.
- 431 [53] E. K. Zavadskas, A. Kaklauskas, V. Sarka, The new method of multi-  
 432 criteria complex proportional assessment of projects, Technological and  
 433 economic development of economy 1 (3) (1994) 131–139.
- 434 [54] M. Yazdani, P. Zarate, E. K. Zavadskas, Z. Turskis, A combined compro-  
 435 mise solution (CoCoSo) method for multi-criteria decision-making prob-  
 436 lems, Management Decision 57 (9) (2019) 2501–2519. doi:10.1108/  
 437 md-05-2017-0458.  
 438 URL <https://doi.org/10.1108%2Fmd-05-2017-0458>
- 439 [55] D. Diakoulaki, G. Mavrotas, L. Papayannakis, Determining objective  
 440 weights in multiple criteria problems: The critic method, Comput-  
 441 ers & Operations Research 22 (7) (1995) 763–770. doi:10.1016/  
 442 0305-0548(94)00059-h.  
 443 URL <https://doi.org/10.1016%2F0305-0548%2894%2900059-h>

- 444 [56] C. E. Shannon, A mathematical theory of communication, Bell System  
445 Technical Journal 27 (3) (1948) 379–423. doi:10.1002/j.1538-7305.  
446 1948.tb01338.x.  
447 URL <https://doi.org/10.1002%2Fj.1538-7305.1948.tb01338.x>
- 448 [57] A. Charnes, W. Cooper, E. Rhodes, Measuring the efficiency of decision  
449 making units, European Journal of Operational Research 2 (6) (1978)  
450 429–444. doi:10.1016/0377-2217(78)90138-8.  
451 URL <https://doi.org/10.1016%2F0377-2217%2878%2990138-8>