

# JMcDM: A Julia package for multiple-criteria decision-making tools

Mehmet Hakan Satman<sup>a</sup>, Bahadır Fatih Yıldırım<sup>b</sup>, Ersagun Kuruca<sup>c</sup>

<sup>a</sup>*Istanbul University, Department of Econometrics, Beyazit, Istanbul, Turkey*

<sup>b</sup>*Istanbul University, Department of Transportation and Logistics, Avcılar, Istanbul, Turkey*

<sup>c</sup>*Istanbul Technical University, Department of Computer Engineering, Sarıyer, Istanbul, Turkey*

---

## Abstract

*JMcDM* is a *Julia* package that implements some leading multiple-criteria decision making tools for both researchers and developers. *Julia*'s REPL is well suited for researchers to perform their analysis using different methods and compare their results. The package also provides the necessary infrastructure and utility functions for writing recently published methods. The proposed package has brought MCDA tools to a relatively new language such as *Julia* with its significant performance promises. The methods developed in the package are also designed to be familiar to users who previously used *R* and *Python* languages. The paper presents the basics of the design, example usage, and code snippets.

*Keywords:* julia, multiple-criteria, decision-making, outranking

---

## Required Metadata

### Current code version

Nr.	Code metadata description	Please fill in this column
C1	Current code version	v0.1.6
C2	Permanent link to code/repository used for this code version	<a href="https://github.com/jbytecode/JMcDM">https://github.com/jbytecode/JMcDM</a>
C3	Code Ocean compute capsule	
C4	Legal Code License	MIT
C5	Code versioning system used	git
C6	Software code languages, tools, and services used	Julia
C7	Compilation requirements, operating environments & dependencies	Julia 1.4
C8	If available Link to developer documentation/manual	<a href="https://jbytecode.github.io/JMcDM/docs/build">https://jbytecode.github.io/JMcDM/docs/build</a>
C9	Support email for questions	mhsatman@istanbul.edu.tr

Table 1: Code metadata (mandatory)

## 1. Motivation and significance

The one-dimensional array  $a$  is in ascending order if and only if  $a_i \leq a_{i+1}$  where  $i = 1, 2, \dots, n - 1$ , and  $n$  is the length of array. In other terms, the process of ordering numbers requires the logical  $\leq$  operator to be perfectly defined. Since the operator  $\leq$  is not defined for any set of points in higher dimensions,  $\mathbb{R}^p$  for  $p \geq 2$ , there is not a unique ordering of points.

In multi-dimensional case, the binary domination operator  $\succ$  applied on points  $a$  and  $b$ ,  $a \succ b$ , is true iif each item in  $a$  is not worse than the

correspoing item in  $b$  and at least one item is better than the corresponding item in  $b$  [1]. On the other hand, the more relaxed operator  $\succeq$  returns true if each item in  $a$  is as good as the corresponding item in  $b$  [2]. Several outranking methdods in MCDA (Multiple-Criteria Decision Analysis) define a unique ranking mechanism to select the best alternative among others.

Suppose a decision process has  $n$  alternatives and  $m$  criteria which are either to be maximized or minimized. Each single criterion has a weight  $0 \leq w_i \leq 1$  where  $\sum_i^m w_i = 1$ .  $f_i$  is either maximum or minimum.  $g_j(\cdot)$  is evolution function and it is taken as  $g_j(x) = x$  in many methods. A multiple criteria decision problem can be represented using the decision table

<b>Criteria</b>	$C_1$	$C_2$	$\dots$	$C_m$
<b>Weights</b>	$w_1$	$w_2$	$\dots$	$w_m$
<b>Functions</b>	$f_1$	$f_2$	$\dots$	$f_m$
$A_1$	$g_1(A_1)$	$g_2(A_1)$	$\dots$	$g_m(S_A)$
$A_2$	$g_1(A_2)$	$g_2(A_2)$	$\dots$	$g_m(A_2)$
$\vdots$	$\vdots$	$\vdots$	$\ddots$	$\vdots$
$A_n$	$g_1(A_n)$	$g_2(A_n)$	$\dots$	$g_m(A_n)$

Table 2: A decision matrix in general form

without loss of generality. When  $A_1, A_2, \dots, A_n$  are alternatives and  $C_1, C_2, \dots, C_m$  are different situations of a single criterion then the decision problem is said to be single criterion decision problem. If  $A_i$  and  $C_j$  are strategies of two game players then  $g_j(A_i)$  is the gain of the row player when she selects the strategy  $i$  and the column player selects the strategy  $C_j$ .

MCDA is used in material selection [3, 4], supplier selection [5, 6], personnel selection [7], inventory classification [8], service provider selection [9, 10, 11, 12], strategy selection [13, 14, 15], location selection [16, 17],

project selection [18, 19, 20], performance evaluation [21, 22, 23], risk evaluation [24, 25], allocation problems [6, 26, 27], and site selection [28, 29, 30] problems in the literature.

Multiple-criteria decision-making (MCDM) tools provide several algorithms for ordering or selecting alternatives and/or determining the weights when there is uncertainty. Although some algorithms are suitable for hand calculations, a computer software is often required. *PyTOPS* is a Python tool for TOPSIS [31]. *Super Decisions* is a software package which is mainly focused on AHP (Analytic Hierarchy Process) and ANP (Analytic Network Process) [32]. *Visual Promethee* implements Promethee method on Windows platforms [33]. *M-BACBETH* is an other commercial software product that implements MACBETH with an easy to use GUI. [34]. *Sanna* is a standard MS Excel add-in application that supports several basic methods for multi-criteria evaluation of alternatives (WSA, TOPSIS, ELECTRE I and III, PROMETHEE I and II, MAPPAC and ORESTE) [35]. *DEAFrontier* software requires an Excel add-in that can solve up to 50 DMUs with unlimited number of inputs and outputs (subject to the capacity of the standard MS Excel Solver) [36].

*JMcDM* is designed to provide a developer-friendly library for solving multiple-criteria decision problems in *Julia* [37]. Since *Julia* is a dynamic language, it is also useful for researchers that familiar with REPL environments. The package includes multi-criteria decision methods as well as a game solver for zero-sum games, and methods for single criterion methods.

## 2. Software description

## 51 2.1. Software Architecture

52 *JMcDM* provides a framework for performing multi-criteria decision anal-  
53 ysis as well as it includes utility functions for development of new methods.  
54 Each single MCDM method returns an object in subtype of `MCDMResult`  
55 which is defined as

```
56 abstract type MCDMResult end
```

57 and it is used to derive new return types. For instance, the `topsis()` function  
58 always returns a `TopsisResult` object which is defined as

```
59 struct TopsisResult <: MCDMResult  
60     decisionMatrix::DataFrame  
61     weights::Array{Float64,1}  
62     normalizedDecisionMatrix::DataFrame  
63     normalizedWeightedDecisionMatrix::DataFrame  
64     bestIndex::Int64  
65     scores::Array{Float64,1}  
66 end
```

67 and holds many outputs in a single `struct`. Function definitions are also  
68 similar but they may differ depending on the requirements of algorithms.  
69 For instance the function `topsis` is defined as

```
70 function topsis(  
71     decisionMat::DataFrame,  
72     weights::Array{Float64,1},  
73     fns::Array{Function,1})::TopsisResult
```

74 where `decisionMat` is the decision matrix, `weights` are weights of criteria,  
75 and `fns` is an array of functions (either `minimum` or `maximum`) that determine  
76 the optimization directions.

77 The package is registered in *Julia* package repository and it is available  
78 for downloading and installing using *Julia*'s package manager.

```
79 julia> using Pkg
```

```
80 julia> Pkg.add("JMcDM")
```

81 and

```
82 julia> ]
```

```
83 (@v1.5) pkg> add JMcDM
```

84 present two distinct ways of downloading and installing the package.

## 85 2.2. Software Functionalities

86 The package implements methods for TOPSIS<sup>1</sup> [38], ELECTRE<sup>2</sup>[39],  
87 PROMETHEE<sup>3</sup> [40], DEMATEL<sup>4</sup> [41], MOORA<sup>5</sup> [42], VIKOR<sup>6</sup> [43, 44],  
88 AHP<sup>7</sup> [45], GRA<sup>8</sup> [46], NDS<sup>9</sup> [1], SAW<sup>10</sup> [47, 48], ARAS<sup>11</sup> [49], WPM<sup>12</sup> [48],

---

<sup>1</sup>Technique for Order Preference by Similarity to Ideal Solutions

<sup>2</sup>Elimination and Choice Translating Reality

<sup>3</sup>Preference Ranking Organization METHod for Enrichment of Evaluations

<sup>4</sup>The Decision Making Trial and Evaluation Laboratory

<sup>5</sup>Multi-Objective Optimization By Ratio Analysis

<sup>6</sup>VlseKriterijumska Optimizacija I Kaompromisno Resenje in Serbian

<sup>7</sup>Analytic Hierarchy Process

<sup>8</sup>Grey Relational Analysis

<sup>9</sup>Non-dominated Sorting

<sup>10</sup>Simple Additive Weighting

<sup>11</sup>Additive Ratio Assessment

<sup>12</sup>Weighted Product Model

WASPAS<sup>13</sup> [50], EDAS<sup>14</sup> [8], MARCOS<sup>15</sup> [5], MABAC<sup>16</sup> [51], MAIRCA<sup>17</sup> [52], COPRAS<sup>18</sup> [53], COCOSO<sup>19</sup> [54], CRITIC<sup>20</sup> [55], and Entropy[56] for multiple-criteria tools. The package also performs DEA for Data Envelopment Analysis [57] and includes a method for zero-sum game solver. The full set of other tools and utility functions are listed and documented in the source code as well as in the online documentation.

### 2.3. Sample code snippets analysis

Suppose a decision problem is given in Table 3.

Criteria	Age	Size	Price	Distance	Population
Weights	0.35	0.15	0.25	0.20	0.05
Functions	min	max	min	min	max
$A_1$	6	140	150000	950	1500
$A_2$	4	90	100000	1500	2000
$A_3$	12	140	75000	550	1100

Table 3: Decision matrix

In this sample problem, a decision maker is subject to select an apartment by considering age of the building, size (in  $m^2$ s), price (in \$), distance to city centre (in  $ms$ ), and nearby population. The data can be entered as a two-dimensional array (matrix) or as a DataFrame object:

<sup>13</sup>Weighted Aggregated Sum Product ASsessment

<sup>14</sup>Evaluation based on Distance from Average Solution

<sup>15</sup>Measurement Alternatives and Ranking according to COmpromise Solution

<sup>16</sup>Multi-Attributive Border Approximation area Comparison

<sup>17</sup>Multi Attributive Ideal-Real Comparative Analysis

<sup>18</sup>Complex PROportional ASsessment

<sup>19</sup>Combined Compromise Solution

<sup>20</sup>CRiteria Importance Through Intercriteria Correlation

```
101 julia> using JMcDM, DataFrames
```

```
102 julia> df = DataFrame(
```

```
103 :age      => [6.0, 4, 12],
```

```
104 :size     => [140.0, 90, 140],
```

```
105 :price    => [150000.0, 100000, 75000],
```

```
106 :distance => [950.0, 1500, 550],
```

```
107 :population => [1500.0, 2000, 1100]);
```

108 The weight vector **w**, vector of directions **fns**, and **topsis()** function call  
109 can be performed using the *Julia* REPL.

```
110 julia> w = [0.35, 0.15, 0.25, 0.20, 0.05];
```

```
111 julia> fns = [minimum, maximum, minimum, minimum, maximum];
```

```
112 julia> result = topsis(df, w, fns);
```

```
113 julia> result.scores
```

```
114 3-element Array{Float64,1}:
```

```
115 0.5854753145549456
```

```
116 0.6517997936899308
```

```
117 0.41850223305822903
```

```
118
```

```
119 julia> result.bestIndex
```

```
120 2
```

121 In the output above, it is shown that the alternative  $A_2$  has a score of 0.65179  
122 and it is selected as the best. The same analysis can be performed using  
123 **saw()** for the method of Simple Additive Weighting

```
124 julia> result = saw(df, w, fns);
```

```
125 julia> result.bestIndex
```

```
126 2
```



127 as well as using `wpm` for the method of Weighted Product Method

```
128 julia> result = wpm(df, w, fns);
```

```
129 julia> result.bestIndex
```

```
130 2
```

131 For any method, `?methodname` shows the documentation as in the same way  
132 in other *Julia* packages.

### 133 2.3.1. Game Solver

134 A two-player zero-sum game is not a multi-criteria decision method. On  
135 the other hand, assuming the column player's choices are natural states for  
136 the row player, the game matrix represents gains or costs for the row player  
137 depending on the alternative she plays. Table 4 represents the gains of the  
138 row player for a Rock & Paper & Scissors game. Each time the game is  
139 played, the winner takes 1 point.

	Rock	Paper	Scissors
Rock	0	-1	1
Paper	1	0	-1
Scissors	-1	1	0

Table 4: Game matrix for the Rock & Paper & Scissors game

140 Table 4 shows that the row player wins the game if she selects **Rock** and  
141 the column player selects **Scissors**. Similarly, she loses the game if she  
142 selects **Scissors** and the column player selects **Rock**. A tie has a zero gain  
143 for both players. The problem is selecting the best strategy for the row  
144 player. *JMcDM* implements the `game()` method for calculating value and  
145 the best strategy of this kind of games. The code snippet below represents  
146 the problem.

```

147 julia> mat = [0 -1 1; 1 0 -1; -1 1 0];
148 julia> dm = makeDecisionMatrix(mat);
149 julia> result = game(dm);

```

150 The `makeDecisionMatrix()` method returns a modified copy of the matrix  
 151 `mat` as the minimum value of the new matrix is non-negative. The function  
 152 `game()` returns a `GameResult` object which holds the value of the game and  
 153 the probabilities of the alternatives for the row player.

```

154 julia> result.value
155 0.0
156 julia> result.row_player_probabilities
157 3-element Array{Float64,1}:
158 0.3333333333333333
159 0.3333333333333337
160 0.3333333333333333

```

161 It is shown that the value of the game is zero and the row player should select  
 162 the alternatives with equal probability of  $\frac{1}{3}$  in each iteration.

### 163 **3. Illustrative Examples**

164 Since *JMcDM* is designed as a software library and for REPL use, it does  
 165 not implement a significant user interface. However, the `summary()` function  
 166 provides a useful way to perform a list of methods and it returns a text based  
 167 result to compare results.

```

168 julia> methods1 = [:topsis, :electre, :vikor,
169                  :moora, :cocoso, :wpm, :waspas];
170 julia> result1 = summary(df, w, fns, methods1);

```

```
julia> result1
```

3x7 DataFrame

Row	topsis	electre	cocoso	moora	vikor	wpm	waspas
	String	String	String	String	String	String	String
1			✓	✓	✓		
2	✓	✓				✓	✓
3		✓					

Figure 1: Results of TOPSIS, ELECTRE, VIKOR, MOORA, COCOSO, WPM, and WASPAS

Figure 1 represents the output of the `summary()` call for methods TOPSIS, ELECTRE, VIKOR, MOORA, COCOSO, WPM, and WASPAS, respectively.

```
julia> methods2 = [:aras, :saw, :edas, :marcos,
                  :mabac, :mairca, :grey];
julia> result2 = summary(df, w, fns, methods2);
```

Figure 2 represents the output of the `summary()` call for methods ARAS, SAW, EDAS, MARCOS, MABAC, MAIRCA, and GREY, respectively. Figure 1 and Figure 2 also show the necessity of using more than one decision-making tool as they produce different results for the same analysis.

#### 4. Impact

*JMcDM* provides a moderate number of MCDA tools and utility functions for developing new methods as well as performing decision analysis using a single function call for each method. A researcher can easily perform sequential analysis by changing the problem parameters and can compare results of many tools. Existing software packages are mainly focused on providing a small subset of methods. *JMcDM* is an all-in-one solution and has

```
julia> result2
```

3x7 DataFrame

Row	grey	aras	saw	edas	marcos	mabac	mairca
	String	String	String	String	String	String	String
1							
2		✓	✓	✓	✓		
3	✓					✓	✓

Figure 2: Results of ARAS, SAW, EDAS, MARCOS, MABAC, MAIRCA, and GREY

188 potential for increasing user productivity. Seeing the different results pro-  
 189 duced by the methods together also helps to discover which parameters the  
 190 research is more sensitive to and the reasons for them.

## 191 5. Conclusions

192 Multiple-criteria decision-making tools are used in various disciplines in  
 193 the literature. Since it is difficult to compute these tools manually, many soft-  
 194 ware packages and programs have been developed. However, these packages  
 195 include a selected subset of methods. *JMcDM* is a *Julia* package that con-  
 196 tains a significant amount of tools in the literature. Implementations of these  
 197 tools are straightforward to use in *Julia* REPL for researchers. *JMcDM* also  
 198 provides the necessary infrastructure for the development of new methods in  
 199 the literature with its utility functions, comprehensive documentation, and  
 200 unit tests compiled from many text books. The proposed package has also  
 201 brought MCDA tools to a relatively new language such as *Julia* with signif-  
 202 icant performance promises. The methods in the package are also designed  
 203 to be familiar to users who previously used R and Python languages.

## 204 6. Conflict of Interest

205 We wish to confirm that there are no known conflicts of interest associated  
206 with this publication and there has been no significant financial support for  
207 this work that could have influenced its outcome.

## 208 Acknowledgements

209 The authors would like to thank the Editor-in-Chief, editors, reviewers for  
210 providing extremely insightful comments, and other staff of the SoftwareX  
211 Journal.

## 212 References

- 213 [1] K. Deb, A. Pratap, S. Agarwal, T. Meyarivan, A fast and elitist multiob-  
214 jective genetic algorithm: NSGA-II, IEEE Transactions on Evolutionary  
215 Computation 6 (2) (2002) 182–197. doi:10.1109/4235.996017.
- 216 [2] S. Greco, J. Figueira, M. Ehrgott, Multiple criteria decision analysis,  
217 Vol. 37, Springer, 2016.
- 218 [3] K. Maniya, M. Bhatt, A selection of material using a novel type decision-  
219 making method: Preference selection index method, Materials & Design  
220 31 (4) (2010) 1785–1789. doi:10.1016/j.matdes.2009.11.020.  
221 URL <https://doi.org/10.1016%2Fj.matdes.2009.11.020>
- 222 [4] I. Emovon, O. S. Oghenenyero, Application of MCDM method in  
223 material selection for optimal design: A review, Results in Materials 7  
224 (2020) 100115. doi:10.1016/j.rinma.2020.100115.  
225 URL <https://doi.org/10.1016%2Fj.rinma.2020.100115>

- 226 [5] Ž. Stević, D. Pamučar, A. Puška, P. Chatterjee, Sustainable supplier se-  
 227 lection in healthcare industries using a new MCDM method: Measure-  
 228 ment of alternatives and ranking according to COMpromise solution  
 229 (MARCOS), Computers & Industrial Engineering 140 (2020) 106231.  
 230 doi:10.1016/j.cie.2019.106231.  
 231 URL <https://doi.org/10.1016%2Fj.cie.2019.106231>
- 232 [6] A. Rezaei, M. R. Galankashi, S. Mansoorzadeh, F. M. Rafiei, Supplier  
 233 selection and order allocation with lean manufacturing criteria: An inte-  
 234 grated MCDM and bi-objective modelling approach, Engineering Man-  
 235 agement Journal 32 (4) (2020) 253–271. doi:10.1080/10429247.2020.  
 236 1753490.  
 237 URL <https://doi.org/10.1080%2F10429247.2020.1753490>
- 238 [7] A. Ulutaş, G. Popovic, D. Stanujkic, D. Karabasevic, E. K. Zavadskas,  
 239 Z. Turskis, A new hybrid MCDM model for personnel selection based on  
 240 a novel grey PIPRECIA and grey OCRA methods, Mathematics 8 (10)  
 241 (2020) 1698. doi:10.3390/math8101698.  
 242 URL <https://doi.org/10.3390%2Fmath8101698>
- 243 [8] M. K. Ghorabae, E. K. Zavadskas, L. Olfat, Z. Turskis, Multi-criteria  
 244 inventory classification using a new method of evaluation based on dis-  
 245 tance from average solution (EDAS), Informatica 26 (3) (2015) 435–451.  
 246 doi:10.15388/informatica.2015.57.  
 247 URL <https://doi.org/10.15388%2Finformatica.2015.57>
- 248 [9] E. ÖZCAN, M. AHISKALI, 3pl service provider selection with a goal  
 249 programming model supported with multicriteria decision making ap-  
 250 proaches, GAZI UNIVERSITY JOURNAL OF SCIENCE 33 (2) (2020)

- 251 413–427. doi:10.35378/gujs.552070.  
 252 URL <https://doi.org/10.35378%2Fgujs.552070>
- 253 [10] A. R. Mishra, P. Rani, K. Pandey, Fermatean fuzzy CRITIC-EDAS  
 254 approach for the selection of sustainable third-party reverse logistics  
 255 providers using improved generalized score function, Journal of Ambi-  
 256 ent Intelligence and Humanized Computing (feb 2021). doi:10.1007/  
 257 s12652-021-02902-w.  
 258 URL <https://doi.org/10.1007%2Fs12652-021-02902-w>
- 259 [11] R. R. Kumar, B. Kumari, C. Kumar, CCS-OSSR: A framework based  
 260 on hybrid MCDM for optimal service selection and ranking of cloud  
 261 computing services, Cluster Computing (aug 2020). doi:10.1007/  
 262 s10586-020-03166-3.  
 263 URL <https://doi.org/10.1007%2Fs10586-020-03166-3>
- 264 [12] A. E. Youssef, An integrated MCDM approach for cloud service selection  
 265 based on TOPSIS and BWM, IEEE Access 8 (2020) 71851–71865. doi:  
 266 10.1109/access.2020.2987111.  
 267 URL <https://doi.org/10.1109%2Faccess.2020.2987111>
- 268 [13] G. Büyüközkan, E. Mukul, E. Kongar, Health tourism strategy se-  
 269 lection via SWOT analysis and integrated hesitant fuzzy linguistic  
 270 AHP-MABAC approach, Socio-Economic Planning Sciences (2020)  
 271 100929doi:10.1016/j.seps.2020.100929.  
 272 URL <https://doi.org/10.1016%2Fj.seps.2020.100929>
- 273 [14] A. Jain, J. D. Darbari, A. Kaul, P. C. Jha, Selection of a green mar-  
 274 keting strategy using MCDM under fuzzy environment, in: Advances  
 275 in Intelligent Systems and Computing, Springer Singapore, 2019, pp.

- 276 499–512. doi:10.1007/978-981-15-0184-5\_43.  
 277 URL [https://doi.org/10.1007%2F978-981-15-0184-5\\_43](https://doi.org/10.1007%2F978-981-15-0184-5_43)
- 278 [15] Y. S. ÖZDEMİR, , A. ÜSKÜDAR, Strategy selection by using interval  
 279 type-2 fuzzy mcdm and an application, Journal of Engineering Research  
 280 8 (3) (2020) 172–189. doi:10.36909/jer.v8i3.8176.  
 281 URL <https://doi.org/10.36909%2Fjer.v8i3.8176>
- 282 [16] S. Tadić, M. Krstić, V. Roso, N. Brnjac, Dry port terminal location se-  
 283 lection by applying the hybrid grey MCDM model, Sustainability 12 (17)  
 284 (2020) 6983. doi:10.3390/su12176983.  
 285 URL <https://doi.org/10.3390%2Fsu12176983>
- 286 [17] A. Karaşan, İ. Kaya, M. Erdoğan, Location selection of electric vehicles  
 287 charging stations by using a fuzzy MCDM method: a case study in  
 288 turkey, Neural Computing and Applications 32 (9) (2018) 4553–4574.  
 289 doi:10.1007/s00521-018-3752-2.  
 290 URL <https://doi.org/10.1007%2Fs00521-018-3752-2>
- 291 [18] D. Pramanik, S. C. Mondal, A. Halder, A framework for managing un-  
 292 certainty in information system project selection: an intelligent fuzzy  
 293 approach, International Journal of Management Science and Engineer-  
 294 ing Management 15 (1) (2019) 70–78. doi:10.1080/17509653.2019.  
 295 1604191.  
 296 URL <https://doi.org/10.1080%2F17509653.2019.1604191>
- 297 [19] C.-Y. Huang, H.-L. Hsieh, H. Chen, Evaluating the investment projects  
 298 of spinal medical device firms using the real option and DANP-mV based  
 299 MCDM methods, International Journal of Environmental Research and



- Public Health 17 (9) (2020) 3335. doi:10.3390/ijerph17093335.  
URL <https://doi.org/10.3390%2Fijerph17093335>
- [20] D. G. B. Souza, C. E. S. Silva, N. Y. Soma, Selecting projects on the  
brazilian r&d energy sector: A fuzzy-based approach for criteria selec-  
tion, IEEE Access 8 (2020) 50209–50226. doi:10.1109/access.2020.  
2979666.  
URL <https://doi.org/10.1109%2Faccess.2020.2979666>
- [21] M. Abdel-Basset, W. Ding, R. Mohamed, N. Metawa, An integrated  
plithogenic MCDM approach for financial performance evaluation of  
manufacturing industries, Risk Management 22 (3) (2020) 192–218.  
doi:10.1057/s41283-020-00061-4.  
URL <https://doi.org/10.1057%2Fs41283-020-00061-4>
- [22] B. F. Yildirim, B. A. Mercangoz, Evaluating the logistics performance of  
OECD countries by using fuzzy AHP and ARAS-g, Eurasian Economic  
Review 10 (1) (2019) 27–45. doi:10.1007/s40822-019-00131-3.  
URL <https://doi.org/10.1007%2Fs40822-019-00131-3>
- [23] B. A. Mercangoz, , B. Yildirim, S. K. Yildirim, Time period based  
COPRAS-g method: application on the logistics performance index,  
Logforum 16 (2) (2020) 239–250. doi:10.17270/j.log.2020.432.  
URL <https://doi.org/10.17270%2Fj.log.2020.432>
- [24] S. Guo, W. Zhang, X. Gao, Business risk evaluation of electricity retail  
company in china using a hybrid MCDM method, Sustainability 12 (5)  
(2020) 2040. doi:10.3390/su12052040.  
URL <https://doi.org/10.3390%2Fsu12052040>

- [25] Y. Duan, Y. Sun, Y. Zhang, X. Fan, Q. Dong, S. Guo, Risk evaluation of electric power grid investment in china employing a hybrid novel MCDM method, *Mathematics* 9 (5) (2021) 473. doi:10.3390/math9050473.  
URL <https://doi.org/10.3390/math9050473>
- [26] E. F. E. A. Mills, M. A. Baafi, N. Amowine, K. Zeng, A HYBRID GREY MCDM APPROACH FOR ASSET ALLOCATION: EVIDENCE FROM CHINA'S SHANGHAI STOCK EXCHANGE, *Journal of Business Economics and Management* 21 (2) (2020) 446–472. doi:10.3846/jbem.2020.11967.  
URL <https://doi.org/10.3846/jbem.2020.11967>
- [27] D. Sarma, A. Das, P. Dutta, U. K. Bera, A cost minimization resource allocation model for disaster relief operations with an information crowdsourcing-based MCDM approach, *IEEE Transactions on Engineering Management* (2020) 1–21doi:10.1109/tem.2020.3015775.  
URL <https://doi.org/10.1109/tem.2020.3015775>
- [28] A. Ghosh, N. Ghorui, S. P. Mondal, S. Kumari, B. K. Mondal, A. Das, M. S. Gupta, Application of hexagonal fuzzy MCDM methodology for site selection of electric vehicle charging station, *Mathematics* 9 (4) (2021) 393. doi:10.3390/math9040393.  
URL <https://doi.org/10.3390/math9040393>
- [29] G. Sisay, S. L. Gebre, K. Getahun, GIS-based potential landfill site selection using MCDM-AHP modeling of gondar town, ethiopia, *African Geographical Review* (2020) 1–20doi:10.1080/19376812.2020.1770105.  
URL <https://doi.org/10.1080/19376812.2020.1770105>
- [30] M. Lin, C. Huang, Z. Xu, MULTIMOORA based MCDM model for

- 349 site selection of car sharing station under picture fuzzy environment,  
 350 Sustainable Cities and Society 53 (2020) 101873. doi:10.1016/j.scs.  
 351 2019.101873.  
 352 URL <https://doi.org/10.1016%2Fj.scs.2019.101873>
- 353 [31] V. Yadav, S. Karmakar, P. P. Kalbar, A. Dikshit, PyTOPS: A python  
 354 based tool for TOPSIS, SoftwareX 9 (2019) 217–222. doi:10.1016/j.  
 355 softx.2019.02.004.
- 356 [32] W. Adams, R. Saaty, Super decisions software guide (2003).  
 357 URL [https://superdecisions.com/sd\\_resources/v28\\_man01.pdf](https://superdecisions.com/sd_resources/v28_man01.pdf)
- 358 [33] B. Mareschal, Y. D. Smet, Visual PROMETHEE: Developments of the  
 359 PROMETHEE - GAIA multicriteria decision aid methods, in: 2009  
 360 IEEE International Conference on Industrial Engineering and Engineer-  
 361 ing Management, IEEE, 2009. doi:10.1109/ieem.2009.5373124.
- 362 [34] C. A. Bana e Costa, J.-M. de Corte, J.-C. Vansnick, MACBETH  
 363 (Measuring Attractiveness by a Categorical Based Evaluation Tech-  
 364 nique), Wiley Encyclopedia of Operations Research and Management  
 365 Science, John Wiley & Sons, Inc., 2011. doi:10.1002/9780470400531.  
 366 eorms0970.  
 367 URL <https://doi.org/10.1002/9780470400531.eorms0970>
- 368 [35] J. Jablonsky, MS excel based software support tools for decision prob-  
 369 lems with multiple criteria, Procedia Economics and Finance 12 (2014)  
 370 251–258. doi:10.1016/s2212-5671(14)00342-6.  
 371 URL <https://doi.org/10.1016%2Fs2212-5671%2814%2900342-6>
- 372 [36] J. Zhu, Quantitative Models for Performance Evaluation and Bench-  
 373 marking, Springer International Publishing, 2014. doi:10.1007/

- 374 978-3-319-06647-9.  
 375 URL <https://doi.org/10.1007%2F978-3-319-06647-9>
- 376 [37] J. Bezanson, A. Edelman, S. Karpinski, V. B. Shah, Julia: A fresh  
 377 approach to numerical computing, SIAM Review 59 (1) (2017) 65–98.  
 378 doi:10.1137/141000671.  
 379 URL <https://doi.org/10.1137%2F141000671>
- 380 [38] C.-L. Hwang, K. Yoon, Methods for multiple attribute decision making,  
 381 in: Multiple Attribute Decision Making, Springer Berlin Heidelberg,  
 382 1981, pp. 58–191. doi:10.1007/978-3-642-48318-9\_3.
- 383 [39] B. Roy, Classement et choix en présence de points de vue multiples,  
 384 RAIRO - Operations Research - Recherche Opérationnelle 2 (V1) (1968)  
 385 57–75.  
 386 URL <http://eudml.org/doc/104443>
- 387 [40] J.-P. Brans, P. Vincke, Note—a preference ranking organisation method:  
 388 (the promethee method for multiple criteria decision-making), Manage-  
 389 ment science 31 (6) (1985) 647–656.
- 390 [41] A. Gabus, E. Fontela, World problems, an invitation to further thought  
 391 within the framework of dematel, Battelle Geneva Research Center,  
 392 Geneva, Switzerland (1972) 1–8.
- 393 [42] W. K. Brauers, E. K. Zavadskas, The moora method and its application  
 394 to privatization in a transition economy, Control and cybernetics 35  
 395 (2006) 445–469.
- 396 [43] S. Opricovic, Multicriteria optimization of civil engineering systems,  
 397 Faculty of Civil Engineering, Belgrade 2 (1) (1998) 5–21.

- [44] S. Opricovic, G.-H. Tzeng, Multicriteria planning of post-earthquake sustainable reconstruction, *Computer-Aided Civil and Infrastructure Engineering* 17 (3) (2002) 211–220. doi:10.1111/1467-8667.00269. URL <https://doi.org/10.1111%2F1467-8667.00269>
- [45] T. L. Saaty, A scaling method for priorities in hierarchical structures, *Journal of Mathematical Psychology* 15 (3) (1977) 234–281. doi:10.1016/0022-2496(77)90033-5. URL <https://doi.org/10.1016%2F0022-2496%2877%2990033-5>
- [46] D. Ju-Long, Control problems of grey systems, *Systems & Control Letters* 1 (5) (1982) 288–294. doi:10.1016/s0167-6911(82)80025-x. URL <https://doi.org/10.1016%2Fs0167-6911%2882%2980025-x>
- [47] C. W. Churchman, R. L. Ackoff, An approximate measure of value, *Journal of the Operations Research Society of America* 2 (2) (1954) 172–187. doi:10.1287/opre.2.2.172. URL <https://doi.org/10.1287%2Fopre.2.2.172>
- [48] E. Triantaphyllou, S. H. Mann, An examination of the effectiveness of multi-dimensional decision-making methods: A decision-making paradox, *Decision Support Systems* 5 (3) (1989) 303–312. doi:10.1016/0167-9236(89)90037-7. URL <https://doi.org/10.1016%2F0167-9236%2889%2990037-7>
- [49] E. K. Zavadskas, Z. Turskis, A new additive ratio assessment (aras) method in multicriteria decision-making, *Technological and Economic Development of Economy* 16 (2) (2010) 159–172.
- [50] E. K. Zavadskas, Z. Turskis, J. Antucheviciene, Optimization of weighted aggregated sum product assessment, *Electronics and Electrical*

- 423 Engineering 122 (6) (jun 2012). doi:10.5755/j01.eee.122.6.1810.  
 424 URL <https://doi.org/10.5755%2Fj01.eee.122.6.1810>
- 425 [51] D. Pamučar, G. Čirović, The selection of transport and handling re-  
 426 sources in logistics centers using multi-attributive border approximation  
 427 area comparison (MABAC), Expert Systems with Applications 42 (6)  
 428 (2015) 3016–3028. doi:10.1016/j.eswa.2014.11.057.  
 429 URL <https://doi.org/10.1016%2Fj.eswa.2014.11.057>
- 430 [52] D. Pamučar, L. Vasin, L. Lukovac, Selection of railway level crossings for  
 431 investing in security equipment using hybrid dematel-marica model, in:  
 432 XVI international scientific-expert conference on railway, railcon, 2014,  
 433 pp. 89–92.
- 434 [53] E. K. Zavadskas, A. Kaklauskas, V. Sarka, The new method of multi-  
 435 criteria complex proportional assessment of projects, Technological and  
 436 economic development of economy 1 (3) (1994) 131–139.
- 437 [54] M. Yazdani, P. Zarate, E. K. Zavadskas, Z. Turskis, A combined compro-  
 438 mise solution (CoCoSo) method for multi-criteria decision-making prob-  
 439 lems, Management Decision 57 (9) (2019) 2501–2519. doi:10.1108/  
 440 md-05-2017-0458.  
 441 URL <https://doi.org/10.1108%2Fmd-05-2017-0458>
- 442 [55] D. Diakoulaki, G. Mavrotas, L. Papayannakis, Determining objective  
 443 weights in multiple criteria problems: The critic method, Comput-  
 444 ers & Operations Research 22 (7) (1995) 763–770. doi:10.1016/  
 445 0305-0548(94)00059-h.  
 446 URL <https://doi.org/10.1016%2F0305-0548%2894%2900059-h>

- 447 [56] C. E. Shannon, A mathematical theory of communication, Bell System  
448 Technical Journal 27 (3) (1948) 379–423. doi:10.1002/j.1538-7305.  
449 1948.tb01338.x.  
450 URL <https://doi.org/10.1002%2Fj.1538-7305.1948.tb01338.x>
- 451 [57] A. Charnes, W. Cooper, E. Rhodes, Measuring the efficiency of decision  
452 making units, European Journal of Operational Research 2 (6) (1978)  
453 429–444. doi:10.1016/0377-2217(78)90138-8.  
454 URL <https://doi.org/10.1016%2F0377-2217%2878%2990138-8>