


Schematics for Breakout Examples



This document contains wiring diagrams and component lists for the examples. A diagram may be used for more than one example file. The corresponding files are listed for each diagram.

Getting Started: Hello World


/examples/getting_started/hello_world.html

/examples/getting_started/hello_world_node.html

/examples/processing_js/basic_example.html

Component List

- Button
- Led
- 10k resistor
- 330 ohm resistor




Getting Started: Analog Input

/examples/getting_started/analog_input.html


Component List

- Potentiometer



Actuators: Servo

</examples/actuators/servo.html>




Component List

- Servo motor
- Potentiometer

Actuators: DC Motor

</examples/actuators/DCmotor.html>




Note that in this schematic the motor is powered by the Arduino. If you connect anything to the motor you should use an external power supply for the motor. See the schematic on the next page.

Component List

- DC motor
- 0.1 μ F capacitor
- H-bridge SN754410 or equivalent

</examples/actuators/DCmotor.html>




- DC motor
- 0.1 μ F capacitor
- 9V battery & holder
- H-bridge SN754410 or equivalent

Actuators: RGB Led (Common Cathode)

/examples/actuators/rgb_led.html

Component List

- RGB led
- 3 330 ohm resistors
- Button
- 10k resistor




Check the data sheet for the LED to determine if it is common cathode or common anode

Actuators: RGB Led (Common Anode)

/examples/actuators/rgb_led.html

Component List

- RGB led
- 3 330 ohm resistors
- Button
- 10k resistor



Check the data sheet for the LED to determine if it is common cathode or common anode.


Note: In the `rgb_led.html` example change `COMMON_CATHODE` to `COMMON_ANODE` on line 104.

Actuators: BlinkM RGB Led Module

</examples/actuators/blinkM.html>

Component List

- BlinkM led module
- Button
- 10k resistor



Filters: Filtering Analog Input


</examples/filters/convolution.html>

</examples/filters/scaler.html>

</examples/filters/triggerpoint.html>

Component List

- Potentiometer



Filters: Filtering Analog Input


</examples/filters/convolution.html>

</examples/filters/scaler.html>

</examples/filters/triggerpoint.html>

Component List

- Potentiometer




Generators: Generating Output Signals

</examples/generators/oscillator.html>


Component List

- 2 Leds
- 2 330 ohm resistors



Sensors: Force Sensing Resistor (FSR)

</examples/sensors/fsr.html>




Component List

- FSR
- 10k resistor

Sensors: Flex Sensor

</examples/sensors/flex.html>



Component List


- Flex sensor
- 10k resistor

Sensors: Temperature Sensor

</examples/sensors/temperature.html>

Component List

- LM335 temp sensor
- 330 ohm resistor




Sensors: Sharp IR Proximity Sensor

/examples/sensors/sharp_ir.html

Component List

- Sharp IR proximity sensor
- 10uF capacitor




Sensors: Sonar Sensor

</examples/sensors/sonar.html>


Component List

- LV-MaxSonar-EZ1



Sensors: Softpot

</examples/sensors/softpot.html>



Component List

- Softpot
- 10k resistor

Sensors: Analog Accelerometer

/examples/sensors/analog_accelerometer.html


/examples/sensors/calibrate_accelerometer.html

/examples/three_js/accelerometer.html

/examples/processing_js/accelerometer.html

Component List

- ADXL335 (or 330)
- Button
- 10k resistor



The analog accelerometer examples should work for any analog accelerometer. The ADXL335 just happens to be the accelerometer used for this schematic.

Sensors: HMC6352 Compass


</examples/sensors/hmc6352.html>

/examples/processing_js/compass.html


Component List

- HMC6352 compass
- Arduino FIO, Uno or other I/O board

Unlike the other I2C sensors in this document, the HMC6352 is 5v tolerant so you can use it with any I/O board.



Arduino FIO with XBee wireless connection




Arduino Uno or other board

Sensors: HMC5883 3-axis Magnetometer

</examples/sensors/hmc5883.html>


Component List

- HMC5883 magnetometer
- Arduino FIO,
or Pro Mini (3.3v),
or other 3.3v I/O board



Arduino FIO with Xbee
wireless connection

- OR -



Arduino Pro Mini 3.3v with
FTDI Basic Breakout 3.3v

You must use this sensor with a 3.3v or lower I/O board or use a logic level converter if using an I/O board at a higher voltage.


See Appendix A for an example of wiring a low voltage I2C sensor to a 5v I/O board.

Sensors: ADXL345 3-axis Accelerometer

</examples/sensors/adxl345.html>


Component List

- ADXL345 accelerometer
- Arduino FIO,
or Pro Mini (3.3v),
or other 3.3v I/O board



Arduino FIO with Xbee
wireless connection

- OR -



Arduino Pro Mini 3.3v with
FTDI Basic Breakout 3.3v


You must use this sensor with a 3.3v or lower I/O board or use a logic level converter if using an I/O board at a higher voltage.

See Appendix A for an example of wiring a low voltage I2C sensor to a 5v I/O board.

Sensors: ITG3200 3-axis Gyroscope


</examples/sensors/itg3200.html>

/examples/processing_js/gyro.html



Arduino FIO with XBee
wireless connection

- OR -



Arduino Pro Mini 3.3v with
FTDI Basic Breakout 3.3v

Component List


- ITG3200 gyro
- Button
- 10k resistor
- Arduino FIO,
or Pro Mini (3.3v),
or other 3.3v I/O board

You must use this sensor with a 3.3v or lower I/O board or use a logic level converter if using an I/O board at a higher voltage.

See Appendix A for an example of wiring a low voltage I2C sensor to a 5v I/O board.

Boards: Teensy 2.0

</examples/boards/teensy.html>




This schematic is used to test the Teensy 2.0 board with Breakout. The teensy.html example can be used even if you do not have all of these components.

Component List

- Teensy 2.0
- 2 Buttons
- 2 10k resistors
- 2 Leds
- 2 330 ohm resistors
- Potentiometer
- Servo
- HMC6352 Compass
- BlinkM Led Module

Boards: Arduino Mega

</examples/boards/mega.html>




Component List

- Arduino Mega
- 2 Buttons
- 2 10k resistors
- 1 Led
- 1 330 ohm resistors
- Potentiometer
- Servo
- HMC6352 Compass
- BlinkM Led Module

This schematic is used to test the Arduino Mega board with Breakout. The mega.html example can be used even if you do not have all of these components.

Boards: Arduino Uno

</examples/boards/uno.html>



Component List


- Arduino Uno (or other similar)
- 2 Buttons
- 2 10k resistors
- 2 Leds
- 1 RGB Led
- 5 330 ohm resistors
- Potentiometer
- Servo
- HMC6352 Compass
- BlinkM Led Module

This schematic is used to test the Arduino Uno (or similar) board with Breakout. The uno.html example can be used even if you do not have all of these components.

Boards: Arduino Leonardo

</examples/boards/leonardo.html>

Please note: An Arduino Uno R3 is pictured below because the Leonardo board has not yet been added to Fritzing. However the pinout on the Leonardo board is the same as in the illustration below.



Component List

- Arduino Leonardo
- 2 Buttons
- 2 10k resistors
- 2 Leds
- 2 330 ohm resistors
- Potentiometer
- Servo
- HMC6352 Compass
- BlinkM Led Module


This schematic is used to test the Arduino Leonardo board with Breakout. The leonardo.html example can be used even if you do not have all of these components.

Appendix A: Using 3.3v I2C Sensors with a 5v I/O board

Although the itg3200 gyro is featured in this schematic, it applies to any I2C sensors that require 3.3v or less.

Component List

- ITG3200 gyro
(or other I2C sensor)
- Arduino
- PCA9306 level
translator breakout board



You can also connect multiple I2C sensors to the same translator board all sensors share the I2C bus (SCL and SDA)