What is UUID?

- Universally
- Unique
- IDentifier

(Also known as GUID, for "Globally")

UUID variations

- Some have random-ish
 - Others NOT!
- Often factor in date/time
- Some pull in other info bits
- Generated by algorithm, not a central producer
- Attempt to make collision practical impossibility

session ids want unpredictable in addition to unique

• why?

UUID in node

Here's one library:

```
npm install uuid

const { v4: uuidv4 } = require('uuid');
// same as `const uuidv4 = require('uuid').v4;`

const uid = uuidv4();
```

UUID as session id in express

```
app.use(express.urlencoded({ extended: false }));
const sessions = {};

app.post('/session', (req,res) => {
    const username = req.body.username.trim();
    if(username === 'dog' || !username){
        // Give better errors than this!
        res.status(403).send('invalid username');
        return;
    }
    const sid = uuidv4();
    sessions[sid] = { username }; // Do you know why?
    res.cookie('sid', sid);
    res.redirect('/');
});
```

Checking the SID in express

```
app.get('/users', (req,res) => {
  const sid = req.cookies.sid;
  if(!sid || !isValid(sid)) {
    res.clearCookie('sid');
    res.sendStatus(401);
    return;
  }
  const { username } = sessions[sid];
  // Do whatever here
});
```

Removing SID to end session

Imagine we have a /logout route

- Is this a GET or a POST?
 - When we get to REST, the question changes
- How do we clear the sid cookie?
 - res.clearCookie('sid');
 - OR, set cookie to blank value
 - OR, set cookie to immediately expire
- How do we clear the data from the server?

Lab

- Make a server with a dynamic page /
 - checks the sid cookie
 - if you have a valid login:
 - Says you are logged in as \${username}
 - If not a valid sid
 - shows a form asking for username
- Add a dynamic page /login
 - Requires a username to be passed (via POST)
 - If there is a username and it is not "dog"
 - creates a uuid and assign it to sid cookie
 - relates the uuid value to username
 - redirects to /