

# A model of navigation history

Connor G. Brewster

Alan Jeffrey

DRAFT of 2016-06-24

**Abstract:** Navigation has been a core component of the web since its inception: users and scripts can follow hyperlinks, or can go back or forwards through the session history. Despite its long existence, navigation history has no formal model or properties. In this paper, we present a formal model aligned with the WHATWG specification of navigation history, and investigate its properties. The fundamental property of navigation history is that traversing the history by  $\delta$  then by  $\delta'$  should be the same as traversing by  $\delta + \delta'$ . In particular, traversing by  $+1$  (forward) then by  $-1$  (back) is the same as traversing by  $0$  (doing nothing). We show that the specification-aligned model does not satisfy this property, by exhibiting a series of counter-examples, which motivate three patches to the model. The patched model is homomorphic. We present a series of experiments, showing that browsers are inconsistent in their implementation of navigation history, but that their behaviour is closer to the patched model than to the specification-aligned model. We propose patches to the specification to align it with the homomorphic model.

**ACM Classification:** D.2.1 Requirements/Specifications.


**Keywords:** Formal model, Navigation, Session history, Specification, Web browsers.

## 1. Introduction


Navigation has been a core component of the web since its inception: users and scripts can follow hyperlinks, or can go back or forwards through the session history. Users are exposed to this functionality through following hyperlinks, and by the forward and back buttons. Scripts have many ways of accessing session history, via the navigation API [1, §7.7] and the `element.click()` method.

Despite its long existence, navigation history has no formal model or properties. The specification of the navigation API is informal, and has complex dependencies on the rest of the HTML specification [1]. There is little discussion of the goals of the API, and an unclear alignment with browser implementations.

In this paper, we present a formal model of navigation, aligned with the HTML specification, and investigate its properties. The starting point is that there is a total order of *documents*<sup>1</sup>, one of which is *active*, for example:



In diagrams, we use left-to-right order to indicate order, and highlight the active document. The user can *traverse* the history which changes the active document, for example pressing the back button:



<sup>1</sup>We are eliding some of the technical details of the specification here, in particular we are conflating a *browsing context* with the document it contains, and we are ignoring issues around document loading and unloading.



The user can also *navigate*, which replaces any document after the currently active document by a fresh document:




Users can also traverse the history by more than one document at a time, for example by using a pull-down menu from the back or forwards button. This is called *traversing by  $\delta$* , for instance we can traverse our running example by  $-2$  to get:




We formalize the notions of traversal and navigation in §2, and show that they satisfy two pleasant properties:

- *traverse-then-traverse*: traversing by  $\delta$  then by  $\delta'$  is the same as traversing by  $\delta + \delta'$ .
- *navigate-then-traverse*: navigating then traversing by  $-1$  has the original active document.


Thus far, the model is refreshingly simple, and corresponds well to the specification and to browser implementations. Where the problems arise is in the *hierarchical* nature of documents. HTML documents can contain `iframe` elements, which are independent documents in their own right, often used to embed third party content such as advertisements. We can treat each document as a tree, for example:




The problem comes from the ability of each document to navigate separately and maintain its own session history, but that traversal is a global operation that operates on the *joint session history*. For example if document 2 in the previous example navigates, the resulting state is:



and then if document 1 navigates, the state is:



Note that node 4 here is in an unusual state: it is active, but has an inactive ancestor. The specification [1, §7.7] distinguishes between *active* documents such as 4, and *fully active* documents such as 0, 3 and 5. Active documents can become fully active by traversals involving their ancestors. For example, after traversing by  $-1$ , document 4 is fully active:



As even a simple example like this shows, the combination of features quickly results in a complex mix of session history, ordering, and document hierarchy, which leads to the problems:

- *Formally* there is no simple model, and the model provided by the specification does not satisfy the traverse-then-traverse property.
- *Experimentally* the browsers disagree with each other, and with the HTML specification, about the semantics of navigation.

In this paper, we address these:

- §2 provides a formal model of navigation history, which is intended to align with the specification. We show, through a series of examples, that it does not satisfy the traverse-then-traverse property, and give patches to the model for each example. The final model does satisfy the traverse-then-traverse property.
- §3 investigates how well the patched model aligns with existing browser implementations. We show ways in which the browsers exhibit behaviours which are not aligned with the specification, and discuss how our proposed model matches these behaviours.

Finally, we propose changed wording to the specification, which would bring it in line with our patched model.

## 2. Model

### 2.1. Preliminaries

A *directed graph*  $G = (V, \rightarrow)$  consists of:

- a set  $V$  (the *vertices*), and
- a relation  $\rightarrow \subseteq (V \times V)$

The *transitive closure* of  $\rightarrow$  is defined as  $v \rightarrow^+ v'$  whenever there exists  $v_0, \dots, v_n$  such that:

$$v = v_0 \rightarrow \dots \rightarrow v_n = v'$$

A *forest* is a directed graph where:

- there is no  $v$  such that  $v \rightarrow^+ v$  (*acyclicity*)
- if  $v \rightarrow v' \leftarrow v''$  then  $v = v''$  (*at most one parent*).

A *root vertex* of a forest is a vertex  $v$  such that there is no  $w \rightarrow v$ . A *tree* is a forest with a unique root vertex.

## 2.2. Definitions

A *navigation history*  $H = (D, A, \rightarrow, \leq, \sim)$  consists of:

- a set  $D$  (the *documents*),
- a subset  $A \subseteq D$  (the *active documents*),
- a forest  $(D, \rightarrow)$  (the *document hierarchy*),
- a total order  $(D, \leq)$  (the *chronological order*), and
- an equivalence relation  $(D, \sim)$  (the *same-session equivalence*).

such that:

- for every  $d$  there is a unique  $d' \in A$  such that  $d \sim d'$ ,
- for every  $d \rightarrow e \sim e'$  we have  $d \rightarrow e'$ , and
- for every  $d \rightarrow e$ , we have  $d \leq e$ .

Define:

- $d_0$  is the unique active root document,
- $d \twoheadrightarrow e$  when  $d \rightarrow e$  and  $e \in A$ ,
- $FA = \{d \mid d_0 \twoheadrightarrow^* d\}$  (the *fully active documents*),
- $d \lesssim e$  whenever  $d \sim e$  and  $d < e$ ,
- the *session future* of  $d$  is  $\{e \mid d \lesssim e\}$ ,
- the *session past* of  $d$  is  $\{e \mid d \gtrsim e\}$ ,
- the *joint session future* is  $\{e \mid \exists d \in FA . d \lesssim e\}$ ,
- the *joint session past* is  $\{e \mid \exists d \in FA . d \gtrsim e\}$ ,

Define *deleting  $d$  from  $H$* , when  $d \notin FA$ , to be  $H'$  where:

- $D' = D \setminus \{e \mid d \rightarrow^* e\}$ ,
- $e \in A'$  whenever  $e \in A$ ,
- $e \leq' f$  whenever  $e \leq f$ ,
- $e \rightarrow' f$  whenever  $e \rightarrow f$ , and
- $e \sim' f$  whenever  $e \sim f$ .

Define *replacing  $d$  by  $d'$  in  $H$* , where  $d \in A$  and  $d' \notin D$ , to be  $H'$  where:

- $D' = D \cup \{d'\}$ ,
- $e \in A'$  whenever  $e \in A$  and  $e \neq d$ , or  $e = d'$ ,
- $e \leq' f$  whenever  $e \leq f$ , or  $f = d'$ ,
- $e \rightarrow' f$  whenever  $e \rightarrow f$ , or  $e \rightarrow d$  and  $f = d'$ , and
- $e \sim' f$  whenever  $e \sim f$ , or  $e \sim d$  and  $f = d'$ , or  $d \sim f$  and  $e = d'$ .

Define *navigating from  $d$  to  $d'$  in  $H$*  to be the result of:

- deleting the session future of  $d$ , and
- replacing  $d$  by  $d'$ .

Define *traversing the history to  $d$  in  $H$*  to be  $H'$  where:

- $D'$  is  $D$ ,
- $e \in A'$  whenever  $d \not\sim e \in A$ , or  $d = e$ ,
- $e \leq' f$  whenever  $e \leq f$ ,
- $e \rightarrow' f$  whenever  $e \rightarrow f$ , and
- $e \sim' f$  whenever  $e \sim f$ .

Define  *$H$  traverses the history by  $+\delta$  to  $H'$*  when:

- the joint session future of  $H$  is  $d_1 > \dots > d_\delta > \dots$ ,
- $H$  traverses the history to  $d_\delta$  in  $H'$

Define  *$H$  traverses the history by  $-\delta$  to  $H'$*  when:

- the joint session past of  $H$  is  $d_1 < \dots < d_\delta < \dots$ ,
- $H$  traverses the history to  $d_\delta$  in  $H'$

Define  *$H$  traverses the history by 0 to  $H'$*  when  $H = H'$ .

[This defn is meant to align with the spec.]


## 2.3. Properties

[State some goals, e.g.  $\text{go}(\delta);\text{go}(\delta')$  is the same as  $\text{go}(\delta + \delta')$ ,  $\text{navigate};\text{go}(-1)$  has the same fully active documents as doing nothing, session history can be implemented effeciently in memory...]


[I suspect none of these are true of the current spec, can we find a model in which they are true?]

**Goal 1:** If  $H$  traverses the history by  $\delta$  to  $H'$  and  $H'$  traverses the history by  $\delta'$  to  $H''$  then  $H$  traverses the history by  $\delta + \delta'$  to  $H''$ .


**Counterexample 1:** Let  $H$  be:




which traverses the history by 1 to:



which traverses the history by 1 to:



but  $H$  traverses the history 2 to:



This counterexample is caused by the definition of ‘traverses the history by  $\delta$ ’ which only traverses one document’s session history. Instead, we should traverse the history of all  $\delta$  documents.

**Patch 1:** Define  $H$  traverses the history by  $+\delta$  to  $H'$  when:


- the joint session future of  $H$  is  $d_1 < \dots < d_\delta < \dots$ ,
- there is some  $H = H_0, \dots, H_\delta = H'$ , such that
- $H_{i-1}$  traverses the history to  $d_i$  in  $H_i$  for each  $1 \leq i \leq \delta$ .

Define  $H$  traverses the history by  $-\delta$  to  $H'$  when:


- the joint session past of  $H$  is  $d_1 > \dots > d_\delta > \dots$ ,
- there is some  $H = H_0, \dots, H_\delta = H'$ , such that
- $H_{i-1}$  traverses the history to  $d_i$  in  $H_i$  for each  $1 \leq i \leq \delta$ .

Unfortunately, Goal 1 is not satisfied, even with this patch.


**Counterexample 2:** Let  $H$  be:




which moves forwards by 1 to:



which in turn moves forwards by 1 to:



but  $H$  goes forward by 2 to:




The problem this time is that the definition of ‘joint session history’ only includes the fully active documents, not all active documents.


**Patch 2:** Define:

- the *joint session future* is  $\{e \mid \exists d \in A . d \lesssim e\}$ , and
- the *joint session past* is  $\{e \mid \exists d \in A . d \gtrsim e\}$ .


**Counterexample 3:** Let  $H$  be:



which traverses the history by  $-1$  to:



which traverses the history by 1 to:



which is not the same as  $H$ .

[ASAJ: Not sure about this...]

**Patch 3:** Define  $H$  *traverses the history from  $d'$*  when there is some  $d$  such that:

- $d \lesssim d'$ ,
- for any  $e \lesssim d'$  we have  $e \leq d$ , and
- $H$  traverses the history to  $d$ .

Define  $H$  *traverses the history by  $-\delta$  to  $H'$*  when:

- the joint session past and active documents of  $H$  is  $d_1 > \dots > d_\delta > \dots$ ,
- there is some  $H = H_0, \dots, H_\delta = H'$ , such that
- $H_{i-1}$  traverses the history from  $d_i$  in  $H_i$  for each  $1 \leq i \leq \delta$ .

**Goal 2:** If  $d$  in  $H$  navigates to  $d'$  in  $H'$ , and  $H'$  traverses the history by  $-1$  to  $H''$ , then  $FA = FA''$ .

### 3. Experiments

[In this section various different navigation and traversal scenarios are tested in popular web browsers to see where they differ in behaviour from both the spec and each other.]

**Experiment 1:** In this experiment Goal 1 is tested.

- $H$  *traverses the history by  $-4$  to  $H'$*
- $H'$  *traverses the history by  $+4$  to  $H''$*

By Goal 1, these traversals should be the same thing as  $H$  *traversing by 0* which is a no-op; therefore,  $H = H''$ .

Firefox:




Figure 1: Initial State

Navigate document 1 to Page 2:






Figure 2: Navigate document 1 to Page 2.

Navigate document 3 to Page 3:




Figure 3: Navigate document 3 to Page 3.

Navigate document 2 to Page 2:




Figure 4: Navigate document 2 to Page 2.

Navigate document 5 to Page 3:





Figure 5: Navigate document 5 to Page 3.

$H$  traverses the history by  $-4$  to  $H'$ :

Figure 6: Traversal by  $-4$ .

This state is obviously wrong, as document 4 should have traversed to document 1. This is similar to counterexample 1.

$H'$  traverses the history by 4 to  $H''$ :




Figure 7: Traversal by 4.

While this result does satisfy Goal 1, there are still some issues:

- Figure 6 yields an incorrect traversal. [CGB: I believe this actually does break Goal 1 as navigating by  $-1$  four times should yield the correct state.]
- It is impossible to get back to Page 1 on both Frames. [CGB: Looks to be a bug in FF, when holding down the back button, the list of pages to traverse to shows up. Clicking on the oldest item on the list does nothing and does not activate that item.]

Safari:




Figure 8: Initial State

Navigate document 1 to Page 2:




Figure 9: Navigate document 1 to Page 2.

Navigate document 3 to Page 3:




Figure 10: Navigate document 3 to Page 3.

Navigate document 2 to Page 2:




Figure 11: Navigate document 2 to Page 2.

Navigate document 5 to Page 3:




Figure 12: Navigate document 5 to Page 3.

$H$  traverses the history by  $-4$  to  $H'$ :




Figure 13: Traversal by  $-4$ .

$H'$  traverses the history by  $4$  to  $H''$ :




Figure 14: Traversal by 4.

These results in Safari satisfy Goal 1.  
Chrome:




Figure 15: Initial State

Navigate document 1 to Page 2:




Figure 16: Navigate document 1 to Page 2.

Navigate document 3 to Page 3:




Figure 17: Navigate document 3 to Page 3.

Navigate document 2 to Page 2:




Figure 18: Navigate document 2 to Page 2.

Navigate document 5 to Page 3:





Figure 19: Navigate document 5 to Page 3.

$H$  traverses the history by  $-4$  to  $H'$ :

Figure 20: Traversal by  $-4$ .

$H'$  traverses the history by 4 to  $H''$ :




Figure 21: Traversal by 4.

These results in Chrome satisfy Goal 1.

**Experiment 2:** In this experiment *pushState* and *replaceState* traversals are tested against Goal 1.

Firefox:




Figure 22: Initial State

Advance document 1 to 6:





Figure 23: Advance document 1 to 6

Advance document 3 to 7:







Figure 24: Advance document 3 to 7

Advance document 2 to 6:

Figure 25: Advance *document2* to 6

Advance *document2* to 7:








Figure 26: Advance document 2 to 7

Traverse  $H$  by  $-4$ :

Figure 27: Traverse  $H$  by  $-4$ 

Traverse  $H$  by 4:

Figure 28: Traverse  $H$  by 4

The last traversal does not satisfy Goal 1.

## 4. Specification

[Suggested edits to the spec: 1. traverse to each document, not just the selected one, 2. keep all documents in the session history, not just the fully active ones, 3. change the session history order.]

## 5. Conclusion

[We did stuff.]

## References

- [1] WHATWG. HTML living standard. <https://html.spec.whatwg.org/>, 2016.