

[NAME](#) | [SYNOPSIS](#) | [DESCRIPTION](#) | [RETURN VALUE](#) | [ERRORS](#) | [VERSIONS](#) |
[CONFORMING TO](#) | [EXAMPLE](#) | [SEE ALSO](#) | [COLOPHON](#)

Search online pages**PIPE(2)****Linux Programmer's Manual****PIPE(2)****NAME** [top](#)

pipe, pipe2 - create pipe

SYNOPSIS [top](#)

```
#include <unistd.h>

int pipe(int pipefd[2]);

#define _GNU_SOURCE          /* See feature_test_macros(7) */
#include <fcntl.h>          /* Obtain O_* constant definitions */
#include <unistd.h>

int pipe2(int pipefd[2], int flags);
```

DESCRIPTION [top](#)

pipe() creates a pipe, a unidirectional data channel that can be used for interprocess communication. The array *pipefd* is used to return two file descriptors referring to the ends of the pipe. *pipefd[0]* refers to the read end of the pipe. *pipefd[1]* refers to the write end of the pipe. Data written to the write end of the pipe is buffered by the kernel until it is read from the read end of the pipe. For further details, see [pipe\(7\)](#).

If *flags* is 0, then **pipe2()** is the same as **pipe()**. The following values can be bitwise ORed in *flags* to obtain different behavior:

O_CLOEXEC

Set the close-on-exec (**FD_CLOEXEC**) flag on the two new file descriptors. See the description of the same flag in [open\(2\)](#) for reasons why this may be useful.

O_DIRECT (since Linux 3.4)

Create a pipe that performs I/O in "packet" mode. Each [write\(2\)](#) to the pipe is dealt with as a separate packet, and [read\(2\)](#)s from the pipe will read one packet at a time. Note the following points:

- * Writes of greater than **PIPE_BUF** bytes (see [pipe\(7\)](#)) will be split into multiple packets. The constant **PIPE_BUF** is defined in *<limits.h>*.

- * If a `read(2)` specifies a buffer size that is smaller than the next packet, then the requested number of bytes are read, and the excess bytes in the packet are discarded. Specifying a buffer size of **PIPE_BUF** will be sufficient to read the largest possible packets (see the previous point).
- * Zero-length packets are not supported. (A `read(2)` that specifies a buffer size of zero is a no-op, and returns 0.)

Older kernels that do not support this flag will indicate this via an **EINVAL** error.

O_NONBLOCK

Set the **O_NONBLOCK** file status flag on the two new open file descriptions. Using this flag saves extra calls to `fcntl(2)` to achieve the same result.

RETURN VALUE [top](#)

On success, zero is returned. On error, -1 is returned, and `errno` is set appropriately.

On Linux (and other systems), `pipe()` does not modify `pipefd` on failure. A requirement standardizing this behavior was added in POSIX.1-2016. The Linux-specific `pipe2()` system call likewise does not modify `pipefd` on failure.

ERRORS [top](#)

EFAULT `pipefd` is not valid.

EINVAL (`pipe2()`) Invalid value in `flags`.

EMFILE The per-process limit on the number of open file descriptors has been reached.

ENFILE The system-wide limit on the total number of open files has been reached.

ENFILE The user hard limit on memory that can be allocated for pipes has been reached and the caller is not privileged; see `pipe(7)`.

VERSIONS [top](#)

`pipe2()` was added to Linux in version 2.6.27; glibc support is available starting with version 2.9.

CONFORMING TO [top](#)

pipe(): POSIX.1-2001, POSIX.1-2008.

pipe2() is Linux-specific.

EXAMPLE [top](#)

The following program creates a pipe, and then [fork\(2\)](#)s to create a child process; the child inherits a duplicate set of file descriptors that refer to the same pipe. After the [fork\(2\)](#), each process closes the file descriptors that it doesn't need for the pipe (see [pipe\(7\)](#)). The parent then writes the string contained in the program's command-line argument to the pipe, and the child reads this string a byte at a time from the pipe and echoes it on standard output.

Program source

```
#include <sys/types.h>
#include <sys/wait.h>
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#include <string.h>

int
main(int argc, char *argv[])
{
    int pipefd[2];
    pid_t cpid;
    char buf;

    if (argc != 2) {
        fprintf(stderr, "Usage: %s <string>\n", argv[0]);
        exit(EXIT_FAILURE);
    }

    if (pipe(pipefd) == -1) {
        perror("pipe");
        exit(EXIT_FAILURE);
    }

    cpid = fork();
    if (cpid == -1) {
        perror("fork");
        exit(EXIT_FAILURE);
    }

    if (cpid == 0) { /* Child reads from pipe */
        close(pipefd[1]); /* Close unused write end */

        while (read(pipefd[0], &buf, 1) > 0)
            write(STDOUT_FILENO, &buf, 1);

        write(STDOUT_FILENO, "\n", 1);
        close(pipefd[0]);
    }
```

```

        _exit(EXIT_SUCCESS);

    } else {
        /* Parent writes argv[1] to pipe */
        close(pipefd[0]);           /* Close unused read end */
        write(pipefd[1], argv[1], strlen(argv[1]));
        close(pipefd[1]);           /* Reader will see EOF */
        wait(NULL);                 /* Wait for child */
        exit(EXIT_SUCCESS);
    }
}

```

SEE ALSO [top](#)

[fork\(2\)](#), [read\(2\)](#), [socketpair\(2\)](#), [splice\(2\)](#), [tee\(2\)](#), [vmsplice\(2\)](#),
[write\(2\)](#), [popen\(3\)](#), [pipe\(7\)](#)

COLOPHON [top](#)

This page is part of release 4.13 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2017-07-13

PIPE(2)

Pages that refer to this page: [eventfd\(2\)](#), [fork\(2\)](#), [getrlimit\(2\)](#), [socketpair\(2\)](#), [statfs\(2\)](#), [syscalls\(2\)](#), [pmda\(3\)](#), [pmdaconnect\(3\)](#), [popen\(3\)](#), [capabilities\(7\)](#), [fifo\(7\)](#), [inode\(7\)](#), [man-pages\(7\)](#), [pipe\(7\)](#), [signal-safety\(7\)](#)

Copyright and license for this manual page

HTML rendering created 2017-09-15 by [Michael Kerrisk](#), author of *The Linux Programming Interface*, maintainer of the [Linux man-pages project](#).

For details of in-depth **Linux/UNIX system programming training courses** that I teach, look [here](#).

Hosting by [jambit GmbH](#).

