


Final Exam

Total marks: 50

Duration: 95 minutes

CSE331: Automata and Computability

There are a total of six problems. You have to solve **any five** of them.**Problem 1 (CO1): DFA Minimization (10 points)**Minimize the following DFA. You must **show** all the steps of the minimization algorithm.**Problem 2 (CO3): Nonregular Languages (10 points)**Let $\Sigma = \{0, 1\}$. Consider the following language.

$$L = \{w \in \Sigma^* : w = 0^n 1^m 0^k \text{ where } n = m \text{ or } m \neq k\}$$

- Use the pumping lemma to **demonstrate** that L is not regular. (8 points)
- Find** a string $w \in L$ such that there exist $x, y, z \in \Sigma^*$ with $y \neq \varepsilon$ such that $w = xyz$ and $xy^iz \in L$ for all $i \geq 0$. Does this contradict the pumping lemma? (2 points)

Problem 3 (CO2): Derivations, Parse Trees and Ambiguity (10 points)

Take a look at the grammar below and solve the following problems.

$$A \rightarrow A1 \mid 0A1 \mid 01$$

- Give** a leftmost derivation for the string 001111. (3 points)
- Sketch** the parse tree corresponding to the derivation you gave in (a). (2 points)
- Demonstrate** that there are two more parse trees (apart from the one you already found in (b)) for the same string. (4 points)
- Find** a string w of length six such that w has exactly one parse tree in the grammar above. (1 point)

Final Exam
Total marks: 50
Duration: 95 minutes

CSE331: Automata and Computability

Problem 4 (CO2): Chomsky Normal Form (10 points)

Convert the following grammar into Chomsky Normal Form. You must show work. Here **a**, **b**, **c** are terminals and the rest are variables.

$$\begin{aligned} S &\rightarrow \mathbf{b}X\mathbf{a}Y|ZX\mathbf{b} \\ X &\rightarrow \mathbf{a}Y \mid \mathbf{b}Y \mid Y \\ Y &\rightarrow X \mid \mathbf{c} \mid \varepsilon \\ Z &\rightarrow Z\mathbf{a}X \end{aligned}$$

Problem 5 (CO4): The CYK Algorithm (10 points)

Apply the CYK algorithm to determine whether the string **abcaa** can be derived in the following grammar. You must show the entire CYK table. Here **a**, **b**, **c** are terminals and the rest are variables.

$$\begin{aligned} S &\rightarrow CA \\ A &\rightarrow AA \mid AD \mid \mathbf{a} \\ B &\rightarrow AB \mid BC \mid \mathbf{b} \\ C &\rightarrow CA \mid BC \mid \mathbf{c} \\ D &\rightarrow \mathbf{a} \end{aligned}$$

Problem 6 (CO2): Models Recognizing CFLs (10 points)

Let $\Sigma = \{0, 1\}$. Consider the following language.

$$L = \{w \in \Sigma^* : w = 0^n 1^n \text{ where } n \text{ is odd}\}$$

- (a) **Construct** a context-free grammar that generates L . (5 points)
- (b) **Design** a pushdown automaton that recognizes L . (5 points)

