MECH 503 Homework 2

Jincong Li 60539939

Feb 16th

Q1

$$\mathbf{u} = \begin{bmatrix} x_1^3 + x_1 x_2^2 + x_3^2 \\ -x_2^3 + x_3^2 \\ -x_1^3 + 2x_1 x_2 x_3 \end{bmatrix}$$

$$\nabla \mathbf{u} = \begin{bmatrix} 3x_1^2 + x_2^2 & 2x_1 x_2 & 2x_3 \\ 0 & -3x_2^2 & 2x_3 \\ -3x_1^2 + 2x_2 x_3 & 2x_1 x_3 & 2x_1 x_2 \end{bmatrix}$$

$$\nabla \mathbf{u}^T = \begin{bmatrix} 3x_1^2 + x_2^2 & 0 & -3x_1^2 + 2x_2 x_3 \\ 2x_1 x_2 & -3x_2^2 & 2x_1 x_3 \\ 2x_3 & 2x_3 & 2x_1 x_2 \end{bmatrix}$$

Thus, the infinitisimal strain tensor is determined to be:

$$\varepsilon = \begin{bmatrix} 3.0x_1^2 + 1.0x_2^2 & 1.0x_1x_2 & -1.5x_1^2 + 1.0x_2x_3 + 1.0x_3 \\ 1.0x_1x_2 & -3.0x_2^2 & 1.0x_1x_3 + 1.0x_3 \\ -1.5x_1^2 + 1.0x_2x_3 + 1.0x_3 & 1.0x_1x_3 + 1.0x_3 & 2.0x_1x_2 \end{bmatrix}$$

at point $\mathbf{x} = [1, 0, 1]^T$,

$$\varepsilon = \begin{bmatrix} 3.0 & 0 & -0.5 \\ 0 & 0 & 2.0 \\ -0.5 & 2.0 & 0 \end{bmatrix}$$

The vorticity tensor is

$$\omega = \begin{bmatrix} 0 & 1.0x_1x_2 & 1.5x_1^2 - 1.0x_2x_3 + 1.0x_3 \\ -1.0x_1x_2 & 0 & -1.0x_1x_3 + 1.0x_3 \\ -1.5x_1^2 + 1.0x_2x_3 - 1.0x_3 & 1.0x_1x_3 - 1.0x_3 & 0 \end{bmatrix}$$

at point $\mathbf{x} = [1, 0, 1]^T$,

$$\omega = \begin{bmatrix} 0 & 0 & 2.5 \\ 0 & 0 & 0 \\ -2.5 & 0 & 0 \end{bmatrix}$$

Deformation gradient is

$$\mathbf{F} = \begin{bmatrix} 3x_1^2 + x_2^2 + 1 & 2x_1x_2 & 2x_3 \\ 0 & 1 - 3x_2^2 & 2x_3 \\ -3x_1^2 + 2x_2x_3 & 2x_1x_3 & 2x_1x_2 + 1 \end{bmatrix}$$

The stretch ratio for the point $\mathbf{x} = [1, 0, 1]^T$ is

$$\lambda = \sqrt{22}$$

Thus, the relative length change is

$$\lambda_{rel} = -1 + \sqrt{22} \cong 3.69$$

The relative volum change at the given point is

$$\frac{\delta V}{\delta V_0} = \text{Tr}(\varepsilon)$$
$$= 3$$

The deviatoric infinitisimal strain tensor is determined to be:

$$\mathbf{e} = \varepsilon - \frac{1}{3} \text{Tr}(\varepsilon)$$

$$= \begin{bmatrix} 2.0 & 0 & -0.5 \\ 0 & -1.0 & 2.0 \\ -0.5 & 2.0 & -1.0 \end{bmatrix}$$

Q2

$$\mathbf{E_L} = \begin{bmatrix} 2 & 0.1 & 0 \\ 0.1 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$
$$\mathbf{n} = \begin{bmatrix} \frac{1}{\sqrt{5}}, \frac{2}{\sqrt{5}}, 0 \end{bmatrix}^T$$
$$\varepsilon_L = \mathbf{n}^T \mathbf{E_L} \mathbf{n}$$
$$= 1.28$$

Thus, the length of the fiber in the defromed configuration is

$$l = 1.28 * \sqrt{5}$$
$$\cong 2.86217$$

Q3

For each deformation gradient, their Jacobian values are computed to be:0.997 $1.003 \ 1.000 \ 1.003 \ 1.003$. Also note that the angle of rotation given in the question is 0.1 degree which is too small to show in plots, so I changed it into $0.1 \ \text{rads} = 5.73$ degree to have better view. The deformed configuration of the line and square elements under different deformation gradient is shown below in Figure 1. It seems like there is a typo in the question statement.




Figure 1: Deformation of Line and Square Element by Each F

But the for the same conclusion. I chose to use ${\bf F_5}$ and ${\bf F_2F_3}$ to show the ${\bf F_5}$

can be decomposed into a rigid body rotation $\mathbf{F_3}$ and a stretch of element $\mathbf{F_2}$. The result is shown in Figure 2.




Figure 2: Deformation of the Square Element by ${\bf F_5}$ and ${\bf F_2F_3}$

Q4

$$dl_{f1,F4} = 0.002$$

$$dl_{f2,F4} = 0.001$$

$$d\theta_{f1f2,F4} = -0.00499 rads = 0.2807 degree$$