Package 'soundmeteR'

May 19, 2023

Type Package

Title R package for sound meter alike analysis
Version 0.1.0
Author Cássio Rachid Simões, Shaka Nóbrega Marinho Furtado, Ingrid Maria Denóbile Torres, Marcelo Felgueiras Napoli and Carlos Barros de Araújo
Maintainer Cássio Rachid Simões <cassiorachid@gmail.com></cassiorachid@gmail.com>
Description An R package designed for sound analysis through spectral analysis in octaves and one-thirds octaves, making possible calibration to obtain sound pressure level (SPL) and Sound Intensity Level (SIL).
<pre>URL https://github.com/cassiorachid/soundmeteR</pre>
BugReports https://github.com/cassiorachid/soundmeteR/issues
License GPL (>=3)
Depends tuneR, seewave, dplyr, progress
Encoding UTF-8
LazyData TRUE
RoxygenNote 7.2.3
R topics documented:
dBtoLinear
freq.bands
LineartodB
pwrspec
rms.dB
soundmeter
sumdB
tham
timbre
timbreCal
Tweighting
Index 16

2 dBtoLinear

dBto	Ιi	naa	r
OBLO	1 1	nea	1

Convert deciBels scales to linear

Description

Function to convert dB scales. The conversion can be made either from dB to μ Pa (dBtoLinear) or from μ Pa to dB (LineartodB).

Usage

```
dBtoLinear(x, factor="IL", ref=1)
```

Arguments

x	Numerical. A numeric vector or a numeric matrix with dB values.
factor	Character. Specify in what factor the function should use to convert your data.

SPL (Sound Pressure Level) for amplitude like data (factor 20) or IL (Intensity

Level) for power like (fator 10). (By default IL)

ref Numerical. Reference value for conversion. For Sound in water the ref is 1 µPa

and on air 20 µPa. (By default 1)

Details

For details about the factor choice, we recommend the reading of this web page.

Value

The same object of the input with the converted values.

See Also

```
rms.dB, LineartodB, convSPL
```

```
dBtoLinear(c(80,60,65,62))
LineartodB(dBtoLinear(c(80,60,65,62)))
```

freq.bands 3

Description

Function to compute intervals from patterns defined by the user. This function was adapted from octaves functions from seewave package.

Usage

```
freq.bands(x, interval = 2, below = 3, above = 3)
```

Arguments

X	Numerical. The frequency values to start the bands' calculation.
interval	Numeric. The interval pattern to be applied. See details for more.
below	Numerical. Number of intervals below x.
above	Numerical. Number of intervals above x.

Details

The interval specified is applied by x/interval (for bellow) of x*interval (for upper). Some examples of intervals that can be applied are:

- Octaves = 2
- Third of octaves = $2^{(1/3)}$
- Perfect fifth (music theory) = 3/2
- Major third (music theory) = 5/4
- Minor third (music theory) = 6/5
- This link shows other values that can be used.

Value

A numeric vector with the frequency limits of each interval.

See Also

octaves

4 LineartodB

Examples

```
freq.bands(1000, interval=2, below = 1, above = 1) #octaves
freq.bands(1000, interval=2^(1/3), below = 3, above = 3) #Third of octaves

#https://academics.hamilton.edu/music/spellman/class_notes/music_theory.htm
freq.bands(440, interval=3/2, below = 0, above = 1) #Perfect fifth (music theory) of A 440
freq.bands(440, interval=5/4, below = 0, above = 1) #Major third (music theory) of A 440
freq.bands(440, interval=6/5, below = 0, above = 1) #Minor third (music theory) of A 440
```

LineartodB

Convert linear scales to deciBels

Description

Function to convert dB scales. The conversion can be made either from dB to μ Pa (dBtoLinear) or from μ Pa to dB (LineartodB).

Usage

```
LineartodB(x, factor="IL", ref=1)
```

Arguments

X	Numerical. A numeric vector or a numeric matrix with dB values linear values (μPa) .
factor	Character. Specify in what factor the function should use to convert your data. SPL (Sound Pressure Level) for amplitude like data (factor 20) or IL (Intensity Level) for power like (fator 10). (By default IL)
ref	Numerical. Reference value for conversion. For Sound in water the ref is 1 µPa

Details

For details about the factor choice, we recommend the reading of this web page.

and on air 20 µPa. (By default 1)

Value

The same object of the input with the converted values.

See Also

```
rms.dB, dBtoLinear, convSPL
```

```
dBtoLinear(c(80,60,65,62))
LineartodB(dBtoLinear(c(80,60,65,62)))
```

pwrspec 5

pwrspec

Power Spectrum of a sound file

Description

This functions computes a power spectrum from a sound file.

Usage

```
pwrspec(
   file,
   channel = "left",
   from = 0,
   to = Inf,
   bandpass = c(0, Inf),
   res.scale = "microPa",
   ref = 1
)
```

Arguments

file	A wave file path in your computer or a class Wave object already loaded into R environment.
channel	Character. Choose "left" or "right" channel. Argument passe to mono function from tuneR to extract the desired channel.
from	Numeric. The start time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.
to	Numeric. The end time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.
bandpass	A vector with length two with lower and upper limits of the band pass interval in Hz.
res.scale	Character. Specify the kind of scale the power spectrum amplitude should be adjusted. microPa for linear values in μPa , and dB fo decibells values in dB-SPL. (By default "microPa")
ref	Numerical. Reference value for dB conversion. For Sound in water the ref is 1 μ Pa and on air 20 μ Pa. (By default 1)

Value

This function returns a data.frame with Frequency (Hz) and Intensity (microPa) of the file.

References

Power spectrum adapted from: Carcagno, S. 2013. Basic Sound Processing with R [Blog post]. Retrieved from http://samcarcagno.altervista.org/blog/basic-sound-processing-r/

Miyara, F. 2017. Software-Based Acoustical Measurements. Springer. 429 pp. DOI: 10.1007/978-3-319-55871-4

6 rms.dB

Examples

```
data(tham)
pwrspec(tham)

#with from, to and bandpass
pwrspec(tham, from=3.8, to=7.1, bandpass=c(900,2000))

#from and to relative to duration (negatives values from the end of the soundfiles)
pwrspec(tham, from=-3.49, to=-0.9, bandpass=c(900,2000))
```

rms.dB

Root Mean Square with dB values

Description

Function to compute the root mean square (RMS) of values in decibels (dB).

Usage

```
rms.dB(x, level="SPL", ref=1, ...)
```

Arguments

X	Numerical. A numeric vector or a numeric matrix with dB values.
level	Character. Specify in what scale your data is. SPL for Sound Pressute Level or IL for Intensity Level. (By default SPL)
na.rm	Logical. Argument passed to mean. Should NA be removed? (By default FALSE)
ref	Numerical. Reference value for conversion. For Sound in water the ref is 1microPa and on air 20 microPa. (By default 1)

Details

This function converts your dB data to linear values (through dBtoLinear function), compute the Root Mean Square (rms), and converts the result back to dB (through Linear todB function).

This function was adapted from meandB and rms functions from seewave package. See their help for more details.

Value

A numeric value that represents the root mean square of x.

See Also

```
meandB, rms
```

song.level 7

Examples

```
rms.dB(c(80,60,65,62))
```

song.level

RMS from a sample of a sound file

Description

RMS from a sample of a sound file

Usage

```
song.level(
  files = "wd",
  channel = "left",
  from = 0,
  to = Inf,
  freq.interval = c(0, Inf),
  fdom.int = c(0, Inf),
  wl = 512,
  ovlp = 50,
  CalibPosition = NULL,
  CalibValue = NULL,
  freq.weight = "none",
  ref = 20
)
```

Arguments

files	The audiofile to be analyzed. Can be "wd" to get all ".wav" files on the work directory, a file name (or a character containing a list of filenames) that exist in the work directory (only ".wav" files accepted), or an Wave object (or a list containing more than one Wave object). (By default: "wd")
channel	Argument passed to mono function from tuneR to extract the desired channel.
from	Numeric. The start time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.
to	Numeric. The end time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.
freq.interval	Frequency interval to compute the RMS. Can be a vector with length two with lower and upper interval of frequencies (in Hz), or a pattern to calculate a interval (as octaves). For the last, see freq.bands function for details.
fdom.int	Vector with length two. Vector with length two with lower and upper interval of frequencies (in Hz) to find the dominant frequency. This frequency will be used as the center the interval only if a pettern is specified.

8 soundmeter

wl Explain.

ovlp Explain.

CalibPosition Missing

CalibValue Canbe a value to apply of the ref value from a calib signal (specified by Calib-Position).

freq.weight Character. Argument passed to dBweight to indicate the weighting curve to use on the anlysis. 'A', 'B', 'C', 'D', 'ITU', and 'none' are supported. See dBweight for details. (By default: "none")

Numerical. The reference value for dB conversion. For sound in water, the

common is 1 microPa, and for sound on air 20 microPa. (By default 20)

Examples

ref

```
song.level(tham, freq.interval=c(22, 20000))
song.level(tham, freq.interval=c(22, 20000), CalibValue = 130.24)
song.level(tham, freq.interval=c(22, 20000), CalibValue = 130.24, freq.weight="A")
song.level(tham, freq.interval=c(22, 20000), CalibValue = 130.24, freq.weight="B")
song.level(tham, freq.interval=c(22, 20000), CalibValue = 130.24, freq.weight="C")
song.level(tham, from = 3.883035, to=7.044417, freq.interval=c(22.09429, 22627.38), CalibValue = 130.24, freq.weight="A"
#Perfect fifth (music theory)
song.level(tham, fdom.int = c(800, 2000), from = 3.8, to=7, freq.interval=3/2, CalibValue = 130.24, freq.weight="A"
#Perfect fifth (music theory)
song.level(tham, fdom.int = c(800, 2000), from = 3.8, to=7, freq.interval=3/2, CalibValue = 130.24, freq.weight="A"
#Perfect fifth (music theory)
song.level(tham, fdom.int = c(800, 2000), from = 3.8, to=7, freq.interval=3/2, CalibValue = 130.24, freq.weight="A"
```

soundmeter

Function that makes sound meter alike measurements

Description

Function that makes sound meter alike measurements

Usage

```
soundmeter(
  files = "wd",
  from = 0,
  to = Inf,
  CalibPosition = NULL,
  CalibValue = NULL,
```

soundmeter 9

```
ref = 20,
fw = "none",
bands = "octaves",
tw = "fast",
progressbar = T,
channel = "left",
saveresults = F,
outname = NULL
)
```

Arguments

CalibPosition anda de mãos dadas com calib value. Pode ser negativo, positivo ou data frame

com essas combinações

CalibValue Anda de mãos dadas com calib position. Quando tem o position, ele é consider-

ado o valor de referência, quando não tem o position, ele é considerado o valor

de calibração.

fw Character. Argument passed to dBweight to indicate the frequency weighting

curve to use on the anlysis. 'A', 'B', 'C', 'D', 'ITU', and 'none' are supported.

See dBweight for details. (By default: "none")

tw Time weighting

progressbar Logical. Activate or deactivate a progress bar with elapsed time and the last

concluded file number. (By default: TRUE)

channel Only "left" or "right" acepted. By default "left"

saveresults Logical. Set TRUE if you want to save a txt file with the results of the function

execution. (By default: FALSE)

outname Character. If saveresults is TRUE, you can specify a name to appear on the txt

file name after the default name. (By default: NULL)

Details

If your reference signal is in a separate file, we recommend you to get the CalibValue with timbre function. It's examples provide more details.

```
data("tham")
soundmeter(tham, CalibValue = 130.24, tw="slow") #slow time window with calib value
soundmeter(tham, CalibValue = 130.24, tw="fast") #fast
soundmeter(tham, CalibValue = 130.24, tw="fast", fw="A") #fast with frequency weight
soundmeter(tham, CalibValue = NULL, tw="fast", ref=1) #fast time window in dBFS
```

10 sumdB

sumdB

Sum with dB values

Description

Sum with dB values

Usage

```
sumdB(x, level = "IL", na.rm = FALSE, ...)
```

Arguments

X	Numerical. A numeric vector or matrix with dB values.
level	Character. Specify in what scale your data is. SPL for Sound Pressute Level or IL for Intensity Level. (By default SPL)
na.rm	Logical. Argument passed to sum. Should NA be removed? (By default FALSE)

Details

This function computes the sum of dB values.

This function converts your dB data to linear values (through dBtoLinear function), compute the sum, and converts the result back to dB (through LineartodB function).

Value

A numeric value that represents the sum of x.

See Also

moredB

```
sumdB(c(80,60,65,62))
sumdB(c(30,30), level="IL")
sumdB(c(30,30), level="SPL")
```

tham 11

tham

Thamnophilus stictocephalus song in a landscape

Description

Thamnophilus stictocephalus song in a landscape

Usage

data(tham)

Format

An object of class "Wave"; see readWave.

Details

A landscape recording presenting *Thamnophilus stictocephalus* song between 3.883035 and 7.044417 seconds. The "calib.value" for this record is 130.24.

Source

Recording by Ingrid Maria Denóbile Torres

timbre

Level per octaves or one-thirds octaves

Description

Escrever

Usage

Arguments

files	The audiofile to be analyzed. Can be "wd" to get all ".wav" files on the work directory, a file name (or a character containing a list of filenames) that exist in the work directory (only ".wav" files accepted), or an Wave object (or a list containing more than one Wave object). (By default: "wd")
channel	Character. Choose "left" or "right" channel. Argument passe to mono function from tuneR to extract the desired channel.
from	Numeric. The start time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.

12 timbre

to	Numeric. The end time in seconds of the sample you want to analyze. Could also be relative to the end of the file (in negative values), see examples.
weighting	Character. Argument passed to dBweight to indicate the weighting curve to use on the anlysis. 'A', 'B', 'C', 'D', 'ITU', and 'none' are supported. See dBweight for details. (By default: "none")
bands	Character. Choose the type of frequency band of the output. "octaves" to octaves bands intervals or "thirds" to one-third octaves bands intervals. (by deafault: "thirds")
ref	Numerical. The reference value for dB conversion. For sound in water, the common is 1 microPa, and for sound on air 20 microPa. (By default 20)
saveresults	Logical. Set TRUE if you want to save a txt file with the results of the function execution. (By default: FALSE)
outname	Character. If saveresults is TRUE, you can specify a name to appear on the txt file name after the default name. (By default: NULL)
Leq.calib	Numerical. The sound pressure level (in dB SPL) that the signal in the audio file must have (by default: NULL). Can not be set if Calib.value is also set.
Calib.value	Numerical. The calibration value returned from the analysis of a reference signal using Leq. calib (by default: NULL). Can not be set if Leq. calib is also set.
time.mess	Logical. Activate or deactivate message of time to complete the function execution. (By default: TRUE)
stat.mess	Logical. Activate or deactivate status message of the function execution. (By default: TRUE)

Details

Caution: You need to use an audiofile with entire values of seconds of duration to avoid bugs. Example: 35s, 60s, 19s. By default, the function will trunc your audiofile to the next entire value of seconds.

These function works only with mono audiofiles.

The audio files need to have at least 44100Hz of sampling rate.

If you intend to work with decibels at full scale (dBFS), we recommend setting ref=1. With this, your results will be relative to 0 dBFS.

References

Power spectrum adapted from: Carcagno, S. 2013. Basic Sound Processing with R [Blog post]. Retrieved from http://samcarcagno.altervista.org/blog/basic-sound-processing-r/

Miyara, F. 2017. Software-Based Acoustical Measurements. Springer. 429 pp. DOI: 10.1007/978-3-319-55871-4

```
data(tham)
timbre(tham)
timbre(tham, Calib.value=130.24)
```

timbreCal 13

```
timbre(tham, Calib.value=130.24, weighting="A")
timbre(tham, Calib.value=130.24, weighting="A", bands="octaves")

timbre(tham, Leq.calib=48.17, weighting="A")

timbre(tham, from=-3.49, to=-0.9, ref=1) #dB at Full Scale
timbre(tham, from=-3.49, to=-0.9, Calib.value=130.24) #song Sound Pressure Level
timbre(tham, from=0, to=3.8, Calib.value=130.24) #background Sound Pressure Level
```

timbreCal

Timbre analysis for audiofiles with reference signal

Description

This function passes the parameters to timbre to automatize the calibration and return spectral analysis with dB SPL results.

Usage

Arguments

files	The audiofile to be analyzed. Can be "wd" to get all ".wav" files on the work directory, a file name (or a character containing a list of filenames) that exist in the work directory (only ".wav" files accepted), or an Wave object (or a list containing more than one Wave object). (By default: "wd")
channel	Argument passed to mono function from tuneR to extract the desired channel.
SignalDur	Numerical. Specify the reference signal duration (in seconds) on the beggining of the audiofile. (By default: $NULL$)
RefValue	Numerical. Specify the reference signal sound pressure level (in deciBells SPL) on the beggining of the audiofile. (By default: $NULL$)
ref	Numerical. The reference value for dB conversion. For sound in water, the common is 1 microPa, and for sound on air 20 microPa. (By default 20)
weighting	Character. Indicate the weighting curve to use on the anlysis. A, B, C and none are supported. (By default: "none")
bands	Character. Choose the type of frequency band of the output. "octaves" to octaves bands intervals or "thirds" to one-third octaves bands intervals. (by deafault: "thirds")
saveresults	Logical. Set TRUE if you want to save a txt file with the results of the function execution. (By default: $FALSE$)

Tweighting

outname	Character. If saveresults is TRUE, you can specify a name to appear on the txt file name after the default name. (By defaulf: NULL)
time.mess	Logical. Activate or deactivate message of time to complete the function execution. (By default: TRUE)
stat.mess	Logical. Activate or deactivate status message of the function execution. (By default: TRUE)

Details

To use this function, the audio file must begin with 2 seconds of silence, followed by a reference signal with known SPL, followed by another 2 seconds of silence, and the following sound to analyze.

The duration of the reference signal must be specified (in seconds) on the SignalDur argument and his value (in dB SPL) on the refValue argument.

See Also

timbre

Tweighting	Time Weighting of a Audiofile	

Description

Escrever descrição

Usage

```
Tweighting(file, window = "fast", Leq.calib = NULL, ...)
```

Arguments

file	Wave object
window	Character. Wich time window should be used. 'fast' or 'slow' are accepted. (by default: "fast")
Leq.calib	Numeric. The sound pressure level (in dB SPL) that the signal in the audio file must have (by default: NULL). This parameter is passed to timbre function.
	Further arguments passed to timbre.

Details

This function split your audiofile in smaller files defined as fast (0.125s) and slow (1s) and analyze each one with timbre function.

Value

A numeric vector

Tweighting 15

See Also

timbre, soundmeter

```
#creating an example sound file
som=sine(1000, duration = 44500)

#default options without calibration (results in dBFS)
Tweighting(som)

#Simulation of a calib signal with a Leq of 94dB in the field ####
#fast
Tweighting(som, window = "fast", bands="octaves", Leq.calib=94)
#slow
Tweighting(som, window = "slow", bands="octaves", Leq.calib=94)

#Using the result of the simulation above to calibrate the sound and output
#fast
Tweighting(som, window = "fast", bands="octaves", Calib.value=309.67)
#slow
Tweighting(som, window = "slow", bands="octaves", Calib.value=309.67)

#With tham data
data(tham)
Tweighting(tham, window = "fast", bands="octaves", Calib.value=130.24) #fast
Tweighting(tham, window = "slow", bands="octaves", Calib.value=130.24) #slow
```

Index

```
\ast datasets
     tham, 11
convSPL, 2, 4
dBtoLinear, 2, 4, 6, 10
\mathsf{dBweight}, \textcolor{red}{9}, \textcolor{red}{12}
freq.bands, 3, 7
LineartodB, 2, 4, 6, 10
mean, 6
meandB, 6
mono, 5, 7, 11, 13
moredB, 10
octaves, 3
pwrspec, 5
readWave, 11
rms, 6
rms.dB, 2, 4, 6
seewave, 3, 6
song.level, 7
soundmeter, 8, 15
sum, 10
sumdB, 10
tham, 11
timbre, 9, 11, 13–15
timbreCal, 13
tuneR, 5, 7, 11, 13
Tweighting, 14
```