Package 'soundmeteR'

June 8, 2022

Type Package

Title R package for sound meter alike analysis

Version 0.0.2

Author Cássio Rachid Simões, Shaka Nóbrega Marinho Furtado, Ingrid Maria Denóbile Torres, Marcelo Felgueiras Napoli and Carlos Barros de Araújo

Maintainer Cássio Rachid Simões <cassiorachid@gmail.com>

Description An R package designed for sound analysis through spectral analysis in octaves and one-thirds octaves, making possible calibration to obtain sound pressure level (SPL) and Sound Intensity Level (SIL).

URL https://github.com/cassiorachid/soundmeteR

BugReports https://github.com/cassiorachid/soundmeteR/issues

License GPL (>=3)

Depends tuneR, seewave

Encoding UTF-8

LazyData true

RoxygenNote 7.1.2

R topics documented:

---

dBtoLinear   *Convert deciBels scales to linear*

Description

Function to convert dB scales. The conversion can be made either from dB to linear (dBtoLinear) or from linear to dB (LineartodB).

Usage

```
dBtoLinear(x, factor="IL", ref=1)
```

Arguments

x	Numerical. A numeric vector or a numeric matrix with dB values for dBtoLinear funcion or linear values for LineartodB.
factor	Character. Specify in what factor the function should use to convert your data. SPL (Sound Pressure Level) for amplitude like data (factor 20) or IL (Intensity Level) for power like (fator 10). (By default IL)
ref	Numerical. Reference value for conversion. For Sound in water the ref is 1 microPa and on air 20 microPa. (By default 1)

Details

For details about the factor choice, we recommend the reading of this web page.

Value

The same object of the input with the converted values.

See Also

rms.dB, LineartodB, convSPL

Examples

```
dBtoLinear(c(80,60,65,62))
LineartodB(dBtoLinear(c(80,60,65,62)))
```

LineartodB   *Convert linear scales to deciBels*

Description

Function to convert dB scales. The conversion can be made either from dB to linear (dBtoLinear)
or from linear to dB (LineartodB).

Usage

```
LineartodB(x, factor="IL", ref=1)
```

Arguments

x	Numerical. A numeric vector or a numeric matrix with dB values for dBtoLinear funcion or linear values for LineartodB.
factor	Character. Specify in what factor the function should use to convert your data. SPL (Sound Pressure Level) for amplitude like data (factor 20) or IL (Intensity Level) for power like (fator 10). (By default IL)
ref	Numerical. Reference value for conversion. For Sound in water the ref is 1 microPa and on air 20 microPa. (By default 1)

Details

For details about the factor choice, we recommend the reading of this web page.

Value

The same object of the input with the converted values.

See Also

rms.dB, dBtoLinear, convSPL

Examples

```
dBtoLinear(c(80,60,65,62))
LineartodB(dBtoLinear(c(80,60,65,62)))
```

rms.dB	*Root Mean Square with dB values*

Description

Function to compute the root mean square (RMS) of values in decibels (dB).

Usage

```
rms.dB(x, level="SPL", ref=1, ...)
```

Arguments

x	Numerical. A numeric vector or a numeric matrix with dB values.
level	Character. Specify in what scale your data is. SPL for Sound Pressute Level or IL for Intensity Level. (By default SPL)
ref	Numerical. Reference value for conversion. For Sound in water the ref is 1microPa and on air 20 microPa. (By default 1)
...	Further arguments passed to mean.

Details

This function converts your dB data to linear values (through dBtoLinear function), compute the Root Mean Square (rms), and converts the result back to dB (through LineartodB function).

This function was adapted from meandB and rms functions from seewave package. See their help for more details.

Value

A numeric value that represents the root mean square of x.

See Also

meandB, rms

Examples

```
rms.dB(c(80,60,65,62))
```

---

soundmeter *Function that makes sound meter alike measurements*

Description

Function that makes sound meter alike measurements

Usage

```
soundmeter(
  files = "wd",
  from = 0,
  to = Inf,
  CalibPosition = NULL,
  CalibValue = 0,
  ref = 20,
  fw = "none",
  bands = "octaves",
  banpass = NULL,
  tw = "fast",
  time.mess = T,
  stat.mess = T,
  channel = "left",
  saveresults = F,
  outname = NULL
)
```

Arguments

CalibPosition	anda de mãos dadas com calib value. Pode ser negativo, positivo ou data.frame com essas combinações
CalibValue	Anda de mãos dadas com calib position. Quando tem o position, ele é considerado o valor de referência, quando não tem o position, ele é considerado o valor de calibração.
fw	Character. Argument passed to [dBweight](#) to indicate the frequency weighting curve to use on the anlysis. 'A', 'B', 'C', 'D', 'ITU', and 'none' are supported. See [dBweight](#) for details. (By default: "none")
tw	Time weighting
time.mess	Logical. Activate or deactivate message of time to complete the function execution. (By default: TRUE)
stat.mess	Logical. Activate or deactivate status message of the function execution. (By default: TRUE)
channel	Only "left" or "right" acepted. By default "left"
saveresults	Logical. Set TRUE if you want to save a txt file with the results of the function execution. (By default: FALSE)
outname	Character. If saveresults is TRUE, you can specify a name to appear on the txt file name after the default name. (By default: NULL)
bandpass	falta implementar...

Details

If your reference signal is in a separate file, we recommend you to get the `CalibValue` with [Tweighting](#) function. It's examples provide more details.

Examples

```
data("tham")
soundmeter(tham, CalibValue = 130.24, tw="slow") #slow time window with calib value
soundmeter(tham, CalibValue = NULL, tw="fast") #fast time window in dBFS
```

---

tham   Thamnophilus stictocephalus *song in a landscape*

Description

Thamnophilus stictocephalus song in a landscape

Usage

```
data(tham)
```

Format

An object of class "Wave"; see [readWave](#).

Details

A landscape recording presenting *Thamnophilus stictocephalus* song between 3.883035 and 7.044417 seconds. The "calib.value" for this record is 130.24.

Source

Recording by Ingrid Maria Denóbile Torres

---

timbre   *Level per octaves or one-thirds octaves*

Usage

```
timbre(files="wd", weighting="none", bands="thirds", ref=20, saveresults=F,
       outname=NULL, Leq.calib=NULL, Calib.value=NULL, time.mess=T, stat.mess=T)
```

Arguments

files	The audiofile to be analyzed. Can be "wd" to get all ".wav" files on the work directory, a file name (or a character containing a list of filenames) that exist in the work directory (only ".wav" files accepted), or an Wave object (or a list containing more than one Wave object). (By default: "wd")
weighting	Character. Argument passed to dBweight to indicate the weighting curve to use on the anlysis. 'A', 'B', 'C', 'D', 'ITU', and 'none' are supported. See dBweight for details. (By default: "none")
bands	Character. Choose the type of frequency band of the output. "octaves" to octaves bands intervals or "thirds" to one-third octaves bands intervals. (by deafault: "thirds")
ref	Numerical. The reference value for dB conversion. For sound in water, the common is 1 microPa, and for sound on air 20 microPa. (By default 20)
saveresults	Logical. Set TRUE if you want to save a txt file with the results of the function execution. (By default: FALSE)
outname	Character. If saveresults is TRUE, you can specify a name to appear on the txt file name after the default name. (By default: NULL)
Leq.calib	Numerical. The sound pressure level (in dB SPL) that the signal in the audio file must have (by default: NULL). Can not be set if Calib.value is also set.
Calib.value	Numerical. The calibration value returned from the analysis of a reference signal using Leq.calib (by default: NULL). Can not be set if Leq.calib is also set.
time.mess	Logical. Activate or deactivate message of time to complete the function execution. (By default: TRUE)
stat.mess	Logical. Activate or deactivate status message of the function execution. (By default: TRUE)

Details

Caution: You need to use an audiofile with entire values of seconds of duration to avoid bugs. Example: 35s, 60s, 19s. By default, the function will trunc your audiofile to the next entire value of seconds.

These function works only with mono audiofiles.

The audio files need to have at least 44100Hz of sampling rate.

If you intend to work with decibels at full scale (dBFS), we recommend setting ref=1. With this, your results will be relative to 0 dBFS.

References

Power spectrum adapted from: Carcagno, S. 2013. Basic Sound Processing with R [Blog post]. Retrieved from http://samcarcagno.altervista.org/blog/basic-sound-processing-r/

Miyara, F. 2017. Software-Based Acoustical Measurements. Springer. 429 pp. DOI: 10.1007/978-3-319-55871-4

---

timbreCal   *Timbre analysis for audiofiles with reference signal*

Description

This function passes the parameters to `timbre` to automatize the calibration and return spectral analysis with dB SPL results.

Usage

```
timbreCal(files="wd", SignalDur=NULL, RefValue=NULL, ref=20, weighting="none",
        bands="thirds", saveresults=F, outname=NULL, time.mess=T, stat.mess=T)
```

Arguments

files	The audiofile to be analyzed. Can be "wd" to get all ".wav" files on the work directory, a file name (or a character containing a list of filenames) that exist in the work directory (only ".wav" files accepted), or an Wave object (or a list containing more than one Wave object). (By default: "wd")
SignalDur	Numerical. Specify the reference signal duration (in seconds) on the beggining of the audiofile. (By default: NULL)
RefValue	Numerical. Specify the reference signal sound pressure level (in deciBells SPL) on the beggining of the audiofile. (By default: NULL)
ref	Numerical. The reference value for dB conversion. For sound in water, the common is 1 microPa, and for sound on air 20 microPa. (By default 20)
weighting	Character. Indicate the weighting curve to use on the anlysis. A, B, C and none are supported. (By default: "none")
bands	Character. Choose the type of frequency band of the output. "octaves" to octaves bands intervals or "thirds" to one-third octaves bands intervals. (by deafault: "thirds")
saveresults	Logical. Set `TRUE` if you want to save a txt file with the results of the function execution. (By default: `FALSE`)
outname	Character. If `saveresults` is `TRUE`, you can specify a name to appear on the txt file name after the default name. (By deaulf: NULL)
time.mess	Logical. Activate or deactivate message of time to complete the function execution. (By default: `TRUE`)
stat.mess	Logical. Activate or deactivate status message of the function execution. (By default: `TRUE`)

Details

To use this function, the audio file must begin with 2 seconds of silence, followed by a reference signal with known SPL, followed by another 2 seconds of silence, and the following sound to analyze.

The duration of the reference signal must be specified (in seconds) on the `SignalDur` argument and his value (in dB SPL) on the `refValue` argument.

See Also

`timbre`

Tweighting   *Time Weighting of a Audiofile*

Description

Escrever descrição

Usage

```
Tweighting(file, window = "fast", Leq.calib = NULL, ...)
```

Arguments

file	Wave object
window	Character. Wich time window should be used. 'fast' or 'slow' are accepted. (by default: "fast")
Leq.calib	Numeric. The sound pressure level (in dB SPL) that the signal in the audio file must have (by default: NULL). This parameter is passed to timbre function.
...	Further arguments passed to timbre.

Details

This function split your audiofile in smaller files defined as fast (0.125s) and slow (1s) and analyze each one with timbre function.

Value

A numeric vector

See Also

timbre, soundmeter

Examples

```
#creating an example sound file
som=sine(1000, duration = 44500)

#default options without calibration (results in dBFS)
Tweighting(som)

#Simulation of a calib signal with a Leq of 94dB in the field ####
#fast
Tweighting(som, window = "fast", bands="octaves", Leq.calib=94)
#slow
Tweighting(som, window = "slow", bands="octaves", Leq.calib=94)

#Using the result of the simulation above to calibrate the sound and output
#fast
Tweighting(som, window = "fast", bands="octaves", Calib.value=309.67)
#slow
Tweighting(som, window = "slow", bands="octaves", Calib.value=309.67)
```

```
#With tham data
data(tham)
Tweighting(som, window = "fast", bands="octaves", Calib.value=130.24) #fast
Tweighting(som, window = "slow", bands="octaves", Calib.value=130.24) #slow
```

Index