


**GRIDLOK SINGLE DIRECTIONAL BRACE**  
**ISOMETRIC VIEW**

TABLE 1 - PLENUM HEIGHT STUD SPECIFICATION

PLENUM HEIGHT (mm)	BRACE STUD TYPE
0-1600	64x0.50BMT LIPPED STUD
1600-2000	92x0.75BMT LIPPED STUD
2000-2600	BOXED 64x0.50BMT LIPPED STUD
2600-3000	BOXED 92x0.75BMT LIPPED STUD
3000+	SPECIFIC ENGINEERING REQUIRED

- NOTES:
1. INSTALL STUDS AS PER MANUFACTURER'S SPEC
  2. INSTALL GRIDLOCK AS PER MANUFACTURER'S SPEC
  3. WHERE BOXED STUDS ARE USED INSTALL AS PER MANUFACTURER'S SPEC
  4. SCREWED CONNECTION MIN SPACING AS SHOWN:  

  5. REPRESENTATIVE ONLY. SEE BREVITY SPEC FOR DETAILS
  6. ANY CHANGES ON SITE TO BE APPROVED BY BREVITY

DESIGNER:

**Brevity**

Victoria Park Market,  
Unit 72B,  
210 Victoria Street West  
Auckland 1010

+64 9 216 7104  
[www.teambrevity.com](http://www.teambrevity.com)

Tolerances (unless specified)	1-100	<1000	>1000
	± 2	± 10	± 70



Rev	Description
A	FOR CONSENT

Designed	BREVITY LTD	16/01/23
Drawn	BREVITY LTD	16/01/23

**GRIDLOK SINGLE  
DIRECTIONAL BRACE  
SPECIFICATION DRAWING**

Scale  
Do not Scale

DRG No. 050-31F Sheet 1 OF 1