

GRIDLOK BRACE - ISOMETRIC VIEW

TABLE 1 - PLENUM HEIGHT STUD SPECIFICATION

PLENUM HEIGHT (mm)	BRACE STUD TYPE
0-1600	64x0.50BMT LIPPED STUD
1600-2000	92x0.75BMT LIPPED STUD
2000-2600	BOXED 64x0.50BMT LIPPED STUD
2600-3000	BOXED 92x0.75BMT LIPPED STUD
3000+	SPECIFIC ENGINEERING REQUIRED


NOTES: 1. INSTALL STUDS AS

1. INSTALL STUDS AS PER MANUFACTURER'S SPEC

2. INSTALL GRIDLOCK AS PER MANUFACTURER'S SPEC

3. WHERE BOXED STUDS ARE USED INSTALL AS PER MANUFACTURER'S SPEC

4. SCREWED CONNECTION MIN SPACING AS SHOWN:



5. REPRESENTATIVE ONLY. SEE BREVITY SPEC FOR DETAILS

6. ANY CHANGES ON SITE TO BE APPROVED BY BREVITY

DESIGNER:



Victoria Park Market, Unit 72B, 210 Victoria Street West Auckland 1010

+64 9 216 7104 www.teambrevity.com

Tolerances (unless	1-100	<1000	>1000
specified)	± 2	± 10	± 70

All dim.



Rev	Description
Α	FOR CONSENT

Designed	BREVITY LTD	16/01/23
Drawn	BREVITY LTD	16/01/23

GRIDLOK BRACE SPECIFICATION DRAWING

Scale	Do not Scale	
DRG No.	Sheet	
050-33E	1 OF 1	