

Homework 2

```
1. public static void printLots(List<Object> L, List<Integer> P)
   {
       Iterator<Integer> itr2 = P.iterator();

       for (int x : P)
       {
           Object s = "";
           int count = itr2.next();
           Iterator<Object> itr1 = L.iterator();

           for (int i=0; i<count+1; i++)
           {
               if (itr1.hasNext())
               {
                   s= itr1.next();
               }
               else
               {
                   s="That index is out of bounds";
               }
           }
           System.out.println(s);
       }
   }
```

2. (Problem 4 from Weiss)

```
public List intersection(List L1, List L2,)
{
    Iterator itr1 = L1.iterator();
    List<Object> L3 = new LinkedList<Object>();

    while (itr1.hasNext())
    {
        Iterator itr2 = L2.iterator();
        Object target = itr1.next();

        while (itr2.hasNext())
        {
            if itr2.next().equals(target);
            {
                L3.add(target);
            }
        }
    }
}
```

```

    }
    }
    return L3;
}

```

3. (Problem 24 from Weiss)

```

public class Written3<AnyType>
{
    int top1;
    int top2;
    AnyType[] array;

    Written3(int n)
    {
        array = (AnyType[]) new Object[n];

        top1=-1;
        top2=array.length;
    }

    public boolean empty1()
    {
        if (top1== -1)
        {
            return true;
        }
        else
        {
            return false;
        }
    }

    public boolean empty2()
    {
        if(top2==array.length)
        {
            return true;
        }
        else
        {
            return false;
        }
    }

    public AnyType peek1()
    {
        return array[top1];
    }

    public AnyType peek2()

```

```

{
    return array[top2];
}

public AnyType pop1()
{
    if (top1 > -1)
    {
        AnyType popped= array[top1];
        top1--;
        return popped;
    }
    else
    {
        System.out.println("Error: Cannot pop empty stack");
        return null;
    }
}

public AnyType pop2()
{
    if (top2<array.length)
    {
        AnyType popped = array[top2];
        top2--;
        return popped;
    }
    else
    {
        System.out.println("Error: Cannot pop empty stack");
        return null;
    }
}

public void push1(AnyType a)
{
    if (top2-top1>1)
    {
        top1++;
        array[top1]=a;
    }
    else
    {
        System.out.println("StackOverflow Error");
    }
}

public void push2(AnyType a)
{
    if(top2-top1>1)
    {
        top2--;
        array[top2]=a;
    }
}

```

```

        else
        {
            System.out.println("StackOverflow Error");
        }
    }
}

```

- 4.a) 1. Move 4 from the front of the input track to holding track s1 (output track: blank)
 2. Move 3 from the front of the input track to holding track s1 (output track: blank)
 3. Move 1 from the front of the input track to the output track (output track: 1)
 4. Move 8 from the front of the input track to holding track s2 (output track: 1)
 5. Move 2 from the front of the input track to the output track (output track: 21)
 6. Move 7 from the front of the input track to holding track s2
 7. Move 6 from the front of the input track to holding track s2
 8. Move 9 from the front of the input track to holding track s3
 9. Move 5 from the front of the input track to holding track s2
 10. Move 3 from holding track s1 to the output track (output track: 321)
 11. Move 4 from holding track s1 to the output track (output track: 4321)
 12. Move 5 from holding track s2 to the output track (output track: 54321)
 13. Move 6 from holding track s2 to the output track (output track: 654321)
 14. Move 7 from holding track s2 to the output track (output track: 7654321)
 15. Move 8 from holding track s2 to the output track (output track: 87654321)
 16. Move 9 from holding track s1 to the output track (output track: 987654321)
- b) An example would be 135798642