# Carryover effects in free recall reveal how prior experiences influence memories of new experiences

Jeremy R. Manning<sup>1,\*</sup>, Andrew C. Heusser<sup>1,2</sup>, Kirsten Ziman<sup>1,3</sup>,
Emily Whitaker<sup>1</sup>, and Paxton C. Fitzpatrick<sup>1</sup>

<sup>1</sup>Dartmouth College

<sup>2</sup>Akili Interactive

<sup>3</sup>Princeton University

\*Corresponding author: jeremy.r.manning@dartmouth.edu

4 Abstract

10

11

12

13

14

15

16

We perceive, interpet, and remember ongoing experiences through the lens of our prior experiences. Inferring that we are one type of situation versus another can lead us to interpret the same physical experience differently. In turn, this can affect how we focus our attention, form expectations of what will happen next, remember what is happening now, draw on our prior related experiences, and so on. To study these phenomena, we asked participants to perform simple word list learning tasks. Across different experimental conditions, we held the set of to-be-learned words constant, but we manipulated the orders in which the words were studied. We found that these order manipulations affected not only how the participants recalled the ordered lists, but also how they recalled later randomly ordered lists. Our work shows how structure in our ongoing experiences can exert influence on how we remember unrelated subsequent experiences.

## <sup>7</sup> Introduction

Experience is subjective: different people who encounter identical physical experiences 18 can take away very different meanings and memories. One reason is that our subjective ex-19 periences in the moment are shaped in part the idiosyncratic prior experiences, memories, 20 goals, thoughts, expectations, and emotions that we bring with us into the present moment. These factors collectively define a *context* for our experiences <sup>13</sup>. situation models: forming 22 expectations, predicting ambiguous future experiences The contexts we encounter help us to construct situation models 15,24 or schemas 2,18 that describe how experiences are likely to unfold based on our prior experiences with similar contextual cues. For example, when 25 we enter a sit-down restaurant, we might expect to be seated at a table, given a menu, and served food. Priming someone to expect a particular situation or context can also influence how they resolve potentail ambiguities in their ongoing experiences, including 28 ambiguous movies and narratives<sup>32</sup>. 29

Our understanding of how we form situation models and schemas, and how they in-30 teract with our subjective experiences and memories, is constrained in part by substantial differences in how we study these processes. Situation models and schemas are most often 32 studied using "naturalistic" stimuli such as narratives and movies 20,33,34. In contrast, our 33 understanding of how we organize our memories has been most widely studied using more traditional paradigms like free recall of random word lists 11. In free recall, partici-35 pants study lists of items and are instructed to recall the items in any order they choose. The orders in which words come to mind can provide insights into how participants have organized their memories of the studied words. Because random word lists are unstruc-38 tured by design, it is not clear if or how non-trivial situation models might apply to these stimuli. Nevertheless, there are some commonalities between memory for word lists and memory for real-world experiences.


Like remembering real-world experiences, remembering words on a studied list re-42 quires distinguishing the current list from the rest of one's experience. To model this 43 fundamental memory capability, cognitive scientists have posited the existence of a special representation, called *context*, that is associated with each list. According to early 45 theories e.g. 1,6 context representations are composed of many features which fluctuate 46 from moment to moment, slowly drifting through a multidimensional feature space. Dur-47 ing recall, this representation forms part of the retrieval cue, enabling us to distinguish list items from non-list items. Understanding the role of context in memory processes is particularly important in self-cued memory tasks, such as free recall, where the retrieval 50 cue is "context" itself.

Over the past half-century, context-based models have enjoyed impressive success at 52 explaining many stereotyped behaviors observed during free recall and other list-learning 53 tasks<sup>6-8,12,21-23,27? -29</sup>. These phenomena include the well-known recency and primacy effects (superior recall of items from the end and, to a lesser extent, from the beginning of 55 the study list), as well as semantic and temporal clustering effects? The contiguity effect 56 is an example of temporal clustering, which is perhaps the dominant form of organization in free recall. This effect can be seen in the tendency for people to successively recall items 58 that occupied neighboring positions in the study list. For example, if a list contained the 59 sub-sequence "ABSENCE HOLLOW PUPIL" and the participant recalls the word "HOLLOW", it is far more likely that the next response will be either "PUPIL" or "ABSENCE" than some other list item 10. In addition, there is a strong forward bias in the contiguity effect: subjects 62 make forward transitions (i.e., "HOLLOW" followed by "PUPIL") about twice as often as 63 they make backward transitions, despite an overall tendency to begin recall at the end of the list. There are also striking effects of semantic clustering <sup>3,4,9,14,25</sup>, whereby the recall 65 of a given item is more likely to be followed by recall of a similar or related item than

a dissimilar or unrelated one. In general, people organize memories for words along a wide variety of stimulus dimensions. As captured by models like the *Context Maintenance* and *Retrieval Model*<sup>22</sup>, the stimulus features associated with each word (e.g. the word's meaning, font size, font color, location on the screen, size of the object the word represents, etc.) are incorporated into the participant's mental context representation <sup>13,15–17,30</sup>. During a memory test, any of these features may serve as a memory cue, which in turn leads the participant to recall in succession words that share stimulus features.

A key mystery is whether the sorts of situation models and schemas that people use to organize their memories of real-world experiences might map onto the clustering effects that reflect how people organize their memories for word lists. On one hand, situation models and clustering effects both reflect statistical regularities in ongoing experience. Our memory systems exploit these regularities when generating inferences about the unobserved past and yet-to-be-experienced future <sup>5,19,24,26,31</sup>. On the other hand, the rich structure of real-world experiences and other naturalistic stimuli that enable people to form deep and meaningful situation models and schemas have no obvious analog in simple word lists. Often lists in free recall studies are explicitly *designed* to be devoid of exploitable temporal structure, for example by sorting the words in a random order <sup>11</sup>.

We designed an experimental paradigm to explore how people organize their memories for simple stimuli (word lists) whose temporal properties change across different "situations," analogous to how the content of real-world experiences change across different real-world situations. We asked participants to study and freely recall a series of word lists (Fig. 1). Across the different conditions in the experiment, we varied the lists' presentation orders in different ways across lists. The studied items (words) were designed to vary along three general dimensions: semantic (word *category*, and physical *size* of the referent), lexicographic (word *length* and *first letter*), and visual (font *color* and



**Figure 1: Feature-rich free recall.** After studying lists comprised of words that vary along several feature dimensions, participants verbally recall words in any order (microphone icon).

the onscreen *location* of each word). In our main manipulation conditions, we asked par-92 ticipants to study and recall eight lists whose items were sorted by a target feature (e.g., 93 word category). Next, we asked them to study and recall an additional eight lists whose 94 items had the same features, but that were sorted in a random temporal order. We were in-95 terested in how these order manipulations affected participants' recall behaviors on early 96 (sorted) lists, as well as how order manipulations on early lists affected recall behaviors 97 on later (unsorted) lists. We used a series of control conditions as a baseline; in these 98 control conditions all of the lists were sorted randomly, but we manipulated the presence 99 or absence of the visual features. Finally, in an adaptive experimental condition we used 100 participants' recall behaviors on early lists to manipulate, in real-time, the presentation 101 orders of subsequent lists. In this adaptive condition, we sought to identify potential 102 commonalities within and across participants in how people organized their memories 103 and how those organizational tendancies affect overall performance.

#### 5 Materials and methods

#### 106 Participants

We enrolled a total of 491 Dartmouth undergraduate students across 11 experimental conditions. The conditions included two primary controls (feature rich, reduced), two secondary controls (reduced (early), reduced (late)), six order manipulation conditions (category, size, length, first letter, color, and location), and a final adaptive condition. Each of these conditions are described in the *Experimental design* subsection below.

Participants received course credit for enrolling in our study. We asked each participant to fill out a demographic survey that included information about their self-reported age, gender, ethnicity, race, education, vision, reading impairments, medications or recent injuries, coffee consumption on the day of testing, and level of alertness at the time of testing. All components of the demographics survey were optional. One participant elected not to fill out any part of the demographic survey, and all other participants report some or all of their requested demographic information.

We aimed to run (to completion) at least 60 participants in each of the two primary control conditions and in the adaptive condition. In all other conditions we set a target enrollment of at least 30 participants. Because our data collection efforts were coordinated 12 researchers and multiple testing rooms and computers, it was not feasible for individual experimenters to know how many participants had been run in each experimental condition until the relevant databases were synchronized at the end of each working day. We also over-enrolled participants for each condition to help ensure that we met our minimum enrollment targets even if some participants dropped out of the study prematurely or did not show up for their testing session. This led us to exceed our target enrollments for several conditions.

Participants were assigned to experimental conditions based loosely on their date of 129 participation. (This aspect of our procedure helped us to more easily synchronize the ex-130 periment databases across multiple testing computers.) Of the 490 participants who opted 131 to fill out the demographics survey, reported ages ranged from 17 to 31 years (mean: 19.1; 132 standard deviation: 1.356). A total of 318 participants reported their gender as female, 133 170 as male, and 2 participants declined to report their gender. A total of 442 participants 134 reported their ethnicity as "not Hispanic or Latino," 39 as "Hispanic or Latino," and 9 135 declined to report their ethnicity. Participants reported their races as White (345 partic-136 ipants), Asian (120 participants), Black or African American (31 participants), American 137 Indian or Alaska Native (11 particiapnts), Native Hawaiian or Other Pacific Islander (4 138 participants), Mixed race (3 participants), Middle Eastern (1 participant), and Arab (1 139 participant). A total of 5 participants declined to report their race. We note that several 140 participants reported more than one of racial category. Participants reported their highest degrees achieved as "Some college" (359 participants), "High school graduate" (117 142 participants), "College graduate" (7 participants), "Some high school" (5 participants), 143 "Doctorate" (1 participant), and "Master's degree" (1 participant). A total of 482 participants reported no reading impairments, and 8 reported mild reading impairments such 145 as mild dyslexia. A total of 489 participants reported having normal color vision and 1 146 participant reported that they were color blind. A total of 482 participants reported taking 147 no prescription medications and having no recent injuries; 4 participants reported having 148 ADHD, 1 reported having dyslexia, 1 reported having allergies, 1 reported a recently 149 torn ACL/MCL, and 1 reported a concussion from several months prior. The participants 150 reported consuming 0 – 3 cups of coffee prior to the testing session (mean: 0.32 cups; 151 standard deviation: 0.58 cups). Participants reported their current level of alertness, and 152 we converted their responses to numerical scores as follows: "very sluggish" (-2), "a little 153

sluggish" (-1), "neutral" (0), "a little alert" (1), and "very alert" (2). Across all participants, the full range of alertness levels were reported (range: -2 – 2; mean: 0.35; standard deviation: 0.89).

We dropped from our dataset the 1 participant who reported abnormal color vision, as 157 well as 39 participants whose data were corrupted due to technical failures while running 158 the experiment or during the daily database merges. In total, this left usable data from 159 452 participants, broken down by experimental condition as follows: feature rich (67 160 participants), reduced (61 participants), reduced (late) (41 participants), reduced (early), 161 (42 participants), category (30 participants), size (30 participants), length (30 participants), 162 first letter (30 participants), color (31 participants), location (30 participants), and adaptive 163 (60 participants). The participant who declined to fill out their demographic survey 164 participated in the location condition, and we verified verbally that they had normal color 165 vision. 166

### 167 Experimental design

Our experiment is a variant of the classic free recall paradigm that we term feature-rich free 168 recall. In feature-rich free recall, participants study 16 lists, each comprised of 16 words 169 that vary along a number of stimulus dimensions: semantic category, object size, text 170 color, text location, word length, and starting letter (Fig. 1). Each list contains four words from each of four different semantic categories and two object sizes; all other stimulus 172 features are randomized. After studying each list, the participant attempts to recall as 173 many words as they can from that list, in any order they choose. Because each individual 174 word is associated with several well-defined (and quantifiable) features, and because each 175 list incorporates a diverse mix of feature values along each dimension, this allows us to 176 evaluate participants' memory fingerprints in rich detail.

Our experimental paradigm incorporates the Annyang and Google Cloud Speech
API speech-to-text engines to automatically transcribe participants' verbal recalls into
text. This allows recalls to be transcribed in real time—a distinguishing feature of the
experiment; in typical verbal recall experiments the audio data must be parsed manually.
(We have run a pilot experiment to verify that the automatically transcribed recalls are
sufficiently close to human-transcribed recalls to yield reliable data.) This real-time speech
processing component of the paradigm plays an important role in Experiments 3–5.

#### 185 Stimuli

- 186 Real-time speech-to-text processing
- 187 Order manipulation conditions
- 188 Feature dimensions.
- 189 Constructing feature-sorted lists.
- 190 Random conditions
- 191 Adaptive conditions
- 192 Online "fingerprint" analysis.
- 193 Ordering "stabilize" lists by an estimated fingerprint.
- Ordering "destabilize" lists by an estimated fingerprint.

- 195 Analysis
- Probability of first recall and probability of  $n^{th}$  recall
- 197 Lag conditional response probability
- 198 Computing clustering scores and memory fingerprints
- 199 Identifying event boundaries
- 200 Serial position curves and recall accuracy
- 201 Computing low-dimensional embeddings of memory fingerprints


#### 202 Results

- 203 Figure S3.
- Figure S7.
- Figure S4.


## 206 Discussion

## 207 References

- <sup>208</sup> [1] Anderson, J. R. and Bower, G. H. (1972). Recognition and retrieval processes in free recall. *Psychological Review*, 79(2):97–123.
- [2] Baldassano, C., Hasson, U., and Norman, K. A. (2018). Representation of real-world event schemas during narrative perception. *The Journal of Neuroscience*, 38(45):9689–9699.



**Figure 2: Recall dynamics in feature rich free recall (order manipulation conditions). A.** Behavioral plots. **Left panels.** The probabilities of initiating recall with each word are plotted as a function of presentation position. **Middle panels.** The conditional probabilities of recalling each word are plotted as a function of the relative position (Lag) to the words recalled just-prior. **Right panels.** The overall probabilities of recalling each word are plotted as a function of presentation position. **All panels.** Error ribbons denote bootstrap-estimated 95% confidence intervals (calculated across participants). Top panels display the recall dynamics for early (order manipulation) lists in each condition (color). Bottom panels display the recall dynamics for late (randomly ordered) lists. See Figures S1 and S2 for analogous plots for the random (control) and adaptive conditions. **B.** Proportion of event boundaries (see *Methods*) for each condition's feature of focus, plotted as a function of presentation position.



**Figure 3: Memory "fingerprints" (order manipulation conditions).** The across-participant distributions of clustering scores for each feature type (*x*-coordinate) are displayed for each experimental condition (color), separately for order manipulation (early, top) and randomly ordered (late, bottom) lists. See Figures S5 and S6 for analogous plots for the random (control) and adaptive conditions.

- 213 [3] Bousfield, W. A. (1953). The occurrence of clustering in the recall of randomly arranged
  214 associates. *Journal of General Psychology*, 49:229–240.
- <sup>215</sup> [4] Bousfield, W. A., Sedgewick, C. H., and Cohen, B. H. (1954). Certain temporal characteristics of the recall of verbal associates. *American Journal of Psychology*, 67:111–118.
- <sup>217</sup> [5] Bower, G. H., Black, J. B., and Turner, T. J. (1979). Scripts in memory for text. *Cognitive*<sup>218</sup> *Psychology*, 11(2):177–220.
- [6] Estes, W. K. (1955). Statistical theory of spontaneous recovery and regression. *Psychological Review*, 62:145–154.
- <sup>221</sup> [7] Glenberg, A. M., Bradley, M. M., Kraus, T. A., and Renzaglia, G. J. (1983). Studies of the long-term recency effect: support for a contextually guided retrieval theory. *Journal* of Experimental Psychology: Learning, Memory, and Cognition, 12:413–418.







Figure 4: Interactions between feature clustering, recall probability, and contiguity. A. Recall probability versus feature clustering scores for order manipulation (early) lists. B. Recall probability versus feature clustering for randomly ordered (late) lists. C. Recall probability on late lists versus feature clustering on early lists. D. Recall probability on early lists versus feature clustering on late lists. E. Temporal clustering scores (contiguity) versus feature clustering scores on early lists. F. Temporal clustering scores versus feature clustering scores on late lists. G. Temporal clustering scores on early lists versus feature clustering scores on early lists. H. Temporal clustering scores on early lists versus feature clustering scores on late lists. All panels. Each dot in the main scatterplots denotes the average scores for one participant. The colored regression lines are computed across participants. The inset displays condition-averaged results, where each dot reflects a single condition and the regression line is computed across experimental conditions. All error ribbons denote bootstrap-estimated 95% confidence intervals.



**Figure 5: Memory fingerprint dynamics (order manipulation conditions). A.** Each column (and color) reflects an experimental condition. In the top panels, each marker displays a 2D projection of the (across-participant) average memory fingerprint for one list. Order manipulation (early) lists are denoted by circles and randomly ordered (late) lists are denoted by stars. All of the fingerprints (across all conditions and lists) are projected into a common space. The bar plots in the bottom panels display the Euclidean distances of the per-list memory fingerprints to the list 0 fingerprint, for each condition. Error bars denote bootstrap-estimated 95% confidence intervals. The dotted vertical lines denote the boundaries between early and late lists. **B.** In this panel, the fingerprints for early (circle) and late (star) lists are averaged across lists and participants before projecting the fingerprints into a (new) 2D space. See Figure S8 for analogous plots for the random (control) conditions.



**Figure 6: Feature clustering carryover effects. A.** Feature clustering scores for ordder manipulation (early) versus randomly ordered (late) lists. **B.** Accuracy differences (on early versus late lists) versus feature clustering "carryover" (defined as the differences between the average clustering scores on early and late lists). **C.** Temporal clustering differences (on early versus late lists) versus feature clustering carryover. **All panels.** Each dot in the main scatterplots denotes the average scores for one participant. The colored regression lines are computed across participants. The inset displays condition-averaged results, where each dot reflects a single condition and the regression line is computed across experimental conditions. All error ribbons denote bootstrap-estimated 95% confidence intervals.



**Figure 7: Recall performance (adaptive conditions).** The bars display the average probability of recall (taken across words, lists, and participants) for lists from each adaptive condition. Error bars denote bootstrap-estimated 95% confidence intervals. For additional details about participants' behavior and performance during the adaptive conditions, see Figure S2.

- <sup>224</sup> [8] Howard, M. W. and Kahana, M. J. (2002). A distributed representation of temporal context. *Journal of Mathematical Psychology*, 46:269–299.
- <sup>226</sup> [9] Jenkins, J. J. and Russell, W. A. (1952). Associative clustering during recall. *Journal of*<sup>227</sup> *Abnormal and Social Psychology*, 47:818–821.
- [10] Kahana, M. J. (1996). Associative retrieval processes in free recall. *Memory and Cognition*, 24:103–109.
- <sup>230</sup> [11] Kahana, M. J. (2012). *Foundations of human memory*. Oxford University Press, New York, NY.
- [12] Kimball, D. R., Smith, T. A., and Kahana, M. J. (2007). The fSAM model of false recall.

  Psychological Review, 114(4):954–993.
- <sup>234</sup> [13] Manning, J. R. (2020). Context reinstatement. In Kahana, M. J. and Wagner, A. D., editors, *Handbook of Human Memory*. Oxford University Press.
- <sup>236</sup> [14] Manning, J. R. and Kahana, M. J. (2012). Interpreting semantic clustering effects in free recall. *Memory*, 20(5):511–517.

- <sup>238</sup> [15] Manning, J. R., Norman, K. A., and Kahana, M. J. (2015). The role of context in episodic memory. In Gazzaniga, M., editor, *The Cognitive Neurosciences*, pages 557–566.
- MIT Press.
- <sup>241</sup> [16] Manning, J. R., Polyn, S. M., Baltuch, G., Litt, B., and Kahana, M. J. (2011). Oscil-
- latory patterns in temporal lobe reveal context reinstatement during memory search.
- 243 Proceedings of the National Academy of Sciences, USA, 108(31):12893–12897.
- <sup>244</sup> [17] Manning, J. R., Sperling, M. R., Sharan, A., Rosenberg, E. A., and Kahana, M. J.
- 245 (2012). Spontaneously reactivated patterns in frontal and temporal lobe predict semantic
- clustering during memory search. *The Journal of Neuroscience*, 32(26):8871–8878.
- <sup>247</sup> [18] Masís-Obando, R., Norman, K. A., and Baldassano, C. (2022). Scheme representations
- in distinct brain networks support narrative memory during encoding and retrieval.
- *eLife*, 11:e70445.
- 250 [19] Momennejad, I., Russek, E. M., Cheong, J. H., Botvinick, M. M., Daw, N. D., and
- Gershman, S. J. (2017). The successor representation in human reinforcement learning.
- Nature Human Behavior, 1:680–692.
- <sup>253</sup> [20] Nastase, S. A., Goldstein, A., and Hasson, U. (2020). Keep it real: rethinking the
- primacy of experimental control in cognitive neuroscience. *NeuroImage*, 15(222):117254—
- 255 117261.
- <sup>256</sup> [21] Polyn, S. M. and Kahana, M. J. (2008). Memory search and the neural representation
- of context. *Trends in Cognitive Sciences*, 12:24–30.
- <sup>258</sup> [22] Polyn, S. M., Norman, K. A., and Kahana, M. J. (2009). Task context and organization
- in free recall. *Neuropsychologia*, 47:2158–2163.

- <sup>260</sup> [23] Raaijmakers, J. G. W. and Shiffrin, R. M. (1980). SAM: A theory of probabilistic search
- of associative memory. In Bower, G. H., editor, *The Psychology of Learning and Motivation:*
- 262 Advances in Research and Theory, volume 14, pages 207–262. Academic Press, New York,
- 263 NY.
- <sup>264</sup> [24] Ranganath, C. and Ritchey, M. (2012). Two cortical systems for memory-guided
- behavior. *Nature Reviews Neuroscience*, 13:713–726.
- <sup>266</sup> [25] Romney, A. K., Brewer, D. D., and Batchelder, W. H. (1993). Predicting clustering
- from semantic structure. *Psychological Science*, 4:28–34.
- <sup>268</sup> [26] Schapiro, A. and Turk-Browne, N. (2015). Statistical learning. *Brain Mapping: An*
- Encyclopedic Refernce, 3:501–506.
- <sup>270</sup> [27] Sederberg, P. B., Howard, M. W., and Kahana, M. J. (2008). A context-based theory of
- recency and contiguity in free recall. *Psychological Review*, 115(4):893–912.
- <sup>272</sup> [28] Shankar, K. H. and Howard, M. W. (2012). A scale-invariant internal representation
- of time. Neural Computation, 24:134–193.
- 274 [29] Sirotin, Y. B., Kimball, D. R., and Kahana, M. J. (2005). Going beyond a single list:
- modeling the effects of prior experience on episodic free recall. *Psychonomic Bulletin and*
- 276 Review, 12(5):787–805.
- [30] Smith, S. M. and Vela, E. (2001). Environmental context-dependent memory: a review
- and meta-analysis. Psychonomic Bulletin and Review, 8(2):203–220.
- 279 [31] Xu, X., Zhu, Z., and Manning, J. R. (2022). The psychological arrow of time drives
- temporal asymmetries in retrodicting versus predicting narrative events. *PsyArXiv*,
- page doi.org/10.31234/osf.io/yp2qu.

- <sup>282</sup> [32] Yeshurun, Y., Swanson, S., Simony, E., Chen, J., Lazaridi, C., Honey, C. J., and Hasson, U. (2017). Same story, different story: the neural representation of interpretive frameworks. *Psychological Science*, 28(3):307–319.
- <sup>285</sup> [33] Zwaan, R. A., Langston, M. C., and Graesser, A. C. (1995). The construction of situation models in narrative comprehension: an event-indexing model. *Psychological Science*, 6(5):292–297.
- <sup>288</sup> [34] Zwaan, R. A. and Radvansky, G. A. (1998). Situation models in language comprehension and memory. *Psychological Bulletin*, 123(2):162–185.