

¹ Text embedding models yield high-resolution insights
² into conceptual knowledge from short multiple-choice
³ quizzes

⁴ Paxton C. Fitzpatrick¹, Andrew C. Heusser^{1, 2}, and Jeremy R. Manning^{1,*}

¹Department of Psychological and Brain Sciences

Dartmouth College, Hanover, NH 03755, USA

²Akili Interactive Labs

Boston, MA 02110, USA

*Corresponding author: Jeremy.R.Manning@Dartmouth.edu

⁵ **Abstract**

⁶ We develop a mathematical framework, based on natural language processing models, for track-
⁷ ing and characterizing the acquisition of conceptual knowledge. Our approach embeds each
⁸ concept in a high-dimensional representation space, where nearby coordinates reflect similar or
⁹ related concepts. We test our approach using behavioral data from participants who answered
¹⁰ small sets of multiple-choice quiz questions interleaved between watching two course videos
¹¹ from the Khan Academy platform. We apply our framework to the videos' transcripts and
¹² the text of the quiz questions to quantify the content of each moment of video and each quiz
¹³ question. We use these embeddings, along with participants' quiz responses, to track how the
¹⁴ learners' knowledge changed after watching each video. Our findings show how a small set of
¹⁵ quiz questions may be used to obtain rich and meaningful high-resolution insights into what
¹⁶ each learner knows, and how their knowledge changes over time as they learn.

¹⁷ **Keywords:** education, learning, knowledge, concepts, natural language processing

¹⁸ **Introduction**

¹⁹ Suppose that a teacher had access to a complete, tangible “map” of everything a student knows.
²⁰ Defining what such a map might even look like, let alone how it might be constructed or filled in, is
²¹ itself a non-trivial problem. But if a teacher *were* to gain access to such a map, how might it change
²² their ability to teach that student? Perhaps they might start by checking how well the student
²³ knows the to-be-learned information already, or how much they know about related concepts.
²⁴ For some students, they could potentially optimize their teaching efforts to maximize efficiency
²⁵ by focusing primarily on not-yet-known content. For other students (or other content areas), it
²⁶ might be more effective to optimize for direct connections between already known content and
²⁷ new material. Observing how the student’s knowledge changed over time, in response to their
²⁸ teaching, could also help to guide the teacher towards the most effective strategy for that individual
²⁹ student.

³⁰ A common approach to assessing a student’s knowledge is to present them with a set of quiz
³¹ questions, calculate the proportion they answer correctly, and provide them with feedback in the
³² form of a simple numeric or letter grade. While such a grade can provide *some* indication of whether
³³ the student has mastered the to-be-learned material, any univariate measure of performance on a
³⁴ complex task sacrifices certain relevant information, risks conflating underlying factors, and so on.
³⁵ For example, consider the relative utility of the theoretical map described above that characterizes
³⁶ a student’s knowledge in detail, versus a single annotation saying that the student answered 85%
³⁷ of their quiz questions correctly, or that they received a ‘B’. Here, we show that the same quiz data
³⁸ required to compute proportion-correct scores or letter grades can instead be used to obtain far
³⁹ more detailed insights into what a student knew at the time they took the quiz.

⁴⁰ Designing and building procedures and tools for mapping out knowledge touches on deep
⁴¹ questions about what it means to learn. For example, how do we acquire conceptual knowledge?
⁴² Memorizing course lectures or textbook chapters by rote can lead to the superficial *appearance*
⁴³ of understanding the underlying content, but achieving true conceptual understanding seems to
⁴⁴ require something deeper and richer. Does conceptual understanding entail connecting newly

45 acquired information to the scaffolding of one’s existing knowledge or experience [4, 9, 11, 12, 25,
46 56]? Or weaving a lecture’s atomic elements (e.g., its component words) into a structured network
47 that describes how those individual elements are related [35, 60]? Conceptual understanding
48 could also involve building a mental model that transcends the meanings of those individual
49 atomic elements by reflecting the deeper meaning underlying the gestalt whole [32, 36, 53, 59].

50 The difference between “understanding” and “memorizing,” as framed by researchers in ed-
51 ucation, cognitive psychology, and cognitive neuroscience [e.g., 20, 23, 28, 36, 53], has profound
52 analogs in the fields of natural language processing and natural language understanding. For
53 example, considering the raw contents of a document (e.g., its constituent symbols, letters, and
54 words) might provide some clues as to what the document is about, just as memorizing a pas-
55 sage might provide some ability to answer simple questions about it. However, text embedding
56 models [e.g., 5, 6, 8, 10, 13, 34, 43, 61] also attempt to capture the deeper meaning *underlying* those
57 atomic elements. These models consider not only the co-occurrences of those elements within and
58 across documents, but (in many cases) also patterns in how those elements appear across different
59 scales (e.g., sentences, paragraphs, chapters, etc.), the temporal and grammatical properties of the
60 elements, and other high-level characteristics of how they are used [37?]. To be clear, this is not
61 to say that text embedding models themselves are capable of “understanding” deep conceptual
62 meaning in any traditional sense. But rather, their ability to capture the underlying *structure* of
63 text documents beyond their surface-level contents provides a computational framework through
64 which those document’s deeper conceptual meaning may be quantified, explored, and understood.
65 According to these models, the deep conceptual meaning of a document may be captured by a
66 feature vector in a high-dimensional representation space, wherein nearby vectors reflect concep-
67 tually related documents. A model that succeeds at capturing an analogue of “understanding” is
68 able to assign nearby feature vectors to two conceptually related documents, *even when the specific*
69 *words contained in those documents have limited overlap*. In this way, “concepts” are defined implicitly
70 by the model’s geometry [e.g., how the embedding coordinate of a given word or document relates
71 to the coordinates of other text embeddings; 48].

72 Given these insights, what form might a representation of the sum total of a person’s knowledge

73 take? First, we might require a means of systematically describing or representing (at least some
74 subset of) the nearly infinite set of possible things a person could know. Second, we might want to
75 account for potential associations between different concepts. For example, the concepts of “fish”
76 and “water” might be associated in the sense that fish live in water. Third, knowledge may have
77 a critical dependency structure, such that knowing about a particular concept might require first
78 knowing about a set of other concepts. For example, understanding the concept of a fish swimming
79 in water first requires understanding what fish and water *are*. Fourth, as we learn, our “current
80 state of knowledge” should change accordingly. Learning new concepts should both update our
81 characterizations of “what is known” and also unlock any now-satisfied dependencies of those
82 newly learned concepts so that they are “tagged” as available for future learning.

83 Here we develop a framework for modeling how conceptual knowledge is acquired during
84 learning. The central idea behind our framework is to use text embedding models to define the
85 coordinate systems of two maps: a *knowledge map* that describes the extent to which each concept is
86 currently known, and a *learning map* that describes changes in knowledge over time. Each location
87 on these maps represents a single concept, and the maps’ geometries are defined such that related
88 concepts are located nearby in space. We use this framework to analyze and interpret behavioral
89 data collected from an experiment that had participants answer sets of multiple-choice questions
90 about a series of recorded course lectures.

91 Our primary research goal is to advance our understanding of what it means to acquire deep,
92 real-world conceptual knowledge. Traditional laboratory approaches to studying learning and
93 memory (e.g., list-learning studies) often draw little distinction between memorization and under-
94 standing. Instead, these studies typically focus on whether information is effectively encoded or
95 retrieved, rather than whether the information is *understood*. Approaches to studying conceptual
96 learning, such as category learning experiments, can begin to investigate the distinction between
97 memorization and understanding, often by training participants to distinguish arbitrary or random
98 features in otherwise meaningless categorized stimuli [1, 17, 18, 21, 26, 51]. However the objective
99 of real-world training, or learning from life experiences more generally, is often to develop new
100 knowledge that may be applied in *useful* ways in the future. In this sense, the gap between modern

learning theories and modern pedagogical approaches that inform classroom learning strategies is enormous: most of our theories about *how* people learn are inspired by experimental paradigms and models that have only peripheral relevance to the kinds of learning that students and teachers actually seek [23, 36]. To help bridge this gap, our study uses course materials from real online courses to inform, fit, and test models of real-world conceptual learning. We also provide a demonstration of how our models can be used to construct “maps” of what students know, and how their knowledge changes with training. In addition to helping to visually capture knowledge (and changes in knowledge), we hope that such maps might lead to real-world tools for improving how we educate. Taken together, our work shows that existing course materials and evaluative tools like short multiple-choice quizzes may be leveraged to gain highly detailed insights into what students know and how they learn.

Results

At its core, our main modeling approach is based around a simple assumption that we sought to test empirically: all else being equal, knowledge about a given concept is predictive of knowledge about similar or related concepts. From a geometric perspective, this assumption implies that knowledge is fundamentally “smooth.” In other words, as one moves through a space representing an individual’s knowledge (where similar concepts occupy nearby coordinates), their “level of knowledge” should change relatively gradually. To begin to test this smoothness assumption, we sought to track participants’ knowledge and how it changed over time in response to training. Two overarching goals guide our approach. First, we want to gain detailed insights into what learners know at different points in their training. For example, rather than simply reporting on the proportions of questions participants answer correctly (i.e., their overall performance), we seek estimates of their knowledge about a variety of specific concepts. Second, we want our approach to be potentially scalable to large numbers of diverse concepts, courses, and students. This requires that the conceptual content of interest be discovered *automatically*, rather than relying on manually produced ratings or labels.



Figure 1: Experimental paradigm. Participants alternate between completing three 13-question multiple-choice quizzes and watching two Khan Academy lectures. Each quiz contains a mix of 5 questions about Lecture 1, 5 questions about Lecture 2, and 3 questions about general physics knowledge. The specific questions reflected on each quiz, and the orders of each quiz's questions, were randomized across participants.

127 We asked participants in our study to complete brief multiple-choice quizzes before, between,
 128 and after watching two lecture videos from the Khan Academy [31] platform (Fig. 1). The first
 129 lecture video, entitled *Four Fundamental Forces*, discussed the four fundamental forces in physics:
 130 gravity, strong and weak interactions, and electromagnetism. The second, entitled *Birth of Stars*,
 131 provided an overview of our current understanding of how stars form. We selected these particular
 132 lectures to satisfy three general criteria. First, we wanted both lectures to be accessible to a broad
 133 audience (i.e., with minimal prerequisite knowledge) so as to limit the impact of prior training
 134 on participants' abilities to learn from the lectures. To this end, we selected two introductory
 135 videos that were intended to be viewed at the start of students' training in their respective content
 136 areas. Second, we wanted the two lectures to have some related content, so that we could test
 137 our approach's ability to distinguish similar conceptual content. To this end, we chose two videos
 138 from the same Khan Academy course domain, "Cosmology and Astronomy." Third, we sought to
 139 minimize dependencies and specific overlap between the videos. For example, we did not want
 140 participants' abilities to understand one video to (directly) influence their abilities to understand the
 141 other. To satisfy this last criterion, we chose videos from two different lecture series (Lectures 1 and
 142 2 were from the "Scale of the Universe" and "Stars, Black Holes, and Galaxies" series, respectively).

143 We also wrote a set of multiple-choice quiz questions that we hoped would enable us to
 144 evaluate participants' knowledge about each individual lecture, along with related knowledge



Figure 2: Modeling course content. **A. Building a document pool from sliding windows of text.** We decompose each lecture’s transcript into a series of overlapping sliding windows. The full set of transcript snippets (across all windows) may be treated as a set of “documents” for training a text embedding model. **B. Constructing lecture content trajectories.** After training the model on the sliding windows from both lectures, we transform each lecture into a “trajectory” through text embedding space by joining the embedding coordinates of successive sliding windows parsed from its transcript. **C. Embedding multiple lectures and questions in a shared space.** We apply the same model (trained on the two lectures’ windows) to both lectures, along with the text of each question in our pool (Supp. Tab. 1), to project them into a shared text embedding space. This results in one trajectory per lecture and one coordinate for each question. Here, we have projected the 15-dimensional embeddings onto their first 3 principal components for visualization.

145 about physics concepts not specifically presented in either video (see Supp. Tab. 1 for the full list
 146 of questions in our stimulus pool). Participants answered questions randomly drawn from each
 147 content area (Lecture 1, Lecture 2, and general physics knowledge) on each of the three quizzes.
 148 Quiz 1 was intended to assess participants’ “baseline” knowledge before training, Quiz 2 assessed
 149 knowledge after watching the *Four Fundamental Forces* video (i.e., Lecture 1), and Quiz 3 assessed
 150 knowledge after watching the *Birth of Stars* video (i.e., Lecture 2).

151 To study in detail how participants’ conceptual knowledge changed over the course of the
 152 experiment, we first sought to model the conceptual content presented to them at each moment
 153 throughout each of the two lectures. We adapted an approach we developed in prior work [24]
 154 to identify the latent themes in the lectures using a topic model [6]. Briefly, topic models take
 155 as input a collection of text documents, and learn a set of “topics” (i.e., latent themes) from their
 156 contents. Once fit, a topic model can be used to transform arbitrary (potentially new) documents
 157 into sets of “topic proportions,” describing the weighted blend of learned topics reflected in their
 158 texts. We parsed automatically generated transcripts of the two lectures into overlapping sliding
 159 windows, where each window contained the text of the lecture transcript from a particular time

span. We treated the set of text snippets (across all of these windows) as documents to fit the model (Fig. 2A; see *Constructing text embeddings of multiple lectures and questions*). Transforming the text from every sliding window with the model yielded a number-of-windows by number-of-topics (15) topic-proportions matrix describing the unique mixture of broad themes from both lectures reflected in each window’s text. Each window’s “topic vector” (i.e., column of the topic-proportions matrix) is analogous to a coordinate in a 15-dimensional space whose axes are topics discovered by the model. Within this space, each lecture’s sequence of topic vectors (i.e., corresponding to its transcript’s overlapping text snippets across sliding windows) forms a *trajectory* that captures how its conceptual content unfolds over time (Fig. 2B). We resampled these trajectories to a resolution of one topic vector for each second of video (i.e., 1 Hz).

We hypothesized that a topic model trained on transcripts of the two lectures should also capture the conceptual knowledge probed by each quiz question. If indeed the topic model could capture information about the deeper conceptual content of the lectures (i.e., beyond surface-level details such as particular word choices), then we should be able to recover a correspondence between each lecture and questions *about* each lecture. Importantly, such a correspondence could not solely arise from superficial text matching between lecture transcripts and questions, since the lectures and questions often used different words (Supp. Fig. 5) and phrasings. Simply comparing the average topic weights from each lecture and question set (averaging across time and questions, respectively) reveals a striking correspondence (Supp. Fig. 2). Specifically, the average topic weights from Lecture 1 are strongly correlated with the average topic weights from Lecture 1 questions ($r(13) = 0.809$, $p < 0.001$, 95% confidence interval (CI) = [0.633, 0.962]), and the average topic weights from Lecture 2 are strongly correlated with the average topic weights from Lecture 2 questions ($r(13) = 0.728$, $p = 0.002$, 95% CI = [0.456, 0.920]). At the same time, the average topic weights from the two lectures are *negatively* correlated with the average topic weights from their non-matching question sets (Lecture 1 video vs. Lecture 2 questions: $r(13) = -0.547$, $p = 0.035$, 95% CI = [-0.812, -0.231]; Lecture 2 video vs. Lecture 1 questions: $r(13) = -0.612$, $p = 0.015$, 95% CI = [-0.874, -0.281]), indicating that the topic model also exhibits some degree of specificity. The full set of pairwise comparisons between average topic weights for the lectures and question sets




Figure 3: Lecture and question topic overlap. A. Topic weight variability. The bar plots display the variance of each topic's weight across lecture timepoints (top row) and questions (bottom row); colors denote topics. The top-weighted words from the most “expressive” (i.e., variable across observations) topic from each lecture are displayed in the upper right (orange: topic 2; yellow-green: topic 4). The top-weighted words from the full set of topics may be found in Supplementary Table 2. **B. Relationships between topic weight variability.** Pairwise correlations between the distributions of topic weight variance for each lecture and question set. Each row and column corresponds to a bar plot in Panel A.

188 is reported in Supplementary Figure 2.

189 Another, more sensitive, way of summarizing the conceptual content of the lectures and ques-
190 tions is to look at *variability* in how topics are weighted over time and across different questions
191 (Fig. 3). Intuitively, the variability in the expression of a given topic relates to how much “infor-
192 mation” [19] the lecture (or question set) reflects about that topic. For example, suppose a given
193 topic is weighted on heavily throughout a lecture. That topic might be characteristic of some
194 aspect or property of the lecture *overall* (conceptual or otherwise), but unless the topic’s weights
195 changed in meaningful ways over time, the topic would be a poor indicator of any *specific* concep-
196 tual content in the lecture. We therefore also compared the variances in topic weights (across time
197 or questions) between the lectures and questions. The variability in topic expression (over time
198 and across questions) was similar for the Lecture 1 video and questions ($r(13) = 0.824, p < 0.001,$
199 $95\% \text{ CI} = [0.696, 0.973]$) and the Lecture 2 video and questions ($r(13) = 0.801, p < 0.001, 95\%$
200 $\text{CI} = [0.539, 0.958]$). Simultaneously, as reported in Figure 3B, the variabilities in topic expression
201 across *different* videos and lecture-specific questions (i.e., Lecture 1 video vs. Lecture 2 questions;

202 Lecture 2 video vs. Lecture 1 questions) were negatively correlated, and neither video’s topic
203 variability was reliably correlated with the topic variability across general physics knowledge
204 questions. Taken together, the analyses reported in Figure 3 and Supplementary Figure 2 indicate
205 that a topic model fit to the videos’ transcripts can also reveal correspondences (at a coarse scale)
206 between the lectures and questions.

207 While an individual lecture may be organized around a single broad theme at a coarse scale,
208 at a finer scale, each moment of a lecture typically covers a narrower range of content. Given the
209 correspondence we found between the variabilities in topic expression across moments of each
210 lecture and questions from its corresponding set (Fig. 3), we wondered whether the text embedding
211 model might additionally capture these conceptual relationships at a finer scale. For example, if a
212 particular question asks about the content from one small part of a lecture, we wondered whether
213 the text embeddings could be used to automatically identify the “matching” moment(s) in the
214 lecture. To explore this, we computed the correlation between each question’s topic weights
215 and the topic weights for each second of its corresponding lecture, and found that each question
216 appeared to be temporally specific (Fig. 4). In particular, most questions’ topic vectors were
217 maximally correlated with a well-defined (and relatively narrow) range of timepoints from their
218 corresponding lectures, and the correlations fell off sharply outside of that range (Supp. Figs. 3, 4).
219 We also qualitatively examined the best-matching intervals for each question by comparing the
220 question’s text to the transcribed text from the most-correlated parts of the lectures (Supp. Tab. 3).
221 Despite that the questions were excluded from the text embedding model’s training set, in general
222 we found (through manual inspection) a close correspondence between the conceptual content
223 that each question probed and the content covered by the best-matching moments of the lectures.
224 Two representative examples are shown at the bottom of Figure 4.

225 The ability to quantify how much each question is “asking about” the content from each moment
226 of the lectures could enable high-resolution insights into participants’ knowledge. Traditional
227 approaches to estimating how much a student “knows” about the content of a given lecture entail
228 administering some form of assessment (e.g., a quiz) and computing the proportion of correctly
229 answered questions. But if two students receive identical scores on such an exam, might our



Figure 4: Which parts of each lecture are captured by each question? Each panel displays time series plots showing how each question’s topic vector correlates with each video timepoint’s topic vector (Panel A.: correlations for the *Four Fundamental Forces* lecture and associated questions; Panel B.: correlations for the *Birth of Stars* lecture and associated questions). The colors denote question identities. The diamonds in each panel denote the moment of peak correlation between the indicated question and the lecture trajectory. The associated questions’ text and snippets of the lectures’ transcripts from the surrounding 30 seconds, are displayed at the bottom of the figure.

modeling framework help us to gain more nuanced insights into the *specific* content that each student has mastered (or failed to master)? For example, a student who misses three questions that were all about the same concept (e.g., concept *A*) will have gotten the same *proportion* of questions correct as another student who missed three questions about three *different* concepts (e.g., *A*, *B*, and *C*). But if we wanted to help these two students fill in the “gaps” in their understandings, we might do well to focus specifically on concept *A* for the first student, but to also add in materials pertaining to concepts *B* and *C* for the second student. In other words, raw “proportion-correct” measures may capture *how much* a student knows, but not *what* they know. We wondered whether our modeling framework might enable us to (formally and automatically) infer participants’ knowledge at the scale of individual concepts (e.g., as captured by a single moment of a lecture).

We developed a simple formula (Eqn. 1) for using a participant’s responses to a small set of multiple-choice questions to estimate how much the participant “knows” about the concept reflected by any arbitrary coordinate x in text embedding space (e.g., the content reflected by

any moment in a lecture they had watched; see *Estimating dynamic knowledge traces*). Essentially, the estimated knowledge at coordinate x is given by the weighted proportion of quiz questions the participant answered correctly, where the weights reflect how much each question is “about” the content at x . When we apply this approach to estimate the participant’s knowledge about the content presented in each moment of each lecture, we can obtain a detailed time course describing how much “knowledge” that participant has about the content presented at any part of the lecture. As shown in Figure 5A and C, we can apply this approach separately for the questions from each quiz participants took throughout the experiment. From just a few questions per quiz (see *Estimating dynamic knowledge traces*), we obtain a high-resolution snapshot (at the time each quiz was taken) of what the participants knew about any moment’s content, from either of the two lectures they watched (comprising a total of 1,100 samples across the two lectures).

While the time courses in Figure 5A and C provide detailed *estimates* about participants’ knowledge, these estimates are of course only *useful* to the extent that they accurately reflect what participants actually know. As one sanity check, we anticipated that the knowledge estimates should reflect a content-specific “boost” in participants’ knowledge after watching each lecture. In other words, if participants learn about each lecture’s content upon watching it, the knowledge estimates should capture that. After watching the *Four Fundamental Forces* lecture, participants should exhibit more knowledge for the content of that lecture than they had before, and that knowledge should persist for the remainder of the experiment. Specifically, knowledge about that lecture’s content should be relatively low when estimated using Quiz 1 responses, but should increase when estimated using Quiz 2 or 3 responses (Fig. 5B). Indeed, we found that participants’ estimated knowledge about the content of *Four Fundamental Forces* was substantially higher on Quiz 2 versus Quiz 1 ($t(49) = 8.764, p < 0.001$) and on Quiz 3 versus Quiz 1 ($t(49) = 10.519, p < 0.001$). We found no reliable differences in estimated knowledge about that lecture’s content on Quiz 2 versus 3 ($t(49) = 0.160, p = 0.874$). Similarly, we hypothesized (and subsequently confirmed) that participants should show greater estimated knowledge about the content of the *Birth of Stars* lecture after (versus before) watching it (Fig. 5D). Specifically, since participants watched that lecture after taking Quiz 2 (but before Quiz 3), we hypothesized that their knowledge estimates



Figure 5: Estimating knowledge about the content presented at each moment of each lecture. **A. Knowledge about the time-varying content of *Four Fundamental Forces*.** Each trace displays the weighted proportion of correctly answered questions about the content reflected in each moment of the lecture (see *Estimating dynamic knowledge traces*), using responses from a single quiz (color). The traces are averaged across participants. **B. Average estimated knowledge about *Four Fundamental Forces*.** Each bar displays the across-timepoint average knowledge, estimated using the responses to one quiz's questions. **C. Knowledge about the time-varying content of *Birth of Stars*.** The panel is in the same format as Panel A, but here the knowledge estimates are for the moment-by-moment content of the *Birth of Stars* lecture. **D. Average estimated knowledge about *Birth of Stars*.** The panel is in the same format as Panel B, but here the knowledge estimates are for the content of the *Birth of Stars* lecture. All panels: error ribbons and error bars denote 95% confidence intervals, estimated across participants.

271 should be relatively low on Quizzes 1 and 2, but should show a “boost” on Quiz 3. Consistent
272 with this prediction, we found no reliable differences in estimated knowledge about the *Birth of*
273 *Stars* lecture content on Quizzes 1 versus 2 ($t(49) = 1.013, p = 0.316$), but the estimated knowl-
274 edge was substantially higher on Quiz 3 versus 2 ($t(49) = 10.561, p < 0.001$) and Quiz 3 versus 1
275 ($t(49) = 8.969, p < 0.001$).

276 If we are able to accurately estimate a participant’s knowledge about the content tested by
277 a given question, our estimates of their knowledge should carry some predictive information
278 about whether they are likely to answer that question correctly or incorrectly. We developed a
279 statistical approach to test this claim. For each quiz question a participant answered, in turn,
280 we used Equation 1 to estimate their knowledge at the given question’s embedding space co-
281 ordinate based on other questions that participant answered on the same quiz. We repeated
282 this for all participants, and for each of the three quizzes. Then, separately for each quiz, we
283 fit a generalized linear mixed model (GLMM) with a logistic link function to explain the like-
284 lihood of correctly answering a question as a function of estimated knowledge for its embed-
285 ding coordinate, while accounting for random variation among participants and questions (see
286 *GLMM METHODS SECTION PLACEHOLDER*). To assess the predictive value of the knowledge
287 estimates, we compared each GLMMs to an analogous (i.e., nested) “null” model that did not
288 consider estimated knowledge using parametric bootstrap likelihood-ratio tests.

289 We carried out three different versions of the analyses described above, wherein we considered
290 different sources of information in our estimates of participants’ knowledge for each quiz question.
291 First, we estimated knowledge at each question’s embedding coordinate using *all other* questions
292 answered by the same participant on the same quiz (“All questions”; Fig. 6, top row). This test was
293 intended to assess the overall predictive power of our approach. Second, we estimated knowledge
294 for each question about one lecture using only questions (from the same participant and quiz)
295 about the *other* lecture (“Across-lecture”; Fig. 6, middle rows). This test was intended to assess the
296 *generalizability* of our approach by asking whether our predictions held across the content areas of
297 the two lectures. Third, we estimated knowledge for each question about a given lecture using only
298 the other questions (from the same participant and quiz) about that *same* lecture (“Within-lecture”;




Figure 6: Predicting success on held-out questions using estimated knowledge. We used generalized linear mixed models (GLMMs) to model the likelihood of correctly answering a quiz question as a function of estimated knowledge for its embedding coordinate (see *GLMM METHODS SECTION PLACEHOLDER*). Separately for each quiz (column), we examined this relationship based on three different sets of knowledge estimates: knowledge for each question based on all other questions the same participant answered on the same quiz (“All questions”; top row), knowledge for each question about one lecture based on all questions (from the same participant and quiz) about the *other* lecture (“Across-lecture”; middle rows), and knowledge for each question about one lecture based on all other questions (from the same participant and quiz) about the *same* lecture (“Within-lecture”; bottom rows). The background in each panel displays the relative density of observed correctly (blue) versus incorrectly (red) answered questions over the range of knowledge estimates. The black curves display the (population-level) GLMM-predicted probabilities of correctly answering a question as a function of estimated knowledge. Error ribbons denote 95% confidence intervals.

299 Fig. 6, bottom rows). This test was intended to assess the *specificity* of our approach by asking
300 whether our predictions could distinguish between questions about different content covered by
301 the same lecture.

302 Our null hypothesis in performing these analyses is that the knowledge estimates we compute
303 based on the quiz questions' embedding coordinates do *not* provide useful information about
304 participants' abilities to answer those questions. What result might we expect to see if this is
305 the case? To provide an intuition for this, consider the expected outcome if we carried out these
306 same analyses using a simple proportion-correct measure in lieu of our knowledge estimates.
307 Suppose a participant correctly answered n out of 13 questions on a given quiz. If we held out a
308 single correctly answered question and computed the proportion of remaining questions answered
309 correctly, that proportion would be $(n - 1)/12$. Whereas if we held out a single *incorrectly* answered
310 question and did the same, that proportion would be $n/12$. Thus for a given participant and quiz,
311 a "knowledge estimate" computed as the simple (i.e., unweighted) remaining proportion-correct
312 is perfectly inversely related to success on a held-out question: it will always be *lower* for correctly
313 answered questions than for incorrectly answered questions. Given that our knowledge estimates
314 are computed as a weighted version of this same proportion-correct score (where each held-in
315 question's weight reflects its embedding-space distance from the held-out question; see Eqn. 1),
316 if these weights are uninformative (e.g., simply randomly distributed), then we would expect, on
317 average, to see this same inverse relationship. It is only if the spatial relationships among the quiz
318 questions' embedding coordinates map onto participants' knowledge in a meaningful way that
319 we would expect this relationship to be non-negative [PHRASING].

320 When we fit a GLMM to estimates of participants' knowledge for each Quiz 1 question based on
321 all other Quiz 1 questions, we observed this inverse relationship expected under our null hypoth-
322 esis. Specifically, higher estimated knowledge at the embedding coordinate of a held-out Quiz 1
323 question was associated with a lower likelihood of answering the question correctly (odds ratio
324 (OR) = 0.136, likelihood-ratio test statistic (λ_{LR}) = 19.749, 95% CI = [14.352, 26.545], $p = 0.001$).
325 However, when we repeated this analysis for quizzes 2 and 3, the direction of this relationship
326 reversed: higher estimated knowledge for a given question predicted a greater likelihood of an-

327 swering it correctly (Quiz 2: $OR = 2.905$, $\lambda_{LR} = 17.333$, 95% CI = [14.966, 29.309], $p = 0.002$;
328 Quiz 3: $OR = 3.238$, $\lambda_{LR} = 6.882$, 95% CI = [6.228, 8.184], $p = 0.017$). Taken together, these results
329 suggest that our knowledge estimations can reliably predict participants' likelihood of success
330 on individual quiz questions, provided they have at least some amount of structured knowledge
331 about the underlying concepts being tested. In other words, when participants' correct responses
332 primarily arise from knowledge about the content probed by each question (e.g., after watching
333 one or both lectures), these successes can be predicted from their ability to answer other questions
334 about conceptually similar content (as captured by embedding-space distance). However, when a
335 sufficiently large portion of participants' correct responses (presumably) reflect successful random
336 guessing (such as on a multiple-choice quiz taken before viewing either lecture), our approach fails
337 to predict these successes since they do not map onto embedding space distances in a meaningful
338 way.

339 When we

340 Taken together, the results of these sets of analyses suggest that our knowledge estimations
341 can reliably predict participants' abilities to answer individual quiz questions, generalize across
342 content areas, and distinguish between questions about similar content, provided that a basic set
343 of assumptions about that content (as described above) can be assumed.

344 For the initial quizzes participants took (prior to watching either lecture), predicted knowledge
345 tended to be low overall, and relatively unstructured (Fig. 6, left column). When we held out indi-
346 vidual questions and predicted their knowledge at the held-out questions' embedding coordinates,
347 we found no reliable differences in the predictions when the held-out question had been correctly
348 versus incorrectly answered. This "null" effect persisted when we used *all* of the Quiz 1 questions
349 from a given participant to predict a held-out question ("All questions"; $U = 50587$, $p = 0.723$),
350 when we used questions from one lecture to predict knowledge at the embedding coordinate of
351 a held-out question about the *other* lecture ("Across-lecture"; predicting knowledge for held-out
352 *Four Fundamental Forces Questions* using *Birth of Stars* questions: $U = 8244$, $p = 0.184$; predicting
353 knowledge for held-out *Birth of Stars* questions: $U = 8202.5$, $p = 0.161$), and when we used ques-
354 tions from one lecture to predict knowledge at the embedding coordinate of a held-out question

355 about the *same* lecture (“Within-lecture”; *Four Fundamental Forces*: $U = 7681.5$, $p = 0.746$; *Birth of*
356 *Stars*: $U = 8125$, $p = 0.204$). We believe that this reflects a floor effect: when knowledge is low
357 everywhere, there is little signal to differentiate between what is known versus unknown.

358 After watching *Four Fundamental Forces*, predicted knowledge for held-out questions that were
359 answered correctly (from the second quiz; Fig. 6, middle column) exhibited a significant positive
360 shift relative to held-out questions that were answered incorrectly. This held when we included
361 all questions in the analysis ($U = 58332$, $p < 0.001$), when we predicted knowledge across-
362 lectures (*Four Fundamental Forces*: $U = 6749.5$, $p = 0.014$; *Birth of Stars*: $U = 8480$, $p = 0.016$),
363 and when we predicted knowledge at the embedding coordinates of held-out *Four Fundamental*
364 *Forces* questions using other *Four Fundamental Forces* questions from the same quiz and participant
365 ($U = 7224$, $p < 0.001$). This difference did *not* hold for within-lecture knowledge predictions at
366 knowledge at embedding space coordinates of *Birth of Stars* questions ($U = 7419$, $p = 0.739$). Again,
367 we suggest that this might reflect a floor effect whereby, at that point in the participants’ training,
368 their knowledge about the content of the *Birth of Stars* material is relatively low everywhere in that
369 region of text embedding space.

370 Finally, after watching *Birth of Stars*, predicted knowledge for held-out correctly answered ques-
371 tions (from the third quiz; Fig. 6, right column) was higher than for held-out incorrectly answered
372 questions. This held when we included all questions in the analysis ($U = 38279$, $p = 0.022$),
373 when we carried out across-lecture predictions (*Four Fundamental Forces*: $U = 6684.5$, $p = 0.032$;
374 *Birth of Stars*: $U = 6414.5$, $p = 0.002$), and when we carried out within-lecture knowledge predic-
375 tions for held-out *Birth of Stars* questions using other *Birth of Stars* questions from the same quiz
376 and participant ($U = 6126$, $p = 0.006$). However, we found the *opposite* effect when we carried
377 out within-lecture knowledge predictions for held-out *Four Fundamental Forces* questions using
378 other *Four Fundamental Forces* questions from the same quiz and participant ($U = 6734$, $p = 0.027$).
379 Specifically, on Quiz 3, our knowledge predictions for held-out correctly answered questions about
380 *Four Fundamental Forces* were reliably *lower* than those for their incorrectly answered counterparts.
381 Speculatively, we suggest that this may reflect participants forgetting some of the *Four Fundamental*
382 *Forces* content. If this forgetting happens in a relatively “random” way (with respect to spatial dis-

383 tance within the text embedding space), then it could explain why some held-out questions about
384 *Four Fundamental Forces* were answered incorrectly, even if questions at nearby coordinates (i.e.,
385 about similar content) were answered correctly. This might lead our approach to over-estimate
386 knowledge for held-out questions about “forgotten” knowledge that participants answered in-
387 correctly. Taken together, the results in Figure 6 indicate that our approach can reliably predict
388 acquired knowledge (especially about recently learned content), and that the knowledge predic-
389 tions are generalizable across the content areas spanned by the two lectures, while also specific
390 enough to distinguish between questions about more subtly different content within the same
391 lecture.

392 That the knowledge predictions derived from the text embedding space reliably distinguish
393 between held-out correctly versus incorrectly answered questions (Fig. 6) suggests that spatial
394 relationships within this space can help explain what participants know. But how far does this
395 explanatory power extend? For example, suppose we know that a participant correctly answered a
396 question at embedding coordinate x . As we move farther away from x in the embedding space, how
397 does the likelihood that the participant knows about the content at a given location “fall off” with
398 distance? Conversely, suppose the participant instead answered that same question *incorrectly*.
399 Again, as we move farther away from x in the embedding space, how does the likelihood that the
400 participant does *not* know about a coordinate’s content change with distance? We reasoned that,
401 assuming our embedding space is capturing something about how individuals actually organize
402 their knowledge, a participant’s ability to answer questions embedded very close to x should
403 tend to be similar to their ability to answer the question embedded *at* x . Whereas at another
404 extreme, once we reach some sufficiently large distance from x , our ability to infer whether or
405 not a participant will correctly answer a question based on their ability to answer the question
406 at x should be no better than guessing based on their *overall* proportion of correctly answered
407 questions. In other words, beyond the maximum distance at which the participant’s ability to
408 answer the question at x is informative of their ability to answer a second question at location y ,
409 then guessing the outcome at y based on x should be no more successful than guessing based on a
410 measure that does not consider embedding space distance.




Figure 7: Knowledge falls off gradually in text embedding space. A. Performance versus distance. For each participant, for each correctly answered question (blue) or incorrectly answered question (red), we computed the proportion of correctly answered questions within a given distance of that question’s embedding coordinate. We used these proportions as a proxy for participants’ knowledge about the content within that region of the embedding space. We repeated this analysis for all questions and participants, and separately for each quiz (column). The black lines denote the average proportion correct across *all* questions included in the analysis at the given distance. **B. Maximum distance for which performance is reliably different from the average.** We used a bootstrap procedure (see *Estimating the “smoothness” of knowledge*) to estimate the point at which the blue and red lines in Panel A reliably diverged from the black line. We repeated this analysis separately for correctly and incorrectly answered questions from each quiz. **All panels.** Error ribbons denote bootstrap-estimated 95% confidence intervals.

With these ideas in mind, we asked: conditioned on answering a question correctly, what proportion of all questions (within some radius, r , of that question’s embedding coordinate) were answered correctly? We plotted this proportion as a function of r . Similarly, we could ask, conditioned on answering a question incorrectly, how the proportion of correct responses changed with r . As shown in Figure 7, we found that quiz performance falls off smoothly with distance, and the “rate” of the falloff does not appear to change across the different quizzes, as measured by the distance at which performance becomes statistically indistinguishable from a simple proportion correct score (see *Estimating the “smoothness” of knowledge*). This suggests that, at least within the region of text embedding space covered by the questions our participants

420 answered (and as characterized using our topic model), the rate at which knowledge changes
421 with distance is relatively constant, even as participants' overall level of knowledge varies across
422 quizzes or regions of the embedding space.

423 Knowledge estimates need not be limited to the content of the lectures. As illustrated in
424 Figure 8, our general approach to estimating knowledge from a small number of quiz questions
425 may be extended to *any* content, given its text embedding coordinate. To visualize how knowledge
426 "spreads" through text embedding space to content beyond the lectures participants watched, we
427 first fit a new topic model to the lectures' sliding windows with $k = 100$ topics. Conceptually,
428 increasing the number of topics used by the model functions to increase the "resolution" of the
429 embedding space, providing a greater ability to estimate knowledge for content that is highly
430 similar to (but not precisely the same as) that contained in the two lectures. We note that we
431 used these 2D maps solely for visualization; all relevant comparisons, distance computations, and
432 statistical tests we report above were carried out in the original 15-dimensional space, using the
433 15-topic model. Aside from increasing the number of topics from 15 to 100, all other procedures
434 and model parameters were carried over from the preceding analyses. As in our other analyses,
435 we resampled each lecture's topic trajectory to 1 Hz and projected each question into a shared text
436 embedding space.

437 We projected the resulting 100-dimensional topic vectors (for each second of video and each quiz
438 question) onto a shared 2-dimensional plane (see *Creating knowledge and learning map visualizations*).
439 Next, we sampled points from a 100×100 grid of coordinates that evenly tiled a rectangle enclos-
440 ing the 2D projections of the videos and questions. We used Equation 4 to estimate participants'
441 knowledge at each of these 10,000 sampled locations, and averaged these estimates across par-
442 ticipants to obtain an estimated average *knowledge map* (Fig. 8A). Intuitively, the knowledge map
443 constructed from a given quiz's responses provides a visualization of how "much" participants
444 knew about any content expressible by the fitted text embedding model at the point in time when
445 they completed that quiz.

446 Several features of the resulting knowledge maps are worth noting. The average knowledge
447 map estimated from Quiz 1 responses (Fig. 8A, leftmost map) shows that participants tended to




Figure 8: Mapping out the geometry of knowledge and learning. **A.** Average “knowledge maps” estimated using each quiz. Each map displays a 2D projection of the estimated knowledge about the content reflected by *all* regions of topic space (see *Creating knowledge and learning map visualizations*). The topic trajectories of the two lectures are indicated by dotted lines (blue: Lecture 1; green: Lecture 2), and the coordinates of each question are indicated by dots (light blue: Lecture 1-related; light green: Lecture 2-related; purple: general physics knowledge). Each map reflects an average across all participants. For individual participants’ maps, see Supplementary Figures 7, 8, and 9. **B.** Average “learning maps” estimated between each successive pair of quizzes. The learning maps follow the same general format as the knowledge maps in Panel A, but here the shading at each coordinate indicates the *difference* between the corresponding coordinates in the indicated pair of knowledge maps—i.e., how much the estimated knowledge “changed” between the two quizzes. Each map reflects an average across all participants. For individual participants’ maps, see Supplementary Figures 10 and 11. **C.** Word clouds for sampled points in topic space. Each word cloud displays the weighted blend of words underlying the topic proportions represented at the corresponding colored star’s location on the maps. In each word cloud, the words’ relative sizes correspond to their relative weights at the starred location, and their colors indicate their relative weights in *Four Fundamental Forces* (blue) versus *Birth of Stars* (green) lectures, on average, across all timepoints’ topic vectors.

448 have relatively little knowledge about any parts of the text embedding space (i.e., the shading is
449 relatively dark everywhere). The knowledge map estimated from Quiz 2 responses shows a marked
450 increase in knowledge on the left side of the map (around roughly the same range of coordinates
451 traversed by the *Four Fundamental Forces* lecture, indicated by the dotted blue line). In other words,
452 participants' estimated increase in knowledge is localized to conceptual content that is nearby (i.e.,
453 related to) the content from the lecture they watched prior to taking Quiz 2. This localization is
454 non-trivial: these knowledge estimates are informed only by the embedded coordinates of the
455 *quiz questions*, not by the embeddings of either lecture (see Eqn. 4). Finally, the knowledge map
456 estimated from Quiz 3 responses shows a second increase in knowledge, localized to the region
457 surrounding the embedding of the *Birth of Stars* lecture participants watched immediately prior to
458 taking Quiz 3.

459 Another way of visualizing these content-specific increases in knowledge after participants
460 viewed each lecture is displayed in Figure 8B. Taking the point-by-point difference between the
461 knowledge maps estimated from responses to a successive pair of quizzes yields a *learning map*
462 that describes the *change* in knowledge estimates from one quiz to the next. These learning maps
463 highlight that the estimated knowledge increases we observed across maps were specific to the
464 regions around the embeddings of each lecture, in turn.

465 Because the 2D projection we used to construct the knowledge and learning maps is invertible,
466 we may gain additional insights into these maps' meanings by reconstructing the original high-
467 dimensional topic vector for any location on the map we are interested in. For example, this could
468 serve as a useful tool for an instructor looking to better understand which content areas a student
469 (or a group of students) knows well (or poorly). As a demonstration, we show the top-weighted
470 words from the blends of topics reconstructed from three example locations on the maps (Fig. 8C):
471 one point near the *Four Fundamental Forces* embedding (yellow), a second point near the *Birth of*
472 *Stars* embedding (orange), and a third point between the two lectures' embeddings (pink). As
473 shown in the word clouds in the panel, the top-weighted words at the example coordinate near the
474 *Four Fundamental Forces* embedding tended to be weighted more heavily by the topics expressed
475 in that lecture. Similarly, the top-weighted words at the example coordinate near the *Birth of Stars*

embedding tended to be weighted more heavily by the topics expressed in *that* lecture. And the top-weighted words at the example coordinate between the two lectures' embeddings show a roughly even mix of words most strongly associated with each lecture.

479 Discussion

We developed a computational framework that uses short multiple-choice quizzes to gain nuanced insights into what learners know and how their knowledge changes with training. First, we show that our approach can automatically match the conceptual knowledge probed by individual quiz questions to the corresponding moments in lecture videos when those concepts were presented (Fig. 4). Next, we demonstrate how we can estimate moment-by-moment "knowledge traces" that reflect the degree of knowledge participants have about each video's time-varying content, and capture temporally specific increases in knowledge after viewing each lecture (Fig. 5). We also show that these knowledge estimates can generalize to held-out questions (Fig. 6). Finally, we use our framework to construct visual maps that provide snapshot estimates of how much participants know about any concept within the scope of our text embedding model, and how much their knowledge of those concepts changes with training (Fig. 8).

We view our work as making several contributions to the study of how people acquire conceptual knowledge. First, from a methodological standpoint, our modeling framework provides a systematic means of mapping out and characterizing knowledge in maps that have infinite (arbitrarily many) numbers of coordinates, and of "filling out" those maps using relatively small numbers of multiple choice quiz questions. Our experimental finding that we can use these maps to predict responses to held-out questions has several psychological implications as well. For example, concepts that are assigned to nearby coordinates by the text embedding model also appear to be "known to a similar extent" (as reflected by participants' responses to held-out questions; Fig. 6). This suggests that participants also *conceptualize* similarly the content reflected by nearby embedding coordinates. How participants' knowledge falls off with spatial distance is captured by the knowledge maps we infer from their quiz responses (e.g., Figs. 7, 8). In other words, our

502 study shows that knowledge about a given concept implies knowledge about related concepts,
503 and we also show how estimated knowledge falls off with distance in text embedding space.

504 In our study, we characterize the “coordinates” of participants’ knowledge using a relatively
505 simple “bag of words” text embedding model [LDA; 6]. More sophisticated text embedding mod-
506 els, such as transformer-based models [15, 47, 58, 61] can learn complex grammatical and semantic
507 relationships between words, higher-order syntactic structures, stylistic features, and more. We
508 considered using transformer-based models in our study, but we found that the text embeddings
509 derived from these models were surprisingly uninformative with respect to differentiating or oth-
510 erwise characterizing the conceptual content of the lectures and questions we used. We suspect
511 that this reflects a broader challenge in constructing models that are high-resolution within a given
512 domain (e.g., the domain of physics lectures and questions) *and* sufficiently broad so as to enable
513 them to cover a wide range of domains. For example, we found that the embeddings derived even
514 from much larger and more modern models like BERT [15], GPT [61], LLaMa [58], and others that
515 are trained on enormous text corpora, end up yielding poor resolution within the content space
516 spanned by individual course videos (Supp. Fig. 6). Whereas the LDA embeddings of the lectures
517 and questions are “near” each other (i.e., the convex hull enclosing the two lectures’ trajectories is
518 highly overlapping with the convex hull enclosing the questions’ embeddings), the BERT embed-
519 dings of the lectures and questions are instead largely distinct (top row of Supp. Fig. 6). The LDA
520 embeddings of the questions for each lecture and the corresponding lecture’s trajectory are also
521 similar. For example, as shown in Fig. 2C, the LDA embeddings for *Four Fundamental Forces* ques-
522 tions (blue dots) appear closer to the *Four Fundamental Forces* lecture trajectory (blue line), whereas
523 the LDA embeddings for *Birth of Stars* questions (green dots) appear closer to the *Birth of Stars*
524 lecture trajectory (green line). The BERT embeddings of the lectures and questions do not show
525 this property (Supp. Fig. 6). We also examined per-question “content matches” between individual
526 questions and individual moments of each lecture (Figs. 4, 6). The time series plot of individual
527 questions’ correlations are different from each other when computed using LDA (e.g., the traces
528 can be clearly visually separated), whereas the correlations computed from BERT embeddings of
529 different questions all look very similar. This tells us that LDA is capturing some differences in

content between the questions, whereas BERT is not. The time series plots of individual questions' correlations have clear "peaks" when computed using LDA, but not when computed using BERT. This tells us that LDA is capturing a "match" between the content of each question and a relatively well-defined time window of the corresponding lectures. The BERT embeddings appear to blur together the content of the questions versus specific moments of each lecture. Finally, we also compared the pairwise correlations between embeddings of questions within versus across content areas (i.e., content covered by the individual lectures, lecture-specific questions, and by the "general physics knowledge" questions). The LDA embeddings show a strong contrast between same-content embeddings versus across-content embeddings. In other words, the embeddings of questions about the *Four Fundamental Forces* material are highly correlated with the embeddings of the *Four Fundamental Forces* lecture, but not with the embeddings of *Birth of Stars*, questions about *Birth of Stars*, or general physics knowledge questions. We see a similar pattern with the LDA embeddings of the *Birth of Stars* questions (Fig. 3, Supp. Fig. 2). In contrast, the BERT embeddings are all highly correlated with each other (Supp. Fig. 6). Taken together, these comparisons illustrate how LDA (trained on the specific content in question) provides both coverage of the requisite material and specificity at the level of the content covered by individual questions. BERT, on the other hand, essentially assigns both lectures and all of the questions (which are all broadly about "physics") into a tiny region of its embedding space, thereby blurring out meaningful distinctions between different specific concepts covered by the lectures and questions. We note that these are not criticisms of BERT (or other large language models trained on large and diverse corpora). Rather, our point is that simple fine-tuned models trained on a relatively small but specialized corpus can outperform much more complicated models trained on much larger corpora, when we are specifically interested in capturing subtle conceptual differences at the level of a single course lecture or question. Of course if our goal had been to find a model that generalized to many different content areas, we would expect our approach to perform comparatively poorly relative to BERT or other much larger models. We suggest that bridging the tradeoff between high resolution within each content area versus the ability to generalize to many different content areas will be an important challenge for future work in this domain.

558 Another application for large language models that does *not* require explicitly modeling the
559 content of individual lectures or questions is to leverage the models' abilities to generate text. For
560 example, generative text models like ChatGPT [47] and LLaMa [58] are already being used to build
561 a new generation of interactive tutoring systems [e.g., 38]. Unlike the approach we have taken here,
562 these generative text model-based systems do not explicitly model what learners know, or how
563 their knowledge changes over time with training. One could imagine building a hybrid system
564 that combines the best of both worlds: a large language model that can *generate* text, combined
565 with a smaller model that can *infer* what learners know and how their knowledge changes over
566 time. Such a hybrid system could potentially be used to build the next generation of interactive
567 tutoring systems that are able to adapt to learners' needs in real time, and that are able to provide
568 more nuanced feedback about what learners know and what they do not know.

569 At the opposite end of the spectrum from large language models, one could also imagine
570 *simplifying* some aspects of our LDA-based approach by computing simple word overlap metrics.
571 For example, the Jaccard similarity between text A and B is computed as the number of unique
572 words in the intersection of words from A and B divided by the number of unique words in the
573 union of words from A and B . In a supplementary analysis (Supp. Fig. 5), we compared the
574 LDA-based question-lecture matches we reported in Figure 4 with the Jaccard similarities between
575 each question and each sliding window of text from the corresponding lecture. As shown in
576 Supplementary Figure 5, this simple word-matching approach does not appear to capture the same
577 level of specificity as the LDA-based approach. Whereas the LDA-based approach often yields a
578 clear peak in the time series of correlations between each question and the corresponding lecture,
579 the Jaccard similarity-based approach does not. Furthermore, these LDA-based matches appear
580 to capture conceptual overlaps between the questions and lectures (Supp. Tab. 3), whereas simple
581 word matching does not. For example, one of the example questions examined in Supplementary
582 Figure 5 asks "Which of the following occurs as a cloud of atoms gets more dense?" The LDA-based
583 matches identify lecture timepoints where the relevant *topics* are discussed (e.g., when words like
584 "cloud," "atom," "dense," etc., are mentioned *together*). The Jaccard similarity-based matches,
585 on the other hand, are strong when *any* of these words are mentioned, even if they do not occur

586 together.

587 We view our approach as occupying a sort of “sweet spot,” between much larger language
588 models and simple word matching-based approaches, that enables us to capture the relevant
589 conceptual content of course materials at an appropriate semantic scale. Our approach enables us
590 to accurately and consistently identify each question’s content in a way that also matches up with
591 what is presented in the lectures. In turn, this enables us to construct accurate predictions about
592 participants’ knowledge of the conceptual content tested by held-out questions (Fig. 6).

593 One limitation of our approach is that topic models contain no explicit internal representations
594 of more complex aspects of “knowledge,” like knowledge graphs, dependencies or associations
595 between concepts, causality, and so on. These representations might (in principle) be added
596 as extensions to our approach to more accurately and precisely capture, characterize, and track
597 learners’ knowledge. However, modeling these aspects of knowledge will likely require substantial
598 additional research effort.

599 Within the past several years, the global pandemic forced many educators to suddenly adapt to
600 teaching remotely [30, 44, 55, 62]. This change in world circumstances is happening alongside (and
601 perhaps accelerating) geometric growth in the availability of high-quality online courses from plat-
602 forms such as Khan Academy [31], Coursera [63], EdX [33], and others [52]. Continued expansion
603 of the global internet backbone and improvements in computing hardware have also facilitated
604 improvements in video streaming, enabling videos to be easily shared and viewed by increasingly
605 large segments of the world’s population. This exciting time for online course instruction provides
606 an opportunity to re-evaluate how we, as a global community, educate ourselves and each other.
607 For example, we can ask: what defines an effective course or training program? Which aspects of
608 teaching might be optimized and/or augmented by automated tools? How and why do learning
609 needs and goals vary across people? How might we lower barriers to receiving a high-quality
610 education?

611 Alongside these questions, there is a growing desire to extend existing theories beyond the
612 domain of lab testing rooms and into real classrooms [29]. In part, this has led to a recent
613 resurgence of “naturalistic” or “observational” experimental paradigms that attempt to better

reflect more ethologically valid phenomena that are more directly relevant to real-world situations and behaviors [45]. In turn, this has brought new challenges in data analysis and interpretation. A key step towards solving these challenges will be to build explicit models of real-world scenarios and how people behave in them (e.g., models of how people learn conceptual content from real-world courses, as in our current study). A second key step will be to understand which sorts of signals derived from behaviors and/or other measurements [e.g., neurophysiological data; 2, 16, 42, 46, 49] might help to inform these models. A third major step will be to develop and employ reliable ways of evaluating the complex models and data that are a hallmark of naturalistic paradigms.

Beyond specifically predicting what people *know*, the fundamental ideas we develop here also relate to the notion of “theory of mind” of other individuals [22, 27, 41]. Considering others’ unique perspectives, prior experiences, knowledge, goals, etc., can help us to more effectively interact and communicate [50, 54, 57]. One could imagine future extensions of our work (e.g., analogous to the knowledge and learning maps shown in Fig. 8), that attempt to characterize how well-aligned different people’s knowledge bases or backgrounds are. In turn, this might be used to model how knowledge (or other forms of communicable information) flows not just between teachers and students, but between friends having a conversation, individuals on a first date, participants at a business meeting, doctors and patients, experts and non-experts, political allies or adversaries, and more. For example, the extent to which two people’s knowledge maps “match” or “align” in a given region of text embedding space might serve as a predictor of how effectively they will be able to communicate about the corresponding conceptual content.

Ultimately, our work suggests a rich new line of questions about the geometric “form” of knowledge, how knowledge changes over time, and how we might map out the full space of what an individual knows. Our finding that detailed estimates about knowledge may be obtained from short quizzes shows one way that traditional approaches to evaluation in education may be extended. We hope that these advances might help pave the way for new approaches to teaching or delivering educational content that are tailored to individual students’ learning needs and goals.

641 **Materials and methods**

642 **Participants**

643 We enrolled a total of 50 Dartmouth undergraduate students in our study. Participants received
644 optional course credit for enrolling. We asked each participant to complete a demographic survey
645 that included questions about their age, gender, native spoken language, ethnicity, race, hearing,
646 color vision, sleep, coffee consumption, level of alertness, and several aspects of their educational
647 background and prior coursework.

648 Participants' ages ranged from 18 to 22 years (mean: 19.52 years; standard deviation: 1.09
649 years). A total of 15 participants reported their gender as male and 35 participants reported their
650 gender as female. A total of 49 participants reported their native language as "English" and 1
651 reported having another native language. A total of 47 participants reported their ethnicity as
652 "Not Hispanic or Latino" and three reported their ethnicity as "Hispanic or Latino." Participants
653 reported their races as White (32 participants), Asian (14 participants), Black or African American
654 (5 participants), American Indian or Alaska Native (1 participant), and Native Hawaiian or Other
655 Pacific Islander (1 participant). (Note that some participants selected multiple racial categories.)

656 A total of 49 participants reporting having normal hearing and 1 participant reported having
657 some hearing impairment. A total of 49 participants reported having normal color vision and 1
658 participant reported being color blind. Participants reported having had, on the night prior to
659 testing, 2–4 hours of sleep (1 participant), 4–6 hours of sleep (9 participants), 6–8 hours of sleep (35
660 participants), or 8+ hours of sleep (5 participants). They reported having consumed, on the same
661 day and leading up to their testing session, 0 cups of coffee (38 participants), 1 cup of coffee (10
662 participants), 3 cups of coffee (1 participant), or 4+ cups of coffee (1 participant).

663 No participants reported that their focus was currently impaired (e.g., by drugs or alcohol).
664 Participants reported their current level of alertness, and we converted their responses to numerical
665 scores as follows: "very sluggish" (-2), "a little sluggish" (-1), "neutral" (0), "fairly alert" (1), and
666 "very alert" (2). Across all participants, a range of alertness levels were reported (range: -2–1;
667 mean: -0.10; standard deviation: 0.84).

Participants reported their undergraduate major(s) as “social sciences” (28 participants), “natural sciences” (16 participants), “professional” (e.g., pre-med or pre-law; 8 participants), “mathematics and engineering” (7 participants), “humanities” (4 participants), or “undecided” (3 participants). Note that some participants selected multiple categories for their undergraduate major(s). We also asked participants about the courses they had taken. In total, 45 participants reported having taken at least one Khan Academy course in the past, and 5 reported not having taken any Khan Academy courses. Of those who reported having watched at least one Khan Academy course, 7 participants reported having watched 1–2 courses, 11 reported having watched 3–5 courses, 8 reported having watched 5–10 courses, and 19 reported having watched 10 or more courses. We also asked participants about the specific courses they had watched, categorized under different subject areas. In the “Mathematics” area, participants reported having watched videos on AP Calculus AB (21 participants), Precalculus (17 participants), Algebra 2 (14 participants), AP Calculus BC (12 participants), Trigonometry (11 participants), Algebra 1 (10 participants), Geometry (8 participants), Pre-algebra (7 participants), Multivariable Calculus (5 participants), Differential Equations (5 participants), Statistics and Probability (4 participants), AP Statistics (2 participants), Linear Algebra (2 participants), Early Math (1 participant), Arithmetic (1 participant), and other videos not listed in our survey (5 participants). In the “Science and engineering” area, participants reported having watched videos on Chemistry, AP Chemistry, or Organic Chemistry (21 participants); Physics, AP Physics I, or AP Physics II (18 participants); Biology, AP Biology; or High school Biology (15 participants); Health and Medicine (1 participant); or other videos not listed in our survey (5 participants). We also asked participants whether they had specifically seen the videos used in our experiment. Of the 45 participants who reported having having taken at least one Khan Academy course in the past, 44 participants reported that they had not watched the *Four Fundamental Forces* video, and 1 participant reported that they were not sure whether they had watched it. All participants reported that they had not watched the *Birth of Stars* video. When we asked participants about non-Khan Academy online courses, they reported having watched or taken courses on Mathematics (15 participants), Science and engineering (11 participants), Test preparation (9 participants), Economics and finance (3 participants), Arts and humanities (2 participants).

696 ipants), Computing (2 participants), and other categories not listed in our survey (17 participants).
697 Finally, we asked participants about in-person courses they had taken in different subject areas.
698 They reported taking courses in Mathematics (38 participants), Science and engineering (37 par-
699 ticipants), Arts and humanities (34 participants), Test preparation (27 participants), Economics
700 and finance (26 participants), Computing (14 participants), College and careers (7 participants), or
701 other courses not listed in our survey (6 participants).

702 Experiment

703 We hand-selected two course videos from the Khan Academy platform: *Four Fundamental Forces*
704 (an introduction to gravity, electromagnetism, the weak nuclear force, and the strong nuclear force;
705 duration: 10 minutes and 29 seconds) and *Birth of Stars* (an introduction to how stars are formed;
706 duration: 7 minutes and 57 seconds). All participants viewed the videos in the same order (i.e.,
707 *Four Fundamental Forces* followed by *Birth of Stars*).

708 We then hand-created 39 multiple-choice questions: 15 about the conceptual content of *Four*
709 *Fundamental Forces* (i.e., Lecture 1), 15 about the conceptual content of *Birth of Stars* (i.e., Lecture 2),
710 and 9 questions that tested for general conceptual knowledge about basic physics (covering material
711 that was not presented in either video). To help broaden the set of lecture-specific questions,
712 our team worked through each lecture in small segments to identify what each segment was
713 “about” conceptually, and then write a question about that concept. The general physics questions
714 were drawn our team’s prior coursework and areas of interest, along with internet searches and
715 brainstorming with the project team and other members of J.R.M.’s lab. Although we attempted to
716 design the questions to test “conceptual knowledge,” we note that estimating the specific “amount”
717 of conceptual understanding that each question “requires” to answer is somewhat subjective, and
718 might even come down to the “strategy” a given participant uses to answer the question at that
719 particular moment. The full set of questions and answer choices may be found in Supplementary
720 Table 1. The final set of questions (and response options) was reviewed and approved by J.R.M.
721 before we collected or analyzed the text or experimental data.

722 Over the course of the experiment, participants completed three 13-question multiple-choice

723 quizzes: the first before viewing Lecture 1, the second between Lectures 1 and 2, and the third
724 after viewing Lecture 2 (see Fig. 1). The questions appearing on each quiz, for each participant,
725 were randomly chosen from the full set of 39, with the constraints that (a) each quiz contained
726 exactly 5 questions about Lecture 1, 5 questions about Lecture 2, and 3 questions about general
727 physics knowledge, and (b) each question appear exactly once for each participant. The orders of
728 questions on each quiz, and the orders of answer options for each question, were also randomized.
729 We obtained informed consent from all participants, and our experimental protocol was approved
730 by the Committee for the Protection of Human Subjects at Dartmouth College. We used this
731 experiment to develop and test our computational framework for estimating knowledge and
732 learning.

733 **Analysis**

734 **Statistics**

735 All of the statistical tests performed in our study were two-sided. The 95% confidence intervals
736 we reported for each correlation were estimated by generating 10,000 bootstrap distributions of
737 correlation coefficients by sampling (with replacement) from the observed data.

738 **Constructing text embeddings of multiple lectures and questions**

739 We adapted an approach we developed in prior work [24] to embed each moment of the two
740 lectures and each question in our pool in a common representational space. Briefly, our approach
741 uses a topic model [Latent Dirichlet Allocation; 6] trained on a set of documents, to discover a set
742 of k “topics” or “themes.” Formally, each topic is defined as a distribution of weights over words
743 in the model’s vocabulary (i.e., the union of all unique words, across all documents, excluding
744 “stop words.”). Conceptually, each topic is intended to give larger weights to words that are
745 semantically related (as inferred from their tendency to co-occur in the same document). After
746 fitting a topic model, each document in the training set, or any *new* document that contains at
747 least some of the words in the model’s vocabulary, may be represented as a k -dimensional vector

748 describing how much the document (most probably) reflects each topic. To select an appropriate
749 k for our model, as a starting point, we identified the minimum number of topics that yielded
750 at least one “unused” topic (i.e., in which all words in the vocabulary were assigned uniform
751 weights) after training. This indicated that the number of topics was sufficient to capture the set
752 of latent themes present in the two lectures (from which we constructed our document corpus, as
753 described below). We found this value to be $k = 15$ topics. We found that with a limited number
754 of additional adjustments following [7], such as removing corpus-specific stop-words, the model
755 yielded (subjectively) sensible and coherent topics. The distribution of weights over words in
756 the vocabulary for each discovered topic is shown in Supplementary Figure 1, and each topic’s
757 top-weighted words may be found in Supplementary Table 2.

758 As illustrated in Figure 2A, we start by building up a corpus of documents using overlapping
759 sliding windows that span each video’s transcript. Khan Academy provides professionally created,
760 manual transcriptions of all videos for closed captioning. However, such transcripts would not
761 be readily available in all contexts to which our framework could potentially be applied. Khan
762 Academy videos are hosted on the YouTube platform, which additionally provides automated
763 captions. We opted to use these automated transcripts [which, in prior work, we have found to be
764 of sufficiently near-human quality to yield reliable data in behavioral studies; 64] when developing
765 our framework in order to make it more directly extensible and adaptable by others in the future.

766 We fetched these automated transcripts using the `youtube-transcript-api` Python pack-
767 age [14]. The transcripts consisted of one timestamped line of text for every few seconds (mean:
768 2.34 s; standard deviation: 0.83 s) of spoken content in the video (i.e., corresponding to each indi-
769 vidual caption that would appear on-screen if viewing the lecture via YouTube, and when those
770 lines would appear). We defined a sliding window length of (up to) $w = 30$ transcript lines, and
771 assigned each window a timestamp corresponding to the midpoint between the timestamps for its
772 first and last lines. This w parameter was chosen to match the same number of words per sliding
773 window (rounded to the nearest whole word, and before preprocessing) as the sliding windows
774 we defined in our prior work [24] (i.e., 185 words per sliding window).

775 These sliding windows ramped up and down in length at the beginning and end of each

776 transcript, respectively. In other words, each transcript’s first sliding window covered only its first
777 line, the second sliding window covered the first two lines, and so on. This ensured that each line
778 from the transcripts appeared in the same number (w) of sliding windows. We next performed a
779 series of standard text preprocessing steps: normalizing case, lemmatizing, removing punctuation
780 and removing stop-words. We constructed our corpus of stop words by augmenting the Natural
781 Language Toolkit [NLTK; 3] English stop word list with the following additional words, selected
782 using one of the approaches suggested by [7]: “actual,” “actually,” “also,” “bit,” “could,” “e,”
783 “even,” “first,” “follow,” “following,” “four,” “let,” “like,” “mc,” “really,” “saw,” “see,” “seen,”
784 “thing,” and “two.” This yielded sliding windows with an average of 73.8 remaining words, and
785 lasting for an average of 62.22 seconds. We treated the text from each sliding window as a single
786 “document,” and combined these documents across the two videos’ windows to create a single
787 training corpus for the topic model.

788 After fitting a topic model to the two videos’ transcripts, we could use the trained model to
789 transform arbitrary (potentially new) documents into k -dimensional topic vectors. A convenient
790 property of these topic vectors is that documents that reflect similar blends of topics (i.e., documents
791 that reflect similar themes, according to the model) will yield similar coordinates (in terms of
792 correlation, cosine similarity, Kullback-Leibler divergence, Euclidean distance, or other geometric
793 measures). In general, the similarity between different documents’ topic vectors may be used to
794 characterize the similarity in conceptual content between the documents.

795 We transformed each sliding window’s text into a topic vector, and then used linear interpolation
796 (independently for each topic dimension) to resample the resulting time series to one vector
797 per second. We also used the fitted model to obtain topic vectors for each question in our pool (see
798 Supp. Tab. 1). Taken together, we obtained a *trajectory* for each video, describing its path through
799 topic space, and a single coordinate for each question (Fig. 2C). Embedding both videos and all of
800 the questions using a common model enables us to compare the content from different moments
801 of videos, compare the content across videos, and estimate potential associations between specific
802 questions and specific moments of video.

803 **Estimating dynamic knowledge traces**

804 We used the following equation to estimate each participant's knowledge about timepoint t of a
805 given lecture, $\hat{k}(t)$:

$$\hat{k}(f(t, L)) = \frac{\sum_{i \in \text{correct}} \text{ncorr}(f(t, L), f(i, Q))}{\sum_{j=1}^N \text{ncorr}(f(t, L), f(j, Q))}, \quad (1)$$

806 where

$$\text{ncorr}(x, y) = \frac{\text{corr}(x, y) - \text{mincorr}}{\text{maxcorr} - \text{mincorr}}, \quad (2)$$

807 and where mincorr and maxcorr are the minimum and maximum correlations between any lecture
808 timepoint and question, taken over all timepoints in the given lecture, and all five questions *about*
809 that lecture appearing on the given quiz. We also define $f(s, \Omega)$ as the s^{th} topic vector from the set
810 of topic vectors Ω . Here t indexes the set of lecture topic vectors, L , and i and j index the topic
811 vectors of questions used to estimate the knowledge trace, Q . Note that "correct" denotes the set
812 of indices of the questions the participant answered correctly on the given quiz.

813 Intuitively, $\text{ncorr}(x, y)$ is the correlation between two topic vectors (e.g., the topic vector from one
814 timepoint in a lecture, x , and the topic vector for one question, y), normalized by the minimum and
815 maximum correlations (across all timepoints t and questions Q) to range between 0 and 1, inclusive.
816 Equation 1 then computes the weighted average proportion of correctly answered questions about
817 the content presented at timepoint t , where the weights are given by the normalized correlations
818 between timepoint t 's topic vector and the topic vectors for each question. The normalization step
819 (i.e., using ncorr instead of the raw correlations) ensures that every question contributes some
820 non-negative amount to the knowledge estimate.

821 **GLMM METHODS SECTION PLACEHOLDER**

822 **Estimating the "smoothness" of knowledge**

823 In the analysis reported in Figure 7A, we show how participants' ability to correctly answer
824 quiz questions changes as a function of distance from a given correctly or incorrectly answered

825 reference question. We used a bootstrap-based approach to estimate the maximum distances over
826 which these proportions of correctly answered questions could be reliably distinguished from
827 participants' overall average proportion of correctly answered questions.

828 For each of 10,000 iterations, we drew a random subsample (with replacement) of 50 partic-
829 ipants from our dataset. Within each iteration, we first computed the 95% confidence interval
830 (CI) of the across-subsample-participants mean proportion correct on each of the three quizzes,
831 separately. To compute this interval for each quiz, we repeatedly (1,000 times) subsampled par-
832 ticipants (with replacement, from the outer subsample for the current iteration) and computed
833 the mean proportion correct of each of these inner subsamples. We then identified the 2.5th and
834 97.5th percentiles of the resulting distributions of 1,000 means. These three intervals (one for each
835 quiz) served as our thresholds for confidence that the proportion correct within a given distance
836 from a reference question was reliably different (at the $p < 0.05$ significance level) from the average
837 proportion correct across all questions on the given quiz.

838 Next, for each participant in the current subsample, and for each of the three quizzes they
839 completed (separately), we iteratively treated each of the 15 questions appearing on the given
840 quiz as the "reference" question. We constructed a series of concentric 15-dimensional "spheres"
841 centered on the reference question's embedding space coordinate, where each successive sphere's
842 radius increased by 0.01 (correlation distance) between 0 and 2, inclusive (i.e., tiling the range
843 of possible correlation distances with 201 spheres in total). We then computed the proportion
844 of questions enclosed within each sphere that the participant answered correctly, and averaged
845 these per-radius proportion correct scores across reference questions that were answered correctly,
846 and those that were answered incorrectly. This resulted in two number-of-spheres sequences of
847 proportion-correct scores for each subsample participant and quiz: one derived from correctly
848 answered reference questions, and one derived from incorrectly answered reference questions.

849 We computed the across-subsample-participants mean proportion correct for each radius value
850 (i.e., sphere) and "correctness" of reference question. This yielded two sequences of proportion-
851 correct scores for each quiz, analogous to the blue and red lines displayed in Figure 7A, but for
852 the present subsample. For each quiz, we then found the minimum distance from the reference

853 question (i.e., sphere radius) at which each of these two sequences of per-radius proportion correct
854 scores intersected the 95% confidence interval for the overall proportion correct (i.e., analogous to
855 the black error bands in Fig. 7A).

856 This resulted in two “intersection” distances for each quiz (for correctly answered and incor-
857 rectly answered reference questions). Repeating this full process for each of the 10,000 bootstrap
858 iterations output two distributions of intersection distances for each of the three quizzes. The
859 means and 95% confidence intervals for these distributions are plotted in Figure 7B.

860 **Creating knowledge and learning map visualizations**

861 An important feature of our approach is that, given a trained text embedding model and partic-
862 ipants’ quiz performance on each question, we can estimate their knowledge about *any* content
863 expressible by the embedding model—not solely the content explicitly probed by the quiz ques-
864 tions, or even appearing in the lectures. To visualize these estimates (Fig. 8, Supp. Figs. 7, 8, 9, 10,
865 and 11), we used Uniform Manifold Approximation and Projection [UMAP; 39, 40] to construct a
866 2D projection of the text embedding space. Whereas our main analyses used a 15-topic embedding
867 space, we used a 100-topic embedding space for these visualizations. This change in the number
868 of topics overcame an undesirable behavior in the UMAP embedding procedure, whereby embed-
869 ding coordinates for the 15-topic model tended to be “clumped” into separated clusters, rather
870 than forming a smooth trajectory through the 2D space. When we increased the number of topics
871 to 100, the embedding coordinates in the 2D space formed a smooth trajectory through the space,
872 with substantially less clumping (Fig. 8). Creating a “map” by sampling this 100-dimensional
873 space at high resolution to obtain an adequate set of topic vectors spanning the embedding space
874 would be computationally intractable. However, sampling a 2D grid is trivial.

875 At a high level, the UMAP algorithm obtains low-dimensional embeddings by minimizing
876 the cross-entropy between the pairwise (clustered) distances between the observations in their
877 original (e.g., 100-dimensional) space and the pairwise (clustered) distances in the low-dimensional
878 embedding space (in our approach, the embedding space is 2D). In our implementation, pairwise
879 distances in the original high-dimensional space were defined as 1 minus the correlation between

880 each pair of coordinates, and pairwise distances in the low-dimensional embedding space were
881 defined as the Euclidean distance between each pair of coordinates.

882 In our application, all of the coordinates we embedded were topic vectors, whose elements
883 are always non-negative and sum to one. Although UMAP is an invertible transformation at
884 the embedding locations of the original data, other locations in the embedding space will not
885 necessarily follow the same implicit “rules” as the original high-dimensional data. For example,
886 inverting an arbitrary coordinate in the embedding space might result in negative-valued vectors,
887 which are incompatible with the topic modeling framework. To protect against this issue, we
888 log-transformed the topic vectors prior to embedding them in the 2D space. When we inverted
889 the embedded vectors (e.g., to estimate topic vectors or word clouds, as in Fig. 8C), we passed
890 the inverted (log-transformed) values through the exponential function to obtain a vector of non-
891 negative values, and normalized them to sum to one.

892 After embedding both lectures’ topic trajectories and the topic vectors of every question, we
893 defined a rectangle enclosing the 2D projections of the lectures’ and quizzes’ embeddings. We then
894 sampled points from a regular 100×100 grid of coordinates that evenly tiled this enclosing rectangle.
895 We sought to estimate participants’ knowledge (and learning, i.e., changes in knowledge) at each
896 of the resulting 10,000 coordinates.

897 To generate our estimates, we placed a set of 39 radial basis functions (RBFs) throughout the
898 embedding space, centered on the 2D projections for each question (i.e., we included one RBF for
899 each question). At coordinate x , the value of an RBF centered on a question’s coordinate μ , is given
900 by:

$$\text{RBF}(x, \mu, \lambda) = \exp \left\{ -\frac{\|x - \mu\|^2}{\lambda} \right\}. \quad (3)$$

901 The λ term in the RBF equation controls the “smoothness” of the function, where larger values
902 of λ result in smoother maps. In our implementation we used $\lambda = 50$. Next, we estimated the
903 “knowledge” at each coordinate, x , using:

$$\hat{k}(x) = \frac{\sum_{i \in \text{correct}} \text{RBF}(x, q_i, \lambda)}{\sum_{j=1}^N \text{RBF}(x, q_j, \lambda)}. \quad (4)$$

904 Intuitively, Equation 4 computes the weighted proportion of correctly answered questions, where
905 the weights are given by how nearby (in the 2D space) each question is to the x . We also defined
906 *learning maps* as the coordinate-by-coordinate differences between any pair of knowledge maps.
907 Intuitively, learning maps reflect the *change* in knowledge across two maps.

908 Author contributions

909 Conceptualization: P.C.F., A.C.H., and J.R.M. Methodology: P.C.F., A.C.H., and J.R.M. Software:
910 P.C.F. Validation: P.C.F. Formal analysis: P.C.F. Resources: P.C.F., A.C.H., and J.R.M. Data curation:
911 P.C.F. Writing (original draft): J.R.M. Writing (review and editing): P.C.F., A.C.H., and J.R.M. Visu-
912 alization: P.C.F. and J.R.M. Supervision: J.R.M. Project administration: P.C.F. Funding acquisition:
913 J.R.M.

914 Data availability

915 All of the data analyzed in this manuscript may be found at <https://github.com/ContextLab/efficient-learning-khan>.
916

917 Code availability

918 All of the code for running our experiment and carrying out the analyses may be found at
919 <https://github.com/ContextLab/efficient-learning-khan>.

920 Acknowledgements

921 We acknowledge useful discussions, assistance in setting up an earlier (unpublished) version of
922 this study, and assistance with data collection efforts from Will Baxley, Max Bluestone, Daniel
923 Carstensen, Kunal Jha, Caroline Lee, Lucy Owen, Xinming Xu, and Kirsten Ziman. Our work was

924 supported in part by NSF CAREER Award Number 2145172 to J.R.M. The content is solely the
925 responsibility of the authors and does not necessarily represent the official views of our supporting
926 organizations. The funders had no role in study design, data collection and analysis, decision to
927 publish, or preparation of the manuscript.

928 **References**

- 929 [1] Ashby, F. G. and Maddox, W. T. (2005). Human category learning. *Annual Review of Psychology*,
930 56:149–178.
- 931 [2] Bevilacqua, D., Davidesco, I., Wan, L., and Chaloner, K. (2019). Brain-to-brain synchrony and
932 learning outcomes vary by student-teacher dynamics: evidence from a real-world classroom
933 electroencephalography study. *Journal of Cognitive Neuroscience*, 31(3):401–411.
- 934 [3] Bird, S., Klein, E., and Loper, E. (2009). *Nature language processing with Python: analyzing text
935 with the natural language toolkit*. Reilly Media, Inc.
- 936 [4] Blaye, A., Bernard-Peyron, V., Paour, J.-L., and Bonthoux, F. (2006). Category flexibility in chil-
937 dren: distinguishing response flexibility from conceptual flexibility; the protracted development
938 of taxonomic representations. *European Journal of Developmental Psychology*, 3(2):163–188.
- 939 [5] Blei, D. M. and Lafferty, J. D. (2006). Dynamic topic models. In *Proceedings of the International
940 Conference on Machine Learning*, pages 113–120, New York, NY. Association for Computing
941 Machinery.
- 942 [6] Blei, D. M., Ng, A. Y., and Jordan, M. I. (2003). Latent dirichlet allocation. *Journal of Machine
943 Learning Research*, 3:993–1022.
- 944 [7] Boyd-Graber, J., Mimno, D., and Newman, D. (2014). Care and feeding of topic models:
945 problems, diagnostics, and improvements. In Airolidi, E. M., Blei, D. M., Erosheva, E. A., and
946 Fienberg, S. E., editors, *Handbook of Mixed Membership Models and Their Applications*. CRC Press.

- 947 [8] Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A.,
948 Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child,
949 R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., Litwin, M.,
950 Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., and Amodei,
951 D. (2020). Language models are few-shot learners. *arXiv*, 2005.14165.
- 952 [9] Caramazza, A. and Mahon, B. Z. (2003). The organization of conceptual knowledge: the
953 evidence from category-specific semantic deficits. *Trends in Cognitive Sciences*, 7(8):354–361.
- 954 [10] Cer, D., Yang, Y., Kong, S. Y., Hua, N., Limtiaco, N., John, R. S., Constant, N., Guajardo-
955 Cespedes, M., Yuan, S., Tar, C., Sung, Y.-H., Strope, B., and Kurzweil, R. (2018). Universal
956 sentence encoder. *arXiv*, 1803.11175.
- 957 [11] Constantinescu, A. O., O'Reilly, J. X., and Behrens, T. E. J. (2016). Organizing conceptual
958 knowledge in humans with a gridlike code. *Science*, 352(6292):1464–1468.
- 959 [12] Deacon, D., Grose-Fifer, J., Yang, C. M., Stanick, V., Hewitt, S., and Dynowska, A. (2004).
960 Evidence for a new conceptualization of semantic representation in the left and right cerebral
961 hemispheres. *Cortex*, 40(3):467–478.
- 962 [13] Deerwester, S., Dumais, S. T., Furnas, G. W., Landauer, T. K., and Harshman, R. (1990).
963 Indexing by latent semantic analysis. *Journal of the American Society for Information Science*,
964 41(6):391–407.
- 965 [14] Depoix, J. (2018). YouTube transcript API. <https://github.com/jdepoix/youtube-transcript-api>.
- 966
- 967 [15] Devlin, J., Chang, M.-W., Lee, K., and Toutanova, K. (2018). BERT: pre-training of deep
968 bidirectional transformers for language understanding. *arXiv*, 1810.04805.
- 969 [16] Dikker, S., Wan, L., Davidesco, I., Kaggen, L., Oostrik, M., McClintock, J., Rowland, J.,
970 Michalareas, G., van Bavel, J. J., Ding, M., and Poeppel, D. (2017). Brain-to-brain synchrony
971 tracks real-world dynamic group interactions in the classroom. *Current Biology*, 27(9):1375–1380.

- 972 [17] Estes, W. K. (1986a). Array models for category learning. *Cognitive Psychology*, 18(4):500–549.
- 973 [18] Estes, W. K. (1986b). Memory storage and retrieval processes in category learning. *Journal of*
974 *Experimental Psychology: General*, 115:155–174.
- 975 [19] Fisher, R. A. (1922). On the mathematical foundations of theoretical statistics. *Philosophical*
976 *Transactions of the Royal Society A*, 222(602):309–368.
- 977 [20] Gallagher, J. J. (2000). Teaching for understanding and application of science knowledge.
978 *School Science and Mathematics*, 100(6):310–318.
- 979 [21] Gluck, M. A., Shohamy, D., and Myers, C. E. (2002). How do people solve the “weather
980 prediction” task? individual variability in strategies for probabilistic category learning. *Learning*
981 *and Memory*, 9:408–418.
- 982 [22] Goldstein, T. R. and Winner, E. (2012). Enhancing empathy and theory of mind. *Journal of*
983 *Cognition and Development*, 13(1):19–37.
- 984 [23] Hall, R. and Greeno, J. (2008). *21st century education: A reference handbook*, chapter Conceptual
985 learning, pages 212–221. Sage Publications.
- 986 [24] Heusser, A. C., Fitzpatrick, P. C., and Manning, J. R. (2021). Geometric models reveal behav-
987 ioral and neural signatures of transforming experiences into memories. *Nature Human Behaviour*,
988 5:905–919.
- 989 [25] Huebner, P. A. and Willits, J. A. (2018). Structured semantic knowledge can emerge au-
990 tomatically from predicting word sequences in child-directed speech. *Frontiers in Psychology*,
991 9:doi.org/10.3389/fpsyg.2018.00133.
- 992 [26] Hulbert, J. C. and Norman, K. A. (2015). Neural differentiation tracks improved recall of com-
993 peting memories following interleaved study and retrieval practice. *Cerebral Cortex*, 25(10):3994–
994 4008.
- 995 [27] Kanske, P., Böckler, A., and Singer, T. (2015). Models, mechanisms and moderators dissociating
996 empathy and theory of mind. In *Social Behavior From Rodents to Humans*, pages 193–206. Springer.

- 997 [28] Katona, G. (1940). *Organizing and memorizing: studies in the psychology of learning and teaching*.
998 Columbia University Press.
- 999 [29] Kaufman, D. M. (2003). Applying educational theory in practice. *British Medical Journal*,
1000 326(7382):213–216.
- 1001 [30] Kawasaki, H., Yamasaki, S., Masuoka, Y., Iwasa, M., Fukita, S., and Matsuyama, R. (2021).
1002 Remote teaching due to COVID-19: an exploration of its effectiveness and issues. *International
1003 Journal of Environmental Research and Public Health*, 18(5):2672.
- 1004 [31] Khan, S. (2004). *The Khan Academy*. Salman Khan.
- 1005 [32] Kintsch (1970). *Learning, memory, and conceptual processes*. Wiley.
- 1006 [33] Kolowich, S. (2013). How EdX plans to earn, and share, revenue from its free online courses.
1007 *The Chronicle of Higher Education*, 21:1–5.
- 1008 [34] Landauer, T. K. and Dumais, S. T. (1997). A solution to Plato’s problem: the latent semantic
1009 analysis theory of acquisition, induction, and representation of knowledge. *Psychological Review*,
1010 104:211–240.
- 1011 [35] Lee, H. and Chen, J. (2022). Predicting memory from the network structure of naturalistic
1012 events. *Nature Communications*, 13(4235):doi.org/10.1038/s41467-022-31965-2.
- 1013 [36] Maclellan, E. (2005). Conceptual learning: the priority for higher education. *British Journal of
1014 Educational Studies*, 53(2):129–147.
- 1015 [37] Manning, J. R. (2021). Episodic memory: mental time travel or a quantum “memory wave”
1016 function? *Psychological Review*, 128(4):711–725.
- 1017 [38] Manning, J. R., Menjunatha, H., and Kording, K. (2023). Chatify: A Jupyter extension
1018 for adding LLM-driven chatbots to interactive notebooks. [https://github.com/ContextLab/
1019 chatify](https://github.com/ContextLab/chatify).

- 1020 [39] McInnes, L., Healy, J., and Melville, J. (2018a). UMAP: Uniform manifold approximation and
1021 projection for dimension reduction. *arXiv*, 1802(03426).
- 1022 [40] McInnes, L., Healy, J., Saul, N., and Großberger, L. (2018b). UMAP: Uniform Manifold
1023 Approximation and Projection. *Journal of Open Source Software*, 3(29):861.
- 1024 [41] Meltzoff, A. N. (2011). Social cognition and the origins of imitation, empathy, and theory of
1025 mind. In *The Wiley-Blackwell Handbook of Childhood Cognitive Development*. Wiley-Blackwell.
- 1026 [42] Meshulam, M., Hasenfratz, L., Hillman, H., Liu, Y. F., Nguyen, M., Norman, K. A., and Hasson,
1027 U. (2020). Neural alignment predicts learning outcomes in students taking an introduction to
1028 computer science course. *Nature Communications*, 12(1922):doi.org/10.1038/s41467-021-22202-3.
- 1029 [43] Mikolov, T., Chen, K., Corrado, G., and Dean, J. (2013). Efficient estimation of word represen-
1030 tations in vector space. *arXiv*, 1301.3781.
- 1031 [44] Moser, K. M., Wei, T., and Brenner, D. (2021). Remote teaching during COVID-19: implications
1032 from a national survey of language educators. *System*, 97:102431.
- 1033 [45] Nastase, S. A., Goldstein, A., and Hasson, U. (2020). Keep it real: rethinking the primacy of
1034 experimental control in cognitive neuroscience. *NeuroImage*, 15(222):117254–117261.
- 1035 [46] Nguyen, M., Chang, A., Micciche, E., Meshulam, M., Nastase, S. A., and Hasson, U. (2022).
1036 Teacher-student neural coupling during teaching and learning. *Social Cognitive and Affective
1037 Neuroscience*, 17(4):367–376.
- 1038 [47] OpenAI (2023). ChatGPT. <https://chat.openai.com>.
- 1039 [48] Piantadosi, S. T. and Hill, F. (2022). Meaning without reference in large language models.
1040 *arXiv*, 2208.02957.
- 1041 [49] Poulsen, A. T., Kamronn, S., Dmochowski, J., Parra, L. C., and Hansen, L. K. (2017). EEG
1042 in the classroom: synchronised neural recordings during video presentation. *Scientific Reports*,
1043 7:43916.

- 1044 [50] Ratka, A. (2018). Empathy and the development of affective skills. *American Journal of*
1045 *Pharmaceutical Education*, 82(10):doi.org/10.5688/ajpe7192.
- 1046 [51] Reilly, D. L., Cooper, L. N., and Elbaum, C. (1982). A neural model for category learning.
1047 *Biological Cybernetics*, 45(1):35–41.
- 1048 [52] Rhoads, R. A., Berdan, J., and Toven-Lindsey, B. (2013). The open courseware movement in
1049 higher education: unmasking power and raising questions about the movement’s democratic
1050 potential. *Educational Theory*, 63(1):87–110.
- 1051 [53] Scott, P., Asoko, H., and Leach, J. (2007). *Handbook of research on science education*, chapter
1052 Student conceptions and conceptual learning in science. Routledge.
- 1053 [54] Shao, Y. N., Sun, H. M., Huang, J. W., Li, M. L., Huang, R. R., and Li, N. (2018). Simulation-
1054 based empathy training improves the communication skills of neonatal nurses. *Clinical Simula-*
1055 *tion in Nursing*, 22:32–42.
- 1056 [55] Shim, T. E. and Lee, S. Y. (2020). College students’ experience of emergency remote teaching
1057 during COVID-19. *Children and Youth Services Review*, 119:105578.
- 1058 [56] Simon, M. A., Tzur, R., Heinz, K., and Kinzel, M. (2004). Explicating a mechanism for
1059 conceptual learning: elaborating the construct of reflective abstraction. *Journal for Research in*
1060 *Mathematics Education*, 35(5):305–329.
- 1061 [57] Stepien, K. A. and Baernstein, A. (2006). Education for empathy. *Journal of General Internal*
1062 *Medicine*, 21:524–530.
- 1063 [58] Touvron, H., Lavril, T., Izacard, G., Martinet, X., Lachaux, M.-A., Lacroix, T., Rozière, B.,
1064 Goyal, N., Hambro, E., Azhar, F., Rodriguez, A., Joulin, A., Grave, E., and Lample, G. (2023).
1065 LLaMA: open and efficient foundation language models. *arXiv*, 2302.13971.
- 1066 [59] Tulchinskii, E., Kuznetsov, K., Kushnareva, L., Cherniavskii, D., Barannikov, S., Pio-
1067 ntkovskaya, I., Nikolenko, S., and Burnaev, E. (2023). Intrinsic dimension estimation for robust
1068 detection of AI-generated texts. *arXiv*, 2306.04723.

- 1069 [60] van Paridon, J., Liu, Q., and Lupyan, G. (2021). How do blind people know that blue is cold?
1070 distributional semantics encode color-adjective associations. *Proceedings of the Annual Meeting of*
1071 *the Cognitive Science Society*, 43(43).
- 1072 [61] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., and
1073 Polosukhin, I. (2017). Attention is all you need. In *Advances in Neural Information Processing*
1074 *Systems*.
- 1075 [62] Whalen, J. (2020). Should teachers be trained in emergency remote teaching? Lessons learned
1076 from the COVID-19 pandemic. *Journal of Technology and Teacher Education*, 28(2):189–199.
- 1077 [63] Young, J. R. (2012). Inside the Coursera contract: how an upstart company might profit from
1078 free courses. *The Chronicle of Higher Education*, 19(7):1–4.
- 1079 [64] Ziman, K., Heusser, A. C., Fitzpatrick, P. C., Field, C. E., and Manning, J. R. (2018). Is
1080 automatic speech-to-text transcription ready for use in psychological experiments? *Behavior*
1081 *Research Methods*, 50:2597–2605.