

llmXive Automated Review of KVarN: Variance-Normalized KV-Cache Quantization Mitigates Error Accumulation in Reasoning Tasks

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer's exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer's section also names the underlying model that produced it.

This paper's panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_claim_accuracy.md`

The review focuses on the accuracy of factual claims and the alignment between claims and cited evidence.

1. Overstated Baseline Performance Claims In the Introduction, the authors claim that methods like KIVI “underperform in decode-heavy reasoning scenarios due to error accumulation.” While the paper proposes a method to mitigate this, the provided experimental tables (Tab. 1: AIME24/MATH500, Tab. 3: IFEval) do not support a claim of significant “underperformance” or “failure.” KIVI achieves 55.5% vs 61.1% (FP16) on AIME24 and 77.8% vs 82.6% on MATH500. These are competitive results, not a collapse. The text implies a qualitative failure that the quantitative data does not fully substantiate. The claim should be tempered to reflect that KIVI shows *relative degradation* compared to the proposed method in long contexts, rather than a general inability to handle reasoning tasks.

2. Conflation of MSE and End-to-End Quality The paper makes a central claim that “top 5% errors cause most end-to-end degradation” (Section Key Ideas, Fig. outlier_impact). This is supported by the KL-divergence analysis in the figure. However, the Appendix section “Outlier Contributions to MSE” explicitly states that these outliers contribute a “minority of MSE.” The manuscript risks confusing readers by using the “5% rule” to justify the *magnitude* of the problem without clearly distinguishing that the *impact* (KL/accuracy) is disproportionate to the *magnitude* (MSE). The claim “outlier errors contribute disproportionately to end-to-end quality” is accurate, but the phrasing “cause most end-to-end degradation” without the “disproportionally” qualifier in the main text is slightly misleading when contrasted with the MSE data.

3. Contextual Nuance in Benchmark Citations The Introduction cites `kamradt2023needle` to support the claim that KIVI “excels in prefill settings.” The paper’s own Appendix (Section NiaH) notes that “Static NiaH is easier than accumulated pseudo-decode.” The claim that KIVI excels in NIAH is true for the static setting but potentially false for the accumulated setting the paper aims to solve. The text should clarify that KIVI’s success is limited to *static* retrieval tasks, whereas the proposed method targets the *accumulated* error regime, to avoid implying KIVI fails at NIAH entirely.

4. Citation Consistency The bibliography lists URLs for datasets (MATH500, AIME24, etc.) as “mismatch” in the metadata. While the paper text cites standard arXiv or GitHub links for these benchmarks (e.g., `lightman2024lets_math500`), the metadata flags suggest the provided citation keys in the LaTeX source might not resolve to the correct URLs in the final bibliography. This is a minor technical issue but affects the verifiability of the “standard benchmarks” claim.

Overall, the core scientific claim (variance normalization helps) is supported by the data, but

the narrative framing of the baseline’s failure and the distinction between error magnitude and quality impact requires tightening to match the evidence precisely.

Action items.

- **[writing]** The claim that KIVI ‘underperform[s] in decode-heavy reasoning scenarios due to error accumulation’ (Intro) is not supported by the provided tables. Table 1 (AIME24/MATH500) and Table 3 (IF-Eval) show KIVI results are within 1-2% of FP16 and often comparable to other baselines, not a catastrophic failure. The text overstates the baseline’s failure mode without citing a specific experiment showing KIVI collapse in long-horizon decoding.
- **[writing]** The citation for the ‘Needle-in-a-Haystack’ benchmark (kamradt2023needle) is used to claim KIVI excels in prefill settings. However, the paper’s own Figure NIAH (Appendix) and text suggest static NIAH is ‘much easier’ than the accumulated setting. The claim that KIVI ‘excels’ here needs to be qualified by the specific context (static vs. accumulated) to avoid misleading readers about its robustness in the proposed ‘pseudo-decode’ regime.
- **[writing]** The claim that ‘top 5% errors cause most end-to-end degradation’ (Key Ideas) is supported by Fig. outlier_impact (KL-divergence) but contradicted by the text in the Appendix (‘Outlier Contributions to MSE’) which states they cause a ‘minority of MSE’. The paper conflates MSE (reconstruction error) with end-to-end quality (KL/accuracy) without clearly distinguishing that the 5% rule applies specifically to the impact on generation quality, not the raw error magnitude.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_figure_critic.md

Figure 1

The figure is a bar chart with clear axes but lacks a functional caption, making the metric ‘Error fraction due to Mag.’ and the significance of the dashed baseline impossible to interpret.

Figure 2

The figure provides a clear visual schematic of the KVarN pipeline, but the caption is marred by missing text placeholders for the method name and table references, and it fails to explicitly define the ‘s₂’ symbol shown in the diagram.

Figure 3

The figure effectively illustrates the proposed pseudo-decode setting and error accumulation mechanism. However, the caption contains two instances of missing text where the method name and a table reference should be.

Figure 4

The figure clearly displays the performance curves for KIVI and KVarN, but the caption is insufficient as it merely lists a filename without describing the experiment, and the y-axis label lacks specific definition regarding the error metric.

Figure 5

Figure 5 presents timing data clearly with labeled bars, but the overlapping x-axis labels reduce readability, and the inconsistent y-axis scales across subplots may mislead interpretation of the overhead magnitude.

Figure 6

The figure provides a clear schematic of the attention layer, but the caption is incomplete and lacks the descriptive detail found in other figures. Additionally, the placement of the Hadamard transform relative to RoPE differs between the query/key and value paths without explanation.

Figure 7

The figure effectively visualizes the joint distributions, but the caption contains a grammatical error and makes a claim about ‘ablations’ having off-diagonals that is not supported by the visual evidence in the HK and VarN(K) subplots.

Figure 8

Figure 8’s bar chart is visually clear but suffers from multiple caption issues including incomplete cross-references, grammatical errors, and insufficient explanation of the plotted data and color coding.

Figure 9

The figure effectively visualizes the Needle-in-a-Haystack results with a clear legend, but the caption contains a grammatical error omitting the second method’s name, and the x-axis uses non-uniform spacing on a linear scale.

Figure 10

Figure 10 is a clear and well-constructed bar chart that effectively communicates the median dequantization time for KIVI and KVarN across different context lengths. The axes are labeled

with appropriate units, the legend is distinct, and the specific values are annotated directly on the bars, making the data easily interpretable and consistent with the caption.

Action items.

- **[fatal]** Figure 1: The caption is explicitly ‘(no caption)’, leaving the plot’s context, the definition of ‘Mag.’, and the experimental setup undefined.
- **[science]** Figure 1: The y-axis label ‘Error fraction due to Mag.’ is ambiguous; it is unclear if this represents the fraction of total error or the fraction of magnitude, and the baseline (dashed line) is not defined.
- **[writing]** Figure 2: The caption contains multiple placeholders (e.g., ‘Schematic layout of .’, ‘VarN(\$\$)’, ‘see e.g. Tab. .’) where the method name ‘KVarN’ and specific table references should be, making the text incomplete.
- **[writing]** Figure 2: The caption states ‘We store... a second scale’ but does not explicitly define the symbol ‘ s_2 ’ shown in the diagram, relying on the reader to infer its meaning from the visual context.
- **[writing]** Figure 3: The caption contains a missing method name in the sentence ‘is designed to operate in this regime’.
- **[writing]** Figure 3: The caption contains a missing reference in the sentence ‘see e.g. Tab. .’.
- **[science]** Figure 4: The y-axis label ‘MAE(attention-output)’ is ambiguous; the caption refers to ‘reconstruction error’ but does not specify if this is the error of the quantized cache against the original, or the error in the attention output itself, which are distinct metrics.
- **[writing]** Figure 4: The caption is a bare filename (‘sinkh_only_l1_pooled_abs_Qwen_Qwen3-4B_ctx32768_B64_N8_K500000.pdf’) and lacks a descriptive sentence explaining the experimental setup, model, or context length (32k) shown in the filename.
- **[writing]** Figure 4: The x-axis label ‘Context length (kTokens)’ is slightly non-standard; ‘k’ usually implies 1000, but ‘kTokens’ is not a standard unit abbreviation (e.g., ‘k tokens’ or ‘thousands of tokens’ is preferred).
- **[writing]** Figure 5: The x-axis labels (‘VarN(.) all layers’, ‘128-token generation’) are rotated and overlap, making them difficult to read; consider horizontal alignment or better spacing.
- **[science]** Figure 5: The y-axis scales differ significantly across the three subplots (0-1200, 0-4000, 0-7000 ms), which visually exaggerates the relative overhead of variance normalization; using a consistent scale or normalizing the data would improve comparability.
- **[writing]** Figure 6: The caption is incomplete, containing only the title ‘Arrangement of Hadamard transforms...’ and a filename, but lacks the explanatory text found in other captions (e.g., Figure 2) that describes the specific operations (e.g., ‘Every token is Hadamard-rotated...’).
- **[science]** Figure 6: The diagram shows a Hadamard transform (H) applied to the W_v path, but the W_q and W_k paths show H applied *after* RoPE. This contradicts the standard ‘pre-RoPE’

rotation logic implied by the W_q/W_k flow and the caption’s claim of a specific ‘arrangement’ without explaining the discrepancy.

- **[science]** Figure 7: The caption claims ‘KIVI and ablations of our method have substantial off-diagonals,’ but the ‘HK’ and ‘VarN(K)’ subplots show tight diagonal alignment with minimal off-diagonal spread, contradicting the text.
- **[writing]** Figure 7: The caption contains a missing subject in the phrase ‘tightly controls token scales’ (likely ‘KVarN’), making the sentence grammatically incomplete.
- **[writing]** Figure 8 caption contains incomplete cross-references: ‘complement Fig. .’ and ‘see e.g. Tab. .’ lack specific figure/table numbers.
- **[writing]** Figure 8 caption has a grammatical error: ‘It shows much MSE remains’ should be ‘It shows how much MSE remains’ or ‘It shows the remaining MSE’.
- **[science]** Figure 8 caption claims to show MSE when replacing top k% errors, but the x-axis labels (‘fix top 1%’, ‘fix bottom 99%’, etc.) are ambiguous about whether bars represent MSE of the replaced portion or the remaining error.
- **[science]** Figure 8 lacks a legend explaining the blue vs. orange bar colors, which appear to represent different conditions not defined in the caption.
- **[science]** Figure 8 y-axis label ‘MSE(fp16, variant)’ is unclear about what ‘variant’ refers to; the caption does not specify which quantization method or baseline is being measured.
- **[writing]** Figure 9 caption: The phrase ‘KIVI vs. under Static’ is grammatically incomplete; the second method name is missing (likely ‘KVarN’ based on the paper title).
- **[science]** Figure 9: The x-axis labels (3, 6, 9, 12, 16, 19, 22, 25, 28, 31) are non-uniformly spaced but plotted on a linear grid, which visually distorts the density of data points at higher context lengths.

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_jargon_police.md

The manuscript relies heavily on domain-specific jargon that creates a barrier for non-specialist readers, particularly those in adjacent fields like general NLP or systems engineering. While the technical precision is high, the density of undefined acronyms and specialized terms impedes accessibility.

First, the acronym **VarN** is used frequently (e.g., Figure 1 caption, Section 2.3, Algorithm 1) before being explicitly defined as “Variance-Normalized” in a way that a general reader can immediately grasp. The Introduction mentions “variance-normalization” but does not immediately link it to the acronym “VarN” in a clear, definitional sentence.

Second, the term “**incoherence processing**” (Section 2.2) is used without explanation. This is a specific term from matrix theory and quantization literature referring to making matrix columns less correlated (often via Hadamard rotation). For a broader audience, this should be described as “rotating the data to distribute outliers evenly” or similar plain language.

Third, “**Sinkhorn-iteration**” or “**Sinkhorn-Knopp**” (Introduction, Section 2.3) is mentioned as the basis for the normalization. While standard in optimal transport, the iterative nature of balancing row and column sums is not explained. A brief parenthetical description (e.g., “an iterative method to balance row and column variances”) would suffice.

Fourth, the coined term “**pseudo-decode**” (Section 3.2) is central to the paper’s evaluation methodology but is not defined in plain English. The text describes the mechanics but lacks a high-level summary of *why* this term is used instead of “approximate decoding” or “simulated decoding.”

Finally, the metric “**bits/elem**” appears in table headers (e.g., Table 1). While common in compression, “average bits per element” is more accessible.

These changes are minor but essential for the paper to meet the standard of clarity expected for a broad scientific audience.

Action items.

- **[writing]** The manuscript relies heavily on domain-specific jargon that creates a barrier for non-specialist readers, particularly those in adjacent fields like general NLP or systems engineering. While the technical precision is high, the density of undefined acronyms and specialized terms impedes accessibility. First, the acronym VarN is used frequently (e.g., Figure 1 caption, Section 2.3, Algorithm 1) before being explicitly defined as “Variance-Normalized” in a way that a general reader can immediately

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The paper presents a logical argument that token magnitude errors are the primary driver of quantization degradation in reasoning tasks, and that variance normalization (KVarN) mitigates this. The decomposition of error into magnitude and directional components (Eq. 2) is mathematically sound and supports the premise that standard methods fail to preserve token scales.

However, a logical tension exists between the main text’s emphasis on outlier errors driving end-to-end quality (via KL-divergence) and the Appendix figure stating that top 5% errors contribute *less* to MSE than the remaining 95%. While the authors correctly identify that KL-divergence is the relevant metric for generation quality, the paper does not explicitly explain *why* MSE is a poor proxy in this context, creating a potential confusion for readers regarding the nature of the “error accumulation” being mitigated. The causal link between “reducing

magnitude error” and “improving reasoning” relies on the assumption that magnitude errors disproportionately affect attention logits in a way that MSE fails to capture; this mechanism should be stated more explicitly to close the logical gap.

Furthermore, the “pseudo-decode” evaluation method is introduced as a proxy for error accumulation. The logic assumes that quantizing in blocks of size b and re-accessing the quantized cache mimics the error growth of true autoregressive decoding. While plausible, the paper does not provide a logical derivation or empirical validation that the error growth rate in this block-wise setting correlates linearly or predictably with the true token-by-token accumulation. Without this validation, the claim that KVarN “mitigates error accumulation” based solely on pseudo-decode results is a slight overreach.

Finally, the claim of “SOTA” performance is logically supported by outperforming KIVI, but the comparison to the FP16 baseline is ambiguous. In Table 1, KVarN’s performance on AIME24 (60.0%) falls within one standard deviation of the FP16 baseline ($61.1\% \pm 3.1$). The paper frames the result as a “substantial improvement” over quantization baselines but does not logically address whether KVarN actually recovers the full precision performance or merely narrows the gap. If the goal is to match FP16, the statistical overlap suggests the claim of “SOTA” (implying parity with full precision) is not fully supported by the data presented.

Action items.

- **[science]** The claim that ‘top 5% errors cause most end-to-end degradation’ (Fig. 1, Eq. 2) is supported by KL-divergence data but contradicted by the MSE analysis in Appendix Fig. ‘Outlier Contributions to MSE’ which states top 5% contribute less to MSE. The paper must explicitly reconcile why KL-divergence (not MSE) is the correct metric for reasoning tasks to avoid logical confusion regarding error accumulation mechanisms.
- **[science]** The ‘pseudo-decode’ evaluation method (Sec 3.2) assumes error accumulation occurs by quantizing blocks sequentially. However, the paper does not logically demonstrate that this specific block-wise quantization schedule accurately models the error propagation dynamics of true autoregressive decoding, where every single token generation step involves a new quantization event. A justification or comparison to true decoding error curves is needed.
- **[science]** The conclusion states KVarN achieves SOTA on AIME24/MATH500 with 2.3 bits/element. However, Table 1 shows KVarN’s accuracy (60.0% AIME, 79.2% MATH) is statistically indistinguishable from FP16 baselines ($61.1\% \pm 3.1$, $82.6\% \pm 0.5$) given the standard deviations, yet the paper claims ‘substantial improvement’ over KIVI without addressing the overlap with the full-precision baseline. The logical leap from ‘better than KIVI’ to ‘SOTA’ requires clarification on whether it matches FP16 performance.

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: qwen.qwen3.5-122b

Prompt: `agents/prompts/paper_reviewer_overreach.md`

The paper makes several claims that extend beyond the immediate evidence provided in the results.

First, the use of the term “SOTA” (State-of-the-Art) and “substantial improvement” in the Abstract, Contributions, and Conclusion is an overreach. While the method performs well, the quantitative results in Tables 1, 2, and 3 show margins that are often marginal or within the standard deviation of the baselines. For instance, on IFEval (Table 3), KVarN achieves 80.4% vs. KIVI’s 80.3% (Strict) and 83.4% vs. 83.2% (Loose). These differences are statistically indistinguishable given the reported variances (e.g., $\pm 0.3\%$). Claiming “substantial improvement” or “best performance” across the board for such narrow margins misrepresents the magnitude of the gain. The authors should qualify these claims, perhaps stating “competitive performance” or “comparable to SOTA with lower bit-width” where the gains are not statistically significant.

Second, the causal link between “magnitude errors” and the observed performance gains is asserted too strongly. The paper decomposes error into magnitude and direction (Eq. 1) and shows magnitude errors dominate the top 5% outliers (Fig. 1a). It then claims KVarN’s success is *because* it fixes these magnitude errors. However, the Sinkhorn-Knopp algorithm (VarN) is a complex iterative process that alters the entire distribution of the matrix, not just the magnitude of outliers. The paper does not provide an ablation study isolating the effect of the variance normalization from the Hadamard rotation or the specific iterative balancing to prove that *only* the magnitude correction is responsible for the end-to-end gains. The claim that “outlier errors contribute disproportionately” is supported by the KL-divergence analysis, but the leap to “therefore, fixing magnitude errors is the key” is an extrapolation not fully backed by the provided ablation data.

Third, the runtime overhead claim of “0.18%” is based on a specific measurement (1.9ms vs 1050ms) for a specific context length and batch size. Extrapolating this to a general claim of “negligible overhead” for all reasoning tasks is an overreach. In scenarios with shorter contexts or different hardware, the fixed cost of the Sinkhorn iterations could become a more significant fraction of the total latency. The paper should clarify the conditions under which this overhead holds or provide a sensitivity analysis.

Finally, the claim that KVarN is “not suitable for SSMs or MLA architectures” (Limitations) is a necessary limitation, but the paper does not discuss *why* the variance normalization specifically fails for these architectures beyond a brief mention. While this is a limitation, the broader claim that the method is universally applicable to “reasoning tasks” (Title/Abstract) might be slightly overreaching if the “reasoning” tasks tested are limited to standard Transformer-based benchmarks and do not include the specific long-context reasoning challenges where SSMs/MLA are often deployed.

Action items.

- **[science]** The claim that KVarN achieves ‘SOTA’ on AIME24, MATH500, HumanEval, and IFEval (Abstract, Conclusion) is overreaching. Table 1 and Table 3 show KVarN matches or slightly exceeds baselines (e.g., +0.1% on AIME24, +0.1% on IFEval Strict) but does not demonstrate a statistically significant or substantial improvement over all SOTA methods,

particularly given the small margins and standard deviations.

- **[writing]** The paper claims ‘substantial improvement’ (Contributions, Introduction) and ‘best performance’ (Experiments) based on differences often within the noise margin (e.g., 60.0% vs 55.5% on AIME24 is significant, but 80.4% vs 80.3% on IFEval is not). The language should be tempered to reflect ‘competitive’ or ‘comparable’ performance where margins are negligible, reserving ‘substantial’ for clear wins.
- **[science]** The assertion that ‘outlier errors contribute disproportionately to end-to-end quality’ (Contributions) is supported by Fig. 3 (KL divergence) but the paper extrapolates this to claim that fixing *only* magnitude errors (via VarN) is the *sole* reason for the performance gains. It does not rule out that the Sinkhorn iterations might also be stabilizing the distribution in ways not captured by the simple magnitude/direction decomposition.
- **[writing]** The runtime overhead claim of ‘0.18%’ (Abstract, Conclusion) is derived from a specific micro-benchmark (1.9ms vs 1050ms). Extrapolating this to a general ‘negligible overhead’ for all inference scenarios is an overreach, as the relative cost of normalization may increase significantly for shorter sequences or different hardware configurations not tested.

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_safety_ethics.md

The manuscript presents a technical advancement in KV-Cache quantization (KVarN) for large language models. From a safety and ethics perspective, the paper is generally sound as it does not involve human subjects, sensitive personal data, or the generation of harmful content directly. The datasets used (AIME24, MATH500, HumanEval, IFEval) are standard academic benchmarks with no apparent privacy or consent issues.

However, three specific areas require attention to meet standard publication ethics and safety disclosure requirements:

1. **Funding and Conflict of Interest:** The text references NeurIPS 2026 guidelines (Section: Related Work/Conclusion area) but lacks a dedicated “Funding” or “Conflict of Interest” section. Authors must explicitly disclose funding sources and any potential conflicts to ensure transparency.
2. **Environmental Impact:** The Appendix reports a computational cost of approximately 50 GPU days. While the method claims low latency overhead, the total carbon footprint of the training/evaluation process is not estimated. Given the increasing emphasis on the environmental impact of AI research, a brief statement estimating the CO2 emissions or referencing the energy consumption is necessary.
3. **Safety Implications of Limitations:** The “Limitations” section correctly identifies archi-

tectural constraints (SSMs, MLA). However, it does not address the safety implications of the core mechanism: mitigating error accumulation in *reasoning* tasks. If error accumulation is not perfectly mitigated in edge cases, could this lead to subtle reasoning failures in safety-critical applications (e.g., medical or legal advice)? A brief discussion on the potential risks of deploying such compressed models in high-stakes environments would strengthen the ethical rigor of the paper.

No dual-use risks or data privacy violations were identified. The code availability link (GitHub) is standard practice and does not raise immediate safety concerns, provided the repository does not contain unredacted sensitive data (which is unlikely for this type of benchmark).

Action items.

- **[writing]** Funding and Conflict of Interest: The text references NeurIPS 2026 guidelines (Section: Related Work/Conclusion area) but lacks a dedicated “Funding” or “Conflict of Interest” section. Authors must explicitly disclose funding sources and any potential conflicts to ensure transparency.
- **[writing]** Environmental Impact: The Appendix reports a computational cost of approximately 50 GPU days. While the method claims low latency overhead, the total carbon footprint of the training/evaluation process is not estimated. Given the increasing emphasis on the environmental impact of AI research, a brief statement estimating the CO2 emissions or referencing the energy consumption is necessary.
- **[writing]** Safety Implications of Limitations: The “Limitations” section correctly identifies architectural constraints (SSMs, MLA). However, it does not address the safety implications of the core mechanism: mitigating error accumulation in *reasoning* tasks. If error accumulation is not perfectly mitigated in edge cases, could this lead to subtle reasoning failures in safety-critical applications (e.g., medical or legal advice)? A brief discussion on the potential risks of deploying such compressed model

Scientific Evidence

Weights the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_scientific_evidence.md

The scientific evidence presented for KVarN is generally robust in its experimental design, utilizing multiple models (Qwen3-4B, Llama-3.1-8B, Phi-4-14B) and diverse benchmarks (reasoning, code, instruction following, retrieval). The decomposition of error into magnitude and directional components (Eq. 2, Fig 1) provides a compelling mechanistic explanation for the observed improvements, supported by the visual evidence in Figure 1b showing reduced token norm deviation.

However, the statistical rigor regarding the primary claims of “substantial improvement” requires strengthening. In Table 1 (AIME24/MATH500), the proposed method’s results are

presented as point estimates (e.g., 60.0%) or with standard deviations that appear to be derived from a single run or a very small sample size, whereas baselines like KIVI show larger variances (e.g., 55.5 ± 6.9). Without reporting the number of independent seeds (n) for KVarN and conducting a statistical significance test (e.g., paired t-test) against the baselines, the claim of “substantial improvement” is not fully supported by the evidence. The observed gains, while positive, could potentially be within the noise floor of the evaluation metric, especially given the high variance in reasoning tasks.

Furthermore, the “pseudo-decode” evaluation method introduced in Section 3.2 is a critical contribution for efficiently measuring error accumulation. While the results in Figure 4 suggest KVarN accumulates less error than KIVI, the paper does not explicitly validate this proxy against full autoregressive decoding. A correlation analysis between the pseudo-decode error metrics and the actual end-to-end accuracy on a held-out set of reasoning problems is necessary to confirm that the proxy accurately predicts real-world performance degradation.

Finally, the comparison with eviction-based methods in the Appendix (Table 5) requires clarification on the definition of “equivalent memory footprint.” The authors compare 2-bit quantization against 7x compressed 16-bit eviction methods. While the bit-widths may align, the overhead of storing eviction indices or the specific implementation details of the 7x compression (e.g., does it include the prompt cache?) must be explicitly detailed to ensure the comparison is fair and the claim of superiority is scientifically sound. The current presentation risks conflating quantization efficiency with eviction efficiency without a unified cost model.

Action items.

- **[science]** The claim that KVarN achieves SOTA on AIME24 and MATH500 relies on a single run (or unspecified n) for the proposed method, while baselines like KIVI report standard deviations (e.g., 60.0 ± 1.1 vs 55.5 ± 6.9 in Tab 1). To validate statistical significance, the authors must report the number of independent seeds (n) for KVarN and perform a t-test or report confidence intervals for the proposed method’s gains.
- **[science]** The ‘pseudo-decode’ evaluation method (Sec 3.2, Fig 4) is a novel proxy for error accumulation but lacks validation against true autoregressive decoding. The authors should demonstrate a strong correlation between the pseudo-decode error metrics and actual end-to-end reasoning performance on a held-out subset to prove the proxy’s predictive validity.
- **[science]** The paper claims KVarN outperforms eviction methods (SnapKV, PyramidKV) at equivalent memory footprint (Tab 5, Appendix). However, the comparison mixes quantization (2-bit) with eviction (7x compression of 16-bit). The authors must clarify if the ‘equivalent footprint’ claim holds strictly for the KV-cache size or if it includes the overhead of storing eviction indices, and ensure the comparison is fair regarding total memory usage.

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The statistical analysis in the manuscript is generally sound in its presentation of mean performance and standard deviations across multiple benchmarks. However, several critical statistical details are missing or insufficiently justified to fully support the claims of “substantial improvement” and “error mitigation.”

First, regarding **reproducibility and variance estimation**, Table 1 (Section 4.1) presents results as Mean $\pm$ Standard Deviation (e.g., 60.0 ± 1.1 for KVarN on AIME24). While the Appendix mentions “Avg@3” for MATH500 and AIME24, this crucial parameter ($N=3$) is not explicitly linked to the standard deviation calculations in the main text or table captions. For $N=3$, the standard deviation is a highly unstable estimator of population variance. The authors should explicitly state the number of runs for every reported metric and consider reporting the Standard Error of the Mean (SEM) or 95% Confidence Intervals (CIs) instead of, or in addition to, the standard deviation, especially given the small sample size.

Second, the **statistical significance of improvements** is not addressed. The paper claims KVarN achieves “best performance” and “substantial improvement” over SOTA (KIVI). For instance, on AIME24 with Qwen3-4B, KVarN scores 60.0% while KIVI scores 55.5%. However, the standard deviation for KIVI is reported as 6.9%. The difference (4.5%) is smaller than the standard deviation of the baseline. Without a formal hypothesis test (e.g., a paired t-test or a non-parametric equivalent like the Wilcoxon signed-rank test) or a reported p-value, it is statistically premature to claim a definitive improvement. The observed gain could easily be due to random variation in the prompt sampling or model initialization. The authors must perform and report significance tests for the primary comparisons in Tables 1, 2, and 3.

Third, the **methodological validity of the “pseudo-decode” setting** (Section 3.2) requires statistical justification. The authors introduce this as an efficient proxy for error accumulation in autoregressive decoding. The core assumption is that the error accumulation observed in the block-wise pseudo-decode setting correlates strongly with the actual performance degradation in full autoregressive generation. The paper presents qualitative plots (Fig. 4) showing error trends but lacks a quantitative statistical analysis (e.g., Pearson/Spearman correlation coefficient) demonstrating that the pseudo-decode metric is a reliable predictor of end-to-end accuracy. Without this validation, the use of this proxy to claim “mitigation of error accumulation” is methodologically weak.

Finally, the **decomposition of error** (Eq. 2, Section 3.1) is presented as a deterministic algebraic identity, which is correct. However, the interpretation of Figure 1a (showing magnitude errors dominate) relies on the distribution of these errors across the dataset. The authors should clarify if the “top 5% errors” are defined globally across the entire dataset or per-sample, and whether the statistical significance of the dominance of magnitude errors over directional errors was tested.

In summary, while the experimental design is robust in terms of benchmark selection, the statistical reporting lacks the rigor required to confirm that the observed improvements are not due to chance. The addition of significance testing, clearer reporting of sample sizes for variance

estimates, and validation of the pseudo-decode proxy is necessary.

Action items.

- **[writing]** Table 1 (math_reasoning_results) reports standard deviations (e.g., 60.0 ± 1.1) but does not specify the number of independent runs (N) used to calculate them. The text mentions ‘Avg@3’ in the appendix, but this must be explicitly stated in the main results tables or caption to allow for proper statistical interpretation of the variance.
- **[science]** The claim that KVarN ‘outperforms’ KIVI on AIME24 (60.0% vs 55.5%) relies on a difference of 4.5%. Without a reported p-value or confidence interval for this difference, it is unclear if this improvement is statistically significant or within the noise of the evaluation (given the reported std dev of 6.9% for KIVI). Please add significance testing (e.g., paired t-test or bootstrap CI) for key comparisons.
- **[science]** The ‘pseudo-decode’ evaluation method (Sec 3.2) is a novel proxy for error accumulation. The statistical validity of this proxy relies on the assumption that block-wise quantization error accumulation linearly approximates autoregressive decoding error. The paper lacks a statistical validation (e.g., correlation analysis) between the pseudo-decode metric and actual end-to-end performance degradation to justify this methodological choice.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript demonstrates a strong command of technical writing, with a clear logical flow from the problem statement (error accumulation in reasoning tasks) to the proposed solution (KVarN) and empirical validation. The structure is well-organized, and the use of figures and tables effectively supports the narrative. The prose is generally precise, and the mathematical notation is consistent.

However, there are minor stylistic and grammatical issues that detract from the overall polish. The most notable is the informal footnote in the Introduction defining the acronym “KVarN” with a whimsical Swedish translation. While creative, this breaks the formal tone expected in a scientific preprint and should be relocated or removed. Additionally, there are instances of minor redundancy (e.g., “Generally... often”) and inconsistent spacing in units (e.g., “2.3bit” vs “2.3 bits”) that should be corrected.

The transition between sections is smooth, and the “Key Ideas” subsection effectively summarizes the core contributions before diving into the methods. The description of the “pseudo-decode” evaluation method is clear, though the adjective “fast” could be more precisely defined to avoid ambiguity regarding whether it refers to the evaluation speed or the model’s inference speed.

Overall, the writing quality is high and the paper is highly readable. Addressing the minor stylistic inconsistencies and the informal footnote will elevate the manuscript to a professional

standard suitable for publication.

Action items.

- **[writing]** In the Introduction (e001), the footnote defining ‘KVarN’ as a Swedish noun (‘the grinding apparatus...’) is overly informal and distracts from the technical contribution. Consider moving this etymological note to the Appendix or removing it to maintain a professional academic tone.
- **[writing]** In Section 2.1 (e001), the sentence ‘Generally K quantization is often considered to be more difficult than V quantization’ contains a redundancy (‘Generally’ and ‘often’). Rephrase to ‘K quantization is generally considered more difficult than V quantization’ for conciseness.
- **[writing]** In Section 3.2 (e001), the phrase ‘We propose a fast pseudo-decode setting’ is slightly ambiguous. Clarify if ‘fast’ refers to the computational speed of the evaluation method itself or the speed of the resulting model inference. Suggest: ‘We propose an efficient pseudo-decode setting to measure error accumulation.’
- **[writing]** In the Conclusion (e001), the phrase ‘2.3bit/element’ lacks a space between the number and unit. Standardize to ‘2.3 bits/element’ throughout the manuscript for consistency with the rest of the text.