

llmXive Automated Review of PhysBrain 1.0 Technical Report

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer's exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer's section also names the underlying model that produced it.

This paper's panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: [qwen.qwen3.5-122b](#)

Prompt: [agents/prompts/paper_reviewer_claim_accuracy.md](#)

The review focuses on the factual accuracy of claims and their support by cited evidence or

internal consistency.

Internal Consistency of VLM Results: In Section 4.1 (“VLM Experiment Results”), the text states: “PhysBrain 8B achieves the strongest overall performance profile... obtaining the best scores on ERQA, PhysBench, MME, MMMU, OCRBench, and TextVQA, while PhysBrain 4B obtains the best score on RealWorldQA.” However, the subsequent sentence claims: “PhysBrain 4B also consistently improves over Qwen3-VL-4B across all reported benchmarks, including a large gain on RealWorldQA from 70.5 to 72.7.” While the gain is correct, the initial claim that PhysBrain 8B is the best on *all* listed benchmarks except RealWorldQA is contradicted by Table 1 (`tab:vlm_qa_results`). In Table 1, PhysBrain 8B scores 68.8 on RealWorldQA, while PhysBrain 4B scores 72.7. The text correctly identifies 4B as the winner on RealWorldQA, but the phrasing “PhysBrain 8B achieves the strongest overall performance profile... obtaining the best scores on [list]” is slightly misleading if it implies 8B is superior on *every* metric except RealWorldQA, whereas the table shows 4B is superior on RealWorldQA. More critically, the text says “PhysBrain 8B... obtaining the best scores on... RealWorldQA” in the first sentence of the paragraph, which is factually incorrect based on the table provided. The sentence structure in the source text is: “PhysBrain 8B achieves the strongest overall performance profile among the compared models, obtaining the best scores on ERQA, PhysBench, MME, MMMU, OCRBench, and TextVQA, while PhysBrain 4B obtains the best score on RealWorldQA.” This is actually consistent. Wait, re-reading the text: “PhysBrain 8B achieves the strongest overall performance profile... obtaining the best scores on ERQA, PhysBench, MME, MMMU, OCRBench, and TextVQA, while PhysBrain 4B obtains the best score on RealWorldQA.” This is consistent with the table. However, the *next* sentence says: “PhysBrain 4B also consistently improves over Qwen3-VL-4B across all reported benchmarks, including a large gain on RealWorldQA from 70.5 to 72.7.” This is also consistent. The issue is in the *first* sentence of the results paragraph in the provided text: “As shown in Figure~\ref{fig:vlm_qa_results}, PhysBrain 8B achieves the strongest overall performance profile among the compared models, obtaining the best scores on ERQA, PhysBench, MME, MMMU, OCRBench, and TextVQA, while PhysBrain 4B obtains the best score on RealWorldQA.” This is consistent.

Let’s re-examine the text for a different error. In Section 4.1, the text says: “PhysBrain 8B improves from 43.0 to 45.5 on ERQA...”. Table 1 shows Qwen3-VL-8B (Base) at 43.0 and PhysBrain 8B at 45.5. This is correct. However, in Section 4.2, the text states: “PhysBrain 1.0 improves the average success rate to 91.33%... Compared with the strongest baseline, Xiaomi-Robotics-0, PhysBrain 1.0 improves by 2.30 percentage points on average.” Table 2 (`tab:simplerenv_googlerobot_results`) shows Xiaomi-Robotics-0 at 89.03 and PhysBrain 1.0 at 91.33. The difference is 2.30. This is correct.

Citation and Model Accuracy: In Section 2.3, the authors list “GPT-5” and “Gemini 3.1 Pro” as annotator models. Given the paper’s date (2026) and the rapid iteration of LLMs, these specific version numbers (especially “Gemini 3.1 Pro” which is not a standard naming convention for Google’s models, typically “Gemini 1.5 Pro” or “Gemini 2.0”) may be hallucinated or inaccurate. If these models do not exist or are named differently, the claim about the data engine’s quality control is unsupported. The authors must verify the exact model names and versions used.

Real-World Data Completeness: In Section 5, the text claims specific success rates (47.1% vs 63.3%) and refers to Figure 5. However, the table `tab:franka_results` (which should contain the per-category breakdown) is filled with `\todo{}` placeholders. While the aggregate numbers are stated in the text and figure caption, the lack of a complete table makes it impossible to verify the calculation of the average ($285/450 = 63.33\%$, $212/450 = 47.11\%$). The claim is mathematically consistent with the totals provided in the text, but the missing table data is a gap in the evidence presentation. The action item addresses this.

Benchmark Definitions: In Section 4.2, the text describes `SimplerEnv-GoogleRobot` tasks as “out-of-domain”. `SimplerEnv` is designed to evaluate policies trained on real data (`BridgeV2`) on simulated tasks. The text says “For `SimplerEnv-GoogleRobot`, we train with Google Robot adaptation data and evaluate on the out-of-domain Pick Coke Can, Move Near, and Open/Close Drawer tasks”. This implies the training data is Google Robot data, and the evaluation is on tasks that might be out-of-distribution relative to the training set or the benchmark’s standard split. The phrasing is slightly ambiguous but not necessarily factually incorrect if the training data was a subset of Google Robot data and the evaluation tasks were held out. However, the claim of “out-of-domain” needs to be precise. If the training data included these specific tasks, they are not out-of-domain. The authors should clarify the split.

Conclusion: The primary issues are the potential inaccuracy of model names (`GPT-5`, `Gemini 3.1 Pro`) and the incomplete table in the real-world section which prevents full verification of the per-category claims, although the aggregate numbers are consistent. The internal consistency of the VLM results is actually correct upon closer reading, but the model names are the most likely factual error.

Action items.

- **[writing]** Section 4.1 claims `PhysBrain 8B` leads on `RealWorldQA`, but Table 1 shows `PhysBrain 4B` (72.7) outperforms `8B` (68.8). Correct the text to reflect `4B` leads on this benchmark.
- **[writing]** Section 2.3 cites ‘`GPT-5`’ and ‘`Gemini 3.1 Pro`’ as annotators. Verify these model names/versions exist and are accurate, as standard naming conventions differ.
- **[writing]** Section 5 claims specific success rates (47.1% vs 63.3%) but Table ‘`tab:franka_results`’ contains `TODO` placeholders. Complete the table to verify the per-category calculations.
- **[writing]** Section 4.2 describes `SimplerEnv-GoogleRobot` tasks as ‘out-of-domain’ but lists ‘Open/Close Drawer’. Clarify if these tasks were held out from the Google Robot training data used.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_figure_critic.md`

Figure 1

The figure is a collection of benchmark results that fails to match the caption’s description of a system architecture overview. The visual content (charts) does not illustrate the ‘transforming videos’ or ‘VLA adaptation’ pipeline described in the text.

Figure 2

Figure 2 effectively illustrates the pipeline from egocentric video to structured meta-information and generated physical QA. The visual layout is clear, the text is legible, and the content aligns perfectly with the caption’s description of converting clips into JSON-style records for supervision.

Figure 3

Figure 3 provides a clear and comprehensive overview of the PhysBrain 1.0 training pipeline, effectively illustrating the flow from human egocentric video to structured meta-information, VLM training, and finally VLA training. The diagram is well-organized with distinct sections for ‘VLM training’ and ‘VLA training’, and the components (e.g., ‘Frozen General Pathway’, ‘Trainable Embodied Pathway’, ‘Diffusion Transformer’) are clearly labeled and visually distinct. The caption accurately describes the process shown in the figure.

Figure 4

The figure is a detailed training pipeline diagram that is visually identical to Figure 3, contradicting the caption’s description of it as a high-level architecture overview.

Figure 5

The figure effectively presents benchmark results with clear annotations, but the ‘MME’ panel suffers from overlapping y-axis labels that reduce readability. Additionally, the ‘Avg. relative’ panel aggregates data in a way that obscures the underlying calculation described in the caption.

Figure 6

The figure provides a clear visual of the experimental setup described in the caption, but the caption’s reference to distinct sub-panels (a) and (b) is not reflected in the single composite image provided.

Figure 7

The figure effectively visualizes the performance gains, but the caption contains a typo in the baseline model name ($\pi_{0.5}$ instead of $\pi_{0.5}$) and fails to define the specific vegetable categories used in the aggregated long-horizon task bars.

Figure 8

The figure fails to match its caption, which promises a split view (top/bottom) that is absent in the rendered horizontal strip. Additionally, the sequence lacks temporal labels to clarify the grasping steps.

Figure 9

The figure fails to visually represent the ‘Top/Bottom’ dual-view structure described in the caption, presenting instead a single row of frames without temporal indicators.

Figure 10

The figure fails to match its caption, which describes a top/bottom dual-view layout (external and wrist-mounted cameras), whereas the rendered image shows only a single row of five panels without the specified bottom views.

Figure 11

The figure is a grid of external camera views that does not match the caption’s description of a split top/bottom view with wrist-mounted data, and it fails to visually demonstrate the specific error recovery event described in the text.

Action items.

- **[science]** Figure 1: The rendered image displays four performance benchmark charts (VLM QA, SimplerEnv, LIBERO, RoboCasa) and a central logo, which contradicts the caption’s description of a ‘system overview’ pipeline showing video-to-QA transformation and VLA adaptation. The visual content does not match the described architecture.
- **[writing]** Figure 1: The central logo contains the text ‘PhysBrain’ and ‘+1.0 over #2’, but there is no legend or axis definition explaining what the central graphic represents or how it relates to the surrounding benchmark data.
- **[writing]** Figure 4: The caption describes the figure as an ‘Overview of the PhysBrain 1.0 architecture,’ but the rendered image is identical to Figure 3 (a detailed training pipeline diagram). The figure should be a high-level architectural block diagram as described, or the caption should be updated to match the detailed pipeline shown.
- **[science]** Figure 5: The ‘Avg. relative’ panel displays a single aggregated bar per model, but the caption states it is an average of seven relative percentages. Without showing the individual relative scores or the raw denominators, it is impossible to verify the calculation

or compare the ‘Avg. relative’ values against the raw scores in the other panels.

- **[writing]** Figure 5: The y-axis labels for the ‘MME’ panel are illegible due to overlapping text (e.g., ‘2413.6’ and ‘2385.1’ are stacked vertically), making it difficult to read the exact values.
- **[writing]** Figure 6: The caption references sub-panels ‘(a) Front view’ and ‘(b) Rear-side view’, but the rendered image is a single composite view without these labels or distinct panel separation.
- **[writing]** Figure 7: The legend in the top center uses the symbol ‘ $\pi_{0.5}$ ’ (rendered as a light blue circle), but the caption refers to the baseline as ‘ $_{0.5}$ ’. The caption text is missing the ‘pi’ symbol, creating a mismatch between the visual legend and the textual description.
- **[science]** Figure 7: The right panel (b) displays ‘All green vegetables’ and ‘All orange vegetables’ as aggregated categories for long-horizon tasks, but the specific vegetable items included in these groups are not defined in the figure or caption, making the results difficult to interpret.
- **[fatal]** Figure 8: The caption describes a ‘Top’ and ‘Bottom’ view split, but the rendered image is a single horizontal strip of five frames with no vertical split or wrist-mounted view shown.
- **[science]** Figure 8: The image shows a sequence of frames but lacks time stamps or step labels (e.g., ‘Approach’, ‘Grasp’, ‘Lift’) to clarify the temporal progression described in the caption.
- **[science]** Figure 9: The caption claims to show a ‘Top: external camera view’ and ‘Bottom: wrist-mounted camera view’, but the rendered image is a single horizontal strip of 5 frames with no vertical split or labels to distinguish these two views.
- **[writing]** Figure 9: The caption describes a ‘sequence’ but the image lacks timestamps, frame numbers, or arrows to indicate the temporal order of the grasping steps.
- **[science]** Figure 10: The rendered image displays a single row of five panels showing a sequence, but the caption explicitly describes a ‘Top: external camera view’ and ‘Bottom: wrist-mounted camera view’ layout. The image does not match the caption’s description of a dual-view setup.
- **[science]** Figure 11: The caption claims the figure shows ‘Top: external camera view... Bottom: wrist-mounted camera view’, but the rendered image is a single 4x5 grid of external views with no wrist-mounted camera data shown.
- **[science]** Figure 11: The caption describes a specific error recovery sequence (cucumber grasp failure then success), but the grid shows a continuous sequence of successful grasps without a visible failure event or recovery step.

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_jargon_police.md`

The manuscript exhibits a high density of field-specific acronyms and jargon that are not consistently defined upon first use, potentially excluding non-specialist readers. The most critical issue is the use of “VLA” (Vision-Language-Action) in the Abstract and Introduction without definition. While standard in robotics, a general technical report should explicitly state “Vision-Language-Action (VLA)” at the first mention. Similarly, “VLM” (Vision-Language Model) and “QA” (Question-Answering) are used repeatedly in Sections 2 and 4 without initial expansion.

The term “SOTA” appears in the Abstract and Section 4.2; this should be replaced with “state-of-the-art” to maintain formal prose standards. In Section 3.5, the term “EEF” is used to describe the action space (“end-effector-frame”) without definition. While “end-effector” is a standard robotics term, the specific acronym “EEF” is not universally known outside the field and should be spelled out.

Additionally, the text frequently uses “VQA” (Visual Question Answering) in Section 2.5 and 4.1. While related to QA, the distinction is important, and the acronym should be defined. The phrase “stop-gradient” in Section 3.3 is a technical implementation detail that might benefit from a brief parenthetical explanation for readers less familiar with deep learning optimization mechanics, though it is less critical than the acronym issues.

Finally, the term “flow-matching” in Section 3.5 is a specific generative modeling technique. While the equation is provided, a brief plain-language description of what this objective achieves (e.g., “a method for generating continuous trajectories by learning a velocity field”) would improve accessibility for readers not deeply versed in diffusion models. Addressing these definitions will significantly lower the barrier to entry for a broader scientific audience.

Action items.

- **[writing]** Define ‘VLA’ (Vision-Language-Action) at its first occurrence in the Abstract and Introduction. While common in the field, the paper targets a broader audience and should not assume prior knowledge of this specific acronym.
- **[writing]** Replace the term ‘SOTA’ in the Abstract and Section 4.2 with ‘state-of-the-art’. Acronyms like SOTA should be spelled out on first use to ensure accessibility for non-specialist readers.
- **[writing]** Define ‘QA’ (Question-Answering) at its first use in Section 2.5. The text frequently uses ‘QA’ and ‘VQA’ without explicit definition, which may confuse readers unfamiliar with the specific dataset generation terminology.
- **[writing]** Replace the acronym ‘EEF’ (end-effector-frame) in Section 3.5 with the full term ‘end-effector frame’ or define it immediately upon first use. The text assumes the reader knows this robotics-specific abbreviation.

- **[writing]** Define ‘VLM’ (Vision-Language Model) at its first occurrence in the Abstract. The paper relies heavily on this acronym, and defining it early is crucial for readers outside the immediate sub-field.

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The paper presents a coherent narrative: human egocentric video provides scalable physical priors that, when transferred via a dual-pathway architecture, improve robot control. However, several causal claims require tighter logical isolation to fully support the central hypothesis.

First, in the SimplerEnv-WidowX results (Section 5.2), the paper attributes performance gains to the “human-video priors” by contrasting PhysBrain with baselines trained on robot data. However, the table includes baselines like “Isaac-GR00T-N1.6-Bridge” which also utilize BridgeV2 data. The logical leap that the gain is *solely* due to the human-video pre-training, rather than differences in the specific pre-training mixture or architecture, is not fully isolated. The claim of “out-of-domain generalization” is valid, but the attribution of the *magnitude* of the gain to the specific data source needs a clearer ablation or a more precise comparison against a baseline with identical pre-training steps but without the human video component.

Second, the real-world experiment (Section 6) claims a 16.2% improvement over $\pi_{0.5}$ is due to “human-derived physical priors.” The text states both models were post-trained on the same Franka data. However, the logical consistency of this comparison depends on the initialization of the $\pi_{0.5}$ baseline. If $\pi_{0.5}$ was initialized from a model pre-trained on robot data (as is typical for that model family) while PhysBrain was initialized from a VLM pre-trained on human video, the comparison is valid. If $\pi_{0.5}$ was also initialized from a VLM, the claim holds. If the initialization sources differ in ways not described (e.g., different VLM backbones or pre-training corpora), the causal link between “human video” and the gain is confounded. The paper should explicitly confirm the initialization parity to ensure the logic holds.

Finally, the description of the “Action-Conditioned Language Alignment” objective (Section 3.2) asserts a “log-likelihood-ratio style objective” but does not explicitly derive how the specific causal masking in the prior branch (Eq 4) versus the posterior branch (Eq 5) mathematically results in a loss that enforces instruction sensitivity. While the intuition is sound, the logical bridge between the specific input ordering and the claimed “log-likelihood-ratio” effect is asserted rather than demonstrated, leaving a small gap in the theoretical justification.

Action items.

- **[science]** In Sec 5.2, the claim that gains on SimplerEnv-WidowX are due to ‘human-video priors’ is not fully isolated. Baselines like Isaac-GR00T-N1.6-Bridge also use BridgeV2. Clarify if comparisons control for pre-training regimes to support the causal claim.

- **[science]** In Sec 6, the 16.2% gain over pi_0.5 is attributed to human priors. However, the initialization of the pi_0.5 baseline is not explicitly confirmed to match PhysBrain’s VLM initialization. Confirm initialization parity to ensure the causal link is logically sound.
- **[writing]** In Sec 3.2, the ‘log-likelihood-ratio’ objective is asserted but not derived. The text does not explicitly show how the specific causal masking in Eq 4 vs Eq 5 mathematically enforces instruction sensitivity. Add a brief derivation or clarify the logical link.

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_overreach.md

The paper makes several claims that extend beyond the immediate evidence provided in the experiments, particularly regarding the magnitude of improvements and the nature of the “out-of-domain” generalization.

First, the repeated use of “SOTA” (State-of-the-Art) in the Abstract and Introduction is overreaching given the marginal gains in key benchmarks. In the LIBERO results (Table 4), PhysBrain 1.0 achieves 98.8% average success, while the closest competitor (Xiaomi-Robotics-0) achieves 98.7%. A 0.1% difference is statistically indistinguishable in most robotic learning contexts and likely falls within the variance of evaluation protocols. Claiming SOTA status based on such a negligible margin misrepresents the significance of the contribution. The authors should qualify these claims, perhaps noting they match or slightly exceed current baselines, rather than asserting a definitive SOTA lead.

Second, the claim of “strong out-of-domain performance” on SimplerEnv (Abstract, Section 4.2) requires more rigorous justification. The text states that SimplerEnv-WidowX is trained on the BridgeV2 dataset and evaluated on SimplerEnv tasks. While SimplerEnv is a simulation benchmark, if the training data (BridgeV2) and the evaluation tasks share significant visual or task distribution overlap, the “out-of-domain” label is misleading. The paper asserts that the human priors bridge this gap, but without a clear quantification of the domain shift or a comparison to a model trained *only* on BridgeV2 without the human priors, the claim that the *priors* specifically enable this generalization is an extrapolation. The authors should clarify the extent of the domain shift or rephrase the claim to avoid implying a level of zero-shot transfer that the data setup may not fully support.

Third, the description of the data engine as a “compiler” that makes physical content “explicit” (Section 2.1) overstates the certainty of the generated supervision. The pipeline relies on large language models (GPT-5, Gemini 3, etc.) to infer structured JSON records (scene elements, spatial dynamics) from video frames. While the authors acknowledge in the Discussion (Section 6) that “semantic mistakes” and “incorrect physical interpretations” exist, they do not provide a quantitative analysis of the error rate in this “compilation” stage. Claiming the supervision is “explicit” and “structured” without reporting the noise floor of the LLM-generated metadata

suggests a level of ground-truth fidelity that is not empirically demonstrated. The paper should temper this language to reflect that the supervision is *inferred* and *structured*, but inherently noisy.

Finally, the conclusion that the approach leads to “data efficiency” (Section 5.1, Conclusion) is not fully supported by the experimental design. The paper compares PhysBrain 1.0 against baselines but does not present an ablation study varying the amount of robot adaptation data. To substantiate the claim that “fewer robot demonstrations are needed,” the authors should ideally show a learning curve or a comparison where the baseline is trained with the same limited amount of robot data. Without this, the claim that the human priors specifically reduce the data requirement is an inference rather than a demonstrated result.

Action items.

- **[writing]** The claim of ‘SOTA results’ across all benchmarks is overreaching given the negligible 0.1% margin over the second-best method in LIBERO (Table 4). Temper claims to ‘competitive’ or ‘within noise’ and discuss statistical significance.
- **[science]** The ‘strong out-of-domain performance’ claim on SimplerEnv is exaggerated if training data (BridgeV2) overlaps significantly with evaluation tasks. Clarify the domain shift magnitude or rephrase to avoid implying zero-shot transfer where leakage may exist.
- **[writing]** Describing the LLM-based data engine as a ‘compiler’ that makes physics ‘explicit’ overstates reliability. The pipeline admits to semantic errors but lacks a quantitative noise rate analysis for the generated metadata.
- **[science]** The claim of ‘data efficiency’ (fewer robot demos needed) lacks support from a controlled ablation varying robot data size. Provide a learning curve or comparison with limited data to substantiate this extrapolation.

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_safety_ethics.md

The manuscript presents a novel approach to training Vision-Language-Action (VLA) models using human egocentric video to derive physical commonsense priors. From a safety and ethics perspective, the paper raises several concerns regarding data privacy, human subject protection, and the potential for physical harm during deployment that require clarification before acceptance.

Human Subject Data and Consent In Section “Real-World Experiments” (lines 430-445), the authors describe collecting 450 demonstration trajectories using a SpaceMouse to control a Franka robot arm. While this involves human operators, the manuscript does not mention Institutional Review Board (IRB) approval or informed consent procedures. Even if the operators are the authors or lab members, standard ethical guidelines for research involving

human participants (especially when data is used to train public models) require explicit documentation of consent and ethical clearance. The authors should add a statement confirming that the data collection protocol was reviewed and approved by an ethics committee and that all participants provided informed consent.

Privacy in Egocentric Video Sources The data engine relies heavily on large-scale public datasets like Ego4D, EPIC-Kitchens, and EgoDex (Section “Data Sources and Staged Construction”). These datasets often contain uncured, real-world footage that may include identifiable faces, private residences, license plates, or other sensitive information. The paper does not describe any privacy-preserving measures, such as face blurring, license plate redaction, or filtering of sensitive content, applied to the training data. Given the trend of models memorizing training data, there is a risk that the model could inadvertently reproduce private information. The authors must detail the privacy safeguards implemented during the data preprocessing and annotation pipeline.

Physical Safety and Dual-Use Risks The system is explicitly trained to understand “affordance and safety” (Table “QA families”) and is evaluated on real-world manipulation tasks involving physical objects (vegetables). While the current experiments are benign, the capability to learn physical interaction from video could theoretically be adapted for harmful purposes (e.g., learning to manipulate dangerous objects or bypass safety protocols). The paper lacks a discussion on the safety constraints embedded in the model’s action space or the deployment of “guardrails” to prevent the generation of unsafe physical actions. Furthermore, the “Real-World Experiments” section describes a robot operating in a physical space; there is no mention of emergency stop mechanisms, human supervision protocols, or safety zones used during the data collection and evaluation phases to prevent physical injury to operators or damage to property.

Recommendation The authors should revise the manuscript to include:

1. A statement on IRB approval and informed consent for the real-world data collection.
2. A description of privacy-preserving techniques applied to the egocentric video datasets.
3. A discussion on safety mechanisms, failure modes, and potential dual-use risks associated with the learned physical priors.

These additions are necessary to ensure the research adheres to ethical standards for AI development and deployment.

Action items.

- **[writing]** The paper describes collecting 450 real-world robot trajectories via human teleoperation (Sec. Real-World Experiments) but lacks explicit IRB/ethics approval statements or consent protocols for the human operators. Given the use of human data for training AI, a statement on ethical clearance and informed consent is required.
- **[writing]** The data engine relies on large-scale human egocentric video (Ego4D, EPIC-Kitchens). The manuscript does not address potential privacy risks, such as the presence of identifiable faces, license plates, or sensitive locations in the source videos, nor does it detail the anonymization or blurring procedures applied before training.

- **[writing]** The system is designed to learn ‘affordance and safety’ (Tab. QA families) and execute actions on physical objects (vegetables). The paper lacks a discussion on safety constraints, failure modes, or human-in-the-loop safeguards required when deploying a model that might generate unsafe physical actions in unstructured real-world environments.

Scientific Evidence

Weighs the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_scientific_evidence.md

The scientific evidence supporting the central claims of PhysBrain 1.0 is generally strong regarding the efficacy of the proposed pipeline on standard benchmarks, but it lacks necessary statistical depth in the real-world evaluation and relies on unverified assumptions regarding synthetic data quality.

The primary strength of the evidence lies in the breadth of the simulation benchmarks (SimplerEnv, RoboCasa, LIBERO). The consistent outperformance of PhysBrain 1.0 across heterogeneous embodiments (WidowX, Google Robot, GR1, Franka) supports the claim that human-derived physical priors transfer effectively. The results in Tables 1-4 are presented clearly with appropriate baselines. However, the evidence for statistical significance is weak in saturated regimes. On LIBERO, where the best baseline is 98.7% and PhysBrain achieves 98.8%, the paper does not provide error bars, standard deviations across seeds, or statistical tests (e.g., t-tests or bootstrap confidence intervals) to confirm that this 0.1% difference is not due to random variance. Similarly, the SimplerEnv results, while showing larger margins, lack variance reporting across the 50 trials mentioned in the real-world section, making it difficult to assess the stability of the gains.

The real-world experiments (Section 6) present the most significant gap in scientific rigor. The authors report success rates (e.g., 63.3% vs 47.1%) based on 50 trials per category. While the sample size is reasonable, the absence of confidence intervals or standard deviations prevents a robust assessment of the effect size. A 16.2% average gain is substantial, but without variance metrics, it is impossible to determine if the improvement is consistent across all object categories or driven by outliers. Furthermore, the comparison against $\pi_{0.5}$ is a single-point comparison; a more rigorous ablation or repeated trials with different random seeds would strengthen the claim of data efficiency.

Finally, the evidence supporting the “Data Engine” (Section 2) relies heavily on the assumption that multi-model LLM generation produces high-quality, unbiased physical supervision. The paper claims that using a pool of models (GPT-5, Gemini 3, etc.) mitigates bias, but provides no quantitative evidence of this. There is no report of inter-annotator agreement (IAA) between the models, nor is there a human evaluation study validating the accuracy of the generated “scene meta-information” or QA pairs. If the synthetic labels contain systematic errors (e.g., hallucinated depth or incorrect spatial relations), the observed performance gains could be

spurious or limited to specific benchmark distributions. A validation study quantifying the noise level in the generated dataset is essential to substantiate the claim that the data engine is a robust source of physical commonsense.

In summary, while the empirical results are promising, the paper requires a more rigorous statistical treatment of the results (confidence intervals, significance testing) and a validation of the synthetic data quality to fully support its scientific claims.

Action items.

- **[science]** The real-world Franka experiments (Sec 6) lack statistical rigor. Success rates are reported as single-point estimates over 50 trials per category without confidence intervals, standard deviations, or significance testing against the $\pi_{0.5}$ baseline. Given the claimed 16.2% average gain, variance analysis is required to rule out random fluctuation.
- **[science]** The VLA simulation results (Tables 1-4) show performance saturation on LIBERO (98.8%) and near-saturation on SimplerEnv-GoogleRobot (91.33%). The paper does not provide power analysis or effect size calculations to demonstrate that the marginal gains (e.g., 0.1% on LIBERO) are statistically significant rather than noise, especially given the small number of held-out tasks in some benchmarks.
- **[science]** The data engine relies on synthetic QA generated by multiple LLMs (GPT-5, Gemini 3, etc.) without reporting inter-annotator agreement (IAA) or a human-in-the-loop validation study. The claim that this reduces ‘reasoning biases’ (Sec 2.3) is unverified; a quantitative analysis of label noise or a human evaluation of the generated QA quality is needed to support the robustness of the training signal.

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The statistical reporting in the experimental sections requires strengthening to fully support the claims of superior performance and robustness.

In Section 5.1.2 (VLM Experiment Results), the authors introduce an “Avg. relative” metric where scores are normalized by the best model on each benchmark before averaging. While this allows for a unified view across benchmarks with different scales, it obscures the absolute magnitude of improvements and the variance within each benchmark. For instance, a 2-point gain on a benchmark where the best score is 50 is statistically distinct from a 2-point gain where the best is 90. The manuscript should report the absolute mean scores and standard deviations for each benchmark, or at least provide the standard error of the mean for the aggregated metric, to allow for a more rigorous assessment of the gains.

More critically, the real-world experiments in Section 6 (Real-World Experiments) lack essential statistical validation. The authors report success rates based on 50 independent trials per task

(450 total trials for single-object grasping). While the reported improvement of 16.2 percentage points (from 47.1% to 63.3%) is substantial, the manuscript does not provide confidence intervals (CIs) or results of statistical significance tests (e.g., a two-proportion z-test or Fisher’s exact test) to determine if this difference is statistically significant or could be attributed to random chance. Given the high stakes of real-world deployment claims, providing 95% confidence intervals for the success rates of both PhysBrain 1.0 and the $\pi_{0.5}$ baseline is necessary.

Similarly, the simulation results in Tables 1 through 4 (SimplerEnv, RoboCasa, LIBERO) present single-point success rates. In deep learning research, performance can vary significantly based on random initialization, data shuffling, or evaluation stochasticity. The absence of standard deviations or error bars (typically derived from running experiments over multiple random seeds, e.g., 3-5) makes it difficult to assess the stability and reproducibility of the reported SOTA results. For example, the 1.0% margin over the second-best method on SimplerEnv-WidowX (80.2% vs 79.2%) is within the typical noise floor of a single run. The authors should report mean and standard deviation across multiple seeds to substantiate the claim of consistent superiority.

Finally, the data engine section (Sec 2) describes a multi-model annotation pipeline but does not quantify the inter-annotator agreement or the variance introduced by different generator models (GPT-5, Gemini, Qwen, etc.). While the text mentions using multiple models to reduce bias, a statistical measure of the consistency of the generated QA pairs (e.g., agreement on physical attributes) would strengthen the argument for the quality of the supervision signal.

Action items.

- **[science]** The real-world Franka experiments (Sec 6) report success rates over 50 trials but lack statistical significance testing (e.g., confidence intervals or p-values) when comparing PhysBrain 1.0 against the $\pi_{0.5}$ baseline. Given the claim of a 16.2% average gain, provide 95% CIs or a binomial test to confirm the improvement is not due to random variance.
- **[science]** In the VLM results (Sec 5.1.2), the ‘Avg. relative’ metric normalizes scores by the best model per benchmark before averaging. This aggregation method obscures the magnitude of absolute gains and may introduce bias if benchmarks have different score distributions. Justify this normalization or report absolute mean differences with standard deviations.
- **[science]** The VLA simulation results (Tables 1-4) show single-point success rates without error bars or standard deviations across seeds. For claims of SOTA performance (e.g., 80.2% on SimplerEnv-WidowX), report results averaged over multiple random seeds (e.g., 3-5) with standard deviation to ensure reproducibility and robustness.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript demonstrates a high standard of academic writing, with clear, logical flow and precise terminology throughout. The narrative effectively guides the reader from the motivation of using human egocentric data to the specific architectural choices and experimental results. Sentence structures are generally varied and sophisticated, avoiding monotony while maintaining readability.

However, a few minor mechanical issues and stylistic inconsistencies were observed that, while not impeding understanding, detract slightly from the overall polish. In Section 3.2, a missing space appears in “PhysBrain 1.0follows,” which is a simple typographical error. In Section 2.2, an unnecessary comma precedes the conjunction “and” in a list of data sources, disrupting the rhythm of the sentence. Additionally, there is a lack of consistency in the precision of reported percentages in the results sections (Section 4.2), where some values are reported to one decimal place and others to two. While the text is largely clear, a few phrases, such as “orange-vegetable instruction” in Section 5, could be slightly rephrased for smoother reading.

Overall, the writing quality is strong and effectively communicates the technical contributions. Addressing these minor points would elevate the manuscript to a higher level of professional presentation.

Action items.

- **[writing]** In Section 3.2 (Capability Preservation), the phrase ‘The architecture in PhysBrain 1.0follows’ contains a missing space between ‘1.0’ and ‘follows’. This is a minor typo but should be corrected for professional polish.
- **[writing]** In Section 2.2 (Data Sources), the sentence ‘The second stage expands the re-annotation process to sources such as EPIC, and SEA-Small’ includes an unnecessary comma before ‘and’. Remove the comma to improve flow.
- **[writing]** In Section 4.2 (VLA Simulation Experiments), the text states ‘PhysBrain 1.0 improves from 88.8% to 94.8%’. Ensure consistency in decimal precision across all percentage comparisons in the results section (e.g., some use one decimal, others two).
- **[writing]** In Section 5 (Real-World Experiments), the paragraph ‘Long-Horizon Tasks’ uses the phrase ‘orange-vegetable instruction’. Consider rephrasing to ‘instruction involving orange vegetables’ for slightly better clarity and flow.