

llmXive Automated Review of On the Scaling of PEFT: Towards Million Personal Models of Trillion Parameters

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer's exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer's section also names the underlying model that produced it.

This paper's panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: [qwen.qwen3.5-122b](#)

Prompt: `agents/prompts/paper_reviewer_claim_accuracy.md`

The paper makes several specific quantitative claims regarding PEFT scaling, LoRA memory capacity, and system performance that require tighter citation anchoring to ensure the cited sources actually support the attributed numbers.

In the Introduction, the authors state that diversity among LoRA variants raises AIME24 accuracy from 0.3644 to 0.4867. While these numbers appear later in Section 4.3, the introduction presents them as a primary contribution without a direct cross-reference. For a claim of this magnitude, the text should explicitly point to the specific experiment (e.g., “Section 4.3, Figure 4”) to allow immediate verification.

In Section 3.2, the paper cites \citep{biderman2024loraforgets} for the claim that LoRA forgets less than full fine-tuning, and immediately follows with \citep{shuttleworth2025lorail-lusion} regarding representation movement. Given that the latter paper’s title (“An Illusion of Equivalence”) suggests a complex relationship between LoRA and full fine-tuning, the text should clarify whether both sources support the specific claim about “forgetting” or if they address distinct phenomena. Conflating them without distinction risks misrepresenting the nuance of the cited work.

In Section 4.1, the authors introduce a “LoRA memory capacity scaling law” with specific bounds (10^{-3} to 10^{-2} tokens/parameter) derived from “DishNameBenchmark.” However, no citation is provided for this benchmark or the specific derivation of these bounds. If DishNameBenchmark is an internal tool, it requires a citation (e.g., a technical report or preprint) to substantiate the factual claim of the capacity limit. Without this, the specific numbers appear unsupported by external or referenced evidence.

Finally, in Section 5.1, the claim that MinT has “built and audited a 10^6 -entry packed adapter catalog” is a concrete factual assertion about system scale. While the MinT framework is cited, the specific number 10^6 is not explicitly linked to a table, figure, or section within the reference or the current paper. A direct pointer to the evidence (e.g., “Table 5.2”) is necessary to verify this specific metric.

These issues are primarily writing-level fixes (adding specific cross-references) but are critical for claim accuracy, ensuring that every numerical assertion is directly traceable to its evidentiary source.

Action items.

- **[writing]** In Section 1, the claim that LoRA diversity raises AIME24 accuracy from 0.3644 to 0.4867 lacks a direct cross-reference to the specific experiment (Section 4.3) where these numbers are derived, hindering immediate verification.
- **[writing]** In Section 3.2, the text cites both Biderman et al. (2024) and Shuttleworth et al. (2025) to support claims about LoRA forgetting and representation movement. The latter’s title (‘An Illusion of Equivalence’) suggests nuance; the text should clarify if both sources support the specific ‘forgetting less’ claim or address different aspects.
- **[writing]** In Section 4.1, the specific LoRA memory capacity law (10^{-3} to 10^{-2} tokens/-param) is attributed to ‘DishNameBenchmark’ but lacks a citation. If internal, a technical report or preprint citation is needed to substantiate these specific numerical bounds.

- **[writing]** In Section 5.1, the claim of a ‘ 10^6 -entry packed adapter catalog’ in MinT is a specific factual assertion. The text cites the MinT framework but does not link this number to a specific table, figure, or section within the reference or paper for verification.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_figure_critic.md

Figure 1

Figure 1 effectively illustrates the biological analogy for PEFT scaling axes, but the provided caption is incomplete, missing the description for panel (c), and contains unformatted citation placeholders.

Figure 2

The figure fails to visualize the ‘task-success’ metric mentioned in the caption, and the lack of a legend makes it impossible to distinguish between the two plotted lines. Additionally, the x-axis scaling is unclear due to sparse tick marks.

Figure 3

Figure 3 clearly compares two architectures with labeled lines and axes, but the caption does not explicitly link the plotted ‘mean rollout probability difference’ to the claimed ‘training-inference mismatch’ metric, and the x-axis lacks unit context.

Figure 4

The figure effectively visualizes the probability difference trends, but the legend labels (‘R3 (Ours)’, ‘Baseline’) do not align clearly with the caption’s terminology (‘R3-fixed’, ‘original’), and the y-axis label appears visually truncated.

Figure 5

The figure visually supports the general claim that R3 is more stable than baselines, but the y-axis scale and lack of precision make the specific numerical claim in the caption unverifiable, and the faint grid lines hinder accurate reading.

Figure 6

The figure clearly displays the R3 method outperforming baselines, but the caption’s claim that baselines ‘trend downward’ is not supported by the visual data, which shows fluctuation or stability rather than a consistent decline.

Figure 7

The figure displays two loss curves but fails to distinguish between the ‘model’ and ‘MTP’ components mentioned in the caption, as there is no legend or line style differentiation. Additionally, the y-axis label is not repeated on the right subplot despite the different scale.

Figure 8

The figure clearly displays the relationship between LoRA rank and mean gain with appropriate error bars, but the x-axis scaling and the definitions of the shaded background regions are not explicitly explained in the caption.

Figure 9

The figure clearly displays a performance peak at middle ranks, but the x-axis scaling is visually misleading for logarithmic data, and the caption lacks sufficient detail to interpret the axes and highlighted regions independently.

Figure 10

The figure effectively illustrates the separation between mean and best scores, but the linear spacing of logarithmic x-axis values distorts the data trend, and the y-axis lacks specific metric definitions.

Figure 11

The figure effectively visualizes the gap between mean and best performance across LoRA ranks, but the caption lacks a precise definition of the shaded region and does not fully explain the connection between the visual gap and the ‘reliability’ claim.

Figure 12

The figure presents a clear line plot, but the caption’s claim that performance ‘flattens’ at high ranks is factually contradicted by the steep downward slope of the data shown. Additionally, the specific metric defining the ‘adapter footprint’ on the x-axis is not explicitly defined.

Action items.

- **[writing]** Figure 1: The caption text is truncated and missing the description for panel (c) ‘Scale Out’, which is clearly depicted in the image as ‘Sustain a persistent population’.
- **[writing]** Figure 1: The caption contains raw citation placeholders (e.g., ‘encode2012’,

‘1000genomes2012’, ‘[thesis_fig1.pdf]’) instead of formatted references.

- **[science]** Figure 2: The caption claims to show ‘Stable reward and task-success curves’, but the plot only displays ‘Normalized Reward’ on the y-axis. The ‘task-success’ metric is missing from the visualization.
- **[science]** Figure 2: The x-axis is labeled ‘Training Step’ but the tick marks (15, 30, 45) are extremely sparse and do not align with the data density, making it difficult to determine the actual scale or duration of the training run.
- **[writing]** Figure 2: The legend is missing from the image; while the caption mentions ‘reward and task-success’, the plot contains two lines (blue and grey) without a legend to identify which corresponds to which metric or if they represent different models.
- **[science]** Figure 3: The y-axis label ‘Mean rollout probability difference’ is not explicitly defined as the metric for ‘training-inference mismatch’ (TIM) in the caption; the caption claims to show TIM but does not confirm that the plotted metric is the standard or intended definition of TIM.
- **[writing]** Figure 3: The x-axis label ‘Training step’ lacks units or context (e.g., thousands of steps, epochs), making it ambiguous whether the scale represents 60 steps or 60,000 steps.
- **[science]** Figure 4: The legend labels ‘R3 (Ours)’, ‘GSPO + Rollout Correction’, and ‘Baseline’ contradict the caption’s description of ‘R3-fixed’ (low) vs ‘original’ and ‘rollout-corrected’ (high). The plot shows ‘R3 (Ours)’ as the low line, but the caption implies ‘R3-fixed’ is the low line, creating ambiguity about which method is the proposed solution versus the baseline.
- **[writing]** Figure 4: The y-axis label ‘Max rollout probability difference’ is truncated to ‘Max rollout probability difference’ (missing the ‘Max’ or cut off visually) in the rendered image, making it hard to read the full label.
- **[science]** Figure 5: The caption claims the R3 run maintains near-zero KL divergence (0.000026 at step 46), but the y-axis scale (0.000 to 0.004) and the visual flatness of the blue line make it impossible to verify this specific value or distinguish it from zero, rendering the claim unverifiable from the figure.
- **[writing]** Figure 5: The y-axis label ‘PPO KL divergence’ lacks units or a clear indication of the scale’s precision, and the grid lines are too faint to aid in reading values accurately.
- **[science]** Figure 6: The caption claims baselines ‘trend downward,’ but the ‘Baseline’ (grey dashed) and ‘GSPO + Rollout Correction’ (cyan dashed) lines show no consistent downward trend over the full 50 steps; the Baseline fluctuates and the GSPO line remains relatively flat after step 20, making the textual claim misleading.
- **[writing]** Figure 6: The y-axis values are negative (ranging from -0.96 to -0.56), yet the caption and title do not specify the metric’s range or sign convention, which could confuse readers regarding whether higher (less negative) is better.
- **[science]** Figure 7: The caption claims to show ‘model and MTP components’ (plural), but the plot contains no legend or distinct line styles to differentiate the two curves. It is

impossible to determine which line corresponds to the ‘model’ loss and which to the ‘MTP’ loss.

- **[writing]** Figure 7: The y-axis label ‘Loss’ is shared for both subplots, but the scales differ (0.0–0.8 vs 0.0–1.2). While the grid lines help, explicitly labeling the y-axis on the right subplot or adding a unit (e.g., ‘Cross-Entropy Loss’) would improve clarity.
- **[writing]** Figure 8: The x-axis uses a logarithmic scale (1, 2, 4, 8...) but lacks explicit tick labels for the intermediate values (e.g., 3, 5, 6, 7) or a clear ‘log’ indicator, which may confuse readers regarding the spacing.
- **[writing]** Figure 8: The shaded background regions (‘frontier’, ‘default’, ‘cost warning’) are not defined in the caption, leaving the criteria for these specific rank ranges ambiguous.
- **[writing]** Figure 9: The caption ‘Middle-rank peak’ is too brief and does not explain the axes (LoRA rank, Mean gain) or the highlighted region ($r=16$, $r=32$), making the figure’s specific claim unclear without external context.
- **[science]** Figure 9: The x-axis uses a non-standard logarithmic-like spacing (1, 2, 4, 8, 16, 32, 64, 128, 256) but the visual distance between 1 and 2 is identical to 128 and 256, which is misleading for a log-scale representation.
- **[science]** Figure 10: The x-axis labels (1, 2, 4, 8, 16, 32, 64, 128, 256) are spaced linearly rather than logarithmically, which distorts the visual representation of the data trend across orders of magnitude.
- **[writing]** Figure 10: The y-axis label ‘Final score’ is generic and does not specify the metric or task used to derive the scores, making the results difficult to interpret without external context.
- **[science]** Figure 11: The plot displays ‘Final score’ vs ‘LoRA rank’ with ‘Mean score’ and ‘Best score’ lines, but the caption describes ‘Mean–best separation’ and ‘reliability’ without explicitly defining the shaded region or explaining how the visual gap represents the separation metric mentioned in the title.
- **[writing]** Figure 11: The caption repeats the title ‘Mean–best separation’ and discusses ‘reliability’ and ‘capacity’ but fails to explicitly state that the shaded area represents the variance or standard deviation across seeds, which is critical for interpreting the ‘mean behavior’ claim.
- **[science]** Figure 12: The caption claims the ‘observed performance frontier flattens’ beyond the middle-rank region, but the plot shows a steep, monotonic decline in ‘Mean gain’ as the adapter footprint increases from 4x to 16x. The visual data directly contradicts the textual claim of a flattening frontier.
- **[writing]** Figure 12: The x-axis label ‘Adapter footprint relative to $r=16$ ’ is ambiguous regarding the specific metric used (e.g., parameter count, memory usage, or FLOPs), which is critical for interpreting the ‘opportunity cost’ mentioned in the caption.

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_jargon_police.md`

The manuscript relies heavily on domain-specific acronyms and proprietary shorthand that significantly hinder accessibility for non-specialist readers. The most critical issue is the failure to define acronyms at their first occurrence. For instance, ‘MoE’ (Mixture of Experts) is used extensively in the Introduction and Section 3 without expansion, assuming the reader is already fluent in sparse architecture terminology. Similarly, ‘TIM’ (training-inference mismatch) is introduced in Section 3.4 as a noun phrase (‘TIM is critical’) before the acronym is ever defined, forcing the reader to guess the meaning or search backward.

Specific terms like ‘DAPO’, ‘GRPO’, ‘R3’, ‘MLA’, ‘DSA’, and ‘MinT’ appear as proper nouns or acronyms without definition. ‘MinT’ is particularly opaque; the text refers to ‘MinT separates concerns’ without stating what the acronym stands for or providing a full name. ‘R3’ is introduced as ‘Router Replay R3’, which is slightly better, but the text should explicitly state ‘Router Replay (R3)’ to ensure clarity. ‘OLoRA’ and ‘PiSSA’ are used in Section 4.1 without defining them as ‘Orthonormal LoRA’ and ‘Principal Singular Values and Singular Vectors Adaptation’, respectively.

Furthermore, the paper uses ‘PEFT’ in the title and introduction without spelling out ‘parameter-efficient fine-tuning’. While common in the field, the paper’s ambitious scope suggests a need for broader clarity. Benchmarks like ‘AIME’ and ‘GPQA’ are mentioned without context; ‘GPQA’ in particular is not a standard acronym for a general audience. The text also uses ‘MoE’ repeatedly in Section 3.4 when discussing ‘GLM5’ and ‘DeepSeekV3-style’ architectures, assuming the reader understands the specific implications of these sparse structures.

To improve accessibility, the authors should adopt a strict policy of defining every acronym at its first use and replacing jargon with plain language where possible. For example, instead of ‘MoE’, use ‘sparse mixture-of-experts models’ on first mention. Instead of ‘TIM’, write ‘training-inference mismatch (TIM)’. This would make the paper’s core arguments about scaling and personalization accessible to a wider audience, including researchers in adjacent fields and practitioners who may not be deeply familiar with the specific RL and PEFT sub-communities.

Action items.

- **[writing]** The manuscript relies heavily on domain-specific acronyms and proprietary shorthand that significantly hinder accessibility for non-specialist readers. The most critical issue is the failure to define acronyms at their first occurrence. For instance, ‘MoE’ (Mixture of Experts) is used extensively in the Introduction and Section 3 without expansion, assuming the reader is already fluent in sparse architecture terminology. Similarly, ‘TIM’ (training-inference mismatch) is introduced in Section 3.4

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The paper presents a coherent three-axis framework (Scale Up, Down, Out) for PEFT, and the logical flow between these sections is generally sound. The dependency chain (Scale Up enables Scale Down, which enables Scale Out) is clearly articulated. However, several causal claims lack sufficient internal justification or alternative explanations.

First, in Section 3.2.1, the paper claims that OLoRA-tail (initializing from minor singular vectors) prevents KL divergence explosion in RLVR, whereas standard LoRA and OLoRA (principal vectors) fail. The text attributes this to “preserving pretrained geometry” and avoiding “aggressive updates.” While the empirical results (Figure 4) are clear, the logical link between “minor singular vectors” and “RL stability” is not rigorously derived. The paper cites a general “KL leash” argument but does not explicitly show why the minor subspace specifically satisfies the trust-region constraints better than the principal subspace in the context of the specific RL objective used. This leaves a gap between the proposed mechanism and the observed outcome.

Second, in Section 5.1, the paper argues that the performance gain from aggregating 198 distinct LoRA models (Collaboration) over repeated sampling (Repetition) proves the existence of “complementary policies” and “collective intelligence.” The logic assumes that because the models were trained with different data permutations/masking, they represent distinct strategies. However, the paper does not explicitly rule out the alternative hypothesis that these models are simply converging to different local optima of a similar policy surface, and that the gain is merely due to ensemble diversity rather than true complementary reasoning capabilities. The distinction between “stochastic noise” and “complementary policies” is asserted but not fully logically disentangled.

Finally, the dependency claim in the Introduction (“Scale Up without Scale Down yields expensive priors”) is a strong logical assertion. While the paper demonstrates that Scale Up is possible (Kimi K2) and Scale Down is beneficial (OLoRA-tail), it does not provide a logical or empirical argument that the Scale Up experiment *would have failed* without the Scale Down techniques. The necessity of the coupling is assumed rather than proven, which weakens the logical consistency of the “dependency chain” argument.

Action items.

- **[science]** The claim that OLoRA-tail’s minor subspace initialization prevents KL explosion lacks a derived causal mechanism. The text asserts stability but does not explain why the minor subspace specifically satisfies RL trust-region constraints better than the principal subspace, beyond empirical observation.
- **[science]** The argument that LoRA diversity yields ‘complementary policies’ rather than ‘stochastic noise’ is not fully supported. The paper does not rule out that distinct LoRA

variants are merely different local optima of the same policy surface, weakening the leap to ‘collective intelligence’.

- **[writing]** The claim that ‘Scale Up without Scale Down yields expensive priors’ assumes necessity without proof. The paper shows both are possible but does not demonstrate that the Scale Up experiment would fail without the specific Scale Down techniques, leaving the dependency chain unproven.

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_overreach.md

The paper presents an ambitious framework for scaling PEFT, but several claims extrapolate beyond the immediate empirical evidence provided, particularly regarding the stability of extreme compression and the system-level feasibility of the proposed “million model” architecture.

First, in Section 3.2.1 (Rank Reduction), the authors claim that OLoRA-tail maintains a “consistent $\sim +20\%$ gain” at rank $r=1$ across batch sizes. While the data shows a significant improvement over standard LoRA (which degrades to -18%), the term “consistent” glosses over the high seed sensitivity and variance explicitly highlighted in Figure 4d and the surrounding text. The text admits that low-rank regimes are “sharply batch- and seed-sensitive.” Claiming a consistent gain without quantifying the variance or providing confidence intervals for the $r=1$ regime overstates the reliability of the method for production use. The evidence supports that OLoRA-tail *enables* learning at $r=1$ where LoRA fails, but not that it does so with the stability implied by “consistent.”

Second, the “Scale Out” axis relies heavily on an extrapolation from a controlled experiment with $k=198$ models to a vision of “million personal models” (Title, Abstract, Conclusion). The paper fits a linear curve to accuracy vs. $\ln(k)$ for k up to 198 and assumes this trend holds for $k=1,000,000$. This ignores the likely non-linear system costs associated with managing a million distinct adapters, such as routing overhead, memory bandwidth saturation, and the “cold load” penalties described in Section 6.3. While the authors mention “bounded residency,” the claim that diversity scales predictably to a million models without a corresponding analysis of the system-level bottlenecks (beyond simple load times) is an overreach. The data supports the *principle* of diversity, but not the specific *scale* of the proposed architecture.

Finally, the taxonomy of “Scale-Induced Failure Modes” in Section 2.4 lists four categories, including “adapter-semantics failures” and “lifecycle failures.” The paper then presents Router Replay R3 as a solution that “substantially reduces TIM” (Training-Inference Mismatch). However, the evidence provided (probability difference metrics) only addresses the algorithmic mismatch (TIM). It does not provide evidence that R3 resolves the broader semantic failures related to checkpoint conversion, quantization, or serving runtime interpretation mentioned in the taxonomy. The paper conflates solving one specific failure mode (routing mismatch) with

resolving the entire class of scale-induced failures, which is an unjustified generalization.

To address these overreaches, the authors should temper the language regarding the stability of $r=1$ adapters, explicitly discuss the system-level scaling limits that challenge the “million model” extrapolation, and clarify that R3 addresses routing mismatch specifically rather than the entire taxonomy of failure modes.

Action items.

- **[writing]** The claim that OLoRA-tail maintains a consistent $\sim +20\%$ gain at rank $r=1$ across all batch sizes (Section 3.2.1, Fig 4 caption) appears to overstate the evidence. The text notes LoRA degrades to -18% at $bs=128$, but the ‘consistent’ gain claim implies stability that the data (showing variance in Fig 4d) may not fully support without explicit confidence intervals or a definition of ‘consistent’ in the presence of seed sensitivity.
- **[science]** The extrapolation from a controlled model-count experiment ($k=198$) to a ‘million personal models’ architecture (Title, Abstract) is a significant leap. While the $\ln(k)$ fit is provided, the paper does not sufficiently discuss the non-linear system costs (e.g., routing overhead, memory bandwidth saturation) that would likely dominate at $k=1,000,000$, potentially invalidating the linear scaling assumption for the ‘Scale Out’ axis.
- **[writing]** The assertion that ‘Router Replay R3’ reduces the semantic gap in MoE models (Section 2.4) is supported by probability difference metrics, but the paper overclaims the resolution of ‘adapter-semantics failures’ and ‘lifecycle failures’ generally. The evidence shows R3 helps with routing mismatch, but does not prove it solves the broader class of semantic mismatches in checkpoint conversion or serving runtimes mentioned in the taxonomy.

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_safety_ethics.md`

This review focuses exclusively on safety, ethics, and dual-use risks associated with the proposed architecture for “million personal models.”

The paper presents a technically ambitious framework for scaling Parameter-Efficient Fine-Tuning (PEFT) to create persistent, individualized AI agents. While the technical contributions regarding LoRA scaling and infrastructure are significant, the manuscript currently lacks a critical discussion of the ethical implications and safety risks inherent in deploying millions of persistent, memory-capable agents.

Privacy and Consent: The core thesis relies on “personal models” that accumulate “memories, preferences, skills” (Section 1, 5.1). The paper describes “Context Distillation” (Algorithm 1) as a method to permanently write context-time behaviors into model parameters. There is no mention of how user data used for this distillation is obtained, whether explicit consent is required, or how users can audit or delete their personal model’s memory. In a “million

personal models” scenario, the risk of non-consensual data harvesting or the creation of detailed psychological profiles is substantial. The manuscript should explicitly address data governance, user consent mechanisms, and the “right to be forgotten” for these persistent adapters.

Dual-Use and Social Manipulation: Section 5.2 (“User Simulators and Agent Environments”) and the OASIS experiments (Table 4) demonstrate that per-user LoRA adapters can preserve identity heterogeneity and model social dynamics, including polarization and community formation. The paper notes that these simulators “better match real group-opinion dynamics” than prompt-only baselines. This capability presents a severe dual-use risk: such systems could be weaponized to generate highly convincing, personalized disinformation campaigns, automate propaganda, or manipulate public opinion at scale by simulating specific demographic groups or individuals. The paper currently treats this as a feature for “collective intelligence” without acknowledging the potential for malicious exploitation. A discussion on the risks of automated social engineering and the need for watermarking or provenance tracking for simulated agents is necessary.

Security and Poisoning: The mechanism of “Context Learning” as a write policy (Section 5.1) implies that a model’s behavior can be permanently altered by the context it processes. This creates a vulnerability to “poisoning” attacks. If a malicious actor can inject specific context into a user’s interaction stream, they could potentially “distill” harmful behaviors, biases, or jailbreaks directly into the user’s personal adapter. Since these adapters are persistent and shared across sessions, the damage would be long-lasting. The paper should address potential attack vectors where the “write policy” is exploited to corrupt personal models.

Recommendation: The authors should add a dedicated “Safety and Ethics” section (or significantly expand the Conclusion) to address:

1. **Data Privacy:** Protocols for consent, data minimization, and user control over personal adapter memory.
2. **Dual-Use Mitigation:** Risks associated with high-fidelity user simulation for manipulation and proposed safeguards (e.g., usage policies, detection mechanisms).
3. **Security:** Vulnerabilities in the “Context Distillation” process and potential defenses against poisoning attacks.

Without these considerations, the deployment of such a system at the proposed scale poses significant societal risks that are currently unaddressed.

Action items.

- **[writing]** The paper proposes ‘million personal models’ with persistent memory of user preferences and skills (Section 5.1, 5.2). It lacks a dedicated ethics section addressing privacy, consent for data used to train personal adapters, and the risk of creating highly convincing user simulators for manipulation or social engineering.
- **[writing]** The ‘User Simulators’ section (5.2) and ‘OASIS’ experiment (Table 4) demonstrate the ability to model human social dynamics and polarization. The paper does not discuss dual-use risks, such as the potential for these simulators to be used for automated disinformation campaigns, targeted propaganda, or psychological profiling without consent.

- **[writing]** The ‘Context Distillation’ mechanism (Section 5.1) allows converting context-time improvements into permanent parameter updates. There is no discussion of safeguards against ‘poisoning’ attacks where malicious actors could inject harmful behavioral patterns or biases into a user’s personal model via crafted context, which would then persist indefinitely.

Scientific Evidence

Weighs the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_scientific_evidence.md

The paper presents a compelling three-axis framework for PEFT scaling, supported by a mix of theoretical arguments and empirical results. However, the strength of the scientific evidence is currently undermined by a lack of rigorous statistical validation in key claims and insufficient detail on experimental controls for high-variance regimes.

First, the central claim in Section 4.3 regarding “Diversity as a Source of Collective Intelligence” relies on a comparison between Collaboration (distinct LoRA variants) and Repetition (repeated sampling). The paper asserts a +0.0533 accuracy advantage for collaboration at $k=198$. While the trend is visually clear in Figure 4, the text does not report p-values, confidence intervals, or a statistical test (e.g., bootstrap or t-test) to confirm that this gain is statistically significant and not a result of random variance in the majority voting process. Without this, the claim that diversity provides a *computational* resource rather than just noise reduction remains speculative.

Second, the “DishNameBenchmark” results in Section 4.1 propose a sharp capacity law for LoRA memory (10^{-3} to 10^{-2} tokens/param). The evidence for this “sharp transition” is presented as a curve, but the experimental setup is opaque. Specifically, the method of “data permutation and masking” used to generate the variants is not detailed. It is unclear if the observed saturation is a true capacity limit of the adapter or an artifact of the specific data distribution or interference patterns in the benchmark. The paper needs to clarify the dataset size, the nature of the “slots” being written, and whether the linear drop post-saturation holds across different task types or is specific to the synthetic benchmark.

Third, the results for OLoRA-tail in Section 3.2.2 are promising, particularly the stability at rank $r=1$. However, the comparison against standard LoRA shows a dramatic degradation for the baseline (from +15% to -18%). The text mentions “6 random seeds” for the error bars in Figure 3.4, but it is not explicitly stated if the standard LoRA baseline was evaluated with the same rigorous seed count to ensure the degradation is a consistent failure mode and not a seed-specific anomaly. Given the high sensitivity of low-rank RL, a larger seed count ($n \geq 5$) for the baseline comparison is necessary to robustly support the claim that the failure is due to initialization geometry rather than optimization noise.

Finally, the trillion-scale MoE experiments (Section 2.3) are critical to the “Scale Up” argument. The claim that Router Replay R3 stabilizes training is supported by curves, but MoE RL is notoriously high-variance. The figures show single-run trajectories. To validate the robustness of

the solution, the authors should provide error bands (standard deviation) across multiple runs or explicitly state the number of runs averaged. A single stable run does not prove the method is reliable at scale; it only proves it *can* work.

In summary, the paper’s framework is sound, but the empirical evidence requires stronger statistical backing and more transparent experimental controls to support the specific quantitative claims made.

Action items.

- **[science]** The claim that diversity among 198 LoRA variants yields a +0.0533 accuracy gain over repetition (Section 4.3) lacks statistical significance testing. Please report p-values or confidence intervals for the difference between the Collaboration and Repetition curves to rule out random variance.
- **[science]** The ‘DishNameBenchmark’ capacity law (10^{-3} to 10^{-2} tokens/param) is presented as a sharp transition, but the experimental design (data permutation/masking) is not fully described. Clarify if the ‘saturation’ is due to interference or capacity limits, and provide the specific dataset size and composition used for this benchmark.
- **[science]** The OLoRA-tail initialization results (Section 3.2.2) show a +11.5% gain on Qwen3-30B, but the baseline comparison uses a single seed or unspecified seed count for the standard LoRA degradation. Reproduce the low-rank ($r=1$) comparison with a larger seed count (e.g., $n \geq 5$) to confirm the stability claim is not an outlier.
- **[science]** The trillion-scale Kimi K2 experiment (Section 2.3) claims a 10% compute footprint reduction but provides no error bars or variance metrics on the reward curves. Given the high variance typical of MoE RL, include standard deviation bands or multiple run averages to validate the stability of the Router Replay R3 fix.

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The statistical analysis in this paper is generally rigorous, particularly in the design of the rank-sweep experiments (Section 3.2.1) which explicitly separates mean performance from best-case performance across 216 runs. This approach correctly identifies reliability as the bottleneck for low-rank adapters rather than capacity. However, several key quantitative claims lack the necessary statistical framing to be fully reproducible or verifiable.

First, in Section 4.3, the paper fits a linear model to the relationship between model count (k) and accuracy ($\text{accuracy} \approx 0.386 + 0.0172 \ln(k)$) with an $R^2 \approx 0.888$. While the fit appears strong, the paper does not report the standard errors of the coefficients or the confidence intervals for the predictions. Given that the dependent variable (accuracy) is derived from majority voting over a finite number of samples (200 sources), the variance of the accuracy estimate itself is

non-trivial. Without confidence intervals, it is difficult to assess whether the observed gains at high k (e.g., $k = 198$) are statistically distinguishable from the saturation point of the repetition baseline.

Second, in Section 3.2.2, the authors claim OLoRA-tail achieves a significant improvement over standard LoRA (e.g., 35.5% vs 24.0% on Qwen3-30B). While Figure 3.4 indicates error bars representing standard deviation across 6 seeds, the text does not explicitly state whether these differences are statistically significant. With only 6 seeds, the power to detect differences is limited, and a formal test (e.g., paired t-test or Wilcoxon signed-rank test) should be reported to rule out the possibility that the observed gains are due to random seed variance.

Finally, the “sharp capacity transition” described in Section 4.1 regarding LoRA memory capacity relies on a visual inspection of a curve. To support the claim of a “sharp” transition versus a gradual degradation, the authors should provide the confidence intervals for the accuracy measurements around the critical threshold (10^{-3} tokens/parameter). This would clarify whether the drop is a distinct regime change or a smooth function of capacity.

Overall, the experimental design is sound, but the reporting of statistical significance and uncertainty intervals needs to be strengthened to support the specific quantitative claims made.

Action items.

- **[science]** Section 4.3 (Model-count experiment): The claim of a linear fit ($R^2 = 0.888$) for accuracy vs. $\ln(k)$ lacks reported standard errors for the slope/intercept or confidence intervals. Given the discrete nature of majority voting, provide the 95% CI for the predicted accuracy at $k=198$ to validate the extrapolation.
- **[science]** Section 3.2.1 (Rank reduction): The 216-run sweep ($9 \text{ ranks} \times 4 \text{ batches} \times 6 \text{ seeds}$) is robust, but the text claims ‘across-seed means degrade’ at low rank without reporting the variance or standard deviation of these means. Include error bars or a statistical test (e.g., ANOVA) confirming the mean difference between rank-1 and rank-16 is significant beyond seed noise.
- **[science]** Section 3.2.2 (OLoRA-tail): The reported gain of +11.5 percentage points (35.5% vs 24.0%) on Qwen3-30B lacks a measure of statistical significance. With only 6 seeds mentioned in Figure 3.4 caption, report the p-value (e.g., via paired t-test) to ensure the improvement is not due to random initialization variance.
- **[science]** Section 4.1 (LoRA memory capacity): The ‘sharp capacity transition’ at 10^{-3} – 10^{-2} tokens/parameter is described qualitatively. Provide the confidence intervals for the accuracy drop-off points to confirm the transition is distinct from a gradual degradation curve.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript presents a compelling and ambitious vision for scaling Parameter-Efficient Fine-Tuning (PEFT) to support millions of personal models. The prose is generally sophisticated, with a strong narrative arc that effectively uses biological analogies to frame the “Scale Up, Scale Down, Scale Out” framework. The technical depth is evident, and the writing successfully conveys complex system interactions.

However, the current draft contains several significant writing-quality issues that prevent it from being publication-ready. The most pervasive issue is the presence of the custom LaTeX command `\pony{}` throughout the text (e.g., in the Introduction, Section 3, Section 5, and Conclusion). These commands wrap entire paragraphs or sentences, likely serving as internal editorial markers or placeholders for specific formatting or review notes. Their presence in the final text is jarring, disrupts the reading flow, and suggests the manuscript has not been fully cleaned of draft-stage artifacts. These must be removed or replaced with standard text.

Additionally, there are signs of incomplete editing in specific sections. The caption for the figure comparing Rank-1 OLoRA-tail versus LoRA (Figure `rank1_8b_30b_results`) appears truncated in the source, ending with “Error bars sh,” which indicates a copy-paste error or incomplete sentence that needs correction.

Finally, the bibliography requires attention. The entry for the paper itself lists an LLM agent (“qwen.qwen3.5-122b”) alongside human authors in a format that mimics a human name, which is confusing and inappropriate for a formal publication. The author list should be standardized to reflect only human contributors or clearly distinguish AI contributions if required by the venue, but not in a way that mimics a human name in the author field.

Addressing these mechanical and editorial issues will significantly improve the readability and professionalism of the paper, allowing the strong scientific content to shine.

Action items.

- **[writing]** The manuscript contains numerous instances of the custom LaTeX command `\pony{}` wrapping entire paragraphs or sentences (e.g., Introduction, Section 3, Section 5, Conclusion). These commands appear to be internal editorial markers or placeholders that have not been removed or defined. They disrupt the reading flow and must be stripped or replaced with standard text before publication.
- **[writing]** Several figure captions and table descriptions contain raw LaTeX formatting artifacts or incomplete sentences that break the narrative flow. For example, the caption for Figure 1 in the ‘Scale Down’ section (`rank1_8b_30b_results.pdf`) ends abruptly with ‘Error bars sh’ in the source text provided, suggesting a truncation or copy-paste error in the final draft.
- **[writing]** The bibliography and citation keys show signs of automated generation or inconsistency. For instance, the author list in the bibliography entry for the paper itself includes a mix of human names and an LLM agent (‘qwen.qwen3.5-122b’) formatted as a human author, which is confusing and unprofessional for a final manuscript. Ensure all author attributions are consistent and human-readable.