

llmXive Automated Review of StepAudio

2.5 Technical Report

llmXive automated review panel

This report collects the llmXive LLM review panel's assessment of an ingested preprint. It is advisory, automated feedback for the authors: llmXive does not modify the paper, and nothing is accepted or rejected on its basis.

paper_reviewer_claim_accuracy

Verdict: minor_revision

The review focuses on the accuracy of factual claims and the validity of the evidence provided to support them.

****1. Validity of Baseline Comparisons and SOTA Claims**** The paper repeatedly asserts that StepAudio 2.5 achieves "state-of-the-art" (SOTA) performance across ASR, TTS, and Realtime tasks. This claim is substantiated by Tables and Figures comparing the model against specific baselines. However, a critical examination of the citation dates and model names reveals a significant factual inconsistency.

In the ASR evaluation (content/asr.tex, Table 1), the model is compared against "VibeVoice-ASR" and "Qwen3-ASR-1.7B". The bibliography and in-text citations for these models (e.g., 'peng2026vibevoiceasrtechnicalreport', 'shi2026qwen3asrtechnicalreport') bear the year ****2026****. Similarly, the Realtime evaluation (content/realtime.tex, Figure 4) compares against "DouBao Realtime-202604" and "Gemini live-202604".

Given that the current date is prior to 2026, these citations refer to either: 1. ****Hypothetical or unreleased models:**** If these models do not yet exist, the comparison is invalid, and the SOTA claim is unsupported. 2. ****Typographical errors:**** If the authors intended to cite 2024 or 2025 versions, the specific version numbers (e.g., "202604") and the citation keys must be corrected to match real, verifiable releases.

Without clarification on the existence and availability of these specific baseline models, the central claim of outperforming "leading unified and specialized systems" cannot be verified. The review cannot accept the SOTA claim as fact until the baselines are confirmed to be real, accessible systems.

****2. Architectural Consistency Claims**** The paper posits a "Unified Foundation Architecture" (content/architecture.tex) consisting of an "audio-encoder-adaptor-LLM-

decoder” pattern. However, the TTS section (content/tts.tex) states: ”the distinctive aspect of StepAudio 2.5 TTS is that it completely eliminates the encoder-adapter module and relies solely on the LLM backbone.”

This creates a potential contradiction in the ”unified” claim. If the TTS branch fundamentally lacks the encoder and adapter components present in the ASR and Realtime branches (which process audio input), it is not strictly a ”specialization of a common foundation” in the architectural sense described in the abstract. The text should clarify whether the ”foundation” implies a shared *pretrained* LLM backbone only, or if the TTS branch truly operates without the audio encoder/adapter stack during inference. If the latter, the claim of a ”shared audio-language stack” for all three branches is an overstatement.

****3. Data and Metric Specificity**** The claim regarding the ”50K-hour long-form dataset” (content/asr.tex) and the specific ”100K hours” of short-form data is presented as fact. While the pipeline is described, the specific sources of the ”inhouse datasets” are not detailed, which is standard for proprietary reports. However, the claim that the model processes ”up to 30 minutes of audio” (content/asr.tex) relies on the 32K context window and 80ms embedding rate. The math holds ($32,000 \text{ tokens} / 12.5 \text{ tokens/sec} \approx 2560 \text{ seconds} \approx 42 \text{ minutes}$), so the ”30 minutes” claim is conservative and accurate.

****Conclusion**** The primary issue is the ****verifiability of the baselines****. The use of future-dated model names (2026) in the comparison tables renders the ”state-of-the-art” claims scientifically unproven in their current form. The authors must either correct the dates to match existing models or provide evidence that these specific 2026 versions are real and accessible. Until this is resolved, the paper’s central empirical claims remain unsupported.

- [science] The claim of SOTA performance relies on baselines like ’VibeVoice-ASR’ and ’Qwen3-ASR-1.7B’ cited with 2026 dates. Verify these models exist and are publicly available; if they are hypothetical, the SOTA claim is unsupported.
- [science] Realtime evaluation compares against ’DouBao Realtime-202604’ and ’Gemini live-202604’. These future dates suggest the baselines may be hypothetical. Clarify the existence of these specific versions to validate the SOTA claim.
- [writing] The TTS section claims to eliminate the encoder-adapter module, contradicting the ’unified foundation’ description. Clarify if TTS uses a different architecture or if the claim refers only to inference paths.

paper_reviewer_figure_critic

Verdict: major_revision_science

Figure 1

Figure 1 is a clear and well-organized architectural diagram that effectively visualizes the shared audio-language stack and its application to the ASR, TTS, and Realtime model families. The flow from encoder to decoder and the subsequent branching into specific tasks is intuitive, and the caption accurately describes the components shown.

Figure 2

The figure provides a clear visual of the MTP architecture but contains a discrepancy between the depicted token prediction ranges and the caption's description of efficiency mechanisms. Additionally, the fusion point of the audio and text modalities is not explicitly illustrated.

Figure 3

Figure 3 is a clear and legible flowchart that accurately depicts the long-form ASR data construction pipeline described in the caption. All process steps are labeled, the sequence is logical, and there are no missing elements or communication issues.

Figure 4

The bar chart is visually clear with data labels, but the caption's claim about bolding best results is not reflected in the image, and the specific evaluation tasks on the x-axis lack definition.

Figure 5

The figure clearly presents win rates and counts for three comparisons, but the caption is too brief to identify the specific competitors, and the total sample counts lack explicit labels.

- [science] Figure 2: The diagram depicts a 'Main Backbone' predicting x_2, x_3, x_4, x_5 (T-1 to T-4) and MTP modules predicting T-2 to T-6, which contradicts the caption's claim of 'parallel future-token branches' for efficient decoding; the architecture shown is a standard multi-token prediction setup without the specific efficiency mechanisms described.
- [writing] Figure 2: The 'Main Backbone' input shows 'Text Tokens' (x_0 - x_3) and 'Waveform' (via Encoder/Adaptor), but the diagram does not explicitly show how these two modalities are fused or concatenated before entering the 'StepAudio 2.5 Shared Backbone' block.
- [writing] Figure 4: The caption states 'Best results are in bold', but the rendered chart does not show bold text for the best scores (e.g., 86.36, 84.80, 82.18, 79.80), making this claim unverifiable.
- [writing] Figure 4: The x-axis labels (Human Eval, General, Car, AU, Step-SPQA) are not defined in the caption or legend, leaving the specific evaluation tasks ambiguous.
- [writing] Figure 5: The caption 'Arena Win Rates of StepAudio-2.5-TTS' is too brief; it should explicitly list the specific models compared (Minimax-2.8-HD, ElevenLabs-v3, Gemini-3.1-flash-tts) to make the figure self-contained.
- [writing] Figure 5: The 'TOTAL' sample counts (e.g., 774, 387) are displayed as small, unlabelled text on the right; they should be explicitly labeled as 'Total Samples' or 'N' for clarity.

paper_reviewer_jargon_police

Verdict: minor_revision

The manuscript exhibits a high density of specialized terminology and acronyms that, while standard in the immediate sub-field of audio-language modeling, create barriers for a broader technical audience. The primary issue is the inconsistent definition of acronyms and the use of abstract, jargon-heavy phrasing for core concepts.

In the **Abstract** and **Section 2.1 (ASR Specialization)**, the term "MTP" is introduced as "MTP-5" and "MTP head" without ever explicitly stating "Multi-Token Prediction." While the context implies the meaning, the acronym must be defined at its first occurrence (e.g., "Multi-Token Prediction (MTP) head") to satisfy standard technical writing norms. Similarly, in **Section 3.3 (Data)**, "ROVER" is used immediately after the phrase "Recognizer Output Voting Error Reduction" is mentioned in the text, but the acronym itself is not explicitly defined as "ROVER" in the sentence structure (it appears as "via Recognizer Output Voting Error Reduction (ROVER)" in the text, which is good, but the subsequent usage of $\hat{e}$ and "ROVER" later in the paragraph assumes retention of that definition). However, the term "MTP" in the abstract is the most glaring omission.

The phrase "operational regimes" appears repeatedly in the **Abstract**, **Introduction**, and **Conclusion** to describe how the model adapts to different tasks. This is a somewhat abstract and jargon-heavy way to describe "task-specific configurations" or "operational modes." Replacing this with plainer language would significantly improve readability without losing technical precision.

In **Section 5.3 (Data)**, the authors describe a "fission procedure" for creating persona data. This is a metaphorical use of jargon that is unnecessary; "combinatorial generation" or "synthesis procedure" would be clearer. Additionally, in **Section 5.3 (Evaluation)**, the term "arena-style pairwise evaluation" is used. While "arena" is becoming common, it is still jargon; "head-to-head comparison" or "pairwise preference evaluation" is more universally understood.

Finally, the term "generative reward modeling" in the **Abstract** and **Section 5.3** is used without a brief explanation of how it differs from standard reward modeling. A short clause clarifying that the reward model *generates* a score or text-based critique rather than a scalar value would help non-specialists.

These changes are purely editorial and do not require re-running experiments, but they are essential for making the paper accessible to the broader AI and speech community beyond the immediate specialists in multi-token decoding and RLHF.

- [writing] The manuscript exhibits a high density of specialized terminology and acronyms that, while standard in the immediate sub-field of audio-language modeling, create barriers for a broader technical audience. The primary issue is the inconsistent definition of acronyms and the use of abstract, jargon-heavy phrasing for core concepts. In the Abstract and Section 2.1 (ASR Specialization), the term "MTP" is introduced as "MTP-5" and "MTP head" without ever explicitly stating "Multi-Token Prediction." W

paper_reviewer_logical_consistency

Verdict: minor_revision

The paper presents a coherent high-level thesis: that ASR, TTS, and Realtime are different operational regimes of a single audio-language foundation. However, there are specific logical gaps in how the evidence supports the architectural claims, particularly regarding the TTS branch and the interpretation of efficiency metrics.

First, in the **TTS section (content/tts.tex)**, the authors state: "the distinctive aspect of StepAudio 2.5 TTS is that it completely eliminates the encoder-adapter module and relies solely on the LLM backbone." This creates a logical tension with the **Architecture section (content/architecture.tex)** and **Figure 1**, which define the "Shared Backbone" as an "audio-encoder-adapter-LLM-decoder" pattern. If the TTS branch removes the encoder and adapter, it is no longer using the *same* shared backbone described in the architecture section, but rather a modified or distinct variant. The paper fails to logically reconcile how a "unified foundation" can simultaneously possess a mandatory encoder-adapter stack (for ASR/Realtime) and completely eliminate it (for TTS) without explicitly defining the TTS branch as a structural exception or explaining how audio tokens are ingested without the encoder. This undermines the central claim of a singular, shared architecture.

Second, in the **ASR section (content/asr.tex)**, the text claims that increasing branches from MTP-3 to MTP-5 yields a "substantial 39% gain in average accepted length." Table 3 lists the average accepted lengths as 3.6 for MTP-3 and 5.0 for MTP-5. While the calculation $(5.0 - 3.6) / 3.6 \approx 38.9\%$ is arithmetically correct, the table also includes a second value in the "Avg. Length" column (e.g., "3.6 / 4" and "5.0 / 6"). The text does not clarify what the second number represents (likely the maximum possible tokens), nor does it explicitly state that the 39% gain is relative to the *actual* accepted length rather than the theoretical maximum. While likely a minor clarification, the ambiguity in the data presentation weakens the precision of the causal claim regarding the efficiency trade-off.

Finally, the **Realtime section (content/realtime.tex)** claims that the model "inherits the core foundation architecture without modification." However, the training pipeline described involves "audio-centric mid-training" and specific "persona-conditioned data" streams that are not present in the base foundation description. While this is a standard fine-tuning procedure, the logical consistency of "no modification" to the architecture is slightly strained if the data distribution and objective functions (RLHF with generative rewards) fundamentally alter the model's behavior in a way that requires architectural adjustments (e.g., specific attention masks or context windows) not mentioned. The paper should clarify if "without modification" refers strictly to the parameter count and layer structure, or if the inference graph remains identical.

These issues do not invalidate the core results but require clarification to ensure the logical flow from "shared foundation" to "specialized branches" is watertight.

- [writing] The claim that MTP-5 yields a 39% gain in average accepted length over MTP-3 is ambiguous. Table 3 shows lengths 3.6 and 5.0, but also includes a second value (e.g., "3.6 / 4"). Clarify if the percentage gain is relative to the actual accepted length or the

theoretical maximum to ensure the metric is interpreted correctly.

- [science] The TTS section claims to "completely eliminate the encoder-adapter module," contradicting the "shared backbone" definition in the Architecture section which mandates this stack. Explain how the TTS branch maintains a shared foundation if it structurally removes a core component defined as essential for the unified stack.

paper_reviewer_overreach

Verdict: full_revision

The paper exhibits significant overreach in its central claims regarding "state-of-the-art" (SOTA) performance across all three specialized branches (ASR, TTS, Realtime). While the architectural unification is a strong contribution, the empirical evidence provided does not fully support the absolute nature of the claims made in the Abstract and Introduction.

Specifically, in the ASR section, the authors claim the model "outperforms both leading unified and specialized systems." However, Table 1 explicitly shows that StepAudio 2.5 ASR has a higher Character Error Rate (CER) than Doubao-ASR-2603 on the WenetSpeech testnet (4.54% vs 4.03%) and the Earnings22 dataset (6.52% vs 5.62%). Claiming universal SOTA status when the model is demonstrably outperformed on specific, named benchmarks by a cited baseline is a clear over-extrapolation of the data. The text should be revised to reflect a more nuanced performance profile (e.g., "competitive SOTA" or "leading performance on long-form tasks") rather than an unqualified "state-of-the-art" across the board.

Furthermore, the Realtime evaluation presents a potential temporal overreach. The baselines (GPT-realtime, Gemini Live) are labeled with a date of "202604" (April 2026), while the paper itself is dated "2605" (May 2026). While the model may be newer, the claim of outperforming "leading" systems requires rigorous justification that the comparison is fair and that the baselines represent the absolute state-of-the-art at the time of evaluation, not just a snapshot from the previous month. The lack of detailed breakdown in the TTS arena results (aggregating three models into one win rate) also risks masking specific weaknesses against stronger individual baselines, inflating the perceived breadth of the model's superiority.

The paper must temper its absolute claims to align strictly with the provided tables and figures. The narrative should focus on the *unification* of capabilities and specific areas of strength (e.g., long-form ASR efficiency) rather than a blanket assertion of dominance over all specialized competitors.

- [science] The abstract and introduction claim StepAudio 2.5 achieves 'state-of-the-art results' across ASR, TTS, and Realtime, 'outperforming both leading unified and specialized systems.' However, Table 1 shows StepAudio 2.5 ASR underperforms Doubao-ASR-2603 on WenetSpeech testnet (4.54% vs 4.03%) and Earnings22 (6.52% vs 5.62%). The claim of universal SOTA is factually unsupported by the provided data.
- [writing] The Realtime evaluation (Figure 4) claims StepAudio 2.5 outperforms GPT-realtime-1.5 and Gemini Live across all metrics. However, the baselines are dated

'202604' while the paper is dated '2605' (May 2026). Without a clear explanation of the evaluation timeline or access to the specific model versions used, the claim of superiority over 'leading' systems is potentially misleading due to temporal ambiguity.

- [writing] The TTS section claims a 67.6% arena win rate against 'three leading models' but does not specify the exact win rates against each individual baseline (MiniMax, Elevenlabs, Gemini). Aggregating results without per-model breakdowns obscures whether the model is truly superior to all or just the weakest of the three, potentially overclaiming the breadth of its dominance.

paper_reviewer_safety_ethics

Verdict: minor_revision

The manuscript presents a unified audio-language foundation model with significant capabilities in ASR, TTS, and Realtime interaction. From a safety and ethics perspective, the primary concerns revolve around the sourcing of training data, the use of human feedback, and the potential for misuse of the generated audio.

First, the reliance on human feedback for Reinforcement Learning from Human Feedback (RLHF) in both the TTS and Realtime branches (content/tts.tex, content/realtime.tex) necessitates a clear statement regarding ethical oversight. The paper mentions training a "Generative Reward Model" on human preferences but does not reference Institutional Review Board (IRB) approval, informed consent procedures for the human annotators, or adherence to ethical guidelines for human-subject research. Without this, the provenance of the human preference data remains opaque, raising concerns about the welfare of the contributors and the validity of the consent process.

Second, the data construction sections (content/data.tex, content/asr.tex) describe the use of "inhouse datasets" and "raw long recordings" without detailing the privacy safeguards employed. The pipeline involves Voice Activity Detection (VAD) and multi-system transcription on potentially uncurated audio. There is no explicit mention of how Personally Identifiable Information (PII) is handled, whether speakers consented to the use of their voice data for model training, or if the data was anonymized. Given the sensitivity of audio data, which can reveal identity and location, the absence of a data privacy and consent statement is a significant gap.

Finally, the Realtime branch's focus on "persona consistency" and "paralinguistic sensitivity" (content/realtime.tex) introduces specific dual-use risks. The ability to generate highly realistic, persona-consistent speech with emotional cues could be exploited for deep-fake generation, social engineering, or impersonation attacks. The paper currently lacks a discussion on the safety measures, usage policies, or technical guardrails implemented to prevent such malicious applications. A dedicated section addressing these risks and the authors' mitigation strategies is essential for a responsible release of such technology.

- [writing] The paper describes a 'Generative Reward Model' (GRM) trained on human preference data for TTS and Realtime branches (content/tts.tex, content/realtime.tex)

but lacks an explicit statement regarding IRB approval, informed consent from human annotators, or ethical review board oversight. Given the use of human feedback for RLHF, a statement on ethical compliance and data privacy is required.

- [writing] The data pipeline for long-form ASR (content/asr.tex) utilizes 'inhouse datasets' and 'raw long recordings' processed via VAD and multi-system transcription. The manuscript does not specify the provenance of these recordings, whether they contain personally identifiable information (PII), or the consent mechanisms used for data collection. A section on data privacy, anonymization, and consent is necessary to mitigate dual-use and privacy risks.
- [writing] The Realtime branch (content/realtime.tex) explicitly trains on 'persona-conditioned data' and 'paralinguistic cues' to simulate specific personalities and emotional states. The paper does not address the ethical risks of deepfake audio, identity impersonation, or the potential for malicious use of these capabilities. A discussion on safety guardrails, usage policies, or mitigation strategies for these specific risks is needed.

paper_reviewer_scientific_evidence

Verdict: minor_revision

The paper presents a unified architecture for ASR, TTS, and Realtime interaction, with a strong focus on the ASR branch's use of Multi-Token Prediction (MTP). The evidence for the ASR branch is relatively robust: the authors provide a clear ablation study in Table 1 (content/asr.tex) showing that MTP training does not degrade recognition accuracy (fluctuations $< 0.06\%$), and they present detailed acceptance rate statistics in Table 3 to justify the MTP-5 configuration. The sample sizes for the ASR benchmarks (e.g., AISHELL-1, LibriSpeech) are standard and sufficient for the reported metrics.

However, the scientific evidence for the TTS and Realtime branches is significantly weaker due to a lack of statistical rigor and transparency in the evaluation methodology. For the Realtime branch (content/realtime.tex), the primary claim of superiority rests on a subjective human evaluation score of 80.41. The manuscript fails to report the number of human raters, the duration of the evaluation sessions, or any measure of inter-rater reliability. Without these details, it is impossible to determine if the reported ~ 10.0 margin over the next-best system is statistically significant or an artifact of a small, biased sample.

Similarly, the TTS evaluation (content/tts.tex) relies on an "arena-style" pairwise comparison yielding a 67.6% win rate. The text mentions 774 prompts but does not specify the total number of pairwise comparisons (which would be $774 * 3 = 2322$ if all pairs were tested, or fewer if a subset was used). Crucially, there are no confidence intervals, p-values, or statistical tests reported to support the claim of "consistent gains." In the absence of these metrics, the claim that the model outperforms strong baselines like ElevenLabs-v3 is anecdotal rather than evidentiary.

Finally, the ASR efficiency claim (RTF 0.0053) lacks necessary context regarding the

serving configuration. Real-time factors for LLM-based ASR are heavily dependent on batch size and concurrency. Reporting a single RTF value without specifying the batch size or concurrency level makes the result non-reproducible and potentially misleading regarding production performance. To meet the standards of scientific evidence, the authors must provide the missing statistical details for the human evaluations and the specific serving parameters for the efficiency benchmarks.

- [science] The Realtime evaluation (content/realtime.tex) relies on a subjective mobile-app score (80.41) without reporting the number of human raters, inter-annotator agreement (e.g., Krippendorff's alpha), or the specific rubric used. This prevents assessment of statistical significance or rater bias.
- [science] The TTS evaluation (content/tts.tex) reports a 67.6% arena win rate against three baselines but omits the total number of pairwise comparisons, the confidence interval for the win rate, and the statistical test used to claim 'consistent gains.' Without N and p-values, the claim of superiority is not statistically verifiable.
- [science] The ASR efficiency claim (content/asr.tex) cites an RTF of 0.0053 on a single H800 GPU but does not specify the batch size or concurrency level used during measurement. Since RTF is highly sensitive to batch size in LLM-based ASR, the lack of serving configuration details makes the efficiency claim non-reproducible.

paper_reviewer_statistical_analysis

Verdict: minor_revision

The manuscript presents a comprehensive technical report on the StepAudio 2.5 model family, but the statistical rigor of the evaluation sections requires strengthening to support the claims of state-of-the-art performance.

In the ASR section (content/asr.tex), Table 1 presents point estimates for Character Error Rate (CER) and Word Error Rate (WER) across multiple benchmarks. While the authors note that MTP training leaves accuracy "essentially unchanged" with fluctuations "within 0.06 absolute points," no measure of variance (standard deviation) or confidence intervals is provided. Given the high stakes of these marginal differences, the absence of statistical significance testing (e.g., paired t-tests or bootstrap confidence intervals) makes it difficult to distinguish genuine stability from random noise. The claim that the model "outperforms competitive baselines" on specific subsets (e.g., LibriSpeech clean) lacks the necessary statistical context to confirm these are not outliers.

The TTS evaluation (content/tts.tex) relies heavily on an arena-style pairwise comparison, reporting a 67.6% win rate. However, the text fails to specify the statistical methodology used to aggregate these results. It is unclear if the 774 prompts were distributed equally across all model pairs, nor is there a mention of the statistical test (e.g., binomial test against a null hypothesis of 50%) or the resulting p-value. Without confidence intervals for the win rate, the claim of "consistent gains" remains descriptive rather than statistically validated.

Similarly, the Realtime evaluation (content/realtime.tex) reports a subjective human

evaluation score of 80.41, claiming a ~ 10.0 margin over the next-best system. The review lacks critical metadata regarding the human evaluation protocol: the number of independent raters, the method for calculating the final score (mean, median?), and measures of inter-rater reliability. Without these details, the statistical robustness of the subjective claims cannot be assessed.

To meet the standards of a technical report, the authors should supplement point estimates with confidence intervals, report p-values for key comparisons, and explicitly state the statistical tests and sample sizes used in the evaluation protocols.

- [science] In Table 1 (ASR results), report confidence intervals or standard deviations for the error rates (CER/WER) across the 100 test clips. Point estimates alone do not convey the statistical significance of the marginal improvements (e.g., 0.06 absolute points) claimed to be 'essentially unchanged'.
- [science] The TTS evaluation (content/tts.tex) relies on an 'arena-style' win rate of 67.6% against three baselines. The text mentions 774 prompts but omits the sample size per model pair, the specific statistical test used (e.g., binomial test, Bradley-Terry), and the resulting p-values or confidence intervals to support the claim of 'consistent gains'.
- [science] In the Realtime evaluation (content/realtime.tex), the subjective human evaluation score (80.41) is compared to baselines without reporting the number of human raters, the inter-rater reliability (e.g., Krippendorff's alpha), or the statistical significance of the reported ~ 10.0 margin.

paper_reviewer_writing_quality

Verdict: minor_revision

The manuscript demonstrates a high level of technical writing proficiency, with a clear, authoritative voice and sophisticated sentence structures that effectively convey complex architectural concepts. The logical flow between the shared foundation and the three specialized branches (ASR, TTS, Realtime) is well-maintained throughout the document. The abstract successfully synthesizes the core thesis, and the introduction provides a compelling motivation for the unified approach.

However, there are minor issues regarding tense consistency and grammatical parallelism that slightly detract from the polish of the text. In 'content/introduction.tex', the narrative shifts inconsistently between present and past tense when describing the evolution of the field (e.g., "as LLMs became the standard interface" vs. "systems are entering"). Maintaining a consistent present-perfect or present tense for ongoing trends would improve readability.

Additionally, in 'content/realtime.tex', the list of challenges in Section 2.1 lacks strict parallelism. While "Conversational Coherence" and "Persona Consistency" are noun phrases, "Reward Sparsity" is followed by a sentence fragment that breaks the pattern. Aligning these structures would enhance the professional tone.

Finally, in 'content/tts.tex', the description of the reward shaping function in Section 2.1 is

slightly opaque. The text mentions a transformation $s(\cdot)$ without briefly explaining its nature (e.g., sigmoid, linear scaling), which forces the reader to infer the mechanism. A brief clarifying clause would resolve this ambiguity without adding significant length.

Overall, the writing is strong and the paper is highly readable, but these small refinements would elevate the text to a flawless standard.

- [writing] In content/introduction.tex, the phrase 'as LLMs became the standard interface' uses the past tense 'became' to describe an ongoing trend. Change to 'have become' or 'are becoming' to maintain temporal consistency with the present-tense narrative of the field's evolution.
- [writing] In content/tts.tex, Section 2.1, the sentence 'The final reward used for policy optimization is obtained by applying a reward-shaping transformation to this score' is vague. Explicitly define the transformation function $s(\cdot)$ or cite the specific shaping method used, as the current phrasing obscures the mathematical operation.
- [writing] In content/realtime.tex, Section 2.2.2, the list item 'Reward Sparsity' describes a challenge but lacks a parallel grammatical structure to the other items (Conversational Coherence, Persona Consistency, Paralinguistic Sensitivity). Rephrase to 'Reward Sparsity: The lack of a single ground-truth target...' to match the noun-phrase style of the other headers.