

llmXive Automated Review of LongLive-2.0: An NVFP4 Parallel Infrastructure for Long Video Generation

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer’s exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer’s section also names the underlying model that produced it.

This paper’s panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_claim_accuracy.md

The paper generally maintains high factual accuracy regarding its core contributions and experimental results. The claims about NVFP4 training and inference speeds, memory reductions, and the “clean pipeline” are well-supported by the provided tables (Table 1, Table 3, Table 4) and the described methodology. The citations to NVFP4 specifications (nvidia2024blackwell, ocp2023mx) and related quantization works (cook2025four, abecassis2025pretraining) appear appropriate and support the technical definitions provided.

However, there are minor discrepancies in unit reporting and comparative baselines that require correction to ensure the claims are strictly accurate:

1. **Unit Discrepancy in Teaser:** The teaser figure caption (main-llmxive.tex, lines 108-112) states training latency is reduced from “1372.9 ms” to “639.5 ms”. Table 1 (sec/05_experiment.tex, line 108) clearly lists these values as “1372.9” and “639.5” with the column header “(s)” for seconds. A latency of ~1.3 seconds per iteration is plausible for long video training, whereas 1.3 milliseconds is physically impossible for a 5B model. The caption incorrectly uses “ms”, which misrepresents the scale of the result.
2. **Attribution of Speedup:** The abstract and teaser claim a “1.84x faster inference” speedup. Table 3 (sec/05_experiment.tex, line 136) shows the BF16 baseline (4 steps) at 24.8 FPS and the final NVFP4 model (2 steps) at 45.7 FPS. The ratio 45.7/24.8 is indeed ~1.84. However, this speedup is a compound effect of NVFP4 quantization *and* the reduction from 4 to 2 denoising steps (distillation). The text implies NVFP4 alone achieves this, or conflates the two optimizations. The claim should be refined to state that the *combination* of NVFP4 and 2-step distillation achieves this speedup, as the NVFP4 4-step model (29.7 FPS) only offers a ~1.2x speedup over the BF16 baseline.
3. **Compression Ratio Clarity:** In Section 3.2, the claim of a “3.6x KV-cache compression ratio” is mathematically derived from the 4-bit data size (0.5 bytes) plus the specific overhead model (9/8 bytes total). While the math holds, the phrasing “close to a 3.6x” is slightly ambiguous regarding whether it includes the scale factors in the denominator. The current text is acceptable but could be more precise by explicitly stating the formula used ($4 / 1.125$).

These issues are primarily presentational and do not invalidate the scientific findings, but they should be corrected to ensure the paper’s claims are rigorously accurate.

Action items.

- **[writing]** Teaser caption (main-llmxive.tex, lines 108-112) claims training latency is 1372.9 ms, but Table 1 (sec/05_experiment.tex, line 108) reports 1372.9 s. The unit ‘ms’ is a typo that misrepresents the magnitude of the speedup.

- **[writing]** Abstract (line 48) claims 1.84x inference speedup. Table 3 (sec/05_experiment.tex, line 136) shows this ratio comes from comparing 4-step BF16 (24.8 FPS) to 2-step NVFP4 (45.7 FPS). The claim conflates quantization with step distillation; clarify that the speedup requires both.
- **[writing]** Section 3.2 (sec/03_inference_infra.tex, line 168) claims a 3.6x KV-cache compression ratio. While $4/(9/8) \approx 3.55$, the text implies this is the total ratio including overhead. Clarify that 3.6x is the theoretical payload compression before scale overhead.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_figure_critic.md

Figure 1

The figure is incomplete as it only displays the iteration speed data while the caption explicitly promises a second chart for peak memory. Additionally, the x-axis label ‘Training Video Frames’ conflicts with the caption’s terminology regarding sequence lengths.

Figure 2

The figure effectively demonstrates the visual difference between the model with and without the multi-shot attention sink, but the caption contains a grammatical error in the final sentence.

Figure 3

The figure fails to provide a valid comparison because the PTQ and Ours rows display entirely different video scenes rather than the same content processed by different methods, rendering the visual evidence for the caption’s claims invalid.

Figure 4

The figure effectively visualizes the comparison between the two strategies, but the caption is truncated at the end, and the third text label is positioned ambiguously, potentially confusing the reader about the row definitions.

Figure 5

The figure provides a high-level overview but contains ambiguities in the training pipeline regarding the role of LoRA and lacks clear data flow connections in the inference section for VAE decoding.

Figure 6

Figure 6 effectively illustrates the training infrastructure and load balancing concepts, but the legend in the middle panel is incomplete as it omits fill patterns for two entries, and the speedup claim in the right panel lacks a precise visual indicator.

Figure 7

The figure effectively contrasts the pipeline steps of previous methods with LongLive 2.0, but the diagram for LongLive 2.0 contradicts the caption by including a DMD loop that the text claims is bypassed.

Figure 8

The figure provides a high-level schematic of the DMD training infrastructure but lacks clarity on the specific data types (BF16 vs NVFP4) used in the LoRA modules and suffers from poor legibility in the loss calculation and update flow annotations.

Figure 9

The figure effectively illustrates the asynchronous decoding pipeline and memory benefits, but the specific memory reduction claim lacks a precise visual pointer, and the timeline alignment for the initial idle state is slightly inconsistent with subsequent chunks.

Figure 10

Figure 10 provides a schematic overview of the attention sink mechanism but lacks the quantitative data or detailed annotations necessary to scientifically demonstrate the attention distribution. Additionally, the caption is too brief to explain the specific visual elements shown in the diagram.

Action items.

- **[science]** Figure 1: The caption claims the figure shows ‘Iteration speed and peak memory’ with ‘Left: iteration speed. Right: peak memory,’ but the rendered image contains only a single chart showing ‘Training Time per Iteration’ (speed). The peak memory data is missing.
- **[science]** Figure 1: The x-axis label ‘Training Video Frames’ (128, 256, 512, 768) contradicts the caption’s reference to ‘sequence lengths’ and ‘long contexts,’ creating ambiguity about whether the x-axis represents frame count or token sequence length.
- **[writing]** Figure 2 caption: The sentence ‘With the multi-shot attention sink stabilizes shot-level appearance’ is grammatically incorrect and should be rephrased (e.g., ‘With the

multi-shot attention sink, shot-level appearance is stabilized’).

- **[science]** Figure 3: The ‘PTQ’ and ‘Ours’ rows depict completely different video scenes (different furniture, lighting, and background portraits), making a direct comparison of ‘temporal visual quality’ or facial details scientifically invalid.
- **[writing]** Figure 3: The caption states the first column shows the ‘initial frame,’ but the images in the ‘Shot 1’ column are visually distinct between the PTQ and Ours rows, contradicting the premise of a controlled comparison.
- **[writing]** Figure 4: The caption text is truncated at the end (‘...various t’), cutting off the sentence and likely the citation.
- **[science]** Figure 4: The label ‘DMD on Diffusion Model (with AR mask)’ is visually unaligned and appears to be a third category rather than a description of the ‘Standalone LoRA injection’ row, creating ambiguity about the experimental setup.
- **[science]** Figure 5: The ‘Training Infra’ box shows ‘LoRA Few-step’ as a distinct input to the final model, but the caption describes LoRA as ‘standalone weights’ derived in parallel. The diagram implies LoRA is a training step added to the AR model, whereas the text suggests it is a separate injection for inference, creating ambiguity about the training pipeline’s output.
- **[writing]** Figure 5: The ‘Inference Infra’ box lists ‘VAE Async Decode’ but does not visually connect the VAE to the ‘Model’ output in the same way the ‘Training Infra’ connects components, making the data flow for asynchronous decoding unclear.
- **[writing]** Figure 6: The legend at the top of the middle panel defines ‘Video Seq.’ and ‘Halo’ with specific fill patterns, but the ‘Clean Latent Seq.’ and ‘Noisy Latent Seq.’ entries in the same legend lack the corresponding fill pattern swatches, making them visually ambiguous.
- **[writing]** Figure 6: The ‘NVFP4 GEMM Speedup 2-4x’ label in the right panel is a floating text annotation without a clear visual pointer or bracket indicating exactly which components (e.g., DGDRAD, WGRAD, FPROP) constitute the speedup.
- **[science]** Figure 7: The ‘LongLive 2.0’ column depicts a feedback loop labeled ‘DMD’ and ‘LoRA Weights’ on the AR Model, but the caption explicitly claims the method ‘bypasses... intermediate DMD’ and achieves results by ‘injecting standalone LoRA weights’. The diagram contradicts the text by showing DMD as part of the LongLive 2.0 pipeline rather than a separate pre-training step.
- **[writing]** Figure 7: The ‘LongLive 2.0’ column contains a red arrow and text (‘LoRA Weights’) that are visually cluttered and overlap with the ‘AR Model’ box, making the diagram difficult to parse.
- **[science]** Figure 8: The diagram shows ‘LoRA BF16’ modules attached to the Generator and Fake Score models, but the caption describes a ‘low-precision NVFP4 setup’ without explaining the presence of BF16 LoRA weights or how they interact with the NVFP4 quantization.

- **[writing]** Figure 8: The ‘update’ arrows and ‘Diffusion Loss’/‘DMD Loss’ boxes are extremely small and low-contrast, making the specific gradient flow paths difficult to trace and read.
- **[science]** Figure 9: The diagram labels the top row ‘NVFP4 KV Cache Window’ but the text ‘Memory 10GB↓’ is placed ambiguously near the window boundary without a clear pointer indicating if it refers to the window size or total memory reduction.
- **[writing]** Figure 9: The ‘Wait / Idle’ block in the bottom row is unlabeled with a chunk index (0-4) like the others, making the timeline alignment slightly ambiguous compared to the rest of the sequence.
- **[science]** Figure 10: The diagram illustrates the ‘Multi-shot Attention Sink’ mechanism with visual examples and a heatmap, but it lacks a quantitative plot (e.g., attention weights vs. token index) or explicit numerical labels to substantiate the claim of ‘sink’ behavior or the specific attention distribution.
- **[writing]** Figure 10: The caption is a single phrase (‘Multi-shot Attention Sink for streaming multi-shot inference’) that merely names the figure rather than explaining the visual components (e.g., the meaning of the blue squares, the ‘Key’/‘Query’ arrows, or the specific role of the ‘Global-level Sink’ vs ‘Shot-level Sink’).

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_jargon_police.md`

The manuscript relies heavily on domain-specific acronyms and proprietary hardware terminology that significantly raises the barrier to entry for non-specialist readers. While the technical depth is appropriate for a systems-focused venue, the “jargon density” is high, and several critical terms are used without definition.

First, the core acronym **NVFP4** is introduced in the Abstract and Title without any explanation of what it represents (NVIDIA 4-bit Floating Point). The paper assumes the reader knows this refers to the E2M1 format with hierarchical scaling. This should be explicitly defined upon first mention (e.g., “NVFP4, a 4-bit floating-point format...”). Similarly, **W4A4** is used to describe the inference precision but is never expanded to “4-bit weights and 4-bit activations.”

Second, standard deep learning acronyms are frequently used without expansion. **SP** (Sequence Parallelism) and **AR** (Auto-Regressive) appear in the Abstract and Introduction without being spelled out. **DMD** (Distribution Matching Distillation) is treated as a known entity in the Abstract, despite being a specific algorithmic technique. **DiT** (Diffusion Transformer) is used throughout Section 1 and 2 without definition. **VAE** (Variational Autoencoder) appears in Section 3.3 without expansion. **RHT** (Random Hadamard Transform) is introduced in Section 2.2 as a “stabilization technique” without defining the acronym.

Finally, the text frequently references hardware-specific concepts like “Blackwell GPUs” and

“Tensor Cores” without briefly contextualizing why these specific architectures are required for the claimed speedups (i.e., native support for the specific low-precision formats). While the paper is technically sound, the lack of definitions for these acronyms and terms excludes readers who are not deeply embedded in the current wave of low-precision training literature. A pass of the text to spell out these terms at first use is necessary to improve accessibility.

Action items.

- **[writing]** Define ‘NVFP4’ at first use in the Abstract and Introduction. Currently, the term appears as a proper noun without explanation of the underlying format (E2M1) or scaling hierarchy for non-specialist readers.
- **[writing]** Replace or define ‘SP’ (Sequence Parallelism) and ‘AR’ (Auto-Regressive) at their first occurrence in the Abstract. Acronyms should be spelled out before abbreviation to ensure accessibility.
- **[writing]** Define ‘DMD’ (Distribution Matching Distillation) upon first mention in the Abstract. The term is used as a standard method without context for readers unfamiliar with specific distillation literature.
- **[writing]** Clarify ‘W4A4’ in the Abstract and Section 3.1. While common in quantization circles, the specific meaning (4-bit weights, 4-bit activations) should be explicitly stated for a broader audience.
- **[writing]** Define ‘DiT’ (Diffusion Transformer) at first use in Section 1. The acronym is used frequently but not explicitly defined in the main text, assuming prior knowledge of the architecture.
- **[writing]** Define ‘RHT’ (Random Hadamard Transform) in Section 2.2. The acronym is introduced without expansion, which may obscure the specific stabilization technique being referenced.
- **[writing]** Define ‘VAE’ (Variational Autoencoder) at first use in Section 3.3. While common, the full term should be provided for readers outside the specific generative modeling sub-field.

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The paper presents a coherent logical argument for the necessity of infrastructure co-design in long video generation. The premises regarding memory bottlenecks in AR training and inference are well-supported by the problem statement, and the proposed solutions (Balanced SP, NVFP4) follow logically from these premises. The causal chain linking “Balanced SP” to “balanced loss computation” and “reduced VAE overhead” is clearly articulated in Section 2.1 and Appendix B, with the mechanism (paired clean/noisy chunk ownership) explicitly defined.

However, there are minor inconsistencies in the quantitative claims and unit definitions that slightly weaken the internal logical consistency:

1. **Unit Mismatch in Storage Calculation:** In Section 3.2, the authors state that storage cost changes from “ $4T_cHd$ bytes” to “ $\frac{9}{8}T_cHd$ bytes”. The factor of 4 implies the baseline is 32-bit (FP32) precision. However, the entire paper establishes BF16 (16-bit, 2 bytes) as the baseline precision for training and inference comparisons (e.g., Table 1, Table 3). If the baseline is BF16, the initial storage should be $2T_cHd$ bytes. This arithmetic inconsistency suggests a copy-paste error or a confusion between FP32 and BF16 in the text, which undermines the precision of the claimed compression ratio.
2. **Attribution of Speedup:** The Abstract and Teaser caption attribute a “1.84x” speedup (40.3ms $\rightarrow$ 21.9ms) to the “NVFP4” infrastructure. While Table 3 confirms these specific numbers, the table reveals that the 45.7 FPS (21.9ms) result is achieved by the “2 Steps” configuration, which combines NVFP4 quantization with the DMD distillation reducing steps from 4 to 2. The BF16 baseline (24.8 FPS) is 4 steps. The logical leap that NVFP4 *alone* provides the full 1.84x speedup is not fully supported; the speedup is a compound effect of quantization and step reduction. The text should clarify that the speedup is achieved by the *combination* of NVFP4 and the few-step distillation to avoid over-attributing the gain to the precision format alone.

These issues are primarily presentational and do not invalidate the core scientific claims, but correcting them is necessary for strict logical consistency in the reported metrics.

Action items.

- **[writing]** In Section 3.2, the text claims storage changes from ‘ $4 T_c H d$ bytes’ to ‘ $\frac{9}{8} T_c H d$ bytes’. This implies a 32-bit baseline, but the paper uses BF16 (16-bit). Correct the baseline byte count to 2 to match the BF16 definition used elsewhere.
- **[writing]** The Abstract claims NVFP4 yields a 1.84x speedup (40.3ms to 21.9ms). Table 3 shows this result requires both NVFP4 and 2-step distillation. Clarify that the speedup is a compound effect of quantization and step reduction, not NVFP4 alone.

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_overreach.md

The review focuses exclusively on potential over-claiming and over-reach in the manuscript.

The paper makes several strong claims regarding the novelty and causal impact of its contributions that appear to slightly exceed the immediate evidence provided.

First, the claim in the Abstract and Conclusion that LongLive-2.0 is the “first NVFP4 training and inference system for long video generation” is a definitive statement of novelty. While the

authors cite NVFP4 applications in LLMs, they do not explicitly demonstrate that no prior work has applied NVFP4 to video diffusion or autoregressive video models. Given the rapid pace of the field, this absolute claim risks overreach. It would be more scientifically rigorous to phrase this as “To our knowledge, the first...” or to provide a brief discussion in the Related Work section explicitly ruling out prior video-specific NVFP4 implementations.

Second, the Introduction and Section 1 argue that the “remarkably clean training pipeline” (direct AR fine-tuning without ODE/DMD) is a direct result of the “high-quality infrastructure.” This implies a causal relationship where the infrastructure *enables* the algorithmic simplification. However, the paper does not present an ablation study isolating the infrastructure’s role from other factors, such as the specific AR objective, the dataset quality, or the base model architecture. It is possible that the clean pipeline is a result of the algorithmic design choices rather than the infrastructure alone. Attributing the algorithmic simplification primarily to the infrastructure without controlling for these variables constitutes an over-interpretation of the results.

Third, the Teaser caption and Section 5.3 claim that NVFP4 “preserves the overall scene composition, subject structure, and shot-level semantics” of the BF16 baseline. While the VBench scores in Table 4 are high, the experimental setup compares the full LongLive-2.0 system (NVFP4 + Balanced SP + Clean Pipeline) against baselines that may use different pipelines. The paper lacks a controlled experiment comparing NVFP4 vs. BF16 *within the exact same training pipeline* to isolate the quantization effect on semantic preservation. Without this control, attributing the preservation of semantics solely to NVFP4 is an overreach, as the “clean pipeline” or other infrastructure components could be the primary drivers of the quality.

These issues are primarily matters of phrasing and the strength of causal claims rather than fundamental flaws in the science. The authors should temper their language to reflect the limitations of their ablation studies and ensure novelty claims are appropriately qualified.

Action items.

- **[writing]** The claim of being the ‘first NVFP4 training and inference system for long video generation’ (Abstract) is potentially overreaching. Qualify with ‘to our knowledge’ or explicitly rule out prior video-specific NVFP4 work in Related Work.
- **[writing]** Attributing the ‘clean pipeline’ solely to ‘high-quality infrastructure’ (Intro) overstates causality. The paper lacks ablation isolating infrastructure from dataset or algorithmic design. Temper claims to reflect correlation rather than sole causation.
- **[writing]** Claiming NVFP4 ‘preserves semantics’ (Teaser) without a controlled NVFP4-vs-BF16 ablation within the same pipeline is overreach. The observed quality may stem from the ‘clean pipeline’ or SP, not just quantization. Clarify this limitation.

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: qwen.qwen3.5-122b

Prompt: `agents/prompts/paper_reviewer_safety_ethics.md`

The paper presents a significant technical advancement in long video generation infrastructure but lacks necessary depth in its safety and ethical disclosures.

Broader Impacts and Dual-Use Risks: The “Broader Impacts” section (Conclusion) is critically underdeveloped. The authors state that the infrastructure “involves no negative social implications” and simply “shares the ethical impacts with existing video generation models.” This is a dangerous oversimplification. LongLive-2.0’s specific capabilities—real-time (45.7 FPS), interactive, multi-shot generation—significantly lower the barrier for creating high-quality, coherent deepfakes and disinformation campaigns. The ability to switch prompts mid-generation and maintain subject consistency (as highlighted in the “Multi-Shot Attention Sink” section) directly facilitates the creation of convincing synthetic media for malicious purposes. The manuscript must explicitly discuss these dual-use risks and propose concrete mitigation strategies (e.g., watermarking, detection mechanisms, or usage policies) rather than deferring the issue to “existing models.”

Data Privacy and Consent: In the Appendix section “Multi-shot Long-video Dataset,” the authors describe curating 120K long videos and filtering for quality (e.g., removing logos/watermarks). However, there is no mention of how the dataset was sourced, whether it complies with copyright laws, or if the individuals depicted in the videos provided consent for their likeness to be used in training a generative model. Given the increasing regulatory scrutiny on AI training data (e.g., GDPR, EU AI Act), the absence of a data governance statement, consent protocol, or reference to an ethics review board (IRB) is a significant omission. The authors should clarify the provenance of the data and the measures taken to ensure privacy and legal compliance.

Conclusion: While the technical contributions are sound, the paper fails to adequately address the societal implications of its high-efficiency, real-time generation capabilities. A revision is required to expand the “Broader Impacts” section with specific risk analysis and to provide transparency regarding data sourcing and consent.

Action items.

- **[writing]** The paper presents a significant technical advancement in long video generation infrastructure but lacks necessary depth in its safety and ethical disclosures. Broader Impacts and Dual-Use Risks: The “Broader Impacts” section (Conclusion) is critically underdeveloped. The authors state that the infrastructure “involves no negative social implications” and simply “shares the ethical impacts with existing video generation models.” This is a dangerous oversimplification. LongLive-2.0’s specific cap

Scientific Evidence

Weights the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_scientific_evidence.md`

The paper presents a compelling system-level contribution, but the scientific evidence supporting the quantitative claims requires strengthening regarding statistical rigor and experimental controls.

First, the efficiency claims in Table 1 (sec/05_experiment.tex) are presented as single-point measurements (e.g., 639.5s for 64s video). In distributed training systems, iteration time can fluctuate due to network jitter, GPU thermal throttling, or data loading variance. Without reporting standard deviations or results from multiple independent runs (e.g., $n=3$ or $n=5$), it is impossible to determine if the reported 2.1x speedup is statistically significant or within the noise margin of the hardware. The authors should provide error bars or a statistical significance test (e.g., t-test) comparing the NVFP4+Balanced SP configuration against the BF16+SP baseline.

Second, the performance evaluation on VBench-Long (Table 2, sec/05_experiment.tex) relies on aggregate scores. While the authors claim LongLive-2.0 achieves the “best average rank,” the table does not provide the variance of these scores across the test set or the number of samples used for the 60s generation benchmark. Given the high dimensionality of video generation metrics, a single run on a specific prompt set may not be representative. The authors should report the mean and standard deviation of the scores across multiple seeds or a larger, stratified subset of the benchmark to ensure the observed improvements are robust.

Third, the ablation study in the Appendix regarding NVFP4 quantization (Table ‘appendix_ll2_precision_settings’) compares a PTQ model and a Pre-trained NVFP4 model against a BF16 baseline. However, the BF16 baseline appears to be a standard training run, while the NVFP4 models involve specific quantization-aware training procedures. To rigorously isolate the impact of the precision format from potential differences in training dynamics (e.g., optimizer behavior, gradient noise), the authors should ideally re-run the BF16 baseline with the exact same random seeds, data shuffling, and hyperparameters used for the NVFP4 runs. Without this control, the ~ 1.0 point drop in VBench scores for the NVFP4 model could be partially attributed to training instability rather than the quantization format itself.

Finally, the claim that the “clean pipeline” (Section 4.1) leads to better results is qualitative. While the authors compare their pipeline to complex multi-stage baselines, they do not provide a controlled experiment where the *only* variable changed is the pipeline complexity (e.g., training a model with the LongLive-2.0 infrastructure but using the Self-Forcing multi-stage algorithm, or vice versa). While this may be difficult to implement, a more detailed analysis of the training loss curves or convergence rates between the proposed method and the baselines would provide stronger evidence that the pipeline simplification does not come at the cost of optimization stability.

Action items.

- **[science]** Table 1 (sec/05_experiment.tex) reports training iteration times but lacks standard deviation or confidence intervals across multiple runs. Given the stochastic nature of training and the claim of a 2.1x speedup, statistical significance testing or error bars are required to rule out variance as a confounding factor.
- **[science]** The claim of ‘strong performance’ on VBench-Long (Table 2, sec/05_experiment.tex) lacks supporting evidence. The authors should report the mean and standard deviation of the scores across multiple seeds or a larger, stratified subset of the benchmark to ensure the observed improvements are robust.

ment.tex) relies on a single aggregate score without reporting the variance across the 120K dataset samples or the specific distribution of scores. A statistical test comparing the mean/median of LongLive-2.0 against the best baseline (LongLive) is needed to confirm the improvement is not due to random sampling.

- **[science]** The ablation study for NVFP4 quantization (Appendix, Table ‘appendix_ll2_precision_settings’) compares PTQ vs. Pre-trained NVFP4 but does not include a baseline BF16 model trained with the exact same random seeds and data shuffling to isolate the quantization effect from training dynamics. Re-running the BF16 baseline with matched seeds is necessary to attribute the ~1.0 point drop solely to quantization.

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The paper presents a compelling system-level contribution to long video generation, focusing on NVFP4 quantization and sequence parallelism. However, from a statistical analysis perspective, the evaluation of performance gains lacks necessary rigor regarding variance and reproducibility.

The primary concern lies in the reporting of efficiency metrics. Tables 1, 3, and 4 (e.g., `tab:wan22_ffn1_nvfp4`, `tab:inference_progressive`) present single-point measurements for iteration time, end-to-end latency, and FPS. In systems research, especially involving GPU workloads with stochastic elements (like video generation sampling) and hardware variability, reporting a single run is insufficient to establish statistical significance. The authors claim specific speedups (e.g., “2.15x faster training”) without providing standard deviations, confidence intervals, or the number of independent trials (N) used to derive these averages. Without this information, it is impossible to determine if the observed improvements are statistically significant or within the noise margin of the hardware environment.

Furthermore, the performance benchmarks on VBench and VBench-Long (Table 5, `tab:vbench_long_30s_60s`) report mean scores but omit measures of dispersion (e.g., standard deviation or standard error). The claim that LongLive-2.0 achieves the “best average rank” relies on these point estimates. To support the conclusion that the method is robustly superior, the authors should report the variance across different random seeds or prompt sets and, ideally, conduct statistical significance tests (such as paired t-tests) against the baselines.

Finally, the “Estimated” nature of the 64s results in Table 4 (Appendix, `tab:sp_inference_h100`) should be explicitly flagged with uncertainty bounds if derived from extrapolation, rather than presented as precise measurements. To meet the standards of rigorous statistical reporting, the authors must supplement their efficiency and quality tables with variance metrics and specify the experimental protocol (number of runs, seeds) used to generate the data.

Action items.

- **[science]** Table 1 (tab:wan22_ffn1_nvfp4) and Table 3 (tab:inference_progressive) report single-point latency/FPS measurements without standard deviations, confidence intervals, or sample sizes (N). Given the stochastic nature of video generation and hardware variability, statistical significance of the reported speedups (e.g., 2.15x) cannot be assessed. Please report mean $\pm$ std dev over multiple runs.
- **[science]** The VBench-Long results in Table 5 (tab:vbench_long_30s_60s) present mean scores but lack measures of variance (e.g., standard error) or statistical tests (e.g., t-tests) to validate the claim that LongLive-2.0 is ‘significantly’ better than baselines. Without variance estimates, the robustness of the ranking claims is unclear.
- **[science]** The paper claims a ‘2.15x speedup’ and ‘1.84x speedup’ in the abstract and conclusion based on single measurements. These point estimates should be accompanied by confidence intervals or a statement on the number of trials performed to ensure reproducibility and statistical reliability of the performance gains.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript presents a technically dense contribution with generally clear and professional writing. The logical flow between the infrastructure challenges and the proposed solutions (Balanced SP, NVFP4, asynchronous decoding) is well-structured. The abstract effectively summarizes the key contributions, and the introduction sets the stage clearly.

However, there are a few specific areas where the writing quality can be improved to ensure maximum clarity and professionalism. First, in the Conclusion, the phrase “a algorithm–infrastructure co-design system” contains a grammatical error; it should be “an algorithm–infrastructure co-design system.” Second, in Section 2.2 under “NVFP4 Preliminaries,” the authors present Equation 2 and then immediately repeat the exact same equation as Equation 3 with identical variable definitions. This duplication disrupts the reading flow and should be removed. Third, in Section 3.2, the description of storage costs (“4 T_c H d bytes”) lacks standard mathematical formatting, making it slightly harder to parse compared to the rest of the paper; using inline math mode ($4T_c H d$) would be preferable. Finally, the abstract’s phrasing “throughout the full training and inference workflow” is slightly redundant and could be tightened for better impact. Addressing these minor issues will polish the manuscript to a high standard.

Action items.

- **[writing]** In the Conclusion, correct the grammatical error ‘a algorithm–infrastructure’ to ‘an algorithm–infrastructure’ (Section 6, line 1).
- **[writing]** In Section 2.2 (NVFP4 Training), the text presents Equation 2 and then imme-

diately repeats the exact same equation as Equation 3 with identical variable definitions. Remove the duplicate equation to improve flow and avoid confusion.

- **[writing]** In Section 3.2 (Parallel KV Quantization), the sentence ‘The storage cost changes from $4 T_c H d$ bytes to $9/8 T_c H d$ bytes’ contains awkward spacing around the variables. Standardize the mathematical notation (e.g., use $4T_c H d$) for better readability.
- **[writing]** In the Abstract, the phrase ‘throughout the full training and inference workflow’ is slightly redundant. Consider simplifying to ‘across the full training and inference workflow’ or ‘for the full training and inference workflow’.