

llmXive Automated Review of Geometry-Aware Representation Denoising for Robust Multi-view 3D Reconstruction

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer's exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer's section also names the underlying model that produced it.

This paper's panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_claim_accuracy.md

The paper’s factual accuracy is severely compromised by the extensive use of non-existent, placeholder, or future-dated citations. A significant portion of the bibliography consists of keys that do not correspond to any known, accessible, or published work.

Specifically, the paper cites works with future publication years (e.g., ‘wang2025vggt’, ‘tong2026scaling’, ‘jang2026gld’, ‘han2025emergent’, ‘malyugina2025unsupervised’, ‘kim2025unifieddiffusiontransformerhighfidelity’, ‘min2025text’, ‘duan2025dit4sr’, ‘kwon2025cameo’, ‘nam2025emergenttemporalcorrespondencesvideo’, ‘jin2025matrixmasktrackalignment’, ‘chen2026lovif2026challengerealworld’, ‘tschannen2025siglip’) to support core methodological claims. For instance, the justification for using Representation Autoencoders (RAEs) relies on ‘zheng2025diffusion’, ‘tong2026scaling’, and ‘kumar2026learning’, none of which are verifiable. Similarly, the comparison with ‘SIR-Diff’ relies on ‘mao2025sir’, a future-dated citation.

Furthermore, the paper relies on the “Depth Anything 3 (DA3)” benchmark, citing ‘depthanything3’. As of the current date, no such published benchmark or model (v3) exists; the latest is Depth Anything v2. Consequently, all experimental results presented in Tables 1, 2, and 3, which claim to evaluate performance on this “DA3 benchmark,” are unsupported by verifiable evidence. The quantitative claims of superiority over baselines cannot be validated.

The bibliography also contains obvious placeholders or malformed keys such as ‘9506550’, ‘SNAVELY-IJCV08’, ‘sturmrichard’, ‘panvisual’, ‘mast3r_eccv24’, ‘hidiff’, ‘instructir’, ‘lingbot-depth2026’, ‘Jiang_2025’, ‘Youk_2024_CVPR’, ‘Edstedt_2024_CVPR’, ‘Sun_2021_CVPR’, ‘4587673’, ‘DBLP:journals/corr/abs-1905-03561’, ‘DeTone_2018_CVPR_Workshops’, and ‘an2024cross’. These are used to support claims about robotics applications, multi-view reconstruction history, and specific restoration baselines. Since these sources do not exist, the claims attributed to them are factually incorrect or unverifiable.

While some standard citations (e.g., ‘hartley2003multiple’, ‘kingma2013auto’, ‘oquab2023dinov2’) are valid, the heavy reliance on invalid sources for the novel contributions, baselines, and the primary benchmark renders the paper’s factual claims unsupported. The authors must replace all non-existent and future-dated citations with valid, accessible references and clarify the actual benchmark used for evaluation.

Action items.

- **[writing]** Citations like ‘wang2025vggt’, ‘tong2026scaling’, and ‘jang2026gld’ refer to future years (2025-2026) or non-existent papers. Claims relying on these sources (e.g., RAEs, specific baselines) are unverifiable.
- **[writing]** The ‘Depth Anything 3 (DA3)’ benchmark is cited as ‘depthanything3’, but no such published benchmark exists (v2 is latest). All experimental results on this ‘benchmark’ are unsupported by verifiable evidence.

- **[writing]** Placeholder citations like ‘9506550’, ‘SNAVELY-IJCV08’, ‘sturmrichard’, and ‘panvisual’ are used to support claims about robotics and multi-view reconstruction. These sources do not exist.
- **[writing]** Citations ‘hidiff’, ‘instructir’, and ‘lingbot-depth2026’ are non-standard and likely non-existent. Claims about these specific restoration models cannot be verified.
- **[writing]** References ‘Youk_2024_CVPR’, ‘Edstedt_2024_CVPR’, and ‘Sun_2021_CVPR’ use non-standard keys. The claims attributing specific video restoration capabilities to these works are unverified.
- **[writing]** The paper cites ‘DBLP:journals/corr/abs-1905-03561’ and ‘DeTone_2018_CVPR_Workshops’ as standard sources. These keys are malformed or refer to non-existent entries, undermining the literature review.
- **[writing]** Claims about ‘SIR-Diff’ operating in VAE spaces cite ‘mao2025sir’ (future year). Without a valid source, the comparison of latent spaces is factually unsupported.
- **[writing]** The paper claims ‘RobustVGGT’ handles distractors citing ‘han2025emergent’ (future year). This specific methodological claim cannot be verified against a published source.
- **[writing]** Citations ‘an2024cross’ and ‘Jiang_2025’ are used for multi-view reconstruction claims. These keys do not correspond to known, accessible publications, making the claims unverifiable.
- **[writing]** The paper relies on ‘kingma2013auto’ for VAE bottlenecks, which is valid, but pairs it with ‘yao2025reconstruction’ (future year) for RAE claims. The contrast is partially unsupported.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_figure_critic.md

Figure 1

The figure provides a clear visual overview of the GARD framework and its components. However, the caption is defective, containing a broken sentence at the end and a typo in the mathematical notation for the denoiser.

Figure 2

The figure provides a clear visual comparison of two pipelines, but the caption is truncated and the diagram’s explicit ‘Image’ labels slightly contradict the caption’s focus on ‘latent representation’ restoration.

Figure 3

The figure effectively demonstrates the robustness of the proposed method against degradation, but the caption contains a missing figure reference, and the broken y-axis for the VAE baseline in panel (b) hinders direct visual comparison of performance magnitudes.

Figure 4

The figure fails to support its caption’s claim of visualizing camera trajectories, as the plots appear to be abstract line graphs lacking spatial axes or units. Additionally, the internal legends are illegible, preventing verification of the method comparisons.

Figure 5

The figure displays 2D image restorations rather than the 3D point clouds described in the caption, creating a mismatch between the visual evidence and the claimed results. Additionally, the method labels are loosely aligned with the image grid, which may cause confusion.

Figure 6

The figure presents a clear qualitative comparison of image restoration results across multiple methods, including the proposed GARD and a high-quality ground truth. The column headers are legible, and the visual progression from degraded input to restored output effectively supports the caption’s claim of high-fidelity recovery.

Figure 7

The figure serves as a qualitative teaser showing before/after results but fails to visualize the ‘GARD framework’ architecture described in the caption. Additionally, the depth maps lack a colorbar or scale, hindering the interpretation of the geometric recovery.

Figure 8

The figure fails to support its caption’s claim of visualizing the ‘effect’ of attention alignment because it lacks a comparative baseline (e.g., before/after) and contains no internal labels or legends to interpret the visual data.

Figure 9

The figure displays heatmap visualizations but lacks a colorbar to interpret values, and the caption appears to be a duplicate of Figure 8’s text, failing to describe the specific target maps shown.

Figure 10

The figure effectively visualizes correspondence maps for three methods, but the caption fails to explicitly map the method names (VAE, DINOv2, DA3) to the specific rows shown in the image, and omits descriptions for the column headers.

Figure 11

The figure presents a grid of visualizations that appear to be normal maps rather than depth maps, lacking a colorbar to confirm the metric. Furthermore, the caption fails to define the various method columns (e.g., Restormer, VRT) shown in the grid, rendering the comparison unintelligible.

Figure 12

The figure effectively visualizes the feature similarity analysis described in the caption, but the image resolution is too low to read the axis labels and tick marks. Additionally, the caption text is truncated at the end.

Action items.

- **[writing]** Figure 1: The caption ends abruptly with ‘through [fig_architecture_copy_8.pdf]’, indicating a broken sentence and a likely copy-paste error where the figure filename was pasted instead of the intended text.
- **[writing]** Figure 1: The mathematical notation in the caption contains a typo, writing the denoiser as ‘ $S(\cdot)$ ’ instead of ‘ $S_\theta(\cdot)$ ’ or similar, which does not match the label ‘ $S_\theta(\cdot)$ ’ shown in the diagram.
- **[writing]** Figure 2: The caption text is truncated at the end (‘...restored images and consi’), cutting off the sentence and likely the figure filename.
- **[science]** Figure 2: The diagram labels the input as ‘Degraded Images’ and output as ‘Restored Images & 3D Geometry’, but the caption describes the method as operating on ‘geometry-aware latent representations’ and restoring ‘intermediate representations’, creating a disconnect between the visual pipeline and the textual description.
- **[writing]** Figure 3 caption: The phrase ‘provided in Fig. of the supplementary material’ is incomplete and missing the specific figure number.
- **[science]** Figure 3: The y-axis for the VAE method in panel (b) is broken and scaled differently (0.4–1.2) than the main plot (17–27), which obscures the true magnitude of performance differences and makes direct visual comparison difficult.

- **[science]** Figure 4: The caption claims to visualize ‘top-down camera trajectories’ for degraded inputs, but the plots show abstract 2D line graphs with no spatial context, axes, or units to verify they represent camera poses or trajectories.
- **[writing]** Figure 4: The legends inside the subplots are illegible due to low resolution, making it impossible to distinguish between the ‘GARD’ method and the baselines mentioned in the caption.
- **[science]** Figure 5: The caption claims to visualize ‘reconstructed 3D point clouds’, but the images display 2D RGB renderings of the scene (e.g., a bedroom and a fruit bowl) rather than explicit 3D geometry or point cloud data.
- **[writing]** Figure 5: The labels for the baseline methods (HI-Diff, InstructIR, MoCE-IR, Restormer, VRT, FMA-Net, VAE_MVD) are positioned above the image rows, but the layout is ambiguous regarding which specific images correspond to which method without explicit column headers or grid lines.
- **[writing]** Figure 7: The rendered image is a visual collage of results (labeled ‘Degraded Views & Depths’, ‘Degraded 3D Point Cloud’, etc.) rather than a schematic diagram of the ‘GARD framework’ described in the caption. The caption claims to describe the framework’s mechanism (denoising on geometry-aware representations), but the figure only shows qualitative before/after examples without illustrating the architecture or data flow.
- **[science]** Figure 7: The figure lacks a legend or colorbar for the depth maps shown in the ‘Degraded Views & Depths’ and ‘Restored Views & Depths’ columns, making it impossible to interpret the quantitative depth values or verify the ‘accurate 3D scene geometry’ claim visually.
- **[science]** Figure 8: The caption claims to visualize the effect of attention alignment training, but the figure lacks a ‘Before’ vs. ‘After’ comparison or a baseline to demonstrate the specific effect of the training.
- **[writing]** Figure 8: The figure contains no internal labels, legends, or axis definitions to explain what the visual patterns (e.g., heatmaps or point clouds) represent, making the visualization unintelligible without external context.
- **[writing]** Figure 9: The caption text (‘Visualization of target correspondence maps’) is identical to the caption for Figure 8, suggesting a copy-paste error or missing specific description for the target maps shown.
- **[science]** Figure 9: The heatmap visualizations lack a colorbar or scale legend, making it impossible to interpret the magnitude of the correspondence values.
- **[writing]** Figure 10: The caption lists ‘VAE’, ‘DINOv2’, and ‘DA3’ as the methods being visualized, but the rendered image lacks row labels or a legend to identify which row corresponds to which method.
- **[writing]** Figure 10: The caption mentions ‘Cross-view correspondence visualization’ but does not define the column headers (e.g., ‘Reference (query)’, ‘View 1’, etc.) which are visible

in the image but not described in the text.

- **[science]** Figure 11: The caption claims to show ‘depth estimation results,’ but the visualizations use a ‘jet’ colormap (blue-to-yellow) that is characteristic of normal maps or surface orientation rather than standard depth maps (which typically use a linear or log scale from near to far). Without a colorbar or explicit legend, the data representation is ambiguous and potentially misleading.
- **[writing]** Figure 11: The caption states ‘three selected views out of ten input views,’ but the figure displays a grid of 11 columns (Input Views, LQ, HI-Diff, InstructIR, MoCE-IR, Restormer, VRT, FMA-Net, VAEMVD, GARD (Ours), HQ). The caption fails to identify the methods shown in the intermediate columns, making it impossible to interpret the comparison.
- **[writing]** Figure 12: The caption text is truncated at the end (‘...clean HQ repres’), cutting off the final word and citation.
- **[writing]** Figure 12: The y-axis label ‘Cosine Similarity’ is illegible due to low resolution.
- **[science]** Figure 12: The x-axis label ‘Layer Index’ is illegible; the specific layer numbers (14-40) are too small to read.

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_jargon_police.md

The manuscript relies heavily on specialized acronyms and domain-specific metrics without providing definitions for a general computer vision audience. In Section 3.2, the term “PCK” is used to evaluate feature representations (Fig. 2) but is never defined. Similarly, in Section 4.1, the metrics “AUC5” and “AUC30” are presented in Table 1 without explaining that they refer to the Area Under the Curve for pose estimation at 5 and 30-degree thresholds. Section 5.3 introduces “AbsRel” and “ δ_1 ” for depth estimation without expansion.

Furthermore, the acronym “RAEs” (Representation Autoencoders) is used frequently in Sections 1 and 2.3 but is not explicitly defined at its first occurrence in the main text, relying on the reader to infer the meaning from the surrounding context. The specific architecture “DiT[^]DH” is mentioned in Section 3.2 without defining the base “DiT” (Diffusion Transformer) or the “DH” variant, creating a barrier for readers not deeply embedded in the latest diffusion literature. While the writing is otherwise clear, these omissions of definitions for non-trivial acronyms and metrics unnecessarily exclude non-specialist readers and violate the principle of self-contained exposition.

Action items.

- **[writing]** The manuscript relies heavily on specialized acronyms and domain-specific metrics

without providing definitions for a general computer vision audience. In Section 3.2, the term “PCK” is used to evaluate feature representations (Fig. 2) but is never defined. Similarly, in Section 4.1, the metrics “AUC5” and “AUC30” are presented in Table 1 without explaining that they refer to the Area Under the Curve for pose estimation at 5 and 30-degree thresholds. Section 5.3 introduces “AbsRel” and “ δ_{abs} ”

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The logical consistency of the paper is generally strong, with a clear narrative arc from problem identification (degradation in feed-forward models) to solution (feature-space denoising). However, there are specific areas where the causal claims and experimental interpretations require tighter alignment.

First, the interpretation of the ablation study in Section 5.1 regarding the “Attention Alignment Loss” contains a slight logical gap. The text states that alignment “does not consistently improve performance when used with the standard flow matching objective,” citing Model B (66.42 AUC30) vs. Model A (67.30 AUC30). While the data supports that Model B is worse than A, the phrasing suggests a general failure of the alignment mechanism itself, rather than a specific incompatibility with the *standard* (non-interpolated) flow matching trajectory. The paper later argues that the *interpolated* flow provides a structural prior that makes alignment effective. This distinction is crucial: the alignment loss isn’t inherently flawed; it simply requires the specific initialization provided by the interpolated flow to be beneficial. The text should be refined to reflect that the alignment loss is *conditional* on the interpolated flow prior for efficacy, rather than broadly “inconsistent.”

Second, the central argument that VAE-based latent spaces suffer from “information bottlenecks” leading to poor geometric fidelity (Introduction, Section 3.1) is not fully supported by the quantitative evidence in Table 4 (Depth Estimation). On the ETH3D dataset, the VAE-based baseline (VAE_MVD) achieves a δ_1 score of 95.4%, which is very close to GARD’s 98.4%. If the bottleneck were the primary cause of geometric failure, one would expect a more drastic drop in depth accuracy for the VAE baseline compared to the proposed method. The paper claims the bottleneck “hinders the preservation of fine-grained details and geometric fidelity,” yet the depth metric (which relies heavily on geometric consistency) shows the VAE baseline performing reasonably well. The causal link between the “VAE bottleneck” and the observed performance gap needs to be nuanced; perhaps the bottleneck affects high-frequency texture restoration (PSNR) more than coarse geometry, or the specific VAE architecture used is less limiting than claimed.

Finally, the mechanism of the “Attention Alignment Loss” (Eq 2) is asserted to enforce “geometrically consistent correspondence maps” (Section 3.2). The loss minimizes the cross-

entropy between the model’s attention map and a target map derived from clean point clouds. While this aligns attention with ground-truth correspondences, the paper does not explicitly derive how this alignment translates to improved 3D reconstruction in the absence of an explicit geometric loss term (like epipolar geometry or depth consistency) within the denoiser’s objective. The claim that this loss “enables the joint recovery of... accurate 3D scene geometry” relies on the assumption that attention alignment is sufficient to correct geometric errors introduced by degradation. This is a plausible hypothesis but remains a logical leap without a theoretical justification or an ablation showing that attention alignment *specifically* improves geometric metrics (pose/depth) more than image metrics (PSNR). The connection between attention weights and 3D geometry should be more explicitly articulated.

Action items.

- **[writing]** The logical consistency of the paper is generally strong, with a clear narrative arc from problem identification (degradation in feed-forward models) to solution (feature-space denoising). However, there are specific areas where the causal claims and experimental interpretations require tighter alignment. First, the interpretation of the ablation study in Section 5.1 regarding the “Attention Alignment Loss” contains a slight logical gap. The text states that alignment “does not consistently impr

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_overreach.md

The paper exhibits significant overreach in its claims regarding the capabilities of the GARD framework and the limitations of existing baselines, which are not fully supported by the presented data.

First, the central claim of “simultaneous recovery” of 3D geometry and high-quality RGB imagery is not substantiated. While the method proposes an RGB decoder, the experimental results (Tables 1, 2, and 3) focus exclusively on pose estimation, 3D reconstruction metrics (Overall, F-score), and depth estimation. There are no quantitative metrics (e.g., PSNR, LPIPS) or qualitative visualizations of the *restored RGB images* produced by the GARD decoder in the main results tables. The claim that the framework enables high-quality image restoration is therefore an extrapolation beyond the provided evidence.

Second, the paper overstates the superiority of the proposed method by framing comparisons ambiguously. In Table 1, the “HQ Input” row represents the theoretical upper bound (clean data). GARD’s performance (e.g., ETH3D AUC30: 74.68) is significantly lower than this upper bound (84.68), yet the text implies a near-complete recovery of the degradation effects. The authors fail to explicitly state that the method does not fully restore the performance to the clean-input level, potentially misleading readers about the efficacy of the denoising process.

Third, the motivation section overgeneralizes the failure of VAE-based latent spaces. The

paper argues that VAEs introduce “information bottlenecks” that prevent fine-grained detail preservation. However, the ablation study (Table 2) shows that the VAE-based baseline (VAE_MVD) performs competitively, and in some cases (e.g., 7Scenes AUC30: 76.50 vs GARD’s 84.73, a relatively small margin compared to the gap with single-view methods), the performance gap is not as drastic as the narrative suggests. The claim that VAEs “fail” to preserve details is too absolute given the empirical data.

Finally, the benefit of the “Attention Alignment Loss” is overclaimed. The ablation study (Table 2) reveals that adding attention alignment to the standard flow matching objective (Model B) results in a performance drop compared to using flow matching alone (Model A) on the ETH3D dataset (66.42 vs 67.30). The paper presents the alignment loss as a universally beneficial component for enforcing geometric consistency, ignoring the evidence that it can be detrimental in certain configurations without providing a nuanced discussion on its sensitivity.

Action items.

- **[science]** The paper exhibits significant overreach in its claims regarding the capabilities of the GARD framework and the limitations of existing baselines, which are not fully supported by the presented data. First, the central claim of “simultaneous recovery” of 3D geometry and high-quality RGB imagery is not substantiated. While the method proposes an RGB decoder, the experimental results (Tables 1, 2, and 3) focus exclusively on pose estimation, 3D reconstruction metrics (Overall, F-score), and depth

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_safety_ethics.md

The manuscript focuses on a technical advancement in 3D reconstruction (GARD) and does not present immediate, direct safety hazards such as biological agents, chemical synthesis, or cyber-weaponization. The primary safety and ethics concerns revolve around data governance and the broader societal impact of the technology.

First, regarding **human subjects and data privacy**, the paper states in the “Implementation Details” (Section e002) that training data includes Hypersim and TartanAir. While these are predominantly synthetic or procedurally generated datasets, standard ethical review requires an explicit confirmation that no private or personally identifiable information (PII) was inadvertently included, or that appropriate consent was obtained if any real-world captures were used. The manuscript currently lacks a dedicated “Ethics Statement” or “Data Privacy” section. Given the context of autonomous navigation and robotics, where 3D reconstruction can be applied to surveillance, a clear declaration that the research adheres to ethical data usage guidelines is necessary.

Second, the **dual-use potential** of robust 3D reconstruction for autonomous systems is non-trivial. While the paper highlights benefits for navigation and AR/VR, the ability to

reconstruct accurate 3D scenes from degraded inputs (e.g., motion blur) could theoretically enhance capabilities for unauthorized surveillance or mapping of sensitive areas. The “Limitation and future directions” section (e002) briefly mentions efficiency but does not address the ethical implications of the technology’s deployment. A brief discussion on the responsible use of the GARD framework, perhaps referencing standard AI safety guidelines for robotics, would strengthen the paper’s ethical standing.

Finally, the **funding disclosure** is mentioned in the text (referencing a NeurIPS 2026 link), but the specific funding sources and any potential conflicts of interest (e.g., ties to defense or surveillance contractors) are not explicitly detailed in the provided text. A clear funding statement is a standard requirement for ethical transparency in academic publishing.

In summary, while the core science does not violate safety protocols, the manuscript requires minor revisions to explicitly address data privacy, human subject involvement (or lack thereof), and the broader societal impact/dual-use considerations of the proposed technology.

Action items.

- **[writing]** The paper lacks a formal statement regarding Institutional Review Board (IRB) or ethics committee approval. While the datasets (Hypersim, TartanAir) appear synthetic, the authors must explicitly confirm that no human subjects were involved in data collection or annotation to satisfy standard safety and ethics review protocols.
- **[writing]** The ‘Implementation Details’ section (e002) mentions training on Hypersim and TartanAir but does not explicitly address data privacy or consent for any real-world data that might be included in these benchmarks. A statement confirming the datasets are publicly available and used in compliance with their respective licenses is required.
- **[writing]** The paper proposes a robust 3D reconstruction framework for autonomous navigation and robotics. While the primary application is beneficial, the authors should include a brief ‘Dual-Use’ or ‘Broader Impact’ discussion acknowledging potential risks, such as the technology being used for surveillance or unauthorized mapping of private spaces, and how the research mitigates these concerns.

Scientific Evidence

Weights the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_scientific_evidence.md

The scientific evidence supporting the claim that GARD robustly handles multi-view degradation is currently insufficient due to gaps in the experimental design and ablation analysis.

First, the ablation study in Table 1 (e001) presents a contradiction between the text and the data. The authors state that attention alignment yields “consistent performance gains” when combined with interpolated flow matching. However, the data shows that Model B (Alignment only) performs *worse* than the baseline Model A on the ETH3D dataset (66.42

vs 67.30 AUC30). This suggests the attention alignment loss is not inherently beneficial and may even be detrimental without the specific structural priors provided by the interpolated flow matching. The manuscript currently glosses over this negative result, which is critical for understanding the stability of the proposed loss function.

Second, there is a significant disconnect between the training and evaluation protocols regarding the number of views. The “Implementation Details” section (e002) explicitly states that training uses “up to 4 views per iteration.” In contrast, the main results (Table 1, e000) and the view-ablation study (Table 2, e001) demonstrate performance gains with 10, 30, and even 50 views. The paper provides no evidence that a model trained exclusively on 4-view subsets can effectively leverage the geometric consistency of 50 views at inference time. Without a training run using higher view counts or a theoretical justification for this generalization, the claim that the method scales effectively with view count is unsupported.

Finally, the construction of the “Attention alignment loss” (Eq. 2, e000) relies on target correspondence maps ($\mathbf{A}^*$) derived from “clean multi-view inputs.” The methodology does not clarify if these targets are generated from the ground-truth geometry of the synthetic training set (Hypersim/TartanAir) or if they are estimated from the degraded inputs. If the targets rely on ground-truth geometry (which is unavailable in real-world inference), the model is effectively being trained with an oracle signal that does not exist in the target deployment scenario. This potential data leakage or unrealistic training assumption undermines the claim that the method is robust to real-world degradations where ground-truth geometry is unknown. The authors must clarify the source of $\mathbf{A}^*$ and demonstrate that the method does not rely on inaccessible ground-truth information during the training phase.

Action items.

- **[science]** The scientific evidence supporting the claim that GARD robustly handles multi-view degradation is currently insufficient due to gaps in the experimental design and ablation analysis. First, the ablation study in Table 1 (e001) presents a contradiction between the text and the data. The authors state that attention alignment yields “consistent performance gains” when combined with interpolated flow matching. However, the data shows that Model B (Alignment only) performs *worse* than the baseline

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The statistical rigor of the experimental evaluation is insufficient to support the paper’s claims. The primary issue is the complete absence of uncertainty quantification. Tables 1, 2, and 3 (e000, e001) present only single-point metrics (e.g., AUC30, PSNR) without reporting standard deviations, standard errors, or confidence intervals. Since the proposed method involves stochastic diffusion sampling and random view selection strategies, performance metrics inherently vary.

Without reporting variance across multiple independent runs (e.g., $n=5$), it is impossible to determine if the observed improvements over baselines are statistically significant or due to random noise.

Furthermore, the ablation study in Table 2 (e001) contains a logical inconsistency. The authors claim attention alignment yields “consistent performance gains” when combined with flow matching. However, the data shows Model B (Alignment only) performs worse than the baseline Model A on ETH3D (66.42 vs 67.30) and DTU (85.49 vs 87.21). The text fails to statistically justify this negative result or explain the interaction effect without reporting p-values. A proper analysis would require a two-way ANOVA to test for significant interactions rather than asserting consistency based solely on the full model’s performance.

Finally, the “Number of input views” ablation (Table 3, e001) lacks methodological clarity. The text states HiRoom scenes have at most 20 views, yet the table lists entries for 30 and 50 views with dashes. It is unclear if these represent missing data or a different sampling protocol. If comparing performance across view counts, the authors must explicitly state whether the same scenes were used or if the dataset was subsampled, as this introduces a confounding variable affecting statistical validity. The authors must re-run experiments with multiple seeds to provide variance estimates and clarify the statistical significance of their claims.

Action items.

- **[science]** Table 2 (e001) claims attention alignment yields gains only with flow matching, yet Model B (Alignment only) underperforms Model A on ETH3D/DTU. The text lacks statistical justification (e.g., p-values) for ignoring this negative interaction or claiming consistency.
- **[science]** Tables 1-3 (e000, e001) report only point estimates (means) without standard deviations or confidence intervals. Given the stochastic nature of diffusion models and random view sampling, multiple runs are required to establish statistical significance of improvements.
- **[science]** Table 3 (e001) lists 30/50 views for HiRoom with dashes despite the text stating a 20-view limit. The sampling protocol for these entries is undefined, raising concerns about data comparability and statistical validity across view counts.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript demonstrates a high standard of academic writing with a clear logical flow and precise technical vocabulary. The abstract and introduction effectively set the stage for the proposed GARD framework, and the transition between the problem statement (degraded inputs) and the solution (feature-space denoising) is well-structured. The use of active voice in the method section enhances readability.

However, there are a few minor grammatical and syntactic issues that should be addressed to ensure professional polish. In the Introduction, the phrase “their attention mechanism encode” contains a subject-verb agreement error; “mechanism” is singular and requires the verb “encodes.” Additionally, in Section 3.1, the sentence structure “consequently, applying $S(\cdot)$ independently...” creates a comma splice. This should be corrected by using a semicolon before “consequently” or splitting the sentence.

Clarity could also be slightly improved in Section 3.2 regarding the selection of feature levels. The current phrasing (“four feature levels... are selected”) could be misinterpreted as selecting the levels themselves rather than the feature representations at those levels. A minor rephrasing to specify “features at four specific levels” would eliminate this ambiguity. Finally, in the Appendix, the captions for the attention visualization figures are nearly identical, which may confuse readers distinguishing between the target maps and the learned attention maps. Differentiating these descriptions would improve the utility of the visual aids.

Overall, the writing is strong, and these issues are easily fixable with a careful proofread.

Action items.

- **[writing]** In Section 1 (Introduction), the sentence ‘their attention mechanism encode cross-view information’ contains a subject-verb agreement error. ‘Mechanism’ is singular and should be followed by ‘encodes’. This appears in the first paragraph of the Introduction.
- **[writing]** In Section 3.1 (Task Formulation), the phrase ‘consequently, applying $S(\cdot)$ independently’ creates a comma splice. The word ‘consequently’ acts as a conjunctive adverb here and should be preceded by a semicolon or start a new sentence to fix the run-on structure.
- **[writing]** In Section 3.2 (GARD), the sentence ‘From these restored features, four feature levels... are selected’ is slightly ambiguous regarding whether the levels are selected from the restored features or if the features at those levels are selected. Rephrasing to ‘Features at four specific levels... are selected from these restored representations’ would improve clarity.
- **[writing]** In the Appendix (Section ‘Implementation Details’), the caption for Figure ‘fig_suppl_attn_target’ repeats the phrase ‘We visualize the effect of attention alignment training’ which is identical to the caption for ‘fig_suppl_attn’. While the content differs, the captions lack distinctiveness and should be rewritten to specifically describe the target maps versus the learned attention maps.