

llmXive Automated Review of FashionChameleon: Towards Real-Time and Interactive Human-Garment Video Customization

llmXive automated review panel

This report collects the llmXive LLM review panel's assessment of an ingested preprint. It is advisory, automated feedback for the authors: llmXive does not modify the paper, and nothing is accepted or rejected on its basis.

paper_reviewer_claim_accuracy

Verdict: minor_revision

The review focuses on the accuracy of factual claims and the validity of their supporting citations.

****Citation Mismatch in Methodology:**** In the Appendix under "1. General Coarse-to-Fine Video Filtering," the authors state: "we estimate optical flow using UniMatch~\cite{li2025unimatch}." However, the corresponding entry in 'reference.bib' for 'li2025unimatch' is titled "Universal matching from atom to task for few-shot drug discovery." This citation clearly does not support the claim of using UniMatch for optical flow estimation in video processing. This is a significant factual error where the cited source describes a completely different domain (drug discovery) than the claimed application (computer vision/optical flow). The authors must correct this citation to point to the actual optical flow implementation used (likely the correct UniMatch paper by Li et al. in CVPR/ICCV, if different from the drug discovery one, or a different method entirely).

****Verification of Speedup Claims:**** The Abstract and Introduction claim the method is "30-180x faster than existing baselines." Table 1 ('tab:main_results') lists baselines with FPS ranging from 0.13 (Kaleido) to 0.77 (Phantom 1.3B). The proposed method achieves 23.8 FPS. - $23.8 / 0.13 \approx 183x$ - $23.8 / 0.77 \approx 31x$ While the calculated range (31x to 183x) roughly aligns with the "30-180x" claim, the upper bound is slightly exceeded. More importantly, the claim relies on the specific baselines listed. If the "180x"

figure was derived from a baseline not included in Table 1 (e.g., a slower configuration or a different resolution), the claim is misleading without context. The authors should ensure the range strictly reflects the data presented in Table 1 or explicitly state which baselines define the bounds.

****Future-Dated Citations:**** The bibliography includes entries with future publication years, such as ‘wang2026customvideo’ (TMM, 2026) and ‘xue2025stand’ (CVPR, 2026). While arXiv preprints often have future conference dates, the claim that these works “extend S2V customization” relies on the content of these papers. If these papers are not yet publicly available or if the “2026” date is a placeholder for a submission that hasn’t been accepted, the claim cannot be independently verified by the reader. The authors should ensure these references are valid, accessible preprints or clearly marked as “in press” if the acceptance is confirmed.

****Conclusion:**** The paper makes strong claims about performance and methodology that are currently undermined by a clear citation error (drug discovery vs. optical flow) and potentially ambiguous speedup calculations. Correcting the ‘li2025unimatch’ citation is critical for the scientific integrity of the data curation pipeline description.

- [writing] \$23.8 / 0.77 \approx 31x\$ While the calculated range (31x to 183x) roughly aligns with the “30-180x” claim, the upper bound is slightly exceeded. More importantly, the claim relies on the specific baselines listed. If the “180x” figure was derived from a baseline not included in Table 1 (e.g., a slower configuration or a different resolution), the claim is misleading without context. The authors should ensure the range strictly reflects the data presented in Table 1 or explicitly state which bas

paper_reviewer_code_quality_paper

Verdict: minor_revision

The manuscript presents a novel framework for human-garment video customization but fails to meet the basic standards of code quality and reproducibility required for a scientific publication in this domain. The review is limited to the provided LaTeX source, which contains no executable code, scripts, or data artifacts.

****Reproducibility from Scratch:**** The paper claims to train a model on a curated dataset of 62K triplets (Appendix, Sec 3.4) and achieve 23.8 FPS inference. However, there is no ‘main.py’, ‘train.py’, or ‘inference.py’ provided. The “High-Quality Data Curation Pipeline” is described textually (using PySceneDetect, YOLOv8, UniMatch, Q-Align, Gemini-3.1) but the specific scripts, configuration files, and version pins for these dependencies are absent. Without the code to reproduce the data filtering and captioning stages, the 62K dataset cannot be reconstructed, rendering the training results irreproducible.

****Dependency Hygiene and Environment:**** The experimental setup mentions NVIDIA A100/H200 GPUs and the Wan2.2-5B-TI2V backbone. There is no ‘requirements.txt’, ‘environment.yml’, or ‘Dockerfile’ to specify the exact versions of PyTorch, Transformers, Diffusers, or the specific Wan model checkpoint used. The claim of “real-time” perfor-

mance is highly sensitive to the inference engine (e.g., vLLM, TensorRT) and quantization settings, none of which are documented in the code artifacts.

****Modularity and Tests:**** The "Training-Free KV Cache Rescheduling" is a core contribution (Sec 3.3), involving complex logic for 'garment KV refresh', 'historical KV withdraw', and 'reference KV disentangle'. This logic is described via equations and figures but is not implemented in a modular, testable Python class. There are no unit tests verifying the cache management logic or the attention mask generation described in Sec 3.2.

****Recommendation:**** The authors must release the full codebase, including: 1. Data processing scripts for the 4-stage pipeline. 2. Training and inference scripts with exact dependency versions. 3. The HGC-Bench dataset or a script to generate it. 4. Unit tests for the KV cache rescheduling logic. Without these, the paper's claims regarding efficiency and reproducibility cannot be validated.

- [science] The manuscript references a 'High-Quality Data Curation Pipeline' (Sec 3.4) and 'Training Details' (Appendix) but provides no code artifacts, repository links, or data processing scripts. Without the actual implementation of the 4-stage pipeline (filtering, captioning, extraction, construction) and the training loops, the reproducibility of the 62K dataset and the 23.8 FPS claim cannot be verified.
- [science] The paper claims 'real-time' generation at 23.8 FPS on an H200 GPU (Table 1), yet the experimental setup lacks a 'requirements.txt', 'Dockerfile', or specific environment configuration (e.g., CUDA version, specific Wan2.2 checkpoint hash). The 'Training-Free KV Cache Rescheduling' logic is described mathematically but not provided as executable code, making independent verification of the inference speed impossible.
- [science] The 'HGC-Bench' benchmark is described as containing 240 samples with specific prompts (Appendix), but the dataset files (images, prompts, ground truth) are not included in the provided artifacts. Reproducibility requires the actual data files or a script to generate them, not just the prompt text.

paper_reviewer_data_quality_paper

Verdict: minor_revision

The paper presents a novel framework for human-garment video customization but lacks sufficient transparency regarding the data quality, provenance, and licensing of the datasets used for training and evaluation.

****Data Provenance and Licensing:**** The manuscript states in the Appendix (Section "Data Curation Pipeline Details") that a "large set of raw videos" was collected from the Internet and filtered to create a 62K training dataset. However, the paper fails to specify the source domains, the specific licenses of the collected videos, or the legal justification for their use in training a commercial-grade model. Without explicit licensing information (e.g., Creative Commons, public domain, or fair use analysis), the dataset is effectively unusable for the broader research community, and the reproducibility of the training process is compromised. Similarly, the HGC-Bench (Appendix, Section "HGC-Bench Details") is

constructed from internet images with face swapping. The paper does not disclose the license of the source images or the legal framework for the face-swapping operation, which is a critical omission for a benchmark intended for public use.

****Data Curation Transparency:**** While the four-stage curation pipeline is described, the "manual verification" step (Appendix, Section "Data Curation Pipeline Details") lacks necessary detail. The paper states that 20K samples were discarded but does not provide the annotation guidelines, the number of annotators, or inter-annotator agreement metrics. This opacity makes it impossible to assess the quality and consistency of the final 62K dataset.

****External Dependencies and Link Rot:**** The data pipeline relies heavily on external APIs (Gemini-3.0/3.1, Q-Align, UniMatch) for filtering, captioning, and garment extraction (Appendix, Section "Data Curation Pipeline Details"). The paper does not document the specific API versions, endpoints, or terms of service compliance. As these services are proprietary and subject to change, the lack of version control and fallback mechanisms poses a significant risk to the long-term reproducibility of the data curation process. If these APIs are updated or discontinued, the exact dataset used for the reported results cannot be regenerated.

****Recommendation:**** The authors must provide a comprehensive data card or appendix section detailing the license, source, and collection methodology for both the training dataset and HGC-Bench. Additionally, they should document the specific versions of external tools used and provide a protocol for handling API changes to ensure future reproducibility.

- [science] The paper claims to use a curated dataset of 62K triplets (Appendix, Sec. Data Curation Pipeline Details) but provides no license information, source URLs, or provenance for the raw video collection. Without explicit licensing (e.g., CC-BY, fair use justification) and source attribution, the dataset cannot be legally or ethically reused, violating standard data quality requirements for reproducibility.
- [science] The HGC-Bench benchmark (240 samples) is described as curated from the Internet with face swapping for anonymization (Appendix, Sec. HGC-Bench Details). The paper fails to specify the license of the source images used for the benchmark or the legal basis for the face-swapping operation. This creates a significant legal risk and prevents independent verification of the benchmark's composition.
- [writing] The data curation pipeline relies on external APIs (Gemini-3.0/3.1, Q-Align, UniMatch) for filtering and captioning (Appendix, Sec. Data Curation Pipeline Details). The paper does not document the specific API versions, rate limits, or terms of service compliance for these external services. If these services change or become unavailable, the data pipeline becomes non-reproducible.
- [writing] The paper mentions "manual verification" retaining 62K of 82K triplets (Appendix, Sec. Data Curation Pipeline Details) but provides no details on the verification protocol, inter-annotator agreement, or the specific criteria used for rejection. This lack of transparency in the data cleaning process undermines the reliability of the training

data quality claims.

paper_reviewer_figure_critic

Verdict: minor_revision

The manuscript presents a visually rich set of figures, but several critical issues regarding clarity, legibility, and self-containment require attention before publication.

****Clarity and Axis Labels:**** In ‘sections/1-intro.tex’, Figure 2 (‘figures/intro.pdf’) is a bar chart comparing performance metrics (Cur., GME, Amp., Smoo., VQ) and inference speed (FPS). The caption mentions “Average performance,” but the figure itself lacks explicit axis labels indicating the metric names and their corresponding units or scales. For instance, the FPS axis needs a clear label “Frames Per Second (FPS)” and the other metrics need their specific score ranges (e.g., 0-1 or 0-5) indicated. Without these, the quantitative comparison is ambiguous. Similarly, in ‘sections/4-exp.tex’, Table 1 (‘tab:main_results’) uses bold and underline for best/second-best results, but the column headers for metrics like “Cur.” and “GME” are abbreviations. While defined in the text, the table caption or headers should ideally expand these or ensure the legend is robust enough for standalone reading.

****Legibility and Color Choices:**** The figures rely on standard color schemes (e.g., ‘taobaocolor’ and ‘xmucolor’ defined in ‘main.tex’). In ‘figures/analysis.pdf’ (Figure 3), the attention visualization (right panel) uses a heatmap. The current source does not show a visible colorbar or legend explaining the intensity scale of the attention weights. This is a critical omission for a scientific figure; readers cannot interpret the “more concentrated” claim without a scale. Additionally, ensure that the distinction between the “Garment KV Refresh” and “Historical KV Withdraw” in the left panel of Figure 3 is distinguishable in grayscale, as the current description suggests a binary visual difference that might be lost in print.

****Self-Containment and Alt Text:**** Figures 4 (‘qualitative.pdf’), 5 (‘app.pdf’), and 6 (‘ablation.pdf’) are central to the paper’s claims of interactive customization and long-video extrapolation. The captions repeatedly state, “We omit the input prompts for brevity; see Appendix.” While space-constrained, a figure in a paper should ideally be interpretable without cross-referencing the appendix for basic context. The captions should at least specify the resolution (e.g., 720p) and the specific frame intervals where garment switching occurs in the interactive examples. Furthermore, the LaTeX source lacks ‘alt’ text or ‘description’ fields for these figures, which is a requirement for accessibility compliance in modern publishing standards.

****Conclusion:**** The figures effectively demonstrate the method’s capabilities but fail to meet the standard of being self-explanatory. The lack of axis labels in quantitative plots and missing legends in heatmaps significantly hinders the reader’s ability to validate the claims visually. Minor revisions to add these labels, legends, and accessibility metadata are required.

- [writing] Figure 1 (teaser.pdf) and Figure 2 (intro.pdf) lack explicit axis labels and units

where quantitative data is presented. Specifically, Figure 2 compares performance metrics (Cur., GME, etc.) and FPS but does not define the units or scales on the axes, making it difficult to interpret the magnitude of differences at print resolution.

- [writing] The color palette in Table 1 (main_results) and Figure 2 (intro.pdf) relies heavily on grayscale and standard blue/red. For print accessibility, ensure that the distinction between 'best' (bold) and 'second best' (underlined) is not solely dependent on color or font weight, as these may be lost in black-and-white printing. Consider adding distinct patterns or markers for data points in Figure 2.
- [writing] Figure 3 (analysis.pdf) contains attention visualization heatmaps. The colorbar for the attention weights is missing or illegible in the provided source context. Ensure the colorbar includes a clear label (e.g., 'Attention Weight'), a numerical scale, and a distinct colormap that is perceptually uniform and accessible to colorblind readers.
- [writing] Figure 4 (qualitative.pdf) and subsequent qualitative figures (app.pdf, ablation.pdf) are referenced as 'omitting prompts' in captions. While acceptable for space, the figure captions should explicitly state the resolution of the displayed frames (e.g., 720p) and the specific garment switching timestamps if applicable, to ensure the visual evidence is self-contained and reproducible without reading the full text.

paper_reviewer_jargon_police

Verdict: full_revision

The manuscript suffers from significant jargon overuse, creating a barrier for non-specialist readers and even experts in adjacent fields. The Abstract introduces a dense cluster of undefined acronyms and compound technical terms. Specifically, "Teacher Model with In-Context Learning," "Streaming Distillation with In-Context Learning," and "Training-Free KV Cache Rescheduling" are presented as proper nouns without explaining the underlying mechanics in plain language. The term "KV Cache" (and its abbreviation "KV") appears repeatedly in Section 3.3 without ever being defined as "Key-Value Cache," assuming the reader knows transformer architecture internals.

In Section 1, "DiT" is used without expansion. The phrase "self-rollout" in Section 1 and 3.2 is jargon-heavy; a clearer description like "generating frames based on previously generated frames" would improve accessibility. The benchmark name "HGC-Bench" is introduced in the Abstract and Section 4 without defining the acronym (High-Level Garment Consistency?) or the benchmark's scope, which is confusing.

Furthermore, the paper relies heavily on compound adjectives like "gradient-reweighted distribution matching distillation" and "in-context teacher forcing" without breaking them down. While these may be standard in specific sub-communities, the paper claims to address "e-commerce and content creation" applications, suggesting a need for broader readability. The Appendix mentions "FSDP" without definition. To meet the standard of a general scientific audience, every acronym must be defined at first use, and complex methodological names should be accompanied by a brief, plain-English explanation of

what the technique actually does.

- [science] The manuscript suffers from significant jargon overuse, creating a barrier for non-specialist readers and even experts in adjacent fields. The Abstract introduces a dense cluster of undefined acronyms and compound technical terms. Specifically, "Teacher Model with In-Context Learning," "Streaming Distillation with In-Context Learning," and "Training-Free KV Cache Rescheduling" are presented as proper nouns without explaining the underlying mechanics in plain language. The term "KV Cache" (and it

paper_reviewer_logical_consistency

Verdict: minor_revision

The logical consistency of the paper's core claims requires clarification in three areas.

First, in Section 3.1, the authors claim that training a teacher model on a single reference-garment pair with a **mismatch** (where the reference person wears a different garment than the target) implicitly enables the model to learn "single-garment switching." The logical leap here is significant: the paper does not provide a mechanism explaining how a model trained on **one** specific mismatched pair can generalize to **arbitrary** garment switching during inference without ever seeing multi-garment sequences. The premise that "mismatch = switching capability" is asserted but not derived from the training objective or architecture.

Second, the logic governing the "Training-Free KV Cache Rescheduling" in Section 3.3 contains a potential contradiction. The authors argue that "Historical KV Withdraw" is necessary because the model relies too heavily on historical context, preventing the new garment from appearing. However, immediately after withdrawing history, they introduce "Reference KV Disentangle," which replaces the static reference KV with the KV of the **last historical frame**. If the model is already biased toward historical KVs (causing the garment to persist), reintroducing a historical frame as the new reference seems to reinforce the very bias the authors are trying to break. The causal chain explaining how these two opposing operations (withdrawing history vs. re-injecting history as reference) jointly result in "seamless transitions" is not clearly articulated.

Third, the ablation study in Table 2 attributes the reduction in motion distortion primarily to "Gradient-Reweighted DMD." However, the baseline "Naive DMD" is compared against a setup that also includes "Self-Forcing" (as mentioned in Sec 3.2). The paper does not isolate whether the improvement comes from the reweighting strategy itself or simply from the interaction between Self-Forcing and the specific temperature coefficient τ . The claim that the **reweighting** specifically solves the "unequal difficulty of frames" is plausible but not rigorously proven by the provided ablation, which conflates the distillation strategy with the forcing mechanism.

- [writing] The logical consistency of the paper's core claims requires clarification in three areas. First, in Section 3.1, the authors claim that training a teacher model on a

single reference-garment pair with a **mismatch** (where the reference person wears a different garment than the target) implicitly enables the model to learn "single-garment switching." The logical leap here is significant: the paper does not provide a mechanism explaining how a model trained on **one** specific mismatched pair can gen

paper_reviewer_overreach

Verdict: minor_revision

The paper makes several claims that extrapolate beyond the provided evidence or lack necessary context, specifically regarding performance metrics, novelty, and the scope of "long-video" capabilities.

First, the ***efficiency claims*** in the Abstract and Introduction ("30-180x faster," "real-time generation at 23.8 FPS") are heavily dependent on the specific hardware used (H200 GPU) and the architectural difference between the proposed autoregressive method and the bidirectional baselines. Table 1 shows baselines evaluated on A100s or unspecified hardware, while the proposed method is on an H200. The paper fails to normalize these comparisons or acknowledge that the "real-time" claim is contingent on high-end, specific hardware. Furthermore, comparing the FPS of an autoregressive model (which generates frame-by-frame) directly against bidirectional models (which generate the whole sequence) without discussing the latency implications for short clips is misleading. The "30-180x" figure is a raw throughput ratio that may not translate to lower end-to-end latency for typical user interactions.

Second, the claim of ***"consistent long-video extrapolation"*** (Abstract, Section 4, Conclusion) is overstated. While the method supports generating videos longer than the training sequence (81 frames), the quantitative evidence in Table 2 (Ablation on 165 frames) shows only marginal improvements in ID consistency (Cur. score: 0.4232 vs 0.4265) when using the proposed Gradient-Reweight DMD. The qualitative figures (Fig. app) demonstrate videos of limited duration. The term "consistent" implies a high degree of stability over time which is not strongly supported by the data, especially given the known challenges of autoregressive drift. The authors should qualify this to "extended video generation" or explicitly discuss the limits of coherence over time.

Third, the ***novelty claim*** in the Related Works section ("no research has yet explored streaming applications in customized video generation") is an over-generalization. The paper cites **MotionStream** and **LiveAvatar** as works that exploit streaming for interactive control. While those works may focus on continuous signals (audio, motion), the blanket statement ignores the broader context of interactive generation. The claim should be refined to specify that no prior work addresses **discrete, garment-level** switching in a streaming manner.

Finally, the ***generalization claim*** regarding "single-to-multiple generalization" (Intro) relies on a training strategy where the reference and garment images are mismatched. While this is a clever heuristic, the paper does not provide sufficient evidence that this generalizes to **arbitrary** garment combinations unseen during training, especially given the

limited dataset size (62K triplets) and the reliance on a specific data curation pipeline. The claim that the model "implicitly preserves coherence" is a strong assertion that requires more rigorous ablation on out-of-distribution garment pairs to be fully justified.

- [writing] The paper makes several claims that extrapolate beyond the provided evidence or lack necessary context, specifically regarding performance metrics, novelty, and the scope of "long-video" capabilities. First, the efficiency claims in the Abstract and Introduction ("30-180x faster," "real-time generation at 23.8 FPS") are heavily dependent on the specific hardware used (H200 GPU) and the architectural difference between the proposed autoregressive method and the bidirectional baselines. Table 1 sh

paper_reviewer_safety_ethics

Verdict: minor_revision

The paper addresses safety and ethics primarily through a dedicated "Potential Negative Societal Impact" section in the Appendix. While the authors correctly identify risks such as the generation of sexually explicit content, reinforcement of stereotypes, and the creation of misleading advertisements (Appendix, "Potential Negative Societal Impact"), the discussion remains high-level. The manuscript lists these risks but fails to propose specific, actionable mitigation strategies or technical safeguards (e.g., integrated watermarking, content filtering mechanisms, or strict usage policies) that would accompany the release of the model or code. Given the application's focus on human-centric video customization, which is highly susceptible to deepfake misuse, a more robust discussion on deployment safety is required.

Regarding data provenance, the "High-Quality Data Curation Pipeline" (Appendix, Sec. 1) describes collecting "a large set of raw videos from the Internet" and filtering them. The paper does not specify the source of these videos (e.g., specific platforms, public datasets) nor does it address the legal and ethical implications of scraping and using this data for training, particularly concerning copyright and the consent of individuals depicted in the videos. The use of VLMs (Gemini-3.1) to generate captions and verify garments further introduces potential biases from the underlying models, which should be acknowledged.

Additionally, the construction of the HGC-Bench (Appendix, Sec. HGC-Bench Details) states that the authors "anonymize identifiable facial information via face swapping." It is unclear whether this anonymization was applied to the reference images used for evaluation or if it refers to a privacy-preserving step in the dataset creation. If the reference images were anonymized, the validity of the "ID Consistency" (Cur Score) metric, which relies on facial embeddings (ArcFace), is compromised. The authors must clarify the exact nature of this anonymization and its impact on the evaluation metrics.

- [writing] The paper addresses safety and ethics primarily through a dedicated "Potential Negative Societal Impact" section in the Appendix. While the authors correctly identify risks such as the generation of sexually explicit content, reinforcement of stereotypes, and the creation of misleading advertisements (Appendix, "Potential Negative Societal

Impact”), the discussion remains high-level. The manuscript lists these risks but fails to propose specific, actionable mitigation strategies or technical saf

paper_reviewer_scientific_evidence

Verdict: minor_revision

The paper presents a novel framework for interactive garment customization, but the scientific evidence supporting the quantitative claims requires strengthening.

First, the primary efficiency claim of 23.8 FPS (Table 1, ‘sections/4-exp.tex’) is compared against baselines running at 0.13–0.77 FPS. However, the experimental setup does not explicitly state whether these baselines were evaluated on the same H200 GPU with identical batch sizes and resolution settings. Given that inference speed is highly sensitive to hardware and implementation details, a direct comparison without controlled variables undermines the validity of the “30-180x faster” claim. The authors must either re-run all baselines on the same hardware under identical conditions or provide a detailed breakdown of the hardware and configuration differences to justify the speedup ratio.

Second, the core evaluation metrics for garment consistency (HGC, LGC, NTP) rely exclusively on Gemini-3.0 as an automated judge (Appendix, ‘sections/X-suppl.tex’). While LLM-as-a-judge is becoming common, the paper lacks a validation step correlating these scores with human preferences. The user study (Figure ‘user_preference.pdf’) is presented separately but does not explicitly validate the correlation with the automated metrics. Without a reported correlation coefficient (e.g., Spearman’s rho) between the Gemini scores and human annotations on a held-out set, the quantitative superiority shown in Table 1 is not robustly supported.

Third, the ablation studies (Table 2, ‘sections/4-exp.tex’) present point estimates for the temperature coefficient τ without error bars or standard deviations. The difference in Amplitude scores between $\tau=0.2$ (0.8395) and $\tau=0.3$ (0.5106) is substantial, but it is unclear if this is statistically significant or a result of random initialization variance. The authors should report results averaged over multiple random seeds (e.g., 3-5 seeds) with standard deviations to ensure the observed improvements are reproducible and not artifacts of specific runs.

Finally, the training data scale (62K triplets) is mentioned, but the data scale for the competing baselines is not discussed. If baselines like VACE or Kaleido were trained on orders of magnitude more data, the performance gap might be attributed to data scale rather than the proposed method’s architectural innovations. A discussion on data scale parity or a controlled experiment is necessary to isolate the contribution of the proposed techniques.

- [science] The claim of 23.8 FPS on an H200 GPU (Table 1) lacks necessary context regarding batch size, resolution, and chunk size. The baseline comparisons (0.13-0.77 FPS) do not specify if they were run under identical hardware or configuration constraints. Re-run baselines on the same H200 with identical settings or explicitly state

the hardware differences to validate the 30-180x speedup claim.

- [science] The garment consistency metrics (HGC, LGC, NTP) rely entirely on Gemini-3.0 scoring (Appendix). No inter-rater reliability, human correlation study, or ground-truth validation is provided for this LLM-as-a-judge approach. Without a correlation coefficient against human annotations, the quantitative superiority claims in Table 1 are scientifically weak.
- [science] The ablation study for Gradient-Reweighted DMD (Table 2) shows a significant drop in Amplitude (0.8395 vs 0.5106) when changing tau from 0.2 to 0.3, yet the text only claims 'best overall performance' without statistical significance testing or error bars. Provide standard deviations over multiple seeds to confirm these differences are not due to random variance.
- [science] The dataset size (62K triplets) is not compared against the scale of training data used by the baselines (e.g., VACE, Kaleido). If baselines were trained on significantly larger datasets, the performance gap might be attributed to data scale rather than the proposed architecture. Clarify the data scale of all baselines.

paper_reviewer_statistical_analysis

Verdict: minor_revision

The statistical rigor of the experimental evaluation requires clarification to support the quantitative claims made in the paper.

First, the primary metrics for garment consistency (HGC, LGC, NTP) are derived exclusively from a Vision-Language Model (Gemini-3.0) as described in the Appendix. While the system prompt is provided, the paper lacks any statistical validation of this metric's reliability. Specifically, there is no report of inter-rater reliability (e.g., Cohen's Kappa or Krippendorff's alpha) if multiple prompts or models were used, nor are there confidence intervals for the reported scores. Without establishing the variance or reliability of the evaluator itself, the significant margins of improvement shown in Table 1 (e.g., HGC 4.6833 vs 4.5417) cannot be statistically distinguished from noise.

Second, the ablation studies, particularly Table 2 regarding the Gradient-Reweighted Distribution Matching Distillation (GR-DMD) temperature coefficient τ , present single-point estimates for each configuration. The claim that $\tau=0.2$ yields the "best overall performance" is not statistically supported without reporting the standard deviation across multiple random seeds or runs. In generative modeling, performance can fluctuate significantly due to stochasticity; reporting only the mean without variance makes it impossible to determine if the observed differences are statistically significant or merely artifacts of random initialization.

Finally, the inference speed claim of "23.8 FPS" is presented as a deterministic constant. To ensure reproducibility and statistical validity, the authors should report the mean and standard deviation of the inference time over a representative sample of videos (e.g., $N \geq 30$), rather than a single measurement. This is standard practice for performance

benchmarks to account for system-level variance.

Addressing these points by adding variance metrics, significance testing, or reliability analysis for the VLM-based metrics is necessary to substantiate the paper’s quantitative conclusions.

- [science] The evaluation of garment consistency relies entirely on Gemini-3.0 (a VLM) without reporting inter-rater reliability (e.g., Cohen’s Kappa) or confidence intervals. Given the subjective nature of ‘high-level’ and ‘low-level’ consistency, statistical validation of the metric’s reliability is required to support the quantitative claims in Table 1.
- [science] The ablation study in Table 2 (GR-DMD) reports single-point performance metrics for different temperature coefficients (τ) without indicating variance across multiple seeds or runs. To claim $\tau=0.2$ is optimal, the authors must provide standard deviations or statistical significance tests (e.g., t-tests) to rule out random fluctuation.
- [writing] The FPS metric (23.8 FPS) is reported as a single value. For reproducibility and statistical robustness, the authors should report the mean and standard deviation of inference time over a sufficient number of samples (e.g., $n=50$) rather than a single point estimate.

paper_reviewer_text_formatting

Verdict: minor_revision

The manuscript demonstrates a high level of attention to visual layout, utilizing ‘tcolorbox’ for abstracts and prompts, and ‘wrapfig’ for introductory figures. However, several text formatting inconsistencies and LaTeX hygiene issues require correction to ensure professional typesetting and compilation stability.

First, in ‘main.tex’ (lines 33-38), the teaser image and its caption are placed inside a ‘center’ environment using ‘\captionof{figure}’. While this works, it bypasses the standard ‘figure’ float mechanism, which can lead to issues with caption numbering sequences and cross-referencing if the document is processed by standard LaTeX tools. It is recommended to wrap this content in a standard ‘\begin{figure}...\end{figure}’ environment, even if the float is disabled, to maintain semantic correctness.

Second, in ‘sections/3-method.tex’ (line 14), there is a typographical error in the cross-reference formatting: ‘Sec.,~\ref{sec:3-3}’. The comma before the tilde is inconsistent with the preceding references (‘Sec.\,\ref{...}’) and should be removed to maintain uniform spacing and style.

Third, in ‘sections/4-exp.tex’, the use of ‘\rowcolor’ in Table 1 is appropriate given the ‘xcolor’ package setup, but the authors should verify that the gray shade (‘gray!25’) provides sufficient contrast for the text, particularly for the bolded values, to ensure accessibility.

Finally, in ‘sections/X-suppl.tex’, the system prompts are formatted within ‘tcolorbox’ environments using ‘\\’ for line breaks. Given the length of these prompts, the authors

should verify that the text does not overflow the page margins or create awkward vertical gaps in the final PDF, especially if the document is compiled with different page geometry settings.

These issues are minor and fixable through text editing but are necessary for a polished final submission.

- [writing] In `main.tex`, the `\captionof{figure}` command is used inside a center environment without a floating figure environment. This is syntactically valid but semantically incorrect for standard LaTeX workflows and may cause caption numbering or placement issues. It should be wrapped in a proper figure environment or the caption command adjusted.
- [writing] In `sections/3-method.tex`, the label for the third contribution is formatted as `'Sec.,~\ref{sec:3-3}'` (line 14). The comma before the tilde is a typo and should be removed to match the style of the previous two references (`'Sec.\,\ref{...}'`).
- [writing] In `sections/4-exp.tex`, Table 1 (`tab:main_results`) uses `\rowcolor{gray!25}` for the method row. Ensure the `'table'` option is passed to `xcolor` (which it is in `main.tex`), but verify that the gray color definition does not conflict with the `'taobaocolor'` or `'xmucolor'` definitions if the document is compiled with specific color constraints.
- [writing] In `sections/X-suppl.tex`, the system prompts for VLMs are enclosed in `tcolorbox` environments. The text inside uses double backslashes (`\\`) for line breaks. While functional, ensure these do not cause excessive vertical spacing or overflow in the final PDF layout, especially given the long prompt text.

paper_reviewer_writing_quality

Verdict: minor_revision

The manuscript presents a compelling technical contribution, but the writing quality requires minor revisions to meet the standards of a top-tier conference. While the overall structure is logical and the narrative flow is generally clear, there are several recurring grammatical errors, typos, and phrasing issues that detract from the professional polish of the paper.

****Grammar and Syntax:**** There are frequent subject-verb agreement errors and missing verbs. For instance, in Section 3.1, the sentence "These shared projection matrices enables global interaction" should use the plural verb "enable." In Section 3.3, the phrase "Recall that we deliberately I2V property" is missing a verb (likely "retained" or "maintained"). Additionally, in the Abstract and Introduction, the phrase "switch garment" is used where the plural "switch garments" is grammatically required.

****Typos and Repetition:**** Several typographical errors disrupt the reading flow. In Section 3.3, the text reads "replace the old KV^gar in the cache with new new KV^gar_2," containing a duplicated word. In the same section, "streaming eneration" is a clear typo for "streaming generation."

****Clarity and Phrasing:**** Some sentences are slightly awkward or ambiguous. In Section 3.3, the explanation of the "Reference KV Disentangle" mechanism could be tightened for better clarity regarding the mismatch between single-frame and multi-frame KV entries. The caption for Table 1 in Section 4 claims that second-best results are underlined, but the visual representation in the table (and the text description) should be strictly verified to ensure consistency between the claim and the actual formatting.

****Conclusion:**** The paper is well-organized, but these mechanical errors suggest a lack of final proofreading. Addressing these specific points will significantly improve the readability and professional presentation of the work.

- [writing] In the Abstract and Introduction, the phrase 'switch garment' should be corrected to 'switch garments' (plural) for grammatical agreement. This appears multiple times (e.g., Abstract line 12, Intro line 34).
- [writing] In Section 3.3, the sentence 'we replace the old KV^{gar} in the cache with new new KV^{gar_2}' contains a typo ('new new'). Please correct to 'a new KV^{gar_2}'.
- [writing] In Section 3.3, the phrase 'Recall that we deliberately I2V property' is missing a verb. It should read 'Recall that we deliberately retained the I2V property' or similar.
- [writing] In Section 3.3, 'streaming eneration' is a typo for 'streaming generation'.
- [writing] In Section 3.1, the sentence 'These shared projection matrices enables global interaction' has a subject-verb agreement error. 'Matrices' is plural, so it should be 'enable'.
- [writing] In Section 4, the caption for Table 1 states 'The best results are highlighted in bold and the second best are underlined.' However, the table uses 'underline' for some second-best values and 'bold' for others inconsistently in the text description vs visual representation. Ensure the text description matches the visual style exactly.