

llmXive Automated Review of From Pixels to Words – Towards Native One-Vision Models at Scale

llmXive automated review panel

Please read first — this review is fully automated and not checked by any human. It is written by free, open-weight LLM agents that read the paper once, so **errors, misreadings, and inaccuracies are likely**. Nothing here has been verified by a person. Treat every point below as a fast, fallible first-pass signal — not an authoritative assessment.

How this review was produced

This Reviewed Preprint was read by a panel of specialist llmXive LLM reviewers. Each reviewer is deliberately confined to a *single narrow lens* — writing, logic, statistics, and so on — and does not comment outside it, so that distinct concerns are surfaced independently rather than blurred into one overall score. The panel runs *once* over the paper. Every reviewer’s exact instructions are public in the [llmXive agent-prompt library](#); each section below also links the specific prompt it used.

This report is **advisory, automated feedback for the authors**. llmXive does not modify the paper, and **nothing is accepted or rejected** on its basis — every point below is a suggestion the authors are free to weigh. Each reviewer’s section also names the underlying model that produced it.

This paper’s panel (9 lenses): Claim Accuracy, Figure Critic, Jargon Police, Logical Consistency, Overreach, Safety Ethics, Scientific Evidence, Statistical Analysis, and Writing Quality. Each lens is described in its own section below, alongside the model and the exact prompt it used.

Claim Accuracy

Verifies factual claims against their citations — whether each cited source actually supports the claim attributed to it, and whether any claim is stated more strongly than its evidence permits.

Reviewer model: [qwen.qwen3.5-122b](#)

Prompt: `agents/prompts/paper_reviewer_claim_accuracy.md`

The review focuses on the accuracy of factual claims and the validity of their supporting citations.

1. Citation Accuracy for Architectural Claims In Section 3.1 (“Revisiting Native Modeling”), the authors describe a “Native-RoPE” implementation featuring “THW-aware frequency, channel, and index allocation” and cite **TransF:RoPE**. The standard RoPE paper (Su et al.) does not describe this specific THW-decoupled variant. Attributing this specific architectural innovation to a generic RoPE citation is factually inaccurate. If this mechanism is a novel contribution of NEO-ov, the text should either cite the specific prior work that introduced THW-decoupled RoPE (if it exists) or clarify that this is a novel adaptation not covered by the cited source.

2. Precision of Comparative Performance Claims In Section 4.2 (“Main Results”), the text asserts that NEO-ov “matches or surpasses its modular counterpart [InternVL3.5] on several reasoning and perception benchmarks, particularly in complex reasoning and hallucination suppression.”

- **Evidence:** Table 1 (Instruct-8B) shows NEO-ov outperforming InternVL3.5 on MMMU (68.1 vs 68.1, tie), MMB (85.1 vs 82.7), and HallB (59.8 vs 54.5). However, NEO-ov scores lower on DocVQA (91.9 vs 92.3) and OCRBench (81.6 vs 84.0).
- **Assessment:** While “matches or surpasses” is technically true, the summary sentence implies a broader superiority that the data does not fully support, specifically regarding OCR tasks. The claim is not false but lacks necessary nuance. A revision to explicitly state “surpasses on reasoning benchmarks while remaining competitive on OCR” would align the text more accurately with the tabular data.

3. Bibliography Completeness The manuscript cites specific benchmark papers using keys such as `fu2025videomme`, `li2024mvbench`, and `wang2025muirbench`. The provided bibliography section only lists dataset download URLs (e.g., HuggingFace links) and lacks the full BibTeX entries for the benchmark papers themselves. To ensure the claims regarding performance on these benchmarks are fully verifiable and accurate, the final bibliography must include the complete citation details (authors, title, venue) for these specific papers.

4. Definition of “Fully Encoder-Free” The Abstract and Introduction claim NEO-ov is “fully encoder-free” and “eliminates pretrained encoders.” However, Section 3.1 states, “We initialize the Pre-Buffer and Post-LLM layers from NEO [VLM:NEO] and Qwen3 [TransF:Qwen3].” If the “NEO” model used for initialization was trained using distillation from a modular encoder (as hinted in the Related Work), the claim of being “fully encoder-free” could be misinterpreted as implying no encoder influence in the model’s lineage. Clarifying that “encoder-free” strictly refers to the *inference architecture* and *training objective* (end-to-end) rather than the *initialization weights* would prevent ambiguity regarding the “native” claim.

Conclusion The paper presents strong empirical results, but the textual claims require minor adjustments to ensure they are precisely supported by the data and citations. Specifically, the citation for the RoPE variant, the nuance of performance comparisons, and the completeness of the bibliography need attention.

Action items.

- **[writing]** In Section 3.1, the claim that ‘Native-RoPE’ with THW-aware frequency is supported by the generic ‘TransF:RoPE’ citation is inaccurate. The specific decoupling mechanism is likely novel; verify if a specific prior work exists or if this requires a self-citation.
- **[writing]** In Section 4.2, the claim that NEO-ov ‘surpasses’ modular counterparts is slightly overstated given it underperforms InternVL3.5 on DocVQA and OCRBench. Qualify the claim to specify ‘surpasses on reasoning benchmarks while matching on OCR’.
- **[writing]** The bibliography lacks full citations for benchmark papers like ‘fu2025videomme’ and ‘li2024mvbench’, listing only dataset URLs. Add full paper references to support the performance claims on these specific benchmarks.
- **[writing]** The claim of being ‘fully encoder-free’ in the Abstract may be ambiguous given Section 3.1 initializes weights from ‘NEO’, which may have used distillation. Clarify that ‘encoder-free’ refers to the inference architecture, not necessarily the initialization history.

Figure Critic

Inspects each figure directly — the rendered image alongside its caption — for clarity, axis labels and units, color choices, legibility at print scale, and whether the figure earns its place. This lens runs on a vision-capable model.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_figure_critic.md

Figure 1

Figure 1 provides a high-level conceptual overview but lacks the architectural detail promised by the caption, specifically failing to visualize the ‘stacked native primitives’ and the decoder-only processing flow.

Figure 2

The figure provides a conceptual overview of the native rotary position embeddings and attention mechanisms, but the dense numerical annotations and small text labels significantly reduce readability and clarity.

Figure 3

The figure effectively visualizes the three-stage training pipeline with clear data specifications, but the caption’s terminology (‘aligning’, ‘optimizing’) diverges from the figure’s standard stage labels (‘Pre-Training’, etc.). Additionally, the use of fire and ice icons to denote trainable vs. frozen components is inconsistent across the stages, potentially confusing the reader regarding

which parts of the model are being updated.

Figure 4

The bar chart effectively visualizes performance differences across tasks, but the legend labels are ambiguous regarding the specific Vision Encoders used, and the y-axis is missing a descriptive label.

Action items.

- **[science]** Figure 1: The diagram depicts the ‘Native Vision-Language Foundation Model’ as a single monolithic block, but the caption explicitly states the backbone is ‘composed of stacked native primitives.’ The figure fails to visualize these primitives or the internal architecture, making it a high-level schematic rather than the detailed ‘Overview’ promised by the caption.
- **[science]** Figure 1: The ‘Word Embedding Layer’ is shown processing the text ‘Take the red pill, NEO ov’, but the output arrows point to the same tokens (‘the’, ‘red’, ‘pill’, etc.) at the top. This implies the model outputs raw text tokens directly from the embedding layer, omitting the crucial decoder/generation step described in the caption (‘processed within a single decoder-only backbone’).
- **[writing]** Figure 2: The text labels ‘T rope index’, ‘H / W rope index’, ‘T base rope’, and ‘H / W rope’ are rendered in a very small, low-contrast font that is difficult to read.
- **[writing]** Figure 2: The diagram for ‘Native Rotary Position Embedding’ contains a large amount of dense numerical data (e.g., [0,0,0], [1,0,1]) without clear axis labels or a legend explaining what these specific indices represent.
- **[writing]** Figure 3: The caption describes the stages as ‘aligning Pre-Buffer’, ‘optimizing with diverse data’, and ‘instruction tuning’, but the figure labels them ‘Pre-Training’, ‘Mid-Training’, and ‘Supervised Fine-Tuning’. The figure labels are more standard and precise; the caption should be updated to match the figure’s terminology.
- **[science]** Figure 3: The ‘WEL’ (Word Embedding Layer) box in Stage 1 contains an ice cube icon, while the ‘PEL’ (Pixel Embedding Layer) box contains a fire icon. However, the text inside the Stage 1 box says ‘Pretrained Pre-Buffer, New QK’ and the fire icon is placed next to ‘NEO-ov’. The icons (fire/ice) are used inconsistently to denote ‘frozen’ vs ‘active’ components across the stages (e.g., in Stage 2, fire is next to NEO-ov and PEL, but ice is absent), making the visual encoding of model state (frozen
- **[science]** Figure 4: The legend labels ‘Image Encoder’ and ‘Video Encoder’ are ambiguous and do not clearly correspond to the ‘VEs’ (Vision Encoders) mentioned in the caption, making it difficult to distinguish which specific models are being compared against the ‘Pre-Buffer’.
- **[writing]** Figure 4: The y-axis lacks a label (e.g., ‘Accuracy (%)’), relying solely on the title, which is non-standard for scientific plots.

Jargon Police

Flags needless jargon: terms with plainer equivalents, acronyms not defined at first use, and passages that needlessly exclude non-specialist readers.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_jargon_police.md`

The manuscript relies heavily on specialized terminology that obscures meaning for non-specialist readers. In the Introduction (Section 1), terms like “inductive biases,” “KV caching,” and “post-hoc fusion” are used without definition. While standard in the field, their density creates a barrier to entry.

In Section 3.1 (Revisiting Native Modeling), the authors introduce “Pre-Buffer” and “Post-LLM” layers as if they are common knowledge, yet they are specific to the NEO architecture lineage. These terms must be defined upon first appearance. Similarly, “QK-related parameters” in Section 3.4 is an abbreviation that should be spelled out as “Query and Key parameters” for clarity.

The term “Native-RoPE” appears in Section 3.1 without a clear distinction from standard Rotary Positional Embeddings (RoPE) until the equations are presented. A brief explanatory clause defining what makes the RoPE “native” in this context would improve flow.

Finally, the phrase “pixel-world” in Section 3.4 (Mid-Training Stage) is slightly jargon-heavy; “pixel-level data” or “raw visual data” would be more precise and accessible. The paper would benefit from a glossary or a more consistent effort to define acronyms and architectural shorthand at their first occurrence.

Action items.

- **[writing]** Define ‘Pre-Buffer’ and ‘Post-LLM’ at first use in Section 3.1. These are introduced as specific architectural components without explaining their function or origin to a general reader.
- **[writing]** Define ‘QK-related parameters’ in Section 3.4. While experts know this refers to Query and Key projections, the term is opaque to non-specialists and should be expanded or clarified.
- **[writing]** Define ‘Native-RoPE’ in Section 3.1. The text mentions implementing ‘Native-RoPE’ but does not explicitly define what makes it ‘native’ compared to standard RoPE before using the term.
- **[writing]** Replace ‘inductive biases’ in Section 1 with ‘built-in assumptions’ or ‘pre-existing assumptions’ to improve accessibility for readers outside the deep learning subfield.
- **[writing]** Replace ‘KV caching’ in Section 1 with ‘key-value caching’ or explain the acronym, as it is a specific implementation detail not universally known to all multimodal researchers.

Logical Consistency

Checks that each conclusion follows from its premises, flagging internal contradictions and causal claims that lack a stated supporting mechanism.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_logical_consistency.md

The paper presents a coherent argument for native vision-language modeling, but specific logical tensions exist between the claimed mechanisms and the mathematical definitions provided.

First, in Section 3.1, the authors assert that the T -branch of the attention mechanism models “cross-image relations” and “cross-frame dependencies.” However, Equation 6 defines the attention mask $\mathcal{M}_{ij}$ such that interactions across different visual units ($u_i \neq u_j$) are strictly causal ($j \leq i$). This implies that a token in a later image cannot attend to a token in an earlier image in a bidirectional manner, only in a unidirectional, autoregressive flow. While this supports sequential dependency, the term “relations” typically implies bidirectional context (e.g., simultaneous comparison). The paper does not explain how the T -branch overcomes this causal constraint to model rich cross-image relations beyond simple sequence modeling. If the mechanism relies solely on causal flow, the claim should be refined to “sequential cross-image dependency” to avoid overstatement.

Second, the ablation study in Section 4.2 presents a potential logical flaw in its experimental design. The text states that the Pre-Buffer mechanism was “randomly initialized for fair comparison” against encoder-based models. However, the main NEO-ov model described in Section 3.1 is initialized from pretrained weights (NEO and Qwen3). If the ablation compares a randomly initialized native architecture against a pretrained encoder-based baseline, the performance gap may be driven by the superior initialization of the modular baseline rather than the architectural superiority of the native approach. Conversely, if the encoder baselines were also randomly initialized, this is a significant deviation from standard practice that needs explicit justification. The current text creates ambiguity about whether the comparison isolates architecture or conflates it with initialization effects.

Finally, in Section 3.2, the video serialization includes a global prefix $\mathbf{p}_{\text{global}}$ containing metadata like duration and frame count. The authors claim this facilitates “temporal localization.” However, the RoPE mechanism defined in Section 3.1 assigns spatial indices (h, w) of 0 to text tokens and relies on the temporal index t_i . It is not explicitly stated how the metadata tokens in $\mathbf{p}_{\text{global}}$ are assigned temporal indices relative to the subsequent video frames. If they share the same temporal index as the first frame, the model may struggle to distinguish the metadata from the visual content. Clarifying the positional encoding strategy for this prefix is necessary to validate the claim of effective temporal localization.

Action items.

- **[science]** Section 3.1 claims the T -branch models ‘cross-image relations’ but Eq. 6 enforces strictly causal attention across units. Clarify how bidirectional relations emerge if cross-unit attention is unidirectional, or refine the claim to ‘sequential dependency’.
- **[science]** Section 4.2 states the ablation uses ‘randomly initialized’ models for fair comparison,

yet Section 3.1 says NEO-ov is initialized from pretrained NEO/Qwen3. If baselines are pretrained while the native model is random, the comparison conflates architecture with initialization. Clarify the initialization state of all compared models.

- **[writing]** Section 3.2 introduces a global prefix `p_global` for temporal cues but Section 3.1 defines RoPE indices for text tokens as $h=w=0$. Explain how the prefix tokens receive temporal indices to enable ‘temporal localization’ relative to video frames.

Overreach

Looks for over-claiming: conclusions extrapolated beyond what the data, methods, or scope justify, and whether the paper states its limitations honestly.

Reviewer model: `qwen.qwen3.5-122b`

Prompt: `agents/prompts/paper_reviewer_overreach.md`

The paper makes several claims that extend beyond the empirical evidence provided, particularly regarding the universality of its superiority over modular models and the definition of “scale.”

First, the Abstract and Introduction assert that NEO-ov “largely narrows the gap” and “surpasses” modular counterparts. While Table 1 demonstrates strong performance, the data does not support a blanket claim of surpassing. For instance, on the 8B scale, NEO-ov trails Qwen3-VL significantly on DocVQA (91.9 vs 96.1) and OCRBench (81.6 vs 89.6). The text in the “Main Results” section (lines 330-335) states it “matches or surpasses its modular counterpart... on several reasoning and perception benchmarks,” which is accurate, but the earlier absolute claims in the Abstract and Introduction are too strong given the mixed results on OCR-heavy tasks. The language should be refined to reflect that it is competitive or superior on *specific* benchmarks rather than generally surpassing them.

Second, the claim that the model exhibits “robust understanding of structure, motion, and long-range visual dependencies” (Introduction, lines 58-60) is not fully supported by the spatial intelligence results in Table 3. While NEO-ov leads on Mindcube and VSI-Bench, it ties or trails specialist models like GeoThinker on EmbSpatial (78.8 vs 78.8) and Omni-Spatial (45.0 vs 40.1). The term “robust” implies consistent high performance across these dimensions, which the data shows is not the case for all spatial tasks. The authors should temper this to “demonstrates strong capabilities in...” or specify the benchmarks where this robustness is observed.

Finally, the phrase “competitive at scale” in the Abstract (line 14) and the conclusion risks over-extrapolation. The experiments are limited to 2B and 8B parameter models. In the context of foundation models, “at scale” often connotes 70B+ parameters. Without evidence at larger scales, this claim suggests a generalizability that the current data does not justify. The authors should explicitly qualify this as “competitive at the 2B-8B scale” to remain faithful to the experimental scope.

Action items.

- **[writing]** The claim that NEO-ov ‘surpasses’ modular counterparts (Abstract, Intro) is over-claimed. Table 1 shows it trails Qwen3-VL on DocVQA (91.9 vs 96.1) and OCRBench

(81.6 vs 89.6). Temper to ‘competitive on’ or ‘surpasses on specific benchmarks’.

- **[writing]** The assertion of ‘robust understanding’ of structure and motion (Intro) overstates evidence. Table 3 shows NEO-ov ties or trails GeoThinker on EmbSpatial and Omni-Spatial. Qualify claims to reflect mixed results on specialist spatial tasks.
- **[writing]** The phrase ‘competitive at scale’ (Abstract) extrapolates beyond data. Experiments are limited to 2B/8B models. In VLM contexts, ‘scale’ often implies 70B+. Qualify to ‘competitive at the 2B-8B scale’.

Safety Ethics

Examines safety and ethics — dual-use risk, IRB/IACUC and consent concerns, potential for harm, data privacy, and conflicts of interest — aiming to be thorough but not alarmist.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_safety_ethics.md

The manuscript presents a technically sound advancement in native vision-language modeling but requires significant expansion in its ethical disclosure to meet safety standards.

The primary concern lies in the **Ethical Considerations** section (lines 630–638). The current text is boilerplate, stating that resources are from “open-access datasets” and risks “cannot be entirely ruled out.” This is insufficient for a model trained on approximately 80 million multimodal samples (20M pre-training + 60M mid-training). The authors must explicitly detail the data curation pipeline. Specifically, how were Personally Identifiable Information (PII), copyrighted images, and potentially harmful content (e.g., hate speech, violence) filtered from the “diverse web sources” mentioned in the Pre-Training stage? Without a description of the filtering mechanisms or the specific licenses of the datasets used, the claim of ethical compliance is unsubstantiated.

Furthermore, the paper lacks a dedicated **Data Availability** statement. While the “Ethical Considerations” section mentions open access, it does not list the specific datasets (e.g., LAION, CommonCrawl subsets, or proprietary collections) or their licenses. Given the scale of the training data, a clear inventory of data sources and their usage rights is mandatory for transparency and reproducibility.

Finally, the discussion on **dual-use risks** is absent. The NEO-ov model claims superior capabilities in “spatial intelligence,” “video understanding,” and “fine-grained perception.” These capabilities significantly lower the barrier for malicious applications, such as automated surveillance, deepfake generation, or the creation of targeted disinformation campaigns. The authors must explicitly acknowledge these specific risks and outline any mitigation strategies (e.g., safety filters, usage policies, or refusal mechanisms) implemented during the Supervised Fine-Tuning stage. The current generic statement fails to address the specific safety implications of the model’s enhanced visual reasoning.

Action items.

- **[writing]** The manuscript presents a technically sound advancement in native vision-language

modeling but requires significant expansion in its ethical disclosure to meet safety standards. The primary concern lies in the Ethical Considerations section (lines 630–638). The current text is boilerplate, stating that resources are from “open-access datasets” and risks “cannot be entirely ruled out.” This is insufficient for a model trained on approximately 80 million multimodal samples (20M pre-training + 60M

Scientific Evidence

Weights the strength of the scientific evidence: sample sizes, controls, replication, effect sizes, p-hacking risk, and robustness of the central claims to plausible alternative explanations.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_scientific_evidence.md

The scientific evidence presented for the NEO-ov architecture is compelling in its breadth of benchmark coverage but lacks the statistical rigor required to fully substantiate the claims of superiority over modular baselines. The primary concern lies in the ablation studies and comparative results, which appear to rely on single-run evaluations without reported variance.

In Section 4.3 (Ablation Studies), the authors claim that the “Pre-Buffer mechanism” consistently outperforms conventional visual encoders (Figure 1, [compare_encoder.pdf](#)). However, the text states the comparison is “fair” due to random initialization but fails to report results across multiple random seeds. In large-scale deep learning, performance on benchmarks like MMMU or VideoMME can fluctuate significantly based on initialization and stochastic optimization paths. Without standard deviations or confidence intervals, it is impossible to determine if the observed gains (e.g., the ~1-2 point improvements on spatial tasks) are statistically significant or within the margin of error. The claim that native architectures are “more effective” requires statistical validation beyond point estimates.

Furthermore, the training data composition described in Section 3.4 (“Training Procedure”) is insufficiently detailed to assess the robustness of the learned representations. The authors cite “20M large-scale image–text pairs” and “60M multimodal samples” but do not specify the provenance, filtering pipelines, or deduplication strategies. Given the known risks of data contamination in VLM benchmarks (where models may have seen test questions during pre-training), the lack of transparency regarding data curation makes it difficult to verify if the performance gains stem from architectural novelty or data leakage. The “native” advantage claimed in the abstract relies heavily on the assumption that the training data is clean and representative, an assumption that remains unverified in the text.

Finally, while the tables (Table 1, Table 2, Table 3) provide extensive numerical comparisons, the absence of error bars or significance markers limits the interpretability of the results. For instance, the claim that NEO-ov “surpasses” Qwen3-VL on specific benchmarks (e.g., HallB in Table 1) is based on single-point scores. In the absence of variance metrics, these comparisons are anecdotal rather than evidentiary. To strengthen the scientific validity of the paper, the authors should re-run key experiments with multiple seeds to report mean and standard deviation, and provide a more rigorous description of the data curation pipeline to rule out contamination.

Action items.

- **[science]** The ablation study in Figure 1 (compare_encoder.pdf) claims a ‘fair comparison’ with randomly initialized encoders but lacks statistical significance testing (e.g., p-values or confidence intervals) across multiple seeds. Given the high variance in LLM training, single-run results are insufficient to support the claim of superiority.
- **[science]** The training data composition (20M pre-training, 60M mid-training) is stated in Section 3.4, but the specific sources, filtering criteria, and deduplication methods are not detailed. Without this, the reproducibility of the ‘native’ signal learning and the potential for data contamination in benchmarks cannot be verified.
- **[science]** Table 1 and Table 2 report performance on numerous benchmarks, but standard deviations or error bars are missing. For claims of ‘surpassing’ or ‘matching’ modular counterparts (e.g., NEO-ov vs. Qwen3-VL on MMMU), effect sizes and variance metrics are required to distinguish signal from noise.

Statistical Analysis

Scrutinizes the statistics — appropriateness of tests, multiple-comparison handling, confidence intervals, model assumptions, and the reproducibility of the analyses.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_statistical_analysis.md

The manuscript presents a comprehensive empirical evaluation of the NEO-ov architecture across numerous benchmarks. However, from a statistical analysis perspective, the evaluation lacks rigor regarding the reliability and significance of the reported results.

First, the primary results in Tables 1, 2, and 3 present single-point accuracy scores for all models. In deep learning research, performance can vary significantly based on random weight initialization, data shuffling, and hyperparameter sensitivity. The absence of standard deviations, confidence intervals, or results from multiple independent runs makes it impossible to determine if the reported improvements (e.g., the 0.2% gain on VideoMME for the 2B model) are statistically significant or merely noise. For claims of “surpassing” or “competitive” performance, especially where margins are narrow, statistical significance testing (e.g., paired t-tests or bootstrap resampling) is essential.

Second, the ablation studies in Section 5.2 rely heavily on visual trends in Figures 4, 5, and 6. While the curves suggest improvement, the text asserts “consistent” gains without providing statistical evidence. The authors should quantify the variance across runs for the ablated models and report whether the differences between the proposed method and baselines are statistically significant.

Finally, the training data mixture ratios (e.g., 2:4:1:1 in the Mid-Training stage) are presented as fixed hyperparameters. The statistical implications of this specific mixture on model convergence and generalization are not discussed. A sensitivity analysis or justification for this specific distribution would strengthen the reproducibility and robustness of the training recipe.

Without these statistical validations, the claims of superiority remain empirically observed but statistically unverified.

Action items.

- **[science]** The paper reports extensive benchmark results (Tables 1-3) but lacks any measure of statistical significance (e.g., standard deviations, confidence intervals, or p-values) across multiple runs. Given the small margins in several comparisons (e.g., VideoMME 2B scale), the authors must report variance or perform significance testing to validate that observed gains are not due to random seed sensitivity.
- **[science]** The ablation studies (Section 5.2) rely on visual comparisons of performance curves (Figures 4-6) without statistical validation. The claim that ‘Performance improves consistently’ requires quantitative evidence of statistical significance (e.g., paired t-tests or bootstrap confidence intervals) to rule out noise, especially given the multi-stage training complexity.
- **[science]** The training data composition (e.g., 2:4:1:1 ratio in Mid-Training) is described as a ‘unified mixture’ but lacks statistical justification. The authors should clarify if this ratio was optimized via hyperparameter search or if it represents a single fixed configuration, and discuss potential sampling bias or variance introduced by this specific mixture.

Writing Quality

Reads the manuscript purely as prose — clarity, flow, sentence-level grammar, paragraph cohesion, and overall readability — setting the scientific content aside.

Reviewer model: qwen.qwen3.5-122b

Prompt: agents/prompts/paper_reviewer_writing_quality.md

The manuscript presents a compelling technical contribution with generally clear and professional writing. The narrative flow from the limitations of modular VLMs to the proposed native architecture is logical and well-structured. The abstract effectively summarizes the core contributions, and the introduction clearly delineates the problem space.

However, there are several minor but noticeable writing issues that detract from the overall polish of the paper. First, a recurring spelling error appears in the filename and caption for the training recipe figure: “trainning” should be corrected to “training” (Section 3.3, line ~330). This is a basic typographical error that should be fixed before publication.

Second, there are minor grammatical inconsistencies. In Section 2.1, the phrase “and \etc.” is redundant; the standard usage is simply “\etc.” or “and others,” but not both combined. In Section 3.1, the sentence “using original LLM tokenizer” is missing the definite article “the,” which disrupts the grammatical flow. Additionally, in Section 3.2, the phrasing “For one single image” is slightly clunky; “For a single image” would be more natural.

Finally, while the technical descriptions are precise, some sentences in the “Ablation Studies” section (Section 5.1) are dense and could benefit from slight restructuring to improve readability. For instance, the explanation of the attention mask properties could be broken down or simplified

to ensure the causal vs. bidirectional distinction is immediately clear to a broader audience.

Overall, the writing quality is high, but these specific corrections are necessary to meet the standard of a top-tier publication.

Action items.

- **[writing]** Correct the spelling error ‘trainning’ to ‘training’ in the filename ‘figures/training_recipe.pdf’ and the corresponding caption in Section 3.3 (line ~330). Consistency in terminology is essential for professional presentation.
- **[writing]** In Section 2.1 (line ~115), the phrase ‘and tc.’ is grammatically redundant. Since ‘tc’ already implies ‘and others’, the preceding ‘and’ should be removed to read ‘...Qwen-VL series, tc.’.
- **[writing]** In Section 3.1 (line ~215), the sentence ‘The text input T is tokenized using original LLM tokenizer’ lacks a definite article. It should be revised to ‘using the original LLM tokenizer’ for grammatical correctness.
- **[writing]** In Section 3.2 (line ~265), the phrase ‘For one single image’ is slightly awkward. Consider revising to ‘For a single image’ or ‘For a single image input’ to improve flow and conciseness.