

Prospectus:
*How do context and time modulate the geometric trajectory of
memory?*

Paxton Fitzpatrick

February 3, 2019

1 Rationale

In traditional free recall studies, participants are presented with a series of items (e.g. words, pictures, etc.), then asked to recall them to the best of their abilities. The findings yielded by such studies on recall order and transitions (Murdock, 1962; Kahana, 1996), temporal and semantic clustering tendencies (Howard and Kahana, 2002b), and response latency (Murdock and Okada, 1970) have given rise to numerous models of memory encoding, storage, and retrieval (e.g., Atkinson and Shiffrin, 1968; Howard and Kahana, 2002a; Sederberg et al., 2008). These models, in turn, have spurred investigations into the biological underpinnings of their functional predictions (e.g., Polyn et al., 2005; Manning et al., 2011). However, the free recall paradigm is limited in its ability to assess episodic memory for real-world events (see Koriart and Goldsmith, 1994; Huk et al., 2018). Its inherently discretized stimuli, binary accuracy evaluation, and reliance on subjects’ precisely reproduction of the presented stimulus clash with the steady, continuous evolution of real-life situations and the value we instead place on capturing their general gist or substance in assessing our (or others’) memories for them.

The emergence and popularization of naturalistic memory paradigms offers the opportunity to create and refine new context-driven models (**citation needed?**) that better reflect the workings of episodic memory in our day-to-day lives, which, in turn, better inform and constrain subsequent attempts to identify structures and networks behind various memory processes (e.g., Baldassano et al., 2017, 2018). However, the rich complexity and fluidity of naturalistic experiences (and the numerous idiosyncratic ways they may be later described) make them far more difficult to quantitatively measure and analyze than simple stimuli and responses. Heusser et al. (2018a) recently developed a model that depicts the moment-by-moment content of a real-world experience as a geometric trajectory through its self-defined representational space. Verbal memories of that experience may then be similarly cast as “thought trajectories” traversing the experience’s geometric space. By examining the similarity between moments of content and subsequent recountings along their trajectories’ various axes, this framework disentangles the quality of an episodic memory from limiting “proportion recalled” measures.

Predictions from Heusser et al.’s model regarding the geometric structure of narrative experiences and their transformations during encoding have been successfully leveraged to investigate and identify networks of brain regions that participate in processing this structure (e.g., bilateral frontal cortex, cingulate cortex) transformation (e.g., vmPFC, ACC, rMTL). My thesis will investigate how the geometric structure of episodic memories is modulated by factors including the passage of time, contextual congruence of existing memories, and accuracy in predicting future experiences. Additionally, I hope to link my findings with established anatomical and physiological studies to inform and constrain future ROIs and hypotheses in investigations into their neurobiological bases.

2 Methods

2.1 Experimental design and data collection

Participants ($n = 60$) were divided into two equal groups. Both groups attended two study sessions, spaced six to eight days apart. In the first session, all participants viewed the (24-minute) pilot episode of *Atlanta*, and were then given up to one hour (thought all used significantly less time) to recount the episode’s events in as much detail as possible, followed by five minutes to predict how the next episode will unfold the following week. In the second session, both groups began by recounting the prior week’s episode. Then, group 1 viewed and recounts the (22-minute) second episode of *Atlanta*, while group 2 viewed and recounts the (21-minute) pilot episode of *Arrested Development*. All participant audio was recorded using the viewing computer’s built-in microphone and automatically transcribed using Google Cloud Speech-to-Text.

2.2 Stimulus Annotation

To generate the content corpus for each stimulus video, I used ANVIL (Kipp, 2001), an audiovisual annotation tool, along with a custom XML specification file to record the following features for each shot:

- *Narrative Details – External Events* (A few sentences describing physical occurrences and characters’ actions)
- *Narrative Details – Internal State* (A few sentences describing characters’ current emotional states and subtextual implications)
- A list of characters appearing on-screen
- The presence or absence of music
- A transcription of all dialogue
- The name of the character speaking
- Whether the shot took place indoors or outdoors
- The setting of the shot

2.3 Dynamic content modeling

Following Heusser et al. (2018a), I then concatenated all featural annotations within each shot, and created **overlapping sliding windows of 50 shots** upon which I trained a topic model (Blei et al., 2003) using **Hypertools** (Heusser et al., 2018b) to create the representational space for the events of the episode. I used this model to transform both the video sliding windows and **10-sentence sliding windows** of each participant’s recall and prediction transcripts into the topic space defined by the video features. I then used linear interpolation (**cite Scipy?**) to resample the video model to a one-second resolution and dynamic time warping (Berndt and Clifford, 1994) to standardize the shape across-subjects of the recall and prediction models.

2.4 Event segmentation and mapping

I then divided the continuous video, recall, and prediction models into discrete “events.” Using Hidden Markov models (Rabiner, 1989), I parsed the trajectories’ timeseries into K (non-repeating) states, such that the topics represented at each moment were maximally similar within an event, while maximally dissimilar across events (optimal K was computed separately for each model). To map between viewed and remembered events, I computed the average topic vector for each recalled event and assigned it to video event whose average topic vector was maximally similar.

3 Analyses to be employed and expected results

3.1 Comparing immediate and delayed recall

To assess how the one-week delay period affects the geometric structure of remembered content, I plan to examine differences in both the across-subjects average recall trajectory and individual participants' recall trajectories for session 1's episode between the immediate recall period and the recall period at the beginning of session 2.

References

- Atkinson, R. C. and Shiffrin, R. M. (1968). Human memory: A proposed system and its control processes. In Spence, K. W. and Spence, J. T., editors, *The psychology of learning and motivation*, volume 2, pages 89–105. Academic Press, New York.
- Baldassano, C., Chen, J., Zadbood, A., Pillow, J. W., Hasson, U., and Norman, K. A. (2017). Discovering event structure in continuous narrative perception and memory. *Neuron*, 95(3):709–721.
- Baldassano, C., Hasson, U., and Norman, K. A. (2018). Representation of real-world event schemas during narrative perception. *Journal of Neuroscience*, 38(45):9689–9699.
- Berndt, D. J. and Clifford, J. (1994). Using dynamic time warping to find patterns in time series. In *KDD workshop*, volume 10, pages 359–370.
- Blei, D. M., Ng, A. Y., and Jordan, M. I. (2003). Latent dirichlet allocation. *Journal of Machine Learning Research*, 3:993 – 1022.
- Heusser, A. C., Fitzpatrick, P. C., and Manning, J. R. (2018a). How is experience transformed into memory? *bioRxiv*, 409987.
- Heusser, A. C., Ziman, K., Owen, L. L. W., and Manning, J. R. (2018b). HyperTools: a Python toolbox for gaining geometric insights into high-dimensional data. *Journal of Machine Learning Research*, 18(152):1–6.
- Howard, M. W. and Kahana, M. J. (2002a). A distributed representation of temporal context. *Journal of Mathematical Psychology*, 46:269–299.
- Howard, M. W. and Kahana, M. J. (2002b). When does semantic similarity help episodic retrieval? *Journal of Memory and Language*, 46:85–98.
- Huk, A., Bonnen, K., and He, B. J. (2018). Beyond trial-based paradigms: continuous behavior, ongoing neural activity, and naturalistic stimuli. *Journal of Neuroscience*, 10.1523/JNEUROSCI.1920-17.2018.
- Kahana, M. J. (1996). Associative retrieval processes in free recall. *Memory & Cognition*, 24:103–109.
- Kipp, M. (2001). Anvil-a generic annotation tool for multimodal dialogue. In *Seventh European Conference on Speech Communication and Technology*.
- Koriat, A. and Goldsmith, M. (1994). Memory in naturalistic and laboratory contexts: distinguishing accuracy-oriented and quantity-oriented approaches to memory assessment. *Journal of Experimental Psychology: General*, 123(3):297–315.
- Manning, J. R., Polyn, S. M., Baltuch, G., Litt, B., and Kahana, M. J. (2011). Oscillatory patterns in temporal lobe reveal context reinstatement during memory search. *Proceedings of the National Academy of Sciences, USA*, 108(31):12893–12897.
- Murdock, B. B. (1962). The serial position effect of free recall. *Journal of Experimental Psychology*, 64:482–488.

- Murdock, B. B. and Okada, R. (1970). Interresponse times in single- trial free recall. *Journal of Verbal Learning and Verbal Behavior*, 86:263–267.
- Polyn, S. M., Natu, V. S., Cohen, J. D., and Norman, K. A. (2005). Category-specific cortical activity precedes retrieval during memory search. *Science*, 310:1963–1966.
- Rabiner, L. (1989). A tutorial on Hidden Markov Models and selected applications in speech recognition. *Proceedings of the IEEE*, 77(2):257–286.
- Sederberg, P. B., Howard, M. W., and Kahana, M. J. (2008). A context-based theory of recency and contiguity in free recall. *Psychological Review*, 115(4):893–912.