

1 **High-level cognition during story listening is reflected in
2 high-order dynamic correlations in neural activity patterns**

3 Lucy L. W. Owen¹, Thomas H. Chang^{1,2}, and Jeremy R. Manning^{1,†}

¹Department of Psychological and Brain Sciences,
Dartmouth College, Hanover, NH

²Amazon.com, Seattle, WA

†Address correspondence to jeremy.r.manning@dartmouth.edu

4 November 13, 2020

5 **Abstract**

6 Our thoughts arise from coordinated patterns of interactions between brain structures that change
7 with our ongoing experiences. High-order dynamic correlations in neural activity patterns reflect different
8 subgraphs of the brain's functional connectome that display homologous lower-level dynamic correlations.
9 We tested the hypothesis that high-level cognition is reflected in high-order dynamic correlations in brain
10 activity patterns. We developed an approach to estimating high-order dynamic correlations in timeseries
11 data, and we applied the approach to neuroimaging data collected as human participants either listened to
12 a ten-minute story or listened to a temporally scrambled version of the story. We trained across-participant
13 pattern classifiers to decode (in held-out data) when in the session each neural activity snapshot was
14 collected. We found that classifiers trained to decode from high-order dynamic correlations yielded the best
15 performance on data collected as participants listened to the (unscrambled) story. By contrast, classifiers
16 trained to decode data from scrambled versions of the story yielded the best performance when they
17 were trained using first-order dynamic correlations or non-correlational activity patterns. We suggest that
18 as our thoughts become more complex, they are reflected in higher-order patterns of dynamic network
19 interactions throughout the brain.

20 **Introduction**

21 A central goal in cognitive neuroscience is to elucidate the *neural code*: the mapping between (a) mental
22 states or cognitive representations and (b) neural activity patterns. One means of testing models of the
23 neural code is to ask how accurately that model is able to "translate" neural activity patterns into known
24 (or hypothesized) mental states or cognitive representations (e.g., Haxby et al., 2001; Huth et al., 2016, 2012;
25 Kamitani & Tong, 2005; Mitchell et al., 2008; Nishimoto et al., 2011; Norman et al., 2006; Pereira et al.,
26 2018; Tong & Pratte, 2012). Training decoding models on different types of neural features (Fig. 1a) can
27 also help to elucidate which specific aspects of neural activity patterns are informative about cognition—
28 and, by extension, which types of neural activity patterns might compose the neural code. For example,
29 prior work has used region of interest analyses to estimate the anatomical locations of specific neural
30 representations (e.g., Etzel et al., 2009), or to compare the relative contributions to the neural code of




Figure 1: Neural patterns. a. A space of neural features. Within-brain analyses are carried out within a single brain, whereas across-brain analyses compare neural patterns across two or more individuals' brains. Univariate analyses characterize the activities of individual units (e.g., nodes, small networks, hierarchies of networks, etc.), whereas multivariate analyses characterize the patterns of activities across units. Order 0 patterns involve individual nodes; order 1 patterns involve node-node interactions; order 2 (and higher) patterns relate to interactions between homologous networks. Each of these patterns may be static (e.g., averaging over time) or dynamic. **b. Summarizing neural patterns.** To efficiently compute with complex neural patterns, it can be useful to characterize the patterns using summary measures. Dimensionality reduction algorithms project the patterns onto lower-dimensional spaces whose dimensions reflect weighted combinations or non-linear transformations of the dimensions in the original space. Graph measures characterize each unit's participation in its associated network.

multivariate activity patterns versus dynamic correlations between neural activity patterns (e.g., Fong et al., 2019; Manning et al., 2018). An emerging theme in this literature is that cognition is mediated by dynamic interactions between brain structures (Bassett et al., 2006; Demertzi et al., 2019; Friston, 2000; Grossberg, 1988; Lurie et al., 2018; Mack et al., 2017; Preti et al., 2017; Solomon et al., 2019; Sporns & Honey, 2006; Turk-Browne, 2013; Zou et al., 2019).

Studies of the neural code to date have primarily focused on univariate or multivariate neural patterns (for review see Norman et al., 2006), or (more recently) on patterns of dynamic first-order correlations (i.e., interactions between pairs of brain structures; Demertzi et al., 2019; Fong et al., 2019; Lurie et al., 2018; Manning et al., 2018; Preti et al., 2017; Zou et al., 2019). What might the future of this line of work hold? For example, is the neural code implemented through higher-order interactions between brain struc-

41 tures (e.g., see Reimann et al., 2017)? Second-order correlations reflect *homologous* patterns of correlation.
42 In other words, if the dynamic patterns of correlations between two regions, *A* and *B*, are similar to those
43 between two other regions, *C* and *D*, this would be reflected in the second-order correlations between (*A*–*B*)
44 and (*C*–*D*). In this way, second-order correlations identify similarities and differences between subgraphs
45 of the brain’s connectome. Analogously, third-order correlations reflect homologies between second-order
46 correlations—i.e., homologous patterns of homologous interactions between brain regions. More generally,
47 higher-order correlations reflect homologies between patterns of lower-order correlations. We can then ask:
48 which “orders” of interaction are most reflective of high-level cognitive processes?

49 One reason one might expect to see homologous networks in a dataset is related to the notion that
50 network dynamics reflect ongoing neural computations or cognitive processing (e.g., Beaty et al., 2016). If
51 the nodes in two brain networks are interacting (within each network) in similar ways then, according to
52 our characterization of network dynamics, we refer to the similarities between those patterns of interaction
53 as higher-order correlations. When higher-order correlations are themselves changing over time, we can
54 also attempt to capture and characterize those high-order dynamics.

55 Another central question pertains to the extent to which the neural code is carried by activity patterns
56 that directly reflect ongoing cognition (e.g., following Haxby et al., 2001; Norman et al., 2006), versus the
57 dynamic properties of the network structure itself, independent of specific activity patterns in any given
58 set of regions (e.g., following Bassett et al., 2006). For example, graph measures such as centrality and
59 degree (Bullmore & Sporns, 2009) may be used to estimate how a given brain structure is “communicating”
60 with other structures, independently of the specific neural representations carried by those structures.
61 If one considers a brain region’s position in the network (e.g., its eigenvector centrality) as a dynamic
62 property, one can compare how the positions of different regions are correlated, and/or how those patterns
63 of correlations change over time. We can also compute higher-order patterns in these correlations to
64 characterize homologous subgraphs in the connectome that display similar changes in their constituent
65 brain structures’ interactions with the rest of the brain.

66 To gain insights into the above aspects of the neural code, we developed a computational framework
67 for estimating dynamic high-order correlations in timeseries data. This framework provides an important
68 advance, in that it enables us to examine patterns of higher-order correlations that are computationally
69 intractable to estimate via conventional methods. Given a multivariate timeseries, our framework provides
70 timepoint-by-timepoint estimates of the first-order correlations, second-order correlations, and so on. Our
71 approach combines a kernel-based method for computing dynamic correlations in timeseries data with a di-
72 mensionality reduction step (Fig. 1b) that projects the resulting dynamic correlations into a low-dimensional
73 space. We explored two dimensionality reduction approaches: principle components analysis (PCA; Pear-

74 son, 1901), which preserves an approximately invertible transformation back to the original data (e.g., this
75 follows related approaches taken by Gonzalez-Castillo et al., 2019; McIntosh & Jirsa, 2019; Toker & Som-
76 mer, 2019); and a second non-invertible algorithm that explored patterns in eigenvector centrality (Landau,
77 1895). This latter approach characterizes correlations between each feature dimension's relative *position* in
78 the network in favor of the specific activity histories of different features (also see Betzel et al., 2019; Reimann
79 et al., 2017; Sizemore et al., 2018).

80 We validated our approach using synthetic data where the underlying correlations were known. We
81 then applied our framework to a neuroimaging dataset collected as participants listened to either an audio
82 recording of a ten-minute story, listened to a temporally scrambled version of the story, or underwent a
83 resting state scan (Simony et al., 2016). Temporal scrambling has been used in a growing number of studies,
84 largely by Uri Hasson's group, to identify brain regions that are sensitive to higher-order and longer-
85 timescale information (e.g., cross-sensory integration, rich narrative meaning, complex situations, etc.)
86 versus regions that are primarily sensitive to low-order (e.g., sensory) information. For example, Hasson et
87 al. (2008) argues that when brain areas are sensitive to fine versus coarse temporal scrambling, this indicates
88 that they are "higher order" in the sense that they process contextual information pertaining to further-
89 away timescales. By contrast, low-level regions, such as primary sensory cortices, do not meaningfully
90 change their responses (after correcting for presentation order) even when the stimulus is scrambled at fine
91 timescales.

92 We used a subset of the story listening and rest data to train across-participant classifiers to decode
93 listening times (of groups of participants) using a blend of neural features (comprising neural activity
94 patterns, as well as different orders of dynamic correlations between those patterns that were inferred
95 using our computational framework). We found that both the PCA-based and eigenvector centrality-based
96 approaches yielded neural patterns that could be used to decode accurately (i.e., well above chance). Both
97 approaches also yielded the best decoding accuracy for data collected during (intact) story listening when
98 high-order (PCA: second-order; eigenvector centrality: fourth-order) dynamic correlation patterns were
99 included as features. When we trained classifiers on the scrambled stories or resting state data, only
100 (relatively) lower-order dynamic patterns were informative to the decoders. Taken together, our results
101 indicate that high-level cognition is supported by high-order dynamic patterns of communication between
102 brain structures.

103 **Results**

104 We sought to understand whether high-level cognition is reflected in dynamic patterns of high-order
105 correlations. To that end, we developed a computational framework for estimating the dynamics of stimulus-
106 driven high-order correlations in multivariate timeseries data (see *Dynamic inter-subject functional connectivity*
107 (*DISFC*) and *Dynamic higher-order correlations*). We evaluated the efficacy of this framework at recovering
108 known patterns in several synthetic datasets (see *Synthetic data: simulating dynamic first-order correlations* and
109 *Synthetic data: simulating dynamic higher-order correlations*). We then applied the framework to a public fMRI
110 dataset collected as participants listened to an auditorily presented story, listened to a temporally scrambled
111 version of the story, or underwent a resting state scan (see *Functional neuroimaging data collected during story*
112 *listening*). We used the relative decoding accuracies of classifiers trained on different sets of neural features
113 to estimate which types of features reflected ongoing cognitive processing.

114 **Recovering known dynamic correlations from synthetic data**

115 **Recovering dynamic first-order correlations**

116 We generated synthetic datasets that differed in how the underlying first-order correlations changed over
117 time. For each dataset, we applied Equation 4 with a variety of kernel shapes and widths. We assessed how
118 well the true underlying correlations at each timepoint matched the recovered correlations (Fig. 2). For every
119 kernel and dataset we tested, our approach recovered the correlation dynamics we embedded into the data.
120 However, the quality of these recoveries varied across different synthetic datasets in a kernel-dependent
121 way.

122 In general, wide monotonic kernel shapes (Laplace, Gaussian), and wider kernels (within a shape),
123 performed best when the correlations varied gradually from moment-to-moment (Figs. 2a, c, and d). In the
124 extreme, as the rate of change in correlations approaches 0 (Fig. 2a), an infinitely wide kernel would exactly
125 recover the Pearson's correlation (e.g., compare Eqns. 1 and 4).

126 When the correlation dynamics were unstructured in time (Fig. 2b), a Dirac δ kernel (infinitely narrow)
127 performed best. This is because, when every timepoint's correlations are independent of the correlations at
128 every other timepoint, averaging data over time dilutes the available signal. Following a similar pattern,
129 holding kernel shape fixed, narrower kernel parameters better recovered randomly varying correlations.




Figure 2: Recovering known dynamic first-order correlations from synthetic data. Each panel displays the average correlations between the vectorized upper triangles of the recovered correlation matrix at each timepoint and either the true underlying correlation at each timepoint or a reference correlation matrix. (The averages are taken across 10 different randomly generated synthetic datasets of the given category.) Error ribbons denote 95% confidence intervals (taken across datasets). Different colors denote different kernel shapes, and the shading within each color family denotes the kernel width parameter. For a complete description of each synthetic dataset, see *Synthetic data: simulating dynamic first-order correlations*.
a. Constant correlations. These datasets have a stable (unchanging) underlying correlation matrix. **b. Random correlations.** These datasets are generated using a new independently drawn correlation matrix at each new timepoint. **c. Ramping correlations.** These datasets are generated by smoothly varying the underlying correlations between the randomly drawn correlation matrices at the first and last timepoints. The left panel displays the correlations between the recovered dynamic correlations and the underlying ground truth correlations. The middle panel compares the recovered correlations with the *first* timepoint’s correlation matrix. The right panel compares the recovered correlations with the *last* timepoint’s correlation matrix. **d. Event-based correlations.** These datasets are each generated using five randomly drawn correlation matrices that each remain stable for a fifth of the total timecourse. The left panel displays the correlations between the recovered dynamic correlations and the underlying ground truth correlations. The right panels compare the recovered correlations with the correlation matrices unique to each event. The vertical lines denote event boundaries.




Figure 3: Recovery of simulated first-order and second-order dynamic correlations. Each panel displays the average correlations between the vectorized upper triangles of the recovered correlation matrix and the simulated correlation matrix at each timepoint and for each synthetic dataset. (The averages are taken across 10 different randomly generated synthetic datasets of the given category.) Error ribbons denote 95% confidence intervals (taken across datasets). For a complete description of each synthetic dataset, see *Synthetic data: simulating dynamic higher-order correlations*. All results in this figure used a Laplace kernel (width = 20). **a. Constant correlations.** These first and second order dynamic correlation were simulated from datasets have a stable (unchanging) underlying correlation matrix. **b. Random correlations.** These first and second order dynamic correlation were simulated from datasets are generated using a new independently drawn correlation matrix at each new timepoint. **c. Ramping correlations.** These first and second order dynamic correlation were simulated from datasets are generated by smoothly varying the underlying correlations between the randomly drawn correlation matrices at the first and last timepoints and displays the correlations between the recovered dynamic correlations and the simulated correlation first and second order correlation matrices. **d. Event-based correlations.** These first and second order dynamic correlation were simulated from datasets are each generated using five randomly drawn correlation matrices that each remain stable for a fifth of the total timecourse. The vertical lines denote event boundaries.

130 Recovering dynamic higher-order correlations

131 Following our approach to evaluating our ability to recover known dynamic first-order correlations from
 132 synthetic data, we generated an analogous second set of synthetic datasets that we designed to exhibit
 133 known dynamic first-order *and* second-order correlations (see *Synthetic data: simulating dynamic higher-*
 134 *order correlations*). We generated a total of 40 datasets that varied in how the first-order and second-order
 135 correlations changed over time. We then repeatedly applied Equation 4 using the overall best-performing
 136 kernel from our first-order tests (a Laplace kernel with a width of 20; Fig. 2) to assess how closely the
 137 recovered dynamic correlations matched the dynamic correlations we had embedded into the datasets.

138 Overall, we found that we could reliably recover both first-order and second-order correlations from
 139 the synthetic data (Fig. 3). When the correlations were stable for longer intervals, or changed gradually
 140 (constant, ramping, and event datasets), recovery performance was relatively high, and we were better able
 141 to recover dynamic first-order correlations than second-order correlations. We expected that this would
 142 happen, given that errors in our estimation procedure at lower orders necessarily propagate to higher orders
 143 (since lower-order correlations are used to estimate higher-order correlations). Interestingly, we also found
 144 that when the correlations were particularly *unstable* (random datasets), we better recovered second-order
 145 correlations.

146 Taken together, our explorations using synthetic data indicated that we are able to partially, but not
147 perfectly, recover ground truth dynamic first-order and second-order correlations. This suggests that our
148 modeling approach provides a meaningful (if noisy) estimate of high-order correlations. We next turned
149 to analyses of human fMRI data to examine whether the recovered dynamics might reflect the dynamics of
150 human cognition during a naturalistic story-listening task.

151 **Cognitively relevant dynamic high-order correlations in fMRI data**

152 We used across-participant temporal decoders to identify cognitively relevant neural patterns in fMRI data
153 (see *Forward inference and decoding accuracy*). The dataset we examined (collected by Simony et al., 2016)
154 comprised four experimental conditions that exposed participants to stimuli that varied systematically in
155 how cognitively engaging they were. The *intact* experimental condition had participants listen to an audio
156 recording of a 10-minute story. The *paragraph*-scrambled experimental condition had participants listen to a
157 temporally scrambled version of the story, where the paragraphs occurred out of order (but where the same
158 total set of paragraphs were presented over the full listening interval). All participants in this condition
159 experienced the scrambled paragraphs in the same order. The *word*-scrambled experimental condition had
160 participants listen to a temporally scrambled version of the story where the words in the story occurred in a
161 random order. All participants in the word condition experienced the scrambled words in the same order.
162 Finally, in a *rest* experimental condition, participants lay in the scanner with no overt stimulus, with their
163 eyes open (blinking as needed). This dataset provided a convenient means of testing our hypothesis that
164 different levels of cognitive processing and engagement are reflected in different orders of brain activity
165 dynamics.

166 In brief, we computed timeseries of dynamic high-order correlations that were similar across participants
167 in each of two randomly assigned groups: a training group and a test group. We then trained classifiers
168 on the training group's data to match each sample from the test group with a stimulus timepoint. Each
169 classifier comprised a weighted blend of neural patterns that reflected up to n^{th} -order dynamic correlations
170 (see *Feature weighting and testing*, Fig. 10). We repeated this process for $n \in \{0, 1, 2, \dots, 10\}$. Our examinations
171 of synthetic data suggested that none of the kernels we examined were “universal” in the sense of optimally
172 recovering underlying correlations regardless of the temporal structure of those correlations. We found a
173 similar pattern in the (real) fMRI data, whereby different kernels yielded different decoding accuracies, but
174 no single kernel emerged as the clear “best.” In our analyses of neural data, we therefore averaged our
175 decoding results over a variety of kernel shapes and widths in order to identify results that were robust to
176 specific kernel parameters (see *Identifying robust decoding results*).




Figure 4: Across-participant timepoint decoding accuracy varies with correlation order and cognitive engagement. **a. Decoding accuracy as a function of order: PCA.** Order (*x*-axis) refers to the maximum order of dynamic correlations that were available to the classifiers (see *Feature weighting and testing*). The reported across-participant decoding accuracies are averaged over all kernel shapes and widths (see *Identifying robust decoding results*). The *y*-values are displayed relative to chance accuracy (intact: $\frac{1}{300}$; paragraph: $\frac{1}{272}$; word: $\frac{1}{300}$; rest: $\frac{1}{400}$). The error ribbons denote 95% confidence intervals across cross-validation folds (i.e., random assignments of participants to the training and test sets). The colors denote the experimental condition. Arrows denote sets of features that yielded reliably higher (upwards facing) or lower (downward facing) decoding accuracy than the mean of all other features (via a two-tailed test, thresholded at $p < 0.05$). Figure 5 displays additional comparisons between the decoding accuracies achieved using different sets of neural features. The circled values represent the maximum decoding accuracy within each experimental condition. **b. Normalized timepoint decoding accuracy as a function of order: PCA.** This panel displays the same results as Panel a, but here each curve has been normalized to have a maximum value of 1 and a minimum value of 0 (including the upper and lower bounds of the respective 95% confidence intervals). Panels a and b used PCA to project each high-dimensional pattern of dynamic correlations onto a lower-dimensional space. **c. Timepoint decoding accuracy as a function of order: eigenvector centrality.** This panel is in the same format as Panel a, but here eigenvector centrality has been used to project the high-dimensional patterns of dynamic correlations onto a lower-dimensional space. **d. Normalized timepoint decoding accuracy as a function of order: eigenvector centrality.** This panel is in the same format as Panel b, but here eigenvector centrality has been used to project the high-dimensional patterns of dynamic correlations onto a lower-dimensional space.




Figure 5: Statistical summary of decoding accuracies for different neural features. Each column of matrices displays decoding results for one experimental condition (intact, paragraph, word, and rest). We considered dynamic activity patterns (order 0) and dynamic correlations at different orders (order > 0). We used two-tailed t -tests to compare the distributions of decoding accuracies obtained using each pair of features. The distributions for each feature reflect the set of average decoding accuracies (across all kernel parameters), obtained for each random assignment of training and test groups. In the upper triangles of each matrix, warmer colors (positive t -values) indicate that the neural feature indicated in the given row yielded higher accuracy than the feature indicated in the given column. Cooler colors (negative t -values) indicate that the feature in the given row yielded lower decoding accuracy than the feature in the given column. The lower triangles of each map denote the corresponding p -values for the t -tests. The diagonal entries display the relative average optimized weight given to each type of feature, in a decoder that included all feature types (see *Feature weighting and testing*).

Our approach to estimating dynamic high-order correlations entails mapping the high-dimensional feature space of correlations (represented by a T by $O(K^2)$ matrix) onto a lower-dimensional feature space (represented by a T by K matrix). We carried out two sets of analyses that differed in how this mapping was computed. The first set of analyses used PCA to find a low-dimensional embedding of the original dynamic correlation matrices (Fig. 4a,b). The second set of analyses characterized correlations in dynamics of each feature's eigenvector centrality, but did not preserve the underlying activity dynamics (Fig. 4c,d).

Both sets of temporal decoding analyses yielded qualitatively similar results for the auditory (non-rest) conditions of the experiment (Fig. 4: pink, green, and teal lines; Fig. 5: three leftmost columns). The highest decoding accuracy for participants who listened to the intact (unscrambled) story was achieved using high-order dynamic correlations (PCA: second-order; eigenvector-centrality: fourth-order). Scrambled versions of the story were best decoded by lower-order correlations (PCA/paragraph: first-order; PCA/word: order zero; eigenvector centrality/paragraph: order zero; eigenvector centrality/word: order zero). The two sets

189 of analyses yielded different decoding results on resting state data (Fig. 4: purple lines; Fig. 5: rightmost
190 column). We note that while the resting state times could be decoded reliably, the accuracies were only very
191 slightly above chance. We speculate that the decoders might have picked up on attentional drift, boredom,
192 or tiredness; we hypothesize that these all increased throughout the resting state scan. The decoders might
193 be picking up on aspects of these loosely defined cognitive states that are common across individuals. The
194 PCA-based approach achieved the highest resting state decoding accuracy using order zero features (non-
195 correlational, activation-based), whereas the eigenvector centrality-based approach achieved the highest
196 resting state decoding accuracy using second-order correlations. Taken together, these analyses indicate
197 that high-level cognitive processing (while listening to the intact story) is reflected in the dynamics of high-
198 order correlations in brain activity, whereas lower-level cognitive processing (while listening to scrambled
199 versions of the story that lack rich meaning) is reflected in the dynamics of lower-order correlations and
200 non-correlational activity dynamics. Further, these patterns are associated both with the underlying activity
201 patterns (characterized using PCA) and also with the changing relative positions that different brain areas
202 occupy in their associated networks (characterized using eigenvector centrality).

203 Having established that patterns of high-order correlations are informative to decoders, we next won-
204 dered which specific networks of brain regions contributed most to these patterns. As a representative
205 example, we selected the kernel parameters that yielded decoding accuracies that best matched the average
206 accuracies across all of the kernel parameters we examined. Using Figure 4c as a template, the best-matching
207 kernel was a Laplace kernel with a width of 50 (Fig. 9d). We used this kernel to compute a single K by K
208 n^{th} -order DISFC matrix for each experimental condition. We then used Neurosynth (Rubin et al., 2017) to
209 compute the terms most highly associated with the most strongly correlated pairs of regions in each of these
210 matrices (Fig. 6; see *Reverse inference*).

211 For all of the story listening conditions (intact, paragraph, and word), we found that first- and second-
212 order correlations were most strongly associated with auditory and speech processing areas. During
213 intact story listening, third-order correlations reflected integration with visual areas, and fourth-order
214 correlations reflected integration with areas associated with high-level cognition and cognitive control,
215 such as the ventrolateral prefrontal cortex. However, during listening to temporally scrambled stories,
216 these higher-order correlations instead involved interactions with additional regions associated with speech
217 and semantic processing. By contrast, we found a much different set of patterns in the resting state data.
218 First-order resting state correlations were most strongly associated with regions involved in counting and
219 numerical understanding. Second-order resting state correlations were strongest in visual areas; third-order
220 correlations were strongest in task-positive areas; and fourth-order correlations were strongest in regions
221 associated with autobiographical and episodic memory. We carried out analogous analyses to create maps




Figure 6: Top terms associated with the endpoints of the strongest correlations. Each color corresponds to one order of inter-subject functional correlations. To calculate the dynamic correlations, eigenvector centrality has been used to project the high-dimensional patterns of dynamic correlations onto a lower-dimensional space at each previous order, which allows us to map the brain regions at each order by retaining the features of the original space. The inflated brain plots display the locations of the endpoints of the 10 strongest (absolute value) correlations at each order, thresholded at 0.999, and projected onto the cortical surface (Combrisson et al., 2019). The lists of terms on the right display the top five Neurosynth terms (Rubin et al., 2017) decoded from the corresponding brain maps for each order. Each row displays data from a different experimental condition. Additional maps and their corresponding Neurosynth terms may be found in the *Supplementary materials* (intact: Fig. S1; paragraph: Fig. S2; word: Fig. S3; rest: Fig. S4).




Figure 7: Proposed high-order network dynamics underlying high-level cognition during story listening. Schematic depicts higher orders of network interactions supporting higher-level aspects of cognitive processing. When tasks evoke richer, deeper, and/or higher-level processing, this is reflected in higher-order network interactions.

(and decode the top associated Neurosynth terms) for up to fifteenth-order correlations (Figs. S1, S2, S3, and S4). Of note, examining fifteenth-order correlations between 700 nodes using conventional methods would have required storing roughly $\frac{700^{2 \times 15}}{2} \approx 1.13 \times 10^{85}$ floating point numbers—assuming single-precision (32 bits each), this would require roughly 32 times as many bits as there are molecules in the known universe! Although these fifteenth-order correlations do appear (visually) to have some well-formed structure, we provide this latter example primarily as a demonstration of the efficiency and scalability of our approach.

Discussion

We tested the hypothesis that high-level cognition is reflected in high-order brain network dynamics (e.g., see Reimann et al., 2017; Solomon et al., 2019). We examined high-order network dynamics in functional neuroimaging data collected during a story listening experiment. When participants listened to an auditory recording of the story, participants exhibited similar high-order brain network dynamics. By contrast, when participants instead listened to temporally scrambled recordings of the story, only lower-order brain network dynamics were similar across participants. Our results indicate that higher orders of network interactions support higher-level aspects of cognitive processing (Fig. 7).

The notion that cognition is reflected in (and possibly mediated by) patterns of first-order network dynamics has been suggested by or proposed in myriad empirical studies and reviews (e.g., Chang & Glover, 2010; Demertzi et al., 2019; Fong et al., 2019; Gonzalez-Castillo et al., 2019; Liégeois et al., 2019; Lurie et al., 2018; Manning et al., 2018; Park et al., 2018; Preti et al., 2017; Roy et al., 2019; Turk-Browne, 2013; Zou et al., 2019). Our study extends this line of work by finding cognitively relevant *higher-order* network dynamics that reflect ongoing cognition. Our findings complement other work that uses graph theory and

242 topology to characterize how brain networks reconfigure during cognition (e.g., Bassett et al., 2006; Betzel
243 et al., 2019; McIntosh & Jirsa, 2019; Reimann et al., 2017; Sizemore et al., 2018; Toker & Sommer, 2019; Zheng
244 et al., 2019).

245 An open question not addressed by our study pertains to how different structures integrate incoming
246 information with different time constants. For example, one line of work suggests that the cortical surface
247 comprises a structured map such that nearby brain structures process incoming information at similar
248 timescales. Low-level sensory areas integrate information relatively quickly, whereas higher-level regions
249 integrate information relatively slowly (Baldassano et al., 2017; Chien & Honey, 2019; Hasson et al., 2015,
250 2008; Honey et al., 2012; Lerner et al., 2014, 2011). A similar hierarchy appears to play a role in predicting
251 future events (C. S. Lee et al., 2020). Other related work in human and mouse brains indicates that the
252 temporal response profile of a given brain structure may relate to how strongly connected that structure
253 is with other brain areas (Fallon et al., 2019). Further study is needed to understand the role of temporal
254 integration at different scales of network interaction, and across different anatomical structures. Import-
255 antly, our analyses do not speak to the physiological basis of higher-order dynamics, and could reflect
256 nonlinearities, chaotic patterns, non-stationarities, or multistability, etc. However, our decoding analyses
257 do indicate that higher-order dynamics are consistent across individuals, and therefore unlikely to be driven
258 by non-stimulus-driven dynamics which are unlikely to be similar across individuals.

259 Another potential limitation of our approach relates to recent work suggesting that the brain undergoes
260 rapid state changes, for example across event boundaries (e.g., Baldassano et al., 2017). Shappell et al.
261 (2019) used hidden semi-Markov models to estimate state-specific network dynamics (also see Vidaurre et
262 al., 2018). Our general approach might be extended by considering putative state transitions. For example,
263 rather than weighting all timepoints using a similar kernel (Eqn. 4), the kernel function could adapt on a
264 timepoint-by-timepoint basis such that only timepoints determined to be in the same “state” were given
265 non-zero weight.

266 Identifying high-order network dynamics associated with high-level cognition required several impor-
267 tant methods advances. First, we used kernel-based dynamic correlations to extended the notion of (static)
268 inter-subject functional connectivity (Simony et al., 2016) to a dynamic measure of inter-subject functional
269 connectivity (DISFC) that does not rely on sliding windows (e.g., as in Manning et al., 2018), and that may
270 be computed at individual timepoints. This allowed us to precisely characterize stimulus-evoked network
271 dynamics that were similar across individuals. Second, we developed a computational framework for
272 efficiently and scalably estimating high-order dynamic correlations. Our approach uses dimensionality
273 reduction algorithms and graph measures to obtain low-dimensional embeddings of patterns of network
274 dynamics. Third, we developed an analysis framework for identifying robust decoding results by carrying

275 out our analyses using a range of parameter values and then identifying which results were robust to specific
276 parameter choices.

277 Concluding remarks

278 Methods for characterizing the dynamics of high-order correlations in neural data provide a window into the
279 neural basis of cognition. By showing that high-level cognition is reflected in high-order network dynamics,
280 we have elucidated the next step on the path towards understanding the neural basis of cognition.

281 Methods

282 Our general approach to efficiently estimating high-order dynamic correlations comprises four general
283 steps (Fig. 8). First, we derive a kernel-based approach to computing dynamic pairwise correlations in
284 a T (timepoints) by K (features) multivariate timeseries, \mathbf{X}_0 . This yields a T by $O(K^2)$ matrix of dynamic
285 correlations, \mathbf{Y}_1 , where each row comprises the upper triangle and diagonal of the correlation matrix at
286 a single timepoint, reshaped into a row vector (this reshaped vector is $(\frac{K^2-K}{2} + K)$ -dimensional). Second,
287 we apply a dimensionality reduction step to project the matrix of dynamic correlations back onto a K -
288 dimensional space. This yields a T by K matrix, \mathbf{X}_1 , that reflects an approximation of the dynamic correlations
289 reflected in the original data. Third, we use repeated applications of the kernel-based dynamic correlation
290 step to \mathbf{X}_n and the dimensionality reduction step to the resulting \mathbf{Y}_{n+1} to estimate high-order dynamic
291 correlations. Each application of these steps to a T by K time series \mathbf{X}_n yields a T by K matrix, \mathbf{X}_{n+1} , that
292 reflects the dynamic correlations between the columns of \mathbf{X}_n . In this way, we refer to n as the *order* of the
293 timeseries, where \mathbf{X}_0 (order 0) denotes the original data and \mathbf{X}_n denotes (approximated) n^{th} -order dynamic
294 correlations between the columns of \mathbf{X}_0 . Finally, we use a cross-validation-based decoding approach to
295 evaluate how well information contained in a given order (or weighted mixture of orders) may be used
296 to decode relevant cognitive states. If including a given \mathbf{X}_n in the feature set yields higher classification
297 accuracy on held-out data, we interpret this as evidence that the given cognitive states are reflected in
298 patterns of n^{th} -order correlations.

299 All of the code used to produce the figures and results in this manuscript, along with links to the
300 corresponding datasets, may be found at github.com/ContextLab/timecorr-paper. In addition, we have
301 released a Python toolbox for computing dynamic high-order correlations in timeseries data; our toolbox
302 may be found at timecorr.readthedocs.io.




Figure 8: **Estimating dynamic high-order correlations.** Given a T by K matrix of multivariate timeseries data, \mathbf{X}_n (where $n \in \mathbb{N}, n \geq 0$), we use Equation 4 to compute a timeseries of K by K correlation matrices, \mathbf{Y}_{n+1} . We then approximate \mathbf{Y}_{n+1} with the T by K matrix \mathbf{X}_{n+1} . This process may be repeated to scalably estimate iteratively higher-order correlations in the data. Note that the transposes of \mathbf{X}_n and \mathbf{X}_{n+1} are displayed in the figure for compactness.

303 Kernel-based approach for computing dynamic correlations

Given a T by K matrix of observations, \mathbf{X} , we can compute the (static) Pearson's correlation between any pair of columns, $\mathbf{X}(\cdot, i)$ and $\mathbf{X}(\cdot, j)$ using (Pearson, 1901):

$$\text{corr}(\mathbf{X}(\cdot, i), \mathbf{X}(\cdot, j)) = \frac{\sum_{t=1}^T (\mathbf{X}(t, i) - \bar{\mathbf{X}}(\cdot, i))(\mathbf{X}(t, j) - \bar{\mathbf{X}}(\cdot, j))}{\sqrt{\sum_{t=1}^T \sigma_{\mathbf{X}(\cdot, i)}^2 \sigma_{\mathbf{X}(\cdot, j)}^2}}, \text{ where} \quad (1)$$

$$\bar{\mathbf{X}}(\cdot, k) = \frac{1}{T} \sum_{t=1}^T \mathbf{X}(t, k), \text{ and} \quad (2)$$

$$\sigma_{\mathbf{X}(\cdot, k)}^2 = \frac{1}{T} \sum_{t=1}^T (\mathbf{X}(t, k) - \bar{\mathbf{X}}(\cdot, k))^2 \quad (3)$$

- 304 We can generalize this formula to compute time-varying correlations by incorporating a *kernel function* that
 305 takes a time t as input, and returns how much the observed data at each timepoint $\tau \in [-\infty, \infty]$ contributes
 306 to the estimated instantaneous correlation at time t (Fig. 9; also see Allen et al., 2012, for a similar approach).

307

Given a kernel function $\kappa_t(\cdot)$ for timepoint t , evaluated at timepoints $\tau \in [1, \dots, T]$, we can update the




Figure 9: Examples of kernel functions. Each panel displays per-timepoint weights for a kernel centered at $t = 50$, evaluated at 100 timepoints ($\tau \in [1, \dots, 100]$). **a. Uniform kernel.** The weights are timepoint-invariant; observations at all timepoints are weighted equally, and do not change as a function of τ . This is a special case kernel function that reduces dynamic correlations to static correlations. **b. Dirac δ kernel.** Only the observation at timepoint t is given a non-zero weight (of 1). **c. Gaussian kernels.** Each kernel's weights fall off in time according to a Gaussian probability density function centered on time t . Weights derived using several different example width parameters (σ^2) are displayed. **d. Laplace kernels.** Each kernel's weights fall off in time according to a Laplace probability density function centered on time t . Weights derived using several different example width parameters (b) are displayed. **e. Mexican hat (Ricker wavelet) kernels.** Each kernel's weights fall off in time according to a Ricker wavelet centered on time t . This function highlights the *contrasts* between local versus surrounding activity patterns in estimating dynamic correlations. Weights derived using several different example width parameters (σ) are displayed.

static correlation formula in Equation 1 to estimate the *instantaneous correlation* at timepoint t :

$$\text{timecorr}_{\kappa_t}(\mathbf{X}(\cdot, i), \mathbf{X}(\cdot, j)) = \frac{\sum_{\tau=1}^T (\mathbf{X}(\tau, i) - \tilde{\mathbf{X}}_{\kappa_t}(\cdot, i))(\mathbf{X}(\tau, j) - \tilde{\mathbf{X}}_{\kappa_t}(\cdot, j))}{\sqrt{\sum_{\tau=1}^T \tilde{\sigma}_{\kappa_t}^2(\mathbf{X}(\cdot, i))\tilde{\sigma}_{\kappa_t}^2(\mathbf{X}(\cdot, j))}}, \text{ where} \quad (4)$$

$$\tilde{\mathbf{X}}_{\kappa_t}(\cdot, k) = \sum_{\tau=1}^T \kappa_t(\tau) \mathbf{X}(\tau, k), \quad (5)$$

$$\tilde{\sigma}_{\kappa_t}^2(\mathbf{X}(\cdot, k)) = \sum_{\tau=1}^T (\mathbf{X}(\tau, k) - \tilde{\mathbf{X}}_{\kappa_t}(\cdot, k))^2. \quad (6)$$

308 Here $\text{timecorr}_{\kappa_t}(\mathbf{X}(\cdot, i), \mathbf{X}(\cdot, j))$ reflects the correlation at time t between columns i and j of \mathbf{X} , estimated using
 309 the kernel κ_t . We evaluate Equation 4 in turn for each pair of columns in \mathbf{X} and for kernels centered on each
 310 timepoint in the timeseries, respectively, to obtain a T by K by K timeseries of dynamic correlations, \mathbf{Y} . For
 311 convenience, we then reshape the upper triangles and diagonals of each timepoint's symmetric correlation
 312 matrix into a row vector to obtain an equivalent T by $\left(\frac{K^2-K}{2} + K\right)$ matrix.

313 Dynamic inter-subject functional connectivity (DISFC)

Equation 4 provides a means of taking a single observation matrix, \mathbf{X}_n and estimating the dynamic correlations from moment to moment, \mathbf{Y}_{n+1} . Suppose that one has access to a set of multiple observation matrices that reflect the same phenomenon. For example, one might collect neuroimaging data from several experimental participants, as each participant performs the same task (or sequence of tasks). Let $\mathbf{X}_n^1, \mathbf{X}_n^2, \dots, \mathbf{X}_n^P$ reflect the T by K observation matrices ($n = 0$) or reduced correlation matrices ($n > 0$) for each of P

participants in an experiment. We can use *inter-subject functional connectivity* (ISFC; Simony & Chang, 2020; Simony et al., 2016) to compute the stimulus-driven correlations reflected in the multi-participant dataset at a given timepoint t using:

$$\bar{\mathbf{C}}(t) = M \left(R \left(\frac{1}{2P} \sum_{p=1}^P Z(\mathbf{Y}_{n+1}^p(t))^\top + Z(\mathbf{Y}_{n+1}^p(t)) \right) \right), \quad (7)$$

where M extracts and vectorizes the upper triangle and diagonal of a symmetric matrix, Z is the Fisher z -transformation (Zar, 2010):

$$Z(r) = \frac{\log(1+r) - \log(1-r)}{2}, \quad (8)$$

R is the inverse of Z :

$$R(z) = \frac{\exp(2z-1)}{\exp(2z+1)}, \quad (9)$$

and $\mathbf{Y}_{n+1}^p(t)$ denotes the correlation matrix at timepoint t (Eqn. 4) between each column of \mathbf{X}_n^p and each column of the average \mathbf{X}_n from all *other* participants, $\bar{\mathbf{X}}_n^p$:

$$\bar{\mathbf{X}}_n^p = \frac{1}{P-1} \sum_{q \in \setminus p} \mathbf{X}_n^q, \quad (10)$$

314 where $\setminus p$ denotes the set of all participants other than participant p . In this way, the T by $(\frac{K^2-K}{2} + K)$ DISFC
 315 matrix $\bar{\mathbf{C}}$ provides a time-varying extension of the ISFC approach developed by Simony et al. (2016).

316 **Low-dimensional representations of dynamic correlations**

317 Given a T by $(\frac{K^2-K}{2} + K)$ matrix of n^{th} -order dynamic correlations, \mathbf{Y}_n , we propose two general approaches
 318 to computing a T by K low-dimensional representation of those correlations, \mathbf{X}_n . The first approach uses
 319 dimensionality reduction algorithms to project \mathbf{Y}_n onto a K -dimensional space. The second approach uses
 320 graph measures to characterize the relative positions of each feature ($k \in [1, \dots, K]$) in the network defined
 321 by the correlation matrix at each timepoint.

322 **Dimensionality reduction-based approaches to computing \mathbf{X}_n**

323 The modern toolkit of dimensionality reduction algorithms include Principal Components Analysis (PCA;
 324 Pearson, 1901), Probabilistic PCA (PPCA; Tipping & Bishop, 1999), Exploratory Factor Analysis (EFA;

325 Spearman, 1904), Independent Components Analysis (ICA; Comon et al., 1991; Jutten & Herault, 1991),
326 *t*-Stochastic Neighbor Embedding (*t*-SNE; van der Maaten & Hinton, 2008), Uniform Manifold Approximation
327 and Projection (UMAP; McInnes et al., 2018), non-negative matrix factorization (NMF; D. D. Lee
328 & Seung, 1999), Topographic Factor Analysis (TFA; Manning et al., 2014), Hierarchical Topographic Factor
329 analysis (HTFA; Manning et al., 2018), Topographic Latent Source Analysis (TLSA; Gershman et al.,
330 2011), dictionary learning (J. Mairal et al., 2009; J. B. Mairal et al., 2009), and deep auto-encoders (Hinton
331 & Salakhutdinov, 2006), among others. While complete characterizations of each of these algorithms is
332 beyond the scope of the present manuscript, the general intuition driving these approaches is to compute
333 the T by K matrix, \mathbf{X} , that is closest to the original T by J matrix, \mathbf{Y} , where (typically) $K \ll J$. The different
334 approaches place different constraints on what properties \mathbf{X} must satisfy and which aspects of the data are
335 compared (and how) in order to optimize how well \mathbf{X} approximates \mathbf{Y} .

336 Applying dimensionality reduction algorithms to \mathbf{Y} yields an \mathbf{X} whose columns reflect weighted combi-
337 nations (or nonlinear transformations) of the original columns of \mathbf{Y} . This has two main consequences. First,
338 with each repeated dimensionality reduction, the resulting \mathbf{X}_n has lower and lower fidelity (with respect to
339 what the “true” \mathbf{Y}_n might have looked like without using dimensionality reduction to maintain tractability).
340 In other words, computing \mathbf{X}_n is a lossy operation. Second, whereas each column of \mathbf{Y}_n may be mapped
341 directly onto specific pairs of columns of \mathbf{X}_{n-1} , the columns of \mathbf{X}_n reflect weighted combinations and/or
342 nonlinear transformations of the columns of \mathbf{Y}_n . Many dimensionality reduction algorithms are invertible
343 (or approximately invertible). However, attempting to map a given \mathbf{X}_n back onto the original feature space
344 of \mathbf{X}_0 will usually require $O(TK^{2n})$ space and therefore becomes intractable as n or K grow large.

345 **Graph measure approaches to computing \mathbf{X}_n**

346 The above dimensionality reduction approaches to approximating a given \mathbf{Y}_n with a lower-dimensional
347 \mathbf{X}_n preserve a (potentially recombined and transformed) mapping back to the original data in \mathbf{X}_0 . We also
348 explore graph measures that instead characterize each feature’s relative *position* in the broader network of
349 interactions and connections. To illustrate the distinction between the two general approaches we explore,
350 suppose a network comprises nodes A and B , along with several other nodes. If A and B exhibit uncorrelated
351 activity patterns, then by definition the functional connection (correlation) between them will be close to
352 0. However, if A and B each interact with *other* nodes in similar ways, we might attempt to capture those
353 similarities between A ’s and B ’s interactions with those other members of the network.

354 In general, graph measures take as input a matrix of interactions (e.g., using the above notation, a K
355 by K correlation matrix or binarized correlation matrix reconstituted from a single timepoint’s row of \mathbf{Y}),

and return as output a set of K measures describing how each node (feature) sits within that correlation matrix with respect to the rest of the population. Widely used measures include betweenness centrality (the proportion of shortest paths between each pair of nodes in the population that involves the given node in question; e.g., Barthélemy, 2004; Freeman, 1977; Geisberger et al., 2008; Newman, 2005; Opsahl et al., 2010); diversity and dissimilarity (characterizations of how differently connected a given node is from others in the population; e.g., Lin, 2009; Rao, 1982; Ricotta & Szeidl, 2006); eigenvector centrality and pagerank centrality (measures of how influential a given node is within the broader network; e.g., Bonacich, 2007; Halu et al., 2013; Lohmann et al., 2010; Newman, 2008); transfer entropy and flow coefficients (a measure of how much information is flowing from a given node to other nodes in the network; e.g., Honey et al., 2007; Schreiber, 2000); k -coreness centrality (a measure of the connectivity of a node within its local subgraph; e.g., Alvarez-Hamelin et al., 2005; Christakis & Fowler, 2010); within-module degree (a measure of how many connections a node has to its close neighbors in the network; e.g., Rubinov & Sporns, 2010); participation coefficient (a measure of the diversity of a node's connections to different subgraphs in the network; e.g., Rubinov & Sporns, 2010); and subgraph centrality (a measure of a node's participation in all of the network's subgraphs; e.g., Estrada & Rodríguez-Velázquez, 2005); among others.

For a given graph measure, $\eta : \mathbb{R}^{K \times K} \rightarrow \mathbb{R}^K$, we can use η to transform each row of \mathbf{Y}_n in a way that characterizes the corresponding graph properties of each column. This results in a new T by K matrix, \mathbf{X}_n , that reflects how the features reflected in the columns of \mathbf{X}_{n-1} participate in the network during each timepoint (row).

Dynamic higher-order correlations

Because \mathbf{X}_n has the same shape as the original data \mathbf{X}_0 , approximating \mathbf{Y}_n with a lower-dimensional \mathbf{X}_n enables us to estimate high-order dynamic correlations in a scalable way. Given a T by K input matrix, the output of Equation 4 requires $O(TK^2)$ space to store. Repeated applications of Equation 4 (i.e., computing dynamic correlations between the columns of the outputted dynamic correlation matrix) each require exponentially more space; in general the n^{th} -order dynamic correlations of a T by K timeseries occupies $O(TK^{2^n})$ space. However, when we approximate or summarize the output of Equation 4 with a T by K matrix (as described above), it becomes feasible to compute even very high-order correlations in high-dimensional data. Specifically, approximating the n^{th} -order dynamic correlations of a T by K timeseries requires only $O(TK^2)$ additional space— the same as would be required to compute first-order dynamic correlations. In other words, the space required to store $n + 1$ multivariate timeseries reflecting up to n^{th} order correlations in the original data scales linearly with n using our approach (Fig. 8).

387 **Data**

388 We examined two types of data: synthetic data and human functional neuroimaging data. We constructed
389 and leveraged the synthetic data to evaluate our general approach (for a related validation approach see
390 Thompson et al., 2018). Specifically, we tested how well Equation 4 could be used to recover known dynamic
391 correlations using different choices of kernel (κ ; Fig. 9), for each of several synthetic datasets that exhibited
392 different temporal properties. We also simulated higher-order correlations and tested how well Equation 4
393 could recover these correlations using the best kernel from the previous synthetic data analyses. We then
394 applied our approach to a functional neuroimaging dataset to test the hypothesis that ongoing cognitive
395 processing is reflected in high-order dynamic correlations. We used an across-participant classification test
396 to estimate whether dynamic correlations of different orders contain information about which timepoint in
397 a story participants were listening to.

398 **Synthetic data: simulating dynamic first-order correlations**

399 We constructed a total of 40 different multivariate timeseries, collectively reflecting a total of 4 qualitatively
400 different patterns of dynamic first-order correlations (i.e., 10 datasets reflecting each type of dynamic pat-
401 tern). Each timeseries comprised 50 features (dimensions) that varied over 300 timepoints. The observations
402 at each timepoint were drawn from a zero-mean multivariate Gaussian distribution with a covariance matrix
403 defined for each timepoint as described below. We drew the observations at each timepoint independently
404 from the draws at all other timepoints; in other words, for each observation $s_t \sim \mathcal{N}(\mathbf{0}, \Sigma_t)$ at timepoint t ,
405 $p(s_t) = p(s_t | s_{\setminus t})$.

Constant. We generated data with stable underlying correlations to evaluate how Equation 4 characterized correlation “dynamics” when the ground truth correlations were static. We constructed 10 multivariate timeseries whose observations were each drawn from a single (stable) Gaussian distribution. For each dataset (indexed by m), we constructed a random covariance matrix, Σ_m :

$$\Sigma_m = \mathbf{C}\mathbf{C}^\top, \text{ where} \quad (11)$$

$$\mathbf{C}(i, j) \sim \mathcal{N}(0, 1), \text{ and where} \quad (12)$$

406 $i, j \in [1, 2, \dots, 50]$. In other words, all of the observations (for each of the 300 timepoints) within each dataset
407 were drawn from a multivariate Gaussian distribution with the same covariance matrix, and the 10 datasets
408 each used a different covariance matrix.

409 **Random.** We generated a second set of 10 synthetic datasets whose observations at each timepoint were
 410 drawn from a Gaussian distribution with a new randomly constructed (using Eqn. 11) covariance matrix.
 411 Because each timepoint’s covariance matrix was drawn independently from the covariance matrices for all
 412 other timepoints, these datasets provided a test of reconstruction accuracy in the absence of any meaningful
 413 underlying temporal structure in the dynamic correlations underlying the data.

Ramping. We generated a third set of 10 synthetic datasets whose underlying correlations changed gradually over time. For each dataset, we constructed two *anchor* covariance matrices using Equation 11, Σ_{start} and Σ_{end} . For each of the 300 timepoints in each dataset, we drew the observations from a multivariate Gaussian distribution whose covariance matrix at each timepoint $t \in [0, \dots, 299]$ was given by

$$\Sigma_t = \left(1 - \frac{t}{299}\right)\Sigma_{\text{start}} + \frac{t}{299}\Sigma_{\text{end}}. \quad (13)$$

414 The gradually changing correlations underlying these datasets allow us to evaluate the recovery of dynamic
 415 correlations when each timepoint’s correlation matrix is unique (as in the random datasets), but where the
 416 correlation dynamics are structured and exhibit first-order autocorrelations (as in the constant datasets).

417 **Event.** We generated a fourth set of 10 synthetic datasets whose underlying correlation matrices exhibited
 418 prolonged intervals of stability, interspersed with abrupt changes. For each dataset, we used Equation 11
 419 to generate 5 random covariance matrices. We constructed a timeseries where each set of 60 consecutive
 420 samples was drawn from a Gaussian with the same covariance matrix. These datasets were intended to
 421 simulate a system that exhibits periods of stability punctuated by occasional abrupt state changes.

422 Synthetic data: simulating dynamic high-order correlations

423 We developed an iterative procedure for constructing timeseries data that exhibits known dynamic high-
 424 order correlations. The procedure builds on our approach to generating dynamic first-order correlations.
 425 Essentially, once we generate a timeseries with known first-order correlations, we can use the known first-
 426 order correlations as a template to generate a new timeseries of second-order correlations. In turn, we can
 427 generate a timeseries of third-order correlations from the second-order correlations, and so on. In general,
 428 we can generate order n correlations given a timeseries of order $n - 1$ correlations, for any $n > 1$. Finally,
 429 given the order n timeseries, we can reverse the preceding process to generate an order $n - 1$ timeseries, an
 430 order $n - 2$ order timeseries, and so on, until we obtain an order 0 timeseries of simulated data that reflects
 431 the chosen high-order dynamics.

The central mathematical operations in our procedure are two functions, $\text{vec}(\cdot)$ and $\text{mat}(\cdot)$. The $\text{vec}(\cdot)$ function takes as input a $K \times K$ symmetric matrix and returns as output a $(\frac{K^2-K}{2} + K)$ -dimensional column vector containing the entries in the upper triangle and diagonal. The $\text{mat}(\cdot)$ function inverts $\text{vec}(\cdot)$ by taking as input a $(\frac{K^2-K}{2} + K)$ -dimensional column vector and returning a $K \times K$ symmetric matrix as output. We can then generate an order n correlation matrix (for one timepoint, t) from an order $n - 1$ template (from the same timepoint) as follows:

$$\Sigma_n(t) = \text{mat}(\text{vec}(\Sigma_{n-1}(t)) \otimes \text{vec}(\Sigma_{n-1}(t))^\top). \quad (14)$$

Given a timeseries of order n correlation matrices, we can draw an order $n - 1$ correlation matrix for each timepoint t using

$$\sigma_{n-1}(t) \sim \mathcal{N}(\mathbf{0}, \Sigma_n(t)) \quad (15)$$

$$\Sigma_{n-1}(t) = \text{mat}(\sigma_{n-1}(t)). \quad (16)$$

432 We can then use repeated applications of Equations 15 and 16 in order to obtain a synthetic dataset.

433 When the template first-order correlations are constructed to exhibit different temporal profiles (e.g.,
434 using the constant, random, ramping, and event procedures described above), the resulting high-order
435 correlations and synthetic data will exhibit the same category of temporal profile.

436 Following our approach to generating synthetic data exhibiting known first-order correlations, we
437 constructed a total of 40 additional multivariate timeseries, collectively reflecting a total of 4 qualitatively
438 different patterns of dynamic correlations (i.e., 10 datasets reflecting each type of dynamic pattern: constant,
439 random, ramping, and event).

440 Functional neuroimaging data collected during story listening

441 We examined an fMRI dataset collected by Simony et al. (2016) that the authors have made publicly available
442 at arks.princeton.edu/ark:/88435/dsp015d86p269k. The dataset comprises neuroimaging data collected as
443 participants listened to an audio recording of a story (intact condition; 36 participants), listened to temporally
444 scrambled recordings of the same story (17 participants in the paragraph-scrambled condition listened to
445 the paragraphs in a randomized order and 36 in the word-scrambled condition listened to the words in a
446 randomized order), or lay resting with their eyes open in the scanner (rest condition; 36 participants). Full
447 neuroimaging details may be found in the original paper for which the data were collected (Simony et al.,
448 2016).

449 **Hierarchical topographic factor analysis (HTFA).** Following our prior related work, we used HTFA (Manning et al., 2018) to derive a compact representation of the neuroimaging data. In brief, this approach approximates the timeseries of voxel activations (44,415 voxels) using a much smaller number of radial basis function (RBF) nodes (in this case, 700 nodes, as determined by an optimization procedure described by Manning et al., 2018). This provides a convenient representation for examining full-brain network dynamics.

450 All of the analyses we carried out on the neuroimaging dataset were performed in this lower-dimensional

451 space. In other words, each participant’s data matrix, X_0 , was a number-of-timepoints by 700 matrix of

452 HTFA-derived factor weights (where the row and column labels were matched across participants). Code

453 for carrying out HTFA on fMRI data may be found as part of the BrainIAK toolbox (Capota et al., 2017),

454 which may be downloaded at brainiak.org.

455 **Temporal decoding**

456 We sought to identify neural patterns that reflected participants’ ongoing cognitive processing of incoming

457 stimulus information. As reviewed by Simony et al. (2016), one way of homing in on these stimulus-driven

458 neural patterns is to compare activity patterns across individuals (e.g., using ISFC analyses). In particular,

459 neural patterns will be similar across individuals to the extent that the neural patterns under consideration

460 are stimulus-driven, and to the extent that the corresponding cognitive representations are reflected in

461 similar spatial patterns across people (also see Simony & Chang, 2020). Following this logic, we used an

462 across-participant temporal decoding test developed by Manning et al. (2018) to assess the degree to which

463 different neural patterns reflected ongoing stimulus-driven cognitive processing across people (Fig. 10). The

464 approach entails using a subset of the data to train a classifier to decode stimulus timepoints (i.e., moments

465 in the story participants listened to) from neural patterns. We use decoding (forward inference) accuracy

466 on held-out data, from held-out participants, as a proxy for the extent to which the inputted neural patterns

467 reflected stimulus-driven cognitive processing in a similar way across individuals.

468 **Forward inference and decoding accuracy**

469 We used an across-participant correlation-based classifier to decode which stimulus timepoint matched

470 each timepoint’s neural pattern (Fig. 10). We first divided the participants into two groups: a template group,

471 $\mathcal{G}_{\text{template}}$ (i.e., training data), and a to-be-decoded group, $\mathcal{G}_{\text{decode}}$ (i.e., test data). We used Equation 7 to

472 compute a DISFC matrix for each group ($\bar{\mathbf{C}}_{\text{template}}$ and $\bar{\mathbf{C}}_{\text{decode}}$, respectively). We then correlated the rows of

473 $\bar{\mathbf{C}}_{\text{template}}$ and $\bar{\mathbf{C}}_{\text{decode}}$ to form a number-of-timepoints by number-of-timepoints decoding matrix, Λ . In this

474 way, the rows of Λ reflected timepoints from the template group, while the columns reflected timepoints

479 from the to-be-decoded group. We used Λ to assign temporal labels to each row $\bar{\mathbf{C}}_{\text{decode}}$ using the row of
480 $\bar{\mathbf{C}}_{\text{template}}$ with which it was most highly correlated. We then repeated this decoding procedure, but using
481 $\mathcal{G}_{\text{decode}}$ as the template group and $\mathcal{G}_{\text{template}}$ as the to-be-decoded group. Given the true timepoint labels (for
482 each group), we defined the *decoding accuracy* as the average proportion of correctly decoded timepoints,
483 across both groups. We defined the *relative decoding accuracy* as the difference between the decoding accuracy
484 and chance accuracy (i.e., $\frac{1}{T}$).

485 **Feature weighting and testing**

486 We sought to examine which types of neural features (i.e., activations, first-order dynamic correlations, and
487 higher-order dynamic correlations) were informative to the temporal decoders. Using the notation above,
488 these features correspond to $\mathbf{X}_0, \mathbf{X}_1, \mathbf{X}_2, \mathbf{X}_3$, and so on.

489 One challenge to fairly evaluating high-order correlations is that if the kernel used in Equation 4 is
490 wider than a single timepoint, each repeated application of the equation will result in further temporal
491 blur. Because our primary assessment metric is temporal decoding accuracy, this unfairly biases against
492 detecting meaningful signal in higher-order correlations (relative to lower-order correlations). We attempted
493 to mitigate temporal blur in estimating each \mathbf{X}_n by using a Dirac δ function kernel (which places all of its
494 mass over a single timepoint; Fig. 9b, 10a) to compute each lower-order correlation ($\mathbf{X}_1, \mathbf{X}_2, \dots, \mathbf{X}_{n-1}$). We
495 then used a new (potentially wider, as described below) kernel to compute \mathbf{X}_n from \mathbf{X}_{n-1} . In this way,
496 temporal blurring was applied only in the last step of computing \mathbf{X}_n . We note that, because each \mathbf{X}_n is a
497 low-dimensional representation of the corresponding \mathbf{Y}_n , the higher-order correlations we estimated reflect
498 true correlations in the data with lower-fidelity than estimates of lower-order correlations. Therefore, even
499 after correcting for temporal blurring, our approach is still biased against finding meaningful signal in
500 higher-order correlations.

501 After computing each $\mathbf{X}_1, \mathbf{X}_2, \dots, \mathbf{X}_{n-1}$ for each participant, we divided participants into two equally sized
502 groups (± 1 for odd numbers of participants): $\mathcal{G}_{\text{train}}$ and $\mathcal{G}_{\text{test}}$. We then further subdivided $\mathcal{G}_{\text{train}}$ into $\mathcal{G}_{\text{train}_1}$
503 and $\mathcal{G}_{\text{train}_2}$. We then computed Λ (temporal correlation) matrices for each type of neural feature, using $\mathcal{G}_{\text{train}_1}$
504 and $\mathcal{G}_{\text{train}_2}$. This resulted in $n + 1$ Λ matrices (one for the original timeseries of neural activations, and one
505 for each of n orders of dynamic correlations). Our objective was to find a set of weights for each of these
506 Λ matrices such that the weighted average of the $n + 1$ matrices yielded the highest decoding accuracy.
507 We used quasi-Newton gradient ascent (Nocedal & Wright, 2006), using decoding accuracy (for $\mathcal{G}_{\text{train}_1}$ and
508 $\mathcal{G}_{\text{train}_2}$) as the objective function to be maximized, to find an optimal set of training data-derived weights,
509 $\phi_{0,1,\dots,n}$, where $\sum_{i=0}^n \phi_i = 1$ and where $\phi_i \geq 0 \forall i \in [0, 1, \dots, n]$.




Figure 10: Decoding analysis pipeline. **a. Computing dynamic correlations from timeseries data.** Given a timeseries of observations as a $T \times K$ matrix (or a set of S such matrices), we use Equation 4 to compute each participant's DISFC (relative to other participants in the training or test sub-group, as appropriate). We repeat this process twice—once using the analysis kernel (shown here as a Gaussian in the upper row of the panel), and once using a δ function kernel (lower row of the panel). **b. Projecting dynamic correlations into a lower-dimensional space.** We project the training and test data into K -dimensional spaces to create compact representations of dynamic correlations at the given order (estimated using the analysis kernel). **c. Kernel trick.** We project the dynamic correlations computed using a δ function kernel into a common K -dimensional space. These low-dimensional embeddings are fed back through the analysis pipeline in order to compute features at the next-highest order. **d. Decoding analysis.** We split the training data into two equal groups, and optimize the feature weights (i.e., dynamic correlations at each order) to maximize decoding accuracy. We then apply the trained classifier to the (held-out) test data.

510 After estimating an optimal set of weights, we computed a new set of $n + 1$ Λ matrices correlating the
511 DISFC patterns from $\mathcal{G}_{\text{train}}$ and $\mathcal{G}_{\text{test}}$ at each timepoint. We use the resulting decoding accuracy of $\mathcal{G}_{\text{test}}$
512 timepoints (using the weights in $\phi_{0,1,\dots,n}$ to average the Λ matrices) to estimate how informative the set of
513 neural features containing up to n^{th} order correlations were.

514 We used a permutation-based procedure to form stable estimates of decoding accuracy for each set of
515 neural features. In particular, we computed the decoding accuracy for each of 10 random group assignments
516 of $\mathcal{G}_{\text{train}}$ and $\mathcal{G}_{\text{test}}$. We report the mean accuracy (along with 95% confidence intervals) for each set of neural
517 features.

518 Identifying robust decoding results

519 The temporal decoding procedure we use to estimate which neural features support ongoing cognitive
520 processing is governed by several parameters. In particular, Equation 4 requires defining a kernel function,
521 which can take on different shapes and widths. For a fixed set of neural features, each of these parameters
522 can yield different decoding accuracies. Further, the best decoding accuracy for a given timepoint may be
523 reliably achieved by one set of parameters, whereas the best decoding accuracy for another timepoint might
524 be reliably achieved by a different set of parameters, and the best decoding accuracy across *all* timepoints
525 might be reliably achieved by still another different set of parameters. Rather than attempting to maximize
526 decoding accuracy, we sought to discover the trends in the data that were robust to classifier parameters
527 choices. Specifically, we sought to characterize how decoding accuracy varied (under different experimental
528 conditions) as a function of which neural features were considered.

529 To identify decoding results that were robust to specific classifier parameter choices, we repeated our
530 decoding analyses after substituting into Equation 4 each of a variety of kernel shapes and widths. We
531 examined Gaussian (Fig. 9c), Laplace (Fig. 9d), and Mexican Hat (Fig. 9e) kernels, each with widths of 5, 10,
532 20, and 50 samples. We then report the average decoding accuracies across all of these parameter choices.
533 This enabled us to (partially) factor out performance characteristics that were parameter-dependent, within
534 the set of parameters we examined.

535 Reverse inference

536 The dynamic patterns we examined comprise high-dimensional correlation patterns at each timepoint. To
537 help interpret the resulting patterns in the context of other studies, we created summary maps by computing
538 the across-timepoint average pairwise correlations at each order of analysis (first order, second order, etc.).
539 We selected the 10 strongest (absolute value) correlations at each order. Each correlation is between the

540 dynamic activity patterns (or patterns of dynamic high-order correlations) measured at two RBF nodes
541 (see *Hierarchical Topographic Factor Analysis*). Therefore, the 10 strongest correlations involved up to 20 RBF
542 nodes. Each RBF defines a spatial function whose activations range from 0 to 1. We constructed a map
543 of RBF components that denoted the endpoints of the 10 strongest correlations (we set each RBF to have a
544 maximum value of 1). We then carried out a meta analysis using Neurosynth (Rubin et al., 2017) to identify
545 the 10 terms most commonly associated with the given map. This resulted in a set of 10 terms associated
546 with the average dynamic correlation patterns at each order.

547 Acknowledgements

548 We acknowledge discussions with Luke Chang, Vassiki Chauhan, Hany Farid, Paxton Fitzpatrick, Andrew
549 Heusser, Eshin Jolly, Aaron Lee, Qiang Liu, Matthijs van der Meer, Judith Mildner, Gina Notaro, Stephen
550 Satterthwaite, Emily Whitaker, Weizhen Xie, and Kirsten Ziman. Our work was supported in part by NSF
551 EPSCoR Award Number 1632738 to J.R.M. and by a sub-award of DARPA RAM Cooperative Agreement
552 N66001-14-2-4-032 to J.R.M. The content is solely the responsibility of the authors and does not necessarily
553 represent the official views of our supporting organizations.

554 Author contributions

555 Concept: J.R.M. Implementation: T.H.C., L.L.W.O., and J.R.M. Analyses: L.L.W.O. and J.R.M. Writing:
556 L.L.W.O. and J.R.M.

557 References

- 558 Allen, E. A., Damaraju, E., Plis, S. M., Erhardt, E. B., Eichele, T., & Calhoun, V. D. (2012). Tracking
559 whole-brain connectivity dynamics in the resting state. *Cerebral Cortex*, 24(3), 663–676.
- 560 Alvarez-Hamelin, I., Dall'Asta, L., Barrat, A., & Vespignani, A. (2005). k -corr decomposition: a tool for the
561 visualiztion of large scale networks. *arXiv*, cs/0504107v2.
- 562 Baldassano, C., Chen, J., Zadbood, A., Pillow, J. W., Hasson, U., & Norman, K. A. (2017). Discovering event
563 structure in continuous narrative perception and memory. *Neuron*, 95(3), 709–721.
- 564 Barthélémy, M. (2004). Betweenness centrality in large complex networks. *European Physical Journal B*, 38,
565 163–168.

- 566 Bassett, D., Meyer-Lindenberg, A., Achard, S., Duke, T., & Bullmore, E. (2006, December). Adaptive
567 reconfiguration of fractal small-world human brain functional networks. *Proceedings of the National
568 Academy of Sciences, USA*, 103(51), 19518–23.
- 569 Beaty, R. E., Benedek, M., Silvia, P. J., & Schacter, D. L. (2016). Creative cognition and brain network
570 dynamics. *Trends in Cognitive Sciences*, 20(2), 87–95.
- 571 Betzel, R. F., Byrge, L., Esfahlani, F. Z., & Kennedy, D. P. (2019). Temporal fluctuations in the brain's modular
572 architecture during movie-watching. *bioRxiv*, doi.org/10.1101/750919.
- 573 Bonacich, P. (2007). Some unique properties of eigenvector centrality. *Social Networks*, 29(4), 555–564.
- 574 Bullmore, E., & Sporns, O. (2009). Complex brain networks: graph theoretical analysis of structural and
575 functional systems. *Nature Reviews Neuroscience*, 10(3), 186–198.
- 576 Capota, M., Turek, J., Chen, P.-H., Zhu, X., Manning, J. R., Sundaram, N., . . . Shin, Y. S. (2017). *Brain imaging
577 analysis kit*. Retrieved from <https://doi.org/10.5281/zenodo.59780>
- 578 Chang, C., & Glover, G. H. (2010). Time-frequency dynamics of resting-state brain connectivity measured
579 with fMRI. *NeuroImage*, 50, 81–98.
- 580 Chien, H.-Y. S., & Honey, C. J. (2019). Constructing and forgetting temporal context in the human cerebral
581 cortex. *bioRxiv*, doi.org/10.1101/761593.
- 582 Christakis, N. A., & Fowler, J. H. (2010). Social network sensors for early detection of contagious outbreaks.
583 *PLoS One*, 5(9), e12948.
- 584 Combrisson, E., Vallat, R., O'Reilly, C., Jas, M., Pasarella, A., l Saive, A., . . . Jerbi, K. (2019). Visbrain: a
585 multi-purpose GPU-accelerated open-source suite for multimodal brain data visualization. *Frontiers in
586 Neuroinformatics*, 13(14), 1–14.
- 587 Comon, P., Jutten, C., & Herault, J. (1991). Blind separation of sources, part II: Problems statement. *Signal
588 Processing*, 24(1), 11 - 20.
- 589 Demertzi, A., Tagliazucchi, E., Dehaene, S., Deco, G., Barttfeld, P., Raimondo, F., . . . Sitt, J. D. (2019). Human
590 consciousness is supported by dynamic complex patterns of brain signal coordination. *Science Advances*,
591 5(2), eaat7603.
- 592 Estrada, E., & Rodríguez-Velázquez, J. A. (2005). Subgraph centrality in complex networks. *Physical Review
593 E*, 71(5), 056103.

- 594 Etzel, J. A., Gazzola, V., & Keysers, C. (2009). An introduction to anatomical ROI-based fMRI classification.
595 *Brain Research*, 1281, 114–125.
- 596 Fallon, J., Ward, P., Parkes, L., Oldham, S., Arnatkevičiūtė, A., Fornito, A., & Fulcher, B. D. (2019).
597 Timescales of spontaneous activity fluctuations relate to structural connectivity in the brain. *bioRxiv*,
598 doi.org/10.1101/655050.
- 599 Fong, A. H. C., Yoo, K., Rosenberg, M. D., Zhang, S., Li, C.-S. R., Scheinost, D., ... Chun, M. M. (2019).
600 Dynamic functional connectivity during task performance and rest predicts individual differences in
601 attention across studies. *NeuroImage*, 188, 14–25.
- 602 Freeman, L. C. (1977). A set of measures of centrality based on betweenness. *Sociometry*, 40(1), 35–41.
- 603 Friston, K. (2000). The labile brain. i. neuronal transients and nonlinear coupling. *Phil. Trans. Roy. Soc. Lon.*,
604 355B, 215–236.
- 605 Geisberger, R., Sanders, P., & Schultes, D. (2008). Better approximation of betweenness centrality. *Proceedings*
606 *of the meeting on Algorithm Engineering and Experiments*, 90–100.
- 607 Gershman, S., Blei, D., Pereira, F., & Norman, K. (2011). A topographic latent source model for fMRI data.
608 *NeuroImage*, 57, 89–100.
- 609 Gonzalez-Castillo, J., Caballero-Gaudes, C., Topolski, N., Handwerker, D. A., Pereira, F., & Bandettini, P. A.
610 (2019). Imaging the spontaneous flow of thought: distinct periods of cognition contribute to dynamic
611 functional connectivity during rest. *NeuroImage*, 202(116129).
- 612 Grossberg, S. (1988). Nonlinear neural networks: Principles, mechanisms, and architectures. *Neural*
613 *networks*, 1(1), 17–61.
- 614 Halu, A., Mondragón, R. J., Panzarasa, P., & Bianconi, G. (2013). Multiplex PageRank. *PLoS One*, 8(10),
615 e78293.
- 616 Hasson, U., Chen, J., & Honey, C. J. (2015). Hierarchical process memory: memory as an integral component
617 of information processing. *Trends in Cognitive Science*, 19(6), 304–315.
- 618 Hasson, U., Yang, E., Vallines, I., Heeger, D. J., & Rubin, N. (2008). A hierarchy of temporal receptive windows
619 in human cortex. *Journal of Neuroscience*, 28(10), 2539–2550. doi: 10.1523/JNEUROSCI.5487-07.2008
- 620 Haxby, J. V., Gobbini, M. I., Furey, M. L., Ishai, A., Schouten, J. L., & Pietrini, P. (2001). Distributed and
621 overlapping representations of faces and objects in ventral temporal cortex. *Science*, 293, 2425–2430.

- 622 Hinton, G. E., & Salakhutdinov, R. R. (2006). Reducing the dimensionality of data with neural networks.
623 *Science*, 313(5786), 504–507.
- 624 Honey, C. J., Kötter, R., Breakspear, M., & Sporns, O. (2007). Network structure of cerebral cortex shapes
625 functional connectivity on multiple time scales. *Proceedings of the National Academy of Science USA*, 104(24),
626 10240–10245.
- 627 Honey, C. J., Thesen, T., Donner, T. H., Silbert, L. J., Carlson, C. E., Devinsky, O., . . . Hasson, U. (2012). Slow
628 cortical dynamics and the accumulation of information over long timescales. *Neuron*, 76, 423–434. doi:
629 10.1016/j.neuron.2012.08.011
- 630 Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E., & Gallant, J. L. (2016). Natural speech reveals
631 the semantic maps that tile human cerebral cortex. *Nature*, 532, 453–458.
- 632 Huth, A. G., Nisimoto, S., Vu, A. T., & Gallant, J. L. (2012). A continuous semantic space describes
633 the representation of thousands of object and action categories across the human brain. *Neuron*, 76(6),
634 1210–1224.
- 635 Jutten, C., & Herault, J. (1991). Blind separation of sources, part I: An adaptive algorithm based on
636 neuromimetic architecture. *Signal Processing*, 24(1), 1–10.
- 637 Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human brain. *Nature
638 Neuroscience*, 8, 679–685.
- 639 Landau, E. (1895). Zur relativen Wertbemessung der Turnierresultate. *Deutsches Wochenschach*, 11, 366–369.
- 640 Lee, C. S., Aly, M., & Baldassano, C. (2020). Anticipation of temporally structured events in the brain.
641 *bioRxiv*, 10.1101/2020.10.14.338145.
- 642 Lee, D. D., & Seung, H. S. (1999). Learning the parts of objects by non-negative matrix factorization. *Nature*,
643 401, 788–791.
- 644 Lerner, Y., Honey, C. J., Katkov, M., & Hasson, U. (2014). Temporal scaling of neural responses to compressed
645 and dilated natural speech. *Journal of Neurophysiology*, 111, 2433–2444.
- 646 Lerner, Y., Honey, C. J., Silbert, L. J., & Hasson, U. (2011). Topographic mapping of a hierarchy of
647 temporal receptive windows using a narrated story. *Journal of Neuroscience*, 31(8), 2906–2915. doi: 10.1523/
648 JNEUROSCI.3684-10.2011

- 649 Liégeois, R., Li, J., Kong, R., Orban, C., De Ville, D. V., Ge, T., ... Yeo, B. T. T. (2019). Resting brain
650 dynamics at different timescales capture distinct aspects of human behavior. *Nature Communications*,
651 10(2317), doi.org/10.1038/s41467-019-10317-7.
- 652 Lin, J. (2009). Divergence measures based on the Shannon entropy. *IEEE Transactions on Information Theory*,
653 37(1), 145–151.
- 654 Lohmann, G., Margulies, D. S., Horstmann, A., Pleger, B., Lepsien, J., Goldhahn, D., ... Turner, R. (2010).
655 Eigenvector centrality mapping for analyzing connectivity patterns in fMRI data of the human brain.
656 *PLoS One*, 5(4), e10232.
- 657 Lurie, D., Kessler, D., Bassett, D., Betzel, R., Breakspear, M., Keilholz, S., ... Calhoun, V. (2018). On the
658 nature of time-varying functional connectivity in resting fMRI. *PsyArXiv*, doi.org/10.31234/osf.io/xtzre.
- 659 Mack, M. L., Preston, A. R., & Love, B. C. (2017). Medial prefrontal cortex compresses concept representations
660 through learning. *bioRxiv*, doi.org/10.1101/178145.
- 661 Mairal, J., Ponce, J., Sapiro, G., Zisserman, A., & Bach, F. R. (2009). Supervised dictionary learning. *Advances
662 in Neural Information Processing Systems*, 1033–1040.
- 663 Mairal, J. B., Bach, F., Ponce, J., & Sapiro, G. (2009). Online dictionary learning for sparse coding. *Proceedings
664 of the 26th annual international conference on machine learning*, 689–696.
- 665 Manning, J. R., Ranganath, R., Norman, K. A., & Blei, D. M. (2014). Topographic factor analysis: a Bayesian
666 model for inferring brain networks from neural data. *PLoS One*, 9(5), e94914.
- 667 Manning, J. R., Zhu, X., Willke, T. L., Ranganath, R., Stachenfeld, K., Hasson, U., ... Norman, K. A. (2018).
668 A probabilistic approach to discovering dynamic full-brain functional connectivity patterns. *NeuroImage*,
669 180, 243–252.
- 670 McInnes, L., Healy, J., & Melville, J. (2018). UMAP: Uniform manifold approximation and projection for
671 dimension reduction. *arXiv*, 1802(03426).
- 672 McIntosh, A. R., & Jirsa, V. K. (2019). The hidden repertoire of brain dynamics and dysfunction. *Network
673 Neuroscience*, doi.org/10.1162/netn_a_00107.
- 674 Mitchell, T., Shinkareva, S., Carlson, A., Chang, K., Malave, V., Mason, R., & Just, M. (2008). Predicting
675 human brain activity associated with the meanings of nouns. *Science*, 320(5880), 1191.
- 676 Newman, M. E. J. (2005). A measure of betweenness centrality based on random walks. *Social Networks*, 27,
677 39–54.

- 678 Newman, M. E. J. (2008). The mathematics of networks. *The New Palgrave Encyclopedia of Economics*, 2, 1–12.
- 679 Nishimoto, S., Vu, A., Naselaris, T., Benjamini, Y., Yu, B., & Gallant, J. (2011). Reconstructing visual
680 experience from brain activity evoked by natural movies. *Current Biology*, 21, 1 - 6.
- 681 Nocedal, J., & Wright, S. J. (2006). *Numerical optimization*. New York: Springer.
- 682 Norman, K. A., Newman, E., Detre, G., & Polyn, S. M. (2006). How inhibitory oscillations can train neural
683 networks and punish competitors. *Neural Computation*, 18, 1577–1610.
- 684 Opsahl, T., Agneessens, F., & Skvoretz, J. (2010). Node centrality in weighted networks: generalizing degree
685 and shortest paths. *Social Networks*, 32, 245–251.
- 686 Park, H.-J., Friston, K. J., Pae, C., Park, B., & Razi, A. (2018). Dynamic effective connectivity in resting state
687 fMRI. *NeuroImage*, 180, 594–608.
- 688 Pearson, K. (1901). On lines and planes of closest fit to systems of points in space. *The London, Edinburgh,
689 and Dublin Philosophical Magazine and Journal of Science*, 2, 559–572.
- 690 Pereira, F., Lou, B., Pritchett, B., Ritter, S., Gershman, S. J., Kanwisher, N., ... Fedorenko, E. (2018). Toward
691 a universal decoder of linguistic meaning from brain activation. *Nature Communications*, 9(963), 1–13.
- 692 Preti, M. G., Bolton, T. A. W., & Van De Ville, D. (2017). The dynamic functional connectome: state-of-the-art
693 and perspectives. *NeuroImage*, 160, 41–54.
- 694 Rao, C. R. (1982). Diversity and dissimilarity coefficients: a unified approach. *Theoretical Population Biology*,
695 21(1), 24–43.
- 696 Reimann, M. W., Nolte, M., Scolamiero, M., Turner, K., Perin, R., Chindemi, G., ... Markram, H. (2017).
697 Cliques of neurons bound into cavities provide a missing link between structure and function. *Frontiers
698 in Computational Neuroscience*, 11(48), 1–16.
- 699 Ricotta, C., & Szeidl, L. (2006). Towards a unifying approach to diversity measures: Bridging the gap
700 between the Shannon entropy and Rao's quadratic index. *Theoretical Population Biology*, 70(3), 237–243.
- 701 Roy, D. S., Park, Y.-G., Ogawa, S. K., Cho, J. H., Choi, H., Kamensky, L., ... Tonegawa, S. (2019). Brain-
702 wide mapping of contextual fear memory engram ensembles supports the dispersed engram complex
703 hypothesis. *bioRxiv*, doi.org/10.1101/668483.
- 704 Rubin, T. N., Kyoejo, O., Gorgolewski, K. J., Jones, M. N., Poldrack, R. A., & Yarkoni, T. (2017). Decoding
705 brain activity using a large-scale probabilistic functional-anatomical atlas of human cognition. *PLoS
706 Computational Biology*, 13(10), e1005649.

- 707 Rubinov, M., & Sporns, O. (2010). Complex network measures of brain connectivity: uses and interpreta-
708 tions. *NeuroImage*, 52, 1059–1069.
- 709 Schreiber, T. (2000). Measuring information transfer. *Physical Review Letters*, 85(2), 461–464.
- 710 Shappell, H., Caffo, B. S., Pekar, J. J., & Lindquist, M. A. (2019). Improved state change estimation in
711 dynamic functional connectivity using hidden semi-Markov models. *NeuroImage*, 191, 243–257.
- 712 Simony, E., & Chang, C. (2020). Analysis of stimulus-induced brain dynamics during naturalistic paradigms.
713 *NeuroImage*, 216, 116461.
- 714 Simony, E., Honey, C. J., Chen, J., & Hasson, U. (2016). Dynamic reconfiguration of the default mode
715 network during narrative comprehension. *Nature Communications*, 7(12141), 1–13.
- 716 Sizemore, A. E., Giusti, C., Kahn, A., Vettel, J. M., Betzel, R. F., & Bassett, D. S. (2018). Cliques and cavities
717 in the human connectome. *Journal of Computational Neuroscience*, 44(1), 115–145.
- 718 Solomon, S. H., Medaglia, J. D., & Thompson-Schill, S. L. (2019). Implementing a concept network model.
719 *Behavior Research Methods*, 51, 1717–1736.
- 720 Spearman, C. (1904). General intelligence, objectively determined and measured. *American Journal of
721 Psychology*, 15, 201–292.
- 722 Sporns, O., & Honey, C. J. (2006). Small worlds inside big brains. *Proceedings of the National Academy of
723 Science USA*, 103(51), 19219–19220.
- 724 Thompson, W. H., Richter, C. G., Plavén-Sigray, P., & Fransson, P. (2018). Simulations to benchmark
725 time-varying connectivity methods for fMRI. *PLoS Computational Biology*, 14(5), e1006196.
- 726 Tipping, M. E., & Bishop, C. M. (1999). Probabilistic principal component analysis. *Journal of Royal Statistical
727 Society, Series B*, 61(3), 611–622.
- 728 Toker, D., & Sommer, F. T. (2019). Information integration in large brain networks. *PLoS Computational
729 Biology*, 15(2), e1006807.
- 730 Tong, F., & Pratte, M. S. (2012). Decoding patterns of human brain activity. *Annual Review of Psychology*, 63,
731 483–509.
- 732 Turk-Browne, N. B. (2013). Functional interactions as big data in the human brain. *Science*, 342, 580–584.
- 733 van der Maaten, L. J. P., & Hinton, G. E. (2008). Visualizing high-dimensional data using t-SNE. *Journal of
734 Machine Learning Research*, 9, 2579–2605.

- 735 Vidaurre, D., Abeysuriya, R., Becker, R., Quinn, A. J., Alfaro-Almagro, F., Smith, S. M., & Woolrich, M. W.
736 (2018). Discovering dynamic brain networks from big data in rest and task. *NeuroImage*, 180, 646–656.
- 737 Zar, J. H. (2010). *Biostatistical analysis*. Prentice-Hall/Pearson.
- 738 Zheng, M., Allard, A., Hagmann, P., & Serrano, M. A. (2019). Geometric renormalization unravels self-
739 similarity of the multiscale human connectome. *arXiv*, 1904.11793.
- 740 Zou, Y., Donner, R. V., Marwan, N., Donges, J. F., & Kurths, J. (2019). Complex network approaches to
741 nonlinear time series analysis. *Physics Reports*, 787, 1–97.