

Using Python to Speed-up Applications with GPUs

Travis Oliphant & Siu Kwan Lam

March 12, 2013

Schedule

- ▶ Introduction
 - ▶ Python
 - ▶ Numba
 - ▶ NumbaPro
- ▶ Lab 1
- ▶ Lab 2

Introduction

Why Python?

Pros

- ▶ A dynamic scripting language
- ▶ Rapid development
- ▶ Rich libraries — NumPy, SciPy
- ▶ Great glue language to connect native libraries

Cons

- ▶ Global Interpreter Lock (GIL)
- ▶ Slow execution speed

Our Solution: Numba

- ▶ An opensource **JIT** compiler for **array-oriented programming** in CPython
- ▶ Turn numerical loops into fast native code
- ▶ Maximize hardware utilization
- ▶ Just add a decorator to your compute intensive function

Why Numba?

- ▶ Works with existing CPython
- ▶ Goal: Integration with scientific software stack
 - ▶ Numpy/SciPy/Blaze

Mandelbrot in Numba

```
from numba import autojit
@autojit # <--- All we need to add
def mandel(x, y, max_iters):
    i = 0
    c = complex(x,y)
    z = 0.0j
    for i in range(max_iters):
        z = z*z + c
        if (z.real*z.real + z.imag*z.imag) >= 4:
            return i
    return 255
```

- Over **170x** speedup

Need More Speed? Use NumbaPro “CUDA Python”

- Our commercial product enables parallel compute on GPU.

```
from numbapro import cuda, uint8, f8, uint32
# use CUDA jit
@cuda.jit(argtypes=[uint8[:, :], f8, f8, f8, f8, uint32])
def mandel_kernel(image, min_x, max_x, min_y, max_y, iters):
    height = image.shape[0]
    width = image.shape[1]
    pixel_size_x = (max_x - min_x) / width
    pixel_size_y = (max_y - min_y) / height
    # access thread indices
    x = cuda.threadIdx.x + cuda.blockIdx.x * cuda.blockDim.x
    y = cuda.threadIdx.y + cuda.blockIdx.y * cuda.blockDim.y
    # truncated ...
```

- **1255x** faster on K20

NumbaPro CU API

- ▶ Compute Unit (CU) API
- ▶ Similar to OpenCL
- ▶ Portable parallel programming for GPU, CPU
- ▶ Execute kernels asynchronously

A Saxpy Example

```
def product(tid, A, B, Prod):  
    Prod[tid] = A[tid] * B[tid]  
  
def sum(tid, A, B, Sum):  
    Sum[tid] = A[tid] + B[tid]  
  
cu = CU('gpu') # or CU('cpu')  
... # prepare data  
cu.enqueue(product, ntid=dProd.size,  
            args=(dA, dB, dProd))  
cu.enqueue(sum, ntid=dSum.size,  
            args=(dProd, dC, dSum))  
... # do something while waiting?  
cu.wait()  
  
cu.close() # destroy the compute unit
```

Lab 1

Saxpy in “CUDA Python”

Quick Lesson to CUDA Python

- ▶ Similar to CUDA-C

Memory Transfer

- ▶ Host->Device
 - ▶ `d_ary = cuda.to_device(ary)`
- ▶ Host->Device (allocate only, no copy)
 - ▶ `d_ary = cuda.to_device(ary, copy=False)`
- ▶ Device->Host
 - ▶ `d_ary.to_host()`

Compile and Launch

- ▶ Decorate kernel
 - ▶ `cuda.autojit, cuda.jit`
- ▶ Kernel launch
 - ▶ `a_kernel[griddim, blockddim](arg0, arg1)`
 - ▶ similar to C: `a_kernel<<<griddim, blockdim>>>(arg0, arg1)`
 - ▶ `griddim`: tuple of 1-2 ints
 - ▶ `blockdim`: tuple of 1-3 ints
- ▶ `threadIdx, blockIdx, blockDim -> cuda.threadIdx, cuda.blockIdx, cuda.blockDim`
 - ▶ `i = cuda.threadIdx.x + cuda.blockIdx.x * cuda.blockDim.x`

Lab 2

A “Monty” Carlo Option Pricer in NumbaPro CU API

Quick Lesson on NumbaPro CU API

- ▶ CU = Compute Unit
- ▶ A OpenCL-like API to heterogeneous parallel computing
- ▶ Instantiate a CU for 'gpu' or 'cpu'
 - ▶ `cu = CU('gpu')`
- ▶ Transfer data to the CU
 - ▶ `d_ary = cu.input(ary)`
 - ▶ `d_ary = cu.output(ary)`
 - ▶ `d_ary = cu.inout(ary)`
 - ▶ `d_ary = cu.scratch(shape=arraylen, dtype=np.float32)`
 - ▶ `d_ary = cu.scratch_like(ary)`
- ▶ Enqueue kernels to the CU
 - ▶ `cu.enqueue(kernel, ntid=number_of_threads, args=(arg0, arg1))`
- ▶ The kernel runs asynchronously
- ▶ Wait for the kernel to complete
 - ▶ `cu.wait()`

A Numpy Implementation

```
import numpy as np
from math import sqrt, exp
from timeit import default_timer as timer

def step(dt, prices, c0, c1, noises):
    return prices * np.exp(c0 * dt + c1 * noises)

def monte_carlo_pricer(paths, dt, interest, volatility):
    c0 = interest - 0.5 * volatility ** 2
    c1 = volatility * np.sqrt(dt)

    for j in xrange(1, paths.shape[1]):
        prices = paths[:, j - 1]
        noises = np.random.normal(0., 1., prices.size)
        paths[:, j] = step(dt, prices, c0, c1, noises)
```