3I Atlas [C 2025/N1]

1. It formed around an alien star.

2. The properties of it's materials give us a rare, direct look at the chemistry of a completely different solar system. Meaning they have a knowledge of our chemistry and also theirs is different. Maybe the star that is igniting the life in their system is made from different material also. That might be the course of the reason behind the rare and different chemistry of the object.

3. 3I/ATLAS was clocked at a staggering speed of roughly 250,000 km/h (about 70 km/s) at its closest approach to the Sun.
It accelerated as it approached it. The materials that is made of made possible charging it with energy and becouse of that it can travel with this speed maybe even higher in our solar system.
[It is taking it's motion charge not from a battery but from a whole star (as the Sun).

4. Ejection from a star system is coasting to another. So it is important how and from where a star system is exited from. This equals the entrance point of the "coasting" phenomenon. Because there is zero friction in deep space, the exact amount of "charge" (velocity and kinetic energy) the object was kicked out with billions of years ago is preserved indefinitely. It simply coasts across the void until it hits another gravity well (like our Sun) to give it a new trajectory and a massive speed boost.

5. Space is a true physical vacuum, meaning there is almost zero friction to slow things down. Meaning the materials it is made from where also "charged" from the star they came from (hevaly charged) at the moment of ejection and coasting of the object.

6. It doesn't absorb electrical charge; instead, it literally steals kinetic energy (momentum) from the Sun's immense gravity to accelerate to 250,000 km/h.

7. The object serves as a physical "chemical messenger" coming from different star system with different type of star.

Non-gravitational acceleration

The needed :

As the Sun heated the comet, it released highly pressurized jets of gas (outgassing). In the vacuum of space, these jets act exactly like tiny rocket thrusters, physically pushing.

The thrusters gasus emit a trail [carbon dioxide, water ice, methane, and carbon monoxide]. This is the product of the gasus not the container filling that is ejected thru pressurized jets.

3I Atlas [C 2025/N1] (enter the black hole)

1. 3I Atlas comes from a vary dtant Galaxy.
2. How can it travel so fast thru but we cannot also how it was detected when it got close to the Sun?
3. The 3I Atlas entered thru an frequency entrance the black whole that we call "Ether" or "vaccum" space.
4. We detected it but we had a knowledge that it can shift it's traectory suddenly so that's why we watched it closely. We knew becouse of the way that 3I Atlas appeared. It must have been doing just that thru it's whole travel (changing his traectory suddenly, probably vanishing suddenly and appearing elsewhere is truly possible for 3I Atlas (which may be a reason for it's appearance (as a peache of matter in vaccum space made from unknown materials to us)).

Cammands

```
az login
-----------------------------------------------
# Създаване на ресурсна група
az group create --name SatelliteProjectRG --location francecentral

# Създаване на виртуална мрежа с проверка на IP сегмента
az network vnet create \
  --name SatelliteVNet \
  --resource-group SatelliteProjectRG \
  --address-prefix 10.0.0.0/16 \
  --subnet-name SatelliteSubnet \
  --subnet-prefix 10.0.1.0/24
-----------------------------------------------
az storage account create --name satellitestorage2026 --resource-group SatelliteProjectRG
--location francecentral --sku Standard_LRS

-----------------------------------------------
az storage blob upload --account-name satellitestorage2026 --container-name images --name
RedHatSatellite.vhd --file /path/to/your/RedHatSatellite.vhd

-----------------------------------------------
# Създаване на изображение от VHD
az image create --resource-group SatelliteProjectRG --name SatelliteOSImage --source
https://satellitestorage2026.blob.core.windows.net/images/RedHatSatellite.vhd --os-type Linux

# Пускане на виртуалната машина
az vm create \
  --resource-group SatelliteProjectRG \
```

```
  --name SatelliteControlVM \
  --image SatelliteOSImage \
  --admin-username stanislava \
  --vnet-name SatelliteVNet \
  --subnet SatelliteSubnet \
  --public-ip-address-allocation static

-----------------------------------------------
# Създаване на правило, позволяващо достъп само от вашето публично IP
az network nsg rule create \
  --resource-group SatelliteProjectRG \
  --nsg-name SatelliteVMNSG \
  --name AllowSpecificSource \
  --priority 100 \
  --source-address-prefixes [ВАШЕТО_ПУБЛИЧНО_IP] \
  --destination-port-ranges 22 443 \
  --access Allow \
  --protocol Tcp
```

National Standard Authority of Ireland

Údarás Um Chaighdeáin Náisiúnta na hÉireann
Complex organization registration process.
Type of certification ---> Complex organization
An organization having an identified central function and a network of locations that are any combination of multiple sites, campus (can be more than one campus), or several sites.
All sites shall have a legal or contractual link with the central office.
NOTE: If your organization does not meet ALL the listed criteria, please review the Certification Types again.

IMPORTANT

----------++++++----------
This is an EXCEL table content from the form for registration for certification of Complex organization.
----------++++++----------

Network Link between China and France, Paris Central

Full-Featured Software Development Kit.
Supporting both 32-bit and 64-bit versions of Windows and Linux (x86), the MicroGate Serial API gives developers direct access to the SyncLink adapter and serial link for total control of HDLC/SDLC, BISYNC, MONOSYNC, ISOCHRONOUS, ASYNC and RAW synchronous bit streams. These protocols are used to build applications for networking, X.25, IBM SDLC (SNA), satellite, radio and other serial communications.

SyncLink® GT4e Adapter

Multiport High-Speed PCIe Adapter.

The SyncLink GT4e Adapter features bus master control for sustained 10Mbps synchronous communications simultaneously on all four ports and asynchronous connections up to 8Mbps. The 1x bus connector supports the latest workstation, stand-a-lone server, rack mount server or ruggedize system requiring synchronous or asynchronous connections. The number of adapters one can place in a single system is only limited by the number of slots available in the computer.

The SyncLink GT4e synchronous adapter utilizes the MicroGate FPGA Serial Controller. Beyond providing seamless integration between the hardware and software drivers, MicroGate is able to offer customized serial controller interfaces for users needing additional control over the serial links. There is no need for custom hardware but rather quick modifications to the FPGA programming.

Full-Featured Software Development Kit.
Supporting both 32-bit and 64-bit versions of Windows and Linux (x86), the MicroGate Serial API gives developers direct access to the SyncLink adapter and serial link for total control of HDLC/SDLC, BISYNC, MONOSYNC, ISOCHRONOUS, ASYNC and RAW synchronous bit streams. These protocols are used to build applications for networking, X.25, IBM SDLC (SNA), satellite, radio and other serial communications.

Additional Support.
The SyncLink drivers are part of the base Linux kernel, providing direct support with Linux networking options.

Download the Hardware Guide and MicroGate Serial API for Windows/Linux for details on using the card for a specific application.

SyncLink GT4e Adapter Specifications
A variety of serial protocols and interface standards are supported. Refer to the software documentation included with the card for details on using the card for a specific application.

SDLC, HDLC, BISYNC, MONOSYNC, ISOCHRONOUS, ASYNC, RAW bit-synchronous

protocols

Windows and Linux APIThe MicroGate Serial API Mecrogates

1. China location accessed software from the laptop or desktop (preferably Windows 11 Enterprise Evaluation or by choice) need to have the Microgate Serial API for Windows even without any another accomplying it software for the hardware.
2. The VM that is running on the China located laptop or desktop and is with installed custom image of the Red Hat software Linux Satellite Control Center OS needs to have the Linux Microgate Serial API available.
Link for Linux API download that will be available to access and downloaded directly after the VM OS installation and first running (because of the regional change of VM (Paris Central).
Here is the link: https://microgate.com/
In windows the API must be added in PowerShell profile as a variable that is called
$LINKAPI = "(the API here as a string)"
and will start everytime when the user starts the China located laptop or desktop machine.

Linux Satellite Control center OS (China, France, Paris Central (Azure VM VPN) regional mandatory)

Location in China accessed by VM in cloud running in region Paris in France that is the Central region of the cloud.
1. Download the Red Hat Satellite OS that is downloadable from red hat as VM.
2. Add customization and create the interface and add specific commands and shortkeys also make sure to be able to use a VPN for a connection that comes from only one source possible (periferia) for first location network access (your location).
3. Next log in azure.microaoft.com and create a resource group in Region, France, Paris Central.
4. Log in azure.microsoft.com and create a resource group in Region France, Paris Central.
5. To this resource group add the corresponding resources needed to run a VM machine with the Image of the Linux (Red Hat Satellite Control Central OS VM. Add a virtual machine with custom image) but first upload the created software that you downloaded for customization from Red Hat.
6. In the resource groupCreate a virtual private network in location of the resource (France, Paris Central) and make sure you choose available IP address for this region when creating the VPN in resource group in that region that are actually addresses in that region. Check France, Paris Central region by checking IP location separetly (in browser) by offered IP.
PS: Add microgate-sdk-linux.zip file to OS for use or add it as a sdk in the OS terminal available in the Image uploaded to the region!

Certification Structure Matrix (file upload at the bottom 20MB) for registration of certification

Shared via Excel on Android

OBJ

How to Get ISO 9001 Certification

Request For Quote
"*" indicates required fields

Registration*
Select one or more registrations you are interested in.

Registration*
Select one or more registrations you are interested in.
ISO 9001
ISO 14001
ISO 45001
AS 9100 / AS 9120*
TL 9000
Integrated Management System (Check all standards above that apply)
*If you are interested in AS 9100/9120 please complete ∆ Certification Structure Matrix and attach it using File Uploads section at the end of this form)
∆

*ISO 45001 Applications, please see attached “Supplemental” information and submit to the office accordingly.

File Uploads
Drop files here or
Select files
No file chosen
Max. file size: 20 MB.
If you have extra documents, such as the Certification Structure Matrix please upload them here.
How Did You Hear About Us?
If this is a formal application for certification or registration, then please indicate you have read and accept the NSAI Company Agreement & General Conditions.*
I Accept

How to start ISO 9001 Registration

The ISO 9001 Registration Process comes after your company's ISO 9001 audit. The purpose of registering your company is to show that you've met the requirements. And to do this effectively, you will need to follow eight essential steps. NSAI can guide your company through this ever-evolving world of quality management certifications and assist you through these steps. Contact us today or fill out our RFQ form to find out how NSAI can help.

Satellite certification

ISO 9001 Quality Management System Registration and Certification Services

ISO 9001 is a globally known standard for Quality Management that over 1 million companies use. It was designed to give businesses the tools they need to succeed, like reducing costs and improving productivity. When you obtain an ISO 9001 QMS certification, your customers know they can always count on receiving high-quality products and services from you.

The ISO 9001:2015 standard not only promotes established quality management principles but also takes a closer look at customer focus. It examines the motivation of senior managers and how they develop policies for continual improvement. ISO 9001:2015 provides benefits for businesses that include consistent delivery of high-quality products and services to customers.

The act of continuously bettering your business makes it more adept, reduces mistakes, and keeps a high quality of service delivery. This will not only save you money but also help you meet many compliance standards. Not only is it good for your customers to always receive the products or services they desire, but operational efficiency can also lead to happier employees.

https://www.nsaiinc.com/services/qualitymanagement/iso-9001/

AQUILA specifications

Specification & Dimensions
Parameter Value
Input Range ±25 g
Bias <4 mg
One-Year Stability (3-sigma)

Temperature Sensitivity
<80 µg
<15 µg/°
Scale Factor 1.2 to 1.46 mA/g
One-Year Stability (3-sigma)
Temperature Sensitivity
<70 ppm
<120 ppm/ °C
Axis Misalignment <2,000 µrad
One-year Stability (3-sigma) <80 µra
Vibration Rectification <15 µg/g²RMS (DC-500 Hz
<40 µg/g²RMS (500-2000 Hz
Intrinsic Noise <7 µgRMS (0-10 Hz
<70 µgRMS (10-500 Hz
<1,500 µgRMS (500-10,000 HZ
Environment
Operating Temperature -55°C to +95°C
Shock (survival) 500 g
Vibration Peak Sine 15g @ 20 to 2,000 peak Hz
TiD 50krad
Resolution/Threshold <1 µg
Bandwidth >800 Hz
Temperature
Temperature Sensor Yes
Electrical
Quiescent Current per Supply <36 mA (-15V) & <36mA (+15V)
Quiescent Power @ ±15V DC <1.1 W
Electrical Interface Temp Sensor
Voltage Self Test
Current Self Test
Power/Signal Ground
Input Voltage ±13 to ±18 VDC
Physical
Weight 82.±4 g
Diameter - below mounting surface Ø 25.45 mm Max
Height - bottom to mounting surface 14.85 mm Max
Case Material 300 Series Stainless Steel

AQUILA Datasheet Space Quartz Accelerometer

General Description
AQUILA is a rad-hard Hi-Rel Accelerometer based on
InnaLabs® successful Quartz Pendulum accelerometer

products and heritage. As Europe's first designed and manufactured space-grade accelerometer, AQUILA provides high-performance in a space environment with radiations and single events. The primary applications of AQUILA are Navigation, Delta-V monitoring, Fault Detection Isolation and Recovery (FDIR), and Momentum and Vibration monitoring onboard satellites and spacecraft. AQUILA can also be used in land and aerospace applications where high-performance or radiation tolerance is required.

Principle of Operations

AQUILA is based on Quartz Pendulum accelerometer technology, which is well established for its high performance and use in space applications. AQUILA features an internal temperature sensor that allows the user to carry out temperature calibration and compensation, enhancing the bias, scale factor, and axis misalignment performance over temperature. State-of-the-art manufacturing processes enable InnaLabs® to offer AQUILA at a competitive price.

.

How to Order

AQUILA is available to order under the same name from InnaLabs® from our worldwide network of Agents and Distributors.

Note: AQUILA is still in development, so qualification and deliveries are expected no earlier than late 2022.

ARIETIS-NS

ARIETIS-NS is an ITAR free, space qualified, rad tolerant gyro. It uses automotive quality EEE components that are upscreened by means of radiation testing. ARIETIS-NS is intended for New Space applications, constellations and megaconstellations in both LEO and GEO and for a variety of applications, from Earth Observation to telecom and space exploration. ARIETIS-NS is developed and qualified as per a mix of ESA and IPC standards, allowing InnaLabs® to adapt to customer Product Assurance requirements. ARIETIS-NS Flight Models will be shipped starting in 2022.

Performance Parameters

Micro-thrusters in satellites

A Piezoelectric Actuator is a high-precision device that transforms electrical energy into mechanical displacement using piezoelectric materials. When voltage is applied, the piezo element expands or contracts at the microscopic level, producing fast, accurate, and controlled motion.

Unlike traditional electromagnetic actuators, piezo actuators offer extremely fine positioning, quick response times, and low power consumption, making them ideal for applications requiring micro- or nano-scale motion control.
Precision motion control-based applications.

Converts electrical signals into precise mechanical motion using piezo materials.
∆
∆ High resolution – capable of. ∆ Sub-micron to nanometer precision
∆ Fast response – operates in milliseconds or less
∆ Compact design – no gears or motors ∆ required
∆ No magnetic interference – suitable for sensitive environments
∆ Long cycle life – durable and maintenance-free

Analog Output Gyroscope

Innalabs www.innalabs.com
GI-CVG-U2x10A
Analogue Output Gyroscope
Datasheet
General description
The Innalabs 2000 Family of Gyroscopes is a < 10%hr range of tactical gyroscopes . Coming in a variety of form factors , the U2x00 group of parts is supplied with a rugged and hermetic housing , able to withstand the harshest environmental conditions .
The GI-CVG-U2x10A analogue output family is suitable for a range of applications . The tactical performance , very low noise and high MTBF , combined with the small size make this gyroscope family the ideal choice for platform stabilization .
Principles of Operation
Solid-state Coriolis Vibrating Gyros are based on the control of standing waves in a physical body , called a resonator (shown below , right) which is housed within a protective case (shown below , left) . The protective case which contains the resonator is called a Sensitive Element (SE) , and there is one such SE per axis in all INNALABS CVG gyroscopes .
The oscillations in the resonator are generated and detected by piezo-electric actuators , which are attached to the base of the resonator . A closed-loop electronic system is used to control the standing wave oscillation in the resonator , and to null the effects of Coriolis forces induced by the rotation of the resonator , providing as output a signal which is proportional to the gyroscope angular rate .
This electromechanical system is key to the very low output noise , and facilitates the large

dynamic range required in several demanding applications .
Features
In run Bias stability (room temperature) 0.03"/hr typical
Very low output noise (≤ 0.002 / s RMS @ 100 Hz)
Very High MTBF (500,000 hr)
Moderate bandwidth (2 25 Hz)
Robust (800 g shock)
Applications
The GI-CVG-U2x10A is particularly suited to the following applications :
North Finding Applications
Platform Stabilization of optical systems and payloads , or other sensitive systems on Airborne , Land-based or Marine platforms
Stabilization of Pointing and Directional systems
Rail-tilt compensation systems
Industrial control systems
How to order
The GI-CVG-U2x10A is available in 1-axis and 2-axis models , known as :
GI-CVG-U2110A-1 axis version
GI-CVG-U2210A-2 axis version
Related Products
Innalabs also offers a selection of accessories such as cables for use with the GI-CVG-U2x10A gyroscopes , which help bench and field-testing of these gyroscopes .
See our list of accessories f