## ① 当前作业

» 2023暑期 Python课第四次 课下测试

≫ 2023暑期Python课第三次课下测试

#### り 历史作业

» 2023暑期 Python课第四次 课上测试

» 2023暑期 Python课第三次 课上测试

» 2023暑期 Python课第二次 课下测试

» 2023暑期 Python课第二次 课上测试

» 2023暑期 Python课第一次 课下测试

≫ 2023暑期Python课第一次课上测试

# 2023暑期Python课第四次课上测试

作业时间: 2023-07-06 10:00:00 至 2023-07-06 11:30:00

不定项选择题,答案可能不止一个

● 选择题

1. 首次提交时间:2023-07-06 10:06:41 最后一次提交时间:2023-07-06 10:06:41

The output result of the following code is D

MA = lambda x,y: (x > y) \* x + (x < y) \* y

MI = lambda x,y: (x > y) \* y + (x < y) \* x

a = 10

b = 20

print(MA(a,b),MI(a,b))

A.10 20 B.20 20 C.10 10 D.20 10

2. 首次提交时间:2023-07-06 10:07:24 最后一次提交时间:2023-07-06 10:56:04

Which of the following options describes the correct statement about local variables and global variables? ABCD

A. Local variables are not released after the function operation ends.

B. If a local variable is an undefined composite data type, it is equivalent to a global variable.

C. Local variables act as placeholders within a function and may have the same name as global variables but are different.

D. Local variables and global variables are different, but the 'global' keyword can be used to access global variables within a function.

3. 首次提交时间:2023-07-06 10:08:41 最后一次提交时间:2023-07-06 10:08:41

The option among the following with a value of False is A

A. 'Hello' > 'hello'

B. 'abcd' <'ad'

C. ' ' <'a'

D. 'abc' <'abcd'

4. 首次提交时间:2023-07-06 10:08:49 最后一次提交时间:2023-07-06 10:08:49

The output result of the following code is D

def func(num):

num += 1

a = 10

func(a)

print(a)

A. 11

B. int

C. 出错

D. 10

5.	首次提交时间:2023-07-06 10:09:20 最后一次提交时间:2023-07-06 10:09:20
	The output result of the following code is C
	<pre>for s in "abc":     for i in range(3):         print (s,end="")         if s=="c":             break</pre>
	A. abbbccc B. aaabbbccc C. aaabbbc D. aaabccc
6.	首次提交时间:2023-07-06 10:10:42 最后一次提交时间:2023-07-06 10:10:42
	The option among the following that describes Python character encoding incorrectly is B.  A. print(ord('a')) outputs 97.  B. Python character encoding uses ASCII encoding.  C. print(chr(65)) outputs A  D. chr(x) and ord(x) functions are used for converting between single characters and Unicode code points.
7.	首次提交时间:2023-07-06 10:11:18 最后一次提交时间:2023-07-06 10:11:18
	The option among the following that allows access to the third character from the right to left in the string s is:  D  A. s[: -3]  B. s[3]  C. s[0: -3]  D. s[-3]
8.	首次提交时间:2023-07-06 10:11:52 最后一次提交时间:2023-07-06 10:11:52
	s = list("巴老爷有八十八棵芭蕉树,来了八十八个把式要在巴老爷八十八棵芭蕉树下住。\ 老爷拔了八十八棵芭蕉树,不让八十八个把式在八十八棵芭蕉树下住。八十八个把式\ 烧了八十八棵芭蕉树,巴老爷在八十八棵树边哭。")
	The option(s) among the following that can output the frequency of the character "人" is/are: B  A. print(s.index("人"),6,len(s))  B. print(s.count("人"))  C. print(s.index("人"),6)  D. print(s.index("人"))
9.	首次提交时间:2023-07-06 10:12:41 最后一次提交时间:2023-07-06 10:12:41
	The value of ls[2][ –1][1] in the following code is D
	Is = [3.5, "Python", [10, "LIST"], 3.6]
	A. Y B. L C. P D. I

10.	首次提交时间:2023-07-06 10:13:07 最后一次提交时间:2023-07-06 10:13:07		
	The option among the following that describes import statement incorrectly is		
	A. Using 'import turtle as t' to import the turtle library and alias it as t.		
	B. The 'import' keyword is used to import modules or objects from modules.		
	C. It is possible to use 'from turtle import' setup to import the turtle library.		
	D. Using 'import turtle' to import the turtle library.		
<b>♪ 填空题</b>			
1.	首次提交时间:2023-07-06 10:13:49 最后一次提交时间:2023-07-06 10:13:55	已提交	
	The constructor method is a special method of a class, and its method name isinit (with underscore)		
2.	首次提交时间:2023-07-06 10:14:04 最后一次提交时间:2023-07-06 10:14:05	已提交	
	The_str_ method of a class cannot have any additional parameters and must have a return value of typestr		
3.	首次提交时间:2023-07-06 10:16:26 最后一次提交时间:2023-07-06 10:16:27	已提交	
	The <u>isinstance</u> function can be used to test if an object is an instance of a class.		
4.	首次提交时间:2023-07-06 10:16:34 最后一次提交时间:2023-07-06 10:16:37	已提交	
	The object type returned by <i>readlines</i> function is a <u>list</u> . (string/list/tuple).		
5.	首次提交时间:2023-07-06 10:18:35 最后一次提交时间:2023-07-06 10:18:37	已提交	
	If the parameter dir_path is already an existing folder, the os.mkdir(dir_path) method will <u>raise an error</u> . (not do anything/raise an error/delete all files within the folder)		
6.	首次提交时间:2023-07-06 10:18:55 最后一次提交时间:2023-07-06 10:18:59	已提交	
	In the <i>os</i> library, the function name for getting the current directory is <u>getcwd</u> .		
7.	首次提交时间:2023-07-06 10:19:29 最后一次提交时间:2023-07-06 10:19:36	已提交	
	To open an existing file and append information to the end of the file, the appropriate opening mode is <u>'a'</u> ('a'/'r'/'w'/'x')		
8.	首次提交时间:2023-07-06 10:21:37 最后一次提交时间:2023-07-06 10:21:43	已提交	
	To open an existing file in binary mode, clear its contents, allow both reading and writing, and create the file if it doesn't exist, the appropriate opening mode is $\underline{\ \ \ \ \ \ \ \ \ \ \ \ \ \ }$ . (with single quotation marks)		
9.	首次提交时间:2023-07-06 10:21:53 最后一次提交时间:2023-07-06 10:21:54	已提交	
	Python uses the keyword <u>class</u> to define a class.		
10.	首次提交时间:2023-07-06 10:22:08 最后一次提交时间:2023-07-06 10:22:11	已提交	
	In Python, to close a file object named $f$ , the statement $\underline{f.close()}$ should be used.(Complete statement)		



# 计算机专业课程一体化支撑平台

北京航空航天大学教学成果转化平台

©<u>阔思格睿网络科技(北京)有限责任公司</u> | <u>郑州云海科技有限公司</u>

### 快速导航

♣ QQ学生用户群 328666683

答疑社区

忘记密码

希冀学知桥实训平台

系统能力培养-编译系统赛官网

系统能力培养-操作系统赛官网

#### 公众号与微博



