

1. MATL: POLYPROPYLENE OR POLYETHYLENE
2. BREAK (.03 MAX) AND DEBURR ALL SHARP EDGES.
3. FINISH: NONE.



Confidential information of Optima Batteries, Inc. (Optima) this document, and the information and designs set forth herein, is the exclusive property of Optima and contains confidential information and trade secrets of Optima. This document may not be copied, nor the information contained herein be used or disclosed, except with Optima's prior written consent. Acceptance of this document evidences recipient's agreement to the terms set forth herein.

| | | | | |
|--|--|------------------------|--|------------|
| DO NOT SCALE DRAWING | | THIRD ANGLE PROJECTION | DIMENSIONS ARE IN INCHES MILLIMETERS | |
| NOTICE: THIS DRAWING IS FURNISHED FOR REFERENCE ONLY. THE FURNISHING OR ANY REPRODUCTIONS THEREOF, DOES NOT CONVEY ANY MANUFACTURING RIGHTS. | | | UNLESS OTHERWISE SPECIFIED, TOLERANCE ARE: ONE PLACE ± 0.1 TWO PLACE ± 0.01 THREE PLACE ± 0.005 ANGLES ± 0.5 SCREW THREADS SHALL PROVIDE 70-78% OF FULL THREADS. | |
| TITLE PASTE MIX | | | FILE DIVISION | ASSY DWG |
| COMPONENT SCRAPER | | | PASTE MIX | A2299M0100 |
| MATERIAL NOTED | | | ITEM/SHEET | OF |
| | | | 1 | 1 |
| SCALE 1:1 REF INFO X | | | DWG NO | REV |
| DWR W.R.LLEWELIN DATE 5/12/06 | | | JOHNSON A2299M0013 | B |
| | | | CONTROLS | |

JOHNSON
CONTROLS