

MATERIAL QTY: 2.62 LIQUID CARBURIZE & HARDEN 0.5mm TO 2.0mm DEEP ROCKWELL "C" 58-62

STK: 1 1/2" DIA X 66.5MM (2.62")

MATERIAL: 8620R-01500

HARDEN & TEMPER Rc 58-62

AND GRIND

SAE 8620

THIS DRAWING MAY USE BOTH INCH AND METRIC
UNITS OF MEASUREMENT
('INDICATES INCH DIMENSIONS)

MAXIMUM ALLOWANCE ROUGHNESS OF ALL
METRIC.
1 PLACE mm FINISH DIMENSIONS TO BE 3.2 MICRONS
2 PLACE mm FINISH DIMENSIONS TO BE 1.6 MICRONS
3 PLACE mm FINISH DIMENSIONS TO BE 0.5 MICRONS
ALL GROUND SURFACES TO BE 0.4 MICRONS.
ALL GROUND SURFACES TO BE 0.4 MICRONS.
METRIC - EXCEPT AS NOTED TOLERANCES SHALL BE:
1 PLACE MACHINING '0.3
1 PLACE FABRICATION '1.5
2 PLACE '0.08 BETWEEN MACHINED SURFACES
'0.10 BETWEEN DOWELS IN THE SAME PLANE
'0.10 BETWEEN DOWELS IN THE SAME PLANE
'0.10 BETWEEN DOWELS IN THE SAME PLANE
'0.10 BETWEEN DOWELS IN DIFFERENT PLANES
'0.13 TO SCREW HOLES, NON ACCUMULATIVE
ALL O SURFACES MUST BE FINISHED EXCEPT FOR COLD
DRAWN SURFACES.

WELDMENTS.

PT FOR COLD

PT FOR COLD

SON.

OWN.

ERE TRAPPED AT

WHEN

IEAD AND / OR

IEAD S.

SON LOCATING

1/3.00 mm

ACCURACY OF

N.

DOWEL TOLERANCE

m6 WELDMENTS.
ALL WELD FILLETS TO BE 1/4 INCH.
ALL "V" GROOVES TO BE 90 EXCEPT AS SHOWN. ADD VENT HOLES IN ALL WELDMENTS WHERE TRAPPED AIR IS A POSSIBILITY, I.E. TUBING CAPPED AT BOTH ENDS. BOXED FORMS ETC SPOTFACE SCREW AND / OR BOLT HOLES WHEN CLEARANCE FOR SCREW AND / OR BOLT HEAD AND / OR

ALL EDGES OF PART CONTACT SURFACES ON LOCATING BLOCKS AND FINGERS TO HAVE .12R INCH / 3.00 mm AFTER SPOTTING.

WASHERS IS INFRINGED UPON BY WELD BEADS.

BUILD VENDOR TO BE RESPONSIBLE FOR ACCURACY OF STANDARD PRODUCTS AFTER ALTERATION.

DOWEL HOLE TOLERANCES FOR PRESS FIT USE H6 FOR SLIP FIT USE F7

- Front, RR Rails

MARK INDENTIFICATION AND MATERIAL NUMBERS ON DETAILS. PAINT INDENTIFICATION NUMBERS ON STRUCTURAL WORK.



DRAWING

A-DT1-M420-U11

3rd ANGLE PROJECTION


OP #420 **UNIT #11**

SHT 1 OF 1 SHTS SHOWN ON: DET BY DES BY **RVS** GJS SAFETY OK **RMB**

LOCATING PIN

DRAWING NO. OR TOOL NO.:
A-DT1-M420-U11-D14-PS **DIVISION: AUTOMOTIVE**

PLANT: METALSA LOCATION: APODACA, N.L. MEXIÇO



M000034230

SAFETY ORANGE PAINT X NO PAINT **BLACK OXIDE**

JOB #15143