NAME DATE TIME	(HRS)				
	3.000 —	2 v	Ø 0.354 THRU A	\LL 3.000 — □	
ZX & 0.354 TINO ALL					
	2.250				
			$ ot\supset$ 0.354 THRU A		
	1.135		√ Ø 0.681 X 9	<u>0°</u> 1.425	
	1		d 0 10 =		
	.500		Ø0.197 THRU		
	0 —			2 <u>50</u> 0 – –	
	0.882	30			
	Ŏ.	2.082		0 .250	1.250
	٦			· · · · · · · · · · · · · · · · · · ·	~;
				PAG. 1 de 1	
				■ MEDIDA ESPECIAL	ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER MANUFACTURER, PROCUREMENT OR DISCLOSURE WITHOUT WRITTEN PERMISSION OF THE OWNMER.
QUALITY	NOTES:	TOTAL OF 1 Pza.	UNLESS OTHERWISE SPECIFIED		JOYSON TECHNICAL CENTER
	Pieza libre de filos y rebabas.	PIECES I PZG.	TOLERANCES ISO 2768-1 mK-E DIMENSIONS ASME Y14.5M-1994	JOYSON SAFETY SYSTEMS	MODEL NAME: RB001-AC SERIES NO M2021-093
			MM INCHES ANGLES +.11 +.004004 +1 °-1 °		MACHINE NAME: REMACHADO BRACKET
			MATERIAL: 6061 Alloy	DESIGNER VHGS 25/08/2021	PART NUMBER: RB001-AC-211
	REV DESCRIPTION	DATE APPROVED	SURFACE TREATMENT: POLISHED	PENIEW	SIZE PART NAME PART 211 REV.
AUTHORIZE TALLER	REVIEWS		HARDNESS: N.A.	JATA 25/08/2021	ESCALE 1:2 DRAWING IN INCHES