NAME	DATE TIME	(HRS)						
					ſ	$\langle \phi \rangle$		
							O-	
	_	_					$\sim$	
	17.51	a x 💝 o an THRU A	A I					
0.50 \	/ 150 C	₹8 x ♥ 0.00 THRU A 10.00 THRU A	\ \				$\sim \gamma \zeta$	
0.50 >	(45)	J. J. J. H. H. G.	<u> </u>					
			10.00					
			_					
		<del>      -   -                            </del>	)					
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	10.00					
	ΙΨ	$\Psi \Psi = \Psi = \Psi$	10.00					
		49.00		01.75				
	-	.53	-	31.75				
		9.6		10.00				
		1						
$4 \times \emptyset 4.20 \ \overline{\lor} 12.40$								
$M5x0.8 - 6H \sqrt{10.00}$								
7VI3X0.0 - 011 \$\psi\$ 10.00								
						PAG.1de1	ALL TECHNICAL DATA DISCLOSED II	EDE IN IS THE PROPERTY OF
					E MEDIDA ES		ALL TECHNICAL DATA DISCLOSED H JOYSON SAFETY SYSTEMS AND SHA MANUFACTURER, PROCUREMENT O PERMISSION OF THE OWNMER.	LL NOT BE USED BY ANY OTHER R DISCLOSURE WITHOUT WRITTEN
QUALITY		NOTES: TOTAL OF PIECES 1 Pza.		UNLESS OTHERWISE SPECIFIED			JOYSON TECHNICAL CENTER	
		Pieza libre de filos y rebabas.	ANG. PRO	TOLERANCES ISO 2768-1 mK-E DIMENSIONS ASME Y14.5M-1994	JOYSON SAFETY SYSTEMS		MODEL NAME:	SERIES No
				MM INCHES ANGLES +.11 +.004004 +1 °-1 °		٨	MACHINE NAME:	
				material: 6061 Aluminium	DESIGNER LGG		PART NUMBER: FSR001-TRN-2	
		REV DESCRIPTION	DATE APPROVED	SURFACE TREATMENT: Pulido	DED/IEW/	'	SIZE PART NAME	REV.
AUTHORIZE	TALLER	REVIEWS		HARDNESS: N.A.	KVM	20/01/2022	ESCALE 1:1 DRAWING	G IN MILLIMETERS