

DELY DESCRIPTION DATE ADDROVED TREATMENT:																		
A3 10 550 A3 10 10 50 A3 10 10 50 A3 10 10 10 A4 10 10 50 A3 10 10 10 A4 10 10 50 A4 10 50	NAME DATE	TIME (HRS)	T	TAG X LC		Y LOC		SIZE										
## A				A1	20	170												
Add 1921 292				A2	20	530												
AS 903 20 AS 1903 170 AS 695 170 AS 69				A3	60	680												
AS Color AS A		Y 6.50 IRRO ALL							ALL									
A7 5.90 170		·	·	A5	600	20		☐ Ø 13.50 ▼ 8.50										
AB 460 532 B1 129:99 603 B1 129:99 605 B1 120:99 605 B1 120:96 605 B1 120:96 605 B1 34:10 605 B1 350:19 605 B1 36:19 605 B1 460 505 B1 160 605 C2 150 60 C3 550 60 C4 450 HBU ALL C4 550 60 C5 150 60 C4 450 HBU ALL C4 550 60 C5 150 60 C7 150 6				A6	640	680												
B 1/9% 99			_															
S2 122-97 440 A1 170 460 A2 170 460 A3 170 460 A5 30.17 400 A6 30.17 400 B6 30.17 400 B7 40.17 400 B8 400.17 460 B9 970.27 400 B10 463 500 B11 440 400 B12 455 570 B13 455 570 B14 400 400 C2 150 460 C3 150 460 C4 150 460 C4 150 460 C5 150 460 C4 150 460 C5 150 460 C6 150 460 C7 150 460 C8 23 180 B1 221 231 355.50 B1 221 231 355.50 B1 222 231 355.50 C3 30 470 C4 30 480 C5 37 40 C6 37 40 C7 37 40 C8 40 40 C9 37 180 A1 C9 37 180 A1 C9 37 180 A1 C9 37 180 A1 C9 37 40 C9 37 C9				A8	680	530												
S				B1	129.99	600												
## 2010																		
BS 380.19 480 B8 420.19 440 B8 420.19 440 B9 450.27 420 B10 450.34 550 B11 440 450 B12 455 270 B13 450 2			_			_	_											
84 380.19 600 87 420.119 600 89 420.19 640 89 570.72 620 810 665.36 540 811 640 420 812 6455 270 813 655 310 C1 130 80 C2 150 480 C2 150 480 C3 550 490 C4 550 THRU ALL C3 550 490 C4 550 THRU ALL C3 550 490 C4 550 THRU ALL C4 550 490 C5 550 490 C6 450 THRU ALL C6 550 490 C7 550 480 C8 650 THRU ALL C9 751 THRU E1 231 519-50 E2 231 539-50 E3 493 535.50 C9 3.30 THRU E1 231 519-50 E3 493 535.50 C1 340.00 400 C4 550 THRU ALL E4 493 353.50 C6 450 THRU ALL E4 493 535.50 C7 5780 THRU ALL E4 493 535.50 C7 5780 THRU C7 5780 THRU C8 5780 THRU ALL C9 7580 T							_											
## 450.19				_			_											
## 420.19						-	\dashv	Ø 6 80 THRU AU										
B9 \$70.72 620 B10 605.36 500 B11 640 620 B12 655 270 B13 655 270 B14 605 605 C2 150 490 C3 550 80 C4 550 490 D1 220 584 Ø25 THRU E1 231 519-50 E2 231 519-50 E2 231 519-50 E2 231 519-50 E3 493 519-50 E4 493 535-50 F1 376 615 F2 320 415 G3 347-36 615 G4 475 353-50 F1 376 615 G1 342-06 540 G2 357-94 540 M6d1 0 - 6H THRU ALL PAG, 7 de 2 WEDIDA ESPECIAL PAG, 7 de 2 WEDIDA ESPECIAL			-				_	M8×	(1.25 - 6H TF	IRU ALL								
## BIO 605.36 560 ## BII 640 620 ## BI3 655 270 ## BI3 655 310 ## CC 150 480 ## CC 2 150 480 ## CC 3 550 80 ## CC 4 550 480 ## CC 5 550 480 ## CC 4 550 480 ## CC 5 550 480 ## CC 5 550 480 ## CC 6 55			_				_											
B11 640 620 B12 655 270 B13 655 310 C1 150 80 C2 150 480 C4 550 480 C4 550 480 D1 220 584 0/25 THRU E1 221 519-50 E2 231 535-50 0/3 3.0 THRU ALL E3 493 515-50 0/3 3.50 THRU ALL E4 493 535-50 0/3 3.0 THRU ALL E4 493 535-50 0/3 3.0 THRU ALL E5 493 535-50 0/3 3.0 THRU ALL E6 493 535-50 0/3 3.0 THRU ALL E7 500 615 0/3 81.0 THRU ALL F2 500 615 0/3 81.0 THRU ALL G1 342.66 540 0/3 5 THRU ALL G2 357.94 540 0/45.7 6H THRU ALL D10/24 54 0/45.7 6H THRU ALL D20/25 0/25 THRU ALL D20/25							\dashv											
S12 655 270 B13 655 310 C1 150 80 C2 150 480 C3 550 80 D1 230 584 Ø 25THRU E1 231 519:50 E2 231 535:50 Ø 3.20 THRU ALL E3 493 519:50 E4 493 535:50 F1 304 615 F2 520 615 Ø 38.10 THRU ALL G3 347:20 544 Ø 5 THRU ALL F2 520 615 Ø 38.10 THRU ALL F2 520 615 Ø 38.10 THRU ALL F3 347:20 544 Ø 5 THRU ALL F4 548 648 Ø 5 THRU ALL F4 548 648 Ø 5 THRU ALL F4 548 Ø 5 THRU ALL F5 548 Ø 5 THRU ALL F6 548 Ø 5 THRU ALL F7 548 Ø 5 THRU ALL F8 548 Ø 5 THRU ALL							-											
B13 655 310 C1 150 80 C2 150 480 C4 550 480 D1 230 584 D1 230 584 D1 230 584 D1 230 584 D1 230 585 E1 231 515.50 E2 231 535.50 E3 493 519.50 E4 493 535.50 E4 493 535.50 E5 520 415 C3 357.94 540 D1 20 38.10 THRU ALL B1 326 415 D1 326 415 D1 327 590 415 D1 328 415 D1 328 519.50 D1 3			_				-											
C1 150 80							\dashv											
C2 150 480 C3 550 80 C4 550 480 D1 230 584 Ø 25 THRU E1 231 519.50 E2 231 555.50 E3 493 535.50 E4 493 535.50 E5 493 535.50 F1 326 615 F1 326 615 G1 342.06 540 G2 357.94 540 F1 5074.07 6H THRU ALL MANUAL M																		
C3 550 80 C4 550 480 D1 230 584 E1 231 519.50 E2 231 535.50 M 3.30 THRU ALL E3 493 519.50 F1 326 615 F1 326 615 G1 342.06 540 G2 357.94 540 NOTES: Pleza libre de fitos y rebadas. PAG. 2 de 2 I CIAL OF PAG. 3 de 2 I MEDIDA ESPECIAL PAG. 2 de 2 ALL TITCHICAL DATA DISCLOSS HERE IN IS THE ROPERTY OF PROVINGENT			-				_											
C4 550 480 D1 230 594 Ø25THRU			_				_	Ø 6.50 THRU ALL										
E1 231 519,50 E2 231 535,50 M 3.30 THRU ALL MMx0.7 - 6H THRU ALL E3 493 535.50 E4 493 535.50 E1 326 615 F2 520 615 G1 342.06 540 G2 357.94 540 NOTES: Pleza libre de filos y rebabas. Pleza			_		550	480												
PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PROCURS PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMILISSION OF THE OWNARD. PAG. 2 de				D1	230	584			Ø 25 THR	J								
PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN 5 THE PROPERTY OF MANUFACTURER, PROCURSE WITHOUT WHITT FEMINSION OF THE OWNER.				E1	231	519.50												
STATE STAT				E2			=	ϕ 3.30 THRU ALL M4x0.7 - 6H THRU ALL										
F1 326 615 Ø38.10 THRU						-	\dashv											
F2 520 615 Ø38,10 THRU				E4	493													
GUALITY PAG. 2 de 2 WEDIDA ESPECIAL NOTES: Pieza libre de filos y rebabas. TOTAL OF PZO. ANG. PRO UNLESS OTHERWISE SPECIFIED TOLERANCES ISO 27.88-1 m.K.E. DIMENSIONS ASME Y14.5M-1994 ANG. PRO UNLESS OTHERWISE SPECIFIED TOLERANCES ISO 27.88-1 m.K.E. DIMENSIONS ASME Y14.5M-1994 ANG. PRO WALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF MANUFACTURER, PROCUREARIN AND STALE WAS OTHER WAS AND THE WAS OFTEN THE WAS ON THE WHITE AND THE WAS OFTEN THE W				F1	326	615												
GI 342.06 540 Ø 5 THRU ALL G2 357.94 540 M6x1.0 - 6H THRU ALL PAG, 2 de 2 MEDIDA ESPECIAL NOTES: Pieza libre de filos y rebabas. DIJENENSIONS ASME 114.5M-1994 MM INCHES ANGLES LI-1 LI-1 +.004-0.004 +1-1 LI-1 +.004-0.004 +1-1 MARIAN: DESIGNER DESIGNER DESIGNER DESIGNER PART NUMBER: DESIGNER PART				F2	520	615	\dashv	Ø38.10 THRU										
QUALITY PAG. 2 de 2 ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER MANUFACTURER, PROCUREMENT OR DISCLOSURE WITHOUT WRITT PERMISSION OF THE OWNER OWNER OF THE OWNER OWN				G1	342.06	540		Ø 5 THRII ALL										
NOTES: Pieza libre de filos y rebabas. NOTES: Pieza libre de filos y rebabas. TOTAL OF PZA. UNLESS OTHERWISE SPECIFIED TOLERANCES ISO 2768-1 mK-E DIMENSIONS ASME Y14.5M-1994				G2	357.94	540	\dashv	M6x1.0 - 6H THRU ALL										
NOTES: Pieza libre de filos y rebabas. TOTAL OF PIECES ANG, PRO TOTA	QUALITY		_	•							E MEDII		ALL TECHNIC JOYSON SAF MANUFACTU PERMISSION	AL DATA DISC TY SYSTEMS A RER, PROCURE OF THE OWNM	LOSED HERE II AND SHALL NO MENT OR DISC ER,	N IS THE PROF OT BE USED BY CLOSURE WITI	PERTY OF Y ANY OTHE HOUT WRITT	EN
MATERIAL: DESIGNER DESIG							Pza.	UNLESS OTHE	UNLESS OTHERWISE SPECIFIED		_		JOYSON TECHNICAL CENTER					
MATERIAL: DESIGNER DESIG	RUBA	Pieza	libre de filos y	rebabas	S.			TOLERANCE	S ISO 2768-1 mK-E S ASME Y14.5M-1994		ال (((OYSON						_
MATERIAL: DESIGNER DESIG	A O					ANG. PRO	\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	7			SAFETY SYSTEMS							_
DESIGNER 28/04/2022 SIZE PART NAME POTO DESIGNER 28/04/2022 SIZE PART NAME POTO DESIGNER 28/04/2022 SIZE PART NAME								+.11	+.004004		- APPROVALS	DATE			Lover & Sw	itches Scre	w #2	_
DEV DESCRIPTION DATE ADDROVED DATE ADDROVE	M										DESIGNER	28/04/2022		001)E: /
DEVICEM A		REV	REV DESCRIPTION			DATE APPROVED		SURFACE TREATMENT:			DEVIEW			ME	BCS003-P1	-001		REV.
AUTHORIZE TALLER REVIEWS HARDNESS: REVIEW MA 28/04/2022 ESCALE 1:10 DRAWING IN MILLIMETERS	AUTHORIZE TALLER				REVIEWS			HARDNESS:			MA MA	28/04/2022		1:10 DI	RAWING IN	MILL	LIMETERS	