



CHANGE CHK'D DATE REV









SAE 8620 STK: 7/8" DIA X 87MM (3.43") MATERIAL: 8620R-00875 MATERIAL QTY: 3.43

NOTE:

ALL MACHINED SURFACES TO BE FLAT, PARALLEL AND PERPENDICULAR TO WITHIN 0.015 T.I.R. TO DATUMS A AND B AND CONCENTRIC TO WITHIN 0.03 T.I.R.

LIQUID CARBURIZE & HARDEN 0.5mm TO 2.0mm DEEP ROCKWELL "C" 58-62 AND GRIND

THIS DRAWING MAY USE BOTH INCH AND METRIC UNITS OF MEASUREMENT (\*INDICATES INCH DIMENSIONS)

MAXIMUM ALLOWANCE ROUGHNESS OF ALL

METRIC. 1 PLACE mm FINISH DIMENSIONS TO BE 3.2 MICRONS 2 PLACE mm FINISH DIMENSIONS TO BE 1.6 MICRONS 3 PLACE mm FINISH DIMENSIONS TO BE 0.5 MICRONS

ALL GROUND SURFACES TO BE 0.4 MICRONS. METRIC - EXCEPT AS NOTED TOLERANCES SHALL BE 1 PLACE MACHINING `0.3

1 PLACE MACHINING 0.3
1 PLACE FABRICATION '1.5
2 PLACE '0.08 BETWEEN MACHINED SURFACES
0.03 BETWEEN SINGLE DOWEL AND A HEEL SURFACE
'0.03 BETWEEN DOWELS IN THE SAME PLANE
0.10 BETWEEN DOWELS IN DIFFERENT PLANES

10.13 TO SCREW HOLES, NON ACCUMULATIVE

ALL O SURFACES MUST BE FINISHED EXCEPT FOR COLD DRAWN SURFACES.

WELDMENTS.
ALL WELD FILLETS TO BE 1/4 INCH.
ALL "V" GROOVES TO BE 90 EXCEPT AS SHOWN.
ADD VENT HOLES IN ALL WELDMENTS WHERE TRAPPED AIR IS A POSSIBILITY, I.E. TUBING CAPPED AT BOTH ENDS, BOXED FORMS ETC.

SPOTFACE SCREW AND / OR BOLT HOLES WHEN
CLEARANCE FOR SCREW AND / OR BOLT HEAD AND / OR

WASHERS IS INFRINGED UPON BY WELD BEADS.

ALL EDGES OF PART CONTACT SURFACES ON LOCATING BLOCKS AND FINGERS TO HAVE .12R INCH / 3.00 mm AFTER SPOTTING.

BUILD VENDOR TO BE RESPONSIBLE FOR ACCURACY OF STANDARD PRODUCTS AFTER ALTERATION.

FOR PRESS FIT USE H6 FOR SLIP FIT USE F7

DOWEL TOLERANCE

MARK INDENTIFICATION AND MATERIAL NUMBERS ON DETAILS. PAINT INDENTIFICATION NUMBERS ON STRUCTURAL WORK.



DRAWING

A-DT1-M425-U02

3rd ANGLE PROJECTION

#MH3-425 **UNIT # 02** 

SHT 1 OF 1 SHTS SHOWN ON: DET BY S.J.E. K.R.M. CHK BY SAFETY OK DATE

**LOCATING PIN** 

DRAWING NO. OR TOOL NO.: A-DT1-MH425-U02-D17-PS.000

DIVISION: AUTOMOTIVE 1/2 LOCATION: APODACA, N.L. MEXICO



**PAINT** X NO PAINT **BLACK OXIDE** 

SAFETY ORANGE

JOB #15143 06/20/16