

D3

H1


NOTES:

- F
- DIMENSIONS APPLY BEFORE FINISH.
 - NON-VISUAL SURFACE = INNER WALLS.
 - PAINT PER ENGINEERING STANDARD 10-4.
- G1
- REPLACE (X) IN PART NUMBER WITH "5" FOR PAINTED.
- G2
- REPLACE (#)IN PART NUMBER WITH (APPLICABLE ONLY WITH PAINTED PARTS) COLOR CODE, PER DRAWING 3310896.000.

TOLERANCES UNLESS
OTHERWISE NOTED:
.XX: ±.03 [.76]
.XXX: ±.005 [.127]
ANGULAR: ±1°

| ECN NO. | LET. | BY | DATE | REVISIONS |
|---------|------|-----|---------|---|
| CONT. | - | - | - | COLOR OPTIONS |
| 12213 | H | HJS | 5-10-11 | J1-DEL NOTE 5.PANTONE COLORS, J2-ADD TOLERANCE BLOCK, J4-BLOCK |
| | | | | NAME WAS: ARM, SUPPORT |
| 12213A | J | HJS | 5-12-11 | J1-ADD MATERIAL P/N, J2-REV H |
| | | | | NOTES SHOULD HAVE BEEN H NOT J |
| | | | | J3-REDRAWN IN SOLIDWORKS |

| DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ASME Y14.5M-1994 | | | | |
|--|--|---|---------|--|
| C SIZE | REFER TO DOMETIC QUALITY DESIGNATION STD. 12-50 | UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] | | |
| ECN NO. | LET. | BY | DATE | REVISIONS |
| 8-4947 | D | MM | 10-4-96 | D1- REMOVED EXTRUSION INFO, D2- REMOVED REFERENCES TO CHROME. |
| | | | | NOTE 2 WAS NOTE 3, D3-ADDED VIEW |
| 8-5130 | E | MS | 8-8-97 | ADD MENDE POLAR WHITE (H) |
| 8-5282 | F | MS | 1-30-98 | REVISED NOTES PER ENG STD 10-4 |
| 8-5465 | G | BKD | 3-15-99 | G1-REMOVED "0 FOR SATIN" FROM |
| | | | | NOTE 4, G2-ADDED S = SATIN TO |

| DO NOT SCALE DRAWING | | | |
|---|-----------------|--------------------------------|-----------------------|
|  | | | |
| NAME: ARM, OUTER | | | |
| MATERIAL: 3107376.XXX | | | |
| DRAWN: MM | DATE: 8-9-90 | CHECKED CJ | CHECK DATE 5-12-11 |
| SCALE 1:1 | | PART NUMBER 730468.(X)01(#) | |

PROPRIETARY ITEM: EXCEPT FOR USES EXPRESSLY GRANTED IN WRITING, INFORMATION DISCLOSED HEREIN IS CONFIDENTIAL AND ALL RIGHTS, PATENTS, AND OTHERWISE ARE RESERVED BY THE DOMETIC, LLC. ANY CHANGES TO METHOD AND/OR PROCESS USED TO PRODUCE THIS PART UNDER PURCHASE AGREEMENT REQUIRE EVIDENCE OF CONFORMANCE TO DRAWING SPECIFICATIONS AND MUST BE RE-APPROVED BY DOMETIC ENGINEERING PERSONNEL.

