



ELASTOMER LINING	MATL. CODE
NATURAL RUBBER	R00
NEOPRENE	S40
BROMO BUTYL	S20

- NOTE: 1. ALL CAST RADII TO BE R6 UNLESS OTHERWISE SPECIFIED.
2. REMOVE ALL BURRS AND SHARP EDGES.
3. EXTERNAL SURFACES TO BE RUBBER LINED 6mm THICK UNLESS OTHERWISE SPECIFIED.

MATERIAL: WARMAN CODE D21 UNLESS OTHERWISE SPECIFIED.  
ELASTOMER LINING - REFER TO TABLE

ESTIMATED MASS: 6,0 Kg METAL - D21  
0,7 Kg ELASTOMER  
6,6 Kg TOTAL

ENCUMBRANCE: 493 x 184 x 76

FOR LIMITS OF UNTOLERANCED DIMENSIONS REFER TO DRG. A4-15895.				PRODUCT	
				<b>ISOGATE®</b>	
OFFICE OF ORIGIN : AUSTRALIAN ENGINEERING SYDNEY				Slurry Valves	
Copyright © Weir Minerals Australia Ltd. 2013 Weir Minerals Australia Ltd ("the Company") is the owner of the copyright and all confidential information in this drawing. The drawing must not be copied in whole or in part, in any form or by any means, and the information in it must not be disclosed to any person, or used for any purpose other than the specific purpose for which it has been provided, without the prior written consent of the Company.				<b>WEIR</b> MINERALS	
SCALE: 1:2 APP: A.MCLEAN CHK: T.CHAMPION				TITLE : 200 NB AUTOBALL VALVE GUIDE RAIL AB200-05***	
DRAWING No				REV	
A2-170-0-506332				1	

4											
3											
2											
1	NEW TEMPLATE ADDED, DRAWING NO. CHANGED AND REVISED.	HP	JAN.28.2013	SM	DRN: B.CARRICK						
REV	DESCRIPTION	BY	DATE	CHK	DATE: JUL.11.2003						