



NOTE : 1. SCREW THREAD TOLERANCES TO AS1275-1972

2. AFTER INSPECTION ZINC PLATE TO DRG. A4-110078

4. EACH SCREW MUST BE SUPPLIED WITH 3 THIN NUTS AND 2 WASHERS

4. FOR NUT DETAILS SEE DRG. A4-126939. FOR WASHER DETAILS SEE DRG. ESY7497

5. BOLT HEADS ARE TO AS1111-1972

MATERIAL : WARMAN CODE E62 UNLESS OTHERWISE SPECIFIED.

[illegible]

FOR LIMITS OF UNTOLERANCED DIMENSIONS REFER TO DRG. A4-15895.

© WARMAN INTERNATIONAL LTD. 1992. WARMAN INTERNATIONAL LTD. is the owner of the copyright subsisting in this drawing and these designs, specifications and instructions. They must not be used, reproduced or copied in whole or in part, in any form or by any means, nor may the information therein contained, which is confidential to WARMAN INTERNATIONAL LTD. be disclosed to any person, without the written authority of WARMAN INTERNATIONAL LTD. The drawing has been delivered and received on the express conditions that it may be used only for the specific purpose for which it has been provided, must not be used in any way which may injure or cause loss directly or indirectly to WARMAN INTERNATIONAL LTD. or any related corporation and will be returned to WARMAN INTERNATIONAL LTD. immediately on completion of the task for which it has been provided, or on demand.

Warner CAE-CAD-CAM

OFFICE OF ORIGIN : SYDNEY

WARMAN INTERNATIONAL LTD.

REV	3					WARMAN PUMP		
	2					ADJUSTING SCREW *001XLM		
	1	ADDED C001XLM.	ROH	DEC.9,1996	JA			
DATE	JUL.28,1992	DRN.	1992		BY	DATE	CHK	A4-110-0-126938
SCALE	———	CHKD						
								REV 1