NAME	DATE	TIME (HRS)								
			11.000					, ,	— 1	200
			11.000 🔽					$6 \times 9 \times 0.2$	266 ↓ 1.0	<u> </u>
			9.500							
			7.500	li			i l			
			F F00							
			5.500	1	ı.		.⊕.			
			1.500		14					
			T				J			
			0 –							Ĭ
				•						0.250
				0	0		000			<b>→</b>   <
				0	)2		8.250			
					Ö		$\infty$			
									10 PAG. 1 de 1	ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER
QUALITY								E MEDI	DA ESPECIAL	ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER MANUFACTURER, PROCUREMENT OR DISCLOSURE WITHOUT WRITTEN PERMISSION OF THE OWNMER.
		NOTES:	NOTES: Pieza libre de filos y rebabas.		1 Pzas.	UNLESS OTHE	RWISE SPECIFIED			JOYSON TECHNICAL CENTER
		rieza ilbre			<ul><li>→ -□</li></ul>	TOLERANCES ISO 2768-1 mK-E DIMENSIONS ASME Y14.5M-1994		JOYSON SAFETY SYSTEMS		MODEL NAME: VRSMR001 SERIES NO: M2022-024R
						MM INCHES A	INCHES ANGLES	SAF	ETY SYSTEMS	MACHINE NAME
						$\overline{}$	+.004004 +1 °-1 ° DLICARBONATO	APPROVALS	DATE	RETURN SPRING MACHINE REFURBISH
						SURFACE N		DESIGNER VHG:	S 24/MAR/2022	PART NUMBER: VRSMR001-P2-110 SIZE PART NAME REV.
		REV	DESCRIPTION	DATE	APPROVED	HAPDNESS		REVIEW		A PART 110
AUTHORIZE	TALLER		REVIEWS			N.	Α.	JATA	24/MAR/2022	ESCALE 1:5 <b>DRAWING IN</b> INCHES