| NAME | DATE | TIME (HRS) | | | | |
|--|--------|---|----------------------|-------------------------------|----------------------|--|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | 1 | | |
| 4.71 | | | | | | |
| ϕ 4.76 | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| ϕ 7.62 | | | | | | |
| | | | | | | |
| | | | | 1 | | |
| | | | 4 | 2 | 0.02 | |
| | | | | | | |
| 1400 | | | | | | |
| 14.02 | | | | | | |
| 13 | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | <u> </u> | 0 | | |
| | | | | | | |
| 0.51 X 45° | | | | | | |
| | | 0 | | 0.5 | ΙΛ 43 | |
| | | 0 Ø 4.76 -0.0 | 03 | | | |
| | | | <u> </u> | | | |
| | | | | | | |
| | | | | | PAG. 1 de | 1 LILL TECHNICAL DATA DISCLOSED WITH THE PARTY OF |
| | | | | | | JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER |
| QUALITY | | | | | MEDIDA ESPECIAL | PERMISSION OF THE OWNMER. |
| MOSYOL | | NOTES: Pieza libre de filos y rebabas. | TOTAL OF PIECES 2 PZ | I. UNLESS OTHERWISE SPECIFIED | | JOYSON TECHNICAL CENTER |
| | | | | TOLERANCES ISO 2768-1 mK-F | MOSYOL (| |
| EQUIPO AUTOMOTRIZ AMERICANA 8.A. DE C.V. | | | ANG. PRO 🛑 🗕 | MM INCHES ANGLES | SAFETY SYSTEMS | MODEL NAME: TOQ008-MVA SERIES No M2022-004 |
| BOLSAS DE AIRE | | | | +.11 +.004004 +1°-1° | APPROVALS DATE | MACHINE NAME: QCF Tooling VOLVO |
| NOMBRE: RM | | | | MATERIAL: 4140 T | DESIGNER | PART NUMBER: TOQ008-MVA-505-002 |
| | | REV DESCRIPTION | DATE APPRO | SURFACE Nitrurado | ABG 1/31/2022 | SIZE PART NAME REV. Spring Sensor Pin REV. |
| FIRMA: AUTHORITE | TALLED | | | HARDNESS: HRC 50-55 | REVIEW RVM 1/31/2022 | Α |
| AUTHORIZE | TALLER | REVIEV | ٧S | 111/0 00 00 | | ESCALE 2:1 DRAWING IN MILLIMETERS |