

SECTION A-A

NOTES:

TAG WITH PART NUMBER

APPROXIMATE WEIGHT = 0.624 LBS

DIMENSIONING AND TOLERANCING PER ASME Y14.5-2009 AND LIBBEY CORPORATE STANDARDS

NOTICE

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF LIBBEY, INC, AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT THE EXPRESSED WRITTEN CONSENT OF LIBBEY, INC.

REPORT CHANGES TO ENGINEERING DEPARTMENT WORK TO DIMENSIONS. <u>DO NOT SCALE PRINT</u> .
UNLESS OTHERWISE SPECIFIED:
I UNLESS UTHERWISE SPECIFIED.

UNITS ARE DECIMAL MILLIMETER TOLERANCE ON ALL DIMENSIONS ARE:

ENGLISH DIMENSIONS:

X/X $\pm 1/16$ X.XX $\pm .020$ X.XXX $\pm .010$

REF ASSEMBLY

LIST

LY-01263

± .010


METRIC DIMENSIONS:

CHAMFER BORED & REAMED HOLES: 1/32 x 45° UP TO 3/8 DIA. 1/16 x 45° OVER 3/8 DIA.

CHAMFER TAPPED HOLES TO DEPTH OF ONE THREAD

SURFACE ROUGHNESS NOT TO EXCEED

125 ON MACHINED SURFACES
THIRD ANGLE PROJECTION



REV.

MATERIAL AISI 1045 STEEL, UNS G10450

REVISIONS

DESCRIPTION

 DESIGN
 D. SOLEY
 SAVED
 6/1/2022

 DRAWN
 D. SOLEY
 05/26/2022



CORPORATE OFFICES TOLEDO, OHIO WWW.LIBBEY.COM

BY

DATE

ROTATION BLOCK

X-Y-THETA ADJUSTER

SCALE: SIZE

DRAWING NUMBER

1:1 | A | LY-8853

SHEET 1 OF 1