

NAME	DATE TIME	(HRS)				
	8 0			Ο α		
	60.48			40.00	Ť:	
	99 94	0		74	3	
	-	•		-		+0.05
+0.05 (E) 4 x Ø 4.10 0.00 THRU						.10
19.05						
	$(\Psi -(+)$	-)-		-(+)	15.88	
		, 		\bigvee	I 4	~
2 x ∅ 6.60 THRU ALL						
✓ Ø 12.60 X 90°						
19.05						
10.03						
$^{+0.03}$ $_{2 \times } \oslash$ 7.20 0.00 THRU ALL						
$2 \times \psi$ 7.20 0.00 HINO ALL						
		7				
					PAG. 2 de 2	ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER MANIJEACTURER PROCLIBEMENT OR DISCLOSURE WITHOUT WRITTEN
QUALITY		NO.	I		E MEDIDA ESPECIAL	MANUFACTURER, PROCUREMENT OR DISCLOSURE WITHOUT WRITTEN PERMISSION OF THE OWNMER.
MOSAON		NOTES: Pieza libre de filos y rebabas.	TOTAL OF PIECES 1 Pza.	UNLESS OTHERWISE SPECIFIED TOLERANCES ISO 2748-1 mK-F	MOSYOL	JOYSON TECHNICAL CENTER
EQUIPO AUTOMOTRIZ AMERICANA S.A. DE C.V.			ANG. PRO	TOLERANCES ISO 2768-1 mK-E DIMENSIONS ASME Y14.5M-1994 MM INCHES ANGLES	SAFETY SYSTEMS	MODEL NAME: CART016-TRN SERIES NO M2021-159
BOLSAS DE AIRE				+.11 +.004004 +1°-1°	– APPROVALS DATE	MACHINE NAME: LID.CARTRIDGE FARSIDE LUCID LH
NOMBRE:RM				MATERIAL: SS304	DESIGNER LGG 05/01/2022	PART NUMBER: CARTO 16-TRN-100-006 SIZE PART NAME REV.
FIRMA		REV DESCRIPTION	DATE APPROVED	SURFACE TREATMENT: Pulido	PEMEM	$oldsymbol{A}^{SIZE} oldsymbol{PART NAME}^{PART NAME} oldsymbol{Cartridge Locking Plate} oldsymbol{Rev.} oldsymbol{A}^{Rev.}$
AUTHORIZE	TALLER	REVIEWS		HARDNESS: N.A.	RVM 05/01/2022	ESCALE 1:2 DRAWING IN MILLIMETERS