SPECIFICATIONS:

O-RING
PART NO. 50-222
COMPOUND AA-7446-70
1 1/2" ID x 1 3/4" OD x 1/8" WIDE
BUNA-N MATERIAL
70 DUROMETER



PURCHASE FROM:

ANCHOR PACKING COMPANY ONE BUTTONWOOD SQUARE PHILADELPHIA, PA. 19130

OR NEAREST DISTRIBUTOR

SEE ALSO: LY-5306

۵	ADDED:NOTE	≽	4/30/2010
U	REDRAWN IN SOLIDWORKS ADDED MATERIAL & DUROMETER	KMW	8/2/07
REV.	DESCRIPTION	ВҰ	DATE
	REVISIONS		

MATERIAL

SAVED K. WYGANT ECIFIED: MODELED IVY DRAWN SIONS ARE:

5/28/2010

8/2/07

CORPORATE OFFICES TOLEDO, OHIO WWW.LIBBEY.COM

O-RING, 1-3/40D, 1-1/2ID, 1/8 WIDTH

MOLD OPERATING MECHANISM ASSEMBLY LE BLOWING MACHINE

INFORMATION CONTAINED HEREIN CONSTITUTES

NOTICE

PROPRIETARY CONFIDENTIAL INFORMATION OF LIBBEY, INC, AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT THE EXPRESSED WRITTEN CONSENT OF LIBBEY, INC.

SIZE SCALE:

DRAWING NUMBER

SHEET 1 OF 1

REPORT CHANGES TO ENGINEERING DEPARTMENT. WORK TO DIMENSIONS. DO NOT SCALE PRINT.	UNLESS OTHER WISE SPECIFIED:	INITS ABE DECIMAL INCH	TOLERANCE ON ALL DIMENSIONS ARE:	LISHD	X.X ± .080 X.XX ± .020 X.XXX ± .010	METRIC DIMENSIONS: X mm ± 2 mm	E	CHAMFER BORED & REAMED HOLES: 1/32 x 45° UP TO 3/8 DIA.	1/16 x 45° OVER 3/8 DIA. CHAMFER TAPPED HOLES TO DEPTH OF ONE THREAD	SURFACE ROUGHNESS NOT TO EXCEED 125 ON ENTIREDED STIDEACES	1
REF ASSEMBLY LIST	LE-025	LE-037	LE-035	LE-052							