



MATERIAL SPECIFICATIONS:

TYPE	-----	100% SOLID NEOPRENE
THICKNESS	-----	.125
HARDNESS SHORE A	-----	50 ± 5
TENSILE	-----	1300 PSI MIN
ELONGATION	-----	350% MIN

REFERENCE NOTE:
USE WITH #18 EXAR OR
BRAIDLESS SILICONE
WIRE).

ALT LET	CHANGE NOTICE NO.	DESCRIPTION OF CHANGE
-	33421	STD
A	37263	
B	40282	
-	MISC	17-NOV-83
C	45202	

TOLERANCES		U.S. ELECTRICAL MOTORS DIVISION OF EMERSON ELECTRIC CO. ST. LOUIS, MISSOURI		GASKET (COMBINATION) (OUTLET BOX; 9 LEADS)	
TOLERANCES ON DIMENSIONS EXCEPT WHERE SPECIFIED:		SCALE		TITLE	
.XX ± .030		1:1		702219	
.XXX ± .015		1 IN		140T	
ANGLES ± 30 MINS		SEE NOTE		---	
		MATERIAL		CSTG. PART. TYPE	
		SHEET 1 OF 1		TC	
		PREFIX 1		AL.T.	
		GSK		C 702219 B	