NAME	DATE	TIME (HRS)				
		Ø 15	5 —			
				, _		
				$_$ Ø 6.80 $\overline{\lor}$ 19.0 M8X1.25 - 6H $\overline{\lor}$ 1)5 5 88	
				7410X1.23 - 011 V	10.00	
			((()))			
						_
						_
						_
						_
				— KI.300 HF		_
			A (-+			_
			50			
					<u>-</u>	
					i	
					PAG. 1 de 1	ALL TECHNICAL DATA DISCLOSED HERE IN IS THE PROPERTY OF JOYSON SAFETY SYSTEMS AND SHALL NOT BE USED BY ANY OTHER MANUFACTURER, PROCUREMENT OR DISCLOSURE WITHOUT WRITTEN PERMISSION OF THE OWNMER.
QUALITY					E MEDIDA ESPECIAL	PERMISSION OF THE OWNMER.
		NOTES: Pieza libre de filos y rebabas.	DIECES 112G.	LESS OTHERWISE SPECIFIED	3	JOYSON TECHNICAL CENTER
		1 1024 III010 do 11103 y 10040043.	ANG. PRO DI	LERANCES ISO 2768-1 mK-E MENSIONS ASME Y14.5M-1994	JOYSON SAFETY SYSTEMS	MODEL NAME: HRS002-P1 SERIES NO M2022-063
				MM INCHES ANGLES +.11 +.004004 +1°-1°		MACHINE NAME: Harness Routing and Switches #2
				TERIAL: ACETAL	- APPROVALS DATE	PART NUMBER: 016
		DEV DESCRIPTION	SUR	FACE ATMENT: N/A	DESIGNER JEHC 11/05/2022	SIZE PART NAME REV.
AUTHORIZE	TALLED	REV DESCRIPTION		RDNESS: N/A	REVIEW MA 11/05/2022	A HRS002-P1-016 A
AUTHORIZE	TALLER	REV	/IEWS	. 47.1		ESCALE 1:1 DRAWING IN MILLIMETERS