



SECTION A-A

ETCH PART NUMBER HERE-

NOTES:

REMOVE ALL SHARP EDGES

MARK WITH PART NUMBER APPROXIMATE WEIGHT = 0.48 LBS

REDRAWN, ADDED GD&T, REMOVED NOTE

DESCRIPTION

REVISIONS

8/23/2012

DATE

SHEET

1 OF 1

TDB

NOTICE

INFORMATION CONTAINED HEREIN CONSTITUTES PROPRIETARY CONFIDENTIAL INFORMATION OF LIBBEY, INC, AND IS TO BE ACCEPTED ONLY SUBJECT TO THAT UNDERSTANDING. IT IS TO BE KEPT CONFIDENTIAL AND NOT TO BE COPIED, USED, OR CONVEYED TO OTHERS WITHOUT THE EXPRESSED WRITTEN CONSENT OF LIBBEY, INC.

MATERIAL AISI 1018 STEEL REF ASSEMBLY REPORT CHANGES TO ENGINEERING DEPARTMENT LIST WORK TO DIMENSIONS. DO NOT SCALE PRINT. LY-5025 **DESIGN** SAVED 8/23/2012 UNLESS OTHERWISE SPECIFIED: LY-0813 UNITS ARE DECIMAL INCH LY-0824 DRAWN T. BOTTLES 5/15/2007 TOLERANCE ON ALL DIMENSIONS ARE: LY-01166 ENGLISH DIMENSIONS: LY-01204 X/X X.XX ± 1/16 FINISH MARKS + .020 X.XXX ± .010 CORPORATE OFFICES 32/ N6/ = \ 16/ N5/ = \ TOLEDO, OHIO METRIC DIMENSIONS: WWW.LIBBEY.COM ± 2 mm [X.X] [X.XX] ± .5 mm ROD END CAP ± .25 mm CHAMFER BORED & REAMED HOLES: GLOBAL SPRING CAGE ASSEMBLY 1/32 x 45° UP TO 3/8 DIA. 1/16 x 45° OVER 3/8 DIA. INDEXING PRESS MACHINE CHAMFER TAPPED HOLES TO DEPTH OF ONE SCALE: DRAWING NUMBER SURFACE ROUGHNESS NOT TO EXCEED LY-5025-1-2 125 ON MACHINED SURFACES

REV.