

# **University of Central Florida**

## **CGS 2545**

### **Database Concepts**

DEPARTMENT OF ELECTRICAL ENGINEERING & COMPUTER SCIENCE  
**COMPUTER SCIENCE DIVISION**

# UNIONS CLAUSE

- The SQL UNION clause/operator is used to combine the results of two or more SELECT statements without returning any duplicate rows.
- To use this UNION clause, each SELECT statement must have
  - The same number of columns selected
  - The same number of column expressions
  - The same data type and
  - Have them in the same order
- But they need not have to be in the same length

# UNIONS CLAUSE

- Syntax
  - The basic syntax of a **UNION** clause is as follows

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

```
UNION
```

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

# UNIONS CLAUSE

- Example
  - Consider the following two tables.

**Table 1** – CUSTOMERS Table

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

**Table 2** – ORDERS Table

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060

# UNIONS CLAUSE

- Example
  - join these two tables in our SELECT statement as follows

```
SQL> SELECT ID, NAME, AMOUNT, DATE
FROM CUSTOMERS
LEFT JOIN ORDERS
ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID
UNION
SELECT ID, NAME, AMOUNT, DATE
FROM CUSTOMERS
RIGHT JOIN ORDERS
ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

ID	NAME	AMOUNT	DATE
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL

# UNIONS CLAUSE

- The UNION ALL Clause
  - The UNION ALL operator is used to combine the results of two SELECT statements including duplicate rows.
  - The same rules that apply to the UNION clause will apply to the UNION ALL operator.

# UNIONS CLAUSE

- Syntax
  - The basic syntax of the **UNION ALL** is as follows

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

```
UNION ALL
```

```
SELECT column1 [, column2 ]  
FROM table1 [, table2 ]  
[WHERE condition]
```

# UNIONS CLAUSE

- Example
  - Consider the following two tables.

**Table 1** – CUSTOMERS Table

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

**Table 2** – ORDERS Table

OID	DATE	CUSTOMER_ID	AMOUNT
102	2009-10-08 00:00:00	3	3000
100	2009-10-08 00:00:00	3	1500
101	2009-11-20 00:00:00	2	1560
103	2008-05-20 00:00:00	4	2060



# UNIONS CLAUSE

- join these two tables in our SELECT statement as follows

```
SQL> SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      LEFT JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID
UNION ALL
      SELECT ID, NAME, AMOUNT, DATE
      FROM CUSTOMERS
      RIGHT JOIN ORDERS
      ON CUSTOMERS.ID = ORDERS.CUSTOMER_ID;
```

ID	NAME	AMOUNT	DATE
1	Ramesh	NULL	NULL
2	Khilan	1560	2009-11-20 00:00:00
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00
5	Hardik	NULL	NULL
6	Komal	NULL	NULL
7	Muffy	NULL	NULL
3	kaushik	3000	2009-10-08 00:00:00
3	kaushik	1500	2009-10-08 00:00:00
2	Khilan	1560	2009-11-20 00:00:00
4	Chaitali	2060	2008-05-20 00:00:00

# UNIONS CLAUSE

- There are two other clauses (i.e., operators), which are like the UNION clause
  - SQL INTERSECT: This is used to combine two SELECT statements, but returns rows only from the first SELECT statement that are identical to a row in the second SELECT statement.
  - SQL EXCEPT: This combines two SELECT statements and returns rows from the first SELECT statement that are not returned by the second SELECT statement.