

Virtual Destructors

```
// virt_dtor.h

1  class Base {
2  public:
3      Base() : base_memory(new char[1000]) { }
4      ~Base() { delete[] base_memory; }
5
6  private:
7      char *base_memory;
8  };
9
10 class Derived : public Base {
11 public:
12     Derived() : Base(), derived_memory(new char[1000]) { }
13     ~Derived() { delete[] derived_memory; }
14
15 private:
16     char *derived_memory;
17 };
```

Virtual Destructors

```
// virt_dtor.cpp

1  #include "virt_dtor.h"
2
3  int main() {
4      // Note use of base-class pointer
5      Base *obj = new Derived();
6      delete obj; // calls what destructor(s)?
7      return 0;
8  }
```

`new Derived()` calls `Derived` default constructor, which in turn calls `Base` default constructor; that's good (both memories are allocated)

But which destructor is called?

- Destructor is not `virtual`
- Does that mean `~Base` is called but not `~Derived`?

Virtual Destructors

```
$ g++ -o virt_dtor virt_dtor.cpp -std=c++11 -pedantic -Wall -Wextra
$ valgrind --leak-check=full ./virt_dtor
==6067== Memcheck, a memory error detector
==6067== Copyright (C) 2002-2015, and GNU GPL'd, by Julian Seward et al.
==6067== Using Valgrind-3.11.0 and LibVEX; rerun with -h for copyright info
==6067== Command: ./virt_dtor
==6067==
==6067== error calling PR_SET_PTRACER, vgdb might block
==6067==
==6067== HEAP SUMMARY:
==6067==     in use at exit: 73,704 bytes in 2 blocks
==6067==   total heap usage: 4 allocs, 2 frees, 74,720 bytes allocated
==6067==
==6067== 1,000 bytes in 1 blocks are definitely lost in loss record 1 of 2
==6067==    at 0x4C2E80F: operator new[](unsigned long) (in /usr/lib/valgrind/vgpreload_memcheck-amd64-linux.so)
==6067==    by 0x400856: Derived::Derived() (in /d/Study/PhDCS(JHU)/JHU2020/2020-09-12(Fall) - Intermediate Programming)
==6067==    by 0x4007A1: main (in /d/Study/PhDCS(JHU)/JHU2020/2020-09-12(Fall) - Intermediate Programming)
==6067==
==6067== LEAK SUMMARY:
==6067==     definitely lost: 1,000 bytes in 1 blocks
==6067==     indirectly lost: 0 bytes in 0 blocks
==6067==     possibly lost: 0 bytes in 0 blocks
==6067==     still reachable: 72,704 bytes in 1 blocks
==6067==         suppressed: 0 bytes in 0 blocks
==6067== Reachable blocks (those to which a pointer was found) are not shown.
==6067== To see them, rerun with: --leak-check=full --show-leak-kinds=all
==6067==
==6067== For counts of detected and suppressed errors, rerun with: -v
==6067== ERROR SUMMARY: 1 errors from 1 contexts (suppressed: 0 from 0)
```

Virtual Destructors

// virt_dtor2.h

```
1  class Base {
2  public:
3      Base() : base_memory(new char[1000]) { }
4      virtual ~Base() { delete[] base_memory; }
5
6  private:
7      char *base_memory;
8  };
9
10 class Derived : public Base {
11 public:
12     Derived() : Base(), derived_memory(new char[1000]) { }
13     virtual ~Derived() { delete[] derived_memory; }
14
15 private:
16     char *derived_memory;
17 };
```

Virtual Destructors

```
// virt_dtor2.cpp
1  #include "virt_dtor2.h"
2
3  int main() {
4      // Note use of base-class pointer
5      Base *obj = new Derived();
6      delete obj; // calls what destructor(s)?
7      return 0;
8  }
```

This should fix the problem. Thanks to dynamic binding,
`delete obj` calls `~Derived`, which in turn calls `~Base`

Recall: derived-class destructor always implicitly calls base=class
destructor

Virtual Destructors

```
$ g++ -o virt_dtor2 virt_dtor2.cpp -std=c++11 -pedantic -Wall -Wextra
$ valgrind --leak-check=full ./virt_dtor2
==6077== Memcheck, a memory error detector
==6077== Copyright (C) 2002-2015, and GNU GPL'd, by Julian Seward et al.
==6077== Using Valgrind-3.11.0 and LibVEX; rerun with -h for copyright info
==6077== Command: ./virt_dtor2
==6077==
==6077== error calling PR_SET_PTRACER, vgdb might block
==6077==
==6077== HEAP SUMMARY:
==6077==    in use at exit: 72,704 bytes in 1 blocks
==6077==    total heap usage: 4 allocs, 3 frees, 74,728 bytes allocated
==6077==
==6077== LEAK SUMMARY:
==6077==    definitely lost: 0 bytes in 0 blocks
==6077==    indirectly lost: 0 bytes in 0 blocks
==6077==    possibly lost: 0 bytes in 0 blocks
==6077==    still reachable: 72,704 bytes in 1 blocks
==6077==    suppressed: 0 bytes in 0 blocks
==6077== Reachable blocks (those to which a pointer was found) are not shown.
==6077== To see them, rerun with: --leak-check=full --show-leak-kinds=all
==6077==
==6077== For counts of detected and suppressed errors, rerun with: -v
==6077== ERROR SUMMARY: 0 errors from 0 contexts (suppressed: 0 from 0)
```

Virtual Destructors

To avoid this in general: **Any** `class` with **virtual member functions** `should` also have a `virtual` destructor, even if the destructor does nothing

Quiz - answers

Assume `class C` is derived from `class A` and `class B` and `class D` is derived from `class B`. If `class A` and `class B` both have `virtual` member functions, at the very least, the destructors of which classes must be `virtual`?

A. C and D

B. A and B

C. A, B and C

D. A, B, C and D

E. D only