

Natural language statement

Domain

GroundTruth

1.3.2. Theorem (A. Beurling, H. Helson). Let E subset L^2 , $z \in \text{proper_subset } E$. Then there exists a measurable function Θ , unique up to a multiplicative constant of modulus 1, such that $|\Theta| = 1$ a.e. on T and $E = \Theta H^2$.

Hardy spaces

```

noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // ||z|| = 1})
: C :=
  limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1)

noncomputable def unitCirclePoint (t : R) : {z : C // ||z|| = 1} :=
  <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp>

def HasRadialBoundaryValues (f : C -> C) : Prop :=
  forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)),
    Tendsto (fun r : R => f (r * (unitCirclePoint t).1)) (nhds[<] 1)
      (nhds (boundaryValue f (unitCirclePoint t)))

def HardyClass (p : R>=0inf) (f : C -> C) : Prop :=
  DifferentiableOn C f (Metric.ball (0 : C) 1) /\
  exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 ->
    eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p
      (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C

def HasTaylorSeries (f : C -> C) (a : N -> C) : Prop :=
  forall z in Metric.ball (0 : C) 1, HasSum (fun n : N => a n * z ^ n) (f z)

def HardySquareSummable (a : N -> C) : Prop :=
  Summable fun n : N => ||a n|| ^ 2

noncomputable def CauchyProduct (a b : N -> C) : N -> C :=
  fun n : N => Finset.sum (Finset.range (n + 1)) (fun k => a k * b (n - k))

def IsComplexLinearSubspace (M : Set (N -> C)) : Prop :=
  (0 : N -> C) in M /\
  forall a b : C, forall f g : N -> C, f in M -> g in M -> a * f + b *
    g in M

def ShiftInvariant (M : Set (N -> C)) : Prop :=
  forall f in M, (fun n : N => if n = 0 then 0 else f (n - 1)) in M

def InnerFunction (theta : C -> C) : Prop :=
  HardyClass top theta /\ HasRadialBoundaryValues theta /\
  forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)),
    ||boundaryValue theta (unitCirclePoint t)|| = 1

def InnerGeneratedSubspace (M : Set (N -> C)) (htheta : N -> C) : Prop :=
  HardySquareSummable htheta /\
  M = {f : N -> C | exists g : N -> C, HardySquareSummable g /\ f =
    CauchyProduct htheta g}

theorem nikolski_A_1_3_beurling_invariant_subspaces
{M : Set (N -> C)}
(hlinear : IsComplexLinearSubspace M) (hsquare : forall f in M,
  HardySquareSummable f)
(hclosed : IsClosed {f : l2(N, C) | (f : N -> C) in M})
(hshiftProper : {g : N -> C | exists f in M,
  g = fun n => if n = 0 then 0 else f (n - 1)} subset M) :
exists theta : C -> C, exists htheta : N -> C,
  InnerFunction theta /\ HasTaylorSeries theta htheta /\
  InnerGeneratedSubspace M htheta /\
  forall eta : C -> C, forall heta : N -> C,
    InnerFunction eta -> HasTaylorSeries eta heta ->
    InnerGeneratedSubspace M heta ->
    exists c : C, ||c|| = 1 /\ forall z in Metric.ball (0 : C) 1,
      eta z = c * theta z := by
  sorry

```

2.4.1. Theorem (V. Smirnov, 1928). Let f in H^2 , $f \neq 0$. Then there exist an inner function finn in H^2 and an outer function fout in H^2 such that $f = \text{finn} \cdot \text{fout}$. Moreover, such a factorization is unique up to a constant factor, and $E_{\text{finn}} = \text{finn} H^2$.

Recall that a function f in H^2 is called inner if $|f| = 1$ a.e. on T . It is called outer if $E_f = H^2$.

Hardy spaces

```

noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // ||z|| = 1})
: C :=
  limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1)

noncomputable def unitCirclePoint (t : R) : {z : C // ||z|| = 1} :=
  <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp>

def HasRadialBoundaryValues (f : C -> C) : Prop :=
  forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)),

```

Natural language statement

Domain

GroundTruth

		<pre> Tendsto (fun r : R => f (r * (unitCirclePoint t).1)) (nhds[<] 1) (nhds (boundaryValue f (unitCirclePoint t))) def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C def InnerFunction (theta : C -> C) : Prop := HardyClass top theta /\ HasRadialBoundaryValues theta /\ forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), boundaryValue theta (unitCirclePoint t) = 1 def OuterFunction (p : R>=0inf) (g : C -> C) : Prop := HardyClass p g /\ HasRadialBoundaryValues g /\ exists c : C, c = 1 /\ forall z in Metric.ball (0 : C) 1, g z = c * Complex.exp ((2 * Real.pi : C)^-1 * integral t in Set.Ioc 0 (2 * Real.pi), ((unitCirclePoint t).1 + z) / ((unitCirclePoint t).1 - z) * Real.log boundaryValue g (unitCirclePoint t)) theorem nikolski_A_2_4_inner_outer_factorization {f : C -> C} (hf : HardyClass 2 f) (hnonzero : exists z in Metric.ball (0 : C) 1, f z != 0) : exists theta g : C -> C, InnerFunction theta /\ OuterFunction 2 g /\ (forall z in Metric.ball (0 : C) 1, f z = theta z * g z) /\ forall theta' g' : C -> C, InnerFunction theta' -> OuterFunction 2 g' -> (forall z in Metric.ball (0 : C) 1, f z = theta' z * g' z) -> exists c : C, c = 1 /\ forall z in Metric.ball (0 : C) 1, theta' z = c * theta z /\ g' z = star c * g z := by sorry </pre>
3.6.1. Corollary. If g in H_1 , $g \neq 0$, then $\log g $ in $L_1(T)$. In particular, if g in H_1 and $m\{t \in T : g(t) = 0\} > 0$, then $g = 0$.	Hardy spaces	<pre> noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // z = 1}) : C := limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1) noncomputable def unitCirclePoint (t : R) : {z : C // z = 1} := <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp> def HasRadialBoundaryValues (f : C -> C) : Prop := forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), Tendsto (fun r : R => f (r * (unitCirclePoint t).1)) (nhds[<] 1) (nhds (boundaryValue f (unitCirclePoint t))) def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C theorem nikolski_A_3_6_boundary_uniqueness {p : R>=0inf} {f : C -> C} (hp : p != 0) (hf : HardyClass p f) : HasRadialBoundaryValues f /\ ((exists z in Metric.ball (0 : C) 1, f z != 0) -> IntegrableOn (fun t : R => Real.log boundaryValue f (unitCirclePoint t)) (Set.Ioc 0 (2 * Real.pi))) /\ forall E : Set {z : C // z = 1}, 0 < volume {t in Set.Ioc 0 (2 * Real.pi) unitCirclePoint t in E} -> (forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), unitCirclePoint t in E -> boundaryValue f (unitCirclePoint t) = 0) -> forall z in Metric.ball (0 : C) 1, f z = 0 := by sorry </pre>
3.7.1. Lemma (Blaschke condition, interior uniqueness theorem). Suppose f in $\text{Hol}(D)$, $f \neq 0$, and let $(\lambda_n)_{n \geq 1}$ be the zero sequence of f in D , each zero is repeated	Hardy spaces	<pre> def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> </pre>

Natural language statement

Domain

GroundTruth

according to its multiplicity. Suppose that $\lim_{r \rightarrow 1} \int_0^{2\pi} \log |f(re^{it})| dm < \infty$, then $\sum_{n=1}^{\infty} (1 - |\lambda_{bdn}|) < \infty$. In particular, this holds whenever f in $H_p(D)$, $p > 0$.

3.7.3. Lemma (Blaschke Product). If $(\lambda_{bdn})_{n=1}^{\infty}$ is a sequence in D satisfying the Blaschke condition $\sum_{n=1}^{\infty} (1 - |\lambda_{bdn}|) < \infty$, then the infinite product $B = \prod_{n=1}^{\infty} b_{\lambda_{bdn}}$ converges uniformly on compact subsets of D (and even on compact subsets of $\bar{C}$ $\setminus \{1/\lambda_{bdn}\}_{n=1}^{\infty}$). Moreover $|B| \leq 1$ in D , $|B| = 1$ a.e. on T , and the zeros of B are exactly $(\lambda_{bdn})_{n=1}^{\infty}$ (counting multiplicities).

3.7.2. Remark. The condition $\sum_{n=1}^{\infty} (1 - |\lambda_{bdn}|) < \infty$ is called the Blaschke condition.

5.4.1. Theorem. Let μ be a finite Borel measure on T . The following assertions are equivalent. (1) The family $(z_n)_{n \in \mathbb{N}}$ is a (symmetric or non-symmetric) basis of $L^2(\mu)$. (2) The Riesz projection P_+ is bounded on $L^2(\mu)$. (3) $\sin(\text{Pol}_+, \text{Pol}_-) > 0$. (4) $d\mu = |h|^2 dm$ where h in H^2 is an outer function such that $\text{dist}(h/h, H^\infty) < 1$. (5) $d\mu = w dm$ where $w = e^{u+v}$ and u, v are real valued bounded functions and $\|v\|_{\infty} < \pi/2$ (condition (HS)).

Harmonic analysis

```
eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p
(volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C

def HasZeroSequence (f : C -> C) (a : N -> C) : Prop :=
  (forall n, a n in Metric.ball (0 : C) 1) /\
  forall z in Metric.ball (0 : C) 1,
    {n : N | a n = z}.Finite /\
    exists k : N, (forall j < k, iteratedDeriv j f z = 0) /\
    iteratedDeriv k f z != 0 /\
    {n : N | a n = z}.ncard = k

def BlaschkeCondition (a : N -> C) : Prop :=
  (forall n : N, a n in Metric.ball (0 : C) 1) /\ Summable (fun n : N => 1
    - ||a n||)

theorem nikolski_A_3_7_blaschke_zero_sets
  {p : R>=0inf} {a : N -> C} (hp : p != 0) :
  (exists f : C -> C, HardyClass p f /\
    (exists z in Metric.ball (0 : C) 1, f z != 0) /\ HasZeroSequence f a)
  <=>
    BlaschkeCondition a := by
  sorry
```

```
noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // ||z|| = 1})
: C :=
  limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1)

noncomputable def unitCirclePoint (t : R) : {z : C // ||z|| = 1} :=
  <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp>

def HardyClass (p : R>=0inf) (f : C -> C) : Prop :=
  DifferentiableOn C f (Metric.ball (0 : C) 1) /\
  exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 ->
    eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C

def OuterFunction (p : R>=0inf) (g : C -> C) : Prop :=
  HardyClass p g /\ HasRadialBoundaryValues g /\ exists c : C, ||c|| = 1 /\
  forall z in Metric.ball (0 : C) 1,
    g z = c * Complex.exp
      ((2 * Real.pi : C)^-1 *
        integral t in Set.Ioc 0 (2 * Real.pi),
          ((unitCirclePoint t).1 + z) / ((unitCirclePoint t).1 - z) *
            Real.log ||boundaryValue g (unitCirclePoint t)||)

noncomputable def trigonometricPolynomial (c : Z -> C) (t : R) : C :=
  sum' k : Z, c k * Complex.exp (Complex.I * k * t)

noncomputable def weightedL2NormSq (w : {z : C // ||z|| = 1} -> R) (c : Z
-> C) : R :=
  integral t in Set.Ioc 0 (2 * Real.pi),
    ||trigonometricPolynomial c t|| ^ 2 * w (unitCirclePoint t)

def analyticFourierPart (c : Z -> C) (k : Z) : C :=
  if 0 <= k then c k else 0

noncomputable def circleHilbertTransform (v : {z : C // ||z|| = 1} -> R) (t
: R) : R :=
  Complex.re <| sum' k : Z,
    (if k = 0 then 0 else if 0 < k then -Complex.I else Complex.I) *
    ((2 * Real.pi : C)^-1 * integral s in Set.Ioc 0 (2 * Real.pi),
      (v (unitCirclePoint s) : C) * Complex.exp (-Complex.I * k * s)) *
    Complex.exp (Complex.I * k * t)

theorem nikolski_A_5_4_helson_szego
  {w : {z : C // ||z|| = 1} -> R}
  (hwm eas : AESTronglyMeasurable (fun t => w (unitCirclePoint t))
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))))
  (hwpos : forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), 0 < w
    (unitCirclePoint t))
  (hwint : IntegrableOn (fun t => w (unitCirclePoint t)) (Set.Ioc 0 (2 *
```

Natural language statement

Domain

GroundTruth

		<pre> Real.pi))) : let weightedMeasure := (volume.restrict (Set.Ioc 0 (2 * Real.pi))).withDensity fun t => ENNReal.ofReal (w (unitCirclePoint t)) let complete := forall f : R -> C, MemLp f 2 weightedMeasure -> (forall k : Z, integral t, star (Complex.exp (Complex.I * k * t)) * f t dweightedMeasure = 0) -> f ^m[weightedMeasure] 0 let basis := (exists A B : R, 0 < A /\ A <= B /\ forall c : Z -> C, c.support.Finite -> A * sum' k : Z, c k ^ 2 <= weightedL2NormSq w c /\ weightedL2NormSq w c <= B * sum' k : Z, c k ^ 2) /\ complete let boundedProjection := exists C : R, 0 <= C /\ forall c : Z -> C, c.support.Finite -> weightedL2NormSq w (analyticFourierPart c) <= C ^ 2 * weightedL2NormSq w c let positiveAngle := exists delta : R, 0 < delta /\ forall plus minus : Z -> C, plus.support.Finite -> minus.support.Finite -> (forall k, plus k != 0 -> 0 <= k) -> (forall k, minus k != 0 -> k < 0) -> delta * weightedL2NormSq w plus <= weightedL2NormSq w (fun k => plus k + minus k) let outerDistance := exists h q : C -> C, OuterFunction 2 h /\ HardyClass top q /\ (forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), w (unitCirclePoint t) = boundaryValue h (unitCirclePoint t) ^ 2) /\ eLpNorm (fun t : R => star (boundaryValue h (unitCirclePoint t)) / boundaryValue h (unitCirclePoint t) - boundaryValue q (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < 1 let helsonSzego := exists u v : {z : C // z = 1} -> R, eLpNorm (fun t : R => u (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < inf /\ eLpNorm (fun t : R => v (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < ENNReal.ofReal (Real.pi / 2) /\ forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), w (unitCirclePoint t) = Real.exp (u (unitCirclePoint t) + circleHilbertTransform v t) List.TFAE [basis, boundedProjection, positiveAngle, outerDistance, helsonSzego] := by sorry </pre>
1.3.2. Theorem (Z. Nehari, 1957). If $H : H_2 \rightarrow H_2$ is a bounded Hankel operator, then there exists ϕ in L^1 such that $H = H_\phi$ and $\ H_\phi\ = \ \phi\ _{L^1} = \text{dist}(\phi, H^\infty)$.	Operator theory	<pre> noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // z = 1}) : C := limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1) noncomputable def unitCirclePoint (t : R) : {z : C // z = 1} := <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp> def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C noncomputable def circleFourierCoefficient (phi : {z : C // z = 1} -> C) (k : Z) : C := (2 * Real.pi : C)^-1 * integral t in Set.Ioc 0 (2 * Real.pi), phi (unitCirclePoint t) * Complex.exp (-Complex.I * k * t) def BoundedHankelForm (a : N -> C) : Prop := exists C : R, 0 <= C /\ forall N : N, forall x y : N -> C, Finset.sum (Finset.range N) (fun i => Finset.sum (Finset.range N) (fun j => x i * a (i + j) * y j)) ^ 2 <= C ^ 2 * Finset.sum (Finset.range N) (fun i => x i ^ 2) * Finset.sum (Finset.range N) (fun j => y j ^ 2) </pre>

Natural language statement

Domain

GroundTruth

2.2.5. Theorem (P. Hartman, 1958). Let f in $\text{Lin}f$. Then H_f in Sinf if and only if f in $\text{Hinf} + C$. In other words, a Hankel operator H is compact if and only if $H = H_g$ with some g in $C(T)$.

Operator theory

```

noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // ||z|| = 1})
: C :=
  limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1)

noncomputable def unitCirclePoint (t : R) : {z : C // ||z|| = 1} :=
  <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp>

def HardyClass (p : R>=0inf) (f : C -> C) : Prop :=
  DifferentiableOn C f (Metric.ball (0 : C) 1) /\
  exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 ->
    eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C

noncomputable def circleFourierCoefficient
(phi : {z : C // ||z|| = 1} -> C) (k : Z) : C :=
  (2 * Real.pi : C)^-1 *
  integral t in Set.Ioc 0 (2 * Real.pi),
    phi (unitCirclePoint t) * Complex.exp (-Complex.I * k * t)

def BoundedHankelForm (a : N -> C) : Prop :=
  exists C : R, 0 <= C /\ forall N : N, forall x y : N -> C,
    ||Finset.sum (Finset.range N)
      (fun i => Finset.sum (Finset.range N) (fun j => x i * a (i + j) * y
        j))|| ^ 2 <=
      C ^ 2 * Finset.sum (Finset.range N) (fun i => ||x i|| ^ 2) *
        Finset.sum (Finset.range N) (fun j => ||y j|| ^ 2)

def HasBoundedHankelSymbol (a : N -> C) (phi : {z : C // ||z|| = 1} -> C) :
Prop :=
  AESTronglyMeasurable (fun t : R => phi (unitCirclePoint t))
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) /\
  eLpNorm (fun t : R => phi (unitCirclePoint t)) inf
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < inf /\
  forall n : N, circleFourierCoefficient phi (-(n : Z) + 1) = a n

def CompactHankel (a : N -> C) : Prop :=

```

Natural language statement

Domain

GroundTruth

		<pre> BoundedHankelForm a /\ forall eps : R, 0 < eps -> exists N : N, forall M : N, forall x y : N -> C, sum i in Finset.Icc N M, sum j in Finset.Icc N M, x i * a (i + j) * y j <= eps * (sum i in Finset.Icc N M, x i ^ 2) ^ (1 / 2 : R) * (sum j in Finset.Icc N M, y j ^ 2) ^ (1 / 2 : R) def InHInfinityPlusContinuous (phi : {z : C // z = 1} -> C) : Prop := exists h : C -> C, exists c : {z : C // z = 1} -> C, HardyClass top h /\ Continuous c /\ forall zeta : {z : C // z = 1}, phi zeta = boundaryValue h zeta + c zeta theorem nikolski_B_2_2_hartman_compact_hankel {a : N -> C} : CompactHankel a <=> exists phi : {z : C // z = 1} -> C, HasBoundedHankelSymbol a phi /\ InHInfinityPlusContinuous phi := by sorry </pre>
3.2.4. Corollary (G. Pick, 1916). There exists f in Hinf such that $f(\lambda_k) = w_k$, $k = 1, \dots, n$, and $\ f\ _{\text{Hinf}} \leq 1$ if and only if $I - WW^* \geq 0$: $\sum_{i,j=1}^n a_i a_j (1 - w_i w_j) / (1 - \lambda_i \lambda_j) \geq 0$, a_i in $\mathbb{C}$. Moreover, the solution f is unique if and only if the matrix $I - WW^*$ is degenerated, i.e. $d = \text{rank}(I - WW^*) < n$.	Function theory	<pre> noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // z = 1}) : C := limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1) noncomputable def unitCirclePoint (t : R) : {z : C // z = 1} := <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp> def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C def SchurFunction (f : C -> C) : Prop := HardyClass top f /\ forall z in Metric.ball (0 : C) 1, f z <= 1 noncomputable def PickMatrix {n : N} (z w : Fin n -> C) : Matrix (Fin n) (Fin n) C := fun i j => (1 - w i * star (w j)) / (1 - z i * star (z j)) def PositiveSemidefiniteMatrix {n : N} (A : Matrix (Fin n) (Fin n) C) : Prop := forall c : Fin n -> C, 0 <= Complex.re (sum i, sum j, star (c i) * A i j * c j) theorem nikolski_B_3_2_nevanlinna_pick_interpolation {n : N} {z w : Fin n -> C} (hz : forall i : Fin n, z i in Metric.ball (0 : C) 1) : let solutions := {f : C -> C SchurFunction f /\ forall i : Fin n, f (z i) = w i} (solutions.Nonempty <=> PositiveSemidefiniteMatrix (PickMatrix z w)) /\ (solutions.Nonempty -> (solutions.Subsingleton <=> Matrix.det (PickMatrix z w) = 0)) := by sorry </pre>
4.3.3. Lemma. Let u in $\text{Lin}(T)$ be such that $u = 1$ a.e. on T. The following are equivalent. (1) T_u is invertible. (2) $\text{dist}(u, \text{Hinf}) < 1$, $\text{dist}(u, \text{Hinf}) < 1$. (3) There exists an outer function h in Hinf such that $\ u - h\ _{\text{Hinf}} < 1$. (4) There exist real valued bounded functions a, b and a constant c in $\mathbb{R}$ such that $u = e^{i(c+a+b)}$ and $\ a\ _{\text{Hinf}} < \pi/2$. 3.9.7. Definition. Let f in Hp, $p > 0$. The function $[f]$ is called the outer part of f, and λ_{BS} is called the inner part of f. A function f in Hp which is equal to its outer part (up to a multiplicative constant of modulus 1), $f = \lambda_{\text{BS}}[f]$, will simply be called outer.	Operator theory	<pre> noncomputable def boundaryValue (f : C -> C) (zeta : {z : C // z = 1}) : C := limUnder (nhds[<] (1 : R)) fun r => f (r * zeta.1) noncomputable def unitCirclePoint (t : R) : {z : C // z = 1} := <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp> def HardyClass (p : R>=0inf) (f : C -> C) : Prop := DifferentiableOn C f (Metric.ball (0 : C) 1) /\ exists C : R>=0inf, C < inf /\ forall r : R, 0 <= r -> r < 1 -> eLpNorm (fun t : R => f (r * (unitCirclePoint t).1)) p (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C def OuterFunction (p : R>=0inf) (g : C -> C) : Prop := HardyClass p g /\ HasRadialBoundaryValues g /\ exists c : C, c = 1 /\ forall z in Metric.ball (0 : C) 1, g z = c * Complex.exp </pre>

Natural language statement

Domain

GroundTruth

		<pre> ((2 * Real.pi : C)^-1 * integral t in Set.Ioc 0 (2 * Real.pi), ((unitCirclePoint t).1 + z) / ((unitCirclePoint t).1 - z) * Real.log boundaryValue g (unitCirclePoint t)) noncomputable def circleHilbertTransform (v : {z : C // z = 1} -> R) (t : R) : R := Complex.re < sum' k : Z, (if k = 0 then 0 else if 0 < k then -Complex.I else Complex.I) * ((2 * Real.pi : C)^-1 * integral s in Set.Ioc 0 (2 * Real.pi), (v (unitCirclePoint s) : C) * Complex.exp (-Complex.I * k * s)) * Complex.exp (Complex.I * k * t) noncomputable def circleFourierCoefficient (phi : {z : C // z = 1} -> C) (k : Z) : C := (2 * Real.pi : C)^-1 * integral t in Set.Ioc 0 (2 * Real.pi), phi (unitCirclePoint t) * Complex.exp (-Complex.I * k * t) noncomputable def symbolDistanceToHInfinity (phi : {z : C // z = 1} -> C) : R:=0inf := sInf {r : R>=0inf exists h : C -> C, HardyClass top h /\ eLpNorm (fun t : R => phi (unitCirclePoint t) - boundaryValue h (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= r} def RepresentsToeplitzOperator (phi : {z : C // z = 1} -> C) (T : l2(N, C) ->L[C] l2(N, C)) : Prop := forall f n, 'T f n = sum' j : N, circleFourierCoefficient phi ((n : Z) - j) * f j def EssentiallyBoundedCircleSymbol (u : {z : C // z = 1} -> C) : Prop := AEStronglyMeasurable (fun t : R => u (unitCirclePoint t)) (volume.restrict (Set.Ioc 0 (2 * Real.pi))) /\ eLpNorm (fun t : R => u (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < inf def IsUnimodularCircleSymbol (u : {z : C // z = 1} -> C) : Prop := forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), u (unitCirclePoint t) = 1 theorem nikolski_B_4_3_3_devinatz_widom {u : {z : C // z = 1} -> C} (hu : EssentiallyBoundedCircleSymbol u) (hmod : IsUnimodularCircleSymbol u) : let a := exists T : l2(N, C) ->L[C] l2(N, C), RepresentsToeplitzOperator u T /\ Function.Bijective T let b := symbolDistanceToHInfinity u < 1 /\ symbolDistanceToHInfinity (fun zeta => star (u zeta)) < 1 let c := exists h : C -> C, OuterFunction top h /\ eLpNorm (fun t : R => u (unitCirclePoint t) - boundaryValue h (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < 1 let d := exists v w : {z : C // z = 1} -> R, exists c : R, eLpNorm (fun t : R => v (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < ENNReal.ofReal (Real.pi / 2) /\ eLpNorm (fun t : R => w (unitCirclePoint t)) inf (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < inf /\ forall^m t dvolume.restrict (Set.Ioc 0 (2 * Real.pi)), u (unitCirclePoint t) = Complex.exp (Complex.I * (c + v (unitCirclePoint t) + circleHilbertTransform w t)) List.TFAE [a, b, c, d] := by sorry </pre>
7.2.1. Theorem (V. Adamyan, D. Arov, and M. Krein, 1971). Let H_{ϕ} be a Hankel operator and let R_n be the set of rational functions tending to 0 at infinity and having all poles in D such that their total multiplicity is less than or equal to n. Then $sn(H_{\phi}) = \min\{ H_{\phi} - H_{\psi} : \text{rank } H_{\psi} \leq n\} = \text{dist}(\phi, R_n + H_{\infty}) = \min\{ H_{\infty}(B_{\phi}) : B \text{ is a Blaschke}$	Operator theory	<pre> noncomputable def unitCirclePoint (t : R) : {z : C // z = 1} := <Complex.exp (Complex.I * t), by rw [Complex.norm_exp]; simp> noncomputable def circleFourierCoefficient (phi : {z : C // z = 1} -> C) (k : Z) : C := (2 * Real.pi : C)^-1 * </pre>

Natural language statement

Domain

GroundTruth

product of degree $\leq n$, where the degree deg Theta of an inner function Theta is equal to n if Theta is a finite Blaschke product with n zeros (counting multiplicities) and inf otherwise.

```

integral t in Set.Ioc 0 (2 * Real.pi),
  phi (unitCirclePoint t) * Complex.exp (-Complex.I * k * t)

def BoundedHankelForm (a : N -> C) : Prop :=
  exists C : R, 0 <= C /\ forall N : N, forall x y : N -> C,
    ||Finset.sum (Finset.range N)
      (fun i => Finset.sum (Finset.range N) (fun j => x i * a (i + j) * y
        j))|| ^ 2 <=
      C ^ 2 * Finset.sum (Finset.range N) (fun i => ||x i|| ^ 2) *
        Finset.sum (Finset.range N) (fun j => ||y j|| ^ 2)

def HasBoundedHankelSymbol (a : N -> C) (phi : {z : C // ||z|| = 1} -> C) :
  Prop :=
  AESTronglyMeasurable (fun t : R => phi (unitCirclePoint t))
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) /\
  eLpNorm (fun t : R => phi (unitCirclePoint t)) inf
    (volume.restrict (Set.Ioc 0 (2 * Real.pi))) < inf /\
  forall n : N, circleFourierCoefficient phi (-(n : Z) + 1) = a n

def HankelMatrixRankLE (n : N) (b : N -> C) : Prop :=
  exists u v : Fin n -> N -> C,
    (forall q, HardySquareSummable (u q) /\ HardySquareSummable (v q)) /\
    forall i j, b (i + j) = sum q, u q i * v q j

noncomputable def hankelRankApproximationDistance (a : N -> C) (n : N) :
  R>=0inf :=
  sInf {C : R>=0inf | C < inf /\ exists b : N -> C, HankelMatrixRankLE n b
    /\
    forall N : N, forall x y : N -> C,
      ||sum i in Finset.range N, sum j in Finset.range N,
        x i * (a (i + j) - b (i + j)) * y j|| <=
        C.toReal * (sum i in Finset.range N, ||x i|| ^ 2) ^ (1 / 2 : R) *
          (sum j in Finset.range N, ||y j|| ^ 2) ^ (1 / 2 : R)}

def RationalVanishingAtInfinityDegreeLE (n : N)
  (psi : {z : C // ||z|| = 1} -> C) : Prop :=
  exists numerator denominator : Polynomial C,
    numerator.natDegree < denominator.natDegree /\ denominator.natDegree <=
      n /\
    denominator != 0 /\
    (forall z : C, denominator.IsRoot z -> z in Metric.ball (0 : C) 1) /\
    forall zeta, psi zeta = numerator.eval zeta.1 / denominator.eval
      zeta.1

noncomputable def rationalPlusHInfinityDistance
  (phi : {z : C // ||z|| = 1} -> C) (n : N) : R>=0inf :=
  sInf {C : R>=0inf | exists (psi : {z : C // ||z|| = 1} -> C) (h : C -> C),
    RationalVanishingAtInfinityDegreeLE n psi /\ HardyClass top h /\
    eLpNorm (fun t : R => phi (unitCirclePoint t) - psi (unitCirclePoint
      t) -
      boundaryValue h (unitCirclePoint t)) inf
      (volume.restrict (Set.Ioc 0 (2 * Real.pi))) <= C}

def FiniteBlaschkeProductDegreeLE (n : N) (B : C -> C) : Prop :=
  exists (m : N) ( _ : m <= n) (a : Fin m -> C) (c : C), ||c|| = 1 /\
  (forall i, a i in Metric.ball (0 : C) 1) /\ InnerFunction B /\
  forall z in Metric.ball (0 : C) 1,
    B z = c * prod i, (z - a i) / (1 - star (a i) * z)

noncomputable def finiteBlaschkeHankelDistance
  (phi : {z : C // ||z|| = 1} -> C) (n : N) : R>=0inf :=
  sInf {C : R>=0inf | exists (B : C -> C) (b : N -> C),
    FiniteBlaschkeProductDegreeLE n B /\
    HasBoundedHankelSymbol b (fun zeta => star (boundaryValue B zeta) *
      phi zeta) /\
    hankelFormNorm b = C}

theorem nikolski_B_7_2_1_adamyan_arov_krein
  {a : N -> C} {phi : {z : C // ||z|| = 1} -> C} {n : N} :
  HasBoundedHankelSymbol a phi ->
  hankelRankApproximationDistance a n = rationalPlusHInfinityDistance
    phi n /\

```


Natural language statement

Domain

GroundTruth

		rationalPlusHInfinityDistance phi n = finiteBlaschkeHankelDistance phi n := by sorry
--	--	---