

```
SELECT*
FROM joinsassignment.jtables.users;
```

```
SELECT*
FROM joinsassignment.jtables.viewing_sessions;
```

```
SELECT*
FROM joinsassignment.jtables.subscriptions;
```

```
SELECT*
FROM joinsassignment.jtables.shows;
```

```
SELECT*
FROM joinsassignment.jtables.plans;
```

--Q1. Show every user who has a subscription. Match users to subscriptions.

```
SELECT
    A.user_id,
    A.user_name,
    B.subscription_id,
    B.start_date
FROM joinsassignment.jtables.users AS A
INNER JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id =B.user_id;
```

--Q2.Show every subscription with its matching plan name and monthly price

```
SELECT
    subscription_id,
    user_id,
    plan_name,
    monthly_price
FROM joinsassignment.jtables.subscriptions AS A
INNER JOIN joinsassignment.jtables.plans AS B
ON A.plan_id =B.plan_id;
```

--Q3.Show every viewing session that has a matching show. Include the show title and genre.

```
SELECT
    session_id,
    user_id,
    show_title,
    genre,
    watch_minutes
FROM joinsassignment.jtables.viewing_sessions AS A
INNER JOIN joinsassignment.jtables.shows AS B
ON A.show_id= B.show_id;
```

--Q4.Show every viewing session with the user who watched it. Only show sessions with a matching user.

```
SELECT
    user_name,
    country,
    session_id,
    show_id,
    watch_minutes
FROM joinsassignment.jtables.users AS A
INNER JOIN joinsassignment.jtables.viewing_sessions AS B
ON A.user_id = B.user_id;
```

--Q5.Show users along with their subscriptions, the plan name, and the price. Use only users who have both a subscription and a valid plan.

```
SELECT
    user_name,
    country,
    plan_name,
    monthly_price,
    start_date
FROM joinsassignment.jtables.users AS A
INNER JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id = B.user_id
INNER JOIN joinsassignment.jtables.plans AS C
ON B.plan_id = C.plan_id;
```

--Q6.Show every user and any subscriptions they have. Users without subscriptions must still appear

```
SELECT
    A.user_name,
    A.user_id,
    B.subscription_id,
    B.start_date
FROM joinsassignment.jtables.users AS A
LEFT JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id = B.user_id;
```

--Q7.Show every plan and the subscriptions on it. Plans with no subscribers must still appear.

```
SELECT
    A.plan_id,
    A.plan_name,
    B.subscription_id,
    B.user_id
FROM joinsassignment.jtables.plans AS A
```

```
LEFT JOIN joinsassignment.jtables.subscriptions AS B
ON A.plan_id= B.plan_id;
```

--Q8 Show every show and any viewing sessions on it. Shows that were never watched must still appear

```
SELECT
    A.show_id,
    A.show_title,
    B.session_id,
    B.watch_minutes
FROM joinsassignment.jtables.shows AS A
LEFT JOIN joinsassignment.jtables.viewing_sessions AS B
ON A.show_id = B.show_id;
```

--Q9 Show every viewing session and the user who watched it. Sessions referencing users that do not exist must still appear (with NULL user details)

```
SELECT
    A.session_id,
    A.show_id,
    A.watch_minutes,
    B.user_id,
    B.user_name
FROM joinsassignment.jtables.viewing_sessions AS A
LEFT JOIN joinsassignment.jtables.users AS B
ON A.user_id = B.user_id;
```

--10 Show every user, the plan they are on (if any), and the monthly price. Users without a subscription must still appear.

```
SELECT
    user_name,
    country,
    plan_name,
    monthly_price
FROM joinsassignment.jtables.users AS A
LEFT JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id = B.user_id
LEFT JOIN joinsassignment.jtables.plans AS C
ON B.plan_id = C.plan_id;
```

--Q11 Show every user and every subscription, including users without subscriptions AND subscriptions referencing users that do not exist

```
SELECT
    A.user_id,
    A.user_name,
    B.subscription_id,
```

```

        B.start_date
FROM joinsassignment.jtables.users AS A
FULL OUTER JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id = B.user_id;

```

--Q12 Show every plan and every subscription, including plans without subscribers AND any subscription referencing a plan that does not exist.

```

SELECT
    A. plan_id,
    A.plan_name,
    B.subscription_id,
    B.user_id
FROM joinsassignment.jtables.plans AS A
FULL OUTER JOIN joinsassignment.jtables.subscriptions AS B
ON A.plan_id= B.plan_id;

```

--Q13 Show every show and every viewing session, including shows that were never watched AND sessions referencing shows that do not exist.

```

SELECT
    A.show_id,
    A.show_title,
    B.session_id,
    B.watch_minutes
FROM joinsassignment.jtables.shows AS A
FULL OUTER JOIN joinsassignment.jtables.viewing_sessions AS B
ON A.show_id = B.show_id;

```

--Q14 Show every user and every viewing session, including users with no sessions AND sessions referencing users who do not exist.

```

SELECT
    A.user_id,
    A.user_name,
    B.session_id,
    B.watch_minutes
FROM joinsassignment.jtables.users AS A
FULL OUTER JOIN joinsassignment.jtables.viewing_sessions AS B
ON A.user_id = B.user_id;

```

--Q15 Show every user, every subscription, and every plan in one query – using FULL OUTER JOIN throughout. This is the hardest question – get all gaps visible at once.

```

SELECT
    A.user_id,
    A.user_name,
    B.subscription_id,
    C.plan_id,

```

```
        C.plan_name
FROM joinsassignment.jtables.users AS A
FULL OUTER JOIN joinsassignment.jtables.subscriptions AS B
ON A.user_id = B.user_id
FULL OUTER JOIN joinsassignment.jtables.plans AS C
ON B.plan_id = C.plan_id;
```